





ACP

UL_H-DQPSK_LCH_Pre-AGC





ACP

UL_H-DQPSK_LCH_Pre-AGC





ACP

UL_H-DQPSK_LCH_3dB above AGC





ACP

UL_H-DQPSK_LCH_3dB above AGC





ACP

UL_H-DQPSK_MCH_Pre-AGC





ACP

UL_H-DQPSK_MCH_Pre-AGC





ACP

UL_H-DQPSK_MCH_3dB above AGC





ACP

UL_H-DQPSK_MCH_3dB above AGC





ACP

UL_H-DQPSK_HCH_Pre-AGC



ACP

UL_H-DQPSK_HCH_Pre-AGC





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



ACP

UL_H-DQPSK_HCH_3dB above AGC





ACP

UL_H-DQPSK_HCH_3dB above AGC





ACP

UL_TETRA_LCH_Pre-AGC





ACP

UL_TETRA_LCH_Pre-AGC





ACP

UL_TETRA_LCH_3dB above AGC





ACP

UL_TETRA_LCH_3dB above AGC





ACP

UL_TETRA_MCH_Pre-AGC





ACP

UL_TETRA_MCH_Pre-AGC





ACP

UL_TETRA_MCH_3dB above AGC





ACP

UL_TETRA_MCH_3dB above AGC





ACP

UL_TETRA_HCH_Pre-AGC





ACP

UL_TETRA_HCH_Pre-AGC





ACP

UL_TETRA_HCH_3dB above AGC



ACP

UL_TETRA_HCH_3dB above AGC





SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-ARF-05 Rev 1.1

Page: 239 of 274

6 Noise Figure

Noise Figure			
Test path	Noise figure (dB)	Limit (dB)	Verdict
DL	6.12	≤9	PASS
UL	5.75	≤9	PASS



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Competency Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgs.com.cn
t (86-20) 82155555 sgs.china@sgs.com


Member of the SGS Group (SGS SA)

7 Intermodulation emissions

Intermodulation								
Test path	f0 (MHz)	CW signal spacing (kHz)	Signal level	Worst conducted test level (dBm/300Hz)	Antenna Gain (dBi)	Coupling loss (dB)	ERP (dBm/10k Hz)	Limit (dBm/10k Hz)
DL	765.5	6.25	Pre-AGC	-19.68	0	64.85	-71.45	-30
			3dB above AGC	-20.00	0	64.85	-71.77	-30
		12.5	Pre-AGC	-20.00	0	64.85	-71.77	-30
			3dB above AGC	-20.26	0	64.85	-72.03	-30
		25	Pre-AGC	-26.31	0	64.85	-78.08	-30
			3dB above AGC	-26.02	0	64.85	-77.79	-30

Remark:

- f0 is from Out-of-band Rejection test in the report.
- As part of the system commissioning process, processional Zone Enhancer installers and field technicians measure intermodulation products and noise levels by connecting a spectrum analyzer to the output of the enhancers in the field. Since each deployment involves a unique passive distribution network, technicians are required to access the Effective Radiated Power (ERP) at the antenna by factoring in losses from passive components such as attenuators, coaxial cables, couplers and filters. Necessary adjustments are made to ensure compliance with the regulatory limits outlined below. Setting details were declared by manufacture and stated in the user manual. Therefore, the Coupling loss in engineering practice must be greater than 64.85dB to eliminate the interference.




- According to the declaration from the manufacture, the single Antenna gain should not exceed 0dBi.
- $ERP_{final} = \text{Conducted Power} + 10 \cdot \log(10\text{kHz}/300\text{Hz}) + \text{Antenna Gain} - 2.15\text{dB} - \text{Coupling Loss}$.
- The test plots are only to record the case without engineering practice for reference.



Intermodulation								
Test path	f0 (MHz)	CW signal spacing (kHz)	Signal level	Worst conducted test level (dBm/300Hz)	Antenna Gain (dBi)	Coupling loss (dB)	ERP (dBm/10k Hz)	Limit (dBm/10k Hz)
UL	803.9	6.25	Pre-AGC	-23.52	0	54.85	-65.29	-30
			3dB above AGC	-22.66	0	54.85	-64.43	-30
		12.5	Pre-AGC	-23.41	0	54.85	-65.18	-30
			3dB above AGC	-22.98	0	54.85	-64.75	-30
		25	Pre-AGC	-27.49	0	54.85	-69.26	-30
			3dB above AGC	-32.15	0	54.85	-73.92	-30

Remark:

- f0 is from Out-of-band Rejection test in the report.
- As part of the system commissioning process, processional Zone Enhancer installers and field technicians measure intermodulation products and noise levels by connecting a spectrum analyzer to the output of the enhancers in the field. Since each deployment involves a unique passive distribution network, technicians are required to access the Effective Radiated Power (ERP) at the antenna by factoring in losses from passive components such as attenuators, coaxial cables, couplers and filters. Necessary adjustments are made to ensure compliance with the regulatory limits outlined below. Setting details were declared by manufacture and stated in the user manual. Therefore, the Coupling loss in engineering practice must be greater than 54.85dB to eliminate the interference.




- According to the declaration from the manufacture, the single Antenna gain should not exceed 0dBi.
- $ERP_{final} = \text{Conducted Power} + 10 \cdot \log(10\text{kHz}/300\text{Hz}) + \text{Antenna Gain} - 2.15\text{dB} - \text{Coupling Loss}$.
- The test plots are only to record the case without engineering practice for reference.




Intermodulation

DL_6.25kHz_Pre-AGC



B
Date: 13.APR.2026 14:50:34

DL_6.25kHz_3dB above AGC




B
Date: 13.APR.2026 14:50:56




Intermodulation

DL_12.5kHz_Pre-AGC



B
Date: 13.APR.2026 14:51:53

DL_12.5kHz_3dB above AGC




B
Date: 13.APR.2026 14:52:23




Intermodulation

DL_25kHz_Pre-AGC



B
Date: 13.APR.2026 14:54:59

DL_25kHz_3dB above AGC



B
Date: 13.APR.2026 14:55:15




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Intermodulation

UL_6.25kHz_Pre-AGC



B
Date: 13.APR.2026 15:11:08

UL_6.25kHz_3dB above AGC




B
Date: 13.APR.2026 15:11:36




Intermodulation

UL_12.5kHz_Pre-AGC



B
Date: 13.APR.2026 15:12:10

UL_12.5kHz_3dB above AGC




B
Date: 13.APR.2026 15:12:33




Intermodulation

UL_25kHz_Pre-AGC



B
Date: 13.APR.2026 15:14:21

UL_25kHz_3dB above AGC



B
Date: 13.APR.2026 15:14:58





SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-ARF-05 Rev 1.1

Page: 248 of 274

8 Conducted Spurious emissions

Conducted Spurious emissions						
Test path	Test signal	Test channel	Frequency range (MHz)	Worst test level (dBm)	Limit (dBm)	Verdict
DL	CW	MCH	0.009-1000	-25.74	≤-13	PASS
			1000-7750	-23.29	≤-13	PASS
			769-775	-49.60	≤-46	PASS
			799-805	-57.55	≤-46	PASS
UL	CW	MCH	0.009-1000	-20.57	≤-13	PASS
			1000-8050	-21.06	≤-13	PASS
			769-775	-56.70	≤-46	PASS
			799-805	-55.16	≤-46	PASS
Remark: The conducted spurious emissions 9kHz to 30MHz were very low and not displaved test plots in this report.						



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Competency Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com


Member of the SGS Group (SGS SA)

Conducted Spurious emissions

DL_CW_MCH



B
Date: 10.APR.2026 16:05:45



B
Date: 10.APR.2026 16:06:02



DL CW MCH






SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-ARF-05 Rev 1.1


Page: 251 of 274

Conducted Spurious emissions

UL_CW_MCH



B
Date: 10.APR.2026 16:12:44



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgs.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Member of the SGS Group (SGS SA)




SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-ARF-05 Rev 1.1


Page: 252 of 274

Conducted Spurious emissions

UL_CW_MCH



B
Date: 10.APR.2026 16:13:58



B
Date: 10.APR.2026 16:14:15



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Competency Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgs.com.cn
t (86-20) 82155555 sgs.china@sgs.com


Member of the SGS Group (SGS SA)

9 Noise

Noise						
Noise within the passband						
Test path	Frequency range (MHz)	Worst conducted test level (dBm/10kHz)	Antenna Gain (dBi)	Coupling loss (dB)	ERP (dBm/10kHz)	Limit (dBm/10kHz)
DL	758-775	-28.32	0	64.85	-95.32	-43
Noise outside of the passband						
Test path	Frequency range (MHz)	Worst conducted test level (dBm/10kHz)	Antenna Gain (dBi)	Coupling loss (dB)	ERP (dBm/10kHz)	Limit (dBm/10kHz)
DL	0.009-757	-53.10	0	64.85	-120.10	-70
	776-7750	-49.53	0	64.85	-116.53	-70

Remark:

- As part of the system commissioning process, processional Zone Enhancer installers and field technicians measure intermodulation products and noise levels by connecting a spectrum analyzer to the output of the enhancers in the field. Since each deployment involves a unique passive distribution network, technicians are required to access the Effective Radiated Power (ERP) at the antenna by factoring in losses from passive components such as attenuators, coaxial cables, couplers and filters. Necessary adjustments are made to ensure compliance with the regulatory limits outlined below. Setting details were declared by manufacture and stated in the user manual. Therefore, the Coupling loss in engineering practice must be greater than 64.85dB to eliminate the interference.



- According to the declaration from the manufacture, the single Antenna gain should not exceed 0dBi.
- $ERP_{final} = \text{Conducted Power} + \text{Antenna Gain} - 2.15\text{dB} - \text{Coupling Loss}$.
- The test plots are only to record the case without engineering practice for reference.



Noise						
Noise within the passband						
Test path	Frequency range (MHz)	Worst conducted test level (dBm/10kHz)	Antenna Gain (dBi)	Coupling loss (dB)	ERP (dBm/10kHz)	Limit (dBm/10kHz)
UL	788-805	-27.86	0	54.85	-84.86	-43
Noise outside of the passband						
Test path	Frequency range (MHz)	Worst conducted test level (dBm/10kHz)	Antenna Gain (dBi)	Coupling loss (dB)	ERP (dBm/10kHz)	Limit (dBm/10kHz)
UL	0.009-787	-61.34	0	54.85	-118.34	-70
	806-8050	-57.46	0	54.85	-114.46	-70

Remark:

- As part of the system commissioning process, processional Zone Enhancer installers and field technicians measure intermodulation products and noise levels by connecting a spectrum analyzer to the output of the enhancers in the field. Since each deployment involves a unique passive distribution network, technicians are required to access the Effective Radiated Power (ERP) at the antenna by factoring in losses from passive components such as attenuators, coaxial cables, couplers and filters. Necessary adjustments are made to ensure compliance with the regulatory limits outlined below. Setting details were declared by manufacture and stated in the user manual. Therefore, the Coupling loss in engineering practice must be greater than 54.85dB to eliminate the interference.

- According to the declaration from the manufacture, the single Antenna gain should not exceed 0dBi.
- $ERP_{final} = \text{Conducted Power} + \text{Antenna Gain} - 2.15\text{dB} - \text{Coupling Loss}$.
- The test plots are only to record the case without engineering practice for reference.






SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-ARF-05 Rev 1.1

Page: 255 of 274


Noise within the passband

DL



B
Date: 10.APR.2026 14:17:06

UL



B
Date: 10.APR.2026 14:34:40



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Competency Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgs.com.cn
t (86-20) 82155555 sgs.china@sgs.com

Member of the SGS Group (SGS SA)




SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-ARF-05 Rev 1.1


Page: 256 of 274

Noise outside the passband

DL



B
Date: 10.APR.2026 14:18:09



B
Date: 10.APR.2026 14:20:46



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Competency Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgs.com.cn
t (86-20) 82155555 sgs.china@sgs.com


Member of the SGS Group (SGS SA)

Noise outside the passband

UL



B
Date: 10.APR.2026 14:35:16



B
Date: 10.APR.2026 14:37:48



10 Frequency Stability

Frequency stability vs voltage							
Test path	Test Signal	Test Channel	Temperature	Voltage	Freq. error (Hz)	Tolerance (ppm)	Verdict
DL	FM	MCH	TN	VL	2.0	0.00259	PASS
			TN	VH	1.3	0.00168	PASS
	DMR	MCH	TN	VL	1.6	0.00207	PASS
			TN	VH	1.7	0.00220	PASS
	C4FM	MCH	TN	VL	1.1	0.00142	PASS
			TN	VH	1.6	0.00207	PASS
	H-DQPSK	MCH	TN	VL	1.7	0.00220	PASS
			TN	VH	1.8	0.00233	PASS
	TETRA	MCH	TN	VL	1.8	0.00233	PASS
			TN	VH	1.8	0.00233	PASS
UL	FM	MCH	TN	VL	1.3	0.00162	PASS
			TN	VH	1.4	0.00175	PASS
	DMR	MCH	TN	VL	1.4	0.00175	PASS
			TN	VH	2.1	0.00262	PASS
	C4FM	MCH	TN	VL	1.8	0.00224	PASS
			TN	VH	1.9	0.00237	PASS
	H-DQPSK	MCH	TN	VL	1.1	0.00137	PASS
			TN	VH	1.3	0.00162	PASS
	TETRA	MCH	TN	VL	2.1	0.00262	PASS
			TN	VH	1.4	0.00175	PASS
	AWGN	MCH	TN	VL	1.7	0.00214	PASS
			TN	VH	1.8	0.00227	PASS



Frequency stability vs temperature							
Test Path	Test Signal	Test Channel	Voltage	Temperature (°C)	Freq. error (Hz)	Tolerance (ppm)	Verdict
DL	FM	MCH	VN	+50	1.9	0.00246	PASS
			VN	+40	1.3	0.00168	PASS
			VN	+30	1.3	0.00168	PASS
			VN	+20	1.8	0.00233	PASS
			VN	+10	1.5	0.00194	PASS
			VN	0	1.6	0.00207	PASS
			VN	-10	1.9	0.00246	PASS
			VN	-20	2.0	0.00259	PASS
			VN	-30	1.1	0.00142	PASS
	DMR	MCH	VN	+50	1.4	0.00181	PASS
			VN	+40	1.7	0.00220	PASS
			VN	+30	1.6	0.00207	PASS
			VN	+20	2.0	0.00259	PASS
			VN	+10	1.5	0.00194	PASS
			VN	0	1.7	0.00220	PASS
			VN	-10	1.3	0.00168	PASS
			VN	-20	1.7	0.00220	PASS
			VN	-30	1.1	0.00142	PASS
	C4FM	MCH	VN	+50	1.8	0.00233	PASS
			VN	+40	1.5	0.00194	PASS
			VN	+30	2.1	0.00272	PASS
			VN	+20	1.7	0.00220	PASS
			VN	+10	2.0	0.00259	PASS
			VN	0	2.0	0.00259	PASS
			VN	-10	1.8	0.00233	PASS
			VN	-20	1.1	0.00142	PASS
			VN	-30	1.6	0.00207	PASS



Frequency stability vs temperature							
Test Path	Test Signal	Test Channel	Voltage	Temperature (°C)	Freq. error (Hz)	Tolerance (ppm)	Verdict
DL	D-HQPSK	MCH	VN	+50	1.1	0.00142	PASS
			VN	+40	1.4	0.00181	PASS
			VN	+30	1.8	0.00233	PASS
			VN	+20	1.9	0.00246	PASS
			VN	+10	1.8	0.00233	PASS
			VN	0	1.1	0.00142	PASS
			VN	-10	1.5	0.00194	PASS
			VN	-20	1.5	0.00194	PASS
			VN	-30	1.1	0.00142	PASS
	TETRA	MCH	VN	+50	1.6	0.00207	PASS
			VN	+40	1.4	0.00181	PASS
			VN	+30	2.1	0.00272	PASS
			VN	+20	1.8	0.00233	PASS
			VN	+10	1.6	0.00207	PASS
			VN	0	1.9	0.00246	PASS
			VN	-10	1.7	0.00220	PASS
			VN	-20	1.7	0.00220	PASS
			VN	-30	1.9	0.00246	PASS
	AWGN	MCH	VN	+50	1.2	0.00157	PASS
			VN	+40	2.1	0.00275	PASS
			VN	+30	1.5	0.00197	PASS
			VN	+20	1.7	0.00223	PASS
			VN	+10	1.6	0.00210	PASS
			VN	0	1.4	0.00183	PASS
			VN	-10	1.8	0.00236	PASS
			VN	-20	2.1	0.00275	PASS
			VN	-30	1.1	0.00144	PASS



Frequency stability vs temperature							
Test Path	Test Signal	Test Channel	Voltage	Temperature (°C)	Freq. error (Hz)	Tolerance (ppm)	Verdict
UL	FM	MCH	VN	+50	1.6	0.00207	PASS
			VN	+40	2.0	0.00259	PASS
			VN	+30	1.1	0.00142	PASS
			VN	+20	1.1	0.00142	PASS
			VN	+10	1.8	0.00233	PASS
			VN	0	1.5	0.00194	PASS
			VN	-10	2.0	0.00259	PASS
			VN	-20	1.9	0.00246	PASS
			VN	-30	1.8	0.00233	PASS
	DMR	MCH	VN	+50	1.1	0.00142	PASS
			VN	+40	2.0	0.00259	PASS
			VN	+30	1.5	0.00194	PASS
			VN	+20	2.0	0.00259	PASS
			VN	+10	1.6	0.00207	PASS
			VN	0	1.8	0.00233	PASS
			VN	-10	1.8	0.00233	PASS
			VN	-20	1.9	0.00246	PASS
			VN	-30	1.1	0.00142	PASS
	C4FM	MCH	VN	+50	1.5	0.00194	PASS
			VN	+40	1.2	0.00155	PASS
			VN	+30	1.1	0.00142	PASS
			VN	+20	1.6	0.00207	PASS
			VN	+10	1.1	0.00142	PASS
			VN	0	2.1	0.00272	PASS
			VN	-10	1.3	0.00168	PASS
			VN	-20	2.0	0.00259	PASS
			VN	-30	2.1	0.00272	PASS




Frequency stability vs temperature							
Test Path	Test Signal	Test Channel	Voltage	Temperature (°C)	Freq. error (Hz)	Tolerance (ppm)	Verdict
UL	D-HQPSK	MCH	VN	+50	1.1	0.00142	PASS
			VN	+40	1.5	0.00194	PASS
			VN	+30	1.8	0.00233	PASS
			VN	+20	1.7	0.00220	PASS
			VN	+10	1.3	0.00168	PASS
			VN	0	1.4	0.00181	PASS
			VN	-10	1.3	0.00168	PASS
			VN	-20	1.9	0.00246	PASS
			VN	-30	1.9	0.00246	PASS
	TETRA	MCH	VN	+50	1.9	0.00246	PASS
			VN	+40	1.2	0.00155	PASS
			VN	+30	1.1	0.00142	PASS
			VN	+20	1.9	0.00246	PASS
			VN	+10	1.1	0.00142	PASS
			VN	0	2.1	0.00272	PASS
			VN	-10	1.8	0.00233	PASS
			VN	-20	1.6	0.00207	PASS
			VN	-30	1.7	0.00220	PASS
	AWGN	MCH	VN	+50	1.5	0.00197	PASS
			VN	+40	1.7	0.00223	PASS
			VN	+30	1.8	0.00236	PASS
			VN	+20	2.1	0.00275	PASS
			VN	+10	1.3	0.00170	PASS
			VN	0	1.6	0.00210	PASS
			VN	-10	2.0	0.00262	PASS
			VN	-20	1.1	0.00144	PASS
			VN	-30	1.8	0.00236	PASS



11 Radiated Spurious emissions below 1GHz

Radiated Spurious emissions

DL_CW_MCH_30MHz-1GHz_Horizontal



	Freq	Read	Correction	Limit	Over	
	MHz	Level	Factor	Line	Limit	Pol/Phase
	MHz	dBm	dB	dBm	dB	
1	35.50	-75.92	-1.35	-77.27	-13.00	-64.27 HORIZONTAL
2	58.41	-75.87	-2.84	-78.71	-13.00	-65.71 HORIZONTAL
3	240.83	-75.44	-5.62	-81.06	-13.00	-68.06 HORIZONTAL
4	446.41	-74.47	-0.25	-74.72	-13.00	-61.72 HORIZONTAL
5	609.92	-73.89	2.65	-71.24	-13.00	-58.24 HORIZONTAL
6	897.00	-75.99	7.83	-68.16	-13.00	-55.16 HORIZONTAL


Remark:

The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.



Radiated Spurious emissions

DL_CW_MCH_30MHz-1GHz_Vertical



	Freq	Read	Correction	Level	Limit	Over	Pol/Phase
	MHz	Level	Factor	Level	Line	Limit	
		dBm	dB	dBm	dBm	dB	
1	48.67	-75.27	-4.58	-79.85	-13.00	-66.85	VERTICAL
2	58.82	-76.27	-2.84	-79.11	-13.00	-66.11	VERTICAL
3	175.04	-75.50	-3.27	-78.77	-13.00	-65.77	VERTICAL
4	449.56	-75.00	1.87	-73.13	-13.00	-60.13	VERTICAL
5	560.69	-74.00	3.97	-70.03	-13.00	-57.03	VERTICAL
6	890.73	-74.83	8.33	-66.50	-13.00	-53.50	VERTICAL


Remark:

The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.



Radiated Spurious emissions

UL_CW_MCH_30MHz-1GHz_Horizontal



	Freq	Read Level	Correction Factor	Level	Limit Line	Over Limit	Pol/Phase
	MHz	dBm	dB	dBm	dBm	dB	
1	38.62	-76.91	-0.46	-77.37	-13.00	-64.37	HORIZONTAL
2	56.99	-76.77	-2.89	-79.66	-13.00	-66.66	HORIZONTAL
3	243.38	-76.28	-5.56	-81.84	-13.00	-68.84	HORIZONTAL
4	413.27	-74.73	-0.70	-75.43	-13.00	-62.43	HORIZONTAL
5	620.71	-74.65	2.66	-71.99	-13.00	-58.99	HORIZONTAL
6	897.00	-76.42	7.83	-68.59	-13.00	-55.59	HORIZONTAL


Remark:

The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.



Radiated Spurious emissions

UL_CW_MCH_30MHz-1GHz_Vertical



	Freq	Read	Correction	Limit	Over	
	MHz	Level	Factor	Line	Limit	Pol/Phase
		dBm	dB	dBm	dB	
1	49.53	-77.27	-3.59	-80.86	-13.00	-67.86 VERTICAL
2	56.20	-75.09	-2.90	-77.99	-13.00	-64.99 VERTICAL
3	183.20	-76.07	-3.29	-79.36	-13.00	-66.36 VERTICAL
4	444.85	-74.86	1.82	-73.04	-13.00	-60.04 VERTICAL
5	640.61	-75.09	4.52	-70.57	-13.00	-57.57 VERTICAL
6	897.00	-75.46	8.28	-67.18	-13.00	-54.18 VERTICAL

Remark:


The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.



12 Radiated Spurious emissions above 1GHz

Radiated Spurious emissions

DL_CW_MCH_above 1GHz_Horizontal




	Freq	Read Level	Correction Factor	Level	Limit Line	Over Limit	Pol/Phase
	MHz	dBm	dB	dBm	dBm	dB	
1	1202.37	-58.67	1.59	-57.08	-13.00	-44.08	HORIZONTAL
2	1852.17	-60.81	3.40	-57.41	-13.00	-44.41	HORIZONTAL
3	2683.14	-59.46	7.15	-52.31	-13.00	-39.31	HORIZONTAL
4	3595.95	-61.58	12.02	-49.56	-13.00	-36.56	HORIZONTAL
5	6498.63	-62.62	15.25	-47.37	-13.00	-34.37	HORIZONTAL
6	7530.98	-62.53	12.40	-50.13	-13.00	-37.13	HORIZONTAL



Radiated Spurious emissions

DL_CW_MCH_above 1GHz_Vertical




	Freq	Read	Correction	Level	Limit	Over	Pol/Phase
	MHz	Level	Factor	Level	Line	Limit	
		dBm	dB	dBm	dBm	dB	
1	1315.73	-59.13	1.73	-57.40	-13.00	-44.40	VERTICAL
2	1852.17	-60.38	3.65	-56.73	-13.00	-43.73	VERTICAL
3	2699.67	-58.07	7.16	-50.91	-13.00	-37.91	VERTICAL
4	4467.65	-61.71	11.39	-50.32	-13.00	-37.32	VERTICAL
5	6340.89	-62.66	14.98	-47.68	-13.00	-34.68	VERTICAL
6	7348.18	-62.15	13.13	-49.02	-13.00	-36.02	VERTICAL



Radiated Spurious emissions

DL_CW_MCH_1559-1610MHz_Horizontal




	Freq	Read	Correction	Limit	Over	
	MHz	Level	Factor	Line	Limit	Pol/Phase
	MHz	dBm	dB	dBm	dB	
1	1563.07	-59.52	2.02	-57.50	-40.00	-17.50 HORIZONTAL
2	1569.63	-59.69	2.08	-57.61	-40.00	-17.61 HORIZONTAL
3	1578.24	-61.12	2.19	-58.93	-40.00	-18.93 HORIZONTAL
4	1585.37	-60.64	2.23	-58.41	-40.00	-18.41 HORIZONTAL
5	1590.58	-60.09	2.28	-57.81	-40.00	-17.81 HORIZONTAL
6	1599.77	-59.09	2.32	-56.77	-40.00	-16.77 HORIZONTAL



Radiated Spurious emissions

DL_CW_MCH_1559-1610MHz_Vertical




	Freq	Read	Correction	Limit	Over	
	MHz	Level	Factor	Line	Limit	Pol/Phase
		dBm	dB	dBm	dB	
1	1561.26	-60.42	2.32	-58.10	-40.00	-18.10 VERTICAL
2	1569.12	-60.40	2.38	-58.02	-40.00	-18.02 VERTICAL
3	1582.51	-59.77	2.49	-57.28	-40.00	-17.28 VERTICAL
4	1588.64	-59.99	2.53	-57.46	-40.00	-17.46 VERTICAL
5	1596.12	-60.06	2.62	-57.44	-40.00	-17.44 VERTICAL
6	1604.57	-59.69	2.64	-57.05	-40.00	-17.05 VERTICAL



Radiated Spurious emissions

UL_CW_MCH_above 1GHz_Horizontal




	Freq	Read Level	Correction Factor	Level	Limit Line	Over Limit	Pol/Phase
	MHz	dBm	dB	dBm	dBm	dB	
1	1311.46	-58.34	2.16	-56.18	-13.00	-43.18	HORIZONTAL
2	1850.16	-60.14	3.40	-56.74	-13.00	-43.74	HORIZONTAL
3	3103.47	-59.64	7.48	-52.16	-13.00	-39.16	HORIZONTAL
4	3606.32	-61.72	11.89	-49.83	-13.00	-36.83	HORIZONTAL
5	6841.38	-61.97	16.37	-45.60	-13.00	-32.60	HORIZONTAL
6	7625.09	-62.07	12.09	-49.98	-13.00	-36.98	HORIZONTAL



Radiated Spurious emissions

UL_CW_MCH_above 1GHz_Vertical




	Freq	Read Level	Correction Factor	Level	Limit Line	Over Limit	Pol/Phase
	MHz	dBm	dB	dBm	dBm	dB	
1	1216.59	-59.15	1.20	-57.95	-13.00	-44.95	VERTICAL
2	1857.90	-59.95	3.89	-56.06	-13.00	-43.06	VERTICAL
3	2693.10	-58.97	7.16	-51.81	-13.00	-38.81	VERTICAL
4	4555.27	-61.42	11.65	-49.77	-13.00	-36.77	VERTICAL
5	6784.54	-62.71	15.66	-47.05	-13.00	-34.05	VERTICAL
6	7656.97	-62.35	13.16	-49.19	-13.00	-36.19	VERTICAL



Radiated Spurious emissions

UL_CW_MCH_1559-1610MHz_Horizontal




	Freq	Read	Correction	Limit	Over	
	MHz	Level	Factor	Line	Limit	Pol/Phase
	MHz	dBm	dB	dBm	dB	
1	1561.56	-59.34	2.02	-57.32	-40.00	-17.32 HORIZONTAL
2	1571.80	-60.23	2.14	-58.09	-40.00	-18.09 HORIZONTAL
3	1584.04	-59.11	2.23	-56.88	-40.00	-16.88 HORIZONTAL
4	1594.99	-59.70	2.32	-57.38	-40.00	-17.38 HORIZONTAL
5	1597.92	-59.76	2.32	-57.44	-40.00	-17.44 HORIZONTAL
6	1604.88	-59.36	2.35	-57.01	-40.00	-17.01 HORIZONTAL



Radiated Spurious emissions

UL_CW_MCH_1559-1610MHz_Vertical



	Freq	Read	Correction	Limit	Over	
	MHz	Level	Factor	Line	Limit	Pol/Phase
	MHz	dBm	dB	dBm	dB	
1	1562.97	-59.58	2.32	-57.26	-40.00	-17.26 VERTICAL
2	1571.14	-60.69	2.38	-58.31	-40.00	-18.31 VERTICAL
3	1581.09	-59.86	2.49	-57.37	-40.00	-17.37 VERTICAL
4	1594.07	-59.49	2.58	-56.91	-40.00	-16.91 VERTICAL
5	1598.02	-59.37	2.62	-56.75	-40.00	-16.75 VERTICAL
6	1604.36	-58.56	2.64	-55.92	-40.00	-15.92 VERTICAL

--End of Appendix--

