

RF Test Report

Applicant : Winmate Inc.

Product Name : Vehicle Mounted Computer

Trade Name : Winmate

Model Number : FM07MG-K, FM07xxxxxxxxxx ("X" = A~Z,a~z,0~9," -" Blank or Slash for marketing purpose only, no impact safety related constructions or critical components)

Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2020

Received Date : Aug. 12, 2025

Test Period : Sep. 11, 2025 ~ Oct. 23, 2025

Issued Date : Nov. 21, 2025

Issued by

Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
Frequency Range: 9 kHz to 325 GHz
Bade test site :
Test Firm Registration Number: 226252
Test Firm Designation Number: TW0010
Wugu test site :
Test Firm Registration Number: 191812
Test Firm Designation Number: TW0034

Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Revision History

Rev.	Issued Date	Description	Revised by
00	Nov. 21, 2025	Initial Issue	Rowan Hsieh

Verification of Compliance

Applicant : Winmate Inc.

Product Name : Vehicle Mounted Computer

Trade Name : Winmate

Model Number : FM07MG-K, FM07xxxxxxxxxx ("X" = A~Z,a~z,0~9," -"
Blank or Slash for marketing purpose only, no impact safety
related constructions or critical components)

FCC ID : PX9FM07MG

Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2020

Test Result : Complied

Issued By : Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190
Taiwan Accreditation Foundation accreditation number: 1330



Eurofins E&E Wireless Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Eurofins E&E Wireless Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By

: Kai Yu Yang

TABLE OF CONTENTS

1	General Information	5
1.1.	Summary of Test Result	5
1.2.	Testing Location	6
1.3.	Measurement Uncertainty	6
1.4.	Test Site Environment.....	6
2	EUT Description.....	7
3	Test Methodology.....	9
3.1.	Mode of Operation.....	9
3.2.	EUT Test Step	9
3.3.	Configuration of Test System Details.....	10
3.4.	Test Instruments	11
4	Measurement Procedure.....	13
4.1.	Radiated Emission Measurement.....	13
4.2.	Maximum Conducted Output Power Measurement.....	17
4.3.	6 dB RF Bandwidth Measurement.....	18
4.4.	Maximum Power Density Measurement.....	19
4.5.	Out of Band Conducted Emissions Measurement.....	20
4.6.	Antenna Measurement	20
5	Test Results	21
5.1.	Radiated Emission Measurement.....	21
5.2.	Conducted Test Results.....	59

Appendix A. Test Data

Appendix B. Test Plots

Appendix C. Test Setup Photographs

1 General Information

1.1. Summary of Test Result

Standard	Item	Result	Remark
15.207	AC Power Conducted Emission	N/A	Note
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	Max. Output Power	PASS	-----
15.247(a)(2)	6 dB RF Bandwidth	PASS	-----
15.247(e)	Maximum Power Spectral Density	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.203	Antenna Requirement	PASS	-----

Note: In-vehicle products

Decision Rule

☒ Uncertainty is not included.

☐ Uncertainty is included.

Standard	Description
CFR47, Part 15, Subpart C	Intentional Radiators
ANSI C63.10: 2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES

1.2. Testing Location

Lab Name: Eurofins E&E Wireless Taiwan Co., Ltd.

Site Address: ☐ No. 140-1, Changan Street, Bade District, Taoyuan City, Taiwan (R.O.C.)

Site Address: ☒ No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan (R.O.C.)

1.3. Measurement Uncertainty

Test Item	Frequency	Uncertainty				
		BD		WG		
Conducted Output Power		1.1 dB		1.1 dB		
RF Bandwidth		4.5 %		4.5 %		
Power Spectral Density		1.1 dB		1.1 dB		
Duty Cycle		0.3 %		0.3 %		
Test Item	Frequency	Uncertainty				
		96601-BD	96603-BD	96602-WG	96603-WG	96604-WG
Radiated Emission	9 kHz ~ 30 MHz	1.8 dB	1.8 dB	1.6 dB	1.6 dB	1.7 dB
	30 MHz ~ 1000 MHz	4.7 dB	4.6 dB	4.7 dB	4.7 dB	4.5 dB
	1000 MHz ~ 18000 MHz	4.4 dB	4.5 dB	4.5 dB	4.7 dB	5.0 dB
	18000 MHz ~ 26500 MHz	3.6 dB	3.8 dB	3.8 dB	4.0 dB	4.3 dB
	26500 MHz ~ 40000 MHz	3.9 dB	3.9 dB	4.0 dB	4.0 dB	4.4 dB

1.4. Test Site Environment

Items	Required (IEC 60068-1)	Interval(*)
Temperature (°C)	15-35	20-30
Humidity (%RH)	25-75	45-75

(*)The measurement ambient temperature is within this range.

2 EUT Description

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity(except Max. RF Output Power).

Applicant	Winmate Inc. 9F, No.111-6, Shing-De Rd., San-Chung District, New Taipei City 241, Taiwan			
Product Name	Vehicle Mounted Computer			
Trade Name	Winmate			
Model Number	FM07MG-K, FM07xxxxxxxx ("X" = A~Z,a~z,0~9," -" Blank or Slash for marketing purpose only, no impact safety related constructions or critical components)			
Models different description	Market sales differences			
FCC ID	PX9FM07MG			
Frequency Range	2402 ~ 2480 MHz			
Modulation Type	GFSK			
Operate Temp. Range	-20 ~ +60 °C			
EUT Power Rating	+9 VDC, 5.55 A ~ +36 VDC, 1.38 A			
Antenna information	ANT	Model Number	Type	Max. Gain (dBi)
	ANT-0 (Main)	FM07	PIFA Antenna	0.61
	ANT-1 (Aux)	FM07	PIFA Antenna	0.02
Max. RF Output Power	LE, GFSK:	0.00830 W		
	2LE, GFSK:	0.00834 W		
	BLR C2, GFSK:	0.00826 W		
	BLR C8, GFSK:	0.00838 W		

Testing Sample No.	
Test Item	Sample Number
Radiation	C258131_A003
Conducted	C253131_A005

CH	Freq. (MHz)	CH	Freq. (MHz)	CH	Freq. (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
19	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	---	---
13	2428	27	2456	---	---

3 Test Methodology

3.1. Mode of Operation

In the test report use EUT model: FM07MG-K to operate testing.

Decision of Test Eurofins has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode	Final-Test Mode
Transmit Mode	V
BLE 1M	
BLE 2M	V
BLR C2	
BLR C8	V

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes.


By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

3.2. EUT Test Step

1	Setup the EUT shown on "Configuration of Test System Details".
2	Turn on the power of all equipment.
3	Turn on TX function.
4	EUT run test program.

3.3. Configuration of Test System Details

Radiated Emissions



Devices Description					
	Product	Manufacturer	Model Number	Serial Number	Power Cord
(1)	USB Cable	Shinintech Electronic Co., LTD	24-800-E010	---	---

3.4. Test Instruments

For Conducted

Test Period: Sep. 11, 2025 ~ Sep. 16, 2025

Testing Engineer: Yang Wang

Test Site		RF05-WG				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	Power Sensor	Anritsu	MA24408A	11998	Jan. 17, 2025	1 year
☒	Spectrum Analyzer (10 Hz~26.5 GHz)	Keysight	N9010B	MY64020105	Jan. 20, 2025	1 year

Note: N.C.R. = No Calibration Request.

For Radiated Emissions

Test Period: Sep. 16, 2025 ~ Oct. 23, 2025

Testing Engineer: Jason Yeh

Radiation test sites		Semi Anechoic Room 96603-WG				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	LOOP Antenna (9 kHz~30 MHz)	Schwarzbeck Mess-Elektronik	FMZB 1513-60	00031	Mar. 06, 2025	1 year
☒	Trilog Broadband Antenna (30 MHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	1276	Jan. 20, 2025	1 year
☒	Broadband Horn Antenna (1 GHz~18 GHz)	RF SPIN	DRH18-E	210307A18ES	Dec. 10, 2024	1 year
☒	Broadband Horn Antenna (15 GHz~40 GHz)	Schwarzbeck Mess-Elektronik	BBHA9170	1133	Nov. 01, 2024	1 year
☒	Spectrum Analyzer (2 Hz~50 GHz)	KEYSIGHT	N9030B	MY57143537	Mar. 10, 2025	1 year
☒	Pre-Amplifier	EMCI	EMC001330	980859	Nov. 27, 2024	1 year
☒	Pre-Amplifier	EMCI	EMC118A45SE	980818	Dec. 12, 2024	1 year
☒	Pre-Amplifier	EMCI	EMC184045SE	980861	Dec. 18, 2024	1 year
☒	Coaxial Cable (9 kHz~1000 MHz)	EMCI	EMCCFD400-NM-NM-2000	211009	Oct. 24, 2024	1 year
☒	Coaxial Cable (9 kHz~1000 MHz)	EMCI	EMCCFD400-NM-NM-2000	211010	Oct. 24, 2024	1 year
☒	Coaxial Cable (9 kHz~1000 MHz)	EMCI	EMCCFD400-NM-NM-6000	211018	Oct. 24, 2024	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM-1000	211029	Oct. 24, 2024	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM-2000	211033	Oct. 24, 2024	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM-8000	211038	Oct. 24, 2024	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM-KM-600	211211	Jan. 15, 2025	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM-KM-2000	211210	Jan. 15, 2025	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM-KM-6000	211209	Jan. 15, 2025	1 year
☒	Highpass Filter	Warison	WFIL-H3000-20000F	WR4BBFWC2B1	Oct. 24, 2024	1 year
☒	Highpass Filter	Warison	WFIL-H8000-26000F	001	Oct. 24, 2024	1 year
☒	Software	R_RAM	V1.4	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request.

4 Measurement Procedure

4.1. Radiated Emission Measurement

■ Limit


According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	$2400 / F$ (kHz)	300
0.490 – 1.705	$24000 / F$ (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3


** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

■ Setup


9 kHz ~ 30 MHz



Below 1 GHz



Above 1 GHz



■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height, top surface 1.0 x 1.5 meter. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 30 MHz the resolution bandwidth is set to 10 kHz for peak detection measurements or 9 kHz for quasi-peak detection measurements. The video bandwidth is 3 times of the resolution bandwidth.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements and 10 Hz for average measurements when Duty cycle >0.98 / $1/T$ for average measurements when Duty cycle <0.98 . A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Biconilog/Horn Antenna were used in frequency 30 MHz to 18 GHz at a distance of 3 meter. Loop/Horn Antenna was used in frequency 9 kHz to 30 MHz and 18 to 26.5 GHz at a distance of 1 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts per meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) + AF (dBuV) + CL (dBuV) - Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV) - Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30 dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10


Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.

4.2. Maximum Conducted Output Power Measurement

■ Limit

For systems using digital modulation in the 2400-2483.5 MHz, the limit for peak output power is 30 dBm.

■ Test Setup



■ Test Procedure

The testing follows the Measurement Procedure of ANSI C63.10:2020 section 11.9.2.3.2 Method AVGPM or section 11.9.1.2 Method PKPM1.

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor..


4.3. 6 dB RF Bandwidth Measurement

■ Limit

6 dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

99 % Occupied Bandwidth: N/A

■ Test Setup



■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10:2020 section 11.8.2 option 2 for compliance to FCC 47CFR 15.247 requirements.

6 dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.


The test was performed at 3 channels (Channel low, middle, high)

4.4. Maximum Power Density Measurement

■ Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

■ Test Setup



■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10:2020 section 11.10.2 Method PKPSD.


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = No faster than coupled (auto) time.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.5. Out of Band Conducted Emissions Measurement

■ Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

■ Test Setup



■ Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function. All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels.

4.6. Antenna Measurement

■ Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ Antenna Connector Construction


See section 2 – antenna information.

5 Test Results

5.1. Radiated Emission Measurement


Below 1 GHz

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Transmit mode		
Polarization:	Horizontal		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	38.73	51.96	-12.45	39.51	40.00	-0.49	QP
2	128.94	53.71	-13.45	40.26	43.50	-3.24	QP
3	291.90	56.00	-11.36	44.64	46.00	-1.36	QP
4	343.31	52.08	-10.17	41.91	46.00	-4.10	QP
5	717.73	46.33	-2.93	43.40	46.00	-2.60	QP
6	960.23	40.31	0.22	40.53	54.00	-13.47	QP

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Transmit mode		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	38.98	48.07	-12.45	35.62	40.00	-4.38	QP
2	79.47	54.51	-16.28	38.23	40.00	-1.77	QP
3	129.91	56.54	-13.35	43.19	43.50	-0.31	QP
4	343.31	55.22	-10.17	45.05	46.00	-0.95	QP
5	719.67	46.87	-2.92	43.95	46.00	-2.05	QP
6	960.23	41.88	0.22	42.10	54.00	-11.90	QP

Harmonic


Above 1 GHz

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2402 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	40.10	2.46	42.56	74.00	-31.44	PEAK
2	7206.00	38.24	8.01	46.25	74.00	-27.75	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2402 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	39.93	2.46	42.39	74.00	-31.61	PEAK
2	7206.00	37.90	8.01	45.91	74.00	-28.09	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2440 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4880.00	40.92	2.61	43.53	74.00	-30.47	PEAK
2	7320.00	38.14	8.02	46.16	74.00	-27.84	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2440 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4880.00	40.19	2.61	42.80	74.00	-31.20	PEAK
2	7320.00	37.92	8.02	45.94	74.00	-28.06	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2480 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4960.00	40.15	2.23	42.38	74.00	-31.62	PEAK
2	7440.00	38.38	7.82	46.20	74.00	-27.80	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2480 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4960.00	40.60	2.23	42.83	74.00	-31.17	PEAK
2	7440.00	38.53	7.82	46.35	74.00	-27.65	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2402 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	40.02	2.46	42.48	74.00	-31.52	PEAK
2	7206.00	37.68	8.01	45.69	74.00	-28.31	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2402 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	41.23	2.46	43.69	74.00	-30.31	PEAK
2	7206.00	37.73	8.01	45.74	74.00	-28.26	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2440 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4880.00	40.56	2.61	43.17	74.00	-30.83	PEAK
2	7320.00	38.26	8.02	46.28	74.00	-27.72	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2440 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4880.00	41.88	2.61	44.49	74.00	-29.51	PEAK
2	7320.00	38.46	8.02	46.48	74.00	-27.52	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2480 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4960.00	40.54	2.23	42.77	74.00	-31.23	PEAK
2	7440.00	38.90	7.82	46.72	74.00	-27.28	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2480 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4960.00	41.39	2.23	43.62	74.00	-30.38	PEAK
2	7440.00	38.36	7.82	46.18	74.00	-27.82	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Horizontal		
Remark:	Bluetooth + WLAN 2.4 GHz + WCDMA		




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	3760.00	46.20	0.61	46.81	74.00	-27.19	PEAK
2	4804.00	38.61	2.75	41.36	74.00	-32.64	PEAK
3	4904.00	37.58	2.42	40.00	74.00	-34.00	PEAK
4	5640.00	45.08	3.62	48.70	68.20	-19.50	PEAK
5	7206.00	37.83	8.14	45.97	68.20	-22.23	PEAK
6	7356.00	39.02	8.05	47.07	74.00	-26.93	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Vertical		
Remark:	Bluetooth + WLAN 2.4 GHz + WCDMA		




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	3760.00	46.55	0.61	47.16	74.00	-26.84	PEAK
2	4804.00	42.52	2.75	45.27	74.00	-28.73	PEAK
3	4904.00	43.25	2.42	45.67	74.00	-28.33	PEAK
4	5640.00	40.68	3.62	44.30	68.20	-23.90	PEAK
5	7206.00	38.35	8.14	46.49	68.20	-21.71	PEAK
6	7356.00	42.04	8.05	50.09	74.00	-23.91	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Horizontal		
Remark:	Bluetooth + WLAN 2.4 GHz + LTE		




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	41.17	2.75	43.92	74.00	-30.08	PEAK
2	4904.00	42.93	2.42	45.35	74.00	-28.65	PEAK
3	5190.00	44.38	2.54	46.92	68.20	-21.28	PEAK
4	7206.00	39.04	8.14	47.18	68.20	-21.02	PEAK
5	7356.00	40.63	8.05	48.68	74.00	-25.32	PEAK
6	7785.00	42.23	7.33	49.56	68.20	-18.64	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Vertical		
Remark:	Bluetooth + WLAN 2.4 GHz + LTE		




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	41.66	2.75	44.41	74.00	-29.59	PEAK
2	4904.00	43.09	2.42	45.51	74.00	-28.49	PEAK
3	5190.00	44.13	2.54	46.67	68.20	-21.53	PEAK
4	7206.00	40.14	8.14	48.28	68.20	-19.92	PEAK
5	7356.00	40.51	8.05	48.56	74.00	-25.44	PEAK
6	7785.00	43.55	7.33	50.88	68.20	-17.32	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Horizontal		
Remark:	Bluetooth + WLAN 5 GHz + WCDMA		




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	3760.00	44.45	0.61	45.06	74.00	-28.94	PEAK
2	4804.00	42.56	2.75	45.31	74.00	-28.69	PEAK
3	5640.00	43.53	3.62	47.15	68.20	-21.05	PEAK
4	7206.00	37.84	8.14	45.98	68.20	-22.22	PEAK
5	10460.00	40.76	9.31	50.07	68.20	-18.13	PEAK
6	15690.00	40.05	10.44	50.49	74.00	-23.51	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Vertical		
Remark:	Bluetooth + WLAN 5 GHz + WCDMA		




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	3760.00	41.56	0.61	42.17	74.00	-31.83	PEAK
2	4804.00	40.31	2.75	43.06	74.00	-30.94	PEAK
3	5640.00	42.65	3.62	46.27	68.20	-21.93	PEAK
4	7206.00	37.33	8.14	45.47	68.20	-22.73	PEAK
5	10460.00	42.09	9.31	51.40	68.20	-16.80	PEAK
6	15690.00	40.07	10.44	50.51	74.00	-23.49	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Horizontal		
Remark:	Bluetooth + WLAN 5 GHz + LTE		



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	40.77	2.75	43.52	74.00	-30.48	PEAK
2	5190.00	41.75	2.54	44.29	68.20	-23.91	PEAK
3	7206.00	38.30	8.14	46.44	68.20	-21.76	PEAK
4	7785.00	40.87	7.33	48.20	68.20	-20.00	PEAK
5	10460.00	40.11	9.31	49.42	68.20	-18.78	PEAK
6	15690.00	39.99	10.44	50.43	74.00	-23.57	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	Co-location		
Polarization:	Vertical		
Remark:	Bluetooth + WLAN 5 GHz + LTE		




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	4804.00	40.77	2.75	43.52	74.00	-30.48	PEAK
2	5190.00	41.75	2.54	44.29	68.20	-23.91	PEAK
3	7206.00	38.30	8.14	46.44	68.20	-21.76	PEAK
4	7785.00	40.87	7.33	48.20	68.20	-20.00	PEAK
5	10460.00	40.11	9.31	49.42	68.20	-18.78	PEAK
6	15690.00	39.99	10.44	50.43	74.00	-23.57	PEAK

Band Edge


Peak

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2402 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2374.68	53.26	-4.16	49.10	74.00	-24.90	PEAK
2	2390.00	51.18	-4.21	46.97	74.00	-27.03	PEAK
3	2401.41	104.65	-4.25	100.40	74.00	26.40	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2402 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2325.84	54.05	-4.08	49.97	74.00	-24.03	PEAK
2	2390.00	51.49	-4.21	47.28	74.00	-26.72	PEAK
3	2402.40	108.39	-4.25	104.14	74.00	30.14	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2480 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2479.45	100.02	-4.27	95.75	74.00	21.75	PEAK
2	2483.50	53.06	-4.25	48.81	74.00	-25.19	PEAK
3	2493.58	53.37	-4.23	49.14	74.00	-24.86	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2480 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2479.45	107.89	-4.27	103.62	74.00	29.62	PEAK
2	2483.50	56.86	-4.25	52.61	74.00	-21.39	PEAK
3	2483.56	56.86	-4.25	52.61	74.00	-21.39	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2402 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2376.55	53.33	-4.17	49.16	74.00	-24.84	PEAK
2	2390.00	51.54	-4.21	47.33	74.00	-26.67	PEAK
3	2401.74	105.01	-4.25	100.76	74.00	26.76	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2402 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2324.08	53.25	-4.08	49.17	74.00	-24.83	PEAK
2	2390.00	50.97	-4.21	46.76	74.00	-27.24	PEAK
3	2402.18	108.30	-4.25	104.05	74.00	30.05	PEAK

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2480 MHz		
Polarization:	Horizontal		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2479.72	99.61	-4.27	95.34	74.00	21.34	PEAK
2	2483.50	52.17	-4.25	47.92	74.00	-26.08	PEAK
3	2490.97	53.39	-4.23	49.16	74.00	-24.84	PEAK


Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2480 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2479.78	108.03	-4.27	103.76	74.00	29.76	PEAK
2	2483.50	54.49	-4.25	50.24	74.00	-23.76	PEAK
3	2483.59	54.80	-4.25	50.55	74.00	-23.45	PEAK


Average

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2402 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2384.80	40.33	-4.20	36.13	54.00	-17.87	AVG
2	2390.00	39.93	-4.21	35.72	54.00	-18.28	AVG

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2402 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2384.80	40.30	-4.20	36.10	54.00	-17.90	AVG
2	2390.00	40.01	-4.21	35.80	54.00	-18.20	AVG

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2480 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2483.50	43.17	-4.25	38.92	54.00	-15.08	AVG
2	2483.53	42.94	-4.25	38.69	54.00	-15.31	AVG

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLE 2M 2480 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2483.50	48.68	-4.25	44.43	54.00	-9.57	AVG
2	2483.53	48.37	-4.25	44.12	54.00	-9.88	AVG

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2402 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2324.74	40.21	-4.08	36.13	54.00	-17.87	AVG
2	2390.00	40.01	-4.21	35.80	54.00	-18.20	AVG

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2402 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2325.84	40.18	-4.08	36.10	54.00	-17.90	AVG
2	2390.00	39.90	-4.21	35.69	54.00	-18.31	AVG

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2480 MHz		
Polarization:	Horizontal		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2483.50	41.02	-4.25	36.77	54.00	-17.23	AVG
2	2483.86	41.01	-4.25	36.76	54.00	-17.24	AVG

Test Site:	96603 - WG	Standard:	Part 15.247
Test Mode:	BLR C8 2480 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	2483.50	44.39	-4.25	40.14	54.00	-13.86	AVG
2	2483.53	44.23	-4.25	39.98	54.00	-14.02	AVG

5.2. Conducted Test Results

Duty cycle

Reference Appendix A / Appendix B

Maximum Conducted Output Power Measurement

Reference Appendix A

6 dB RF Bandwidth Measurement

Reference Appendix A / Appendix B

Maximum Power Density Measurement

Reference Appendix A / Appendix B

Out of Band Conducted Emissions Measurement

Reference level

Reference Appendix B

Out of Band Conducted Emissions

Reference Appendix B

Conducted Band Edge

Reference Appendix B

---END---