




Appendix B

Peak Output Power

Carrier power conducted (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ch.: 0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to FCC Part 15
Comment 1: Conducted, 50 Ohm Load
Comment 2: Freq:2.401GHz Pmax:24.57 RBW: 3 MHz



Carrier power conducted (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ch.: 40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to FCC Part 15
Comment 1: Conducted, 50 Ohm Load
Comment 2: Freq:2.442GHz Pmax:24.08 RBW: 3 MHz



Carrier power conducted (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ch.: 78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to FCC Part 15
Comment 1: Conducted, 50 Ohm Load
Comment 2: Freq:2.481GHz Pmax:23.37 RBW: 3 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:1 FP (Ch:0 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2401,66MHz Pmax:23,56dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:1 FP (Ch:0 Data:PSRBS)
Applicant: Kirk Telecom A/S

Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2401,39MHz Pmax:24,08dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:2 FP (Ch:0 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)

Test Site / Operator: ETS / Mr. Matz

Test Specification: according to § 15.247

Comment 1: Dist.: 3m, Ant.: HL025

Comment 2: Freq:2401,66MHz Pmax:26,86dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:2 FP (Ch:0 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)

Test Site / Operator: ETS / Mr. Matz

Test Specification: according to § 15.247

Comment 1: Dist.: 3m, Ant.: HL025


Comment 2: Freq:2401,57MHz Pmax:21,64dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRF4 2G4 Ant:1 FP (Ch:40 Data:PSRBS)
Applicant: Kirk Telecom A/S

Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,67MHz Pmax:23,09dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:1 FP (Ch:40 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)

Test Site / Operator: ETS / Mr. Matz

Test Specification: according to § 15.247

Comment 1: Dist.: 3m, Ant.: HL025


Comment 2: Freq:2442,49MHz Pmax:23,42dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:2 FP (Ch:40 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,67MHz Pmax:27,10dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRF4 2G4 Ant:2 FP (Ch:40 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,86MHz Pmax:21,56dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:1 FP (Ch:78 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2481,36MHz Pmax:21,91dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:1 FP (Ch:78 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2481,27MHz Pmax:22,55dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:2 FP (Ch:78 Data:PSRBS)
Applicant: Kirk Telecom A/S

Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)
Test Site / Operator: ETS / Mr. Matz
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2481,18MHz Pmax:26,12dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT/Model : 2,4GHz DECT/ WRFP4 2G4 Ant:2 FP (Ch:78 Data:PSRBS)
Applicant: Kirk Telecom A/S


Temperature/ Voltage: 22°C / 230 V (AC/DC adaptor)

Test Site / Operator: ETS / Mr. Matz

Test Specification: according to § 15.247

Comment 1: Dist.: 3m, Ant.: HL025


Comment 2: Freq:2481,27MHz Pmax:21,87dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2,4 GHz DECT / WRFP4 2G4 Ant:Ext. FP (Ch:0 Data:PSRBS)
Manufacturer: Kirk Telecom A/S


Test Site / Operator: ETS / Mr. Matz
Temperature/ Voltage: 23°C / 230 V (AC/DC adaptor)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2401,20MHz Pmax:24,70dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2,4 GHz DECT / WRFP4 2G4 Ant:Ext. FP (Ch:0 Data:PSRBS)
Manufacturer: Kirk Telecom A/S


Test Site / Operator: ETS / Mr. Matz
Temperature/ Voltage: 23°C / 230 V (AC/DC adaptor)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2401,11MHz Pmax:29,58dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2,4 GHz DECT / WRFP4 2G4 Ant:Ext. FP (Ch:40 Data:PSRBS)
Manufacturer: Kirk Telecom A/S


Test Site / Operator: ETS / Mr. Matz
Temperature/ Voltage: 23°C / 230 V (AC/DC adaptor)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,02MHz Pmax:26,40dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2,4 GHz DECT / WRFP4 2G4 Ant:Ext. FP (Ch:40 Data:PSRBS)
Manufacturer: Kirk Telecom A/S


Test Site / Operator: ETS / Mr. Matz
Temperature/ Voltage: 23°C / 230 V (AC/DC adaptor)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,12MHz Pmax:29,27dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2,4 GHz DECT / WRFP4 2G4 Ant:Ext. FP (Ch:78 Data:PSRBS)
Manufacturer: Kirk Telecom A/S


Test Site / Operator: ETS / Mr. Matz
Temperature/ Voltage: 23°C / 230 V (AC/DC adaptor)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2481,18MHz Pmax:26,27dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2,4 GHz DECT / WRFP4 2G4 Ant:Ext. FP (Ch:78 Data:PSRBS)
Manufacturer: Kirk Telecom A/S


Test Site / Operator: ETS / Mr. Matz
Temperature/ Voltage: 23°C / 230 V (AC/DC adaptor)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2480,99MHz Pmax:28,24dBm RBW:4MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:1 Ch.0
Manufacturer: Kirk Telecom A/S

Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.401GHz Pmax:20.66dBm RBW: 5 MHz




— MES 10. FCC_2.4G_dBm_v
— LIM FCC_30dBm

Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.401GHz Pmax:24.98dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.402GHz Pmax:20.92dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.401GHz Pmax:24.92dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:2 Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.401GHz Pmax:21.63dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:2 Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.402GHz Pmax:25.23dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:2 Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to §15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.402GHz Pmax:21.63dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:1 Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.401GHz Pmax:25.18dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:3 (ext.) Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to §15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.401GHz Pmax:27.83dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:3 (ext.) Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.400GHz Pmax:27.68dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:3 (ext.) Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.401GHz Pmax:27.63dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:3 (ext.) Ch.0
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to §15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.400GHz Pmax:27.75dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:1 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.442GHz Pmax:20.41dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.443GHz Pmax:21.56dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC $\pm 15\%$ (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.442GHz Pmax:20.41dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.442GHz Pmax:21.47dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:2 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.443GHz Pmax:20.35dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:2 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.442GHz Pmax:21.30dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:2 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.443GHz Pmax:20.41dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:2 Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.443GHz Pmax:21.56dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:3 (ext.) Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.443GHz Pmax:26.00dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:3 (ext.) Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.442GHz Pmax:25.60dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:3 (ext.) Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.443GHz Pmax:25.99dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:3 (ext.) Ch.40
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.442GHz Pmax:25.47dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to §15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.481GHz Pmax:21.40dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:1 Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to §15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.482GHz Pmax:19.94dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.481GHz Pmax:21.46dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:1 Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.482GHz Pmax:19.94dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:2 Ch.78
Manufacturer: Kirk Telecom A/S

Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.481GHz Pmax:21.40dBm RBW: 5 MHz




— MES 10. FCC 2.4G_dBm_v
— LIM FCC_30dBm

Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:2 Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to §15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.481GHz Pmax:23.82dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:2 Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.482GHz Pmax:21.42dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:2 Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC +15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.481GHz Pmax:23.88dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRF4 2G4 / Ant.:3 (ext.) Ch.78
Manufacturer: Kirk Telecom A/S


Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to §15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.482GHz Pmax:26.78dBm RBW: 5 MHz



Carrier power (dBm)
FCC RULES PART 15, SUBPART C

EUT / Model: 2.4 GHz DECT / WRFP4 2G4 / Ant.:3 (ext.) Ch.78
Manufacturer: Kirk Telecom A/S

Operating Condition: Unom:230 V AC -15% (adaptor), Tnom:23°C
Test Site / Operator: ETS / Mr. Treffke
Test Specification: according to S15247 / mode: Tx
Comment 1: Dist.: 3m, Ant.: BBHA9120D
Comment 2: Freq:2.482GHz Pmax:24.46dBm RBW: 5 MHz




Appendix C

Spurious Emissions radiated - Transmitter operating

Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRF-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 0)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2401,14MHz Pmax:122,45dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 0)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2401,15MHz Pmax:121,82dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 40)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2404,53MHz Pmax:55,24dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 40)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2401,38MHz Pmax:54,73dB μ V/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 78)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2400,56MHz Pmax:55,69dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 78)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2405,45MHz Pmax:55,44dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 0)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,79MHz Pmax:55,79dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 0)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2443,67MHz Pmax:55,69dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 40)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,12MHz Pmax:121,48dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 40)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2442,23MHz Pmax:121,97dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)


Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 78)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2443,43MHz Pmax:56,12dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRF-2G4
Manufacturer: KIRK telecom A/S (external antenna)

Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 78)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2437,60MHz Pmax:55,79dBμV/m RBW=100KHz



Carrier power (Field Strength)
FCC RULES PART 15, SUBPART C)

EUT / Model: 2.4 GHz Communication System / WRFP-2G4
Manufacturer: KIRK telecom A/S (external antenna)

Test Site / Operator: ETS / Mr.Matz
Temperature/ Voltage: 23°C / 9V (230V AC/DC adaptor), (mode Tx, Ch 0)
Test Specification: according to § 15.247
Comment 1: Dist.: 3m, Ant.: HL025
Comment 2: Freq:2477,75MHz Pmax:55,86dBμV/m RBW=100KHz

