

RF Exposure Report

Report No.: SA120524E01G

FCC ID: PY312200202

Test Model: WNDAP620

Received Date: May 24, 2012

Test Date: May 31 to June 01, 2012 and Sep. 21, 2015

Issued Date: Sep. 30, 2015

Applicant: Netgear Incorporated.

Address: 350 East Plumeria Drive San Jose California United States 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (3): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
3 Calculation Result of Maximum Conducted Power	7



A D T

Release Control Record

Issue No.	Description	Date Issued
SA120524E01G	Original release.	Sep. 30, 2015

1 Certificate of Conformity

Product: ProSafe 3x3 Single Radio, Dual Band Wireless-N Access Point

Brand: Netgear

Test Model: WNDAP620

Sample Status: ENGINEERING SAMPLE

Applicant: Netgear Incorporated.

Test Date: May 31 to June 01, 2012 and Sep. 21, 2015

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Sep. 30, 2015
Claire Kuan / Specialist

Approved by :  , **Date:** Sep. 30, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Internal Antenna (For 2.4GHz / 5GHz)					
Transmitter Circuit	Antenna Type	Peak Gain (dBi)			
		2.4GHz	5GHz Band 1	5GHz Band 4	
Chain (0)	Dipole	2.3	5.9	5.3	
Chain (1)	Dipole	2.3	5.9	4.9	
Chain (2)	Dipole	2.3	5	5.2	
External Antenna (For 2.4GHz)					
Model	Antenna Type	Gain (dBi) (Exclude cable loss)	Cable Loss (dB)	Net Gain (dBi) (Include cable loss)	Connector Type
ANT-32405	Dipole	5	3.68	1.32	SMA Plug Reverse

3 Calculation Result of Maximum Conducted Power

15.247 (2.4GHz) data was copied from the original test report (Report No.: SA120524E01)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	587.684	7.07	20	0.59549	1
5180-5240	45.508	10.38	20	0.09881	1
5745-5825	140.777	9.91	20	0.27432	1

NOTE:

2.4GHz: Directional gain = 2.3dBi + 10 log (3)= 7.07 dBi

5GHz (5150-5250MHz): Directional gain = 10 log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})² / 3] = 10.38dBi

5GHz (5725-5850MHz): Directional gain = 10 log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})² / 3] = 9.91dBi

--- END ---