FCC Test Report

FCC ID	:	**PY313400247**
Equipment	:	**Home Monitoring IP Camera**
Model No.	:	**HMNC100**
Brand Name	:	**NETGEAR**
Applicant	:	**NETGEAR, Inc.**
Address	:	**350 East Plumeria Drive, San Jose, California 95134, USA**
Standard	:	**47 CFR FCC Part 15.247**
Received Date	:	**Feb. 25, 2014**
Tested Date	:	**Mar. 05 ~ Mar. 21, 2014**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Testing Laboratory
2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 8
1.3 Test Setup Chart 8
1.4 The Equipment List 9
1.5 Test Standards 10
1.6 Measurement Uncertainty 10

2 TEST CONFIGURATION 11

2.1 Testing Condition 11
2.2 The Worst Test Modes and Channel Details 11

3 TRANSMITTER TEST RESULTS 12

3.1 Conducted Emissions 12
3.2 6dB and Occupied Bandwidth 15
3.3 RF Output Power 18
3.4 Power Spectral Density 20
3.5 Unwanted Emissions into Restricted Frequency Bands 22
3.6 Emissions in Non-Restricted Frequency Bands 50

4 TEST LABORATORY INFORMATION 63

Release Record

Report No.	Version	Description	Issued Date
FR422501AC	Rev. 01	Initial issue	Apr. 09, 2014

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.160MHz 56.04 (Margin -9.43dB) - QP	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2483.50MHz 53.84 (Margin -0.16dB) - AV	Pass
15.247(b)(3)	Fundamental Emission Output Power	Power [dBm]: 11b: 23.14 11g: 24.69 HT20: 24.61 HT40: 20.46	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	**IEEE Std. 802.11**	**Ch. Freq. (MHz)**	**Channel Number**	**Transmit Chains (N_{TX})**	**Data Rate / MCS**
2400-2483.5	b	2412-2462	1-11 [11]	2	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	2	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	MCS 0-15
Note 1: RF output power specifies that Maximum Peak Conducted Output Power. Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation. Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.					

1.1.2 Antenna Details

Ant. No.	Type	Operating Frequency (MHz) / Gain (dBi)				
		2400~2483.5	**5150~5250**	**5250~5350**	**5470~5725**	**5725~5850**
1	PIFA	1.66	3.12	0.97	3.29	2.83
2	PIFA	0.45	0.55	1.59	3.25	3.15

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from AC adapter

1.1.4 Accessories

Accessories		
No.	**Equipment**	**Description**
1	AC adapter	Brand Name: NETGEAR Model Name: AD810F13 Power Rating: I/P: 100-240Vac, 50-60Hz, 0.3A O/P: 5.0Vdc, 2.0A Power Line: DC 3m non-shielded cable w/o core
2	AC adapter	Brand Name: NETGEAR Model Name: 2AAM010B NA Power Rating: I/P: 100-240Vac, 50-60Hz, 0.35A O/P: 5.0Vdc, 2.0A Power Line: DC 3m non-shielded cable w/o core
3	USB to LAN connector	0.6m, shielded cable w/o core.

1.1.5 Channel List

Frequency band (MHz)		**2400~2483.5**	
802.11 b / g / n HT20		**802.11n HT40**	
Channel	**Frequency(MHz)**	**Channel**	**Frequency(MHz)**
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	---	---
9	2452	---	---
10	2457	---	---
11	2462	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	Hyperterminal, V5.1		
Duty Cycle and Duty Factor	**Mode**	**Duty cycle (%)**	**Duty factor (dB)**
	11b	100.00%	0.00
	11g	98.29%	0.08
	HT20	98.17%	0.08
	HT40	95.65%	0.19

1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	18
11b	2437	17
11b	2462	17
11g	2412	14.5
11g	2437	20
11g	2462	15
HT20	2412	13
HT20	2437	20
HT20	2462	13.5
HT40	2422	8.5
HT40	2437	14
HT40	2452	8

1.2 Local Support Equipment List

N/A

1.3 Test Setup Chart

Test Setup Diagram


1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 24, 2013	Apr. 23, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV40	101498	Jan. 25, 2014	Jan. 24, 2015
Receiver	R&S	ESR3	101658	Jan. 10, 2014	Jan. 09, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 02, 2014	Jan. 01, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 13, 2014	Feb. 12, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014
Preamplifier	Burgeon	BPA-530	SN:100219	Nov. 28, 2013	Nov. 27, 2014
Preamplifier	Agilent	83017A	MY39501308	Dec. 16, 2013	Dec. 15, 2014
Preamplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 16, 2013	Dec. 15, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 16, 2013	Dec. 15, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 16, 2013	Dec. 15, 2014
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 16, 2013	Dec. 15, 2014
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 16, 2013	Dec. 15, 2014
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission above 1GHz				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Note: Calibration Interval of instruments listed above is two year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247
ANSI C63.10-2009
FCC KDB 558074 D01 DTS Meas Guidance v03r01
FCC KDB 662911 D01 Multiple Transmitter Output v02r01

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	**Uncertainty**
Bandwidth	±35.286 Hz
Conducted power	±0.536 dB
Frequency error	±35.286 Hz
Temperature	±0.3 ^{o}C
Conducted emission	±2.946 dB
AC conducted emission	±2.43 dB
Radiated emission	±2.49 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	21°C / 66%	Peter Lin
Radiated Emissions	03CH01-WS	20°C / 62%	Haru Yang
RF Conducted	TH01-WS	22°C / 64%	Felix Sung

- FCC site registration No.: 657002
- IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	11g	2437	6 Mbps	---
Radiated Emissions ≤1GHz	11g	2437	6 Mbps	---
Radiated Emissions >1GHz Fundamental Emission Output Power 6dB bandwidth Power spectral density	11b 11g HT20 HT40	2412 / 2437 / 2462 2412 / 2437 / 2462 2412 / 2437 / 2462 2422 / 2437 / 2452	1 Mbps 6 Mbps MCS 0 MCS 0	---

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
2. 2 adapters are used for this device. After pretest, AC adapter 2 (model: 2AAM010B NA) was found as the worst case and was record in this test report.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation	11g	Test Freq. (MHz)	2437
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.160	40.87	55.47	-14.60	40.37	0.41	0.09	Average
2*	0.160	56.04	65.47	-9.43	55.54	0.41	0.09	QP
3	0.217	31.95	52.92	-20.97	31.36	0.43	0.16	Average
4	0.217	48.81	62.92	-14.11	48.22	0.43	0.16	QP
5	0.260	25.13	51.43	-26.30	24.54	0.46	0.13	Average
6	0.260	43.20	61.43	-18.23	42.61	0.46	0.13	QP
7	0.334	24.13	49.35	-25.22	23.55	0.50	0.08	Average
8	0.334	42.98	59.35	-16.37	42.40	0.50	0.08	QP
9	0.440	14.95	47.07	-32.12	14.35	0.55	0.05	Average
10	0.440	34.18	57.07	-22.89	33.58	0.55	0.05	QP
11	11.139	17.89	50.00	-32.11	16.01	1.76	0.12	Average
12	11.139	26.74	60.00	-33.26	24.86	1.76	0.12	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation	11g	Test Freq. (MHz)	2437
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.156	44.17	55.65	-11.48	43.60	0.49	0.08	Average
2*	0.156	55.15	65.65	-10.50	54.58	0.49	0.08	QP
3	0.226	31.08	52.61	-21.53	30.39	0.53	0.16	Average
4	0.226	46.97	62.61	-15.64	46.28	0.53	0.16	QP
5	0.320	26.99	49.71	-22.72	26.32	0.58	0.09	Average
6	0.320	41.42	59.71	-18.29	40.75	0.58	0.09	QP
7	0.447	15.69	46.93	-31.24	15.01	0.63	0.05	Average
8	0.447	33.15	56.93	-23.78	32.47	0.63	0.05	QP
9	0.564	13.40	46.00	-32.60	12.67	0.68	0.05	Average
10	0.564	28.89	56.00	-27.11	28.16	0.68	0.05	QP
11	11.559	19.45	50.00	-30.55	17.43	1.90	0.12	Average
12	11.559	28.35	60.00	-31.65	26.33	1.90	0.12	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N_{TX}	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	2	2412	7.25	7.07	---	---	500
11b	2	2437	7.13	7.07	---	---	500
11b	2	2462	7.07	7.07	---	---	500
11g	2	2412	16.35	16.35	---	---	500
11g	2	2437	16.00	15.88	---	---	500
11g	2	2462	16.35	16.35	---	---	500
HT20	2	2412	17.16	16.81	---	---	500
HT20	2	2437	16.81	16.52	---	---	500
HT20	2	2462	17.16	17.57	---	---	500
HT40	2	2422	35.13	35.13	---	---	500
HT40	2	2437	35.13	35.13	---	---	500
HT40	2	2452	35.13	35.13	---	---	500

Worst Plots



Modulation Mode	N_{TX}	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	2	2412	12.45	12.88	---	---
11b	2	2437	12.55	12.70	---	---
11b	2	2462	12.45	12.70	---	---
11g	2	2412	16.64	16.61	---	---
11g	2	2437	17.26	16.97	---	---
11g	2	2462	16.61	16.57	---	---
HT20	2	2412	17.73	17.73	---	---
HT20	2	2437	17.98	17.91	---	---
HT20	2	2462	17.73	17.69	---	---
HT40	2	2422	36.08	36.01	---	---
HT40	2	2437	36.14	36.08	---	---
HT40	2	2452	36.08	36.01	---	---

Worst Plots



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

☒ Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

☐ Antenna gain > 6dBi

☐ Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB

☐ Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

☒ Maximum Peak Conducted Output Power

☐ **Spectrum analyzer**

1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.

☒ **Power meter**

1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

☒ Maximum Conducted Output Power (For reference only)

☒ **Power meter**

1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup

3.3.4 Test Result of Maximum Output Power

Modulation Mode	N_{TX}	Freq. (MHz)	Peak conducted output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	2	2412	19.91	20.33	---	---	205.844	23.14	30
11b	2	2437	19.94	20.12	---	---	201.430	23.04	30
11b	2	2462	19.83	19.85	---	---	192.766	22.85	30
11g	2	2412	17.82	17.31	---	---	114.361	20.58	30
11g	2	2437	22.11	21.21	---	---	294.684	24.69	30
11g	2	2462	18.17	17.11	---	---	117.019	20.68	30
HT20	2	2412	15.61	16.17	---	---	77.791	18.91	30
HT20	2	2437	21.52	21.68	---	---	289.137	24.61	30
HT20	2	2462	16.79	15.82	---	---	85.947	19.34	30
HT40	2	2422	12.41	12.49	---	---	35.160	15.46	30
HT40	2	2437	17.98	16.84	---	---	111.112	20.46	30
HT40	2	2452	12.80	11.34	---	---	32.669	15.14	30

Modulation Mode	N_{TX}	Freq. (MHz)	Conducted (average) output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	2	2412	17.06	18.22	---	---	117.190	20.69	30
11b	2	2437	17.02	17.15	---	---	102.230	20.10	30
11b	2	2462	17.01	17.03	---	---	100.700	20.03	30
11g	2	2412	12.17	11.80	---	---	31.617	15.00	30
11g	2	2437	18.18	17.10	---	---	117.052	20.68	30
11g	2	2462	12.30	11.49	---	---	31.075	14.92	30
HT20	2	2412	10.54	10.16	---	---	21.699	13.36	30
HT20	2	2437	17.39	17.44	---	---	110.290	20.43	30
HT20	2	2462	11.05	10.12	---	---	23.015	13.62	30
HT40	2	2422	7.56	7.68	---	---	11.563	10.63	30
HT40	2	2437	13.35	12.32	---	---	38.688	15.88	30
HT40	2	2452	7.85	6.57	---	---	10.635	10.27	30

Note: Conducted average output power is for reference only.

3.4 Power Spectral Density

3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

☒ Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.

1. Set the RBW = 3kHz, VBW = 10kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

☐ Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.

1. Set the RBW = 100kHz, VBW = 300 kHz.
2. Detector = RMS, Sweep time = auto couple.
3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
4. Perform the measurement over a single sweep.
5. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Modulation Mode	N_{TX}	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11b	2	2412	-5.21	8
11b	2	2437	-5.52	8
11b	2	2462	-5.54	8
11g	2	2412	-13.41	8
11g	2	2437	-7.04	8
11g	2	2462	-12.83	8
HT20	2	2412	-14.37	8
HT20	2	2437	-6.21	8
HT20	2	2462	-13.29	8
HT40	2	2422	-18.59	8
HT40	2	2437	-13.73	8
HT40	2	2452	-18.57	8

Note: Test result for HT20 / HT40 is bin-by-bin summing measured value of each TX port.

Worst Plots



3.5 Unwanted Emissions into Restricted Frequency Bands

3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	84.32	22.07	40.00	-17.93	44.28	-22.21	Peak	---	---
2	159.98	24.35	43.50	-19.15	41.13	-16.78	Peak	---	---
3	263.77	23.37	46.00	-22.63	40.80	-17.43	Peak	---	---
4	335.55	27.99	46.00	-18.01	43.37	-15.38	Peak	---	---
5	455.83	22.76	46.00	-23.24	35.17	-12.41	Peak	---	---
6	960.23	31.96	54.00	-22.04	36.58	-4.62	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	28.25	40.00	-11.75	44.96	-16.71	Peak	---	---
2	84.32	24.33	40.00	-15.67	46.54	-22.21	Peak	---	---
3	119.24	23.62	43.50	-19.88	42.84	-19.22	Peak	---	---
4	215.27	20.71	43.50	-22.79	40.07	-19.36	Peak	---	---
5	772.05	26.79	46.00	-19.21	33.82	-7.03	Peak	---	---
6	960.23	30.77	54.00	-23.23	35.39	-4.62	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b

Modulation	11b	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	37.53	54.00	-16.47	44.66	-7.13	Average	---	---
2	1500.00	50.37	74.00	-23.63	57.50	-7.13	Peak	---	---
3	2390.00	51.76	54.00	-2.24	55.44	-3.68	Average	---	---
4	2390.00	56.32	74.00	-17.68	60.00	-3.68	Peak	---	---
5	4824.00	52.50	54.00	-1.50	47.51	4.99	Average	---	---
6	4824.00	54.60	74.00	-19.40	49.61	4.99	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.46	54.00	-19.54	41.59	-7.13	Average	---	---
2	1500.00	47.85	74.00	-26.15	54.98	-7.13	Peak	---	---
3	2390.00	43.64	54.00	-10.36	47.32	-3.68	Average	---	---
4	2390.00	54.00	74.00	-20.00	57.68	-3.68	Peak	---	---
5	4824.00	53.52	54.00	-0.48	48.53	4.99	Average	---	---
6	4824.00	55.19	74.00	-18.81	50.20	4.99	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2386.00	39.52	54.00	-14.48	43.22	-3.70	Average	---	---
2	2386.00	52.85	74.00	-21.15	56.55	-3.70	Peak	---	---
3	4874.00	53.18	54.00	-0.82	48.08	5.10	Average	---	---
4	4874.00	55.71	74.00	-18.29	50.61	5.10	Peak	---	---
5	7311.00	48.81	54.00	-5.19	39.48	9.33	Average	---	---
6	7311.00	55.36	74.00	-18.64	46.03	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2386.00	37.32	54.00	-16.68	41.02	-3.70	Average	---	---
2	2386.00	50.68	74.00	-23.32	54.38	-3.70	Peak	---	---
3	4874.00	53.68	54.00	-0.32	48.58	5.10	Average	---	---
4	4874.00	55.39	74.00	-18.61	50.29	5.10	Peak	---	---
5	7311.00	48.55	54.00	-5.45	39.22	9.33	Average	---	---
6	7311.00	55.12	74.00	-18.88	45.79	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	44.69	54.00	-9.31	47.99	-3.30	Average	---	---
2	2483.50	59.52	74.00	-14.48	62.82	-3.30	Peak	---	---
3	4924.00	52.73	54.00	-1.27	47.53	5.20	Average	---	---
4	4924.00	55.41	74.00	-18.59	50.21	5.20	Peak	---	---
5	7386.00	43.74	54.00	-10.26	34.35	9.39	Average	---	---
6	7386.00	53.95	74.00	-20.05	44.56	9.39	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.96	54.00	-14.04	43.26	-3.30	Average	---	---
2	2483.50	54.33	74.00	-19.67	57.63	-3.30	Peak	---	---
3	4924.00	53.80	54.00	-0.20	48.60	5.20	Average	---	---
4	4924.00	55.76	74.00	-18.24	50.56	5.20	Peak	---	---
5	7386.00	46.46	54.00	-7.54	37.07	9.39	Average	---	---
6	7386.00	54.22	74.00	-19.78	44.83	9.39	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	29.36	54.00	-24.64	36.49	-7.13	Average	---	---
2	1500.00	42.58	74.00	-31.42	49.71	-7.13	Peak	---	---
3	2390.00	53.54	54.00	-0.46	57.22	-3.68	Average	---	---
4	2390.00	71.22	74.00	-2.78	74.90	-3.68	Peak	---	---
5	4824.00	41.23	54.00	-12.77	36.24	4.99	Average	---	---
6	4824.00	54.69	74.00	-19.31	49.70	4.99	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	28.46	54.00	-25.54	35.59	-7.13	Average	---	---
2	1500.00	41.35	74.00	-32.65	48.48	-7.13	Peak	---	---
3	2390.00	50.42	54.00	-3.58	54.10	-3.68	Average	---	---
4	2390.00	68.08	74.00	-5.92	71.76	-3.68	Peak	---	---
5	4824.00	41.69	54.00	-12.31	36.70	4.99	Average	---	---
6	4824.00	54.93	74.00	-19.07	49.94	4.99	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	46.64	54.00	-7.36	50.32	-3.68	Average	---	---
2	2390.00	63.18	74.00	-10.82	66.86	-3.68	Peak	---	---
3	2483.50	46.25	54.00	-7.75	49.55	-3.30	Average	---	---
4	2483.50	62.55	74.00	-11.45	65.85	-3.30	Peak	---	---
5	4874.00	42.59	54.00	-11.41	37.49	5.10	Average	---	---
6	4874.00	56.16	74.00	-17.84	51.06	5.10	Peak	---	---
7	7311.00	43.57	54.00	-10.43	34.24	9.33	Average	---	---
8	7311.00	59.25	74.00	-14.75	49.92	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.18	54.00	-11.82	45.86	-3.68	Average	---	---
2	2390.00	58.60	74.00	-15.40	62.28	-3.68	Peak	---	---
3	2483.50	41.52	54.00	-12.48	44.82	-3.30	Average	---	---
4	2483.50	57.98	74.00	-16.02	61.28	-3.30	Peak	---	---
5	4874.00	43.75	54.00	-10.25	38.65	5.10	Average	---	---
6	4874.00	58.53	74.00	-15.47	53.43	5.10	Peak	---	---
7	7311.00	46.90	54.00	-7.10	37.57	9.33	Average	---	---
8	7311.00	63.07	74.00	-10.93	53.74	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	53.78	54.00	-0.22	57.08	-3.30	Average	---	---
2	2483.50	71.74	74.00	-2.26	75.04	-3.30	Peak	---	---
3	4924.00	42.86	54.00	-11.14	37.66	5.20	Average	---	---
4	4924.00	56.51	74.00	-17.49	51.31	5.20	Peak	---	---
5	7386.00	43.95	54.00	-10.05	34.56	9.39	Average	---	---
6	7386.00	59.66	74.00	-14.34	50.27	9.39	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	50.96	54.00	-3.04	54.26	-3.30	Average	---	---
2	2483.50	68.04	74.00	-5.96	71.34	-3.30	Peak	---	---
3	4924.00	43.14	54.00	-10.86	37.94	5.20	Average	---	---
4	4924.00	58.01	74.00	-15.99	52.81	5.20	Peak	---	---
5	7386.00	45.98	54.00	-8.02	36.59	9.39	Average	---	---
6	7386.00	62.86	74.00	-11.14	53.47	9.39	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	29.56	54.00	-24.44	36.69	-7.13	Average	---	---
2	1500.00	42.34	74.00	-31.66	49.47	-7.13	Peak	---	---
3	2390.00	53.80	54.00	-0.20	57.48	-3.68	Average	---	---
4	2390.00	71.73	74.00	-2.27	75.41	-3.68	Peak	---	---
5	4824.00	42.68	54.00	-11.32	37.69	4.99	Average	---	---
6	4824.00	56.35	74.00	-17.65	51.36	4.99	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	28.36	54.00	-25.64	35.49	-7.13	Average	---	---
2	1500.00	41.19	74.00	-32.81	48.32	-7.13	Peak	---	---
3	2390.00	50.69	54.00	-3.31	54.37	-3.68	Average	---	---
4	2390.00	68.62	74.00	-5.38	72.30	-3.68	Peak	---	---
5	4824.00	45.52	54.00	-8.48	40.53	4.99	Average	---	---
6	4824.00	62.13	74.00	-11.87	57.14	4.99	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	47.21	54.00	-6.79	50.89	-3.68	Average	---	---
2	2390.00	65.21	74.00	-8.79	68.89	-3.68	Peak	---	---
3	2483.50	47.85	54.00	-6.15	51.15	-3.30	Average	---	---
4	2483.50	63.66	74.00	-10.34	66.96	-3.30	Peak	---	---
5	4874.00	41.65	54.00	-12.35	36.55	5.10	Average	---	---
6	4874.00	56.53	74.00	-17.47	51.43	5.10	Peak	---	---
7	7311.00	43.06	54.00	-10.94	33.73	9.33	Average	---	---
8	7311.00	60.12	74.00	-13.88	50.79	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.42	54.00	-11.58	46.10	-3.68	Average	---	---
2	2390.00	59.93	74.00	-14.07	63.61	-3.68	Peak	---	---
3	2483.50	42.08	54.00	-11.92	45.38	-3.30	Average	---	---
4	2483.50	57.55	74.00	-16.45	60.85	-3.30	Peak	---	---
5	4874.00	43.46	54.00	-10.54	38.36	5.10	Average	---	---
6	4874.00	58.64	74.00	-15.36	53.54	5.10	Peak	---	---
7	7311.00	46.65	54.00	-7.35	37.32	9.33	Average	---	---
8	7311.00	63.46	74.00	-10.54	54.13	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	53.52	54.00	-0.48	56.82	-3.30	Average	---	---
2	2483.50	71.26	74.00	-2.74	74.56	-3.30	Peak	---	---
3	4924.00	43.25	54.00	-10.75	38.05	5.20	Average	---	---
4	4924.00	57.14	74.00	-16.86	51.94	5.20	Peak	---	---
5	7386.00	44.62	54.00	-9.38	35.23	9.39	Average	---	---
6	7386.00	60.20	74.00	-13.80	50.81	9.39	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	51.23	54.00	-2.77	54.53	-3.30	Average	---	---
2	2483.50	69.04	74.00	-4.96	72.34	-3.30	Peak	---	---
3	4924.00	43.95	54.00	-10.05	38.75	5.20	Average	---	---
4	4924.00	57.86	74.00	-16.14	52.66	5.20	Peak	---	---
5	7386.00	45.21	54.00	-8.79	35.82	9.39	Average	---	---
6	7386.00	60.58	74.00	-13.42	51.19	9.39	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40

Modulation	HT40	**Test Freq. (MHz)**	2422
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	30.25	54.00	-23.75	37.38	-7.13	Average	---	---
2	1500.00	43.28	74.00	-30.72	50.41	-7.13	Peak	---	---
3	2390.00	53.76	54.00	-0.24	57.44	-3.68	Average	---	---
4	2390.00	65.70	74.00	-8.30	69.38	-3.68	Peak	---	---
5	4844.00	41.65	54.00	-12.35	36.62	5.03	Average	---	---
6	4844.00	55.34	74.00	-18.66	50.31	5.03	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	29.36	54.00	-24.64	36.49	-7.13	Average	---	---
2	1500.00	42.18	74.00	-31.82	49.31	-7.13	Peak	---	---
3	2390.00	51.64	54.00	-2.36	55.32	-3.68	Average	---	---
4	2390.00	62.95	74.00	-11.05	66.63	-3.68	Peak	---	---
5	4844.00	42.35	54.00	-11.65	37.32	5.03	Average	---	---
6	4844.00	56.04	74.00	-17.96	51.01	5.03	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	53.61	54.00	-0.39	57.29	-3.68	Average	---	---
2	2390.00	66.05	74.00	-7.95	69.73	-3.68	Peak	---	---
3	2483.50	53.84	54.00	-0.16	57.14	-3.30	Average	---	---
4	2483.50	67.43	74.00	-6.57	70.73	-3.30	Peak	---	---
5	4874.00	36.94	54.00	-17.06	31.84	5.10	Average	---	---
6	4874.00	48.55	74.00	-25.45	43.45	5.10	Peak	---	---
7	7311.00	37.73	54.00	-16.27	28.40	9.33	Average	---	---
8	7311.00	50.78	74.00	-23.22	41.45	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	50.56	54.00	-3.44	54.24	-3.68	Average	---	---
2	2390.00	62.48	74.00	-11.52	66.16	-3.68	Peak	---	---
3	2483.50	49.40	54.00	-4.60	52.70	-3.30	Average	---	---
4	2483.50	62.78	74.00	-11.22	66.08	-3.30	Peak	---	---
5	4874.00	36.64	54.00	-17.36	31.54	5.10	Average	---	---
6	4874.00	49.34	74.00	-24.66	44.24	5.10	Peak	---	---
7	7311.00	39.30	54.00	-14.70	29.97	9.33	Average	---	---
8	7311.00	51.85	74.00	-22.15	42.52	9.33	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2452
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	53.62	54.00	-0.38	56.92	-3.30	Average	---	---
2	2483.50	65.03	74.00	-8.97	68.33	-3.30	Peak	---	---
3	4904.00	42.43	54.00	-11.57	37.27	5.16	Average	---	---
4	4904.00	58.11	74.00	-15.89	52.95	5.16	Peak	---	---
5	7356.00	42.46	54.00	-11.54	33.10	9.36	Average	---	---
6	7356.00	58.19	74.00	-15.81	48.83	9.36	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2452
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	50.95	54.00	-3.05	54.25	-3.30	Average	---	---
2	2483.50	62.36	74.00	-11.64	65.66	-3.30	Peak	---	---
3	4904.00	42.89	54.00	-11.11	37.73	5.16	Average	---	---
4	4904.00	58.69	74.00	-15.31	53.53	5.16	Peak	---	---
5	7356.00	42.13	54.00	-11.87	32.77	9.36	Average	---	---
6	7356.00	57.86	74.00	-16.14	48.50	9.36	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6 Emissions in Non-Restricted Frequency Bands

3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.4 Test Setup

Transmitter Radiated Bandedge Emissions



3.6.5 Test Result of Emissions in non-restricted frequency bands

This test item is performed on each TX output individually without summing or adding 10 log(N_{ANT}) since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

3.6.6 Unwanted Emissions into Non-Restricted Frequency Bands

802.11b

Reference Level	Tx 2412MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2437MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2462MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

802.11g

Reference Level	Tx 2412MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2437MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2462MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

802.11n HT20

Reference Level	Tx 2412MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2437MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2462MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

802.11n HT40

Reference Level	Tx 2422MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2437MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

Reference Level	Tx 2452MHz / 30MHz~25GHz (down 20dBc)
	
---	
---	

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

═END═