

RF EXPOSURE REPORT

REPORT NO.: SA140606E08

MODEL NO.: WND930

FCC ID: PY314200281

RECEIVED: June 06, 2014

TESTED: Aug. 07, 2014

ISSUED: Aug. 20, 2014

APPLICANT: Netgear Incorporated

ADDRESS: 350 East Plumeria Drive San Jose, CA
95134

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION.....	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	7



RELEASE CONTROL RECORD


ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA140606E08	Original release	Aug. 20, 2014

1. CERTIFICATION

PRODUCT: Outdoor High Power Wireless N Access Point
BRAND NAME: NETGEAR
MODEL NO.: WND930
TEST SAMPLE: ENGINEERING SAMPLE
APPLICANT: Netgear Incorporated
TESTED DATE: Aug. 07, 2014
STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D03
IEEE C95.1

The above equipment (Model: WND930) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , **DATE:** Aug. 20, 2014
(Lori Chung, Specialist)

APPROVED BY : , **DATE:** Aug. 20, 2014
(May Chen, Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 26cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Internal Antenna				
Transmitter Circuit	Antenna Gain(dBi) Including cable loss	Frequency range	Antenna Type	Connector Type
Chain (0)	5	2.4~2.4835GHz	Panel	i-pex(MHF)
Chain (1)	5		Panel	i-pex(MHF)
Chain (0)	5	5.150~5.850GHz	Panel	i-pex(MHF)
Chain (1)	5		Panel	i-pex(MHF)
External Antenna				
Transmitter Circuit	Antenna Gain(dBi) Including cable loss	Frequency range	Antenna Type	Connector Type
Chain (0)	5	2.4~2.4835GHz	Dipole	N type(M)
Chain (1)	5		Dipole	N type(M)
Chain (0)	7	5.150~5.850GHz	Dipole	N type(M)
Chain (1)	7		Dipole	N type(M)

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

15.247(2.4GHz):

FREQUENCY– (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	474.558	8.01	26	0.35329	1

Note: Directional gain = 5dBi + 10log(2) = 8.01dBi.

15.247(5GHz):

FREQUENCY (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
5745 ~ 5825	507.064	10.01	26	0.59828	1

Note: Directional gain = 7dBi + 10log(2) = 10.01dBi.

15.407(5GHz):

FREQUENCY (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
5180 ~ 5240	35.591	10.01	26	0.04199	1

Note: Directional gain = 7dBi + 10log(2) = 10.01dBi.

CONCLUSION:

Both of the 2.4GHz and 5GHz WLAN can transmit simultaneously, the formula of calculated the MPE is:

$$CPD_1 / LPD_1 + CPD_2 / LPD_2 + ...etc. < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.35329 / 1 + 0.59828 / 1 = 0.952$, which is less than “1”. This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---