



BUREAU
VERITAS

Test Report No.: FS141216N012

RF EXPOSURE REPORT

Applicant	NETGEAR, Inc.
Address	350 East Plumeria Drive San Jose, CA 95134


Manufacturer or Supplier	NETGEAR, Inc.
Address	350 East Plumeria Drive San Jose, CA 95134
Product	ADSL2+ Modem Router
Brand Name	NETGEAR
Model	D2200D-1FRNAS
Additional Model & Model Difference	N/A
Date of tests	Dec. 17, 2014 ~ Mar. 19, 2015

☒ FCC Part 2 (Section 2.1091)

☒ KDB 447498 D03

☒ IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Yuqiang Yin Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	 Date: Mar. 20, 2015

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FS141216N012

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS141216N012	Original release	Mar. 20, 2015



Test Report No.: FS141216N012

1. CERTIFICATION

FCC ID: PY314400297
PRODUCT: ADSL2+ Modem Router
BRAND NAME: NETGEAR
MODEL NO.: D2200D-1FRNAS
TEST SAMPLE: Engineering Sample
APPLICANT: NETGEAR, Inc.
TESTED DATE: Mar. 19, 2015
STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D03
IEEE C95.1



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Total Gain (dBi)	Antenna Type
Chain 0	1.5	4.51	PCB Antenna
Chain 1	1.5		PCB Antenna

Note: Total Gain=1.5+10log(N=2)=1.5+3.01=4.51dBi

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	402.717	4.51	20	0.226	1.00

Conclusion

Therefore device complies with FCC's RF radiation exposure limits for general population in mobile exposure category (distance > 20cm)

--- END ---