FCC RADIO TEST REPORT

FCC ID	:	**PY321100529**
Equipment	:	**Netgear 5G MHS Travel Router**
Brand Name	:	**Netgear**
Model Name	:	**MR6500**
Applicant	:	**Netgear Inc** **350 E. Plumeria Drive, San Jose, CA 95134, United States**
Manufacturer	:	**Netgear Inc** **350 E. Plumeria Drive, San Jose, CA 95134, United States**
Standard	:	**FCC 47 CFR Part 2, Part 27(D)**

The product was received on Oct. 19, 2021 and testing was performed from Oct. 29, 2021 to Jan. 04, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Site 6
1.4 Applied Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Test Mode 7
2.2 Connection Diagram of Test System 8
2.3 Support Unit used in test configuration and system 8
2.4 Measurement Results Explanation Example 8
2.5 Frequency List of Low/Middle/High Channels 9
3 Conducted Test Items **10**
3.1 Measuring Instruments 10
3.2 Conducted Output Power Measurement 11
3.3 Peak-to-Average Ratio 12
3.4 Effective Isotropic Radiated Power 13
3.5 Occupied Bandwidth 14
3.6 Conducted Band Edge 15
3.7 Conducted Spurious Emission 16
3.8 Frequency Stability 17
4 Radiated Test Items **18**
4.1 Measuring Instruments 18
4.2 Radiated Spurious Emission Measurement 20
5 List of Measuring Equipment **21**
6 Uncertainty of Evaluation **23**
Appendix A. Test Results of Conducted Test
Appendix B. Test Results of Radiated Test
Appendix C. Test Setup Photographs

History of this test report

Report No.	Version	Description	Issued Date
FG190614C	01	Initial issue of report	Jan. 24, 2022
FG190614C	02	Revise Product Feature of Equipment Under Test	Jan. 28, 2022

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
3.3	-	Peak-to-Average Ratio	Reporting only	-
3.4	§27.50 (a)(3)	Effective Isotropic Radiated Power	Pass	-
3.5	§2.1049	Occupied Bandwidth	Reporting only	-
3.6	§2.1051 §27.53 (a)(4)	Conducted Band Edge Measurement	Pass	-
3.7	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission	Pass	-
3.8	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Pass	-
4.2	§2.1053 §27.53 (a)(4)	Radiated Spurious Emission	Pass	Under limit 3.43 dB at 6924.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Avis Chuang

Report Producer: Lucy Wu

1 General Description

1.1 Product Feature of Equipment Under Test

LTE/5G NR, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, Wi-Fi 6GHz 802.11a/n/ac/ax, and GNSS

Product Feature	
Antenna Type	WWAN: **<Ant. 1>:** Monopole Antenna **<Ant. 2>:** Monopole Antenna WLAN: **<Ant. 3>:** Monopole Antenna **<Ant. 4>:** Monopole Antenna GPS: PIFA Antenna

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

Antenna Information	
Internal Antenna Gain	**<Ant. 2>:**1.05 dBi
External Connector	TS9

Remark:

1. TS9 connector is for the external antennas, while the external antennas are connected, RF outputs are switched from internal antenna 2 to the external one.
2. The maximum antenna gain allowed for the external antenna is limited by the internal antenna gain, also illustrated in the user manual.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Site

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	TH03-HY
Test Engineer	Bryant Liu
Temperature (℃)	22.8~23.2
Relative Humidity (%)	52~56

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH16-HY (TAF Code: 3786)
Test Engineer	Karl Hou and Andy Yang
Temperature (℃)	18~25
Relative Humidity (%)	50~65
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786

1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ANSI C63.26-2015
- FCC 47 CFR Part 2, Part 27(D)
- ANSI / TIA-603-E
- FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and find X plane as worst plane.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	30	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	30	-	-		v	-	-	v	v	v	v			v		v	
E.I.R.P	30	-	-	v	v	-	-	v	v	v	v	Max. Power					
26dB and 99% Bandwidth	30	-	-	v	v	-	-	v	v	v	v			v		v	
Conducted Band Edge	30	-	-	v	v	-	-	v	v	v	v	v		v	v		v
Conducted Spurious Emission	30	-	-	v	v	-	-	v				v			v	v	v
Frequency Stability	30	-	-		v	-	-	v						v		v	
Radiated Spurious Emission	30	Worst Case													v	v	v
Remark	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. All the radiated test cases were performed with Adapter 1.																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 30 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, 26dB Bandwidth ,Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power Measurement

3.2.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Effective Isotropic Radiated Power

3.4.1 Description of EIRP Power

For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

Remark: EIRP use worst case measure the total power to cover per 5MHz Power.
According to KDB 412172 D01 Power Approach,
EIRP = $P_T + G_T – L_C$, where
P_T = transmitter output power in dBm
G_T = gain of the transmitting antenna in dBi
L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.4.5

1. Determine the EIRP by adding the effective antenna gain to the adjusted power level.

3.5 Occupied Bandwidth

3.5.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.5.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.6 Conducted Band Edge

3.6.1 Description of Conducted Band Edge Measurement

27.53 (a)(4)

For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337 MHz.

(ii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2296 and 2300 MHz, 61 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz.

(iii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.
   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.7 Conducted Spurious Emission

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

   The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [70 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)

   = -40dBm.

3.8 Frequency Stability

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.8.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.1.1 Test Setup

For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.1.2 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

4.2 Radiated Spurious Emission Measurement

4.2.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
   EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
   ERP (dBm) = EIRP - 2.15
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
   The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [70 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
   = -40dBm.

5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 07, 2021	Oct. 29, 2021~ Dec. 03, 2021	Sep. 06, 2022	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00991	18GHz-40GHz	May 12, 2021	Oct. 29, 2021~ Dec. 03, 2021	May 11, 2022	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170576	18GHz-40GHz	May 21, 2021	Oct. 29, 2021~ Dec. 03, 2021	May 20, 2022	Radiation (03CH16-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 15, 2021	Oct. 29, 2021~ Dec. 03, 2021	Oct. 14, 2022	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 22, 2021	Oct. 29, 2021~ Dec. 03, 2021	Jun. 21, 2022	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804012/2	18-40G	Jan. 04, 2021	Oct. 29, 2021~ Dec. 03, 2021	Jan. 03, 2022	Radiation (03CH16-HY)
Signal Generator	Agilent	MG3694C	163401	0.1Hz~40GHz	Jan. 31, 2021	Oct. 29, 2021~ Dec. 03, 2021	Jan. 30, 2022	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	41912 & 05	30MHz to 1GHz	Feb. 08, 2021	Oct. 29, 2021~ Dec. 03, 2021	Feb. 07, 2022	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N-06	47020 & 06	30MHz to 1GHz	Oct. 09, 2021	Oct. 29, 2021~ Dec. 03, 2021	Oct. 08, 2022	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Oct. 12, 2021	Oct. 29, 2021~ Dec. 03, 2021	Oct. 11, 2022	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1212	1G~18GHz	May 18, 2021	Oct. 29, 2021~ Dec. 03, 2021	May 18, 2022	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Jul. 05, 2021	Oct. 29, 2021~ Dec. 03, 2021	Jul. 04, 2022	Radiation (03CH16-HY)
Amplifier	Jet-Power	JPA0118-55-303	1710001800054001	1-18GHz	Jun. 16, 2021	Oct. 29, 2021~ Dec. 03, 2021	Jun. 15, 2022	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz~26.5GHz	Dec. 10, 2020	Oct. 29, 2021~ Dec. 03, 2021	Dec. 09, 2021	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A	MY57290111	3Hz~26.5GHz	Dec. 11, 2020	Oct. 29, 2021~ Dec. 03, 2021	Dec. 10, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/4PE	NA	Aug. 28, 2021	Oct. 29, 2021~ Dec. 03, 2021	Aug. 27, 2022	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/4PE	NA	Aug. 28, 2021	Oct. 29, 2021~ Dec. 03, 2021	Aug. 27, 2022	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300-5757	NA	Aug. 28, 2021	Oct. 29, 2021~ Dec. 03, 2021	Aug. 27, 2022	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Oct. 29, 2021~ Dec. 03, 2021	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Oct. 29, 2021~ Dec. 03, 2021	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Oct. 29, 2021~ Dec. 03, 2021	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Oct. 29, 2021~ Dec. 03, 2021	N/A	Radiation (03CH16-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Radio Communication Analyzer	Anritsu	MT8821C	6201664755	2/3/4G/LTE FDD/TDD with44)/LTE-3CC DLCA/2CC ULCA, CatM1/NB1/NB2	Jul. 21, 2021	Nov. 03, 2021~ Jan. 04, 2022	Jul. 20, 2022	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101909	10Hz~40GHz	Aug. 13, 2021	Nov. 03, 2021~ Jan. 04, 2022	Aug. 12, 2022	Conducted (TH03-HY)
Thermal Chamber	ESPEC	SH-641	92013720	-40℃ ~90℃	Sep. 09, 2021	Nov. 03, 2021~ Jan. 04, 2022	Sep. 08, 2022	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~5A	Oct. 06, 2021	Nov. 03, 2021~ Jan. 04, 2022	Oct. 05, 2022	Conducted (TH03-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#B	1-18GHz	Jan. 09, 2021	Nov. 03, 2021~ Jan. 04, 2022	Jan. 08, 2022	Conducted (TH03-HY)

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.86 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.68 dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.00 dB

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power & EIRP)

LTE Band 30 Maximum Average Power [dBm] (GT - LC = 1.05 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
10	1	0	QPSK	-	**21.97**	-	**23.02**	**0.2004**
10	1	25			21.94			
10	1	49			21.90			
10	25	0			20.80			
10	25	12			20.81			
10	25	25			20.87			
10	50	0			20.84			
10	1	0	16-QAM		21.07		22.29	0.1694
10	1	25			21.24			
10	1	49			21.06			
10	25	0			19.87			
10	25	12			19.81			
10	25	25			19.91			
10	50	0			19.83			
10	1	0	64-QAM		20.93		21.98	0.1578
10	1	25			20.13			
10	1	49			20.07			
10	25	0			18.81			
10	25	12			18.84			
10	25	25			18.92			
10	50	0			18.86			
10	1	0	256-QAM		16.67		18.13	0.0650
10	1	25			17.08			
10	1	49			16.87			
10	25	0			16.81			
10	25	12			16.88			
10	25	25			16.92			
10	50	0			16.82			
Limit	EIRP < 250mW/5MHz			Result			Pass	

LTE Band 30 Maximum Average Power [dBm] (GT - LC = 1.05 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
5	1	0	QPSK	21.93	21.89	21.89	22.99	0.1991
5	1	12		21.85	21.94	21.88		
5	1	24		21.87	21.88	21.84		
5	12	0		20.95	20.85	20.88		
5	12	7		20.93	20.86	20.88		
5	12	13		20.94	20.99	20.95		
5	25	0		20.98	20.90	20.94		
5	1	0	16-QAM	21.12	21.13	21.19	22.39	0.1734
5	1	12		21.31	21.34	21.29		
5	1	24		21.14	21.13	21.21		
5	12	0		19.93	19.99	19.92		
5	12	7		19.92	19.94	19.86		
5	12	13		20.01	19.96	20.03		
5	25	0		19.97	19.93	19.96		
5	1	0	64-QAM	20.94	20.94	20.97	22.02	0.1592
5	1	12		20.18	20.27	20.28		
5	1	24		20.12	20.16	20.12		
5	12	0		18.90	18.94	18.87		
5	12	7		18.90	18.92	18.95		
5	12	13		19.04	19.05	18.99		
5	25	0		19.00	19.00	18.97		
5	1	0	256-QAM	16.78	16.73	16.76	18.26	0.0670
5	1	12		17.13	17.21	17.16		
5	1	24		17.00	17.01	16.99		
5	12	0		16.86	16.87	16.86		
5	12	7		17.03	17.00	17.00		
5	12	13		17.05	17.06	17.06		
5	25	0		16.87	16.96	16.90		
Limit	EIRP < 250mW/5MHz			Result			Pass	

LTE Band 30

Peak-to-Average Ratio

Mode	LTE Band 30 / 10MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	5.01	6.00	6.43	6.75	PASS

LTE Band 30 / 10MHz / QPSK

Middle Channel / Full RB



LTE Band 30 / 10MHz / 16QAM

Middle Channel / Full RB



LTE Band 30 / 10MHz / 64QAM

Middle Channel / Full RB



LTE Band 30 / 10MHz / 256QAM

Middle Channel / Full RB



26dB Bandwidth

Mode	LTE Band 30 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	-	-	-	-	4.97	4.91	9.79	9.61	-	-	-	-
Mode	LTE Band 30 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM
Middle CH	-	-	-	-	4.97	5.12	9.89	9.77	-	-	-	-

LTE Band 30

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



LTE Band 30	
Middle Channel / 5MHz / 256QAM	**Middle Channel / 10MHz / 256QAM**
	

Occupied Bandwidth

Mode	LTE Band 30 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	-	-	-	-	4.49	4.51	9.07	9.03	-	-	-	-
Mode	LTE Band 30 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM	64QAM	256 QAM
Middle CH	-	-	-	-	4.49	4.50	9.03	9.09	-	-	-	-

LTE Band 30

Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



LTE Band 30	
Middle Channel / 5MHz / 256QAM	**Middle Channel / 10MHz / 256QAM**
	

Conducted Band Edge

LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29439 GHz	-39.94 dBm	-8.94 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29690 GHz	-35.95 dBm	-10.95 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30300 GHz	-27.85 dBm	-14.85 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-22.01 dBm	-9.01 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30535 GHz	20.12 dBm	-9.88 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31069 GHz	-53.33 dBm	-40.33 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31183 GHz	-35.64 dBm	-22.64 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32035 GHz	-41.10 dBm	-16.10 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32499 GHz	-43.83 dBm	-12.83 dB

Date: 29.NOV.2021 08:42:35

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29569 GHz	-41.26 dBm	-10.26 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29895 GHz	-40.38 dBm	-15.38 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30895 GHz	-38.80 dBm	-25.80 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30945 GHz	-52.46 dBm	-39.46 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31471 GHz	20.66 dBm	-9.34 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31501 GHz	-23.05 dBm	-10.05 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31691 GHz	-27.91 dBm	-14.91 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32156 GHz	-36.82 dBm	-11.82 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32665 GHz	-42.88 dBm	-11.88 dB

Date: 29.NOV.2021 09:22:34

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29534 GHz	-42.36 dBm	-11.36 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29990 GHz	-32.07 dBm	-7.07 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30357 GHz	-24.39 dBm	-11.39 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30495 GHz	-27.61 dBm	-14.61 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30855 GHz	6.43 dBm	-23.57 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31000 GHz	-26.16 dBm	-13.16 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31108 GHz	-24.87 dBm	-11.87 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32093 GHz	-41.73 dBm	-16.73 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32502 GHz	-43.80 dBm	-12.80 dB

Date: 29.NOV.2021 08:46:45

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29397 GHz	-44.01 dBm	-13.01 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29988 GHz	-41.53 dBm	-16.53 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30876 GHz	-23.75 dBm	-10.75 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.31000 GHz	-27.19 dBm	-14.19 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31043 GHz	6.73 dBm	-23.27 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-27.83 dBm	-14.83 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31621 GHz	-24.98 dBm	-11.98 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32001 GHz	-34.11 dBm	-9.11 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32410 GHz	-41.21 dBm	-10.21 dB

Date: 29.NOV.2021 09:25:41

LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29581 GHz	-41.95 dBm	-10.95 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29811 GHz	-35.83 dBm	-10.83 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30101 GHz	-29.68 dBm	-16.68 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-23.28 dBm	-10.28 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30534 GHz	20.02 dBm	-9.98 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31002 GHz	-52.69 dBm	-39.69 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31388 GHz	-41.39 dBm	-28.39 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32197 GHz	-43.06 dBm	-18.06 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32713 GHz	-44.13 dBm	-13.13 dB

Date: 29.NOV.2021 08:44:27

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29521 GHz	-41.49 dBm	-10.49 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29714 GHz	-41.24 dBm	-16.24 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30562 GHz	-39.90 dBm	-26.90 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30952 GHz	-52.16 dBm	-39.16 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31466 GHz	19.85 dBm	-10.15 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31501 GHz	-23.48 dBm	-10.48 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31794 GHz	-33.54 dBm	-20.54 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32158 GHz	-35.41 dBm	-10.41 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32534 GHz	-42.50 dBm	-11.50 dB

Date: 29.NOV.2021 09:23:20

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29592 GHz	-43.38 dBm	-12.38 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29975 GHz	-32.13 dBm	-7.13 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30358 GHz	-24.00 dBm	-11.00 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30497 GHz	-28.02 dBm	-15.02 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30946 GHz	5.54 dBm	-24.46 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31003 GHz	-27.24 dBm	-14.24 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31181 GHz	-25.58 dBm	-12.58 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32011 GHz	-43.36 dBm	-18.36 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32440 GHz	-44.04 dBm	-13.04 dB

Date: 29.NOV.2021 08:47:30

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29497 GHz	-44.00 dBm	-13.00 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29989 GHz	-42.32 dBm	-17.32 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30880 GHz	-23.75 dBm	-10.75 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.31000 GHz	-25.65 dBm	-12.65 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31061 GHz	5.94 dBm	-24.06 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31507 GHz	-29.17 dBm	-16.17 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31617 GHz	-25.42 dBm	-12.42 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32001 GHz	-33.62 dBm	-8.62 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32405 GHz	-42.84 dBm	-11.84 dB

Date: 29.NOV.2021 09:26:27

LTE Band 30 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29423 GHz	-40.28 dBm	-9.28 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29934 GHz	-34.46 dBm	-9.46 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30385 GHz	-29.30 dBm	-16.30 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30498 GHz	-26.91 dBm	-13.91 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30533 GHz	19.08 dBm	-10.92 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31036 GHz	-55.56 dBm	-42.56 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31502 GHz	-41.21 dBm	-28.21 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32311 GHz	-43.31 dBm	-18.31 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32517 GHz	-42.79 dBm	-11.79 dB

Date: 29.NOV.2021 08:45:13

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29571 GHz	-42.56 dBm	-11.56 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29610 GHz	-41.25 dBm	-16.25 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30844 GHz	-33.68 dBm	-20.68 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30940 GHz	-55.18 dBm	-42.18 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31468 GHz	18.98 dBm	-11.02 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-24.34 dBm	-11.34 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31699 GHz	-32.76 dBm	-19.76 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32033 GHz	-31.65 dBm	-6.65 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32649 GHz	-44.22 dBm	-13.22 dB

Date: 29.NOV.2021 09:24:06

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29550 GHz	-43.86 dBm	-12.86 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29966 GHz	-35.01 dBm	-10.01 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30341 GHz	-25.75 dBm	-12.75 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30497 GHz	-29.65 dBm	-16.65 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30829 GHz	4.21 dBm	-25.79 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31002 GHz	-28.95 dBm	-15.95 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31100 GHz	-27.70 dBm	-14.70 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32011 GHz	-43.75 dBm	-18.75 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32514 GHz	-44.27 dBm	-13.27 dB

Date: 29.NOV.2021 08:48:17

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29245 GHz	-44.18 dBm	-13.18 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29856 GHz	-43.76 dBm	-18.76 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30898 GHz	-25.49 dBm	-12.49 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.31000 GHz	-28.44 dBm	-15.44 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31048 GHz	4.97 dBm	-25.03 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31502 GHz	-29.65 dBm	-16.65 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31603 GHz	-28.12 dBm	-15.12 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32006 GHz	-37.08 dBm	-12.08 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32409 GHz	-43.66 dBm	-12.66 dB

Date: 29.NOV.2021 09:27:12

LTE Band 30 / 5MHz / 256QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29338 GHz	-44.49 dBm	-13.49 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29878 GHz	-44.15 dBm	-19.15 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30388 GHz	-40.57 dBm	-27.57 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30499 GHz	-28.76 dBm	-15.76 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30533 GHz	15.32 dBm	-14.68 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31024 GHz	-56.94 dBm	-43.94 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31171 GHz	-44.88 dBm	-31.88 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32113 GHz	-44.25 dBm	-19.25 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32413 GHz	-44.33 dBm	-13.33 dB

Date: 29.NOV.2021 08:45:59

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29557 GHz	-44.20 dBm	-13.20 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29964 GHz	-44.09 dBm	-19.09 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30784 GHz	-44.79 dBm	-31.79 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30963 GHz	-56.69 dBm	-43.69 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31463 GHz	15.57 dBm	-14.43 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31501 GHz	-29.46 dBm	-16.46 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31603 GHz	-39.66 dBm	-26.66 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32004 GHz	-43.77 dBm	-18.77 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32562 GHz	-44.09 dBm	-13.09 dB

Date: 29.NOV.2021 09:24:52

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29283 GHz	-43.95 dBm	-12.95 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29974 GHz	-39.34 dBm	-14.34 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30400 GHz	-27.57 dBm	-14.57 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-31.16 dBm	-18.16 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30960 GHz	2.39 dBm	-27.61 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31005 GHz	-31.64 dBm	-18.64 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31102 GHz	-29.31 dBm	-16.31 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32106 GHz	-44.03 dBm	-19.03 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32672 GHz	-44.21 dBm	-13.21 dB

Date: 29.NOV.2021 08:49:03

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29595 GHz	-44.22 dBm	-13.22 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29948 GHz	-44.14 dBm	-19.14 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30899 GHz	-26.15 dBm	-13.15 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30997 GHz	-30.25 dBm	-17.25 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31071 GHz	2.62 dBm	-27.38 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31501 GHz	-31.06 dBm	-18.06 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31601 GHz	-29.83 dBm	-16.83 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32027 GHz	-42.43 dBm	-17.43 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32487 GHz	-44.18 dBm	-13.18 dB

Date: 29.NOV.2021 09:27:58

LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29426 GHz	-40.10 dBm	-9.10 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29886 GHz	-33.93 dBm	-8.93 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30395 GHz	-24.97 dBm	-11.97 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-26.54 dBm	-13.54 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30558 GHz	20.65 dBm	-9.35 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31588 GHz	-50.46 dBm	-37.46 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31638 GHz	-39.61 dBm	-26.61 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32358 GHz	-41.15 dBm	-16.15 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32545 GHz	-42.49 dBm	-11.49 dB

Date: 29.NOV.2021 09:32:52

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29540 GHz	-42.15 dBm	-11.15 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29738 GHz	-40.26 dBm	-15.26 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30379 GHz	-41.47 dBm	-28.47 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30450 GHz	-52.01 dBm	-39.01 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31440 GHz	19.97 dBm	-10.03 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31500 GHz	-30.39 dBm	-17.39 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31697 GHz	-32.50 dBm	-19.50 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32089 GHz	-35.92 dBm	-10.92 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32517 GHz	-43.81 dBm	-12.81 dB

Date: 29.NOV.2021 09:35:54

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29598 GHz	-31.79 dBm	-0.79 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29797 GHz	-27.15 dBm	-2.15 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30365 GHz	-25.75 dBm	-12.75 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30496 GHz	-29.72 dBm	-16.72 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31249 GHz	3.91 dBm	-26.09 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31501 GHz	-30.36 dBm	-17.36 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31617 GHz	-27.61 dBm	-14.61 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32194 GHz	-31.22 dBm	-6.22 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32417 GHz	-35.19 dBm	-4.19 dB

Date: 29.NOV.2021 16:20:42

LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29561 GHz	-39.09 dBm	-8.09 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29862 GHz	-35.70 dBm	-10.70 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30321 GHz	-31.48 dBm	-18.48 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-25.71 dBm	-12.71 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30558 GHz	19.78 dBm	-10.22 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31520 GHz	-50.15 dBm	-37.15 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31819 GHz	-39.52 dBm	-26.52 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32262 GHz	-41.14 dBm	-16.14 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32633 GHz	-43.49 dBm	-12.49 dB

Date: 29.NOV.2021 09:33:37

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29365 GHz	-43.71 dBm	-12.71 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29660 GHz	-43.80 dBm	-18.80 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30323 GHz	-41.23 dBm	-28.23 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30426 GHz	-52.02 dBm	-39.02 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31441 GHz	18.98 dBm	-11.02 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31500 GHz	-29.67 dBm	-16.67 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31705 GHz	-34.16 dBm	-21.16 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32212 GHz	-42.59 dBm	-17.59 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32489 GHz	-41.95 dBm	-10.95 dB

Date: 29.NOV.2021 09:36:40

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29597 GHz	-33.98 dBm	-2.98 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29996 GHz	-29.25 dBm	-4.25 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30399 GHz	-25.31 dBm	-12.31 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30497 GHz	-30.16 dBm	-17.16 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30752 GHz	2.40 dBm	-27.60 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31501 GHz	-30.93 dBm	-17.93 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31600 GHz	-26.88 dBm	-13.88 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32023 GHz	-32.93 dBm	-7.93 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32406 GHz	-37.34 dBm	-6.34 dB

Date: 29.NOV.2021 09:39:41

LTE Band 30 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29217 GHz	-44.07 dBm	-13.07 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29742 GHz	-37.59 dBm	-12.59 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30395 GHz	-30.90 dBm	-17.90 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30496 GHz	-32.26 dBm	-19.26 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30558 GHz	19.20 dBm	-10.80 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31562 GHz	-50.25 dBm	-37.25 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31716 GHz	-42.25 dBm	-29.25 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32128 GHz	-41.07 dBm	-16.07 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32421 GHz	-44.24 dBm	-13.24 dB

Date: 29.NOV.2021 09:34:24

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29279 GHz	-43.66 dBm	-12.66 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29925 GHz	-43.91 dBm	-18.91 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30364 GHz	-42.38 dBm	-29.38 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30464 GHz	-50.39 dBm	-37.39 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31441 GHz	18.78 dBm	-11.22 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31501 GHz	-30.41 dBm	-17.41 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31632 GHz	-31.25 dBm	-18.25 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32302 GHz	-39.41 dBm	-14.41 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32477 GHz	-41.28 dBm	-10.28 dB

Date: 29.NOV.2021 09:37:25

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29529 GHz	-36.57 dBm	-5.57 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29978 GHz	-30.79 dBm	-5.79 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30268 GHz	-27.27 dBm	-14.27 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-32.30 dBm	-19.30 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30913 GHz	1.69 dBm	-28.31 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31500 GHz	-32.82 dBm	-19.82 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31604 GHz	-31.55 dBm	-18.55 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32034 GHz	-35.64 dBm	-10.64 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32420 GHz	-39.97 dBm	-8.97 dB

Date: 29.NOV.2021 09:40:27

LTE Band 30 / 10MHz / 256QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29494 GHz	-44.28 dBm	-13.28 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29981 GHz	-44.22 dBm	-19.22 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30393 GHz	-41.57 dBm	-28.57 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30500 GHz	-34.63 dBm	-21.63 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30560 GHz	15.22 dBm	-14.78 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31524 GHz	-53.88 dBm	-40.88 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31714 GHz	-44.89 dBm	-31.89 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32003 GHz	-44.06 dBm	-19.06 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32511 GHz	-44.03 dBm	-13.03 dB

Date: 29.NOV.2021 09:35:09

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29594 GHz	-44.07 dBm	-13.07 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29714 GHz	-44.17 dBm	-19.17 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30383 GHz	-44.88 dBm	-31.88 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30403 GHz	-53.72 dBm	-40.72 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31442 GHz	15.16 dBm	-14.84 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31500 GHz	-36.09 dBm	-23.09 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31601 GHz	-41.08 dBm	-28.08 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32015 GHz	-44.08 dBm	-19.08 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32689 GHz	-44.23 dBm	-13.23 dB

Date: 29.NOV.2021 09:38:10

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29575 GHz	-39.89 dBm	-8.89 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29965 GHz	-32.49 dBm	-7.49 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30397 GHz	-28.90 dBm	-15.90 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30497 GHz	-34.72 dBm	-21.72 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31303 GHz	-0.73 dBm	-30.73 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31501 GHz	-34.78 dBm	-21.78 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31606 GHz	-33.10 dBm	-20.10 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32005 GHz	-38.69 dBm	-13.69 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32408 GHz	-42.47 dBm	-11.47 dB

Date: 29.NOV.2021 09:41:13

Conducted Spurious Emission

LTE Band 30 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	855.29985 MHz	-54.93 dBm	-14.93 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.28576 GHz	-54.28 dBm	-14.28 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.41313 GHz	-52.55 dBm	-12.55 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.92711 GHz	-49.54 dBm	-9.54 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.35419 GHz	-50.47 dBm	-10.47 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.27984 GHz	-49.50 dBm	-9.50 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.52906 GHz	-46.26 dBm	-6.26 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.71011 GHz	-46.89 dBm	-6.89 dB

Date: 29.NOV.2021 08:43:40

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	914.44028 MHz	-54.82 dBm	-14.82 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.18717 GHz	-54.54 dBm	-14.54 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.41420 GHz	-53.05 dBm	-13.05 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.93821 GHz	-49.31 dBm	-9.31 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.34669 GHz	-50.49 dBm	-10.49 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.94526 GHz	-49.45 dBm	-9.45 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.51606 GHz	-46.09 dBm	-6.09 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.70211 GHz	-46.88 dBm	-6.88 dB

Date: 29.NOV.2021 09:32:06

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	896.01949 MHz	-54.61 dBm	-14.61 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.29006 GHz	-54.51 dBm	-14.51 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.50692 GHz	-53.70 dBm	-13.70 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.94341 GHz	-49.44 dBm	-9.44 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.35319 GHz	-50.58 dBm	-10.58 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.28034 GHz	-49.52 dBm	-9.52 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.53756 GHz	-46.12 dBm	-6.12 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.70861 GHz	-46.78 dBm	-6.78 dB

Date: 29.NOV.2021 09:21:48

LTE Band 30 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	978.42829 MHz	-54.86 dBm	-14.86 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.29092 GHz	-54.54 dBm	-14.54 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.41339 GHz	-53.04 dBm	-13.04 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.95620 GHz	-49.32 dBm	-9.32 dB
7.000 GHz	10.000 GHz	1.000 MHz	7.35419 GHz	-50.42 dBm	-10.42 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.95526 GHz	-49.51 dBm	-9.51 dB
14.000 GHz	18.000 GHz	1.000 MHz	15.53206 GHz	-46.26 dBm	-6.26 dB
18.000 GHz	24.000 GHz	1.000 MHz	19.70961 GHz	-46.72 dBm	-6.72 dB

Date: 29.NOV.2021 09:42:18

Frequency Stability

Test Conditions		LTE Band 30 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0058	PASS
40	Normal Voltage	0.0018	
30	Normal Voltage	0.0010	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0072	
0	Normal Voltage	0.0045	
-10	Normal Voltage	0.0003	
-20	Normal Voltage	0.0026	
-30	Normal Voltage	0.0030	
20	Maximum Voltage	0.0027	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0018	

Note:

1. Normal Voltage =3.85 V.；Battery End Point (BEP) =3.4 V.；Maximum Voltage =4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

<Internal Antenna 2>

LTE Band 30

LTE Band 30 / 5MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	4611	-51.36	-40	-11.36	-49.26	-57.28	6.74	12.66	H
	6916.5	-49.52	-40	-9.52	-51.52	-53	8.49	11.97	H
	9222	-54.31	-40	-14.31	-63.06	-55.41	9.71	10.81	H
									H
									H
									H
	4611	-52.07	-40	-12.07	-50.37	-57.99	6.74	12.66	V
	6916.5	-46.55	-40	-6.55	-49.5	-50.03	8.49	11.97	V
	9222	-55.53	-40	-15.53	-63.24	-56.63	9.71	10.81	V
									V
									V
									V
Middle	4614	-51.05	-40	-11.05	-49.26	-56.95	6.74	12.64	H
	6924	-45.65	-40	-5.65	-51.52	-49.11	8.50	11.95	H
	9234	-54.19	-40	-14.19	-63.06	-55.24	9.72	10.76	H
									H
									H
									H
	4614	-52.34	-40	-12.34	-50.37	-58.24	6.74	12.64	V
	6924	-43.43	-40	-3.43	-49.5	-46.89	8.50	11.95	V
	9232	-55.39	-40	-15.39	-63.24	-56.45	9.72	10.77	V
									V
									V
									V

Highest	4620	-52.26	-40	-12.26	-50.39	-58.13	6.75	12.62	H
	6930	-51.69	-40	-11.69	-57.63	-55.13	8.50	11.94	H
	9240	-54.26	-40	-14.26	-63.08	-55.28	9.72	10.74	H
									H
									H
									H
	4620	-54.41	-40	-14.41	-52.2	-60.28	6.75	12.62	V
	6930	-49.23	-40	-9.23	-55.22	-52.67	8.50	11.94	V
	9240	-55.57	-40	-15.57	-63.32	-56.59	9.72	10.74	V
									V
									V
									V

LTE Band 30 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4614	-48.41	-40	-8.41	-46.57	-54.31	6.74	12.64	H
	6918	-49.19	-40	-9.19	-55.16	-52.66	8.49	11.96	H
	9223	-54.41	-40	-14.41	-63.25	-55.51	9.71	10.81	H
									H
									H
									H
	4614	-50.37	-40	-10.37	-48.19	-56.27	6.74	12.64	V
	6918	-47.03	-40	-7.03	-53.05	-50.5	8.49	11.96	V
	9223	-55.36	-40	-15.36	-63.17	-56.46	9.71	10.81	V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.