

Measurement of MPE

1. Foreword

In adopt with the Human Exposure IEEE C95.1, and according to the FCC 1.1310. The *Maximum Permissible Exposure (MPE)* is obligated to measure in order to prove the safety of radiation harmfulness to the human body.

The *Gain* of the antenna used is measured in an *Anechoic chamber*. The *maximum total power to the antenna* is to be recorded. By adopting the ***Friis Transmission Formula*** and the *power gain of the antenna*, we can find the distance right away from the product, where the limit of the MPE is.

2. Description of EUT

Applicant	:	Netgear Inc.
Applicant Address	:	4500 Great America Parkway, Santa Clara CA 95054
Classification	:	Mobile Device (i) Under normal use condition, the antenna is at least 20cm away from the user; (ii) Warning statement for keeping 20cm separation distance and the prohibition of operating next to the person has been printed in the user's manual
Model No.	:	CG814WB
Granted FCC ID	:	PY3CG814WB
Frequency Range	:	2.412 GHz ~ 2.462GHz
Support Channel	:	11 Channels
Modulation Skill	:	BPSK, QPSK, CCK
Power Type	:	By the Power adaptor M/N: AD-121ADT I/P: AC 120V, 60Hz, 18W O/P: DC +12V, 1A
Power Cable	:	I/P (Power to Adapter): 190cm long, non-shielded, no ferrite core O/P (Adapter to EUT): 190cm long, non-shielded, no ferrite core

3. Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	100	6
3.0-30	1842/f	4.89/f	900/f ²	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	100	30
1.34-30	824/f	2.19/f	180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

[The EUT is tested in transmit and receive modes and in the first, middle and the last channel separately. The following shows only our observation have the greatest emissions.]

According to **OET BULLETIN 56 Fourth Edition/August 1999, Equation for Predicting RF Fields:**

$$\text{Friis Transmission Formula: } S = \frac{PG}{4pR^2} = \frac{59.57 \times 1.55239}{4p(20)^2} = 0.01839745 \text{ mW / cm}^2$$

$$\text{Estimated safe separation: } R = \sqrt{\frac{PG}{4p}} = \sqrt{\frac{59.57 \times 1.55239}{4p}} = 1.7127 \text{ cm}$$

Remarks: "The safe estimated separation that the user must maintain from the antenna is at least 1.72 cm."

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

The Numeric gain G of antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain}/10)$$

$$G = \text{Log}^{-1} (1.91 / 10) = 1.55239$$

連展科技股份有限公司

ADVANCED-CONNECTEK INC.

承認書

SPECIFICATION FOR APPROVAL

貴公司

CUSTOMER

產品名稱
DESCRIPTION

2.4GHz Dipole Antenna SMA 90-180 Deg
Male RP

客戶料號
CUSTOMER P/N

連展料號
ACON P/N

ADA06-1K10000

部門確認
DESINGER

工程 機構 品保

檢送日期
SENDING DATE

核准編號
APPROVAL NO.

DESCRIPTION :

Omni - directional antenna which is useful for 802.11b/g (ISM band) ,

Ex : Wireless LAN .

SPECIFICATION :

Part Number : ADA06-1K10000	
Appearance & Dimensions :	108(L) × 10.5(R) mm
Weight :	≤ 20 g
Operation Frequency :	2.4~2.4835 GHz
Impedance :	50 Ohms
Polarization :	Vertical
Antenna Gain :	1.91 dBi (Max.)
Antenna SWR :	≤ 2 : 1
Connector Type :	SMA Male RP

