## #01_GSM850_GPRS (4 Tx slots)_Right Cheek_Ch251

Communication System: GSM850; Frequency: 848.8 MHz;Duty Cycle: 1:2.08
Medium: HSL_850_200729 Medium parameters used: f = 849 MHz; $\sigma$ = 0.94 S/m; $\varepsilon_r$ = 41.599; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 848.8 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.102 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.41 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 0.118 W/kg
**SAR(1 g) = 0.092 W/kg; SAR(10 g) = 0.071 W/kg**
Maximum value of SAR (measured) = 0.101 W/kg




0 dB = 0.101 W/kg = -9.96 dBW/kg

# #02_GSM1900_GPRS (4 Tx slots)_Right Cheek_Ch661

Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:2.08
Medium: HSL_1900_200730 Medium parameters used: f = 1880 MHz; $\sigma$ = 1.39 S/m; $\varepsilon_r$ = 40.211; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(7.82, 7.82, 7.82) @ 1880 MHz; Calibrated: 2020/2/4
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2019/11/14
- Phantom: SAM-Middle; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0350 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.050 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 0.0360 W/kg
**SAR(1 g) = 0.019 W/kg; SAR(10 g) = 0.011 W/kg**
Maximum value of SAR (measured) = 0.0273 W/kg




0 dB = 0.0273 W/kg = -15.64 dBW/kg

## #03_WCDMA V_RMC 12.2Kbps_Left Cheek_Ch4233

Communication System: WCDMA; Frequency: 846.6 MHz;Duty Cycle: 1:1
Medium: HSL_850_200729 Medium parameters used: f = 847 MHz; $\sigma$ = 0.939 S/m; $\varepsilon_r$ = 41.612; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 846.6 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.145 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.56 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.148 W/kg
**SAR(1 g) = 0.125 W/kg; SAR(10 g) = 0.097 W/kg**
Maximum value of SAR (measured) = 0.133 W/kg




0 dB = 0.133 W/kg = -8.76 dBW/kg

## #04_LTE Band 4_20M_QPSK_1_0_Left Cheek_Ch20175

Communication System: LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: HSL_1750_200729 Medium parameters used: f = 1733 MHz; $\sigma$ = 1.348 S/m; $\varepsilon_r$ = 39.474; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(8.06, 8.06, 8.06) @ 1732.5 MHz; Calibrated: 2020/2/4
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn699; Calibrated: 2020/2/26
- Phantom: SAM-Middle; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0721 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.920 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.0560 W/kg
**SAR(1 g) = 0.037 W/kg; SAR(10 g) = 0.022 W/kg**
Maximum value of SAR (measured) = 0.0481 W/kg




0 dB = 0.0481 W/kg = -13.18 dBW/kg

# #05_LTE Band 5_10M_QPSK_1_0_Left Cheek_Ch20525

Communication System: LTE; Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: HSL_850_200729 Medium parameters used : f = 836.5 MHz; $\sigma$ = 0.932 S/m; $\varepsilon_r$ = 41.689; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 836.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.169 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.11 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 0.186 W/kg
**SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.111 W/kg**
Maximum value of SAR (measured) = 0.163 W/kg




0 dB = 0.163 W/kg = -7.88 dBW/kg

## #06_LTE Band 7_20M_QPSK_1_99_Left Cheek_Ch20850

Communication System: LTE ; Frequency: 2510 MHz;Duty Cycle: 1:1
Medium: HSL_2600_200731 Medium parameters used: f = 2510 MHz; $\sigma$ = 1.82 S/m; $\varepsilon_r$ = 39.134; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.51, 4.51, 4.51) @ 2510 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2020/2/18
- Phantom: SAM_Left; Type: SAM; Serial: 1796
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0194 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.706 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.0260 W/kg
**SAR(1 g) = 0.014 W/kg; SAR(10 g) = 0.00657 W/kg**
Maximum value of SAR (measured) = 0.0170 W/kg




0 dB = 0.0170 W/kg = -17.70 dBW/kg

## #07_LTE Band 12_10M_QPSK_1_0_Left Cheek_Ch23095

Communication System: LTE ; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium: HSL_750_200728 Medium parameters used : f = 707.5 MHz; $\sigma$ = 0.886 S/m; $\varepsilon_r$ = 41.885; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.61, 6.61, 6.61) @ 707.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.154 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.96 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.168 W/kg
**SAR(1 g) = 0.140 W/kg; SAR(10 g) = 0.109 W/kg**
Maximum value of SAR (measured) = 0.152 W/kg




0 dB = 0.152 W/kg = -8.18 dBW/kg

# #08_LTE Band 13_10M_QPSK_1_49_Left Cheek_Ch23230

Communication System: LTE; Frequency: 782 MHz;Duty Cycle: 1:1
Medium: HSL_750_200728 Medium parameters used: f = 782 MHz; $\sigma$ = 0.911 S/m; $\varepsilon_r$ = 41.621; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.61, 6.61, 6.61) @ 782 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.190 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.76 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 0.214 W/kg
**SAR(1 g) = 0.176 W/kg; SAR(10 g) = 0.134 W/kg**
Maximum value of SAR (measured) = 0.192 W/kg




0 dB = 0.192 W/kg = -7.17 dBW/kg

# #09_LTE Band 41_20M_QPSK_1_0_Left Cheek_Ch41055

Communication System: LTE ; Frequency: 2636.5 MHz;Duty Cycle: 1:1.59
Medium: HSL_2600_200730 Medium parameters used: f = 2636.5 MHz; $\sigma$ = 2.061 S/m; $\varepsilon_r$ = 38.071; $\rho$ = $1000_{kg/m^3}$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(4.49, 4.49, 4.49) @ 2636.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.00566 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 0.4740 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0 W/kg
**SAR(1 g) = 0.001 W/kg ; SAR(10 g) = 0.001 W/kg**
Maximum value of SAR (measured) = 0.00572 W/kg




0 dB = 0.00572 W/kg = -22.43 dBW/kg

# #10_WLAN2.4GHz_802.11b 1Mbps_Right Cheek_Ch6

Communication System: 802.11b; Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL_2450_200731 Medium parameters used: f = 2437 MHz; $\sigma$ = 1.831 S/m; $\varepsilon_r$ = 38.949; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(4.69, 4.69, 4.69) @ 2437 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.863 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.739 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 1.40 W/kg
**SAR(1 g) = 0.547 W/kg; SAR(10 g) = 0.206 W/kg**
Maximum value of SAR (measured) = 0.786 W/kg




0 dB = 0.786 W/kg = -1.05 dBW/kg

# #11_WLAN5GHz_802.11ac-VHT80 MCS0_Right Cheek_Ch58

Communication System: 802.11ac ; Frequency: 5290 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200729 Medium parameters used : f = 5290 MHz; $\sigma$ = 4.662 S/m; $\varepsilon_r$ = 36.55; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.43, 4.43, 4.43) @ 5290 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.596 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 0 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.924 W/kg
**SAR(1 g) = 0.203 W/kg; SAR(10 g) = 0.048 W/kg**
Maximum value of SAR (measured) = 0.580 W/kg




0 dB = 0.580 W/kg = -2.37 dBW/kg

# #12_WLAN5GHz_802.11ac-VHT80 MCS0_Right Cheek_Ch106

Communication System: 802.11ac ; Frequency: 5530 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200729 Medium parameters used: f = 5530 MHz; $\sigma$ = 4.921 S/m; $\varepsilon_r$ = 36.256; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.19, 4.19, 4.19) @ 5530 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.366 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 0 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 0.590 W/kg
**SAR(1 g) = 0.107 W/kg; SAR(10 g) = 0.023 W/kg**
Maximum value of SAR (measured) = 0.343 W/kg




0 dB = 0.343 W/kg = -4.65 dBW/kg

# #13_WLAN5GHz_802.11ac-VHT80 MCS0_Right Cheek_Ch155

Communication System: 802.11ac ; Frequency: 5775 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200729 Medium parameters used: f = 5775 MHz; $\sigma$ = 5.167 S/m; $\varepsilon_r$ = 35.852; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.17, 4.17, 4.17) @ 5775 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (101x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.722 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 0 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 0.786 W/kg
**SAR(1 g) = 0.146 W/kg; SAR(10 g) = 0.033 W/kg**
Maximum value of SAR (measured) = 0.468 W/kg




0 dB = 0.468 W/kg = -3.30 dBW/kg

## #14_Bluetooth_1Mbps_Right Cheek_Ch78

Communication System: Bluetooth; Frequency: 2480 MHz;Duty Cycle: 1:1.297
Medium: HSL_2450_200731 Medium parameters used: f = 2480 MHz; $\sigma$ = 1.883 S/m; $\varepsilon_r$ = 38.769; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(4.69, 4.69, 4.69) @ 2480 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.516 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.157 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 1.15 W/kg
**SAR(1 g) = 0.444 W/kg; SAR(10 g) = 0.166 W/kg**
Maximum value of SAR (measured) = 0.645 W/kg




0 dB = 0.645 W/kg = -1.90 dBW/kg

# #15_GSM850_GPRS (4 Tx slots)_Right Side_10mm_Ch251

Communication System: GSM850; Frequency: 848.8 MHz;Duty Cycle: 1:2.08
Medium: HSL_850_200729 Medium parameters used: f = 849 MHz; $\sigma$ = 0.94 S/m; $\varepsilon_r$ = 41.599; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 848.8 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (41x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.200 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.30 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.219 W/kg
**SAR(1 g) = 0.172 W/kg; SAR(10 g) = 0.122 W/kg**
Maximum value of SAR (measured) = 0.193 W/kg




0 dB = 0.193 W/kg = -7.14 dBW/kg

# #16_GSM1900_GPRS (4 Tx slots)_Bottom Side_10mm_Ch661

Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:2.08
Medium: HSL_1900_200730 Medium parameters used: f = 1880 MHz; $\sigma$ = 1.39 S/m; $\varepsilon_r$ = 40.211; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(7.82, 7.82, 7.82) @ 1880 MHz; Calibrated: 2020/2/4
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2019/11/14
- Phantom: SAM-Middle; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (41x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.348 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.91 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.390 W/kg
**SAR(1 g) = 0.228 W/kg; SAR(10 g) = 0.121 W/kg**
Maximum value of SAR (measured) = 0.335 W/kg




0 dB = 0.335 W/kg = -4.75 dBW/kg

# #17_WCDMA V_RMC 12.2Kbps__Right Side_10mm_Ch4233

Communication System: WCDMA; Frequency: 846.6 MHz;Duty Cycle: 1:1
Medium: HSL_850_200729 Medium parameters used: f = 847 MHz; $\sigma$ = 0.939 S/m; $\varepsilon_r$ = 41.612; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 846.6 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (41x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.220 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.22 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.237 W/kg
**SAR(1 g) = 0.191 W/kg; SAR(10 g) = 0.136 W/kg**
Maximum value of SAR (measured) = 0.214 W/kg




0 dB = 0.214 W/kg = -6.70 dBW/kg

# #18_LTE Band 4_20M_QPSK_50_0_Bottom Side_10mm_Ch20175

Communication System: LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: HSL_1750_200729 Medium parameters used: f = 1733 MHz; $\sigma$ = 1.348 S/m; $\varepsilon_r$ = 39.474; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(8.06, 8.06, 8.06) @ 1732.5 MHz; Calibrated: 2020/2/4
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn699; Calibrated: 2020/2/26
- Phantom: SAM-Middle; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (51x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.604 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 19.47 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 0.680 W/kg
**SAR(1 g) = 0.403 W/kg; SAR(10 g) = 0.215 W/kg**
Maximum value of SAR (measured) = 0.590 W/kg




0 dB = 0.590 W/kg = -2.29 dBW/kg

# #19_LTE Band 5_10M_QPSK_1_0_Right Side_10mm_Ch20525

Communication System: LTE; Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: HSL_850_200729 Medium parameters used : f = 836.5 MHz; $\sigma$ = 0.932 S/m; $\varepsilon_r$ = 41.689; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 836.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (41x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.222 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.04 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.246 W/kg
**SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.137 W/kg**
Maximum value of SAR (measured) = 0.218 W/kg




0 dB = 0.218 W/kg = -6.62 dBW/kg

# #20_LTE Band 7_20M_QPSK_1_99_Bottom Side_10mm_Ch20850

Communication System: LTE; Frequency: 2510 MHz;Duty Cycle: 1:1
Medium: HSL_2600_200731 Medium parameters used: f = 2510 MHz; σ = 1.82 S/m; $\varepsilon_r$ = 39.134; ρ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.51, 4.51, 4.51) @ 2510 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2020/2/18
- Phantom: SAM_Left; Type: SAM; Serial: 1796
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (51x101x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.255 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.627 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.341 W/kg
**SAR(1 g) = 0.179 W/kg; SAR(10 g) = 0.088 W/kg**
Maximum value of SAR (measured) = 0.232 W/kg




0 dB = 0.232 W/kg = -6.35 dBW/kg

# #21_LTE Band 12_10M_QPSK_1_0_Back_10mm_Ch23095

Communication System: LTE ; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium: HSL_750_200730 Medium parameters used: f = 707.5 MHz; $\sigma$ = 0.894 S/m; $\varepsilon_r$ = 41.999; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.61, 6.61, 6.61) @ 707.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.203 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 14.52 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.195 W/kg
**SAR(1 g) = 0.176 W/kg; SAR(10 g) = 0.142 W/kg**
Maximum value of SAR (measured) = 0.187 W/kg




0 dB = 0.187 W/kg = -7.28 dBW/kg

# #22_LTE Band 13_10M_QPSK_1_49_Left Side_10mm_Ch23230

Communication System: LTE; Frequency: 782 MHz;Duty Cycle: 1:1
Medium: HSL_750_200730 Medium parameters used: f = 782 MHz; $\sigma$ = 0.92 S/m; $\varepsilon_r$ = 41.735; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.61, 6.61, 6.61) @ 782 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (41x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.250 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.86 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.276 W/kg
**SAR(1 g) = 0.216 W/kg; SAR(10 g) = 0.154 W/kg**
Maximum value of SAR (measured) = 0.243 W/kg




0 dB = 0.243 W/kg = -6.14 dBW/kg

## #23_LTE Band 41_20M_QPSK_1_0_Bottom Side_10mm_Ch41055

Communication System: LTE; Frequency: 2636.5 MHz;Duty Cycle: 1:1.59
Medium: HSL_2600_200731 Medium parameters used : f = 2636.5 MHz; $\sigma$ = 1.921 S/m; $\varepsilon_r$ = 38.962; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.51, 4.51, 4.51) @ 2636.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2020/2/18
- Phantom: SAM_Left; Type: SAM; Serial: 1796
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (51x101x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0589 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.751 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.0820 W/kg
**SAR(1 g) = 0.043 W/kg; SAR(10 g) = 0.020 W/kg**
Maximum value of SAR (measured) = 0.0559 W/kg




0 dB = 0.0559 W/kg = -12.53 dBW/kg

# #24_WLAN2.4GHz_802.11b 1Mbps_Left Side_Ch6

Communication System: 802.11b; Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL_2450_200731 Medium parameters used: f = 2437 MHz; $\sigma$ = 1.831 S/m; $\varepsilon_r$ = 38.949; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(4.69, 4.69, 4.69) @ 2437 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (51x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.261 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.833 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 0.339 W/kg
**SAR(1 g) = 0.200 W/kg; SAR(10 g) = 0.096 W/kg**
Maximum value of SAR (measured) = 0.253 W/kg




0 dB = 0.253 W/kg = -5.97 dBW/kg

## #25_Bluetooth_1Mbps_Back_10mm_Ch78

Communication System: Bluetooth; Frequency: 2480 MHz;Duty Cycle: 1:1.297
Medium: HSL_2450_200731 Medium parameters used: f = 2480 MHz; $\sigma$ = 1.883 S/m; $\varepsilon_r$ = 38.769; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(4.69, 4.69, 4.69) @ 2480 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.221 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 3.127 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 0.266 W/kg
**SAR(1 g) = 0.155 W/kg; SAR(10 g) = 0.075 W/kg**
Maximum value of SAR (measured) = 0.199 W/kg




0 dB = 0.199 W/kg = -7.01 dBW/kg

## #26_GSM850_GPRS (4 Tx slots)_Back_15mm_Ch251

Communication System: GSM850; Frequency: 848.8 MHz;Duty Cycle: 1:2.08
Medium: HSL_850_200729 Medium parameters used: f = 849 MHz; $\sigma$ = 0.94 S/m; $\varepsilon_r$ = 41.599; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 848.8 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.156 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.01 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.151 W/kg
**SAR(1 g) = 0.131 W/kg; SAR(10 g) = 0.104 W/kg**
Maximum value of SAR (measured) = 0.142 W/kg




0 dB = 0.142 W/kg = -8.48 dBW/kg

## #27_GSM1900_GPRS (4 Tx slots)_Front_15mm_Ch661

Communication System: PCS; Frequency: 1880 MHz;Duty Cycle: 1:2.08
Medium: HSL_1900_200730 Medium parameters used: f = 1880 MHz; $\sigma$ = 1.39 S/m; $\varepsilon_r$ = 40.211; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(7.82, 7.82, 7.82) @ 1880 MHz; Calibrated: 2020/2/4
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2019/11/14
- Phantom: SAM-Middle; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.109 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.525 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.129 W/kg
**SAR(1 g) = 0.078 W/kg; SAR(10 g) = 0.045 W/kg**
Maximum value of SAR (measured) = 0.108 W/kg




0 dB = 0.108 W/kg = -9.67 dBW/kg

## #28_WCDMA V_RMC 12.2Kbps_Back_15mm_Ch4233

Communication System: WCDMA; Frequency: 846.6 MHz;Duty Cycle: 1:1
Medium: HSL_850_200729 Medium parameters used: f = 847 MHz; $\sigma$ = 0.939 S/m; $\varepsilon_r$ = 41.612; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 846.6 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.171 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.44 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 0.183 W/kg
**SAR(1 g) = 0.159 W/kg; SAR(10 g) = 0.124 W/kg**
Maximum value of SAR (measured) = 0.169 W/kg




0 dB = 0.169 W/kg = -7.72 dBW/kg

## #29_LTE Band 4_20M_QPSK_50_0_Back_15mm_Ch20175

Communication System: LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: HSL_1750_200729 Medium parameters used: f = 1733 MHz; $\sigma$ = 1.348 S/m; $\varepsilon_r$ = 39.474; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(8.06, 8.06, 8.06) @ 1732.5 MHz; Calibrated: 2020/2/4
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn699; Calibrated: 2020/2/26
- Phantom: SAM-Middle; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.216 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.35 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.251 W/kg
**SAR(1 g) = 0.160 W/kg; SAR(10 g) = 0.095 W/kg**
Maximum value of SAR (measured) = 0.216 W/kg




0 dB = 0.216 W/kg = -6.66 dBW/kg

# #30_LTE Band 5_10M_QPSK_1_0_Front_15mm_Ch20525

Communication System: LTE ; Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: HSL_850_200729 Medium parameters used: f = 836.5 MHz; σ = 0.932 S/m; $\varepsilon_r$ =41.689; ρ = 1000 kg/m$^3$
Ambient Temperature：23.4 ℃; Liquid Temperature：22.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.41, 6.41, 6.41) @ 836.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.162 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.02 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.163 W/kg
**SAR(1 g) = 0.144 W/kg; SAR(10 g) = 0.115 W/kg**
Maximum value of SAR (measured) = 0.154 W/kg




0 dB = 0.154 W/kg = -8.12 dBW/kg

## #31_LTE Band 7_20M_QPSK_50_50_Back_15mm_Ch20850

Communication System: LTE; Frequency: 2510 MHz;Duty Cycle: 1:1
Medium: HSL_2600_200731 Medium parameters used: f = 2510 MHz; $\sigma$ = 1.82 S/m; $\varepsilon_r$ = 39.134; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.51, 4.51, 4.51) @ 2510 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2020/2/18
- Phantom: SAM_Left; Type: SAM; Serial: 1796
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0659 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.310 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.101 W/kg
**SAR(1 g) = 0.054 W/kg; SAR(10 g) = 0.028 W/kg**
Maximum value of SAR (measured) = 0.0677 W/kg




0 dB = 0.0677 W/kg = -11.69 dBW/kg

# #32_LTE Band 12_10M_QPSK_1_0_Back_15mm_Ch23095

Communication System: LTE ; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium: HSL_750_200730 Medium parameters used: f = 707.5 MHz; $\sigma$ = 0.894 S/m; $\varepsilon_r$ = 41.999; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.61, 6.61, 6.61) @ 707.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.158 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.90 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.157 W/kg
**SAR(1 g) = 0.139 W/kg; SAR(10 g) = 0.111 W/kg**
Maximum value of SAR (measured) = 0.148 W/kg




0 dB = 0.148 W/kg = -8.30 dBW/kg

# #33_LTE Band 13_10M_QPSK_1_49_Front_15mm_Ch23230

Communication System: LTE; Frequency: 782 MHz;Duty Cycle: 1:1
Medium: HSL_750_200730 Medium parameters used: f = 782 MHz; $\sigma$ = 0.92 S/m; $\varepsilon_r$ = 41.735; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(6.61, 6.61, 6.61) @ 782 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.203 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 15.02 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 0.205 W/kg
**SAR(1 g) = 0.181 W/kg; SAR(10 g) = 0.144 W/kg**
Maximum value of SAR (measured) = 0.192 W/kg




0 dB = 0.192 W/kg = -7.17 dBW/kg

## #34_LTE Band 41_20M_QPSK_50_0_Back_15mm_Ch41055

Communication System: LTE; Frequency: 2636.5 MHz;Duty Cycle: 1:1.59
Medium: HSL_2600_200731 Medium parameters used : f = 2636.5 MHz; $\sigma$ = 1.921 S/m; $\varepsilon_r$ = 38.962; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.51, 4.51, 4.51) @ 2636.5 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1399; Calibrated: 2020/2/18
- Phantom: SAM_Left; Type: SAM; Serial: 1796
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (81x121x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0139 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.028 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.0210 W/kg
**SAR(1 g) = 0.010 W/kg; SAR(10 g) = 0.00408 W/kg**
Maximum value of SAR (measured) = 0.0135 W/kg




0 dB = 0.0135 W/kg = -18.70 dBW/kg

# #35_WLAN2.4GHz_802.11b 1Mbps_Back_15mm_Ch6

Communication System: 802.11b ; Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL_2450_200731 Medium parameters used : f = 2437 MHz; $\sigma$ = 1.831 S/m; $\varepsilon_r$ = 38.949; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(4.69, 4.69, 4.69) @ 2437 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (81x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.109 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.930 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 0.130 W/kg
**SAR(1 g) = 0.082 W/kg; SAR(10 g) = 0.043 W/kg**
Maximum value of SAR (measured) = 0.103 W/kg




0 dB = 0.103 W/kg = -9.87 dBW/kg

# #36_WLAN5GHz_802.11ac-VHT80 MCS0_Back_15mm_Ch58

Communication System: 802.11ac; Frequency: 5290 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200729 Medium parameters used : f = 5290 MHz; $\sigma$ = 4.662 S/m; $\varepsilon_r$ = 36.55; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.43, 4.43, 4.43) @ 5290 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.289 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 3.143 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 0.336 W/kg
**SAR(1 g) = 0.092 W/kg; SAR(10 g) = 0.030 W/kg**
Maximum value of SAR (measured) = 0.231 W/kg




0 dB = 0.231 W/kg = -6.36 dBW/kg

# #37_WLAN5GHz_802.11ac-VHT80 MCS0_Back_15mm_Ch106

Communication System: 802.11ac; Frequency: 5530 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200729 Medium parameters used : f = 5530 MHz; $\sigma$ = 4.921 S/m; $\varepsilon_r$ = 36.256; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.19, 4.19, 4.19) @ 5530 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.231 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 2.542 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 0.230 W/kg
**SAR(1 g) = 0.051 W/kg; SAR(10 g) = 0.016 W/kg**
Maximum value of SAR (measured) = 0.143 W/kg




0 dB = 0.143 W/kg = -8.45 dBW/kg

# #38_WLAN5GHz_802.11ac-VHT80 MCS0_Back_15mm_Ch155

Communication System: 802.11ac ; Frequency: 5775 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200729 Medium parameters used: f = 5775 MHz; $\sigma$ = 5.167 S/m; $\varepsilon_r$ = 35.852; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.17, 4.17, 4.17) @ 5775 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.284 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 2.396 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.257 W/kg
**SAR(1 g) = 0.056 W/kg; SAR(10 g) = 0.018 W/kg**
Maximum value of SAR (measured) = 0.158 W/kg




0 dB = 0.158 W/kg = -8.01 dBW/kg

## #39_Bluetooth_1Mbps_Back_15mm_Ch78

Communication System: Bluetooth; Frequency: 2480 MHz;Duty Cycle: 1:1.297
Medium: HSL_2450_200731 Medium parameters used: f = 2480 MHz; $\sigma$ = 1.883 S/m; $\varepsilon_r$ = 38.769; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.1 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3184; ConvF(4.69, 4.69, 4.69) @ 2480 MHz; Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: SAM_Right; Type: QD000P40CD; Serial: TP:1683
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0941 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.399 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 0.110 W/kg
**SAR(1 g) = 0.068 W/kg; SAR(10 g) = 0.036 W/kg**
Maximum value of SAR (measured) = 0.0847 W/kg




0 dB = 0.0847 W/kg = -10.72 dBW/kg

# #40_WLAN5GHz_802.11ac-VHT80 MCS0_Back_0mm_Ch58

Communication System: 802.11ac; Frequency: 5290 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200803 Medium parameters used: f = 5290 MHz; $\sigma$ = 4.787 S/m; $\varepsilon_r$ = 36.813; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.3 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.43, 4.43, 4.43) @ 5290 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (101x111x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 7.67 W/kg

**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 24.63 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 11.9 W/kg
**SAR(1 g) = 2.13 W/kg; SAR(10 g) = 0.408 W/kg**
Maximum value of SAR (measured) = 7.57 W/kg




0 dB = 7.57 W/kg = 8.79 dBW/kg

# #41_WLAN5GHz_802.11ac-VHT80 MCS0_Back_0mm_Ch106

Communication System: 802.11ac; Frequency: 5530 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200803 Medium parameters used : f = 5530 MHz; $\sigma$ = 5.034 S/m; $\varepsilon_r$ = 36.47; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.3 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.19, 4.19, 4.19) @ 5530 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (101x111x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 5.13 W/kg

**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 16.74 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 7.76 W/kg
**SAR(1 g) = 1.57 W/kg; SAR(10 g) = 0.298 W/kg**
Maximum value of SAR (measured) = 4.64 W/kg




0 dB = 4.64 W/kg = 6.67 dBW/kg

# #42_WLAN5GHz_802.11ac-VHT80 MCS0_Back_0mm_Ch155

Communication System: 802.11ac; Frequency: 5775 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200803 Medium parameters used: f = 5775 MHz; $\sigma$ = 5.31 S/m; $\varepsilon_r$ = 36.106; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.3 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3642; ConvF(4.17, 4.17, 4.17) @ 5775 MHz; Calibrated: 2020/4/29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2019/12/6
- Phantom: SAM_Right; Type: SAM; Serial: TP:1681
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7483)

**Area Scan (101x111x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 6.15 W/kg

**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 21.98 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 11.4 W/kg
**SAR(1 g) = 1.76 W/kg; SAR(10 g) = 0.352 W/kg**
Maximum value of SAR (measured) = 5.20 W/kg




0 dB = 5.20 W/kg = 7.16 dBW/kg