TEST REPORT

Applicant:	Sony Corporation
EUT Description:	GSM/WCDMA/LTE/NR Phone with BT, DTS/UNII a/b/g/n/ac/ax and NFC and GNSS
Brand:	Sony
FCC ID:	PY7-29686W
Standards:	FCC 47 CFR Part 15 Subpart C
Date of Receipt:	2025/03/07
Date of Test:	2025/03/07 to 2025/05/09 (FCC ID: PY7-63277Y (Lead Model)) 2025/03/07 to 2025/05/26 (FCC ID: PY7-29686W (This Model))
Date of Issue:	2025/07/01

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.

ACCREDITED
CERTIFICATE #7088.01

Huang Kun
Approved By:

Chen Chengfu
Reviewed By:

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Revision History

Rev.	Issue Date	Description	Revised by
01	2025/05/30	Original	Chen Chengfu
02	2025/07/01	Updated the test note on page 23, and page 29~44	Chen Chengfu

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Summary of Test Results

Clause	FCC Part	Test Items	Result
4.1	§15.203	Antenna Requirement	PASS
4.2	§15.207	AC Power Line Conducted Emission	PASS
4.3	§15.215 (c)	20dB Bandwidth	PASS
4.4	§15.225(e)	Frequency Stability	PASS
4.5	§15.225(a)(b)(c)	In-Band Emissions	PASS
4.6	§15.225(d) §15.209	Radiated Spurious Emissions	PASS*

Test Method: ANSI C63.10:2020.
Remark:
Pass: Refers to FCC ID: PY7-63277Y (Lead Model) data.
PASS*: There is FCC ID: PY7-29686W (This Model) spot check data.

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Table of Contents

1 General Description 5
1.1 Lab Information 5
1.1.1 Testing Location 5
1.1.2 Test Facility / Accreditations 5
1.2 Client Information 5
1.2.1 Applicant 5
1.2.2 Manufacturer 5
1.3 Product Information 6
1.4 Reuse Of Test Data 7
1.4.1 Introduction 7
1.4.2 Device Differences 7
1.4.3 Spot Check Verification Data 7
2 Test Configuration 8
2.1 Worst-case configuration and Mode 8
2.2 Support Unit used in test 8
2.3 Test Environment 8
2.4 Test RF Cable 8
2.5 Modifications 8
2.6 Test Setup Diagram 9
2.6.1 Conducted Configuration 9
2.6.2 Radiated Configuration 10
2.7 Accessory 10
3 Equipment and Measurement Uncertainty 11
3.1 Test Equipment List 11
3.2 Measurement Uncertainty 12
4 Test Results 13
4.1 Antenna Requirement 13
4.2 AC Power Line Conducted Emissions 14
4.3 20dB Bandwidth 19
4.4 Frequency Stability 20
4.5 In-Band Emissions 21
4.6 Radiated Spurious Emissions 22
5 Test Setup Photos 24
Appendix 25

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

1 General Description

1.1 Lab Information

1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014
Tel.: +86-755-27212361
Contact Email: info@towewireless.com

1.1.2 Test Facility / Accreditations

A2LA (Certificate Number: 7088.01)
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

FCC Designation No.: CN1353
Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory. Designation Number: CN1353.

ISED CAB identifier: CN0152
Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.
CAB identifier: CN0152
Company Number: 31000

1.2 Client Information

1.2.1 Applicant

Applicant:	Sony Corporation
Address:	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

1.2.2 Manufacturer

Manufacturer:	Sony Corporation
Address:	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

1.3 Product Information

EUT Description:	GSM/WCDMA/LTE/NR Phone with BT, DTS/UNII a/b/g/n/ac/ax and NFC and GNSS			
Brand:	Sony			
Hardware Version:	A			
Software Version:	0.87 (Lead Model) 0.87 (This Model)			
SN.:	RF Conducted	HQ652D0109 (Lead Model)		
	RSE & AC power line	HQ652D0109 (Lead Model)		
	RSE	HQ652G0040 (This Model)		
Support Type:	☒Type A	☒Type B	☒Type F	☒Type V
Modulation Type:	ASK			
Frequency Range:	13.553~13.567MHz			
Channel Frequency:	13.56MHz			
Channel Number:	1			
Remark: The above EUT's information was declared by applicant, please refer to the specifications or user manual for more detailed description.				

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

1.4 Reuse Of Test Data

1.4.1 Introduction

According to the manufacturer the major change between FCC ID: PY7-63277Y (Lead Model), and FCC ID: PY7-29686W (This Model) is changing band configuration by software, The FCC ID: PY7-63277Y (Lead Model) conducted test data shall remain representative of FCC ID: PY7-29686W so, FCC ID: PY7-29686W (This Model) leverages conducted test data from FCC ID: PY7-63277Y (Lead Model).

1.4.2 Device Differences

The equipment under test (EUT) in this filing FCC ID: PY7-29686W (This Model) and the reference device certified under FCC ID: PY7-63277Y (Lead Model) share a common design. The components used for 2.4GHz and 5GHz Wi-Fi and BT and NFC, including antennas and output power are identical between the EUT and reference device.

1.4.3 Spot Check Verification Data

In this filing, the worst-case data and spot checks were tested on the EUT as noted below, against the reference device. All the necessary test cases were performed to verify the variant EUT is still in compliance with the spot checked results to the reference device and was performed using the guidance of ANSI C63.10:2020.

According to 484596 Referencing Test Data v03, Spot checks of the following tests were performed:

Sport check Items	Reference (PY7-63277Y) Worst-case	Variant Test (PY7-29686W)	dB Difference	Spot-Check Parameters	Pass Criterion
Radiated Spurious Emission	13.553~13.567MHz R_{dB}=33.92dBμV/m	13.553~13.567MHz V_{dB}=32.18dBμV/m	d_{dB}=1.74dB	C_{dB}=40dBμV/m M_{dB}=| C_{dB} - R_{dB} |=6.08dB $d_{dBmax}(M_{dB})$=3.30dB	$d_{dB} < d_{dBmax}(M_{dB})$ Pass

Note:
R_{dB}: is the corresponding reference measurement level in dB for the lead model.
V_{dB}: is the variant spot-check level in dB.
d_{dB}: is the deviation data.
C_{dB}: is the compliance threshold.
M_{dB}: is the margin in dB from the compliance limit.
d_{dBmax}: is the maximum deviation d_{dB}.

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

2 Test Configuration

2.1 Worst-case configuration and Mode

Support Type:	Type A	Type B	Type F	Type V
With ANT mode:	Working with antenna mode			
ANT Port Terminated mode:	Working without antenna mode			
Remark:	The AC conduction emissions data only reflect the worst Type			

Radiated Configuration:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 300 m open area test site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788 D01.

2.2 Support Unit used in test

Description	Manufacturer	Model	Serial Number
NFC A IC CARD	Tiananxin	T1TOP	14443-3A
NFC B IC CARD	Tiananxin	T4TOP	14443-4B
NFC F IC CARD	Tiananxin	T3TOP	X6319-3F
NFC V IC CARD	Tiananxin	T5TOP	15693-5V

2.3 Test Environment

Temperature:	Normal: 15℃ ~ 35℃
Humidity:	45 ~ 56 % RH Ambient
Voltage:	DC 3.89V
AC Voltage:	AC 120V/60Hz
Remark: The testing environment is within the scope of the EUT user manual and meets the requirements of the standard testing environment.	

2.4 Test RF Cable

For all conducted test items: The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor

2.5 Modifications

No modifications were made during testing.

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

2.6 Test Setup Diagram

2.6.1 Conducted Configuration

Setup 1



Setup 2



All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

2.6.2 Radiated Configuration



2.7 Accessory

Name	Model	Length (cm)	Shielded (Y/N)	Manufacturer
Adapter	XQZ-UC1	/	/	Sony Corporation
USB Cable	XQZ-UB1	100	Y	Sony Corporation
Earphone	MDR-EX15AP	125	/	Sony Corporation

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable to recognized national standards.

3.1 Test Equipment List

RF Conducted					
Description	**Manufacturer**	**Model**	**S.N.**	**Last Due**	**Cal Due**
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2024/05/30	2025/05/29
Mini type temperature chamber	ESPEC	GSU-24V	0060-001323	2024/06/19	2025/06/18

Radiated Emission					
Description	**Manufacturer**	**Model**	**S.N.**	**Last Due**	**Cal Due**
Loop Antenna	Schwarzbeck	FMZB 1519C	1519C-028	2023/06/29	2025/06/28
Biconic Logarithmic Periodic Antennas	Schwarzbeck	VULB9163	1643	2023/06/25	2025/06/24
Signal Analyzer	Keysight	N9020A	MY49100252	2024/03/25	2025/03/24
				2025/03/11	2026/03/10
EMI Tester Receiver	Rohde & Schwarz	ESR7	102719	2024/05/31	2025/05/30
Wideband Radio Communication Tester	R&S	CMW500	150645	2024/03/25	2025/03/24
				2025/03/11	2026/03/10
Low Noise Amplifier	Tonscend	TAP9K3G40	AP23A8060273	2023/04/08	2025/04/07
				2025/03/11	2027/03/10
Low Noise Amplifier	Tonscend	TAP01018050	AP22G806258	2023/04/08	2025/04/07
				2025/03/11	2027/03/10
Band Reject Filter Group	Townshend	JS0806-F	23A806F0652	N/A	N/A
Test Software	Tonscend	TS+	Version: 5.0.0	N/A	N/A

Conducted Emission					
Description	**Manufacturer**	**Model**	**S.N.**	**Last Due**	**Cal Due**
EMI Tester Receiver	Rohde & Schwarz	ESR3	103108	2024/05/31	2025/05/30
LISN	Rohde & Schwarz	ENV 216	102836	2025/01/04	2026/01/03
Test software	Rohde & Schwarz	ELEKTRA V4.61	N/A	N/A	N/A

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

3.2 Measurement Uncertainty

Parameter	U_{lab}
Frequency Error	679.98Hz
Output Power	0.76dB
Conducted Emissions(150KHz~30MHz)	2.43dB
Radiated Emissions(9kHz~30MHz)	2.40dB
Radiated Emissions(30MHz~1000MHz)	4.66dB

Uncertainty figures are valid to a confidence level of 95%

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

4 Test Results

4.1 Antenna Requirement

Standard Applicable:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
The antenna gain and type as provided by the manufacturer are as follows: The antenna Type is LOOP Antenna. Antenna Anti-Replacement Construction: An embedded-in antenna design is used.	

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

4.2 AC Power Line Conducted Emissions

Limits

Frequency range (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

Test Procedure

C63.10:2020, Section 6.2.

Test Settings

1. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
2. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
3. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
4. Set the test-receiver system to Peak detect function and specified bandwidth (if bandwidth =9kHz) with maximum hod mode. Then measurement is also conducted by average detector and Quasi-Peak detector function respectively.
5. Both sides of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Test Setup



Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Test Result

Test mode:	NFC Type B (With ANT)		
Test Voltage:	AC 120V / 60Hz	Phase:	Line



Rg	Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line
1	0.159	52.89	65.52	12.63	24.99	55.52	30.53	9.52	L1
2	0.173	52.18	64.84	12.66	21.31	54.84	33.53	9.48	L1
3	0.182	51.19	64.42	13.23	20.90	54.42	33.52	9.49	L1
4	0.209	49.62	63.26	13.64	18.85	53.26	34.41	9.55	L1
5	1.820	32.25	56.00	23.75	15.25	46.00	30.75	9.99	L1
6	18.825	24.97	60.00	35.03	11.96	50.00	38.04	12.48	L1

Note:
1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Value =Reading[dBµV] + Factor(LISN factor[dB] + Cable loss[dB]).

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Test mode:	NFC Type B (With ANT)		
Test Voltage:	AC 120V / 60Hz	Phase:	Neutral



Rg	Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line
1	0.155	53.68	65.75	12.07	25.00	55.75	30.75	9.63	N
2	0.177	52.05	64.63	12.58	20.78	54.63	33.85	9.65	N
3	0.191	50.80	64.01	13.21	22.36	54.01	31.65	9.68	N
4	0.204	49.75	63.45	13.70	19.26	53.45	34.19	9.70	N
5	1.829	32.94	56.00	23.06	18.14	46.00	27.86	9.95	N
6	18.276	23.95	60.00	36.05	15.45	50.00	34.55	12.61	N

Note:
1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Value =Reading[dBµV] + Factor(LISN factor[dB] + Cable loss[dB]).

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Test mode:	NFC Type A (normal operation with antenna port terminated)		
Test Voltage:	AC 120V / 60Hz	Phase:	Line



Rg	Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line
1	0.150	53.61	66.00	12.39	23.91	56.00	32.09	9.57	L1
2	0.164	53.13	65.28	12.15	25.45	55.28	29.83	9.50	L1
3	0.186	51.22	64.21	12.99	22.08	54.21	32.13	9.50	L1
4	0.213	49.11	63.09	13.98	18.96	53.09	34.13	9.56	L1
5	0.222	48.50	62.74	14.24	20.26	52.74	32.48	9.58	L1
6	0.285	44.66	60.67	16.01	16.24	50.67	34.43	9.72	L1

Note:
1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Value =Reading[dBµV] + Factor(LISN factor[dB] + Cable loss[dB]).

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Test mode:	NFC Type A (normal operation with antenna port terminated)		
Test Voltage:	AC 120V / 60Hz	Phase:	Neutral



Rg	Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line
1	0.150	55.07	66.00	10.93	25.36	56.00	30.64	9.63	N
2	0.164	54.52	65.28	10.76	24.73	55.28	30.55	9.63	N
3	0.213	51.00	63.09	12.09	21.56	53.09	31.53	9.70	N
4	0.240	49.38	62.10	12.72	19.84	52.10	32.26	9.72	N
5	0.290	45.94	60.54	14.60	16.90	50.54	33.64	9.74	N
6	1.059	31.68	56.00	24.32	23.48	46.00	22.52	9.90	N

Note:
1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Value =Reading[dBµV] + Factor(LISN factor[dB] + Cable loss[dB]).

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

4.3 20dB Bandwidth

Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

ANSI C63.10:2020 and 6.9.3

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. The transmitter output is connected to a spectrum analyzer:
   RBW = 1~5% of the 20dB bandwidth.
   VBW = 3 times the RBW.
   Span = Approximately 2 to 5times the 20dB bandwidth.
   Sweep = Auto.
   Detector = Peak.
   Trace = Max hold.
3. Measure and record the results in the test report.

Test Notes

Because the measured signal is CW-like, adjusting the RBW per C63.10would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

Test Setup

Refer to section 2.6.1- Setup 1 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix.**

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

4.4 Frequency Stability

Limits

The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency over a temperature variation of −20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Procedure

ANSI C63.10:2020 Section 6.8

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. The transmitter output is connected to a spectrum analyzer:
   RBW = 1kHz.
   VBW = 3 times the RBW.
   The fc is declaring of channel frequency. Then the frequency error formula is (fc-f)/fc * 10^6 ppm and the limit is less than ± 100ppm.
3. Measure and record the results in the test report.

Test Setup

Refer to section 2.6.1- Setup 2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix.**

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

4.5 In-Band Emissions

Limits

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

Test Procedure

ANSI C63.10:2020 Section 6.4.7

Test Settings

1. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 SAC camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And find the worst-case axis positioning record in the report.
3. For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for Quasi-peak detection measurements in the 30~1000MHz range, 9kHz for Peak and/or Quasi-peak detection measurements in the 150kHz~30MHz range and 200Hz for Peak and/or Quasi-peak detection measurements in the 9~150kHz range, Peak detection is used unless otherwise noted as Quasi-peak or average(9~90kHz and 110~490kHz).
4. Measurements were performed at 3m and the data was extrapolated to the specified measurement distance of 30m using the square of an inverse linear distance extrapolation factor (40dB/decade) as specified in &15.31(f)(2). Extrapolation Factor $20\log_{10}(30/3)^2$=40dB.
5. Measure and record the results in the test report.

Test Setup

Refer to section 2.6.2- Setup 1 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix.**

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

4.6 Radiated Spurious Emissions

Limits

The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

Frequency	Field strength (μV/m)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

Test Procedure

ANSI C63.10:2020 Section 6.5.4.

Test Settings

1. For radiated emissions measurements performed at frequencies less than or equal to 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 80cm above the reference ground plane.
2. Radiated measurements shall be made with the measurement antenna positioned in both horizontal and vertical polarization. The measurement antenna shall be varied from 1m to 4m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level (i.e, field strength or received power), when orienting the measurement antenna in vertical polarization, the minimum height of the lowest element of the antenna shall clear the site reference ground plane by at least 25cm.
3. For each suspected emission, the EUT was ranged its worst case and then tune the antenna tower(from 1~4m) and turntable(from 0~360°) find the maximum reading. Preamplifier and a high pass filter are used for the test in order get better signal level comply with the guidelines.
4. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. spectrum analyzer setting:
   Measurements Below 30MHz: RBW = 9 kHz; VBW ≥ 30 kHz; Detector = Peak
   Measurements 30 ~ 1000MHz: RBW = 120 kHz; VBW ≥ 300 kHz; Detector = Peak
7. The field strength is calculated by adding the Antenna Factor, Cable Factor. The basic equation with a sample calculation is as follows:
   Level = Reading(dBμV) + AF(dB/m) + Factor(dB):
   AF = Antenna Factor(dB/m)
   Factor = Cable Factor(dB) - Preamplifier gain(dB)
   Margin = Limit(dBμV/m) – Level(dBμV/m)
8. Repeat above procedures until all frequencies measured was complete.
9. Measure and record the results in the test report.

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Test Notes

1. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported for frequency range below 1GHz.
2. All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance. The extrapolation factor for the limits were 40*Log (test distance /specification distance).
3. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Test Setup

Refer to section 2.6.2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix.**

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

5 Test Setup Photos

The detailed test data see: **Appendix-A NFC Setup Photos**

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Appendix

20dB Bandwidth

Test Result

TestMode	Frequency[MHz]	20dB EBW[kHz]	Limit[MHz]	Verdict
Type-A	13.56	2.705	---	---
Type-B	13.56	2.698	---	---
Type-F	13.56	2.700	---	---
Type-V	13.56	2.696	---	---

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Test Graphs

Type-A

Type-B

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Type-F

Type-V

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Frequency Stability

Test Result

Voltage											
Type	VDC	(℃)	Startup	Deviation	2mins	Deviation	5mins	Deviation	10mins	Deviation	Limit
			(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(ppm)
V	4.28	20	13.55994	-4.42	13.56009	6.64	13.55999	-0.74	13.55998	-1.47	±100
	3.5	20	13.55999	-0.74	13.55999	-0.74	13.55999	-0.74	13.55998	-1.47	±100

Temperature											
Type	VDC	(℃)	Startup	Deviation	2mins	Deviation	5mins	Deviation	10mins	Deviation	Limit
			(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(MHz)	(ppm)	(ppm)
V	3.89	50	13.55999	-0.74	13.55997	-2.21	13.55998	-1.47	13.55997	-2.21	±100
	3.89	40	13.56	0.00	13.55997	-2.21	13.55997	-2.21	13.55997	-2.21	±100
	3.89	30	13.55998	-1.47	13.55997	-2.21	13.55997	-2.21	13.55997	-2.21	±100
	3.89	20	13.55997	-2.21	13.55997	-2.21	13.55997	-2.21	13.55997	-2.21	±100
	3.89	10	13.55998	-1.47	13.55997	-2.21	13.55997	-2.21	13.55997	-2.21	±100
	3.89	0	13.55997	-2.21	13.55997	-2.21	13.55997	-2.21	13.55998	-1.47	±100
	3.89	-10	13.55997	-2.21	13.55997	-2.21	13.55999	-0.74	13.55998	-1.47	±100
	3.89	-20	13.55999	-0.74	13.55998	-1.47	13.55997	-2.21	13.55998	-1.47	±100

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

In-Band Emissions

Test Result

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type A Polarity: Y		

Test Graph



Data List@3m								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.97	18.76	21.13	39.89	69.54	29.65	Horizontal	PASS
2	13.29	18.76	21.10	39.86	80.51	40.65	Horizontal	PASS
3	13.48	18.51	21.08	39.59	90.47	50.88	Horizontal	PASS
4	13.56	33.97	21.08	55.05	124.00	68.95	Horizontal	PASS
5	13.69	18.23	21.07	39.30	90.47	51.17	Horizontal	PASS
6	13.94	18.99	21.05	40.04	80.51	40.47	Horizontal	PASS
7	14.19	19.43	21.02	40.45	69.54	29.09	Horizontal	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.97	39.89	40	-0.11	29.54	29.65	Horizontal	PASS
2	13.29	39.86	40	-0.14	40.51	40.65	Horizontal	PASS
3	13.48	39.59	40	-0.41	50.47	50.88	Horizontal	PASS
4	13.56	55.05	40	15.05	84.00	68.95	Horizontal	PASS
5	13.69	39.30	40	-0.7	50.47	51.17	Horizontal	PASS
6	13.94	40.04	40	0.04	40.50	40.47	Horizontal	PASS
7	14.19	40.45	40	0.45	29.54	29.09	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type A Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.68	18.97	21.15	40.12	69.54	29.42	Vertical	PASS
2	13.30	19.34	21.10	40.44	80.51	40.07	Vertical	PASS
3	13.44	18.86	21.09	39.95	90.47	50.52	Vertical	PASS
4	13.56	29.80	21.08	50.88	124.00	73.12	Vertical	PASS
5	13.67	19.17	21.07	40.24	90.47	50.23	Vertical	PASS
6	13.92	20.07	21.05	41.12	80.51	39.39	Vertical	PASS
7	14.75	20.47	20.97	41.44	69.54	28.10	Vertical	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m

NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.68	40.12	40	0.12	29.54	29.42	Vertical	PASS
2	13.30	40.44	40	0.44	40.51	40.07	Vertical	PASS
3	13.44	39.95	40	-0.05	50.47	50.52	Vertical	PASS
4	13.56	50.88	40	10.88	84.00	73.12	Vertical	PASS
5	13.67	40.24	40	0.24	50.47	50.23	Vertical	PASS
6	13.92	41.12	40	1.12	40.50	39.39	Vertical	PASS
7	14.75	41.44	40	1.44	29.54	28.10	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth	-	Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type F Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.31	19.14	21.15	40.29	69.54	29.25	Horizontal	PASS
2	13.25	18.95	21.11	40.06	80.51	40.45	Horizontal	PASS
3	13.44	19.71	21.09	40.80	90.47	49.67	Horizontal	PASS
4	13.56	33.05	21.08	54.13	124.00	69.87	Horizontal	PASS
5	13.69	19.59	21.07	40.66	90.47	49.81	Horizontal	PASS
6	13.94	18.99	21.05	40.04	80.51	40.47	Horizontal	PASS
7	14.59	20.14	20.99	41.13	69.54	28.41	Horizontal	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m

NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.31	40.29	40	0.29	29.54	29.25	Horizontal	PASS
2	13.25	40.06	40	0.06	40.51	40.45	Horizontal	PASS
3	13.44	40.80	40	0.8	50.47	49.67	Horizontal	PASS
4	13.56	54.13	40	14.13	84.00	69.87	Horizontal	PASS
5	13.69	40.66	40	0.66	50.47	49.81	Horizontal	PASS
6	13.94	40.04	40	0.04	40.50	40.47	Horizontal	PASS
7	14.59	41.13	40	1.13	29.54	28.41	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth	-	Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type F Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.20	19.66	21.16	40.82	69.54	28.72	Vertical	PASS
2	13.36	18.95	21.09	40.04	80.51	40.47	Vertical	PASS
3	13.46	18.62	21.08	39.70	90.47	50.77	Vertical	PASS
4	13.56	26.90	21.08	47.98	124.00	76.02	Vertical	PASS
5	13.57	18.79	21.08	39.87	90.47	50.60	Vertical	PASS
6	13.79	19.71	21.06	40.77	80.51	39.74	Vertical	PASS
7	14.30	19.76	21.01	40.77	69.54	28.77	Vertical	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m

NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.20	40.82	40	0.82	29.54	28.72	Vertical	PASS
2	13.36	40.04	40	0.04	40.51	40.47	Vertical	PASS
3	13.46	39.70	40	-0.3	50.47	50.77	Vertical	PASS
4	13.56	47.98	40	7.98	84.00	76.02	Vertical	PASS
5	13.57	39.87	40	-0.13	50.47	50.60	Vertical	PASS
6	13.79	40.77	40	0.77	40.50	39.74	Vertical	PASS
7	14.30	40.77	40	0.77	29.54	28.77	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth	-	Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.67	20.37	21.15	41.52	69.54	28.02	Horizontal	PASS
2	13.21	19.48	21.11	40.59	80.51	39.92	Horizontal	PASS
3	13.45	19.20	21.09	40.29	90.47	50.18	Horizontal	PASS
4	13.56	32.13	21.08	53.21	124.00	70.79	Horizontal	PASS
5	13.65	18.90	21.08	39.98	90.47	50.49	Horizontal	PASS
6	13.75	19.48	21.06	40.54	80.51	39.97	Horizontal	PASS
7	14.79	21.11	20.97	42.08	69.54	27.46	Horizontal	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m

NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.67	41.52	40	1.52	29.54	28.02	Horizontal	PASS
2	13.21	40.59	40	0.59	40.51	39.92	Horizontal	PASS
3	13.45	40.29	40	0.29	50.47	50.18	Horizontal	PASS
4	13.56	53.21	40	13.21	84.00	70.79	Horizontal	PASS
5	13.65	39.98	40	-0.02	50.47	50.49	Horizontal	PASS
6	13.75	40.54	40	0.54	40.50	39.97	Horizontal	PASS
7	14.79	42.08	40	2.08	29.54	27.46	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth	-	Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.18	20.57	21.16	41.73	69.54	27.81	Vertical	PASS
2	13.19	18.59	21.11	39.70	80.51	40.81	Vertical	PASS
3	13.45	19.40	21.08	40.48	90.47	49.99	Vertical	PASS
4	13.56	26.99	21.08	48.07	124.00	75.93	Vertical	PASS
5	13.61	18.73	21.08	39.81	90.47	50.66	Vertical	PASS
6	13.93	18.57	21.05	39.62	80.51	40.89	Vertical	PASS
7	14.72	19.18	20.98	40.16	69.54	29.38	Vertical	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m

NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.18	41.73	40	1.73	29.54	27.81	Vertical	PASS
2	13.19	39.70	40	-0.3	40.51	40.81	Vertical	PASS
3	13.45	40.48	40	0.48	50.47	49.99	Vertical	PASS
4	13.56	48.07	40	8.07	84.00	75.93	Vertical	PASS
5	13.61	39.81	40	-0.19	50.47	50.66	Vertical	PASS
6	13.93	39.62	40	-0.38	40.50	40.89	Vertical	PASS
7	14.72	40.16	40	0.16	29.54	29.38	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth	-	Channel	-
SN:	HQ652D0092	Engineer:	欧树炎
Remark:	NFC Type 5V Tag Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.80	19.44	21.14	40.58	69.54	28.96	Horizontal	PASS
2	13.34	18.89	21.10	39.99	80.51	40.52	Horizontal	PASS
3	13.47	18.97	21.08	40.05	90.47	50.42	Horizontal	PASS
4	13.56	30.93	21.08	52.01	124.00	71.99	Horizontal	PASS
5	13.67	19.78	21.07	40.85	90.47	49.62	Horizontal	PASS
6	13.96	19.46	21.04	40.50	80.51	40.01	Horizontal	PASS
7	14.47	20.34	20.99	41.33	69.54	28.21	Horizontal	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m

NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	12.80	40.58	40	0.58	29.54	28.96	Horizontal	PASS
2	13.34	39.99	40	-0.01	40.51	40.52	Horizontal	PASS
3	13.47	40.05	40	0.05	50.47	50.42	Horizontal	PASS
4	13.56	52.01	40	12.01	84.00	71.99	Horizontal	PASS
5	13.67	40.85	40	0.85	50.47	49.62	Horizontal	PASS
6	13.96	40.50	40	0.50	40.51	40.01	Horizontal	PASS
7	14.47	41.33	40	1.33	29.54	28.21	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth	-	Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type V Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	11.92	20.42	21.17	41.59	69.54	27.95	Vertical	PASS
2	13.15	20.08	21.11	41.19	80.51	39.32	Vertical	PASS
3	13.43	19.19	21.09	40.28	90.47	50.19	Vertical	PASS
4	13.56	26.01	21.08	47.09	124.00	76.91	Vertical	PASS
5	13.65	18.76	21.08	39.84	90.47	50.63	Vertical	PASS
6	13.89	19.22	21.05	40.27	80.51	40.24	Vertical	PASS
7	14.53	19.64	21.00	40.64	69.54	28.90	Vertical	PASS

Extrapolated the level(@3m) to 30 meters, Extrapolation Factor $20\log_{10}(30/3)^2$=40dB:

Data List@30m

NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Level@30m [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	11.92	41.59	40	1.59	29.54	27.95	Vertical	PASS
2	13.15	41.19	40	1.19	40.51	39.32	Vertical	PASS
3	13.43	40.28	40	0.28	50.47	50.19	Vertical	PASS
4	13.56	47.09	40	7.09	84.00	76.91	Vertical	PASS
5	13.65	39.84	40	-0.16	50.47	50.63	Vertical	PASS
6	13.89	40.27	40	0.27	40.50	40.24	Vertical	PASS
7	14.53	40.64	40	0.64	29.54	28.90	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Radiated Spurious Emissions

Test Result

9kHz ~ 30MHz

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type A Polarity: Y		

Test Graph



Data List@3m								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	27.61	20.67	48.28	121.57	73.29	Horizontal	PASS
2	0.04	21.37	20.67	42.04	115.50	73.46	Horizontal	PASS
3	0.07	19.53	20.64	40.17	110.60	70.43	Horizontal	PASS
4	0.13	12.91	20.86	33.77	105.30	71.53	Horizontal	PASS
5	0.71	30.81	20.96	51.77	70.61	18.84	Horizontal	PASS
6	13.56	34.30	21.08	55.38	-	-	Horizontal	NA
7	25.52	18.40	21.43	39.83	69.54	29.71	Horizontal	PASS

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	48.28	80	-31.72	41.57	73.29	Horizontal	PASS
2	0.04	42.04	80	-37.96	35.5	73.46	Horizontal	PASS
3	0.07	40.17	80	-39.83	30.6	70.43	Horizontal	PASS
4	0.13	33.77	80	-46.23	25.3	71.53	Horizontal	PASS
5	0.71	51.77	40	11.77	30.61	18.84	Horizontal	PASS
6	13.56	55.38	40	15.38	-	-	Horizontal	PASS
7	25.52	39.83	40	-0.17	29.54	29.71	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

:

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type A Polarity: Y		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.01	28.83	20.70	49.53	127.90	78.37	Vertical	PASS
2	0.02	25.15	20.67	45.82	121.57	75.75	Vertical	PASS
3	0.03	19.13	20.65	39.78	117.00	77.22	Vertical	PASS
4	0.06	16.53	20.65	37.18	111.79	74.61	Vertical	PASS
5	0.07	16.89	20.64	37.53	110.59	73.06	Vertical	PASS
6	0.71	31.19	20.96	52.15	70.61	18.46	Vertical	PASS
7	13.56	30.59	21.08	51.67	-	-	Vertical	NA

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.01	49.53	80	-30.47	47.90	78.37	Vertical	PASS
2	0.02	45.82	80	-34.18	41.57	75.75	Vertical	PASS
3	0.03	39.78	80	-40.22	37.00	77.22	Vertical	PASS
4	0.06	37.18	80	-42.82	31.79	74.61	Vertical	PASS
5	0.07	37.53	80	-42.47	30.59	73.06	Vertical	PASS
6	0.71	52.15	40	12.15	30.61	18.46	Vertical	PASS
7	13.56	51.67	40	11.67	-	-	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	26.40	20.67	47.07	121.62	74.55	Horizontal	PASS
2	0.04	19.42	20.67	40.09	115.62	75.53	Horizontal	PASS
3	0.07	20.58	20.64	41.22	110.60	69.38	Horizontal	PASS
4	0.70	30.58	20.95	51.53	70.68	19.15	Horizontal	PASS
5	0.81	25.16	20.97	46.13	69.42	23.29	Horizontal	PASS
6	1.11	21.26	21.01	42.27	66.69	24.42	Horizontal	PASS
7	13.56	34.23	21.08	55.31	-	-	Horizontal	NA

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	47.07	80	-32.93	41.62	74.55	Horizontal	PASS
2	0.04	40.09	80	-39.91	35.62	75.53	Horizontal	PASS
3	0.07	41.22	80	-38.78	30.60	69.38	Horizontal	PASS
4	0.70	51.53	40	11.53	30.68	19.15	Horizontal	PASS
5	0.81	46.13	40	6.13	29.42	23.29	Horizontal	PASS
6	1.11	42.27	40	2.27	26.69	24.42	Horizontal	PASS
7	13.56	55.31	40	15.31	-	-	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	25.87	20.67	46.54	121.58	75.04	Vertical	PASS
2	0.04	19.19	20.66	39.85	116.53	76.68	Vertical	PASS
3	0.07	17.85	20.64	38.49	110.60	72.11	Vertical	PASS
4	0.71	30.24	20.96	51.20	70.65	19.45	Vertical	PASS
5	0.81	24.97	20.97	45.94	69.45	23.51	Vertical	PASS
6	1.19	21.28	21.01	42.29	66.15	23.86	Vertical	PASS
7	13.56	31.87	21.08	52.95	-	-	Vertical	NA

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	46.54	80	-33.46	41.58	75.04	Vertical	PASS
2	0.04	39.85	80	-40.15	36.53	76.68	Vertical	PASS
3	0.07	38.49	80	-41.51	30.60	72.11	Vertical	PASS
4	0.71	51.20	40	11.2	30.65	19.45	Vertical	PASS
5	0.81	45.94	40	5.94	29.45	23.51	Vertical	PASS
6	1.19	42.29	40	2.29	26.15	23.86	Vertical	PASS
7	13.56	52.95	40	12.95	-	-	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type F Polarity: Y		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	27.40	20.67	48.07	121.63	73.56	Horizontal	PASS
2	0.07	19.20	20.64	39.84	110.60	70.76	Horizontal	PASS
3	0.14	13.45	20.87	34.32	104.88	70.56	Horizontal	PASS
4	0.71	30.48	20.96	51.44	70.65	19.21	Horizontal	PASS
5	0.82	23.81	20.98	44.79	69.35	24.56	Horizontal	PASS
6	13.56	32.28	21.08	53.36	-	-	Horizontal	NA
7	25.42	19.06	21.43	40.49	69.54	29.05	Horizontal	PASS

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	48.07	80	-31.93	41.63	73.56	Horizontal	PASS
2	0.07	39.84	80	-40.16	30.60	70.76	Horizontal	PASS
3	0.14	34.32	80	-45.68	24.88	70.56	Horizontal	PASS
4	0.71	51.44	40	11.44	30.65	19.21	Horizontal	PASS
5	0.82	44.79	40	4.79	29.35	24.56	Horizontal	PASS
6	13.56	53.36	40	13.36	-	-	Horizontal	PASS
7	25.42	40.49	40	0.49	29.54	29.05	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type F Polarity: Y		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.01	27.28	20.69	47.97	125.57	77.60	Vertical	PASS
2	0.02	25.52	20.67	46.19	121.57	75.38	Vertical	PASS
3	0.06	17.78	20.65	38.43	111.79	73.36	Vertical	PASS
4	0.71	31.70	20.96	52.66	70.61	17.95	Vertical	PASS
5	0.76	25.57	20.96	46.53	70.04	23.51	Vertical	PASS
6	5.56	21.86	21.10	42.96	69.54	26.58	Vertical	PASS
7	13.56	31.63	21.08	52.71	-	-	Vertical	NA

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.01	47.97	80	-32.03	45.57	77.60	Vertical	PASS
2	0.02	46.19	80	-33.81	41.57	75.38	Vertical	PASS
3	0.06	38.43	80	-41.57	31.79	73.36	Vertical	PASS
4	0.71	52.66	40	12.66	30.61	17.95	Vertical	PASS
5	0.76	46.53	40	6.53	30.04	23.51	Vertical	PASS
6	5.56	42.96	40	2.96	29.54	26.58	Vertical	PASS
7	13.56	52.71	40	12.71	-	-	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type V Polarity: Y		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	25.67	20.67	46.34	121.59	75.25	Horizontal	PASS
2	0.07	20.96	20.64	41.60	110.60	69.00	Horizontal	PASS
3	0.13	14.35	20.86	35.21	105.30	70.09	Horizontal	PASS
4	0.71	30.80	20.96	51.76	70.57	18.81	Horizontal	PASS
5	0.75	25.19	20.96	46.15	70.08	23.93	Horizontal	PASS
6	13.56	33.97	21.08	55.05	-	-	Horizontal	NA
7	20.30	19.45	20.96	40.41	69.54	29.13	Horizontal	PASS

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	46.34	80	-33.66	41.59	75.25	Horizontal	PASS
2	0.07	41.60	80	-38.4	30.60	69.00	Horizontal	PASS
3	0.13	35.21	80	-44.79	25.30	70.09	Horizontal	PASS
4	0.71	51.76	40	11.76	30.57	18.81	Horizontal	PASS
5	0.75	46.15	40	6.15	30.08	23.93	Horizontal	PASS
6	13.56	55.05	40	15.05	-	-	Horizontal	PASS
7	20.30	40.41	40	0.41	29.54	29.13	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Band:	-
Bandwidth		Channel	-
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type V Polarity: Y		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	26.53	20.67	47.20	121.60	74.40	Vertical	PASS
2	0.07	16.23	20.63	36.86	111.00	74.14	Vertical	PASS
3	0.13	10.18	20.87	31.05	105.03	73.98	Vertical	PASS
4	0.71	30.44	20.96	51.40	70.57	19.17	Vertical	PASS
5	0.82	24.24	20.97	45.21	69.39	24.18	Vertical	PASS
6	8.88	20.00	21.09	41.09	69.54	28.45	Vertical	PASS
7	13.56	36.20	21.08	57.28	-	-	Vertical	NA

The measured data was extrapolated from the test distance (3m) to the specification distance:

Data List@ specification distance								
NO.	Freq. [MHz]	Level@3m [dBµV/m]	Dist. Corr. Factor [dB]	Corrected Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	0.02	47.20	80	-32.80	41.60	74.40	Vertical	PASS
2	0.07	36.86	80	-43.14	31.00	74.14	Vertical	PASS
3	0.13	31.05	80	-48.95	25.03	73.98	Vertical	PASS
4	0.71	51.40	40	11.40	30.57	19.17	Vertical	PASS
5	0.82	45.21	40	5.210	29.39	24.18	Vertical	PASS
6	8.88	41.09	40	1.09	29.54	28.45	Vertical	PASS
7	13.56	57.28	40	17.28	-	-	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

FCC ID: PY7-63277Y (Lead Model)

30MHz ~ 1000MHz

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type V Polarity: Y		

Start of test:2025-04-20 14:47:21

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	67.78	51.80	-25.49	26.31	40.00	13.69	Horizontal	PASS
2	94.89	49.10	-24.97	24.13	43.50	19.37	Horizontal	PASS
3	149.16	52.38	-26.38	26.00	43.50	17.50	Horizontal	PASS
4	159.50	51.22	-25.77	25.45	43.50	18.05	Horizontal	PASS
5	176.28	57.41	-25.00	32.41	43.50	11.09	Horizontal	PASS
6	284.77	55.61	-21.13	34.48	46.00	11.52	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type V Polarity: Y		

Start of test:2025-04-20 14:50:11

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	42.85	47.49	-22.82	24.67	40.00	15.33	Vertical	PASS
2	51.63	48.23	-23.32	24.91	40.00	15.09	Vertical	PASS
3	66.67	45.15	-24.81	20.34	40.00	19.66	Vertical	PASS
4	104.45	46.88	-24.24	22.64	43.50	20.86	Vertical	PASS
5	159.98	49.15	-25.64	23.51	43.50	19.99	Vertical	PASS
6	185.49	45.31	-24.39	20.92	43.50	22.58	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type F Polarity: Y		

Start of test:2025-04-20 14:54:55

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	40.67	42.85	-23.84	19.01	40.00	20.99	Horizontal	PASS
2	54.54	41.79	-23.03	18.76	40.00	21.24	Horizontal	PASS
3	67.78	44.83	-25.49	19.34	40.00	20.66	Horizontal	PASS
4	100.18	46.29	-23.96	22.33	43.50	21.17	Horizontal	PASS
5	159.06	50.96	-25.89	25.07	43.50	18.43	Horizontal	PASS
6	176.28	52.98	-25.00	27.98	43.50	15.52	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type F Polarity: Y		

Start of test:2025-04-20 14:57:47

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	35.58	49.06	-25.02	24.04	40.00	15.96	Vertical	PASS
2	43.39	48.42	-22.77	25.65	40.00	14.35	Vertical	PASS
3	50.76	47.80	-23.40	24.40	40.00	15.60	Vertical	PASS
4	66.67	46.44	-24.81	21.63	40.00	18.37	Vertical	PASS
5	104.35	44.44	-24.26	20.18	43.50	23.32	Vertical	PASS
6	159.69	48.48	-25.69	22.79	43.50	20.71	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Start of test:2025-04-20 15:02:10

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	50.32	40.53	-22.41	18.12	40.00	21.88	Horizontal	PASS
2	67.78	52.40	-25.49	26.91	40.00	13.09	Horizontal	PASS
3	102.22	43.76	-23.78	19.98	43.50	23.52	Horizontal	PASS
4	149.16	48.40	-26.38	22.02	43.50	21.48	Horizontal	PASS
5	160.37	50.98	-25.80	25.18	43.50	18.32	Horizontal	PASS
6	203.39	46.37	-23.99	22.38	43.50	21.12	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Start of test:2025-04-20 15:05:01

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	43.00	47.04	-22.70	24.34	40.00	15.66	Vertical	PASS
2	51.24	47.95	-23.62	24.33	40.00	15.67	Vertical	PASS
3	67.78	59.08	-25.16	33.92	40.00	6.08	Vertical	PASS
4	97.61	44.41	-24.66	19.75	43.50	23.75	Vertical	PASS
5	126.22	44.55	-26.38	18.17	43.50	25.33	Vertical	PASS
6	159.83	47.68	-25.67	22.01	43.50	21.49	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type A Polarity: Y		

Start of test:2025-04-20 15:10:02

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	40.67	44.45	-23.84	20.61	40.00	19.39	Horizontal	PASS
2	54.69	41.49	-22.94	18.55	40.00	21.45	Horizontal	PASS
3	67.78	46.59	-25.49	21.10	40.00	18.90	Horizontal	PASS
4	99.99	43.89	-23.86	20.03	43.50	23.47	Horizontal	PASS
5	149.75	46.46	-26.23	20.23	43.50	23.27	Horizontal	PASS
6	161.53	50.93	-26.06	24.87	43.50	18.63	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652D0109	Engineer:	Ou Shuyan
Remark:	Type A Polarity: Y		

Start of test:2025-04-20 15:12:51

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	34.41	48.79	-24.97	23.82	40.00	16.18	Vertical	PASS
2	42.90	48.18	-22.79	25.39	40.00	14.61	Vertical	PASS
3	49.98	47.80	-22.18	25.62	40.00	14.38	Vertical	PASS
4	67.78	50.15	-25.16	24.99	40.00	15.01	Vertical	PASS
5	104.69	46.54	-24.19	22.35	43.50	21.15	Vertical	PASS
6	159.16	48.83	-25.77	23.06	43.50	20.44	Vertical	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Test for spot check:

FCC ID: PY7-29686W (This Model)

Test Result

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652G0040	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	40.67	42.08	-23.84	18.24	40.00	21.76	Horizontal	PASS
2	67.78	51.14	-25.49	25.65	40.00	14.35	Horizontal	PASS
3	80.93	43.80	-25.91	17.89	40.00	22.11	Horizontal	PASS
4	110.66	46.26	-23.32	22.94	43.50	20.56	Horizontal	PASS
5	183.75	52.49	-24.91	27.58	43.50	15.92	Horizontal	PASS
6	726.99	41.53	-11.92	29.61	47.00	17.39	Horizontal	PASS

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.

Project Information			
Mode:	NFC	Voltage:	120V/60Hz
SN:	HQ652G0040	Engineer:	Ou Shuyan
Remark:	Type B Polarity: Y		

Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBuV]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Verdict
1	46.78	49.09	-23.26	25.83	40.00	14.17	Vertical	PASS
2	67.78	57.34	-25.16	32.18	40.00	7.82	Vertical	PASS
3	81.02	46.17	-25.70	20.47	40.00	19.53	Vertical	PASS
4	143.98	46.44	-25.47	20.97	43.50	22.53	Vertical	PASS
5	212.02	45.45	-24.13	21.32	43.50	22.18	Vertical	PASS
6	727.19	40.22	-12.11	28.11	47.00	18.89	Vertical	PASS

~The End~

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from TOWE.