FCC RADIO TEST REPORT

FCC ID	:	**PY7-52715J**
Equipment	:	**GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac/ax, NFC and GNSS**
Brand Name	:	**Sony**
Applicant	:	**Sony Corporation 1-7-1 Konan, Minato-ku , Tokyo, Japan 108-0075**
Manufacturer	:	**Sony Corporation 1-7-1 Konan, Minato-ku , Tokyo, Japan 108-0075**
Standard	:	**FCC Part 15 Subpart C §15.247**

The product was received on Feb. 03, 2026 and testing was performed from Mar. 05, 2026 to May 26, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory
No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 Number of Channel Measurement 11
3.2 Hopping Channel Separation Measurement 12
3.3 Dwell Time Measurement 13
3.4 20dB and 99% Bandwidth Measurement 14
3.5 Output Power Measurement 15
3.6 Conducted Band Edges Measurement 16
3.7 Conducted Spurious Emission Measurement 17
3.8 Radiated Band Edges and Spurious Emission Measurement 18
3.9 AC Conducted Emission Measurement 22
3.10 Antenna Requirements 24
4 List of Measuring Equipment **25**
5 Measurement Uncertainty **27**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission Test Result
Appendix D. Duty Cycle Plots
Appendix E. Spot Check Evaluation on PY7-52715J

History of this test report

Report No.	Version	Description	Issue Date
FR620306A	01	Initial issue of report	Jun. 29, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	See Note
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	See Note
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	See Note
3.4	15.247(a)(1)	20dB Bandwidth	Pass	See Note
3.4	2.1049	99% Occupied Bandwidth	Pass	See Note
3.5	15.247(b)(1) 15.247(b)(4)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	See Note
3.7	15.247(d)	Conducted Spurious Emission	Pass	See Note
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	6.42 dB under the limit at 44.55 MHz
3.9	15.207	AC Conducted Emission	Pass	8.93 dB under the limit at 1.06 MHz
3.10	15.203	Antenna Requirement	Pass	-

Note:

1. ECR inquiry for data referencing from FCC ID: PY7-75158T has been approved by TCB. The ECR inquiry and the associated document are submitted in the confidential exhibit.
2. The only difference between FCC ID: PY7-75158T and FCC ID: PY7-52715J are Cellular Support Band & RF Circuit.
3. For Radiated is Full test,All the conducted test results are referenced from FCC ID: PY7-75158T (Sporton Test Report FR620304A), and spot check conducted power results to justify data referencing is presented in the Appendix E.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Aya Yang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Specification subject to this standard	
General Specs	GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC and BDS/Galileo/GLONASS/GPS.
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth:PIFA Antenna GPS / Glonass / BDS / Galileo: PIFA Antenna NFC : LOOP Antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	**<Ant. 6>**: -1.9 **<Ant. 7>**: -1.3

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

EUT Information List			
HW Version	**SW Version**	**S/N**	**Performed Test Item**
A	0.27	SOBBBAG0AWD0001D	RF Conducted Measurement
		SOBBBAG0AWC00073	Radiated Spurious Emission
		SOBBBAG0AWC0008E	Conducted Emission

Specification of Accessory		
AC Adapter	**Brand Name**	Sony
	Model Name	XQZ-UC1
Earphone	**Brand Name**	Sony
	Model Name	MDR-EX15AP
USB Cable 1	**Brand Name**	Sony
	Model Name	XQZ-UB1
USB Cable 2	**Brand Name**	Sony
	Model Name	UCB20

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- FCC Part 15 Subpart C §15.247
- ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst plane, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	**Data Rate / Modulation**		
Conducted Test Cases	**Bluetooth BR 1Mbps GFSK**	**Bluetooth EDR 2Mbps π/4-DQPSK**	**Bluetooth EDR 3Mbps 8-DPSK**
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
AC Conducted Emission	Mode 1 :BT Link + WLAN 2.4G Link + MPEG4 + USB Cable + Adapter + Earphone		
Remark: 1. The detailed Radiated test modes are shown in Appendix C.			

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	SonyErricsson	MW600	PY700A2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
3.	Earphone	Sony	MDR-EX15AP	N/A	UnShielded, 1.2m	N/A
4.	Notebook	Dell	Latitude 3420	FCC DoC	N/A	AC I/P：Unshielded, 1.2m DC O/P：Shielded, 1.8m
5.	Notebook	Dell	Latitude 3400	N/A	N/A	AC I/P：Unshielded, 1.2m DC O/P：Shielded, 1.8m

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT Version 4.0.181.1” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.
Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10 clause 7.8.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300 kHz; VBW ≥ RBW; Sweep = No faster than coupled (auto) time; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10 clause 7.8.2.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peaks of two adjacent channels;
   RBW = 300 kHz; VBW ≥ RBW; Sweep = No faster than coupled (auto) time; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10 clause 7.8.4.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

.

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10 clause 6.9.2 and 6.9.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Use the following spectrum analyzer settings for 20 dB Bandwidth measurement.
   Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
   RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ 3 * RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
   Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
   RBW ≥ 1-5% of the 99% bandwidth, VBW ≥ 3 * RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB Bandwidth

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi.

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10 clause 7.8.5.
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10 clause 6.10.
2. Set the maximum power setting and enable the EUT to transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2 and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.7.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10 clause 7.8.7.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurious must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

Please refer to FCC ID: PY7-75158T (Sporton Test Report FR620304A)

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics / spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.8.3 Test Procedures

1. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
2. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT is arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW = 100 kHz for f < 1 GHz, RBW = 1 MHz for f>1 GHz ; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
   (3) For average measurement: use duty cycle correction factor method per 15.35(c).
   Duty cycle = On time/100 milliseconds
   On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$
   Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
   Average Emission Level = Peak Emission Level + 20*log (Duty cycle)
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as "-".
8. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as "-".

Note: The average levels are calculated from the peak level corrected with duty cycle correction factor (-24.82dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup

For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site **v01r01**, and the result comes out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Duty Cycle

Please refer to Appendix D.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.9.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.9.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.10 Antenna Requirements

3.10.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.10.2 Antenna Anti-Replacement Construction

Antenna permanently attached.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Mar. 26. 2026	Nov. 03, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Nov. 12, 2025	Mar. 26. 2026	Nov. 11, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900067 (BOX7)	N/A	Jul. 02, 2025	Mar. 26. 2026	Jul. 01, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Mar. 26. 2026	N/A	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Mar. 26. 2026	Nov. 13, 2026	Conducted (TH05-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 05, 2026	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 05, 2026	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2025	Mar. 05, 2026	Oct. 19, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 2, 2026	Mar. 05, 2026	Mar. 1, 2027	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Mar. 05, 2026	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Oct. 21, 2025	Mar. 05, 2026	Oct. 20, 2026	Conduction (CO07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Apr. 09, 2026~ May 26, 2026	Dec. 10, 2026	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	37059 & 01	30MHz~1GHz	Nov. 26, 2025	Apr. 09, 2026~ May 26, 2026	Nov. 25, 2026	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-02114	1GHz~18GHz	Jul. 02, 2025	Apr. 09, 2026~ May 26, 2026	Jul. 01, 2026	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1223	18GHz-40GHz	Jul. 02, 2025	Apr. 09, 2026~ May 26, 2026	Jul. 01, 2026	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 18, 2026	Apr. 09, 2026~ May 26, 2026	Mar. 17, 2027	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	Feb. 06, 2026	Apr. 09, 2026~ May 26, 2026	Feb. 05, 2027	Radiation (03CH12-HY)
Amplifier	EMCI	EMC051845SE	980729	1GHz-18GHz	Dec. 17, 2025	Apr. 09, 2026~ May 26, 2026	Dec. 16, 2026	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 02, 2025	Apr. 09, 2026~ May 26, 2026	Dec. 01, 2026	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Sep. 09, 2025	Apr. 09, 2026~ May 26, 2026	Sep. 08, 2026	Radiation (03CH12-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz~26.5GHz	Sep. 08, 2025	Apr. 09, 2026~ May 26, 2026	Sep. 07, 2026	Radiation (03CH12-HY)
Notch Filter	Wainwright	WHKX8-5872.5-6750-18000-40ST	SN2	6.75GHz High Pass Filter	Mar. 11, 2026	Apr. 09, 2026~ May 26, 2026	Mar. 10, 2027	Radiation (03CH12-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Notch Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN2	3GHz High Pass Filter	Mar. 11, 2026	Apr. 09, 2026~ May 26, 2026	Mar. 10, 2027	Radiation (03CH12-HY)
Notch Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN111	1.53GHz Low Pass Filter	Nov. 04, 2025	Apr. 09, 2026~ May 26, 2026	Nov. 03, 2026	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803955/2	30MHz~40GHz	Oct. 31, 2025	Apr. 09, 2026~ May 26, 2026	Oct. 30, 2026	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Oct. 31, 2025	Apr. 09, 2026~ May 26, 2026	Oct. 30, 2026	Radiation (03CH12-HY)
RF Cable	EMCI	EMC101Y-KM-KM-1000	240905	30MHz~40GHz	Oct. 31, 2025	Apr. 09, 2026~ May 26, 2026	Oct. 30, 2026	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP210090	N/A	Aug. 26, 2025	Apr. 09, 2026~ May 26, 2026	Aug. 25, 2026	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Apr. 09, 2026~ May 26, 2026	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Apr. 09, 2026~ May 26, 2026	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Apr. 09, 2026~ May 26, 2026	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Apr. 09, 2026~ May 26, 2026	N/A	Radiation (03CH12-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.70 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.50 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90 dB

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.70 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90 dB

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Hank Hsu	Temperature:	21~25	°C
Test Date:	2026/3/26	Relative Humidity:	51~54	%

<ANT 6>

TEST RESULTS DATA
Peak Power Table

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	14.00	20.97	Pass
	39	1	14.00	20.97	Pass
	78	1	**14.10**	20.97	Pass
2DH1	0	1	**16.30**	20.97	Pass
	39	1	16.10	20.97	Pass
	78	1	**16.30**	20.97	Pass
3DH1	0	1	**16.90**	20.97	Pass
	39	1	16.60	20.97	Pass
	78	1	16.80	20.97	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)	Duty Factor (dB)
DH1	0	1	12.90	5.14	10.00
	39	1	12.80	5.14	
	78	1	**13.10**	5.14	
2DH1	0	1	**13.70**	5.07	10.00
	39	1	13.50	5.07	
	78	1	**13.70**	5.07	
3DH1	0	1	13.50	5.07	10.00
	39	1	13.50	5.07	
	78	1	**13.70**	5.07	

<ANT 7>

TEST RESULTS DATA
Peak Power Table

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	**13.50**	20.97	Pass
	39	1	13.40	20.97	Pass
	78	1	13.00	20.97	Pass
2DH1	0	1	15.30	20.97	Pass
	39	1	**15.60**	20.97	Pass
	78	1	15.30	20.97	Pass
3DH1	0	1	15.70	20.97	Pass
	39	1	**16.20**	20.97	Pass
	78	1	15.50	20.97	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)	Duty Factor (dB)
DH1	0	1	12.10	5.16	10.00
	39	1	**12.30**	5.16	
	78	1	12.10	5.16	
2DH1	0	1	12.70	5.06	10.00
	39	1	**13.00**	5.06	
	78	1	12.60	5.06	
3DH1	0	1	12.70	5.08	10.00
	39	1	**13.00**	5.08	
	78	1	12.60	5.08	

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Brian Chen	**Temperature :**	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO :	620306
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	31.22	55.75	24.53	L1	ON	20.1
0.154500	53.56	---	65.75	12.19	L1	ON	20.1
0.170250	---	33.15	54.95	21.80	L1	ON	20.1
0.170250	53.90	---	64.95	11.05	L1	ON	20.1
0.188250	---	27.61	54.11	26.50	L1	ON	20.1
0.188250	53.48	---	64.11	10.63	L1	ON	20.1
0.206250	---	31.14	53.36	22.22	L1	ON	20.1
0.206250	51.35	---	63.36	12.01	L1	ON	20.1
0.226500	---	22.81	52.58	29.77	L1	ON	20.1
0.226500	46.75	---	62.58	15.83	L1	ON	20.1
0.244500	---	25.85	51.94	26.09	L1	ON	20.1
0.244500	44.80	---	61.94	17.14	L1	ON	20.1
0.271500	---	21.95	51.07	29.12	L1	ON	20.1
0.271500	47.89	---	61.07	13.18	L1	ON	20.1
0.300750	---	21.29	50.22	28.93	L1	ON	20.0
0.300750	41.30	---	60.22	18.92	L1	ON	20.0
0.343500	---	19.27	49.12	29.85	L1	ON	20.0
0.343500	40.21	---	59.12	18.91	L1	ON	20.0
0.379500	---	20.24	48.29	28.05	L1	ON	20.0

0.379500	38.83	---	58.29	19.46	L1	ON	20.0
0.420000	---	19.59	47.45	27.86	L1	ON	20.0
0.420000	39.35	---	57.45	18.10	L1	ON	20.0
0.462750	---	17.61	46.64	29.03	L1	ON	20.0
0.462750	35.41	---	56.64	21.23	L1	ON	20.0
0.512250	---	15.41	46.00	30.59	L1	ON	20.0
0.512250	35.56	---	56.00	20.44	L1	ON	20.0
0.550500	---	15.36	46.00	30.64	L1	ON	20.0
0.550500	33.27	---	56.00	22.73	L1	ON	20.0
0.588750	---	17.68	46.00	28.32	L1	ON	20.0
0.588750	35.10	---	56.00	20.90	L1	ON	20.0
0.645000	---	14.97	46.00	31.03	L1	ON	20.0
0.645000	30.53	---	56.00	25.47	L1	ON	20.0
1.063500	---	31.32	46.00	14.68	L1	ON	20.0
1.063500	37.51	---	56.00	18.49	L1	ON	20.0
1.740750	---	20.62	46.00	25.38	L1	ON	20.0
1.740750	35.92	---	56.00	20.08	L1	ON	20.0
18.627000	---	18.81	50.00	31.19	L1	ON	20.8
18.627000	26.04	---	60.00	33.96	L1	ON	20.8

EUT Information

Report NO :	620306
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	34.24	55.88	21.64	N	ON	20.1
0.152250	53.55	---	65.88	12.33	N	ON	20.1
0.159000	---	32.40	55.52	23.12	N	ON	20.1
0.159000	51.73	---	65.52	13.79	N	ON	20.1
0.170250	---	26.61	54.95	28.34	N	ON	20.1
0.170250	51.80	---	64.95	13.15	N	ON	20.1
0.181500	---	25.83	54.42	28.59	N	ON	20.1
0.181500	52.02	---	64.42	12.40	N	ON	20.1
0.190500	---	28.63	54.02	25.39	N	ON	20.1
0.190500	46.64	---	64.02	17.38	N	ON	20.1
0.201750	---	25.90	53.54	27.64	N	ON	20.1
0.201750	46.14	---	63.54	17.40	N	ON	20.1
0.219750	---	22.39	52.83	30.44	N	ON	20.1
0.219750	48.08	---	62.83	14.75	N	ON	20.1
0.242250	---	23.29	52.02	28.73	N	ON	20.1
0.242250	48.87	---	62.02	13.15	N	ON	20.1
0.255750	---	19.78	51.57	31.79	N	ON	20.1
0.255750	43.58	---	61.57	17.99	N	ON	20.1
0.285000	---	20.73	50.67	29.94	N	ON	20.0

0.285000	44.28	---	60.67	16.39	N	ON	20.0
0.312000	---	22.89	49.92	27.03	N	ON	20.0
0.312000	43.52	---	59.92	16.40	N	ON	20.0
0.343500	---	19.04	49.12	30.08	N	ON	20.0
0.343500	37.69	---	59.12	21.43	N	ON	20.0
0.377250	---	17.70	48.34	30.64	N	ON	20.0
0.377250	39.05	---	58.34	19.29	N	ON	20.0
0.417750	---	16.67	47.49	30.82	N	ON	20.0
0.417750	36.33	---	57.49	21.16	N	ON	20.0
0.440250	---	16.11	47.06	30.95	N	ON	20.0
0.440250	30.66	---	57.06	26.40	N	ON	20.0
0.492000	---	15.05	46.13	31.08	N	ON	20.0
0.492000	34.01	---	56.13	22.12	N	ON	20.0
0.557250	---	15.99	46.00	30.01	N	ON	20.0
0.557250	32.19	---	56.00	23.81	N	ON	20.0
0.633750	---	15.70	46.00	30.30	N	ON	20.0
0.633750	25.65	---	56.00	30.35	N	ON	20.0
1.061250	---	37.07	46.00	8.93	N	ON	20.0
1.061250	41.32	---	56.00	14.68	N	ON	20.0
1.765500	---	19.44	46.00	26.56	N	ON	20.0
1.765500	33.60	---	56.00	22.40	N	ON	20.0
18.156750	---	20.81	50.00	29.19	N	ON	20.8
18.156750	25.85	---	60.00	34.15	N	ON	20.8

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Gerry Wei, Tim Lee and Wilson Wu	**Temperature :**	21.8 ~ 23.4 °C
		Relative Humidity :	50.5 ~ 60.7 %

Note symbol

-L	**Low channel location**
-R	**High channel location**

C1.Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	6	Bluetooth BR_FHSS	00	2402	1 Mbps	-	-
Mode 2	2400-2483.5	6	Bluetooth BR_FHSS	39	2441	1 Mbps	-	-
Mode 3	2400-2483.5	6	Bluetooth BR_FHSS	78	2480	1 Mbps	-	-
Mode 4	2400-2483.5	6	Bluetooth BR_FHSS	00	2402	2 Mbps	-	-
Mode 5	2400-2483.5	6	Bluetooth BR_FHSS	39	2441	2 Mbps	-	-
Mode 6	2400-2483.5	6	Bluetooth BR_FHSS	78	2480	2 Mbps	-	-
Mode 7	2400-2483.5	6	Bluetooth BR_FHSS	00	2402	3 Mbps	-	-
Mode 8	2400-2483.5	6	Bluetooth BR_FHSS	39	2441	3 Mbps	-	-
Mode 9	2400-2483.5	6	Bluetooth BR_FHSS	78	2480	3 Mbps	-	-
Mode 10	2400-2483.5	6	Bluetooth BR_FHSS	78	2480	3 Mbps	-	LF
Mode 11	2400-2483.5	6	Bluetooth BR_FHSS	78	2480	3 Mbps	-	SHF

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 12	2400-2483.5	7	Bluetooth BR_FHSS	00	2402	1 Mbps	-	-
Mode 13	2400-2483.5	7	Bluetooth BR_FHSS	39	2441	1 Mbps	-	-
Mode 14	2400-2483.5	7	Bluetooth BR_FHSS	78	2480	1 Mbps	-	-
Mode 15	2400-2483.5	7	Bluetooth BR_FHSS	00	2402	2 Mbps	-	-
Mode 16	2400-2483.5	7	Bluetooth BR_FHSS	39	2441	2 Mbps	-	-
Mode 17	2400-2483.5	7	Bluetooth BR_FHSS	78	2480	2 Mbps	-	-
Mode 18	2400-2483.5	7	Bluetooth BR_FHSS	00	2402	3 Mbps	-	-
Mode 19	2400-2483.5	7	Bluetooth BR_FHSS	39	2441	3 Mbps	-	-
Mode 20	2400-2483.5	7	Bluetooth BR_FHSS	78	2480	3 Mbps	-	-
Mode 21	2400-2483.5	7	Bluetooth BR_FHSS	39	2441	3 Mbps	-	LF
Mode 22	2400-2483.5	7	Bluetooth BR_FHSS	39	2441	3 Mbps	-	SHF

C2.Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Bluetooth BR_FHSS	00	2389.21	46.64	74.00	-27.36	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	00	4804.00	42.83	74.00	-31.17	H	Peak	Pass	-	Harmonic
2	Bluetooth BR_FHSS	39	2497.29	46.66	74.00	-27.34	H	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	39	7323.00	45.22	74.00	-28.78	V	Peak	Pass	-	Harmonic
3	Bluetooth BR_FHSS	78	2483.64	49.91	74.00	-24.09	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	78	7440.00	44.96	74.00	-29.04	V	Peak	Pass	-	Harmonic
4	Bluetooth BR_FHSS	00	2389.58	45.49	74.00	-28.51	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	00	4804.00	41.38	74.00	-32.62	V	Peak	Pass	-	Harmonic
5	Bluetooth BR_FHSS	39	2490.74	45.13	74.00	-28.87	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	39	7323.00	45.92	74.00	-28.08	V	Peak	Pass	-	Harmonic
6	Bluetooth BR_FHSS	78	2483.72	49.57	74.00	-24.43	V	Peak	Pass	-	Band Edge

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
6	Bluetooth BR_FHSS	78	7440.00	45.51	74.00	-28.49	V	Peak	Pass	-	Harmonic
7	Bluetooth BR_FHSS	00	2388.94	45.86	74.00	-28.14	H	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	00	4804.00	42.68	74.00	-31.32	V	Peak	Pass	-	Harmonic
8	Bluetooth BR_FHSS	39	2494.93	45.06	74.00	-28.94	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	39	7323.00	45.30	74.00	-28.70	V	Peak	Pass	-	Harmonic
9	Bluetooth BR_FHSS	78	2483.54	50.19	74.00	-23.81	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	78	7440.00	43.72	74.00	-30.28	H	Peak	Pass	-	Harmonic
10	LF	78	43.58	33.52	40.00	-6.48	V	Peak	Pass	-	LF
11	SHF	78	25816.00	40.23	74.00	-33.77	V	Peak	Pass	-	SHF
12	Bluetooth BR_FHSS	00	2310.18	51.88	74.00	-22.12	H	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	00	4804.00	42.05	74.00	-31.95	V	Peak	Pass	-	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
13	Bluetooth BR_FHSS	39	2496.99	45.38	74.00	-28.62	H	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	39	7323.00	45.96	74.00	-28.04	H	Peak	Pass	-	Harmonic
14	Bluetooth BR_FHSS	78	2483.54	48.91	74.00	-25.09	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	78	7440.00	45.18	74.00	-28.82	H	Peak	Pass	-	Harmonic
15	Bluetooth BR_FHSS	00	2389.76	51.58	74.00	-22.42	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	00	4804.00	42.89	74.00	-31.11	H	Peak	Pass	-	Harmonic
16	Bluetooth BR_FHSS	39	2388.60	51.83	74.00	-22.17	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	39	7323.00	45.43	74.00	-28.57	H	Peak	Pass	-	Harmonic
17	Bluetooth BR_FHSS	78	2483.60	51.15	74.00	-22.85	H	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	78	7440.00	45.10	74.00	-28.90	V	Peak	Pass	-	Harmonic
18	Bluetooth BR_FHSS	00	2388.75	47.47	74.00	-26.53	V	Peak	Pass	-	Band Edge

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
18	Bluetooth BR_FHSS	00	4804.00	41.86	74.00	-32.14	V	Peak	Pass	-	Harmonic
19	Bluetooth BR_FHSS	39	2389.91	52.59	74.00	-21.41	V	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	39	7323.00	45.54	74.00	-28.46	V	Peak	Pass	-	Harmonic
20	Bluetooth BR_FHSS	78	2483.54	45.70	74.00	-28.30	H	Peak	Pass	-	Band Edge
	Bluetooth BR_FHSS	78	7440.00	44.70	74.00	-29.30	V	Peak	Pass	-	Harmonic
21	LF	39	44.55	33.58	40.00	-6.42	V	Peak	Pass	-	LF
22	SHF	39	25704.00	40.35	74.00	-33.65	H	Peak	Pass	-	SHF

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2322.97 44.54 74.00 -29.46 44.71 27.40 6.68 34.25 0.00 206 307 Peak 2 2322.97 19.72 54.00 -34.28 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 103.83 ------ ------ 103.81 27.40 6.80 34.18 0.00 206 307 Peak 2 2402.00 79.01 ------ ------ -- -- -- -- -- -- -- Average

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.21 46.64 74.00 -27.36 46.66 27.39 6.78 34.19 0.00 238 247 Peak 2 2389.21 21.82 54.00 -32.18 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 103.58 ------ ------ 103.56 27.40 6.80 34.18 0.00 238 247 Peak 2 2402.00 78.76 ------ ------ -- -- -- -- -- -- -- Average

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 42.83 74.00 -31.17 54.13 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 18.01 54.00 -35.99 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 42.62 74.00 -31.38 53.92 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 17.80 54.00 -36.20 -- -- -- -- -- -- -- Average

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	2	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2319.69 43.97 74.00 -30.03 44.16 27.40 6.67 34.26 0.00 276 323 Peak 2 2319.69 19.15 54.00 -34.85 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 103.04 ------ ------ 102.70 27.62 6.86 34.14 0.00 276 323 Peak 2 2441.00 78.22 ------ ------ -- -- -- -- -- -- -- Average

Mode	2	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2497.29 46.66 74.00 -27.34 45.72 28.07 6.95 34.08 0.00 276 323 Peak 2 2497.29 21.84 54.00 -32.16 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	2	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.73 44.33 74.00 -29.67 44.35 27.39 6.78 34.19 0.00 200 249 Peak 2 2388.73 19.51 54.00 -34.49 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 103.27 ------ ------ 102.93 27.62 6.86 34.14 0.00 200 249 Peak 2 2441.00 78.45 ------ ------ -- -- -- -- -- -- -- Average

Mode	2	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2498.70 44.99 74.00 -29.01 44.03 28.09 6.95 34.08 0.00 200 249 Peak 2 2498.70 20.17 54.00 -33.83 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 41.69 74.00 -32.31 52.72 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 16.87 54.00 -37.13 -- -- -- -- -- -- -- Average 3 7323.00 44.56 74.00 -29.44 50.11 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 19.74 54.00 -34.26 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 41.46 74.00 -32.54 52.49 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 16.64 54.00 -37.36 -- -- -- -- -- -- -- Average 3 7323.00 45.22 74.00 -28.78 50.77 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.40 54.00 -33.60 -- -- -- -- -- -- -- Average

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.56 49.72 74.00 -24.28 48.95 27.94 6.93 34.10 0.00 213 320 Peak 2 2483.56 24.90 54.00 -29.10 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 103.15 ------ ------ 102.43 27.90 6.92 34.10 0.00 213 320 Peak 2 2480.00 78.33 ------ ------ -- -- -- -- -- -- -- Average

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.64 49.91 74.00 -24.09 49.14 27.94 6.93 34.10 0.00 252 258 Peak 2 2483.64 25.09 54.00 -28.91 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 104.05 ------ ------ 103.33 27.90 6.92 34.10 0.00 252 258 Peak 2 2480.00 79.23 ------ ------ -- -- -- -- -- -- -- Average

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.71 74.00 -32.29 52.43 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 16.89 54.00 -37.11 -- -- -- -- -- -- -- Average 3 7440.00 44.36 74.00 -29.64 50.18 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 19.54 54.00 -34.46 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.78 74.00 -32.22 52.50 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 16.96 54.00 -37.04 -- -- -- -- -- -- -- Average 3 7440.00 44.96 74.00 -29.04 50.78 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 20.14 54.00 -33.86 -- -- -- -- -- -- -- Average

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.49 45.21 74.00 -28.79 45.23 27.39 6.78 34.19 0.00 205 325 Peak 2 2389.49 20.39 54.00 -33.61 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 106.15 ------ ------ 106.13 27.40 6.80 34.18 0.00 205 325 Peak 2 2402.00 81.33 ------ ------ -- -- -- -- -- -- -- Average

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.58 45.49 74.00 -28.51 45.50 27.40 6.78 34.19 0.00 238 250 Peak 2 2389.58 20.67 54.00 -33.33 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 105.96 ------ ------ 105.94 27.40 6.80 34.18 0.00 238 250 Peak 2 2402.00 81.14 ------ ------ -- -- -- -- -- -- -- Average

Mode	4	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 40.71 74.00 -33.29 52.01 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 15.89 54.00 -38.11 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 41.38 74.00 -32.62 52.68 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 16.56 54.00 -37.44 -- -- -- -- -- -- -- Average

Mode	4	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	5	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2342.10 44.47 74.00 -29.53 44.59 27.40 6.71 34.23 0.00 273 323 Peak 2 2342.10 19.65 54.00 -34.35 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 105.31 ------ ------ 104.97 27.62 6.86 34.14 0.00 273 323 Peak 2 2441.00 80.49 ------ ------ -- -- -- -- -- -- -- Average

Mode	5	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2499.65 44.63 74.00 -29.37 43.66 28.10 6.95 34.08 0.00 273 323 Peak 2 2499.65 19.81 54.00 -34.19 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	5	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.78 44.71 74.00 -29.29 44.72 27.40 6.78 34.19 0.00 200 252 Peak 2 2389.78 19.89 54.00 -34.11 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 105.34 ------ ------ 105.00 27.62 6.86 34.14 0.00 200 252 Peak 2 2441.00 80.52 ------ ------ -- -- -- -- -- -- -- Average

Mode	5	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2490.74 45.13 74.00 -28.87 44.27 28.01 6.94 34.09 0.00 200 252 Peak 2 2490.74 20.31 54.00 -33.69 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	5	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 42.51 74.00 -31.49 53.54 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 17.69 54.00 -36.31 -- -- -- -- -- -- -- Average 3 7323.00 45.34 74.00 -28.66 50.89 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.52 54.00 -33.48 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 41.79 74.00 -32.21 52.82 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 16.97 54.00 -37.03 -- -- -- -- -- -- -- Average 3 7323.00 45.92 74.00 -28.08 51.47 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 21.10 54.00 -32.90 -- -- -- -- -- -- -- Average

Mode	5	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.74 49.54 74.00 -24.46 48.77 27.94 6.93 34.10 0.00 210 311 Peak 2 2483.74 24.72 54.00 -29.28 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 105.18 ------ ------ 104.46 27.90 6.92 34.10 0.00 210 311 Peak 2 2480.00 80.36 ------ ------ -- -- -- -- -- -- -- Average

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.72 49.57 74.00 -24.43 48.80 27.94 6.93 34.10 0.00 251 257 Peak 2 2483.72 24.75 54.00 -29.25 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 106.17 ------ ------ 105.45 27.90 6.92 34.10 0.00 251 257 Peak 2 2480.00 81.35 ------ ------ -- -- -- -- -- -- -- Average

Mode	6	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.77 74.00 -32.23 52.49 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 16.95 54.00 -37.05 -- -- -- -- -- -- -- Average 3 7440.00 44.40 74.00 -29.60 50.22 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 19.58 54.00 -34.42 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.83 74.00 -32.17 52.55 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 17.01 54.00 -36.99 -- -- -- -- -- -- -- Average 3 7440.00 45.51 74.00 -28.49 51.33 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 20.69 54.00 -33.31 -- -- -- -- -- -- -- Average

Mode	6	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	7	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.94 45.86 74.00 -28.14 45.88 27.39 6.78 34.19 0.00 204 326 Peak 2 2388.94 21.04 54.00 -32.96 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 106.36 ------ ------ 106.34 27.40 6.80 34.18 0.00 204 326 Peak 2 2402.00 81.54 ------ ------ -- -- -- -- -- -- -- Average

Mode	7	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.66 45.69 74.00 -28.31 45.71 27.39 6.78 34.19 0.00 238 247 Peak 2 2388.66 20.87 54.00 -33.13 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 105.92 ------ ------ 105.90 27.40 6.80 34.18 0.00 238 247 Peak 2 2402.00 81.10 ------ ------ -- -- -- -- -- -- -- Average

Mode	7	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 42.54 74.00 -31.46 53.84 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 17.72 54.00 -36.28 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 42.68 74.00 -31.32 53.98 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 17.86 54.00 -36.14 -- -- -- -- -- -- -- Average

Mode	7	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	8	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2379.30 44.02 74.00 -29.98 44.15 27.30 6.77 34.20 0.00 274 324 Peak 2 2379.30 19.20 54.00 -34.80 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 105.70 ------ ------ 105.36 27.62 6.86 34.14 0.00 274 324 Peak 2 2441.00 80.88 ------ ------ -- -- -- -- -- -- -- Average

Mode	8	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2487.02 44.54 74.00 -29.46 43.73 27.97 6.93 34.09 0.00 274 324 Peak 2 2487.02 19.72 54.00 -34.28 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	8	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.73 44.47 74.00 -29.53 44.49 27.39 6.78 34.19 0.00 201 248 Peak 2 2388.73 19.65 54.00 -34.35 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 105.64 ------ ------ 105.30 27.62 6.86 34.14 0.00 201 248 Peak 2 2441.00 80.82 ------ ------ -- -- -- -- -- -- -- Average

Mode	8	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2494.93 45.06 74.00 -28.94 44.15 28.05 6.94 34.08 0.00 201 248 Peak 2 2494.93 20.24 54.00 -33.76 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	8	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 41.32 74.00 -32.68 52.35 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 16.50 54.00 -37.50 -- -- -- -- -- -- -- Average 3 7323.00 45.08 74.00 -28.92 50.63 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.26 54.00 -33.74 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 41.99 74.00 -32.01 53.02 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 17.17 54.00 -36.83 -- -- -- -- -- -- -- Average 3 7323.00 45.30 74.00 -28.70 50.85 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.48 54.00 -33.52 -- -- -- -- -- -- -- Average

Mode	8	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	9	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.60 49.39 74.00 -24.61 48.62 27.94 6.93 34.10 0.00 210 310 Peak 2 2483.60 24.57 54.00 -29.43 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 105.50 ------ ------ 104.78 27.90 6.92 34.10 0.00 210 310 Peak 2 2480.00 80.68 ------ ------ -- -- -- -- -- -- -- Average

Mode	9	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.54 50.19 74.00 -23.81 49.42 27.94 6.93 34.10 0.00 253 259 Peak 2 2483.54 25.37 54.00 -28.63 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 106.31 ------ ------ 105.59 27.90 6.92 34.10 0.00 253 259 Peak 2 2480.00 81.49 ------ ------ -- -- -- -- -- -- -- Average

Mode	9	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.77 74.00 -32.23 52.49 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 16.95 54.00 -37.05 -- -- -- -- -- -- -- Average 3 7440.00 43.72 74.00 -30.28 49.54 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 18.90 54.00 -35.10 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.70 74.00 -32.30 52.42 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 16.88 54.00 -37.12 -- -- -- -- -- -- -- Average 3 7440.00 43.61 74.00 -30.39 49.43 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 18.79 54.00 -35.21 -- -- -- -- -- -- -- Average

Mode	9	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg		
17.7G ~18G Avg		

Mode	10	
	LF	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
QP/ Peak		

Site : 03CH12-HY
Condition: QP 3m Bilog_37059 & 01_251126 HORIZONTAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	36.79	29.74	40.00	-10.26	38.02	21.13	0.70	30.16	0.05	--	--	Peak
2	103.72	29.62	43.50	-13.88	41.93	16.47	1.27	30.14	0.09	--	--	Peak
3	217.21	21.28	46.00	-24.72	34.28	14.96	1.90	29.98	0.12	--	--	Peak
4	491.72	38.69	46.00	-7.31	41.06	23.93	2.96	29.45	0.19	--	--	Peak
5	743.92	38.79	46.00	-7.21	35.68	28.25	3.70	29.07	0.23	--	--	Peak
6	840.92	38.95	46.00	-7.05	34.75	28.97	3.85	28.84	0.22	--	--	Peak

Site : 03CH12-HY
Condition: QP 3m Bilog_37059 & 01_251126 VERTICAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	43.58	33.52	40.00	-6.48	45.15	17.69	0.80	30.19	0.07	--	--	Peak
2	91.11	34.63	43.50	-8.87	48.39	15.13	1.18	30.16	0.09	--	--	Peak
3	240.49	21.81	46.00	-24.19	32.17	17.44	2.02	29.95	0.13	--	--	Peak
4	515.00	37.34	46.00	-8.66	39.31	24.21	3.03	29.41	0.20	--	--	Peak
5	739.07	38.78	46.00	-7.22	35.79	28.15	3.69	29.08	0.23	--	--	Peak
6	840.92	39.10	46.00	-6.90	34.90	28.97	3.85	28.84	0.22	--	--	Peak

Mode	11	
	SHF	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition: PEAK_74 1m BBHA9170_1223_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 25848.00 39.69 74.00 -34.31 39.76 39.11 23.49 53.13 -9.54 -- -- Peak	 Site : 03CH12-HY Condition: PEAK_74 1m BBHA9170_1223_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 25816.00 40.23 74.00 -33.77 40.19 39.24 23.48 53.14 -9.54 -- -- Peak

Mode	12	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2310.18 51.88 74.00 -22.12 52.09 27.40 6.66 34.27 0.00 100 120 Peak 2 2310.18 27.09 54.00 -26.91 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 99.47 ------ ------ 99.45 27.40 6.80 34.18 0.00 100 120 Peak 2 2402.00 74.68 ------ ------ -- -- -- -- -- -- -- Average

Mode	12	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.86 47.98 74.00 -26.02 47.99 27.40 6.78 34.19 0.00 100 343 Peak 2 2389.86 23.19 54.00 -30.81 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 101.90 ------ ------ 101.88 27.40 6.80 34.18 0.00 100 343 Peak 2 2402.00 77.11 ------ ------ -- -- -- -- -- -- -- Average

Mode	12	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 41.96 74.00 -32.04 53.26 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 17.17 54.00 -36.83 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 42.05 74.00 -31.95 53.35 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 17.26 54.00 -36.74 -- -- -- -- -- -- -- Average

Mode	12	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	13	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.86 45.03 74.00 -28.97 45.05 27.39 6.78 34.19 0.00 115 122 Peak 2 2388.86 20.24 54.00 -33.76 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 99.19 ------ ------ 98.85 27.62 6.86 34.14 0.00 115 122 Peak 2 2441.00 74.40 ------ ------ -- -- -- -- -- -- -- Average

Mode	13	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2496.99 45.38 74.00 -28.62 44.44 28.07 6.95 34.08 0.00 115 122 Peak 2 2496.99 20.59 54.00 -33.41 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	13	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2313.41 43.78 74.00 -30.22 43.98 27.40 6.66 34.26 0.00 105 66 Peak 2 2313.41 18.99 54.00 -35.01 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 101.93 ------ ------ 101.59 27.62 6.86 34.14 0.00 105 66 Peak 2 2441.00 77.14 ------ ------ -- -- -- -- -- -- -- Average

Mode	13	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2489.50 45.14 74.00 -28.86 44.31 27.99 6.93 34.09 0.00 105 66 Peak 2 2489.50 20.35 54.00 -33.65 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	13	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 42.09 74.00 -31.91 53.12 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 17.30 54.00 -36.70 -- -- -- -- -- -- -- Average 3 7323.00 45.96 74.00 -28.04 51.51 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 21.17 54.00 -32.83 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 42.17 74.00 -31.83 53.20 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 17.38 54.00 -36.62 -- -- -- -- -- -- -- Average 3 7323.00 45.03 74.00 -28.97 50.58 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.24 54.00 -33.76 -- -- -- -- -- -- -- Average

Mode	13	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	14	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.56 47.23 74.00 -26.77 46.46 27.94 6.93 34.10 0.00 100 126 Peak 2 2483.56 22.44 54.00 -31.56 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 100.34 ------ ------ 99.62 27.90 6.92 34.10 0.00 100 126 Peak 2 2480.00 75.55 ------ ------ -- -- -- -- -- -- -- Average

Mode	14	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.54 48.91 74.00 -25.09 48.14 27.94 6.93 34.10 0.00 262 93 Peak 2 2483.54 24.12 54.00 -29.88 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 102.35 ------ ------ 101.63 27.90 6.92 34.10 0.00 262 93 Peak 2 2480.00 77.56 ------ ------ -- -- -- -- -- -- -- Average

Mode	14	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 43.73 74.00 -30.27 54.45 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 18.94 54.00 -35.06 -- -- -- -- -- -- -- Average 3 7440.00 45.18 74.00 -28.82 51.00 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 20.39 54.00 -33.61 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.67 74.00 -31.33 53.39 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 17.88 54.00 -36.12 -- -- -- -- -- -- -- Average 3 7440.00 45.16 74.00 -28.84 50.98 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 20.37 54.00 -33.63 -- -- -- -- -- -- -- Average

Mode	14	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	15	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.86 46.41 74.00 -27.59 46.42 27.40 6.78 34.19 0.00 394 28 Peak 2 2389.86 21.62 54.00 -32.38 21.63 27.40 6.78 34.19 0.00 394 28 Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 96.66 ------ ------ 96.64 27.40 6.80 34.18 0.00 394 28 Peak 2 2402.00 71.87 ------ ------ 71.85 27.40 6.80 34.18 0.00 394 28 Average

Mode	15	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.76 51.58 74.00 -22.42 51.59 27.40 6.78 34.19 0.00 161 104 Peak 2 2389.76 26.79 54.00 -27.21 26.80 27.40 6.78 34.19 0.00 161 104 Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 100.07 ------ ------ 100.05 27.40 6.80 34.18 0.00 161 104 Peak 2 2402.00 75.28 ------ ------ 75.26 27.40 6.80 34.18 0.00 161 104 Average

Mode	15	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 42.89 74.00 -31.11 54.19 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 18.10 54.00 -35.90 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 41.97 74.00 -32.03 53.27 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 17.18 54.00 -36.82 -- -- -- -- -- -- -- Average

Mode	15	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	16	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.73 43.93 74.00 -30.07 43.95 27.39 6.78 34.19 0.00 381 39 Peak 2 2388.73 19.14 54.00 -34.86 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 98.95 ------ ------ 98.61 27.62 6.86 34.14 0.00 381 39 Peak 2 2441.00 74.16 ------ ------ -- -- -- -- -- -- -- Average

Mode	16	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2484.19 44.93 74.00 -29.07 44.16 27.94 6.93 34.10 0.00 381 39 Peak 2 2484.19 20.14 54.00 -33.86 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	16	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.60 51.83 74.00 -22.17 51.85 27.39 6.78 34.19 0.00 157 104 Peak 2 2388.60 27.04 54.00 -26.96 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 101.52 ------ ------ 101.18 27.62 6.86 34.14 0.00 157 104 Peak 2 2441.00 76.73 ------ ------ -- -- -- -- -- -- -- Average

Mode	16	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2498.64 45.19 74.00 -28.81 44.23 28.09 6.95 34.08 0.00 157 104 Peak 2 2498.64 20.40 54.00 -33.60 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	16	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 41.77 74.00 -32.23 52.80 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 16.98 54.00 -37.02 -- -- -- -- -- -- -- Average 3 7323.00 45.43 74.00 -28.57 50.98 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.64 54.00 -33.36 -- -- -- -- -- -- -- Average	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 41.97 74.00 -32.03 53.00 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 17.18 54.00 -36.82 -- -- -- -- -- -- -- AVERAGE 3 7323.00 44.98 75.00 -30.02 50.53 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.19 54.00 -33.81 -- -- -- -- -- -- -- Average

Mode	16	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	17	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.60 51.15 74.00 -22.85 50.38 27.94 6.93 34.10 0.00 278 68 Peak 2 2483.60 26.36 54.00 -27.64 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 107.82 ------ ------ 107.10 27.90 6.92 34.10 0.00 278 68 Peak 2 2480.00 83.03 ------ ------ -- -- -- -- -- -- -- Average

Mode	17	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 48.89 74.00 -25.11 48.12 27.94 6.93 34.10 0.00 100 68 Peak 2 2483.52 24.10 54.00 -29.90 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 104.81 ------ ------ 104.09 27.90 6.92 34.10 0.00 100 68 Peak 2 2480.00 80.02 ------ ------ -- -- -- -- -- -- -- Average

Mode	17	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.88 74.00 -31.12 53.60 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 18.09 54.00 -35.91 -- -- -- -- -- -- -- AVERAGE 3 7440.00 44.72 74.00 -29.28 50.54 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 19.93 54.00 -34.07 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.63 74.00 -31.37 53.35 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 17.84 54.00 -36.16 -- -- -- -- -- -- -- AVERAGE 3 7440.00 45.10 74.00 -28.90 50.92 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 20.31 54.00 -33.69 -- -- -- -- -- -- -- AVERAGE

Mode	17	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	18	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.75 46.61 74.00 -27.39 46.63 27.39 6.78 34.19 0.00 395 28 Peak 2 2388.75 21.82 54.00 -32.18 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 96.80 ------ ------ 96.78 27.40 6.80 34.18 0.00 395 28 Peak 2 2402.00 72.01 ------ ------ -- -- -- -- -- -- -- Average

Mode	18	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.75 47.47 74.00 -26.53 47.49 27.39 6.78 34.19 0.00 100 313 Peak 2 2388.75 22.68 54.00 -31.32 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 99.43 ------ ------ 99.41 27.40 6.80 34.18 0.00 100 313 Peak 2 2402.00 74.64 ------ ------ -- -- -- -- -- -- -- Average

Mode	18	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 41.75 74.00 -32.25 53.05 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 16.96 54.00 -37.04 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 41.86 74.00 -32.14 53.16 32.32 11.61 55.85 0.62 -- -- Peak 2 4804.00 17.07 54.00 -36.93 -- -- -- -- -- -- -- AVERAGE

Mode	18	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH00_2402MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	19	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.12 48.46 74.00 -25.54 48.48 27.39 6.78 34.19 0.00 378 28 Peak 2 2389.12 23.67 54.00 -30.33 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 98.55 ------ ------ 98.21 27.62 6.86 34.14 0.00 378 28 Peak 2 2441.00 73.76 ------ ------ -- -- -- -- -- -- -- Average

Mode	19	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2489.26 44.58 74.00 -29.42 43.75 27.99 6.93 34.09 0.00 378 28 Peak 2 2489.26 19.79 54.00 -34.21 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	19	
	Band Edge - L	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.91 52.59 74.00 -21.41 52.60 27.40 6.78 34.19 0.00 131 107 Peak 2 2389.91 27.80 54.00 -26.20 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2441.00 101.32 ------ ------ 100.98 27.62 6.86 34.14 0.00 131 107 Peak 2 2441.00 76.53 ------ ------ -- -- -- -- -- -- -- Average

Mode	19	
	Band Edge - R	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2494.10 44.93 74.00 -29.07 44.04 28.04 6.94 34.09 0.00 131 107 Peak 2 2494.10 20.14 54.00 -33.86 -- -- -- -- -- -- -- AVERAGE	Blank

Mode	19	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 42.56 74.00 -31.44 53.59 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 17.77 54.00 -36.23 -- -- -- -- -- -- -- AVERAGE 3 7323.00 45.19 74.00 -28.81 50.74 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.40 54.00 -33.60 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4882.00 42.18 74.00 -31.82 53.21 32.86 11.39 55.88 0.60 -- -- Peak 2 4882.00 17.39 54.00 -36.61 -- -- -- -- -- -- -- AVERAGE 3 7323.00 45.54 74.00 -28.46 51.09 37.10 13.40 56.45 0.40 -- -- Peak 4 7323.00 20.75 54.00 -33.25 -- -- -- -- -- -- -- AVERAGE

Mode	19	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	20	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.54 45.70 74.00 -28.30 44.93 27.94 6.93 34.10 0.00 367 42 Peak 2 2483.54 20.91 54.00 -33.09 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 99.17 ------ ------ 98.45 27.90 6.92 34.10 0.00 367 42 Peak 2 2480.00 74.38 ------ ------ -- -- -- -- -- -- -- Average

Mode	20	
	Band Edge	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition: PEAK_BE_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2492.62 45.26 74.00 -28.74 44.38 28.03 6.94 34.09 0.00 300 96 Peak 2 2492.62 20.47 54.00 -33.53 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 100.16 ------ ------ 99.44 27.90 6.92 34.10 0.00 300 96 Peak 2 2480.00 75.37 ------ ------ -- -- -- -- -- -- -- Average

Mode	20	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.27 74.00 -31.73 52.99 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 17.48 54.00 -36.52 -- -- -- -- -- -- -- AVERAGE 3 7440.00 44.23 75.00 -30.77 50.05 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 19.44 54.00 -34.56 -- -- -- -- -- -- -- AVERAGE	 Site : 03CH12-HY Condition: PEAK_74 3m 9120D-02114-250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.51 74.00 -31.49 53.23 33.44 11.16 55.91 0.59 -- -- Peak 2 4960.00 17.72 54.00 -36.28 -- -- -- -- -- -- -- AVERAGE 3 7440.00 44.70 74.00 -29.30 50.52 36.74 13.51 56.49 0.42 -- -- Peak 4 7440.00 19.91 54.00 -34.09 -- -- -- -- -- -- -- AVERAGE

Mode	20	
	Harmonic	
	2400-2483.5_Bluetooth BR_FHSS_CH78_2480MHz	
ANT	7	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL
17.7G ~18G Avg	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 HORIZONTAL	 Site : 03CH12-HY Condition: AVG_54 3m 9120D-02114-250702 VERTICAL

Mode	21	
	LF	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
QP/ Peak		

Site : 03CH12-HY
Condition: QP 3m Bilog_37059 & 01_251126 HORIZONTAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	36.79	28.09	40.00	-11.91	36.37	21.13	0.70	30.16	0.05	--	--	Peak
2	166.77	27.53	43.50	-15.97	39.75	16.04	1.67	30.05	0.12	--	--	Peak
3	269.59	21.94	46.00	-24.06	30.42	19.14	2.16	29.90	0.12	--	--	Peak
4	515.00	38.00	46.00	-8.00	39.97	24.21	3.03	29.41	0.20	--	--	Peak
5	729.37	38.68	46.00	-7.32	36.13	27.75	3.66	29.10	0.24	--	--	Peak
6	900.09	38.86	46.00	-7.14	34.16	29.09	4.07	28.72	0.26	--	--	Peak

Site : 03CH12-HY
Condition: QP 3m Bilog_37059 & 01_251126 VERTICAL

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	44.55	33.58	40.00	-6.42	45.74	17.15	0.81	30.19	0.07	--	--	Peak
2	91.11	31.28	43.50	-12.22	45.04	15.13	1.18	30.16	0.09	--	--	Peak
3	240.49	20.27	46.00	-25.73	30.63	17.44	2.02	29.95	0.13	--	--	Peak
4	499.48	37.47	46.00	-8.53	39.72	24.01	2.98	29.43	0.19	--	--	Peak
5	740.04	37.99	46.00	-8.01	35.00	28.15	3.69	29.08	0.23	--	--	Peak
6	840.92	37.94	46.00	-8.06	33.74	28.97	3.85	28.84	0.22	--	--	Peak

Mode	22	
	SHF	
	2400-2483.5_Bluetooth BR_FHSS_CH39_2441MHz	
ANT	7	
Pol.	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition: PEAK_74 1m BBHA9170_1223_250702 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 25704.00 40.35 74.00 -33.65 40.44 39.20 23.41 53.16 -9.54 -- -- Peak	 Site : 03CH12-HY Condition: PEAK_74 1m BBHA9170_1223_250702 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 25632.00 40.30 74.00 -33.70 40.41 39.23 23.37 53.17 -9.54 -- -- Peak

Appendix D. Duty Cycle Plots

<ANT 6_1Mbps>

DH5 on time (One Pulse) Plot on Channel 39	on time (Count Pulses) Plot on Channel 39
	

Note:

1. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.87 / 100 = 5.74 %
2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.82 dB
3. **DH5** has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the on time period to have DH5 packet completing one hopping sequence is

2.87 ms x 20 channels = 57.4 ms

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100 ms / 57.4 ms] = 2 hops

Thus, the maximum possible ON time:

2.87 ms x 2 = 5.74 ms

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

20 x log(5.74 ms/100 ms) = -24.82 dB

<ANT 6_2Mbps>

2DH5 on time (One Pulse) Plot on Channel 39	on time (Count Pulses) Plot on Channel 39
	

Note:

4. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.87 / 100 = 5.74 %
5. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.82 dB
6. **2DH5** has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time 2DH5 packet is observed; the on time period to have DH5 packet completing one hopping sequence is

2.87 ms x 20 channels = 57.4 ms

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100 ms / 57.4 ms] = 2 hops

Thus, the maximum possible ON time:

2.87 ms x 2 = 5.74 ms

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

20 x log(5.74 ms/100 ms) = -24.82 dB

<ANT 6_3Mbps>

3DH5 on time (One Pulse) Plot on Channel 39	on time (Count Pulses) Plot on Channel 39
	

Note:

7. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.87 / 100 = 5.74 %
8. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.82 dB
9. **3DH5** has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time 3DH5 packet is observed; the on time period to have DH5 packet completing one hopping sequence is

2.87 ms x 20 channels = 57.4 ms

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100 ms / 57.4 ms] = 2 hops

Thus, the maximum possible ON time:

2.87 ms x 2 = 5.74 ms

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

20 x log(5.74 ms/100 ms) = -24.82 dB