


FCC SAR Test Report

APPLICANT : Sony Mobile Communications Inc.
BRAND NAME : Sony
FCC ID : PY7-57442Z
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Applied.....	5
4. Equipment Under Test (EUT) Information.....	6
4.1 General Information	6
4.2 Device Serial Number	6
4.3 General LTE SAR Test and Reporting Considerations	7
5. RF Exposure Limits.....	9
5.1 Uncontrolled Environment.....	9
5.2 Controlled Environment.....	9
6. Specific Absorption Rate (SAR).....	10
6.1 Introduction	10
6.2 SAR Definition.....	10
7. System Description and Setup	11
7.1 E-Field Probe	12
7.2 Data Acquisition Electronics (DAE)	12
7.3 Phantom.....	13
7.4 Device Holder.....	14
8. Measurement Procedures	15
8.1 Spatial Peak SAR Evaluation.....	15
8.2 Power Reference Measurement.....	16
8.3 Area Scan	16
8.4 Zoom Scan.....	17
8.5 Volume Scan Procedures.....	17
8.6 Power Drift Monitoring.....	17
9. Test Equipment List.....	18
10. System Verification	19
10.1 Tissue Simulating Liquids.....	19
10.2 Tissue Verification	20
10.3 System Performance Check Results.....	22
11. RF Exposure Positions.....	24
11.1 Ear and handset reference point	24
11.2 Definition of the cheek position.....	25
11.3 Definition of the tilt position.....	26
11.4 Body Worn Accessory	27
11.5 Wireless Router.....	27
12. Conducted RF Output Power (Unit: dBm).....	28
13. RF Exposure Conditions	79
14. SAR Test Results	80
14.1 Head SAR	82
14.2 Hotspot SAR	86
14.3 Body Worn Accessory SAR.....	90
14.4 Repeated SAR Measurement	93
15. Simultaneous Transmission Analysis.....	94
15.1 Head Exposure Conditions	95
15.2 Hotspot Exposure Conditions.....	99
15.3 Body-Worn Accessory Exposure Conditions	103
16. Uncertainty Assessment	105
17. References.....	105
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Antenna Location & Test Setup Photos	

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA760712-01	Rev. 01	Initial issue of report	Nov. 10, 2017
FA760712-01	Rev. 02	Updated UE category in section 4.3	Nov. 24, 2017



1. Statement of Compliance

Applicant Name	Sony Mobile Communications Inc.			
EUT Description	GSM/WCDMA/LTE Phone+Bluetooth, DTS/UNII a/b/g/n/ac and NFC			
Brand Name	Sony			
FCC ID	PY7-57442Z			
HW Version	A			
SW Version	1.14			
RF Exposure Conditions	Equipment Class			
	Licensed	DTS	U-NII	DSS
Head (1g SAR W/kg)	0.81	0.73	0.52	0.19
Body-Worn (1g SAR W/kg)	1.07	0.05	0.12	0.01
Wireless Router (1g SAR W/kg)	1.14	0.19		0.05
Highest Simultaneous Transmission (1g SAR W/kg)	Head:1.54 Body-worn:1.12 Hotspot:1.14	Head:1.54 Body-worn:1.12 Hotspot:1.14	Head:1.33 Body-worn:1.08 Hotspot: NA	Head:1.00 Body-worn:1.08 Hotspot:1.14
Date Tested	201710/01 ~ 2017/10/12			
Test Result	Pass			
Remark:				
1. This device 2.4GHz WLAN support Hotspot operation and Bluetooth support tethering applications.				
2. GSM1900, WCDMA B2/B4 and LTE B2/B4/B25/B66 power reduction is activated in hotspot mode.				

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2. Administration Data

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Sony Mobile Communications Inc.
Address	4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

Manufacturer	
Company Name	Sony Mobile Communications Inc.
Address	4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

4. Equipment Under Test (EUT) Information

4.1 General Information

Wireless Technologies	Frequency	Operating Mode	
GSM	850 1900	· GSM Voice · GPRS (GMSK) · EDGE (8PSK)	Multi-Slot Class: Class 33
	Does device support dual transfer mode? (Yes)		
W-CDMA (UMTS)	Band 2 Band 4 Band 5	· AMR / RMC 12.2Kbps · HSDPA · HSUPA · DC-HSDPA	
LTE	Band 2 Band 4 Band 5 Band 7 Band 12 Band 13 Band 17 Band 25 Band 66	· QPSK · 16QAM · 64QAM · Rel 11 Carrier Aggregation Downlink only (Inter-Band and Intra-Band possible combinations please referred to section 12)	
WiFi	2.4GHz: 2412 MHz ~ 2462 MHz	· 11b · 11g · 11n (HT20) · 11ac (VHT20)	
	5GHz: 5.2GHz: 5180 MHz ~ 5240 MHz 5.3GHz: 5260 MHz ~ 5320 MHz 5.5GHz: 5500 MHz ~ 5720 MHz 5.8GHz: 5745 MHz ~ 5825 MHz	· 11a · 11n (HT20) · 11n (HT40) · 11ac (VHT20) · 11ac (VHT40) · 11ac (VHT80)	
Bluetooth	2.4GHz	· BR / EDR / LE	
NFC	13.56MHz	· ASK	

Accessories Information		
Battery 1	Model Name	LIP1654ERPC
	Type	Li-ion
Earphone 1	Model Name	MH410c
	Type Name	AG-1100
Earphone 2	Model Name	MH410c
	Type Name	AG-1103

4.2 Device Serial Number

Band	SN
WWAN	CQ300004QT
WLAN	CQ300003T2

Note: Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

4.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																																										
FCC ID		PY7-57442Z																																																																								
Operating Frequency Range of each LTE transmission band		LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 25: 1850.7 MHz ~ 1914.3 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz																																																																								
Channel Bandwidth		LTE Band 02:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 04:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 05:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 07: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 13: 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz LTE Band 25:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz																																																																								
Uplink modulations used		QPSK / 16QAM / 64QAM																																																																								
UE Category		Cat 11 on DL and Cat 5 on UL																																																																								
LTE Voice / Data requirements		Data only																																																																								
LTE MPR permanently built-in by design		MPR is permanently implemented for this device by the manufacturer.The specific manufacturer target MPR is indicated alongside the SAR power table.MPR is enabled for this device,according to 3GPP TS36.101 Section 6.2.3-6.2.5 under Table 6.2.3-1. <table><tr><th colspan="8">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</th></tr><tr><th rowspan="2">Modulation</th><th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th><th rowspan="2">MPR (dB)</th></tr><tr><th>1.4 MHz</th><th>3.0 MHz</th><th>5 MHz</th><th>10 MHz</th><th>15 MHz</th><th>20 MHz</th></tr><tr><td>QPSK</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 2</td></tr><tr><td>64 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 2</td></tr><tr><td>64 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 3</td></tr><tr><td>256 QAM</td><td colspan="6">≥ 1</td><td>≤ 5</td></tr></table>			Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3								Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3																																																																										
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																																																			
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																																				
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																																			
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																																			
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																																			
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																																			
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																																			
256 QAM	≥ 1						≤ 5																																																																			
LTE A-MPR		In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																																								
Spectrum plots for RB configuration		A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																																								
Power reduction applied to satisfy SAR compliance		Yes, when operating in hotspot mode that LTE B2 / B4 / B25 / B66 power reduction applied to satisfy SAR compliance.																																																																								
LTE Carrier Aggregation Combinations		Inter-Band and Intra-Band possible combinations as below page and the detail power verification please referred to section 12.																																																																								
LTE Carrier Aggregation Additional Information		This device does not support full CA features on 3GPP Release 11. It supports a maximum of 3 carriers in the downlink only. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. Due to carrier capability, only the combinations listed above are supported. The following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.																																																																								

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	826.5	20450	829		
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5		
H	20643	848.3	20635	847.5	20625	846.5	20625	846.5	20600	844		
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20825	2507.5	20850	2510		
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535		
H	21425	2567.5	21400	2565	21375	2562.5	21375	2562.5	21350	2560		
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23035	701.5	23060	704		
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5	23095	707.5		
H	23173	715.3	23165	714.5	23155	713.5	23155	713.5	23130	711		
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)		Channel #		Freq.(MHz)	
L	23205		779.5		23230		782					
M	23230		782									
H	23255		784.5									
LTE Band 17												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq. (MHz)		Channel #		Freq. (MHz)	
L	23755		706.5		23780		709		23780		709	
M	23790		710		23790		710		23790		710	
H	23825		713.5		23800		711		23800		711	
LTE Band 25												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26047	1850.7	26055	1851.5	26065	1852.5	26090	1855	26115	1857.5	26140	1860
M	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880
H	26683	1914.3	26675	1913.5	26665	1912.5	26640	1910	26615	1907.5	26590	1905
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

7.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

7.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

7.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

7.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1012	May. 22, 2017	May. 21, 2018
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 21, 2017	Mar. 20, 2018
SPEAG	1750MHz System Validation Kit	D1750V2	1068	Nov. 16, 2016	Nov. 15, 2017
SPEAG	1900MHz System Validation Kit	D1900V2	5d018	Jun. 28, 2017	Jun. 27, 2018
SPEAG	2450MHz System Validation Kit	D2450V2	735	Dec. 23, 2016	Dec. 22, 2017
SPEAG	2600MHz System Validation Kit	D2600V2	1058	Jun. 27, 2017	Jun. 26, 2018
SPEAG	5GHz System Validation Kit	D5GHzV2	1171	Jul. 18, 2017	Jul. 17, 2018
SPEAG	Data Acquisition Electronics	DAE4	1424	Feb. 16, 2017	Feb. 15, 2018
SPEAG	Data Acquisition Electronics	DAE3	495	May. 22, 2017	May. 21, 2018
SPEAG	Data Acquisition Electronics	DAE4	778	May. 22, 2017	May. 21, 2018
SPEAG	Dosimetric E-Field Probe	EX3DV4	3976	Feb. 21, 2017	Feb. 20, 2018
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	May. 24, 2017	May. 23, 2018
SPEAG	Dosimetric E-Field Probe	ES3DV3	3071	Dec. 08, 2016	Dec. 07, 2017
WonDer	Thermometer	WD-5016	TM560-1	Mar. 17, 2017	Mar. 16, 2018
WonDer	Thermometer	WD-5016	TM560-2	Mar. 17, 2017	Mar. 16, 2018
TECPEL	Thermometer	UL-A03	TM225-1	Mar. 21, 2017	Mar. 20, 2018
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Apr. 20, 2017	Apr. 19, 2018
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 30, 2017	May. 29, 2018
R&S	BT Base Station	CBT32	100522	Mar. 14, 2017	Mar. 13, 2018
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Dec. 09, 2016	Dec. 08, 2017
Agilent	ENA Network Analyzer	E5071C	MY46316648	Jan. 04, 2017	Jan. 03, 2018
SPEAG	Dielectric Probe Kit	DAK-3.5	1146	Jul. 18, 2017	Jul. 17, 2018
LINE SEIKI	Digital Thermometer	LKMelectronic	DTM3000SPEZIAL	Sep. 06, 2017	Sep. 05, 2018
Anritsu	Power Meter	ML2495A	1438002	Dec. 06, 2016	Dec. 05, 2017
Anritsu	Power Meter	ML2495A	1419002	May. 15, 2017	May. 14, 2018
Anritsu	Power Sensor	MA2411B	1339195	Dec. 06, 2016	Dec. 05, 2017
Anritsu	Power Sensor	MA2411B	1339124	May. 15, 2017	May. 14, 2018
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 23, 2017	Aug. 22, 2018
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 26, 2017	Jun. 25, 2018
Mini-Circuits	Power Amplifier	ZVE-8G+	D120604	Mar. 09, 2017	Mar. 08, 2018
Mini-Circuits	Power Amplifier	ZHL-42W+	QA1344002	Mar. 09, 2017	Mar. 08, 2018
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1 Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR

10.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	HSL	22.3	0.894	40.523	0.89	41.90	0.45	-3.29	±5	2017/10/5
750	MSL	22.5	0.961	54.651	0.96	55.50	0.10	-1.53	±5	2017/10/2
835	HSL	22.3	0.901	42.050	0.90	41.50	0.11	1.33	±5	2017/10/4
835	MSL	22.4	0.957	56.600	0.97	55.20	-1.34	2.54	±5	2017/10/1
1750	HSL	22.3	1.395	40.186	1.37	40.10	1.82	0.21	±5	2017/10/6
1750	MSL	22.4	1.468	55.361	1.49	53.40	-1.48	3.67	±5	2017/10/10
1750	MSL	22.4	1.466	55.282	1.49	53.40	-1.61	3.52	±5	2017/10/11
1900	HSL	22.3	1.388	38.658	1.40	40.00	-0.86	-3.36	±5	2017/10/7
1900	MSL	22.5	1.525	53.202	1.52	53.30	0.33	-0.18	±5	2017/10/8
1900	MSL	22.5	1.523	53.151	1.52	53.30	0.20	-0.28	±5	2017/10/9
2450	HSL	22.2	1.768	39.477	1.80	39.20	-1.78	0.71	±5	2017/10/12
2450	MSL	22.2	2.022	54.912	1.95	52.70	3.69	4.20	±5	2017/10/12
2600	HSL	22.6	1.995	40.263	1.96	39.00	1.79	3.24	±5	2017/10/4
2600	MSL	22.5	2.230	53.903	2.16	52.50	3.24	2.67	±5	2017/10/3
5250	HSL	22.6	4.596	36.689	4.71	35.95	-2.42	2.06	±5	2017/10/11
5250	MSL	22.6	5.187	46.716	5.36	48.95	-3.23	-4.56	±5	2017/10/11
5600	HSL	22.6	4.951	36.202	5.07	35.50	-2.35	1.98	±5	2017/10/11
5600	MSL	22.6	5.619	46.180	5.77	48.50	-2.62	-4.78	±5	2017/10/11
5750	HSL	22.6	5.107	36.004	5.22	35.35	-2.16	1.85	±5	2017/10/11
5750	MSL	22.6	5.817	45.948	5.94	48.28	-2.07	-4.83	±5	2017/10/11

10.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2017/10/5	750	HSL	250	D750V3-1012	EX3DV4 - SN3976	DAE4 Sn1424	2.06	8.22	8.24	0.24
2017/10/2	750	MSL	250	D750V3-1012	EX3DV4 - SN3976	DAE4 Sn1424	2.14	8.71	8.56	-1.72
2017/10/4	835	HSL	250	D835V2-499	EX3DV4 - SN3976	DAE4 Sn1424	2.43	9.45	9.72	2.86
2017/10/1	835	MSL	250	D835V2-499	EX3DV4 - SN3976	DAE4 Sn1424	2.46	9.67	9.84	1.76
2017/10/6	1750	HSL	250	D1750V2-1068	EX3DV4 - SN3976	DAE4 Sn1424	8.84	36.60	35.36	-3.39
2017/10/10	1750	MSL	250	D1750V2-1068	ES3DV3 - SN3071	DAE4 Sn778	9.36	36.20	37.44	3.43
2017/10/11	1750	MSL	250	D1750V2-1068	ES3DV3 - SN3071	DAE4 Sn778	9.60	36.20	38.40	6.08
2017/10/7	1900	HSL	250	D1900V2-5d018	EX3DV4 - SN3976	DAE4 Sn1424	9.68	40.10	38.72	-3.44
2017/10/8	1900	MSL	250	D1900V2-5d018	EX3DV4 - SN3976	DAE4 Sn1424	10.20	40.60	40.80	0.49
2017/10/9	1900	MSL	250	D1900V2-5d018	ES3DV3 - SN3071	DAE4 Sn778	10.20	40.60	40.80	0.49
2017/10/12	2450	HSL	250	D2450V2-735	ES3DV3 - SN3071	DAE4 Sn778	13.40	50.90	53.60	5.30
2017/10/12	2450	MSL	250	D2450V2-735	ES3DV3 - SN3071	DAE4 Sn778	13.10	50.60	52.40	3.56
2017/10/4	2600	HSL	250	D2600V2-1058	EX3DV4 - SN3976	DAE4 Sn1424	14.90	57.00	59.60	4.56
2017/10/3	2600	MSL	250	D2600V2-1058	EX3DV4 - SN3976	DAE4 Sn1424	13.90	54.30	55.60	2.39
2017/10/11	5250	HSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	7.65	81.20	76.50	-5.79
2017/10/11	5250	MSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	7.76	78.10	77.60	-0.64
2017/10/11	5600	HSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	8.57	84.90	85.70	0.94
2017/10/11	5600	MSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	8.14	81.00	81.40	0.49
2017/10/11	5750	HSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	7.80	82.20	78.00	-5.11
2017/10/11	5750	MSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	7.85	78.70	78.50	-0.25

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2017/10/5	750	HSL	250	D750V3-1012	EX3DV4 - SN3976	DAE4 Sn1424	1.39	5.35	5.56	3.93
2017/10/2	750	MSL	250	D750V3-1012	EX3DV4 - SN3976	DAE4 Sn1424	1.45	5.72	5.80	1.40
2017/10/4	835	HSL	250	D835V2-499	EX3DV4 - SN3976	DAE4 Sn1424	1.60	6.14	6.40	4.23
2017/10/1	835	MSL	250	D835V2-499	EX3DV4 - SN3976	DAE4 Sn1424	1.63	6.35	6.52	2.68
2017/10/6	1750	HSL	250	D1750V2-1068	EX3DV4 - SN3976	DAE4 Sn1424	4.75	19.50	19.00	-2.56
2017/10/10	1750	MSL	250	D1750V2-1068	ES3DV3 - SN3071	DAE4 Sn778	5.13	19.40	20.52	5.77
2017/10/11	1750	MSL	250	D1750V2-1068	ES3DV3 - SN3071	DAE4 Sn778	5.17	19.40	20.68	6.60
2017/10/7	1900	HSL	250	D1900V2-5d018	EX3DV4 - SN3976	DAE4 Sn1424	5.07	20.90	20.28	-2.97
2017/10/8	1900	MSL	250	D1900V2-5d018	EX3DV4 - SN3976	DAE4 Sn1424	5.32	21.50	21.28	-1.02
2017/10/9	1900	MSL	250	D1900V2-5d018	ES3DV3 - SN3071	DAE4 Sn778	5.39	21.50	21.56	0.28
2017/10/12	2450	HSL	250	D2450V2-735	ES3DV3 - SN3071	DAE4 Sn778	6.30	23.80	25.20	5.88
2017/10/12	2450	MSL	250	D2450V2-735	ES3DV3 - SN3071	DAE4 Sn778	6.11	23.80	24.44	2.69
2017/10/4	2600	HSL	250	D2600V2-1058	EX3DV4 - SN3976	DAE4 Sn1424	6.72	25.50	26.88	5.41
2017/10/3	2600	MSL	250	D2600V2-1058	EX3DV4 - SN3976	DAE4 Sn1424	6.22	24.30	24.88	2.39
2017/10/11	5250	HSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	2.15	23.30	21.50	-7.73
2017/10/11	5250	MSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	2.10	21.80	21.00	-3.67
2017/10/11	5600	HSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	2.30	24.40	23.00	-5.74
2017/10/11	5600	MSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	2.16	22.80	21.60	-5.26
2017/10/11	5750	HSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	2.18	23.40	21.80	-6.84
2017/10/11	5750	MSL	100	D5GHzV2-1171	EX3DV4 - SN3925	DAE3 Sn495	2.06	21.90	20.60	-5.94



Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

11.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

12. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

General Note:

- For DTM multi-slot class mode, the device was linked with base station simulator (Agilent E5515C) and transmit maximum power on maximum number of TX slots, i.e. one CS timeslot, and additional PS timeslots (1 for DTM class 5 and 9, 2 for DTM class 11) in one TDMA frame.
- Agilent E5515C was used to setup the device operated under DTM mode for power measurement and SAR testing. For conducted power, the power of the burst for voice and the power of the bursts for data was reported separately in the table above, and the frame-average power is derived below to determine SAR testing.

$$DTM \text{ frame average power (dBm)} = 10 \cdot \log [\sum (\text{power of each slot, in mW}) / 8]$$

- Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
- Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode
- Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 4 Tx slot due to its highest frame-average power.

<Default Power Mode>

GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot		32.90	33.14	33.16	34.00	23.90	24.14	24.16	25.00
GPRS 1 Tx slot		32.98	33.14	33.16	34.00	23.98	24.14	24.16	25.00
GPRS 2 Tx slots		31.06	31.24	30.95	31.50	25.06	25.24	24.95	25.50
GPRS 3 Tx slots		29.05	28.96	29.11	29.70	24.79	24.70	24.85	25.44
GPRS 4 Tx slots		27.56	27.63	27.74	28.50	24.56	24.63	24.74	25.50
EDGE 1 Tx slot		25.91	25.86	25.80	27.50	16.91	16.86	16.80	18.50
EDGE 2 Tx slots		25.65	25.62	25.61	27.30	19.65	19.62	19.61	21.30
EDGE 3 Tx slots		25.31	25.32	25.33	27.10	21.05	21.06	21.07	22.84
EDGE 4 Tx slots		25.00	24.96	24.93	26.90	22.00	21.96	21.93	23.90
DTM Multi-slot class 5	GSM 1 Tx slot	30.94	31.12	31.15	31.50	24.64	24.81	24.88	25.48
	GPRS 1 Tx slot	30.36	30.52	30.64	31.50				
DTM Multi-slot class 9	GSM 1 Tx slot	30.93	31.11	31.14	31.50	24.61	24.81	24.84	25.48
	GPRS 1 Tx slot	30.31	30.53	30.57	31.50				
DTM Multi-slot class 11	GSM 1 Tx slot	29.01	29.18	29.22	29.70	24.36	24.53	24.58	25.44
	GPRS 2 Tx slots	28.41	28.58	28.64	29.70				
DTM Multi-slot class 5	GSM 1 Tx slot	30.70	30.87	30.51	31.50	23.05	23.23	22.97	23.87
	EDGE 1 Tx slot	26.43	26.63	26.65	27.30				
DTM Multi-slot class 9	GSM 1 Tx slot	31.06	31.29	30.94	31.50	23.19	23.41	23.15	23.87
	EDGE 1 Tx slot	25.92	26.09	26.14	27.30				
DTM Multi-slot class 11	GSM 1 Tx slot	28.76	28.91	28.95	29.70	22.95	23.10	23.19	23.89
	EDGE 2 Tx slots	26.17	26.31	26.44	27.10				

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		29.84	30.31	30.30	31.00	20.84	21.31	21.30	22.00
GPRS 1 Tx slot		29.85	30.33	30.31	31.00	20.85	21.33	21.31	22.00
GPRS 2 Tx slots		27.47	27.62	27.73	28.00	21.47	21.62	21.73	22.00
GPRS 3 Tx slots		26.13	26.37	26.45	26.50	21.87	22.11	22.19	22.24
GPRS 4 Tx slots		25.10	25.17	25.40	25.50	22.10	22.17	22.40	22.50
EDGE 1 Tx slot		24.52	24.95	25.00	26.00	15.52	15.95	16.00	17.00
EDGE 2 Tx slots		24.37	24.70	24.77	26.00	18.37	18.70	18.77	20.00
EDGE 3 Tx slots		24.03	24.42	24.53	25.50	19.77	20.16	20.27	21.24
EDGE 4 Tx slots		23.27	23.59	23.64	25.00	20.27	20.59	20.64	22.00
DTM Multi-slot class 5	GSM 1 Tx slot	27.45	27.85	27.68	28.00	21.10	21.48	21.31	21.98
	GPRS 1 Tx slot	26.77	27.13	26.96	28.00				
DTM Multi-slot class 9	GSM 1 Tx slot	27.43	27.82	27.69	28.00	21.08	21.46	21.32	21.98
	GPRS 1 Tx slot	26.75	27.11	26.97	28.00				
DTM Multi-slot class 11	GSM 1 Tx slot	26.17	26.36	26.41	26.50	21.48	21.64	21.69	22.24
	GPRS 2 Tx slots	25.50	25.65	25.70	26.50				
DTM Multi-slot class 5	GSM 1 Tx slot	26.83	27.19	27.06	28.00	19.94	20.24	20.15	21.09
	EDGE 1 Tx slot	24.88	25.08	25.06	26.00				
DTM Multi-slot class 9	GSM 1 Tx slot	27.49	27.84	27.69	28.00	20.10	20.42	20.30	21.09
	EDGE 1 Tx slot	24.12	24.35	24.31	26.00				
DTM Multi-slot class 11	GSM 1 Tx slot	25.64	25.71	25.74	26.50	20.75	20.85	20.90	21.60
	EDGE 2 Tx slots	24.65	24.78	24.83	25.50				

<Reduced Power Mode>

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		27.28	27.64	27.52	28.00	18.28	18.64	18.52	19.00
GPRS 1 Tx slot		27.20	27.66	27.58	28.00	18.20	18.66	18.58	19.00
GPRS 2 Tx slots		24.32	24.45	24.50	24.50	18.32	18.45	18.50	18.50
GPRS 3 Tx slots		22.53	22.73	22.71	23.00	18.27	18.47	18.45	18.74
GPRS 4 Tx slots		21.31	21.61	21.60	22.00	18.31	18.61	18.60	19.00
EDGE 1 Tx slot		21.31	21.57	21.59	22.50	12.31	12.57	12.59	13.50
EDGE 2 Tx slots		21.14	21.33	21.39	22.50	15.14	15.33	15.39	16.50
EDGE 3 Tx slots		20.48	20.70	20.64	22.00	16.22	16.44	16.38	17.74
EDGE 4 Tx slots		19.78	19.90	19.92	21.50	16.78	16.90	16.92	18.50
DTM Multi-slot class 5	GSM 1 Tx slot	24.41	24.49	24.50	24.50	18.09	18.24	18.21	18.48
	GPRS 1 Tx slot	23.78	24.02	23.95	24.50				
DTM Multi-slot class 9	GSM 1 Tx slot	24.31	24.50	24.50	24.50	17.99	18.19	18.21	18.48
	GPRS 1 Tx slot	23.69	23.91	23.95	24.50				
DTM Multi-slot class 11	GSM 1 Tx slot	22.44	22.76	22.73	23.00	17.89	18.18	18.14	18.74
	GPRS 2 Tx slots	22.00	22.27	22.23	23.00				
DTM Multi-slot class 5	GSM 1 Tx slot	23.89	24.09	24.04	24.50	16.67	16.89	16.86	17.59
	EDGE 1 Tx slot	21.04	21.28	21.28	22.50				
DTM Multi-slot class 9	GSM 1 Tx slot	24.40	24.50	24.45	24.50	16.85	16.98	16.92	17.59
	EDGE 1 Tx slot	20.50	20.70	20.61	22.50				
DTM Multi-slot class 11	GSM 1 Tx slot	21.76	22.04	21.97	23.00	16.64	16.92	16.88	18.10
	EDGE 2 Tx slots	20.39	20.68	20.65	22.00				

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$. Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPCCH, DPDCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases. Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.							

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration


DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Cycle to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12
Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		


Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)
Setup Configuration



<WCDMA Conducted Power>

General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

<Default Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	24.10	24.16	23.94	24.50	23.76	24.00	24.03	24.50	24.16	24.33	24.27	25.00
3GPP Rel 99	RMC 12.2Kbps	24.11	24.19	23.92	24.50	23.77	24.01	24.04	24.50	24.21	24.34	24.28	25.00
3GPP Rel 6	HSDPA Subtest-1	23.14	23.21	22.95	24.50	22.78	22.99	23.05	24.50	23.21	23.33	23.28	24.00
3GPP Rel 6	HSDPA Subtest-2	23.17	23.24	22.97	24.50	22.79	23.03	23.07	24.50	23.25	23.36	23.30	24.00
3GPP Rel 6	HSDPA Subtest-3	22.65	22.75	22.49	24.00	22.29	22.53	22.55	24.00	22.76	22.87	22.81	23.50
3GPP Rel 6	HSDPA Subtest-4	22.68	22.74	22.50	24.00	22.26	22.56	22.57	24.00	22.74	22.88	22.80	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	23.04	23.16	22.85	24.50	22.70	22.89	22.96	24.50	23.11	23.23	23.18	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	23.02	23.14	22.82	24.50	22.69	22.84	22.94	24.50	23.10	23.22	23.16	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	22.55	22.65	22.39	24.00	22.19	22.43	22.45	24.00	22.66	22.77	22.71	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	22.51	22.64	22.33	24.00	22.20	22.42	22.41	24.00	22.61	22.72	22.73	23.50
3GPP Rel 6	HSUPA Subtest-1	23.14	23.19	22.82	23.50	22.86	22.98	23.05	23.50	23.19	23.30	23.22	23.50
3GPP Rel 6	HSUPA Subtest-2	21.19	21.23	20.89	21.50	21.01	21.02	21.09	21.50	21.20	21.29	21.26	21.50
3GPP Rel 6	HSUPA Subtest-3	22.16	22.21	21.86	22.50	21.96	22.02	22.05	22.50	22.21	22.30	22.25	22.50
3GPP Rel 6	HSUPA Subtest-4	21.19	21.21	20.99	21.50	20.93	21.05	21.08	21.50	21.16	21.25	21.23	21.50
3GPP Rel 6	HSUPA Subtest-5	23.15	23.21	22.84	23.50	22.79	23.01	23.07	23.50	23.20	23.31	23.21	23.50


<Reduced Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513	
Rx Channel		9662	9800	9938		1537	1638	1738	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	18.50	18.59	18.30	19.00	18.37	18.48	18.49	18.50
3GPP Rel 99	RMC 12.2Kbps	18.50	18.60	18.31	19.00	18.37	18.49	18.50	18.50
3GPP Rel 6	HSDPA Subtest-1	17.48	17.48	17.30	18.00	17.40	17.50	17.50	17.50
3GPP Rel 6	HSDPA Subtest-2	17.48	17.50	17.28	18.00	17.40	17.49	17.50	17.50
3GPP Rel 6	HSDPA Subtest-3	16.95	16.99	16.73	17.50	16.91	16.92	16.94	17.00
3GPP Rel 6	HSDPA Subtest-4	16.98	16.93	16.81	17.50	16.92	16.93	17.00	17.00
3GPP Rel 8	DC-HSDPA Subtest-1	17.47	17.40	17.18	18.00	17.32	17.35	17.34	17.50
3GPP Rel 8	DC-HSDPA Subtest-2	17.43	17.44	17.31	18.00	17.35	17.32	17.50	17.50
3GPP Rel 8	DC-HSDPA Subtest-3	16.87	16.99	16.63	17.50	16.77	16.86	16.87	17.00
3GPP Rel 8	DC-HSDPA Subtest-4	16.99	16.88	16.68	17.50	16.86	16.81	16.86	17.00
3GPP Rel 6	HSUPA Subtest-1	17.45	17.48	17.23	18.00	17.37	17.33	17.41	17.50
3GPP Rel 6	HSUPA Subtest-2	15.52	15.48	15.25	16.00	15.38	15.33	15.48	15.50
3GPP Rel 6	HSUPA Subtest-3	16.45	16.45	16.29	17.00	16.33	16.36	16.46	16.50
3GPP Rel 6	HSUPA Subtest-4	15.43	15.47	15.28	16.00	15.33	15.29	15.47	15.50
3GPP Rel 6	HSUPA Subtest-5	17.53	17.51	17.32	18.00	17.41	17.50	17.50	17.50


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4/B5/B12/B17 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 17 SAR test was covered by Band 12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM

Default Power Mode
<LTE Tune-up Limit>

Mode		Average Power (dBm)
LTE	Band 2	24.5
	Band 4	24.5
	Band 5	24.5
	Band 7	24.5
	Band 12	24.5
	Band 13	24.5
	Band 17	24.5
	Band 25	24.0
	Band 66	24.0



<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.51	23.95	23.84	24.5	0
20	QPSK	1	49	23.47	23.88	23.83		
20	QPSK	1	99	23.50	23.78	23.83		
20	QPSK	50	0	22.74	23.22	22.86	23.5	1
20	QPSK	50	24	22.75	23.07	23.21		
20	QPSK	50	50	22.74	22.90	22.94		
20	QPSK	100	0	22.54	23.02	23.01		
20	16QAM	1	0	22.70	23.04	22.92	23.5	1
20	16QAM	1	49	22.70	23.07	23.07		
20	16QAM	1	99	22.87	22.90	23.03		
20	16QAM	50	0	21.59	21.86	21.86	22.5	2
20	16QAM	50	24	21.57	21.97	21.92		
20	16QAM	50	50	21.61	21.88	21.97		
20	16QAM	100	0	21.54	21.91	22.00		
20	64QAM	1	0	21.68	21.93	22.06	22.5	2
20	64QAM	1	49	21.78	22.06	22.09		
20	64QAM	1	99	21.80	21.95	22.02		
20	64QAM	50	0	20.65	20.85	20.86	21.5	3
20	64QAM	50	24	20.63	20.97	20.88		
20	64QAM	50	50	20.63	20.90	20.94		
20	64QAM	100	0	20.59	20.90	20.98		
Channel				18675	18900	19125		
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	23.51	23.82	23.74	24.5	0
15	QPSK	1	37	23.49	23.79	23.88		
15	QPSK	1	74	23.48	23.65	23.74		
15	QPSK	36	0	22.57	22.84	22.84	23.5	1
15	QPSK	36	20	22.67	22.95	23.00		
15	QPSK	36	39	22.64	22.90	22.94		
15	QPSK	75	0	22.64	22.92	22.98		
15	16QAM	1	0	22.80	23.18	22.98	23.5	1
15	16QAM	1	37	22.71	23.10	23.18		
15	16QAM	1	74	22.77	22.84	23.00		
15	16QAM	36	0	21.54	21.87	21.86	22.5	2
15	16QAM	36	20	21.64	21.97	22.00		
15	16QAM	36	39	21.70	21.88	21.94		
15	16QAM	75	0	21.62	21.92	21.97		
15	64QAM	1	0	21.66	22.02	22.06	22.5	2
15	64QAM	1	37	21.64	22.05	22.13		
15	64QAM	1	74	21.64	21.93	22.00		
15	64QAM	36	0	20.45	20.81	20.83	21.5	3
15	64QAM	36	20	20.64	20.96	21.08		
15	64QAM	36	39	20.67	20.90	20.93		
15	64QAM	75	0	20.58	20.89	20.94		



Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	23.58	23.88	23.85	24.5	0
10	QPSK	1	25	23.59	23.88	23.89		
10	QPSK	1	49	23.53	23.83	23.85		
10	QPSK	25	0	22.59	22.98	22.99	23.5	1
10	QPSK	25	12	22.70	22.96	23.02		
10	QPSK	25	25	22.63	22.93	22.97		
10	QPSK	50	0	22.63	22.94	22.98		
10	16QAM	1	0	22.79	23.17	23.10	23.5	1
10	16QAM	1	25	22.79	23.07	23.18		
10	16QAM	1	49	22.68	22.93	23.06		
10	16QAM	25	0	21.57	21.94	21.98	22.5	2
10	16QAM	25	12	21.67	21.97	22.01		
10	16QAM	25	25	21.58	21.90	21.94		
10	16QAM	50	0	21.63	21.93	21.99		
10	64QAM	1	0	21.75	22.05	22.08	22.5	2
10	64QAM	1	25	21.76	22.06	22.14		
10	64QAM	1	49	21.66	21.94	22.02		
10	64QAM	25	0	20.54	20.94	20.96	21.5	3
10	64QAM	25	12	20.63	20.94	20.99		
10	64QAM	25	25	20.55	20.89	20.91		
10	64QAM	50	0	20.64	20.91	20.95		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	23.56	23.92	23.94	24.5	0
5	QPSK	1	12	23.51	23.91	23.91		
5	QPSK	1	24	23.44	23.87	23.87		
5	QPSK	12	0	22.54	22.92	22.96	23.5	1
5	QPSK	12	7	22.58	22.94	22.97		
5	QPSK	12	13	22.50	22.90	22.94		
5	QPSK	25	0	22.54	22.95	23.00		
5	16QAM	1	0	22.75	23.13	23.13	23.5	1
5	16QAM	1	12	22.71	23.11	23.14		
5	16QAM	1	24	22.67	22.96	23.00		
5	16QAM	12	0	21.54	21.93	21.95	22.5	2
5	16QAM	12	7	21.58	21.98	21.98		
5	16QAM	12	13	21.52	21.90	21.94		
5	16QAM	25	0	21.53	21.92	21.95		
5	64QAM	1	0	21.70	22.08	22.07	22.5	2
5	64QAM	1	12	21.65	22.09	22.11		
5	64QAM	1	24	21.59	22.02	22.01		
5	64QAM	12	0	20.54	20.91	20.99	21.5	3
5	64QAM	12	7	20.58	20.97	21.02		
5	64QAM	12	13	20.52	20.92	20.96		
5	64QAM	25	0	20.49	20.87	20.92		



Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	23.49	23.87	23.88	24.5	0
3	QPSK	1	8	23.54	23.89	23.88		
3	QPSK	1	14	23.46	23.84	23.84		
3	QPSK	8	0	22.55	22.92	22.98	23.5	1
3	QPSK	8	4	22.58	22.98	23.00		
3	QPSK	8	7	22.54	22.94	22.97		
3	QPSK	15	0	22.53	22.91	22.94		
3	16QAM	1	0	22.75	23.08	23.05	23.5	1
3	16QAM	1	8	22.74	23.06	23.09		
3	16QAM	1	14	22.61	22.98	23.01		
3	16QAM	8	0	21.60	21.96	22.02	22.5	2
3	16QAM	8	4	21.62	21.99	22.05		
3	16QAM	8	7	21.57	21.96	22.01		
3	16QAM	15	0	21.56	21.94	21.98		
3	64QAM	1	0	21.69	22.04	22.03	22.5	2
3	64QAM	1	8	21.67	22.04	22.03		
3	64QAM	1	14	21.63	21.98	22.02		
3	64QAM	8	0	20.55	20.94	20.99	21.5	3
3	64QAM	8	4	20.57	20.96	20.99		
3	64QAM	8	7	20.53	20.93	20.94		
3	64QAM	15	0	20.51	20.92	20.96		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	23.42	23.76	23.75	24.5	0
1.4	QPSK	1	3	23.49	23.82	23.79		
1.4	QPSK	1	5	23.43	23.75	23.76		
1.4	QPSK	3	0	23.50	23.86	23.84		
1.4	QPSK	3	1	23.56	23.94	23.91		
1.4	QPSK	3	3	23.50	23.88	23.87		
1.4	QPSK	6	0	22.50	22.86	22.88	23.5	1
1.4	16QAM	1	0	22.66	23.02	22.99	23.5	1
1.4	16QAM	1	3	22.72	23.03	23.05		
1.4	16QAM	1	5	22.65	22.94	22.95		
1.4	16QAM	3	0	22.50	22.88	22.82		
1.4	16QAM	3	1	22.54	22.90	22.89		
1.4	16QAM	3	3	22.47	22.84	22.79		
1.4	16QAM	6	0	21.56	21.93	21.95	22.5	2
1.4	64QAM	1	0	21.66	22.04	22.03	22.5	2
1.4	64QAM	1	3	21.70	22.07	22.07		
1.4	64QAM	1	5	21.63	22.05	22.01		
1.4	64QAM	3	0	21.62	21.97	21.95		
1.4	64QAM	3	1	21.66	22.01	21.99		
1.4	64QAM	3	3	21.60	21.95	21.95		
1.4	64QAM	6	0	20.47	20.84	20.83	21.5	3



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	23.52	23.75	23.69	24.5	0
20	QPSK	1	49	23.48	23.62	23.64		
20	QPSK	1	99	23.59	23.61	23.62		
20	QPSK	50	0	22.51	22.86	22.82	23.5	1
20	QPSK	50	24	22.62	22.76	22.82		
20	QPSK	50	50	22.65	22.77	22.85		
20	QPSK	100	0	22.57	22.78	22.75	23.5	1
20	16QAM	1	0	22.54	22.81	22.88		
20	16QAM	1	49	22.67	22.91	22.75		
20	16QAM	1	99	22.79	22.71	22.77	22.5	2
20	16QAM	50	0	21.54	21.68	21.84		
20	16QAM	50	24	21.62	21.79	21.83		
20	16QAM	50	50	21.63	21.76	21.84	22.5	2
20	16QAM	100	0	21.56	21.73	21.80		
20	64QAM	1	0	21.53	21.82	21.88	22.5	2
20	64QAM	1	49	21.67	21.91	21.86		
20	64QAM	1	99	21.74	21.80	21.88		
20	64QAM	50	0	20.53	20.69	20.86	21.5	3
20	64QAM	50	24	20.63	20.77	20.82		
20	64QAM	50	50	20.62	20.76	20.88		
20	64QAM	100	0	20.57	20.74	20.81		
Channel				20025	20175	20325		
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	23.30	23.56	23.62	24.5	0
15	QPSK	1	37	23.33	23.60	23.58		
15	QPSK	1	74	23.45	23.56	23.60		
15	QPSK	36	0	22.52	22.79	22.82	23.5	1
15	QPSK	36	20	22.53	22.78	22.83		
15	QPSK	36	39	22.57	22.71	22.85		
15	QPSK	75	0	22.50	22.73	22.79	23.5	1
15	16QAM	1	0	22.56	22.86	22.91		
15	16QAM	1	37	22.61	22.91	22.72		
15	16QAM	1	74	22.74	22.76	22.79	22.5	2
15	16QAM	36	0	21.52	21.77	21.82		
15	16QAM	36	20	21.53	21.77	21.82		
15	16QAM	36	39	21.57	21.70	21.86	22.5	2
15	16QAM	75	0	21.50	21.74	21.82		
15	64QAM	1	0	21.59	21.83	21.96		
15	64QAM	1	37	21.60	21.89	21.87	21.5	3
15	64QAM	1	74	21.70	21.81	21.85		
15	64QAM	36	0	20.52	20.76	20.84		
15	64QAM	36	20	20.57	20.78	20.86		
15	64QAM	36	39	20.58	20.70	20.87		
15	64QAM	75	0	20.48	20.73	20.78		



Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	23.42	23.60	23.55	24.5	0
10	QPSK	1	25	23.47	23.63	23.59		
10	QPSK	1	49	23.48	23.62	23.57		
10	QPSK	25	0	22.55	22.80	22.74	23.5	1
10	QPSK	25	12	22.55	22.75	22.81		
10	QPSK	25	25	22.51	22.73	22.75		
10	QPSK	50	0	22.53	22.74	22.77	23.5	1
10	16QAM	1	0	22.57	22.87	22.66		
10	16QAM	1	25	22.61	22.91	22.76		
10	16QAM	1	49	22.64	22.78	22.74	22.5	2
10	16QAM	25	0	21.51	21.77	21.72		
10	16QAM	25	12	21.54	21.78	21.80		
10	16QAM	25	25	21.48	21.72	21.73	22.5	2
10	16QAM	50	0	21.51	21.73	21.75		
10	64QAM	1	0	21.60	21.82	21.76		
10	64QAM	1	25	21.61	21.92	21.88	22.5	2
10	64QAM	1	49	21.63	21.76	21.79		
10	64QAM	25	0	20.54	20.77	20.72		
10	64QAM	25	12	20.55	20.76	20.79	21.5	3
10	64QAM	25	25	20.48	20.69	20.75		
10	64QAM	50	0	20.53	20.74	20.79		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	23.36	23.58	23.57	24.5	0
5	QPSK	1	12	23.37	23.63	23.60		
5	QPSK	1	24	23.40	23.56	23.62		
5	QPSK	12	0	22.41	22.74	22.79	23.5	1
5	QPSK	12	7	22.45	22.79	22.79		
5	QPSK	12	13	22.50	22.72	22.75		
5	QPSK	25	0	22.41	22.75	22.76	23.5	1
5	16QAM	1	0	22.54	22.90	22.78		
5	16QAM	1	12	22.57	22.93	22.78		
5	16QAM	1	24	22.58	22.82	22.75	22.5	2
5	16QAM	12	0	21.43	21.77	21.75		
5	16QAM	12	7	21.45	21.78	21.78		
5	16QAM	12	13	21.52	21.74	21.73	22.5	2
5	16QAM	25	0	21.39	21.73	21.73		
5	64QAM	1	0	21.54	21.88	21.89		
5	64QAM	1	12	21.53	21.85	21.87	22.5	2
5	64QAM	1	24	21.58	21.77	21.81		
5	64QAM	12	0	20.46	20.78	20.83		
5	64QAM	12	7	20.47	20.80	20.82	21.5	3
5	64QAM	12	13	20.53	20.75	20.77		
5	64QAM	25	0	20.41	20.73	20.74		



Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	23.33	23.58	23.57	24.5	0
3	QPSK	1	8	23.37	23.54	23.55		
3	QPSK	1	14	23.38	23.56	23.51		
3	QPSK	8	0	22.42	22.76	22.76	23.5	1
3	QPSK	8	4	22.45	22.78	22.78		
3	QPSK	8	7	22.41	22.71	22.73		
3	QPSK	15	0	22.40	22.74	22.74		
3	16QAM	1	0	22.53	22.88	22.74	23.5	1
3	16QAM	1	8	22.57	22.90	22.80		
3	16QAM	1	14	22.57	22.84	22.76		
3	16QAM	8	0	21.47	21.78	21.78	22.5	2
3	16QAM	8	4	21.49	21.81	21.81		
3	16QAM	8	7	21.42	21.76	21.78		
3	16QAM	15	0	21.43	21.76	21.77		
3	64QAM	1	0	21.49	21.82	21.85	22.5	2
3	64QAM	1	8	21.51	21.84	21.91		
3	64QAM	1	14	21.57	21.82	21.86		
3	64QAM	8	0	20.43	20.77	20.78	21.5	3
3	64QAM	8	4	20.45	20.78	20.81		
3	64QAM	8	7	20.42	20.75	20.74		
3	64QAM	15	0	20.40	20.73	20.76		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	23.23	23.56	23.56	24.5	0
1.4	QPSK	1	3	23.28	23.63	23.63		
1.4	QPSK	1	5	23.23	23.57	23.54		
1.4	QPSK	3	0	23.32	23.64	23.60		
1.4	QPSK	3	1	23.40	23.63	23.64		
1.4	QPSK	3	3	23.35	23.60	23.56		
1.4	QPSK	6	0	22.36	22.67	22.69	23.5	1
1.4	16QAM	1	0	22.47	22.83	22.69	23.5	1
1.4	16QAM	1	3	22.54	22.90	22.77		
1.4	16QAM	1	5	22.45	22.82	22.72		
1.4	16QAM	3	0	22.30	22.64	22.65		
1.4	16QAM	3	1	22.37	22.71	22.64		
1.4	16QAM	3	3	22.28	22.63	22.63		
1.4	16QAM	6	0	21.41	21.72	21.72	22.5	2
1.4	64QAM	1	0	21.50	21.80	21.86	22.5	2
1.4	64QAM	1	3	21.53	21.83	21.89		
1.4	64QAM	1	5	21.49	21.78	21.88		
1.4	64QAM	3	0	21.42	21.76	21.73		
1.4	64QAM	3	1	21.49	21.80	21.78		
1.4	64QAM	3	3	21.43	21.75	21.75		
1.4	64QAM	6	0	20.35	20.65	20.67	21.5	3



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	23.63	23.64	23.61	24.5	0
10	QPSK	1	25	23.42	23.46	23.50		
10	QPSK	1	49	23.46	23.42	23.41		
10	QPSK	25	0	22.43	22.58	22.54	23.5	1
10	QPSK	25	12	22.48	22.51	22.53		
10	QPSK	25	25	22.45	22.47	22.52		
10	QPSK	50	0	22.46	22.54	22.49	23.5	1
10	16QAM	1	0	22.63	22.72	22.68		
10	16QAM	1	25	22.71	22.75	22.73		
10	16QAM	1	49	22.74	22.61	22.61	22.5	2
10	16QAM	25	0	21.39	21.52	21.56		
10	16QAM	25	12	21.50	21.53	21.57		
10	16QAM	25	25	21.41	21.47	21.49	22.5	2
10	16QAM	50	0	21.46	21.50	21.53		
10	64QAM	1	0	21.54	21.61	21.60		
10	64QAM	1	25	21.62	21.67	21.70	22.5	2
10	64QAM	1	49	21.61	21.56	21.58		
10	64QAM	25	0	20.42	20.52	20.57		
10	64QAM	25	12	20.50	20.53	20.56	21.5	3
10	64QAM	25	25	20.40	20.46	20.49		
10	64QAM	50	0	20.45	20.48	20.55		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	23.39	23.47	23.52	24.5	0
5	QPSK	1	12	23.35	23.45	23.50		
5	QPSK	1	24	23.43	23.44	23.53		
5	QPSK	12	0	22.42	22.51	22.53	23.5	1
5	QPSK	12	7	22.42	22.54	22.56		
5	QPSK	12	13	22.49	22.48	22.51		
5	QPSK	25	0	22.40	22.52	22.56	23.5	1
5	16QAM	1	0	22.63	22.77	22.71		
5	16QAM	1	12	22.64	22.74	22.71		
5	16QAM	1	24	22.67	22.69	22.62	22.5	2
5	16QAM	12	0	21.38	21.51	21.53		
5	16QAM	12	7	21.42	21.55	21.57		
5	16QAM	12	13	21.49	21.51	21.51	22.5	2
5	16QAM	25	0	21.40	21.49	21.52		
5	64QAM	1	0	21.54	21.63	21.67		
5	64QAM	1	12	21.52	21.67	21.68	22.5	2
5	64QAM	1	24	21.59	21.59	21.62		
5	64QAM	12	0	20.43	20.51	20.56		
5	64QAM	12	7	20.43	20.53	20.58	21.5	3
5	64QAM	12	13	20.47	20.50	20.53		
5	64QAM	25	0	20.36	20.46	20.50		

Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	23.37	23.46	23.51	24.5	0
3	QPSK	1	8	23.36	23.46	23.49		
3	QPSK	1	14	23.34	23.41	23.45		
3	QPSK	8	0	22.42	22.52	22.54	23.5	1
3	QPSK	8	4	22.47	22.55	22.56		
3	QPSK	8	7	22.41	22.48	22.54		
3	QPSK	15	0	22.41	22.50	22.51	23.5	1
3	16QAM	1	0	22.64	22.76	22.69		
3	16QAM	1	8	22.65	22.71	22.68		
3	16QAM	1	14	22.64	22.68	22.58	22.5	2
3	16QAM	8	0	21.48	21.58	21.59		
3	16QAM	8	4	21.49	21.57	21.61		
3	16QAM	8	7	21.47	21.54	21.56	22.5	2
3	16QAM	15	0	21.45	21.52	21.54		
3	64QAM	1	0	21.53	21.64	21.67	22.5	2
3	64QAM	1	8	21.53	21.64	21.66		
3	64QAM	1	14	21.53	21.63	21.63		
3	64QAM	8	0	20.44	20.53	20.56	21.5	3
3	64QAM	8	4	20.46	20.54	20.56		
3	64QAM	8	7	20.41	20.52	20.53		
3	64QAM	15	0	20.40	20.48	20.54	21.5	3
Channel				20407	20525	20643		
Frequency (MHz)				824.7	836.5	848.3	Tune-up limit (dBm)	MPR (dB)
1.4	QPSK	1	0	23.30	23.40	23.41	24.5	0
1.4	QPSK	1	3	23.36	23.45	23.43		
1.4	QPSK	1	5	23.32	23.39	23.37		
1.4	QPSK	3	0	23.40	23.45	23.49	24.5	0
1.4	QPSK	3	1	23.42	23.51	23.52		
1.4	QPSK	3	3	23.39	23.48	23.48		
1.4	QPSK	6	0	22.37	22.45	22.46	23.5	1
1.4	16QAM	1	0	22.57	22.68	22.61	23.5	1
1.4	16QAM	1	3	22.65	22.74	22.62		
1.4	16QAM	1	5	22.59	22.67	22.57		
1.4	16QAM	3	0	22.38	22.47	22.44	23.5	1
1.4	16QAM	3	1	22.42	22.53	22.50		
1.4	16QAM	3	3	22.36	22.44	22.45		
1.4	16QAM	6	0	21.43	21.52	21.51	22.5	2
1.4	64QAM	1	0	21.50	21.58	21.61	22.5	2
1.4	64QAM	1	3	21.54	21.63	21.68		
1.4	64QAM	1	5	21.47	21.56	21.64		
1.4	64QAM	3	0	21.48	21.57	21.56	22.5	2
1.4	64QAM	3	1	21.51	21.60	21.61		
1.4	64QAM	3	3	21.47	21.55	21.55		
1.4	64QAM	6	0	20.35	20.45	20.43	21.5	3



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	23.29	23.35	23.54	24.5	0
20	QPSK	1	49	23.42	23.49	23.71		
20	QPSK	1	99	23.54	23.69	23.77		
20	QPSK	50	0	22.33	22.55	22.61	23.5	1
20	QPSK	50	24	22.48	22.56	22.80		
20	QPSK	50	50	22.51	22.60	22.81		
20	QPSK	100	0	22.46	22.56	22.75	23.5	1
20	16QAM	1	0	22.53	22.62	22.78		
20	16QAM	1	49	22.67	22.75	22.92		
20	16QAM	1	99	22.69	22.90	22.96	22.5	2
20	16QAM	50	0	21.39	21.58	21.65		
20	16QAM	50	24	21.51	21.59	21.77		
20	16QAM	50	50	21.48	21.59	21.78	22.5	2
20	16QAM	100	0	21.47	21.59	21.76		
20	64QAM	1	0	21.44	21.56	21.72		
20	64QAM	1	49	21.56	21.68	21.90	22.5	2
20	64QAM	1	99	21.61	21.82	21.92		
20	64QAM	50	0	20.36	20.55	20.62		
20	64QAM	50	24	20.52	20.61	20.80	21.5	3
20	64QAM	50	50	20.49	20.59	20.79		
20	64QAM	100	0	20.45	20.56	20.76		
Channel				20825	21100	21375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	23.29	23.50	23.56	24.5	0
15	QPSK	1	37	23.29	23.49	23.69		
15	QPSK	1	74	23.48	23.56	23.63		
15	QPSK	36	0	22.39	22.57	22.75	23.5	1
15	QPSK	36	20	22.37	22.62	22.81		
15	QPSK	36	39	22.46	22.57	22.79		
15	QPSK	75	0	22.36	22.57	22.77	23.5	1
15	16QAM	1	0	22.57	22.78	22.84		
15	16QAM	1	37	22.58	22.81	22.97		
15	16QAM	1	74	22.75	22.85	23.00	22.5	2
15	16QAM	36	0	21.38	21.54	21.75		
15	16QAM	36	20	21.42	21.57	21.81		
15	16QAM	36	39	21.49	21.60	21.76	22.5	2
15	16QAM	75	0	21.39	21.55	21.77		
15	64QAM	1	0	21.48	21.66	21.75		
15	64QAM	1	37	21.49	21.68	21.86	22.5	2
15	64QAM	1	74	21.63	21.73	21.93		
15	64QAM	36	0	20.36	20.55	20.76		
15	64QAM	36	20	20.44	20.62	20.79	21.5	3
15	64QAM	36	39	20.49	20.61	20.81		
15	64QAM	75	0	20.40	20.53	20.74		



Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	23.32	23.51	23.67	24.5	0
10	QPSK	1	25	23.31	23.50	23.71		
10	QPSK	1	49	23.43	23.54	23.69		
10	QPSK	25	0	22.34	22.51	22.73	23.5	1
10	QPSK	25	12	22.35	22.56	22.74		
10	QPSK	25	25	22.39	22.59	22.77		
10	QPSK	50	0	22.36	22.55	22.74		
10	16QAM	1	0	22.58	22.74	22.92	23.5	1
10	16QAM	1	25	22.60	22.78	22.96		
10	16QAM	1	49	22.69	22.80	22.96		
10	16QAM	25	0	21.34	21.52	21.71	22.5	2
10	16QAM	25	12	21.39	21.59	21.74		
10	16QAM	25	25	21.35	21.54	21.74		
10	16QAM	50	0	21.39	21.55	21.75		
10	64QAM	1	0	21.46	21.64	21.84	22.5	2
10	64QAM	1	25	21.49	21.69	21.88		
10	64QAM	1	49	21.60	21.72	21.89		
10	64QAM	25	0	20.34	20.52	20.70	21.5	3
10	64QAM	25	12	20.39	20.55	20.74		
10	64QAM	25	25	20.37	20.57	20.76		
10	64QAM	50	0	20.38	20.57	20.74		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	23.31	23.49	23.68	24.5	0
5	QPSK	1	12	23.32	23.49	23.67		
5	QPSK	1	24	23.35	23.52	23.72		
5	QPSK	12	0	22.36	22.52	22.71	23.5	1
5	QPSK	12	7	22.41	22.58	22.73		
5	QPSK	12	13	22.37	22.52	22.75		
5	QPSK	25	0	22.38	22.52	22.76		
5	16QAM	1	0	22.57	22.76	22.93	23.5	1
5	16QAM	1	12	22.61	22.79	22.97		
5	16QAM	1	24	22.58	22.80	22.93		
5	16QAM	12	0	21.34	21.55	21.72	22.5	2
5	16QAM	12	7	21.38	21.56	21.77		
5	16QAM	12	13	21.41	21.57	21.74		
5	16QAM	25	0	21.35	21.56	21.73		
5	64QAM	1	0	21.48	21.64	21.84	22.5	2
5	64QAM	1	12	21.49	21.67	21.84		
5	64QAM	1	24	21.50	21.71	21.91		
5	64QAM	12	0	20.36	20.54	20.75	21.5	3
5	64QAM	12	7	20.41	20.60	20.80		
5	64QAM	12	13	20.40	20.58	20.77		
5	64QAM	25	0	20.32	20.51	20.73		



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.57	23.56	23.54	24.5	0
10	QPSK	1	25	23.13	23.21	23.28		
10	QPSK	1	49	23.20	23.27	23.35		
10	QPSK	25	0	22.13	22.15	22.23	23.5	1
10	QPSK	25	12	22.19	22.28	22.29		
10	QPSK	25	25	22.25	22.31	22.33		
10	QPSK	50	0	22.23	22.25	22.22	23.5	1
10	16QAM	1	0	22.24	22.34	22.37		
10	16QAM	1	25	22.34	22.41	22.51		
10	16QAM	1	49	22.42	22.54	22.54	22.5	2
10	16QAM	25	0	21.13	21.11	21.18		
10	16QAM	25	12	21.19	21.25	21.32		
10	16QAM	25	25	21.24	21.21	21.27	22.5	2
10	16QAM	50	0	21.25	21.25	21.20		
10	64QAM	1	0	21.14	21.21	21.29		
10	64QAM	1	25	21.27	21.34	21.43	22.5	2
10	64QAM	1	49	21.32	21.42	21.46		
10	64QAM	25	0	20.16	20.12	20.19		
10	64QAM	25	12	20.18	20.26	20.33	21.5	3
10	64QAM	25	25	20.24	20.21	20.28		
10	64QAM	50	0	20.27	20.24	20.21		
Channel				23035	23095	23155	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	23.10	23.06	23.30	24.5	0
5	QPSK	1	12	23.24	23.15	23.32		
5	QPSK	1	24	23.23	23.16	23.45		
5	QPSK	12	0	22.20	22.22	22.37	23.5	1
5	QPSK	12	7	22.30	22.25	22.43		
5	QPSK	12	13	22.28	22.23	22.45		
5	QPSK	25	0	22.26	22.23	22.40	23.5	1
5	16QAM	1	0	22.37	22.28	22.57		
5	16QAM	1	12	22.47	22.41	22.60		
5	16QAM	1	24	22.43	22.43	22.66	22.5	2
5	16QAM	12	0	21.20	21.23	21.38		
5	16QAM	12	7	21.31	21.27	21.43		
5	16QAM	12	13	21.30	21.24	21.47	22.5	2
5	16QAM	25	0	21.26	21.22	21.38		
5	64QAM	1	0	21.29	21.20	21.47		
5	64QAM	1	12	21.40	21.31	21.49	22.5	2
5	64QAM	1	24	21.36	21.31	21.60		
5	64QAM	12	0	20.19	20.28	20.41		
5	64QAM	12	7	20.32	20.29	20.46	21.5	3
5	64QAM	12	13	20.30	20.27	20.50		
5	64QAM	25	0	20.27	20.23	20.37		

Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	23.10	23.16	23.32	24.5	0
3	QPSK	1	8	23.12	23.14	23.46		
3	QPSK	1	14	23.22	23.16	23.44		
3	QPSK	8	0	22.19	22.23	22.37	23.5	1
3	QPSK	8	4	22.22	22.26	22.51		
3	QPSK	8	7	22.15	22.24	22.47		
3	QPSK	15	0	22.18	22.23	22.46		
3	16QAM	1	0	22.35	22.33	22.54	23.5	1
3	16QAM	1	8	22.39	22.42	22.69		
3	16QAM	1	14	22.45	22.39	22.63		
3	16QAM	8	0	21.22	21.28	21.42	22.5	2
3	16QAM	8	4	21.27	21.31	21.53		
3	16QAM	8	7	21.20	21.29	21.51		
3	16QAM	15	0	21.21	21.26	21.46		
3	64QAM	1	0	21.28	21.28	21.46	22.5	2
3	64QAM	1	8	21.30	21.35	21.59		
3	64QAM	1	14	21.38	21.31	21.61		
3	64QAM	8	0	20.20	20.26	20.39	21.5	3
3	64QAM	8	4	20.23	20.27	20.51		
3	64QAM	8	7	20.22	20.28	20.46		
3	64QAM	15	0	20.17	20.24	20.47		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.96	23.03	23.32	24.5	0
1.4	QPSK	1	3	23.03	23.11	23.40		
1.4	QPSK	1	5	23.05	23.06	23.30		
1.4	QPSK	3	0	23.11	23.12	23.40		
1.4	QPSK	3	1	23.16	23.19	23.48		
1.4	QPSK	3	3	23.12	23.14	23.44		
1.4	QPSK	6	0	22.10	22.15	22.39	23.5	1
1.4	16QAM	1	0	22.31	22.33	22.56	23.5	1
1.4	16QAM	1	3	22.38	22.39	22.62		
1.4	16QAM	1	5	22.30	22.33	22.58		
1.4	16QAM	3	0	22.01	22.12	22.40		
1.4	16QAM	3	1	22.05	22.17	22.46		
1.4	16QAM	3	3	22.08	22.14	22.39		
1.4	16QAM	6	0	21.15	21.20	21.44	22.5	2
1.4	64QAM	1	0	21.19	21.27	21.57	22.5	2
1.4	64QAM	1	3	21.26	21.34	21.62		
1.4	64QAM	1	5	21.14	21.27	21.56		
1.4	64QAM	3	0	21.20	21.22	21.51		
1.4	64QAM	3	1	21.26	21.25	21.58		
1.4	64QAM	3	3	21.21	21.24	21.50		
1.4	64QAM	6	0	20.12	20.13	20.37	21.5	3



<LTE Band 13>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23230				
Frequency (MHz)				782				
10	QPSK	1	0	23.65			24.5	0
10	QPSK	1	25	23.56				
10	QPSK	1	49	23.58				
10	QPSK	25	0	22.52			23.5	1
10	QPSK	25	12	22.64				
10	QPSK	25	25	22.68				
10	QPSK	50	0	22.62			23.5	1
10	16QAM	1	0	22.53				
10	16QAM	1	25	22.68				
10	16QAM	1	49	22.70			22.5	2
10	16QAM	25	0	21.30				
10	16QAM	25	12	21.43				
10	16QAM	25	25	21.45			22.5	2
10	16QAM	50	0	21.40				
10	64QAM	1	0	21.44				
10	64QAM	1	25	21.52			22.5	2
10	64QAM	1	49	21.56				
10	64QAM	25	0	20.32				
10	64QAM	25	12	20.43			21.5	3
10	64QAM	25	25	20.45				
10	64QAM	50	0	20.40				
Channel				23205	23230	23255	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				779.5	782	784.5		
5	QPSK	1	0	23.29	23.26	23.25	24.5	0
5	QPSK	1	12	23.30	23.36	23.35		
5	QPSK	1	24	23.33	23.34	23.33		
5	QPSK	12	0	22.35	22.40	22.29	23.5	1
5	QPSK	12	7	22.37	22.43	22.42		
5	QPSK	12	13	22.43	22.42	22.38		
5	QPSK	25	0	22.33	22.42	22.39	23.5	1
5	16QAM	1	0	22.59	22.57	22.56		
5	16QAM	1	12	22.65	22.65	22.70		
5	16QAM	1	24	22.68	22.62	22.62	22.5	2
5	16QAM	12	0	21.34	21.39	21.28		
5	16QAM	12	7	21.37	21.46	21.46		
5	16QAM	12	13	21.44	21.39	21.38	22.5	2
5	16QAM	25	0	21.32	21.40	21.37		
5	64QAM	1	0	21.45	21.43	21.42		
5	64QAM	1	12	21.44	21.55	21.52	22.5	2
5	64QAM	1	24	21.52	21.49	21.48		
5	64QAM	12	0	20.36	20.42	20.30		
5	64QAM	12	7	20.37	20.46	20.43	21.5	3
5	64QAM	12	13	20.43	20.42	20.39		
5	64QAM	25	0	20.32	20.36	20.35		



<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23780	23790	23800	24.5	0
Frequency (MHz)				709	710	711		
10	QPSK	1	0	23.74	23.75	23.72		
10	QPSK	1	25	23.72	23.70	23.72	23.5	1
10	QPSK	1	49	23.68	23.69	23.66		
10	QPSK	25	0	22.71	22.75	22.70		
10	QPSK	25	12	22.72	22.72	22.71	23.5	1
10	QPSK	25	25	22.71	22.70	22.69		
10	QPSK	50	0	22.71	22.72	22.68		
10	16QAM	1	0	22.88	22.87	22.88	23.5	1
10	16QAM	1	25	22.94	22.93	22.91		
10	16QAM	1	49	22.92	22.90	22.86		
10	16QAM	25	0	21.68	21.67	21.65	22.5	2
10	16QAM	25	12	21.72	21.72	21.70		
10	16QAM	25	25	21.65	21.67	21.66		
10	16QAM	50	0	21.68	21.68	21.67	22.5	2
10	64QAM	1	0	21.80	21.84	21.80		
10	64QAM	1	25	21.89	21.90	21.88		
10	64QAM	1	49	21.84	21.86	21.82	21.5	3
10	64QAM	25	0	20.69	20.67	20.67		
10	64QAM	25	12	20.62	20.61	20.60		
10	64QAM	25	25	20.59	20.59	20.56	21.5	3
10	64QAM	50	0	20.61	20.58	20.54		
Channel				23755	23790	23825	24.5	0
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	23.39	23.40	23.36		
5	QPSK	1	12	23.43	23.42	23.36	23.5	1
5	QPSK	1	24	23.40	23.40	23.33		
5	QPSK	12	0	22.41	22.37	22.37		
5	QPSK	12	7	22.45	22.44	22.37	23.5	1
5	QPSK	12	13	22.44	22.41	22.37		
5	QPSK	25	0	22.43	22.42	22.36		
5	16QAM	1	0	22.60	22.59	22.61	23.5	1
5	16QAM	1	12	22.64	22.66	22.62		
5	16QAM	1	24	22.66	22.65	22.57		
5	16QAM	12	0	21.42	21.38	21.37	22.5	2
5	16QAM	12	7	21.46	21.44	21.38		
5	16QAM	12	13	21.40	21.41	21.36		
5	16QAM	25	0	21.42	21.35	21.35	22.5	2
5	64QAM	1	0	21.55	21.52	21.51		
5	64QAM	1	12	21.58	21.55	21.52		
5	64QAM	1	24	21.55	21.57	21.48	21.5	3
5	64QAM	12	0	20.45	20.41	20.39		
5	64QAM	12	7	20.50	20.45	20.42		
5	64QAM	12	13	20.43	20.41	20.38	21.5	3
5	64QAM	25	0	20.40	20.39	20.35		



<LTE Band 25>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26140	26340	26590		
Frequency (MHz)				1860	1880	1905		
20	QPSK	1	0	23.08	23.66	23.48	24	0
20	QPSK	1	49	23.07	23.48	23.47		
20	QPSK	1	99	23.07	23.35	23.42		
20	QPSK	50	0	22.06	22.68	22.64	23	1
20	QPSK	50	24	22.14	22.48	22.67		
20	QPSK	50	50	22.25	22.51	22.60		
20	QPSK	100	0	22.19	22.66	22.65		
20	16QAM	1	0	22.18	22.66	22.70	23	1
20	16QAM	1	49	22.26	22.63	22.89		
20	16QAM	1	99	22.41	22.53	22.74		
20	16QAM	50	0	21.05	21.49	21.68	22	2
20	16QAM	50	24	21.15	21.49	21.68		
20	16QAM	50	50	21.25	21.50	21.58		
20	16QAM	100	0	21.18	21.41	21.62		
20	64QAM	1	0	21.15	21.54	21.69	22	2
20	64QAM	1	49	21.29	21.61	21.90		
20	64QAM	1	99	21.37	21.58	21.73		
20	64QAM	50	0	20.04	20.47	20.63	21	3
20	64QAM	50	24	20.13	20.45	20.65		
20	64QAM	50	50	20.23	20.51	20.61		
20	64QAM	100	0	20.18	20.44	20.63		
Channel				26115	26340	26615	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1907.5		
15	QPSK	1	0	22.93	23.33	23.58	24	0
15	QPSK	1	37	23.04	23.33	23.53		
15	QPSK	1	74	23.01	23.31	23.52		
15	QPSK	36	0	22.06	22.46	22.62	23	1
15	QPSK	36	20	22.17	22.46	22.65		
15	QPSK	36	39	22.10	22.50	22.72		
15	QPSK	75	0	22.17	22.46	22.64		
15	16QAM	1	0	22.26	22.72	22.94	23	1
15	16QAM	1	37	22.29	22.67	22.87		
15	16QAM	1	74	22.33	22.50	22.77		
15	16QAM	36	0	21.07	21.46	21.63	22	2
15	16QAM	36	20	21.12	21.46	21.62		
15	16QAM	36	39	21.08	21.50	21.69		
15	16QAM	75	0	21.14	21.44	21.60		
15	64QAM	1	0	21.21	21.62	21.86	22	2
15	64QAM	1	37	21.33	21.60	21.83		
15	64QAM	1	74	21.26	21.57	21.83		
15	64QAM	36	0	20.06	20.43	20.61	21	3
15	64QAM	36	20	20.17	20.47	20.65		
15	64QAM	36	39	20.09	20.52	20.71		
15	64QAM	75	0	20.09	20.41	20.58		



Channel				26090	26340	26640	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1910		
10	QPSK	1	0	22.97	23.50	23.62	24	0
10	QPSK	1	25	23.00	23.41	23.64		
10	QPSK	1	49	23.00	23.46	23.64		
10	QPSK	25	0	22.06	22.48	22.67	23	1
10	QPSK	25	12	22.05	22.47	22.66		
10	QPSK	25	25	22.12	22.52	22.69		
10	QPSK	50	0	22.03	22.45	22.62	23	1
10	16QAM	1	0	22.25	22.80	22.86		
10	16QAM	1	25	22.26	22.65	22.92		
10	16QAM	1	49	22.19	22.59	22.78	22	2
10	16QAM	25	0	21.05	21.44	21.62		
10	16QAM	25	12	21.05	21.44	21.62		
10	16QAM	25	25	21.06	21.48	21.68	21	3
10	16QAM	50	0	21.02	21.43	21.59		
10	64QAM	1	0	21.15	21.64	21.85		
10	64QAM	1	25	21.22	21.63	21.91	22	2
10	64QAM	1	49	21.18	21.59	21.87		
10	64QAM	25	0	20.02	20.42	20.60		
10	64QAM	25	12	20.04	20.45	20.62	21	3
10	64QAM	25	25	20.07	20.49	20.68		
10	64QAM	50	0	20.03	20.44	20.60		
Channel				26065	26340	26665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1912.5		
5	QPSK	1	0	22.91	23.40	23.62	24	0
5	QPSK	1	12	23.01	23.42	23.65		
5	QPSK	1	24	22.97	23.46	23.65		
5	QPSK	12	0	21.93	22.45	22.73	23	1
5	QPSK	12	7	22.04	22.44	22.74		
5	QPSK	12	13	21.99	22.51	22.68		
5	QPSK	25	0	22.05	22.45	22.72	23	1
5	16QAM	1	0	22.17	22.66	22.86		
5	16QAM	1	12	22.26	22.66	22.84		
5	16QAM	1	24	22.13	22.59	22.72	22	2
5	16QAM	12	0	20.94	21.43	21.69		
5	16QAM	12	7	21.06	21.46	21.74		
5	16QAM	12	13	21.00	21.52	21.70	22	2
5	16QAM	25	0	21.02	21.42	21.67		
5	64QAM	1	0	21.08	21.59	21.90		
5	64QAM	1	12	21.19	21.58	21.88	22	2
5	64QAM	1	24	21.10	21.62	21.82		
5	64QAM	12	0	19.95	20.45	20.73		
5	64QAM	12	7	20.08	20.48	20.76	21	3
5	64QAM	12	13	20.03	20.55	20.71		
5	64QAM	25	0	20.01	20.39	20.66		

Channel				26055	26340	26675	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1913.5		
3	QPSK	1	0	22.87	23.40	23.63	24	0
3	QPSK	1	8	22.91	23.41	23.58		
3	QPSK	1	14	22.92	23.45	23.60		
3	QPSK	8	0	21.97	22.45	22.72	23	1
3	QPSK	8	4	21.97	22.49	22.74		
3	QPSK	8	7	21.91	22.42	22.70		
3	QPSK	15	0	21.93	22.42	22.70	23	1
3	16QAM	1	0	22.15	22.64	22.76		
3	16QAM	1	8	22.20	22.61	22.81		
3	16QAM	1	14	22.18	22.62	22.66	22	2
3	16QAM	8	0	21.00	21.49	21.76		
3	16QAM	8	4	21.00	21.51	21.78		
3	16QAM	8	7	20.95	21.47	21.75	22	2
3	16QAM	15	0	20.95	21.43	21.71		
3	64QAM	1	0	21.06	21.55	21.84	22	2
3	64QAM	1	8	21.07	21.58	21.88		
3	64QAM	1	14	21.16	21.62	21.79		
3	64QAM	8	0	19.95	20.46	20.68	21	3
3	64QAM	8	4	19.98	20.49	20.74		
3	64QAM	8	7	19.91	20.45	20.69		
3	64QAM	15	0	19.92	20.41	20.70		
Channel				26047	26340	26683	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1914.3		
1.4	QPSK	1	0	22.82	23.30	23.52	24	0
1.4	QPSK	1	3	22.87	23.36	23.56		
1.4	QPSK	1	5	22.81	23.27	23.55		
1.4	QPSK	3	0	22.91	23.40	23.62	24	0
1.4	QPSK	3	1	22.97	23.46	23.50		
1.4	QPSK	3	3	22.91	23.40	23.64		
1.4	QPSK	6	0	21.86	22.37	22.64	23	1
1.4	16QAM	1	0	22.12	22.56	22.67	23	1
1.4	16QAM	1	3	22.16	22.57	22.73		
1.4	16QAM	1	5	22.10	22.52	22.68		
1.4	16QAM	3	0	21.90	22.40	22.61	23	1
1.4	16QAM	3	1	21.95	22.42	22.64		
1.4	16QAM	3	3	21.89	22.36	22.58		
1.4	16QAM	6	0	20.93	21.43	21.70	22	2
1.4	64QAM	1	0	21.03	21.60	21.82	22	2
1.4	64QAM	1	3	21.07	21.60	21.87		
1.4	64QAM	1	5	21.00	21.57	21.78		
1.4	64QAM	3	0	21.04	21.51	21.71	22	2
1.4	64QAM	3	1	21.09	21.55	21.76		
1.4	64QAM	3	3	21.02	21.51	21.70		
1.4	64QAM	6	0	19.84	20.35	20.59	21	3



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572		
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	23.21	23.42	23.35	24	0
20	QPSK	1	49	23.11	23.41	23.24		
20	QPSK	1	99	22.97	23.19	22.96		
20	QPSK	50	0	21.95	22.34	22.25	23	1
20	QPSK	50	24	21.93	22.32	22.06		
20	QPSK	50	50	21.92	22.26	22.02		
20	QPSK	100	0	21.96	22.29	22.08		
20	16QAM	1	0	22.16	22.58	22.49	23	1
20	16QAM	1	49	22.28	22.50	22.43		
20	16QAM	1	99	22.24	22.34	22.17		
20	16QAM	50	0	20.92	21.24	21.15	22	2
20	16QAM	50	24	20.99	21.31	21.12		
20	16QAM	50	50	20.91	21.25	21.01		
20	16QAM	100	0	20.95	21.32	21.07		
20	64QAM	1	0	21.10	21.56	21.43	22	2
20	64QAM	1	49	21.24	21.59	21.44		
20	64QAM	1	99	21.13	21.36	21.15		
20	64QAM	50	0	19.91	20.25	20.15	21	3
20	64QAM	50	24	19.98	20.32	20.08		
20	64QAM	50	50	19.95	20.29	20.04		
20	64QAM	100	0	19.98	20.33	20.09		
Channel				132047	132322	132597		
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	22.89	23.26	23.16	24	0
15	QPSK	1	37	22.92	23.35	23.14		
15	QPSK	1	74	22.87	23.17	22.92		
15	QPSK	36	0	21.87	22.32	22.06	23	1
15	QPSK	36	20	21.97	22.42	22.14		
15	QPSK	36	39	21.92	22.21	21.98		
15	QPSK	75	0	21.89	22.30	22.06		
15	16QAM	1	0	22.20	22.50	22.47	23	1
15	16QAM	1	37	22.20	22.47	22.41		
15	16QAM	1	74	22.17	22.36	22.19		
15	16QAM	36	0	20.88	21.32	21.08	22	2
15	16QAM	36	20	20.96	21.38	21.17		
15	16QAM	36	39	20.91	21.24	20.98		
15	16QAM	75	0	20.85	21.31	21.05		
15	64QAM	1	0	21.16	21.53	21.41	22	2
15	64QAM	1	37	21.19	21.61	21.41		
15	64QAM	1	74	21.12	21.41	21.19		
15	64QAM	36	0	19.90	20.35	20.08	21	3
15	64QAM	36	20	19.97	20.43	20.17		
15	64QAM	36	39	19.95	20.28	20.00		
15	64QAM	75	0	19.86	20.29	20.04		



Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	22.98	23.37	23.19	24	0
10	QPSK	1	25	23.01	23.38	23.22		
10	QPSK	1	49	22.86	23.34	23.02		
10	QPSK	25	0	21.97	22.38	22.14	23	1
10	QPSK	25	12	21.95	22.37	22.11		
10	QPSK	25	25	21.91	22.31	22.04		
10	QPSK	50	0	21.93	22.34	22.08	23	1
10	16QAM	1	0	22.21	22.46	22.37		
10	16QAM	1	25	22.16	22.45	22.32		
10	16QAM	1	49	22.07	22.36	22.22	22	2
10	16QAM	25	0	20.94	21.37	21.10		
10	16QAM	25	12	20.94	21.35	21.09		
10	16QAM	25	25	20.88	21.30	21.02	22	2
10	16QAM	50	0	20.92	21.34	21.07		
10	64QAM	1	0	21.13	21.48	21.36		
10	64QAM	1	25	21.11	21.52	21.33	22	2
10	64QAM	1	49	21.00	21.40	21.18		
10	64QAM	25	0	19.94	20.37	20.11		
10	64QAM	25	12	19.93	20.35	20.09	21	3
10	64QAM	25	25	19.88	20.32	20.03		
10	64QAM	50	0	19.94	20.36	20.09		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	22.79	23.29	23.02	24	0
5	QPSK	1	12	22.94	23.36	23.11		
5	QPSK	1	24	22.76	23.20	22.92		
5	QPSK	12	0	21.91	22.33	22.04	23	1
5	QPSK	12	7	22.02	22.40	22.13		
5	QPSK	12	13	21.91	22.32	22.03		
5	QPSK	25	0	21.94	22.34	22.06	23	1
5	16QAM	1	0	22.04	22.36	22.11		
5	16QAM	1	12	22.17	22.57	22.31		
5	16QAM	1	24	21.97	22.26	22.08	22	2
5	16QAM	12	0	20.92	21.31	21.03		
5	16QAM	12	7	21.01	21.41	21.14		
5	16QAM	12	13	20.92	21.31	21.03	22	2
5	16QAM	25	0	20.92	21.30	21.01		
5	64QAM	1	0	20.98	21.41	21.13		
5	64QAM	1	12	21.13	21.57	21.27	22	2
5	64QAM	1	24	20.93	21.33	21.06		
5	64QAM	12	0	19.95	20.36	20.10		
5	64QAM	12	7	20.03	20.47	20.16	21	3
5	64QAM	12	13	19.91	20.34	20.05		
5	64QAM	25	0	19.89	20.31	20.03		



Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	22.85	23.30	22.99	24	0
3	QPSK	1	8	22.98	23.35	23.12		
3	QPSK	1	14	22.82	23.25	22.94		
3	QPSK	8	0	21.97	22.40	22.11	23	1
3	QPSK	8	4	22.02	22.45	22.17		
3	QPSK	8	7	21.95	22.38	22.10		
3	QPSK	15	0	21.97	22.36	22.08		
3	16QAM	1	0	22.03	22.31	22.18	23	1
3	16QAM	1	8	22.16	22.47	22.32		
3	16QAM	1	14	22.00	22.27	22.16		
3	16QAM	8	0	21.01	21.45	21.15	22	2
3	16QAM	8	4	21.08	21.47	21.21		
3	16QAM	8	7	20.99	21.40	21.12		
3	16QAM	15	0	20.99	21.40	21.10		
3	64QAM	1	0	20.99	21.40	21.16	22	2
3	64QAM	1	8	21.15	21.55	21.30		
3	64QAM	1	14	20.98	21.39	21.16		
3	64QAM	8	0	20.00	20.43	20.12	21	3
3	64QAM	8	4	20.04	20.50	20.19		
3	64QAM	8	7	19.99	20.44	20.12		
3	64QAM	15	0	19.96	20.39	20.10		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	22.86	23.26	23.00	24	0
1.4	QPSK	1	3	22.93	23.30	23.05		
1.4	QPSK	1	5	22.85	23.27	22.99		
1.4	QPSK	3	0	22.94	23.35	23.09		
1.4	QPSK	3	1	23.03	23.40	23.17		
1.4	QPSK	3	3	22.98	23.36	23.10		
1.4	QPSK	6	0	21.94	22.38	22.07	23	1
1.4	16QAM	1	0	22.10	22.35	22.22	23	1
1.4	16QAM	1	3	22.19	22.45	22.27		
1.4	16QAM	1	5	22.08	22.34	22.18		
1.4	16QAM	3	0	21.93	22.30	22.10		
1.4	16QAM	3	1	21.98	22.38	22.11		
1.4	16QAM	3	3	21.90	22.28	22.04		
1.4	16QAM	6	0	21.01	21.40	21.12	22	2
1.4	64QAM	1	0	21.07	21.56	21.23	22	2
1.4	64QAM	1	3	21.15	21.56	21.34		
1.4	64QAM	1	5	21.05	21.47	21.23		
1.4	64QAM	3	0	21.06	21.42	21.20		
1.4	64QAM	3	1	21.11	21.49	21.24		
1.4	64QAM	3	3	21.05	21.40	21.19		
1.4	64QAM	6	0	19.94	20.34	20.06	21	3

Reduced Power Mode

<LTE Tune-up Limit>

Band 5 Mode		Average Power (dBm)
LTE	Band 2	19.0
	Band 4	18.5
	Band 25	19.0
	Band 66	18.5

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	17.72	17.91	17.90		
20	QPSK	1	49	17.69	17.89	17.89	19	0
20	QPSK	1	99	17.71	17.86	17.88		
20	QPSK	50	0	17.87	18.06	18.12		
20	QPSK	50	24	17.89	18.17	18.16	19	0
20	QPSK	50	50	17.88	18.14	18.12		
20	QPSK	100	0	17.84	18.15	18.14		
20	16QAM	1	0	18.07	18.37	18.39	19	0
20	16QAM	1	49	18.07	18.39	18.50		
20	16QAM	1	99	18.20	18.38	18.39		
20	16QAM	50	0	17.88	18.11	18.11	19	0
20	16QAM	50	24	17.86	18.20	18.11		
20	16QAM	50	50	17.88	18.10	18.16		
20	16QAM	100	0	17.82	18.12	18.14	19	0
20	64QAM	1	0	17.96	18.17	18.27		
20	64QAM	1	49	18.00	18.31	18.28		
20	64QAM	1	99	18.05	18.30	18.24	19	0
20	64QAM	50	0	17.88	18.12	18.13		
20	64QAM	50	24	17.87	18.21	18.08		
20	64QAM	50	50	17.89	18.14	18.16	19	0
20	64QAM	100	0	17.87	18.15	18.18		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	17.87	18.16	18.18		
15	QPSK	1	37	17.88	18.20	18.24	19	0
15	QPSK	1	74	17.87	18.10	18.14		
15	QPSK	36	0	17.86	18.17	18.17	19	0
15	QPSK	36	20	17.99	18.29	18.28		
15	QPSK	36	39	18.03	18.22	18.22		
15	QPSK	75	0	17.97	18.28	18.25	19	0
15	16QAM	1	0	18.16	18.48	18.48		
15	16QAM	1	37	18.16	18.49	18.44		
15	16QAM	1	74	18.26	18.38	18.49	19	0
15	16QAM	36	0	17.88	18.19	18.19		
15	16QAM	36	20	17.95	18.29	18.30		
15	16QAM	36	39	17.99	18.21	18.24	19	0
15	16QAM	75	0	17.93	18.25	18.24		
15	64QAM	1	0	18.06	18.39	18.37		
15	64QAM	1	37	18.07	18.40	18.46	19	0
15	64QAM	1	74	18.08	18.29	18.34		
15	64QAM	36	0	17.90	18.17	18.17		
15	64QAM	36	20	17.99	18.33	18.31	19	0
15	64QAM	36	39	18.02	18.25	18.25		
15	64QAM	75	0	17.94	18.25	18.26		



Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	17.87	18.12	18.14	19	0
10	QPSK	1	25	17.90	18.22	18.24		
10	QPSK	1	49	17.83	18.15	18.15		
10	QPSK	25	0	17.87	18.27	18.28	19	0
10	QPSK	25	12	17.99	18.26	18.26		
10	QPSK	25	25	17.92	18.24	18.24		
10	QPSK	50	0	17.96	18.26	18.27		
10	16QAM	1	0	18.21	18.49	18.45	19	0
10	16QAM	1	25	18.21	18.48	18.49		
10	16QAM	1	49	18.13	18.40	18.42		
10	16QAM	25	0	17.85	18.26	18.27	19	0
10	16QAM	25	12	17.97	18.27	18.28		
10	16QAM	25	25	17.90	18.21	18.22		
10	16QAM	50	0	17.96	18.25	18.28		
10	64QAM	1	0	18.06	18.29	18.39	19	0
10	64QAM	1	25	18.07	18.41	18.43		
10	64QAM	1	49	17.97	18.28	18.39		
10	64QAM	25	0	17.91	18.30	18.28	19	0
10	64QAM	25	12	18.00	18.32	18.28		
10	64QAM	25	25	17.94	18.24	18.25		
10	64QAM	50	0	17.98	18.29	18.27		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	17.78	18.00	18.09	19	0
5	QPSK	1	12	17.78	18.18	18.04		
5	QPSK	1	24	17.81	18.10	18.01		
5	QPSK	12	0	17.94	18.14	18.13	19	0
5	QPSK	12	7	17.91	18.29	18.18		
5	QPSK	12	13	17.90	18.23	18.21		
5	QPSK	25	0	17.84	18.23	18.27		
5	16QAM	1	0	18.14	18.40	18.48	19	0
5	16QAM	1	12	18.15	18.49	18.48		
5	16QAM	1	24	18.27	18.46	18.49		
5	16QAM	12	0	17.93	18.16	18.13	19	0
5	16QAM	12	7	17.94	18.21	18.14		
5	16QAM	12	13	17.93	18.11	18.19		
5	16QAM	25	0	17.82	18.22	18.24		
5	64QAM	1	0	18.02	18.22	18.33	19	0
5	64QAM	1	12	18.04	18.39	18.35		
5	64QAM	1	24	18.15	18.36	18.34		
5	64QAM	12	0	17.96	18.20	18.22	19	0
5	64QAM	12	7	17.91	18.31	18.16		
5	64QAM	12	13	17.98	18.18	18.19		
5	64QAM	25	0	17.91	18.17	18.18		



Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	17.72	17.96	18.15	19	0
3	QPSK	1	8	17.85	18.10	18.09		
3	QPSK	1	14	17.83	18.12	18.11		
3	QPSK	8	0	17.96	18.13	18.19	19	0
3	QPSK	8	4	17.89	18.23	18.19		
3	QPSK	8	7	17.94	18.20	18.19		
3	QPSK	15	0	17.87	18.15	18.26		
3	16QAM	1	0	18.14	18.40	18.46	19	0
3	16QAM	1	8	18.11	18.43	18.47		
3	16QAM	1	14	18.20	18.45	18.49		
3	16QAM	8	0	17.91	18.16	18.12	19	0
3	16QAM	8	4	17.89	18.25	18.20		
3	16QAM	8	7	17.90	18.16	18.26		
3	16QAM	15	0	17.84	18.22	18.18		
3	64QAM	1	0	17.99	18.26	18.36	19	0
3	64QAM	1	8	18.04	18.40	18.33		
3	64QAM	1	14	18.13	18.36	18.26		
3	64QAM	8	0	17.92	18.14	18.18	19	0
3	64QAM	8	4	17.95	18.25	18.18		
3	64QAM	8	7	17.99	18.19	18.22		
3	64QAM	15	0	17.94	18.18	18.19		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	17.80	17.95	18.14	19	0
1.4	QPSK	1	3	17.86	18.09	18.12		
1.4	QPSK	1	5	17.84	18.14	18.04		
1.4	QPSK	3	0	17.97	18.06	18.16		
1.4	QPSK	3	1	17.92	18.27	18.20		
1.4	QPSK	3	3	17.88	18.20	18.15		
1.4	QPSK	6	0	17.94	18.24	18.31	19	0
1.4	16QAM	1	0	18.13	18.41	18.48	19	0
1.4	16QAM	1	3	18.13	18.42	18.40		
1.4	16QAM	1	5	18.26	18.47	18.41		
1.4	16QAM	3	0	17.89	18.15	18.16		
1.4	16QAM	3	1	17.95	18.26	18.21		
1.4	16QAM	3	3	17.92	18.14	18.20		
1.4	16QAM	6	0	17.83	18.17	18.21	19	0
1.4	64QAM	1	0	18.01	18.19	18.29	19	0
1.4	64QAM	1	3	18.05	18.37	18.34		
1.4	64QAM	1	5	18.08	18.37	18.26		
1.4	64QAM	3	0	17.92	18.19	18.16		
1.4	64QAM	3	1	17.97	18.31	18.11		
1.4	64QAM	3	3	17.93	18.23	18.20		
1.4	64QAM	6	0	17.96	18.25	18.27	19	0



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	17.97	18.22	18.30	18.5	0
20	QPSK	1	49	18.10	18.35	18.30		
20	QPSK	1	99	18.17	18.23	18.25		
20	QPSK	50	0	18.12	18.46	18.44	18.5	0
20	QPSK	50	24	18.21	18.39	18.44		
20	QPSK	50	50	18.24	18.42	18.42		
20	QPSK	100	0	18.16	18.36	18.40	18.5	0
20	16QAM	1	0	18.26	18.49	18.49		
20	16QAM	1	49	18.43	18.50	18.48		
20	16QAM	1	99	18.49	18.45	18.45	18.5	0
20	16QAM	50	0	18.11	18.28	18.46		
20	16QAM	50	24	18.22	18.40	18.45		
20	16QAM	50	50	18.22	18.42	18.46	18.5	0
20	16QAM	100	0	18.17	18.32	18.41		
20	64QAM	1	0	18.19	18.47	18.49		
20	64QAM	1	49	18.36	18.45	18.47	18.5	0
20	64QAM	1	99	18.41	18.45	18.46		
20	64QAM	50	0	18.13	18.33	18.45		
20	64QAM	50	24	18.23	18.42	18.44	18.5	0
20	64QAM	50	50	18.27	18.41	18.47		
20	64QAM	100	0	18.21	18.36	18.43		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	17.98	18.24	18.38	18.5	0
15	QPSK	1	37	18.07	18.32	18.34		
15	QPSK	1	74	18.10	18.29	18.31		
15	QPSK	36	0	18.09	18.40	18.41	18.5	0
15	QPSK	36	20	18.12	18.38	18.43		
15	QPSK	36	39	18.16	18.31	18.45		
15	QPSK	75	0	18.10	18.33	18.40	18.5	0
15	16QAM	1	0	18.30	18.45	18.45		
15	16QAM	1	37	18.36	18.46	18.49		
15	16QAM	1	74	18.43	18.48	18.45	18.5	0
15	16QAM	36	0	18.11	18.41	18.47		
15	16QAM	36	20	18.09	18.39	18.43		
15	16QAM	36	39	18.17	18.32	18.45	18.5	0
15	16QAM	75	0	18.09	18.34	18.42		
15	64QAM	1	0	18.19	18.47	18.46		
15	64QAM	1	37	18.24	18.49	18.45	18.5	0
15	64QAM	1	74	18.32	18.47	18.49		
15	64QAM	36	0	18.15	18.42	18.48		
15	64QAM	36	20	18.17	18.40	18.49	18.5	0
15	64QAM	36	39	18.19	18.34	18.49		
15	64QAM	75	0	18.08	18.35	18.41		



Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	18.00	18.25	18.30	18.5	0
10	QPSK	1	25	18.07	18.33	18.37		
10	QPSK	1	49	18.08	18.24	18.26		
10	QPSK	25	0	18.12	18.38	18.32	18.5	0
10	QPSK	25	12	18.11	18.37	18.44		
10	QPSK	25	25	18.10	18.32	18.35		
10	QPSK	50	0	18.11	18.35	18.40		
10	16QAM	1	0	18.32	18.45	18.47	18.5	0
10	16QAM	1	25	18.37	18.46	18.46		
10	16QAM	1	49	18.41	18.43	18.45		
10	16QAM	25	0	18.11	18.37	18.30	18.5	0
10	16QAM	25	12	18.11	18.38	18.43		
10	16QAM	25	25	18.06	18.30	18.36		
10	16QAM	50	0	18.11	18.36	18.40		
10	64QAM	1	0	18.06	18.45	18.44	18.5	0
10	64QAM	1	25	18.12	18.44	18.47		
10	64QAM	1	49	18.20	18.39	18.42		
10	64QAM	25	0	17.99	18.43	18.40	18.5	0
10	64QAM	25	12	18.03	18.36	18.49		
10	64QAM	25	25	18.10	18.36	18.37		
10	64QAM	50	0	17.97	18.39	18.29		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	17.97	18.31	18.36	18.5	0
5	QPSK	1	12	17.97	18.34	18.35		
5	QPSK	1	24	18.03	18.25	18.29		
5	QPSK	12	0	18.03	18.37	18.39	18.5	0
5	QPSK	12	7	18.07	18.40	18.41		
5	QPSK	12	13	18.08	18.34	18.34		
5	QPSK	25	0	17.99	18.36	18.36		
5	16QAM	1	0	18.29	18.45	18.45	18.5	0
5	16QAM	1	12	18.32	18.45	18.40		
5	16QAM	1	24	18.33	18.46	18.46		
5	16QAM	12	0	18.03	18.39	18.38	18.5	0
5	16QAM	12	7	18.07	18.42	18.42		
5	16QAM	12	13	18.11	18.36	18.36		
5	16QAM	25	0	18.00	18.35	18.36		
5	64QAM	1	0	18.16	18.45	18.45	18.5	0
5	64QAM	1	12	18.17	18.46	18.42		
5	64QAM	1	24	18.22	18.46	18.47		
5	64QAM	12	0	18.06	18.43	18.46	18.5	0
5	64QAM	12	7	18.08	18.44	18.49		
5	64QAM	12	13	18.14	18.40	18.39		
5	64QAM	25	0	18.03	18.39	18.38		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	17.90	18.30	18.31	18.5	0
3	QPSK	1	8	17.95	18.28	18.33		
3	QPSK	1	14	18.00	18.23	18.25		
3	QPSK	8	0	18.01	18.31	18.38	18.5	0
3	QPSK	8	4	18.04	18.34	18.34		
3	QPSK	8	7	18.03	18.27	18.24		
3	QPSK	15	0	17.97	18.30	18.29	18.5	0
3	16QAM	1	0	18.20	18.45	18.45		
3	16QAM	1	8	18.26	18.46	18.50		
3	16QAM	1	14	18.32	18.45	18.48	18.5	0
3	16QAM	8	0	18.02	18.33	18.32		
3	16QAM	8	4	18.00	18.37	18.32		
3	16QAM	8	7	18.03	18.28	18.31	18.5	0
3	16QAM	15	0	17.93	18.26	18.32		
3	64QAM	1	0	18.07	18.47	18.45		
3	64QAM	1	8	18.07	18.46	18.41	18.5	0
3	64QAM	1	14	18.14	18.38	18.40		
3	64QAM	8	0	18.05	18.42	18.42		
3	64QAM	8	4	17.98	18.40	18.49	18.5	0
3	64QAM	8	7	18.04	18.37	18.30		
3	64QAM	15	0	17.94	18.35	18.30		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	17.88	18.29	18.31	18.5	0
1.4	QPSK	1	3	17.92	18.31	18.33		
1.4	QPSK	1	5	17.98	18.25	18.22		
1.4	QPSK	3	0	17.99	18.33	18.35	18.5	0
1.4	QPSK	3	1	18.04	18.36	18.40		
1.4	QPSK	3	3	18.05	18.34	18.27		
1.4	QPSK	6	0	17.97	18.28	18.26	18.5	0
1.4	16QAM	1	0	18.27	18.45	18.40	18.5	0
1.4	16QAM	1	3	18.31	18.46	18.45		
1.4	16QAM	1	5	18.28	18.47	18.50		
1.4	16QAM	3	0	17.93	18.38	18.30	18.5	0
1.4	16QAM	3	1	17.99	18.33	18.39		
1.4	16QAM	3	3	18.03	18.32	18.32		
1.4	16QAM	6	0	17.90	18.33	18.34	18.5	0
1.4	64QAM	1	0	18.08	18.42	18.45	18.5	0
1.4	64QAM	1	3	18.08	18.49	18.42		
1.4	64QAM	1	5	18.14	18.45	18.41		
1.4	64QAM	3	0	18.03	18.43	18.41	18.5	0
1.4	64QAM	3	1	17.99	18.37	18.40		
1.4	64QAM	3	3	18.09	18.37	18.33		
1.4	64QAM	6	0	18.03	18.36	18.29	18.5	0



<LTE Band 25>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26140	26340	26590		
Frequency (MHz)				1860	1880	1905		
20	QPSK	1	0	17.65	18.10	18.09	19	0
20	QPSK	1	49	17.61	18.06	18.05		
20	QPSK	1	99	17.60	18.07	18.06		
20	QPSK	50	0	17.81	18.19	18.20	19	0
20	QPSK	50	24	17.91	18.19	18.22		
20	QPSK	50	50	17.99	18.25	18.23		
20	QPSK	100	0	17.95	18.19	18.18	19	0
20	16QAM	1	0	17.99	18.46	18.45		
20	16QAM	1	49	18.12	18.43	18.81		
20	16QAM	1	99	18.27	18.42	18.70	19	0
20	16QAM	50	0	17.79	18.22	18.43		
20	16QAM	50	24	17.86	18.22	18.40		
20	16QAM	50	50	17.98	18.23	18.30	19	0
20	16QAM	100	0	17.92	18.16	18.32		
20	64QAM	1	0	17.82	18.31	18.46		
20	64QAM	1	49	18.01	18.29	18.52	19	0
20	64QAM	1	99	18.06	18.27	18.49		
20	64QAM	50	0	17.84	18.18	18.37		
20	64QAM	50	24	17.88	18.20	18.38	19	0
20	64QAM	50	50	17.98	18.22	18.32		
20	64QAM	100	0	17.99	18.17	18.35		
Channel				26115	26340	26615	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1907.5		
15	QPSK	1	0	17.80	18.19	18.50	19	0
15	QPSK	1	37	17.91	18.23	18.42		
15	QPSK	1	74	17.89	18.21	18.47		
15	QPSK	36	0	17.88	18.29	18.45	19	0
15	QPSK	36	20	18.02	18.29	18.49		
15	QPSK	36	39	17.93	18.34	18.57		
15	QPSK	75	0	17.97	18.30	18.47	19	0
15	16QAM	1	0	18.12	18.50	18.70		
15	16QAM	1	37	18.21	18.51	18.76		
15	16QAM	1	74	18.26	18.47	18.70	19	0
15	16QAM	36	0	17.89	18.29	18.45		
15	16QAM	36	20	17.98	18.31	18.43		
15	16QAM	36	39	17.91	18.32	18.49	19	0
15	16QAM	75	0	17.96	18.25	18.43		
15	64QAM	1	0	17.93	18.38	18.66		
15	64QAM	1	37	18.08	18.38	18.61	19	0
15	64QAM	1	74	18.11	18.38	18.64		
15	64QAM	36	0	17.91	18.29	18.45		
15	64QAM	36	20	18.02	18.32	18.48	19	0
15	64QAM	36	39	17.94	18.35	18.52		
15	64QAM	75	0	17.93	18.25	18.39		



Channel				26090	26340	26640	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1910		
10	QPSK	1	0	17.79	18.25	18.43	19	0
10	QPSK	1	25	17.85	18.22	18.53		
10	QPSK	1	49	17.84	18.24	18.39		
10	QPSK	25	0	17.91	18.30	18.50	19	0
10	QPSK	25	12	17.90	18.28	18.49		
10	QPSK	25	25	17.97	18.34	18.56		
10	QPSK	50	0	17.88	18.29	18.48	19	0
10	16QAM	1	0	18.14	18.59	18.80		
10	16QAM	1	25	18.11	18.53	18.80		
10	16QAM	1	49	18.15	18.50	18.80	19	0
10	16QAM	25	0	17.88	18.29	18.44		
10	16QAM	25	12	17.90	18.28	18.43		
10	16QAM	25	25	17.91	18.31	18.49	19	0
10	16QAM	50	0	17.87	18.27	18.44		
10	64QAM	1	0	17.94	18.43	18.65		
10	64QAM	1	25	18.06	18.40	18.67	19	0
10	64QAM	1	49	18.02	18.37	18.70		
10	64QAM	25	0	17.95	18.30	18.45		
10	64QAM	25	12	17.93	18.29	18.41	19	0
10	64QAM	25	25	17.93	18.32	18.49		
10	64QAM	50	0	17.92	18.27	18.44		
Channel				26065	26340	26665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1912.5		
5	QPSK	1	0	17.71	18.11	18.40	19	0
5	QPSK	1	12	17.87	18.16	18.42		
5	QPSK	1	24	17.85	18.17	18.41		
5	QPSK	12	0	17.80	18.26	18.45	19	0
5	QPSK	12	7	17.95	18.22	18.48		
5	QPSK	12	13	17.84	18.26	18.54		
5	QPSK	25	0	17.97	18.27	18.40	19	0
5	16QAM	1	0	18.04	18.46	18.71		
5	16QAM	1	12	18.18	18.44	18.70		
5	16QAM	1	24	18.16	18.37	18.77	19	0
5	16QAM	12	0	17.85	18.21	18.42		
5	16QAM	12	7	17.91	18.27	18.39		
5	16QAM	12	13	17.89	18.27	18.49	19	0
5	16QAM	25	0	17.95	18.16	18.38		
5	64QAM	1	0	17.89	18.31	18.59		
5	64QAM	1	12	18.00	18.37	18.57	19	0
5	64QAM	1	24	18.09	18.28	18.62		
5	64QAM	12	0	17.90	18.27	18.37		
5	64QAM	12	7	17.94	18.23	18.42	19	0
5	64QAM	12	13	17.90	18.28	18.50		
5	64QAM	25	0	17.86	18.25	18.32		



Channel				26055	26340	26675	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1913.5		
3	QPSK	1	0	17.74	18.12	18.50	19	0
3	QPSK	1	8	17.86	18.13	18.40		
3	QPSK	1	14	17.88	18.14	18.42		
3	QPSK	8	0	17.86	18.20	18.39	19	0
3	QPSK	8	4	18.00	18.21	18.40		
3	QPSK	8	7	17.89	18.30	18.53		
3	QPSK	15	0	17.97	18.27	18.45		
3	16QAM	1	0	18.10	18.44	18.76	19	0
3	16QAM	1	8	18.13	18.44	18.69		
3	16QAM	1	14	18.20	18.38	18.75		
3	16QAM	8	0	17.89	18.23	18.43	19	0
3	16QAM	8	4	17.91	18.22	18.41		
3	16QAM	8	7	17.81	18.28	18.46		
3	16QAM	15	0	17.93	18.22	18.38		
3	64QAM	1	0	17.92	18.37	18.60	19	0
3	64QAM	1	8	18.08	18.29	18.57		
3	64QAM	1	14	18.02	18.30	18.56		
3	64QAM	8	0	17.91	18.24	18.40	19	0
3	64QAM	8	4	17.97	18.22	18.40		
3	64QAM	8	7	17.86	18.26	18.52		
3	64QAM	15	0	17.93	18.19	18.32		
Channel				26047	26340	26683	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1914.3		
1.4	QPSK	1	0	17.78	18.18	18.43	19	0
1.4	QPSK	1	3	17.86	18.21	18.38		
1.4	QPSK	1	5	17.88	18.11	18.44		
1.4	QPSK	3	0	17.86	18.28	18.45		
1.4	QPSK	3	1	17.98	18.20	18.40		
1.4	QPSK	3	3	17.90	18.30	18.53		
1.4	QPSK	6	0	17.96	18.25	18.40	19	0
1.4	16QAM	1	0	18.04	18.43	18.80	19	0
1.4	16QAM	1	3	18.21	18.46	18.75		
1.4	16QAM	1	5	18.19	18.46	18.76		
1.4	16QAM	3	0	17.88	18.22	18.45		
1.4	16QAM	3	1	17.97	18.21	18.42		
1.4	16QAM	3	3	17.82	18.27	18.44		
1.4	16QAM	6	0	17.89	18.20	18.38	19	0
1.4	64QAM	1	0	17.85	18.32	18.65	19	0
1.4	64QAM	1	3	18.01	18.36	18.52		
1.4	64QAM	1	5	18.01	18.29	18.62		
1.4	64QAM	3	0	17.91	18.28	18.36		
1.4	64QAM	3	1	17.95	18.29	18.47		
1.4	64QAM	3	3	17.86	18.30	18.46		
1.4	64QAM	6	0	17.86	18.22	18.39	19	0

<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572	18.5	0
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	18.01	18.33	18.23	18.5	0
20	QPSK	1	49	18.14	18.46	18.25		
20	QPSK	1	99	18.01	18.19	17.97		
20	QPSK	50	0	17.97	18.28	18.20	18.5	0
20	QPSK	50	24	18.07	18.37	18.14		
20	QPSK	50	50	18.02	18.32	18.07		
20	QPSK	100	0	18.03	18.35	18.15	18.5	0
20	16QAM	1	0	18.30	18.45	18.50		
20	16QAM	1	49	18.42	18.49	18.49		
20	16QAM	1	99	18.33	18.48	18.29	18.5	0
20	16QAM	50	0	17.96	18.30	18.20		
20	16QAM	50	24	18.04	18.35	18.15		
20	16QAM	50	50	17.97	18.29	18.07	18.5	0
20	16QAM	100	0	18.01	18.33	18.14		
20	64QAM	1	0	18.23	18.45	18.45		
20	64QAM	1	49	18.35	18.49	18.47	18.5	0
20	64QAM	1	99	18.23	18.44	18.21		
20	64QAM	50	0	17.97	18.30	18.19		
20	64QAM	50	24	18.04	18.35	18.13	18.5	0
20	64QAM	50	50	18.02	18.31	18.07		
20	64QAM	100	0	18.03	18.36	18.14		
Channel				132047	132322	132597	18.5	0
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	18.02	18.33	18.21	18.5	0
15	QPSK	1	37	18.08	18.45	18.22		
15	QPSK	1	74	17.98	18.24	18.00		
15	QPSK	36	0	17.91	18.32	18.08	18.5	0
15	QPSK	36	20	18.01	18.44	18.19		
15	QPSK	36	39	17.98	18.27	18.02		
15	QPSK	75	0	17.93	18.34	18.09	18.5	0
15	16QAM	1	0	18.31	18.45	18.45		
15	16QAM	1	37	18.35	18.44	18.45		
15	16QAM	1	74	18.27	18.46	18.34	18.5	0
15	16QAM	36	0	17.89	18.31	18.11		
15	16QAM	36	20	18.00	18.43	18.19		
15	16QAM	36	39	17.92	18.28	18.03	18.5	0
15	16QAM	75	0	17.91	18.32	18.09		
15	64QAM	1	0	18.20	18.44	18.41		
15	64QAM	1	37	18.23	18.46	18.40	18.5	0
15	64QAM	1	74	18.15	18.43	18.23		
15	64QAM	36	0	17.92	18.38	18.14		
15	64QAM	36	20	18.00	18.43	18.18	18.5	0
15	64QAM	36	39	17.99	18.30	18.06		
15	64QAM	75	0	17.89	18.32	18.08		

Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	18.00	18.28	18.15	18.5	0
10	QPSK	1	25	17.99	18.38	18.14		
10	QPSK	1	49	17.89	18.26	18.00		
10	QPSK	25	0	17.98	18.38	18.15	18.5	0
10	QPSK	25	12	17.94	18.39	18.14		
10	QPSK	25	25	17.94	18.31	18.08		
10	QPSK	50	0	17.98	18.35	18.11	18.5	0
10	16QAM	1	0	18.30	18.45	18.49		
10	16QAM	1	25	18.30	18.45	18.42		
10	16QAM	1	49	18.18	18.46	18.32	18.5	0
10	16QAM	25	0	17.94	18.38	18.13		
10	16QAM	25	12	17.93	18.37	18.13		
10	16QAM	25	25	17.91	18.31	18.07	18.5	0
10	16QAM	50	0	17.96	18.34	18.10		
10	64QAM	1	0	17.97	18.32	18.16		
10	64QAM	1	25	18.17	18.40	18.28	18.5	0
10	64QAM	1	49	17.92	18.30	18.01		
10	64QAM	25	0	17.92	18.38	18.05		
10	64QAM	25	12	17.96	18.39	18.15	18.5	0
10	64QAM	25	25	17.93	18.38	17.99		
10	64QAM	50	0	17.93	18.27	18.06		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	17.84	18.23	17.97	18.5	0
5	QPSK	1	12	18.00	18.38	18.13		
5	QPSK	1	24	17.78	18.16	17.90		
5	QPSK	12	0	17.95	18.33	18.08	18.5	0
5	QPSK	12	7	18.03	18.40	18.14		
5	QPSK	12	13	17.93	18.30	18.04		
5	QPSK	25	0	17.94	18.35	18.06	18.5	0
5	16QAM	1	0	18.15	18.45	18.28		
5	16QAM	1	12	18.30	18.46	18.44		
5	16QAM	1	24	18.09	18.44	18.23	18.5	0
5	16QAM	12	0	17.95	18.33	18.07		
5	16QAM	12	7	18.07	18.43	18.17		
5	16QAM	12	13	17.94	18.31	18.06	18.5	0
5	16QAM	25	0	17.91	18.32	18.06		
5	64QAM	1	0	18.04	18.42	18.18		
5	64QAM	1	12	18.18	18.46	18.28	18.5	0
5	64QAM	1	24	17.97	18.33	18.08		
5	64QAM	12	0	17.96	18.41	18.13		
5	64QAM	12	7	18.06	18.48	18.23	18.5	0
5	64QAM	12	13	17.93	18.38	18.09		
5	64QAM	25	0	17.93	18.33	18.07		



Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	17.74	18.14	17.94	18.5	0
3	QPSK	1	8	17.94	18.33	18.09		
3	QPSK	1	14	17.77	18.14	17.90		
3	QPSK	8	0	17.91	18.31	18.06	18.5	0
3	QPSK	8	4	17.96	18.30	18.12		
3	QPSK	8	7	17.91	18.25	17.96		
3	QPSK	15	0	17.84	18.29	18.01		
3	16QAM	1	0	18.15	18.48	18.21	18.5	0
3	16QAM	1	8	18.30	18.44	18.37		
3	16QAM	1	14	18.04	18.34	18.23		
3	16QAM	8	0	17.85	18.31	17.99	18.5	0
3	16QAM	8	4	17.98	18.41	18.17		
3	16QAM	8	7	17.89	18.23	18.02		
3	16QAM	15	0	17.86	18.24	17.98		
3	64QAM	1	0	17.99	18.34	18.09	18.5	0
3	64QAM	1	8	18.08	18.45	18.19		
3	64QAM	1	14	17.94	18.23	18.07		
3	64QAM	8	0	17.90	18.38	18.07	18.5	0
3	64QAM	8	4	18.00	18.40	18.17		
3	64QAM	8	7	17.90	18.29	18.02		
3	64QAM	15	0	17.84	18.30	18.06		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	17.76	18.14	17.93	18.5	0
1.4	QPSK	1	3	17.95	18.28	18.13		
1.4	QPSK	1	5	17.76	18.15	17.86		
1.4	QPSK	3	0	17.93	18.33	17.98		
1.4	QPSK	3	1	17.97	18.36	18.07		
1.4	QPSK	3	3	17.85	18.20	18.04		
1.4	QPSK	6	0	17.92	18.34	18.02	18.5	0
1.4	16QAM	1	0	18.10	18.47	18.27	18.5	0
1.4	16QAM	1	3	18.30	18.42	18.42		
1.4	16QAM	1	5	18.08	18.37	18.17		
1.4	16QAM	3	0	17.85	18.31	17.99		
1.4	16QAM	3	1	17.97	18.34	18.11		
1.4	16QAM	3	3	17.88	18.24	18.01		
1.4	16QAM	6	0	17.88	18.24	18.03	18.5	0
1.4	64QAM	1	0	18.00	18.38	18.08	18.5	0
1.4	64QAM	1	3	18.10	18.40	18.18		
1.4	64QAM	1	5	17.94	18.32	18.06		
1.4	64QAM	3	0	17.86	18.38	18.09		
1.4	64QAM	3	1	18.05	18.44	18.18		
1.4	64QAM	3	3	17.90	18.38	18.00		
1.4	64QAM	6	0	17.91	18.31	18.06	18.5	0

<LTE Carrier Aggregation>

General Note:

1. This device supports Carrier Aggregation on downlink only for Intra band and Inter-Band, Uplink CA is not supported. For the device supports bands and bandwidths and configurations are provided as follow table was according to 3GPP.
2. All permutations exist. No restrictions on Pcell & Scell combinations. Only LTE Band 29A is limited to Scell.

<Intra-Band combinations>

E-UTRA CA configuration	E-UTRA CA configuration / Bandwidth combination set			
	Component carriers in order of increasing carrier frequency		Maximum aggregated bandwidth [MHz]	Bandwidth combination set
	Channel bandwidths for carrier [MHz]	Channel bandwidths for carrier [MHz]		
CA_7B	15	5	20	0
CA_7C	15	15	40	0
	20	20		
	10	20		
	15	15, 20	40	1
	20	10, 15, 20		
	15	10, 15		
	20	15, 20	40	2
CA_66B	5	5, 10, 15	20	0
	10	5, 10		
	15	5		
CA_66C	5	20	40	0
	10	15, 20		
	15	10, 15, 20		
	20	5, 10, 15, 20		
CA_12B	5	5, 10	15	0

E-UTRACA configuration	E-UTRA CA configuration / Bandwidth combination set			
	Component carriers in order of increasing carrier frequency		Maximum aggregated bandwidth [MHz]	Bandwidth combination set
	Channel bandwidths for carrier [MHz]	Channel bandwidths for carrier [MHz]		
CA_2A-2A	5, 10, 15, 20	5, 10, 15, 20	40	0
CA_4A-4A	5, 10, 15, 20	5, 10, 15, 20	40	0
	5, 10	5, 10	20	1
CA_7A-7A	5	15	40	0
	10	10, 15		
	15	15, 20		
	20	20		
	5, 10, 15, 20	5, 10, 15, 20	40	1
	5, 10, 15, 20	5, 10	30	2
	10, 15, 20	10, 15, 20	40	3
CA_25A-25A	5, 10	5, 10	20	0
	5, 10, 15, 20	5, 10, 15, 20	40	1
CA_66A-66A	5, 10, 15, 20	5, 10, 15, 20	40	0



<Inter-Band combinations>

E-UTRA CA configuration / Bandwidth combination set									
E-UTRA CA Configuration	E- UTRA Bands	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	Maximum aggregated bandwidth [MHz]	Bandwidth combination set
CA_2A-4A	2	Yes	Yes	Yes	Yes	Yes	Yes	40	0
	4			Yes	Yes	Yes	Yes		
	2			Yes	Yes			20	1
	4			Yes	Yes				
	2			Yes	Yes	Yes	Yes	40	2
	4			Yes	Yes	Yes	Yes		
CA_2A-66A	2	Yes	Yes	Yes	Yes	Yes	Yes	40	0
	66			Yes	Yes	Yes	Yes		
	2			Yes	Yes			20	1
	66			Yes	Yes				
	2			Yes	Yes	Yes	Yes	40	2
	66			Yes	Yes	Yes	Yes		
CA_2A-5A	2			Yes	Yes	Yes	Yes	30	0
	5			Yes	Yes				
	2			Yes	Yes			20	1
	5			Yes	Yes				
CA_2A-7A	2			Yes	Yes	Yes	Yes	40	0
	7			Yes	Yes	Yes	Yes		
CA_2A-12A	2			Yes	Yes	Yes	Yes	30	0
	12			Yes	Yes				
	2			Yes	Yes	Yes	Yes	30	1
	12		Yes	Yes	Yes				
	2			Yes	Yes			20	2
	12			Yes	Yes				
CA_2A-13A	2			Yes	Yes	Yes	Yes	30	0
	13				Yes				
	2			Yes	Yes			20	1
	13				Yes				
CA_2A-17A	2			Yes	Yes			20	0
	17			Yes	Yes				
CA_2A-29A	2			Yes	Yes			20	0
	29		Yes	Yes	Yes				
	2			Yes	Yes			20	1
	29			Yes	Yes				
	2			Yes	Yes	Yes	Yes	30	2
	29			Yes	Yes				
CA_4A-5A	4			Yes	Yes			20	0
	5			Yes	Yes				
	4			Yes	Yes	Yes	Yes	30	1
	5			Yes	Yes				
CA_4A-7A	4			Yes	Yes			30	0
	7			Yes	Yes	Yes	Yes		
	4			Yes	Yes	Yes	Yes	40	1
	7			Yes	Yes	Yes	Yes		



E-UTRA CA configuration / Bandwidth combination set									
E-UTRA CA Configuration	E-UTRA Bands	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	Maximum aggregated bandwidth [MHz]	Bandwidth combination set
CA_4A-12A	4	Yes	Yes	Yes	Yes			20	0
	12			Yes	Yes				
	4	Yes	Yes	Yes	Yes	Yes	Yes	30	1
	12			Yes	Yes				
	4			Yes	Yes	Yes	Yes	30	2
	12		Yes	Yes	Yes				
	4			Yes	Yes			20	3
	12			Yes	Yes				
	4			Yes	Yes	Yes	Yes	30	4
	12			Yes	Yes				
	4			Yes	Yes	Yes		20	5
	12			Yes					
CA_4A-13A	4			Yes	Yes	Yes	Yes	30	0
	13				Yes				
	4			Yes	Yes			20	1
	13				Yes				
CA_4A-17A	4			Yes	Yes			20	0
	17			Yes	Yes				
CA_4A-29A	4			Yes	Yes			20	0
	29		Yes	Yes	Yes				
	4			Yes	Yes			20	1
	29			Yes	Yes				
	4			Yes	Yes	Yes	Yes	30	2
	29			Yes	Yes				
CA_5A-7A	5	Yes	Yes	Yes	Yes			30	0
	7				Yes	Yes	Yes		
	5			Yes	Yes			30	1
	7				Yes	Yes	Yes		
CA_5A-25A	5			Yes	Yes			30	0
	25			Yes	Yes	Yes	Yes		
CA_7A-12A	7			Yes	Yes	Yes	Yes	30	0
	12			Yes	Yes				
CA_12A-25A	12			Yes	Yes			30	0
	25			Yes	Yes	Yes	Yes		
CA_12A-66A	12			Yes	Yes			20	0
	66	Yes	Yes	Yes	Yes				
	12			Yes	Yes			30	1
	66	Yes	Yes	Yes	Yes	Yes	Yes		
	12		Yes	Yes	Yes			30	2
	66			Yes	Yes	Yes	Yes		
	12			Yes	Yes			20	3
	66			Yes	Yes				
	12			Yes	Yes			30	4
	66			Yes	Yes	Yes	Yes		
	12			Yes				20	5
	66			Yes	Yes	Yes			



E-UTRA CA configuration / Bandwidth combination set										
E-UTRA CA Configuration	E-UTRA Bands	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	Maximum aggregated bandwidth [MHz]	Bandwidth combination set	
CA_2A-4A-5A	2			Yes	Yes	Yes	Yes	50	0	
	4			Yes	Yes	Yes	Yes			
	5			Yes	Yes					
CA_2A-4A-7A	2			Yes	Yes	Yes	Yes	60	0	
	4			Yes	Yes	Yes	Yes			
	7			Yes	Yes	Yes	Yes			
CA_2A-4A-12A	2			Yes	Yes	Yes	Yes	50	0	
	4			Yes	Yes	Yes	Yes			
	12			Yes	Yes					
CA_2A-4A-29A	2			Yes	Yes	Yes	Yes	50	0	
	4			Yes	Yes	Yes	Yes			
	29			Yes	Yes					
CA_2A-7A-7A	2			Yes	Yes	Yes	Yes	60	0	
	7	See the CA_7A-7A Bandwidth combination set 1 in Table 5.4.2A.1-3								
CA_2A-7A-12A	2			Yes	Yes	Yes	Yes	50	0	
	7			Yes	Yes	Yes	Yes			
	12			Yes	Yes					
CA_2A-12B	2			Yes	Yes	Yes	Yes	35	0	
	12	See CA_12B Bandwidth Combination set 0 in Table 5.4.2A.1-1								
CA_4A-4A-12A	4	See CA_4A-4A Bandwidth Combination set 0 in Table 5.4.2A.1-3							50	0
	12			Yes	Yes					
CA_4A-4A-29A	4	See CA_4A-4A Bandwidth combination set 0 in Table 5.4.2A.1-3							50	0
	29			Yes	Yes					
CA_4A-7A-7A	4			Yes	Yes	Yes	Yes	60	0	
	7	See the CA_7A-7A Bandwidth combination set 1 in Table 5.4.2A.1-3								
CA_4A-7A-12A	4			Yes	Yes			40	0	
	7			Yes	Yes	Yes	Yes			
	12			Yes	Yes					
	4			Yes	Yes	Yes	Yes	50	1	
	7			Yes	Yes	Yes	Yes			
	12			Yes	Yes					
CA_4A-12B	4			Yes	Yes	Yes	Yes	35	0	
	12	See CA_12B Bandwidth Combination set 0 in Table 5.4.2A.1-1								
CA_12A-66B	12			Yes	Yes			30	0	
	66	See CA_66B Bandwidth combination set 0 in Table 5.4.2A.1-1								
CA_12A-66C	12			Yes	Yes			50	0	
	66	See CA_66C Bandwidth combination set 0 in Table 5.4.2A.1-1								
CA_12A-66A-66A	12			Yes	Yes			50	0	
	66	See CA_66A-66A Bandwidth combination set 0 in Table 5.4.2A.1-3								

LTE Carrier Aggregation Conducted Power

General Note:

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink carrier aggregation only. Uplink carrier aggregation is not supported. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For non-contiguous Intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band. For SCC DL RB size and offset will base on the PCC corresponding RB allocation.
- vi. For Inter-band CA, the SCC selected highest bandwidth and near the middle of its transmission band.
- vii. For Intra-band, contiguous CA, the downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements.

$$\text{Nominal channel spacing} = \left\lceil \frac{BW_{\text{Channel}(1)} + BW_{\text{Channel}(2)} - 0.1|BW_{\text{Channel}(1)} - BW_{\text{Channel}(2)}|}{0.6} \right\rceil 0.3 \text{ [MHz]}$$



<Two Carrier power verification>

Configure		PCC						SCC				Power		
		LTE Band	BW (MHz)	UL Freq. (MHz)	UL Channel	Mod.	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	With CA Tx.Power (dBm)	W/O CA Tx.Power (dBm)
Inter-Band		2	20	1880	18900	QPSK	1	0	4	20	2132.5	2175	23.88	23.95
		4	20	1732.5	20175	QPSK	1	0	2	20	1960	900	23.71	23.75
		2	20	1880	18900	QPSK	1	0	66	20	2155	66886	23.90	23.95
		66	20	1745	132322	QPSK	1	0	2	20	1960	900	23.39	23.42
		2	20	1880	18900	QPSK	1	0	5	10	881.5	2525	23.88	23.95
		5	10	836.5	20525	QPSK	1	0	2	20	1960	900	23.60	23.64
		2	20	1880	18900	QPSK	1	0	7	20	2655	3100	23.89	23.95
		7	20	2560	21350	QPSK	1	99	2	20	1960	900	23.75	23.77
		2	20	1880	18900	QPSK	1	0	12	10	737.5	5095	23.95	23.95
		12	10	704	23060	QPSK	1	0	2	20	1960	900	23.55	23.57
		2	20	1880	18900	QPSK	1	0	13	10	751	5230	23.90	23.95
		13	10	782	23230	QPSK	1	0	2	20	1960	900	23.58	23.65
		2	5	1907.5	19175	QPSK	1	0	17	10	740	5790	23.92	23.94
		17	10	710	23790	QPSK	1	0	2	10	1960	900	23.74	23.75
		2	20	1880	18900	QPSK	1	0	29	10	722.5	9715	23.89	23.95
		4	20	1732.5	20175	QPSK	1	0	5	10	881.5	2525	23.72	23.75
		5	10	836.5	20525	QPSK	1	0	4	20	2132.5	2175	23.60	23.64
		4	20	1732.5	20175	QPSK	1	0	7	20	2655	3100	23.65	23.75
		7	20	2560	21350	QPSK	1	99	4	20	2132.5	2175	23.71	23.77
		4	20	1732.5	20175	QPSK	1	0	12	10	737.5	5095	23.74	23.75
		12	10	704	23060	QPSK	1	0	4	20	2132.5	2175	23.48	23.57
		4	20	1732.5	20175	QPSK	1	0	13	10	751	5230	23.74	23.75
		13	10	782	23230	QPSK	1	0	4	20	2132.5	2175	23.63	23.65
		4	10	1732.5	20175	QPSK	1	12	17	10	740	5790	23.62	23.63
		17	10	710	23790	QPSK	1	0	4	10	2132.5	2175	23.85	23.94
		4	20	1732.5	20175	QPSK	1	0	29	10	722.5	9715	23.72	23.75
		5	10	836.5	20525	QPSK	1	0	7	20	2655	3100	23.57	23.64
		7	20	2560	21350	QPSK	1	99	5	10	881.5	2525	23.67	23.77
		5	10	836.5	20525	QPSK	1	0	25	20	1960	8340	23.58	23.64
		25	20	1880	26340	QPSK	1	0	5	10	881.5	2525	23.64	23.66
		7	20	2560	21350	QPSK	1	99	12	10	737.5	5095	23.76	23.77
		12	10	704	23060	QPSK	1	0	7	20	2655	3100	23.49	23.57
		12	10	704	23060	QPSK	1	0	66	20	2155	66886	23.57	23.57
		66	20	1745	132322	QPSK	1	0	12	10	737.5	5095	23.36	23.42
		12	10	704	23060	QPSK	1	0	25	20	1960	8340	23.47	23.57
		25	20	1880	26340	QPSK	1	0	12	10	737.5	5095	23.64	23.66
Intra-Band	Non-Contiguous	2	20	1880	18900	QPSK	1	0	2	5	1987.5	1175	23.72	23.75
		4	20	1732.5	20175	QPSK	1	0	4	5	2152.5	2375	23.75	23.75
		7	20	2560	21350	QPSK	1	99	7	5	2622.5	2775	23.67	23.77
		25	20	1880	26340	QPSK	1	0	25	5	1992.5	8665	23.62	23.66
		66	20	1745	132322	QPSK	1	0	66	5	2197.5	67311	23.41	23.42
	Contiguous	7	20	2560	21350	QPSK	1	99	7	20	2660.20	3152	23.77	23.77
		7	5	2567.5	21425	QPSK	1	24	7	15	2678.20	3332	23.64	23.72
		12	10	704	23060	QPSK	1	0	12	5	741.20	5132	23.56	23.57
		66	20	1745	132322	QPSK	1	0	66	20	2164.80	66984	23.35	23.42
66	10	1745	132322	QPSK	1	25	66	10	2154.30	66879	23.37	23.38		



<Three Carrier power verification>

Configure	PCC							SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Freq. (MHz)	UL Channel	Mod.	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	With CA Tx.Power (dBm)	W/O CA Tx.Power (dBm)
Inter-Band	2	20	1880	18900	QPSK	1	0	4	20	2132.5	2175	5	10	881.5	2525	23.94	23.95
	4	20	1732.5	20175	QPSK	1	0	2	20	1960	900	5	10	881.5	2525	23.75	23.75
	5	10	836.5	20525	QPSK	1	0	2	20	1960	900	4	20	2132.5	2175	23.54	23.64
	2	20	1880	18900	QPSK	1	0	4	20	2132.5	2175	7	20	2655	3100	23.86	23.95
	4	20	1732.5	20175	QPSK	1	0	2	20	1960	900	7	20	2655	3100	23.65	23.75
	7	20	2560	21350	QPSK	1	99	2	20	1960	900	4	20	2132.5	2175	23.67	23.77
	2	20	1880	18900	QPSK	1	0	4	20	2132.5	2175	12	10	737.5	5095	23.90	23.95
	4	20	1732.5	20175	QPSK	1	0	2	20	1960	900	12	10	737.5	5095	23.70	23.75
	12	10	704	23060	QPSK	1	0	2	20	1960	900	4	20	2132.5	2175	23.47	23.57
	2	20	1880	18900	QPSK	1	0	4	20	2132.5	2175	29	10	722.5	9715	23.85	23.95
	4	20	1732.5	20175	QPSK	1	0	2	20	1960	900	29	10	722.5	9715	23.75	23.75
	2	20	1880	18900	QPSK	1	0	7	20	2655	3100	7	5	2687.5	3425	23.92	23.95
	7	20	2560	21350	QPSK	1	99	7	5	2622.5	2775	2	20	1960	900	23.71	23.77
	2	20	1880	18900	QPSK	1	0	7	20	2655	3100	12	10	737.5	5095	23.92	23.95
	7	20	2560	21350	QPSK	1	99	2	20	1960	900	12	10	737.5	5095	23.72	23.77
	12	10	704	23060	QPSK	1	0	2	20	1960	900	7	20	2655	3100	23.49	23.57
	2	20	1880	18900	QPSK	1	0	12	10	740	5120	12	5	732.8	5048	23.90	23.95
	12	10	704	23060	QPSK	1	0	12	5	741.2	5132	2	20	1960	900	23.57	23.57
	4	20	1732.5	20175	QPSK	1	0	4	5	2152.5	2375	12	10	737.5	5095	23.68	23.75
	12	10	704	23060	QPSK	1	0	4	20	2132.5	2175	4	5	2152.5	2375	23.52	23.57
	4	20	1732.5	20175	QPSK	1	0	4	5	2152.5	2375	29	10	722.5	9715	23.70	23.75
	4	20	1732.5	20175	QPSK	1	0	7	20	2655	3100	7	5	2687.5	3425	23.72	23.75
	7	20	2560	21350	QPSK	1	99	7	5	2622.5	2775	4	20	2132.5	2175	23.77	23.77
	4	20	1732.5	20175	QPSK	1	0	7	20	2655	3100	12	10	737.5	5095	23.73	23.75
	7	20	2560	21350	QPSK	1	99	4	20	2132.5	2175	12	10	737.5	5095	23.76	23.77
	12	10	704	23060	QPSK	1	0	4	20	2132.5	2175	7	20	2655	3100	23.47	23.57
	4	20	1732.5	20175	QPSK	1	0	12	10	740	5120	12	5	732.8	5048	23.66	23.75
	12	10	704	23060	QPSK	1	0	12	5	741.2	5132	4	20	2132.5	2175	23.56	23.57
	12	10	704	23060	QPSK	1	0	66	20	2155	66886	66	20	2174.8	67084	23.47	23.57
	66	20	1745	132322	QPSK	1	0	66	20	2164.8	66984	12	10	737.5	5095	23.42	23.42
	12	10	707.5	23095	QPSK	1	0	66	10	2155	66886	66	10	2164.3	66979	23.49	23.57
	66	10	1745	132322	QPSK	1	25	66	10	2154.3	66879	12	10	737.5	5095	23.33	23.38
	12	10	707.5	23095	QPSK	1	0	66	20	2155	66886	66	5	2197.5	67311	23.54	23.57
	66	20	1745	132322	QPSK	1	0	66	5	2197.5	67311	12	10	737.5	5095	23.38	23.42

**<WLAN Conducted Power>****General Note:**

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	15.91	16.00	99.03
		6	2437	15.66	16.00	
		11	2462	15.56	16.00	
	802.11g 6Mbps	1	2412	13.96	14.00	94.39
		6	2437	13.94	14.00	
		11	2462	13.65	14.00	
	802.11n-HT20 MCS0	1	2412	13.81	14.00	94.00
		6	2437	13.76	14.00	
		11	2462	13.55	14.00	
	802.11ac-VHT20 MCS0	1	2412	13.79	14.00	94.06
		6	2437	13.75	14.00	
		11	2462	13.51	14.00	

<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	16.98	17.00	94.87
		40	5200	16.88	17.00	
		44	5220	16.83	17.00	
		48	5240	16.68	17.00	
	802.11n-HT20 MCS0	36	5180	13.87	14.00	95.00
		40	5200	13.85	14.00	
		44	5220	13.83	14.00	
		48	5240	13.82	14.00	
	802.11n-HT40 MCS0	38	5190	12.98	13.00	90.59
		46	5230	12.73	13.00	
	802.11ac-VHT20 MCS0	36	5180	13.84	14.00	94.55
		40	5200	13.83	14.00	
		44	5220	13.82	14.00	
		48	5240	13.81	14.00	
	802.11ac-VHT40 MCS0	38	5190	12.97	13.00	91.23
		46	5230	12.70	13.00	
	802.11ac-VHT80 MCS0	42	5210	11.99	12.00	89.78

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	16.63	17.00	94.87
		56	5280	16.72	17.00	
		60	5300	16.93	17.00	
		64	5320	16.95	17.00	
	802.11n-HT20 MCS0	52	5260	13.84	14.00	95.00
		56	5280	13.83	14.00	
		60	5300	13.85	14.00	
		64	5320	13.86	14.00	
	802.11n-HT40 MCS0	54	5270	12.68	13.00	90.59
		62	5310	12.75	13.00	
	802.11ac-VHT20 MCS0	52	5260	13.54	14.00	94.55
		56	5280	13.55	14.00	
		60	5300	13.57	14.00	
		64	5320	13.82	14.00	
	802.11ac-VHT40 MCS0	54	5270	12.67	13.00	91.23
		62	5310	12.69	13.00	
	802.11ac-VHT80 MCS0	58	5290	11.94	12.00	89.78

5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	16.94	17.00	94.87
		116	5580	16.89	17.00	
		124	5620	16.85	17.00	
		132	5660	16.80	17.00	
		144	5720	16.58	17.00	
	802.11n-HT20 MCS0	100	5500	13.79	14.00	95.00
		116	5580	13.60	14.00	
		124	5620	13.59	14.00	
		132	5660	13.58	14.00	
		144	5720	13.55	14.00	
	802.11n-HT40 MCS0	102	5510	12.93	13.00	90.59
		110	5550	12.83	13.00	
		126	5630	12.80	13.00	
		134	5670	12.78	13.00	
		142	5710	12.76	13.00	
	802.11ac-VHT20 MCS0	100	5500	13.76	14.00	94.55
		116	5580	13.59	14.00	
		124	5620	13.57	14.00	
		132	5660	13.56	14.00	
		144	5720	13.52	14.00	
	802.11ac-VHT40 MCS0	102	5510	12.90	13.00	91.23
		110	5550	12.76	13.00	
		126	5630	12.75	13.00	
		134	5670	12.73	13.00	
		142	5710	12.71	13.00	
	802.11ac-VHT80 MCS0	106	5530	11.69	12.00	89.78
		122	5610	11.65	12.00	
		138	5690	11.62	12.00	

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a MCS0	149	5745	16.78	17.00	94.87
		157	5785	16.71	17.00	
		165	5825	16.65	17.00	
	802.11n-HT20 MCS0	149	5745	13.88	14.00	95.00
		157	5785	13.82	14.00	
		165	5825	13.72	14.00	
	802.11n-HT40 MCS0	151	5755	12.95	13.00	90.59
		159	5795	12.63	13.00	
	802.11ac-VHT20 MCS0	149	5745	13.87	14.00	94.55
		157	5785	13.79	14.00	
		165	5825	13.70	14.00	
	802.11ac-VHT40 MCS0	151	5755	12.90	13.00	91.23
		159	5795	12.57	13.00	
	802.11ac-VHT80 MCS0	155	5775	11.87	12.00	89.78


<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	9.43	6.05	6.07
	CH 39	2441	8.76	5.52	5.54
	CH 78	2480	8.81	5.62	5.64
Tune-up Limit			10.50	7.00	7.00

Mode	Channel	Frequency (MHz)	Average power (dBm)	
			1Mbps	2Mbps
LE	CH 00	2402	-0.24	-0.38
	CH 19	2440	-0.59	-0.81
	CH 39	2480	0.53	0.50
Tune-up Limit			1.50	1.50

General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps (BR), due to its highest average power.
2. The Bluetooth duty cycle is 77.13 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the theoretical duty cycle is 83.3%, therefore the actual duty cycle will be scaled up to the theoretical value of Bluetooth reported SAR calculation



13. RF Exposure Conditions

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge
- The detail antenna location please refers to Appendix D.

14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. When hotspot mode is enabled, power reduction will be activated to limit the maximum power of GSM1900, WCDMA B2/B4 and LTE B2/B4/B25/B66.
5. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
6. In this report, the 10g SAR results which is submitted voluntarily.

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.
3. Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 4 Tx slots due to its highest frame-average power.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq 1/4$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $1/4$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4/B5/B12/B17 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 17 SAR test was covered by Band 12; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

14.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	251	848.8	27.74	28.50	1.191	0.05	0.432	0.515	0.313	0.373
	GSM850	GPRS (4 Tx slots)	Right Tilted	0mm	251	848.8	27.74	28.50	1.191	0.01	0.233	0.278	0.188	0.224
	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	251	848.8	27.74	28.50	1.191	-0.02	0.457	0.544	0.360	0.429
	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	128	824.2	27.56	28.50	1.242	-0.01	0.384	0.477	0.301	0.374
01	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	189	836.4	27.63	28.50	1.222	-0.01	0.459	0.561	0.361	0.441
	GSM850	GPRS (4 Tx slots)	Left Tilted	0mm	251	848.8	27.74	28.50	1.191	-0.08	0.226	0.269	0.180	0.214
	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	810	1909.8	25.40	25.50	1.023	0.07	0.139	0.142	0.092	0.094
	GSM1900	GPRS (4 Tx slots)	Right Tilted	0mm	810	1909.8	25.40	25.50	1.023	-0.04	0.066	0.068	0.043	0.044
	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	810	1909.8	25.40	25.50	1.023	0.11	0.276	0.282	0.183	0.187
02	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	512	1850.2	25.10	25.50	1.096	0.18	0.485	0.532	0.326	0.357
	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	661	1880	25.17	25.50	1.079	0.08	0.401	0.433	0.268	0.289
	GSM1900	GPRS (4 Tx slots)	Left Tilted	0mm	810	1909.8	25.40	25.50	1.023	0.1	0.065	0.067	0.043	0.044

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9400	1880	24.19	24.50	1.074	-0.01	0.360	0.387	0.238	0.256
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	9400	1880	24.19	24.50	1.074	0.02	0.179	0.192	0.119	0.128
03	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9400	1880	24.19	24.50	1.074	0.06	0.663	0.712	0.444	0.477
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9262	1852.4	24.11	24.50	1.094	0.1	0.618	0.676	0.421	0.461
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9538	1907.6	23.92	24.50	1.143	-0.05	0.594	0.679	0.396	0.453
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	9400	1880	24.19	24.50	1.074	0.12	0.137	0.147	0.092	0.099
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	1513	1752.6	24.04	24.50	1.112	0.06	0.414	0.460	0.276	0.307
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	1513	1752.6	24.04	24.50	1.112	0.02	0.202	0.225	0.135	0.150
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1513	1752.6	24.04	24.50	1.112	0	0.722	0.803	0.495	0.550
04	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1312	1712.4	23.77	24.50	1.183	-0.06	0.686	0.812	0.472	0.558
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1413	1732.6	24.01	24.50	1.119	-0.03	0.704	0.788	0.483	0.541
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	1513	1752.6	24.04	24.50	1.112	0.01	0.174	0.193	0.116	0.129
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4182	836.4	24.34	25.00	1.164	0.02	0.457	0.532	0.334	0.389
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	4182	836.4	24.34	25.00	1.164	-0.07	0.249	0.290	0.202	0.235
05	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4182	836.4	24.34	25.00	1.164	0.03	0.464	0.540	0.363	0.423
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4132	826.4	24.21	25.00	1.199	0.08	0.412	0.494	0.325	0.390
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4233	846.6	24.28	25.00	1.180	0.05	0.454	0.536	0.356	0.420
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	4182	836.4	24.34	25.00	1.164	0.01	0.194	0.226	0.147	0.171



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	18900	1880	23.95	24.50	1.135	-0.04	0.325	0.369	0.211	0.239
	LTE Band 2	20M	QPSK	50	0	Right Cheek	0mm	18900	1880	23.22	23.50	1.067	-0.05	0.266	0.284	0.174	0.186
	LTE Band 2	20M	QPSK	1	0	Right Tilted	0mm	18900	1880	23.95	24.50	1.135	-0.13	0.169	0.192	0.113	0.128
	LTE Band 2	20M	QPSK	50	0	Right Tilted	0mm	18900	1880	23.22	23.50	1.067	0.02	0.144	0.154	0.094	0.100
	LTE Band 2	20M	QPSK	1	0	Left Cheek	0mm	18900	1880	23.95	24.50	1.135	0.07	0.503	0.571	0.335	0.380
06	LTE Band 2	20M	QPSK	1	0	Left Cheek	0mm	18700	1860	23.51	24.50	1.256	0.05	0.503	0.632	0.336	0.422
	LTE Band 2	20M	QPSK	1	0	Left Cheek	0mm	19100	1900	23.84	24.50	1.164	-0.01	0.512	0.596	0.338	0.393
	LTE Band 2	20M	QPSK	50	0	Left Cheek	0mm	18900	1880	23.22	23.50	1.067	0.03	0.425	0.453	0.282	0.301
	LTE Band 2	20M	QPSK	1	0	Left Tilted	0mm	18900	1880	23.95	24.50	1.135	0.09	0.155	0.176	0.103	0.117
	LTE Band 2	20M	QPSK	50	0	Left Tilted	0mm	18900	1880	23.22	23.50	1.067	-0.04	0.125	0.133	0.084	0.090
	LTE Band 4	20M	QPSK	1	0	Right Cheek	0mm	20175	1732.5	23.75	24.50	1.189	0.17	0.289	0.343	0.195	0.232
	LTE Band 4	20M	QPSK	50	0	Right Cheek	0mm	20175	1732.5	22.86	23.50	1.159	-0.13	0.241	0.279	0.163	0.189
	LTE Band 4	20M	QPSK	1	0	Right Tilted	0mm	20175	1732.5	23.75	24.50	1.189	0.13	0.165	0.196	0.105	0.125
	LTE Band 4	20M	QPSK	50	0	Right Tilted	0mm	20175	1732.5	22.86	23.50	1.159	0.05	0.134	0.155	0.086	0.100
07	LTE Band 4	20M	QPSK	1	0	Left Cheek	0mm	20175	1732.5	23.75	24.50	1.189	-0.06	0.564	0.670	0.382	0.454
	LTE Band 4	20M	QPSK	50	0	Left Cheek	0mm	20175	1732.5	22.86	23.50	1.159	-0.11	0.478	0.554	0.325	0.377
	LTE Band 4	20M	QPSK	1	0	Left Tilted	0mm	20175	1732.5	23.75	24.50	1.189	0.09	0.214	0.254	0.117	0.139
	LTE Band 4	20M	QPSK	50	0	Left Tilted	0mm	20175	1732.5	22.86	23.50	1.159	-0.11	0.149	0.173	0.081	0.094
	LTE Band 4	20M	QPSK	1	0	Left Cheek	0mm	20175	1732.5	23.75	24.50	1.189	0.02	0.538	0.639	0.365	0.434
08	LTE Band 5	10M	QPSK	1	0	Right Cheek	0mm	20525	836.5	23.64	24.50	1.219	0.01	0.399	0.486	0.316	0.385
	LTE Band 5	10M	QPSK	25	0	Right Cheek	0mm	20525	836.5	22.58	23.50	1.236	0.08	0.314	0.388	0.251	0.310
	LTE Band 5	10M	QPSK	1	0	Right Tilted	0mm	20525	836.5	23.64	24.50	1.219	-0.06	0.220	0.268	0.178	0.217
	LTE Band 5	10M	QPSK	25	0	Right Tilted	0mm	20525	836.5	22.58	23.50	1.236	-0.17	0.183	0.226	0.148	0.183
	LTE Band 5	10M	QPSK	1	0	Left Cheek	0mm	20525	836.5	23.64	24.50	1.219	-0.05	0.359	0.438	0.283	0.345
	LTE Band 5	10M	QPSK	25	0	Left Cheek	0mm	20525	836.5	22.58	23.50	1.236	0.02	0.300	0.371	0.237	0.293
	LTE Band 5	10M	QPSK	1	0	Left Tilted	0mm	20525	836.5	23.64	24.50	1.219	0.06	0.189	0.230	0.153	0.187
	LTE Band 5	10M	QPSK	25	0	Left Tilted	0mm	20525	836.5	22.58	23.50	1.236	0.05	0.158	0.195	0.128	0.158
	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	21350	2560	23.77	24.50	1.183	-0.04	0.273	0.323	0.134	0.159
09	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	20850	2510	23.54	24.50	1.247	0.14	0.339	0.423	0.171	0.213
	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	21100	2535	23.69	24.50	1.205	0.01	0.311	0.375	0.156	0.188
	LTE Band 7	20M	QPSK	50	50	Right Cheek	0mm	21350	2560	22.81	23.50	1.172	0.13	0.236	0.277	0.117	0.137
	LTE Band 7	20M	QPSK	1	99	Right Tilted	0mm	21350	2560	23.77	24.50	1.183	-0.18	0.031	0.037	0.017	0.020
	LTE Band 7	20M	QPSK	50	50	Right Tilted	0mm	21350	2560	22.81	23.50	1.172	0.16	0.026	0.030	0.014	0.016
	LTE Band 7	20M	QPSK	1	99	Left Cheek	0mm	21350	2560	23.77	24.50	1.183	0.17	0.077	0.091	0.038	0.045
	LTE Band 7	20M	QPSK	50	50	Left Cheek	0mm	21350	2560	22.81	23.50	1.172	0.11	0.074	0.087	0.037	0.043
	LTE Band 7	20M	QPSK	1	99	Left Tilted	0mm	21350	2560	23.77	24.50	1.183	0.08	0.036	0.043	0.017	0.020
	LTE Band 7	20M	QPSK	50	50	Left Tilted	0mm	21350	2560	22.81	23.50	1.172	0.13	0.032	0.038	0.014	0.016
10	LTE Band 12	10M	QPSK	1	0	Right Cheek	0mm	23095	707.5	23.56	24.50	1.242	0.05	0.091	0.113	0.074	0.092
	LTE Band 12	10M	QPSK	25	25	Right Cheek	0mm	23095	707.5	22.31	23.50	1.315	0.05	0.079	0.104	0.064	0.084
	LTE Band 12	10M	QPSK	1	0	Right Tilted	0mm	23095	707.5	23.56	24.50	1.242	-0.01	0.059	0.073	0.036	0.045
	LTE Band 12	10M	QPSK	25	25	Right Tilted	0mm	23095	707.5	22.31	23.50	1.315	0.04	0.045	0.059	0.028	0.037
	LTE Band 12	10M	QPSK	1	0	Left Cheek	0mm	23095	707.5	23.56	24.50	1.242	-0.01	0.088	0.109	0.070	0.087
	LTE Band 12	10M	QPSK	25	25	Left Cheek	0mm	23095	707.5	22.31	23.50	1.315	0.02	0.071	0.093	0.057	0.075
	LTE Band 12	10M	QPSK	1	0	Left Tilted	0mm	23095	707.5	23.56	24.50	1.242	0.07	0.057	0.071	0.042	0.052
	LTE Band 12	10M	QPSK	25	25	Left Tilted	0mm	23095	707.5	22.31	23.50	1.315	-0.01	0.043	0.057	0.032	0.042



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 13	10M	QPSK	1	0	Right Cheek	0mm	23230	782	23.65	24.50	1.216	0.03	0.213	0.259	0.171	0.208
	LTE Band 13	10M	QPSK	25	25	Right Cheek	0mm	23230	782	22.68	23.50	1.208	0.01	0.187	0.226	0.152	0.184
	LTE Band 13	10M	QPSK	1	0	Right Tilted	0mm	23230	782	23.65	24.50	1.216	0	0.081	0.099	0.068	0.083
	LTE Band 13	10M	QPSK	25	25	Right Tilted	0mm	23230	782	22.68	23.50	1.208	0.01	0.075	0.091	0.062	0.075
11	LTE Band 13	10M	QPSK	1	0	Left Cheek	0mm	23230	782	23.65	24.50	1.216	-0.03	0.217	0.264	0.173	0.210
	LTE Band 13	10M	QPSK	25	25	Left Cheek	0mm	23230	782	22.68	23.50	1.208	-0.02	0.192	0.232	0.153	0.185
	LTE Band 13	10M	QPSK	1	0	Left Tilted	0mm	23230	782	23.65	24.50	1.216	-0.09	0.081	0.099	0.068	0.083
	LTE Band 13	10M	QPSK	25	25	Left Tilted	0mm	23230	782	22.68	23.50	1.208	-0.05	0.075	0.091	0.062	0.075
	LTE Band 25	20M	QPSK	1	0	Right Cheek	0mm	26340	1880	23.66	24.00	1.081	-0.03	0.298	0.322	0.196	0.212
	LTE Band 25	20M	QPSK	50	0	Right Cheek	0mm	26340	1880	22.68	23.00	1.076	-0.01	0.245	0.264	0.160	0.172
	LTE Band 25	20M	QPSK	1	0	Right Tilted	0mm	26340	1880	23.66	24.00	1.081	0.16	0.158	0.171	0.103	0.111
	LTE Band 25	20M	QPSK	50	0	Right Tilted	0mm	26340	1880	22.68	23.00	1.076	0.09	0.131	0.141	0.086	0.093
	LTE Band 25	20M	QPSK	1	0	Left Cheek	0mm	26340	1880	23.66	24.00	1.081	0.1	0.501	0.542	0.335	0.362
12	LTE Band 25	20M	QPSK	1	0	Left Cheek	0mm	26140	1860	23.08	24.00	1.236	0.07	0.477	0.590	0.319	0.394
	LTE Band 25	20M	QPSK	1	0	Left Cheek	0mm	26590	1905	23.48	24.00	1.127	0.04	0.488	0.550	0.323	0.364
	LTE Band 25	20M	QPSK	50	0	Left Cheek	0mm	26340	1880	22.68	23.00	1.076	0.06	0.405	0.436	0.269	0.290
	LTE Band 25	20M	QPSK	1	0	Left Tilted	0mm	26340	1880	23.66	24.00	1.081	0.04	0.131	0.142	0.089	0.096
	LTE Band 25	20M	QPSK	50	0	Left Tilted	0mm	26340	1880	22.68	23.00	1.076	-0.01	0.111	0.119	0.075	0.081
	LTE Band 66	20M	QPSK	1	0	Right Cheek	0mm	132322	1745	23.42	24.00	1.143	0.04	0.275	0.314	0.186	0.213
	LTE Band 66	20M	QPSK	50	0	Right Cheek	0mm	132322	1745	22.34	23.00	1.164	0.1	0.218	0.254	0.147	0.171
	LTE Band 66	20M	QPSK	1	0	Right Tilted	0mm	132322	1745	23.42	24.00	1.143	-0.03	0.141	0.161	0.090	0.103
	LTE Band 66	20M	QPSK	50	0	Right Tilted	0mm	132322	1745	22.34	23.00	1.164	0.17	0.108	0.126	0.069	0.080
	LTE Band 66	20M	QPSK	1	0	Left Cheek	0mm	132322	1745	23.42	24.00	1.143	-0.14	0.538	0.615	0.367	0.419
	LTE Band 66	20M	QPSK	1	0	Left Cheek	0mm	132072	1720	23.21	24.00	1.199	-0.04	0.517	0.620	0.352	0.422
13	LTE Band 66	20M	QPSK	1	0	Left Cheek	0mm	132572	1770	23.35	24.00	1.161	0	0.556	0.646	0.378	0.439
	LTE Band 66	20M	QPSK	50	0	Left Cheek	0mm	132322	1745	22.34	23.00	1.164	0.01	0.442	0.515	0.299	0.348
	LTE Band 66	20M	QPSK	1	0	Left Tilted	0mm	132322	1745	23.42	24.00	1.143	-0.04	0.172	0.197	0.093	0.106
	LTE Band 66	20M	QPSK	50	0	Left Tilted	0mm	132322	1745	22.34	23.00	1.164	0.06	0.128	0.149	0.069	0.080



<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	1	2412	15.91	16.00	1.021	99.03	1.010	-0.11	0.240	0.247	0.108	0.111
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	1	2412	15.91	16.00	1.021	99.03	1.010	0.02	0.197	0.203	0.091	0.094
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	1	2412	15.91	16.00	1.021	99.03	1.010	-0.17	0.602	0.621	0.271	0.279
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	6	2437	15.66	16.00	1.081	99.03	1.010	-0.1	0.644	0.703	0.292	0.319
14	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	11	2462	15.56	16.00	1.107	99.03	1.010	-0.16	0.653	0.730	0.293	0.327
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	1	2412	15.91	16.00	1.021	99.03	1.010	-0.12	0.457	0.471	0.197	0.203
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	64	5320	16.95	17.00	1.012	94.87	1.054	0.14	0.133	0.142	0.039	0.042
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	64	5320	16.95	17.00	1.012	94.87	1.054	0.17	0.080	0.085	0.022	0.023
15	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	64	5320	16.95	17.00	1.012	94.87	1.054	-0.06	0.368	0.392	0.117	0.125
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	56	5280	16.72	17.00	1.067	94.87	1.054	-0.13	0.341	0.383	0.106	0.119
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	64	5320	16.95	17.00	1.012	94.87	1.054	0.13	0.181	0.193	0.068	0.073
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	100	5500	16.94	17.00	1.014	94.87	1.054	-0.03	0.177	0.189	0.054	0.058
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	100	5500	16.94	17.00	1.014	94.87	1.054	0.11	0.114	0.122	0.036	0.038
16	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	100	5500	16.94	17.00	1.014	94.87	1.054	-0.03	0.482	0.515	0.154	0.165
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	116	5580	16.89	17.00	1.026	94.87	1.054	-0.1	0.445	0.481	0.141	0.152
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	132	5660	16.80	17.00	1.047	94.87	1.054	-0.05	0.395	0.436	0.128	0.141
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	144	5720	16.58	17.00	1.102	94.87	1.054	0.01	0.286	0.332	0.093	0.108
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	100	5500	16.94	17.00	1.014	94.87	1.054	0.09	0.344	0.368	0.100	0.107
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	149	5745	16.78	17.00	1.052	94.87	1.054	0.03	0.102	0.113	0.024	0.027
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	149	5745	16.78	17.00	1.052	94.87	1.054	0.12	0.099	0.110	0.024	0.027
17	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	149	5745	16.78	17.00	1.052	94.87	1.054	0.01	0.283	0.314	0.091	0.101
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	157	5785	16.71	17.00	1.069	94.87	1.054	-0.09	0.252	0.284	0.084	0.095
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	165	5825	16.65	17.00	1.084	94.87	1.054	0.04	0.251	0.287	0.081	0.093
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	149	5745	16.78	17.00	1.052	94.87	1.054	0.05	0.150	0.166	0.044	0.049

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	0mm	0	2402	9.43	10.50	1.281	77.13	1.080	0.11	0.052	0.072	0.026	0.036
	Bluetooth	1Mbps	Right Tilted	0mm	0	2402	9.43	10.50	1.281	77.13	1.080	0.12	0.039	0.054	0.019	0.026
	Bluetooth	1Mbps	Left Cheek	0mm	0	2402	9.43	10.50	1.281	77.13	1.080	-0.1	0.124	0.172	0.062	0.086
	Bluetooth	1Mbps	Left Cheek	0mm	39	2441	8.76	10.50	1.494	77.13	1.080	-0.05	0.117	0.189	0.054	0.087
18	Bluetooth	1Mbps	Left Cheek	0mm	78	2480	8.81	10.50	1.477	77.13	1.080	-0.05	0.119	0.190	0.059	0.094
	Bluetooth	1Mbps	Left Tilted	0mm	0	2402	9.43	10.50	1.281	77.13	1.080	-0.15	0.106	0.147	0.045	0.062

**14.2 Hotspot SAR****<GSM SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	10mm	OFF	251	848.8	27.74	28.50	1.191	0.17	0.549	0.654	0.431	0.513
	GSM850	GPRS (4 Tx slots)	Back	10mm	OFF	251	848.8	27.74	28.50	1.191	0.1	0.529	0.630	0.366	0.436
	GSM850	GPRS (4 Tx slots)	Left Side	10mm	OFF	251	848.8	27.74	28.50	1.191	0.1	0.607	0.723	0.411	0.490
19	GSM850	GPRS (4 Tx slots)	Right Side	10mm	OFF	251	848.8	27.74	28.50	1.191	0.02	0.741	0.883	0.506	0.603
	GSM850	GPRS (4 Tx slots)	Right Side	10mm	OFF	128	824.2	27.56	28.50	1.242	-0.13	0.423	0.525	0.293	0.364
	GSM850	GPRS (4 Tx slots)	Right Side	10mm	OFF	189	836.4	27.63	28.50	1.222	-0.12	0.595	0.727	0.409	0.500
	GSM850	GPRS (4 Tx slots)	Bottom Side	10mm	OFF	251	848.8	27.74	28.50	1.191	0.05	0.176	0.210	0.095	0.113
	GSM1900	GPRS (4 Tx slots)	Front	10mm	ON	661	1880	21.61	22.00	1.094	-0.08	0.351	0.384	0.190	0.208
	GSM1900	GPRS (4 Tx slots)	Back	10mm	ON	661	1880	21.61	22.00	1.094	0.06	0.347	0.380	0.198	0.217
	GSM1900	GPRS (4 Tx slots)	Left Side	10mm	ON	661	1880	21.61	22.00	1.094	0.01	0.126	0.138	0.073	0.080
	GSM1900	GPRS (4 Tx slots)	Right Side	10mm	ON	661	1880	21.61	22.00	1.094	-0.09	0.008	0.009	0.004	0.005
	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	ON	661	1880	21.61	22.00	1.094	0.08	0.650	0.711	0.357	0.391
20	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	ON	512	1850.2	21.31	22.00	1.172	0.03	0.917	1.075	0.502	0.588
	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	ON	810	1909.8	21.60	22.00	1.096	-0.01	0.515	0.565	0.278	0.305

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	10mm	ON	9400	1880	18.60	19.00	1.096	-0.08	0.416	0.456	0.229	0.251
	WCDMA II	RMC 12.2Kbps	Back	10mm	ON	9400	1880	18.60	19.00	1.096	0	0.366	0.401	0.210	0.230
	WCDMA II	RMC 12.2Kbps	Left Side	10mm	ON	9400	1880	18.60	19.00	1.096	-0.03	0.214	0.235	0.127	0.139
	WCDMA II	RMC 12.2Kbps	Right Side	10mm	ON	9400	1880	18.60	19.00	1.096	-0.09	0.016	0.018	0.011	0.012
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	ON	9400	1880	18.60	19.00	1.096	0.01	0.837	0.918	0.455	0.499
21	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	ON	9262	1852.4	18.50	19.00	1.122	0.01	0.893	1.002	0.485	0.544
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	ON	9538	1907.6	18.31	19.00	1.172	-0.03	0.703	0.824	0.380	0.445
	WCDMA IV	RMC 12.2Kbps	Front	10mm	ON	1513	1752.6	18.50	18.50	1.000	-0.03	0.588	0.588	0.327	0.327
	WCDMA IV	RMC 12.2Kbps	Back	10mm	ON	1513	1752.6	18.50	18.50	1.000	0	0.514	0.514	0.294	0.294
	WCDMA IV	RMC 12.2Kbps	Left Side	10mm	ON	1513	1752.6	18.50	18.50	1.000	0.04	0.161	0.161	0.098	0.098
	WCDMA IV	RMC 12.2Kbps	Right Side	10mm	ON	1513	1752.6	18.50	18.50	1.000	0.04	0.014	0.014	0.009	0.009
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1513	1752.6	18.50	18.50	1.000	-0.01	0.984	0.984	0.539	0.539
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1312	1712.4	18.37	18.50	1.030	0.04	0.998	1.028	0.552	0.569
22	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1413	1732.6	18.49	18.50	1.002	-0.03	1.140	1.143	0.628	0.629
	WCDMA V	RMC 12.2Kbps	Front	10mm	OFF	4182	836.4	24.34	25.00	1.164	-0.06	0.554	0.645	0.435	0.506
	WCDMA V	RMC 12.2Kbps	Back	10mm	OFF	4182	836.4	24.34	25.00	1.164	0.01	0.542	0.631	0.374	0.435
	WCDMA V	RMC 12.2Kbps	Left Side	10mm	OFF	4182	836.4	24.34	25.00	1.164	-0.05	0.566	0.659	0.390	0.454
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	OFF	4182	836.4	24.34	25.00	1.164	-0.01	0.606	0.705	0.416	0.484
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	OFF	4132	826.4	24.21	25.00	1.199	-0.14	0.525	0.630	0.363	0.435
23	WCDMA V	RMC 12.2Kbps	Right Side	10mm	OFF	4233	846.6	24.28	25.00	1.180	0.16	0.662	0.781	0.454	0.536
	WCDMA V	RMC 12.2Kbps	Bottom Side	10mm	OFF	4182	836.4	24.34	25.00	1.164	-0.06	0.123	0.143	0.067	0.078

**<LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	10mm	ON	18900	1880	17.91	19.00	1.285	0.06	0.396	0.509	0.215	0.276
	LTE Band 2	20M	QPSK	50	24	Front	10mm	ON	18900	1880	18.17	19.00	1.211	0.01	0.412	0.499	0.223	0.270
	LTE Band 2	20M	QPSK	1	0	Back	10mm	ON	18900	1880	17.91	19.00	1.285	-0.02	0.319	0.410	0.182	0.234
	LTE Band 2	20M	QPSK	50	24	Back	10mm	ON	18900	1880	18.17	19.00	1.211	-0.03	0.336	0.407	0.191	0.231
	LTE Band 2	20M	QPSK	1	0	Left Side	10mm	ON	18900	1880	17.91	19.00	1.285	0.05	0.185	0.238	0.110	0.141
	LTE Band 2	20M	QPSK	50	24	Left Side	10mm	ON	18900	1880	18.17	19.00	1.211	-0.01	0.191	0.231	0.114	0.138
	LTE Band 2	20M	QPSK	1	0	Right Side	10mm	ON	18900	1880	17.91	19.00	1.285	0.15	0.012	0.015	0.008	0.010
	LTE Band 2	20M	QPSK	50	24	Right Side	10mm	ON	18900	1880	18.17	19.00	1.211	-0.18	0.012	0.015	0.008	0.010
	LTE Band 2	20M	QPSK	1	0	Bottom Side	10mm	ON	18900	1880	17.91	19.00	1.285	0.01	0.745	0.958	0.403	0.518
24	LTE Band 2	20M	QPSK	1	0	Bottom Side	10mm	ON	18700	1860	17.72	19.00	1.343	0	0.765	1.027	0.415	0.557
	LTE Band 2	20M	QPSK	1	0	Bottom Side	10mm	ON	19100	1900	17.90	19.00	1.288	0.02	0.716	0.922	0.386	0.497
	LTE Band 2	20M	QPSK	50	24	Bottom Side	10mm	ON	18900	1880	18.17	19.00	1.211	0.02	0.767	0.929	0.414	0.501
	LTE Band 2	20M	QPSK	50	24	Bottom Side	10mm	ON	18700	1860	17.89	19.00	1.291	0	0.772	0.997	0.417	0.538
	LTE Band 2	20M	QPSK	50	24	Bottom Side	10mm	ON	19100	1900	18.16	19.00	1.213	0	0.690	0.837	0.372	0.451
	LTE Band 2	20M	QPSK	100	0	Bottom Side	10mm	ON	18900	1880	18.15	19.00	1.216	0	0.684	0.832	0.369	0.449
	LTE Band 4	20M	QPSK	1	49	Front	10mm	ON	20175	1732.5	18.35	18.50	1.035	-0.06	0.470	0.487	0.263	0.272
	LTE Band 4	20M	QPSK	50	0	Front	10mm	ON	20175	1732.5	18.46	18.50	1.009	-0.01	0.448	0.452	0.250	0.252
	LTE Band 4	20M	QPSK	1	49	Back	10mm	ON	20175	1732.5	18.35	18.50	1.035	0.04	0.404	0.418	0.232	0.240
	LTE Band 4	20M	QPSK	50	0	Back	10mm	ON	20175	1732.5	18.46	18.50	1.009	0.02	0.401	0.405	0.230	0.232
	LTE Band 4	20M	QPSK	1	49	Left Side	10mm	ON	20175	1732.5	18.35	18.50	1.035	-0.17	0.152	0.157	0.092	0.095
	LTE Band 4	20M	QPSK	50	0	Left Side	10mm	ON	20175	1732.5	18.46	18.50	1.009	-0.13	0.143	0.144	0.088	0.089
	LTE Band 4	20M	QPSK	1	49	Right Side	10mm	ON	20175	1732.5	18.35	18.50	1.035	0.19	0.016	0.017	0.011	0.011
	LTE Band 4	20M	QPSK	50	0	Right Side	10mm	ON	20175	1732.5	18.46	18.50	1.009	-0.04	0.016	0.016	0.011	0.011
25	LTE Band 4	20M	QPSK	1	49	Bottom Side	10mm	ON	20175	1732.5	18.35	18.50	1.035	-0.01	1.030	1.066	0.568	0.588
	LTE Band 4	20M	QPSK	50	0	Bottom Side	10mm	ON	20175	1732.5	18.46	18.50	1.009	-0.02	1.030	1.040	0.566	0.571
	LTE Band 4	20M	QPSK	100	0	Bottom Side	10mm	ON	20175	1732.5	18.36	18.50	1.033	-0.02	1.020	1.053	0.554	0.572
	LTE Band 5	10M	QPSK	1	0	Front	10mm	OFF	20525	836.5	23.64	24.50	1.219	-0.03	0.472	0.575	0.371	0.452
	LTE Band 5	10M	QPSK	25	0	Front	10mm	OFF	20525	836.5	22.58	23.50	1.236	0.01	0.397	0.491	0.312	0.386
	LTE Band 5	10M	QPSK	1	0	Back	10mm	OFF	20525	836.5	23.64	24.50	1.219	-0.01	0.472	0.575	0.365	0.445
	LTE Band 5	10M	QPSK	25	0	Back	10mm	OFF	20525	836.5	22.58	23.50	1.236	-0.04	0.388	0.480	0.300	0.371
	LTE Band 5	10M	QPSK	1	0	Left Side	10mm	OFF	20525	836.5	23.64	24.50	1.219	-0.07	0.521	0.635	0.360	0.439
	LTE Band 5	10M	QPSK	25	0	Left Side	10mm	OFF	20525	836.5	22.58	23.50	1.236	0.04	0.434	0.536	0.299	0.370
26	LTE Band 5	10M	QPSK	1	0	Right Side	10mm	OFF	20525	836.5	23.64	24.50	1.219	-0.03	0.538	0.656	0.372	0.453
	LTE Band 5	10M	QPSK	25	0	Right Side	10mm	OFF	20525	836.5	22.58	23.50	1.236	-0.04	0.453	0.560	0.312	0.386
	LTE Band 5	10M	QPSK	1	0	Bottom Side	10mm	OFF	20525	836.5	23.64	24.50	1.219	0.01	0.079	0.096	0.042	0.051
	LTE Band 5	10M	QPSK	25	0	Bottom Side	10mm	OFF	20525	836.5	22.58	23.50	1.236	-0.04	0.069	0.085	0.036	0.044
	LTE Band 7	20M	QPSK	1	99	Front	10mm	OFF	21350	2560	23.77	24.50	1.183	0.02	0.601	0.711	0.275	0.325
	LTE Band 7	20M	QPSK	50	50	Front	10mm	OFF	21350	2560	22.81	23.50	1.172	0.04	0.470	0.551	0.216	0.253
	LTE Band 7	20M	QPSK	1	99	Back	10mm	OFF	21350	2560	23.77	24.50	1.183	-0.05	0.707	0.836	0.321	0.380
27	LTE Band 7	20M	QPSK	1	99	Back	10mm	OFF	20850	2510	23.54	24.50	1.247	-0.03	0.675	0.842	0.313	0.390
	LTE Band 7	20M	QPSK	1	99	Back	10mm	OFF	21100	2535	23.69	24.50	1.205	0	0.691	0.833	0.318	0.383
	LTE Band 7	20M	QPSK	50	50	Back	10mm	OFF	21350	2560	22.81	23.50	1.172	0.01	0.579	0.679	0.263	0.308
	LTE Band 7	20M	QPSK	100	0	Back	10mm	OFF	21350	2560	22.75	23.50	1.189	-0.01	0.576	0.685	0.263	0.313
	LTE Band 7	20M	QPSK	1	99	Left Side	10mm	OFF	21350	2560	23.77	24.50	1.183	0.04	0.120	0.142	0.067	0.079
	LTE Band 7	20M	QPSK	50	50	Left Side	10mm	OFF	21350	2560	22.81	23.50	1.172	-0.03	0.104	0.122	0.058	0.068
	LTE Band 7	20M	QPSK	1	99	Right Side	10mm	OFF	21350	2560	23.77	24.50	1.183	-0.11	0.232	0.274	0.117	0.138
	LTE Band 7	20M	QPSK	50	50	Right Side	10mm	OFF	21350	2560	22.81	23.50	1.172	0.02	0.206	0.241	0.105	0.123
	LTE Band 7	20M	QPSK	1	99	Bottom Side	10mm	OFF	21350	2560	23.77	24.50	1.183	-0.16	0.160	0.189	0.070	0.083
	LTE Band 7	20M	QPSK	50	50	Bottom Side	10mm	OFF	21350	2560	22.81	23.50	1.172	0.05	0.135	0.158	0.060	0.070



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
28	LTE Band 12	10M	QPSK	1	0	Front	10mm	OFF	23095	707.5	23.56	24.50	1.242	-0.11	0.150	0.186	0.121	0.150
	LTE Band 12	10M	QPSK	25	25	Front	10mm	OFF	23095	707.5	22.31	23.50	1.315	0	0.127	0.167	0.101	0.133
	LTE Band 12	10M	QPSK	1	0	Back	10mm	OFF	23095	707.5	23.56	24.50	1.242	-0.03	0.168	0.209	0.133	0.165
	LTE Band 12	10M	QPSK	25	25	Back	10mm	OFF	23095	707.5	22.31	23.50	1.315	0	0.135	0.178	0.099	0.130
	LTE Band 12	10M	QPSK	1	0	Left Side	10mm	OFF	23095	707.5	23.56	24.50	1.242	0.06	0.146	0.181	0.104	0.129
	LTE Band 12	10M	QPSK	25	25	Left Side	10mm	OFF	23095	707.5	22.31	23.50	1.315	0	0.117	0.154	0.083	0.109
	LTE Band 12	10M	QPSK	1	0	Right Side	10mm	OFF	23095	707.5	23.56	24.50	1.242	0.01	0.154	0.191	0.109	0.135
	LTE Band 12	10M	QPSK	25	25	Right Side	10mm	OFF	23095	707.5	22.31	23.50	1.315	0	0.129	0.170	0.092	0.121
	LTE Band 12	10M	QPSK	1	0	Bottom Side	10mm	OFF	23095	707.5	23.56	24.50	1.242	0.1	0.022	0.027	0.013	0.016
	LTE Band 12	10M	QPSK	25	25	Bottom Side	10mm	OFF	23095	707.5	22.31	23.50	1.315	0.14	0.021	0.028	0.012	0.016
29	LTE Band 13	10M	QPSK	1	0	Front	10mm	OFF	23230	782	23.65	24.50	1.216	0.03	0.339	0.412	0.246	0.299
	LTE Band 13	10M	QPSK	25	25	Front	10mm	OFF	23230	782	22.68	23.50	1.208	0.01	0.286	0.345	0.225	0.272
	LTE Band 13	10M	QPSK	1	0	Back	10mm	OFF	23230	782	23.65	24.50	1.216	-0.03	0.339	0.412	0.242	0.294
	LTE Band 13	10M	QPSK	25	25	Back	10mm	OFF	23230	782	22.68	23.50	1.208	-0.02	0.278	0.336	0.199	0.240
	LTE Band 13	10M	QPSK	1	0	Left Side	10mm	OFF	23230	782	23.65	24.50	1.216	-0.06	0.358	0.435	0.249	0.303
	LTE Band 13	10M	QPSK	25	25	Left Side	10mm	OFF	23230	782	22.68	23.50	1.208	-0.05	0.313	0.378	0.217	0.262
	LTE Band 13	10M	QPSK	1	0	Right Side	10mm	OFF	23230	782	23.65	24.50	1.216	0.01	0.332	0.404	0.231	0.281
	LTE Band 13	10M	QPSK	25	0	Right Side	10mm	OFF	23230	782	22.68	23.50	1.208	0.11	0.281	0.339	0.195	0.236
	LTE Band 13	10M	QPSK	1	0	Bottom Side	10mm	OFF	23230	782	23.65	24.50	1.216	-0.11	0.030	0.036	0.017	0.021
	LTE Band 13	10M	QPSK	25	25	Bottom Side	10mm	OFF	23230	782	22.68	23.50	1.208	-0.04	0.030	0.036	0.017	0.021
30	LTE Band 25	20M	QPSK	1	0	Front	10mm	ON	26340	1880	18.10	19.00	1.230	-0.05	0.413	0.508	0.226	0.278
	LTE Band 25	20M	QPSK	50	50	Front	10mm	ON	26340	1880	18.25	19.00	1.189	-0.04	0.414	0.492	0.224	0.266
	LTE Band 25	20M	QPSK	1	0	Back	10mm	ON	26340	1880	18.10	19.00	1.230	0.16	0.338	0.416	0.192	0.236
	LTE Band 25	20M	QPSK	50	50	Back	10mm	ON	26340	1880	18.25	19.00	1.189	-0.06	0.342	0.406	0.193	0.229
	LTE Band 25	20M	QPSK	1	0	Left Side	10mm	ON	26340	1880	18.10	19.00	1.230	-0.04	0.193	0.237	0.115	0.141
	LTE Band 25	20M	QPSK	50	50	Left Side	10mm	ON	26340	1880	18.25	19.00	1.189	-0.02	0.193	0.229	0.115	0.137
	LTE Band 25	20M	QPSK	1	0	Right Side	10mm	ON	26340	1880	18.10	19.00	1.230	0.04	0.012	0.015	0.008	0.010
	LTE Band 25	20M	QPSK	50	50	Right Side	10mm	ON	26340	1880	18.25	19.00	1.189	-0.1	0.012	0.014	0.008	0.010
	LTE Band 25	20M	QPSK	1	0	Bottom Side	10mm	ON	26340	1880	18.10	19.00	1.230	-0.02	0.771	0.949	0.417	0.513
	LTE Band 25	20M	QPSK	1	0	Bottom Side	10mm	ON	26140	1860	17.65	19.00	1.365	-0.04	0.749	1.022	0.406	0.554
31	LTE Band 25	20M	QPSK	1	0	Bottom Side	10mm	ON	26590	1905	18.09	19.00	1.233	0.02	0.734	0.905	0.396	0.488
	LTE Band 25	20M	QPSK	50	50	Bottom Side	10mm	ON	26340	1880	18.25	19.00	1.189	-0.04	0.768	0.913	0.415	0.493
	LTE Band 25	20M	QPSK	50	50	Bottom Side	10mm	ON	26140	1860	17.99	19.00	1.262	-0.03	0.780	0.984	0.423	0.534
	LTE Band 25	20M	QPSK	50	50	Bottom Side	10mm	ON	26590	1905	18.23	19.00	1.194	-0.01	0.698	0.833	0.377	0.450
	LTE Band 25	20M	QPSK	100	0	Bottom Side	10mm	ON	26340	1880	18.19	19.00	1.205	-0.08	0.668	0.805	0.360	0.434
	LTE Band 66	20M	QPSK	1	49	Front	10mm	ON	132322	1745	18.46	18.50	1.009	0.06	0.505	0.510	0.281	0.284
	LTE Band 66	20M	QPSK	50	24	Front	10mm	ON	132322	1745	18.37	18.50	1.030	0.05	0.496	0.511	0.276	0.284
	LTE Band 66	20M	QPSK	1	49	Back	10mm	ON	132322	1745	18.46	18.50	1.009	0.03	0.425	0.429	0.242	0.244
	LTE Band 66	20M	QPSK	50	24	Back	10mm	ON	132322	1745	18.37	18.50	1.030	-0.04	0.422	0.435	0.241	0.248
	LTE Band 66	20M	QPSK	1	49	Left Side	10mm	ON	132322	1745	18.46	18.50	1.009	-0.03	0.154	0.155	0.094	0.095
31	LTE Band 66	20M	QPSK	50	24	Left Side	10mm	ON	132322	1745	18.37	18.50	1.030	-0.05	0.150	0.155	0.091	0.094
	LTE Band 66	20M	QPSK	1	49	Right Side	10mm	ON	132322	1745	18.46	18.50	1.009	0.14	0.016	0.016	0.011	0.011
	LTE Band 66	20M	QPSK	50	24	Right Side	10mm	ON	132322	1745	18.37	18.50	1.030	-0.02	0.015	0.015	0.011	0.011
	LTE Band 66	20M	QPSK	1	49	Bottom Side	10mm	ON	132322	1745	18.46	18.50	1.009	0	0.989	0.998	0.543	0.548
	LTE Band 66	20M	QPSK	1	49	Bottom Side	10mm	ON	132072	1720	18.14	18.50	1.086	-0.13	0.984	1.069	0.550	0.598
	LTE Band 66	20M	QPSK	1	49	Bottom Side	10mm	ON	132572	1770	18.25	18.50	1.059	0.01	0.925	0.980	0.507	0.537
	LTE Band 66	20M	QPSK	50	24	Bottom Side	10mm	ON	132322	1745	18.37	18.50	1.030	0.02	0.981	1.011	0.537	0.553
	LTE Band 66	20M	QPSK	50	24	Bottom Side	10mm	ON	132072	1720	18.07	18.50	1.104	0	0.919	1.015	0.505	0.558
31	LTE Band 66	20M	QPSK	50	24	Bottom Side	10mm	ON	132572	1770	18.14	18.50	1.086	-0.01	0.911	0.990	0.497	0.540
	LTE Band 66	20M	QPSK	100	0	Bottom Side	10mm	ON	132322	1745	18.35	18.50	1.035	-0.03	0.985	1.020	0.539	0.558

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	1	2412	15.91	16.00	1.021	99.03	1.010	-0.13	0.081	0.084	0.043	0.044
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	1	2412	15.91	16.00	1.021	99.03	1.010	0.12	0.118	0.122	0.057	0.059
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	6	2437	15.66	16.00	1.081	99.03	1.010	0.1	0.145	0.158	0.069	0.075
32	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	11	2462	15.56	16.00	1.107	99.03	1.010	0.08	0.167	0.187	0.079	0.088
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	1	2412	15.91	16.00	1.021	99.03	1.010	-0.09	0.088	0.091	0.048	0.049
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	1	2412	15.91	16.00	1.021	99.03	1.010	-0.17	0.076	0.078	0.038	0.039

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	0	2402	9.43	10.50	1.281	77.13	1.080	0.12	0.026	0.036	0.013	0.018
	Bluetooth	1Mbps	Back	10mm	0	2402	9.43	10.50	1.281	77.13	1.080	0.02	0.027	0.037	0.015	0.021
	Bluetooth	1Mbps	Back	10mm	39	2441	8.76	10.50	1.494	77.13	1.080	-0.14	0.015	0.024	0.007	0.012
33	Bluetooth	1Mbps	Back	10mm	78	2480	8.81	10.50	1.477	77.13	1.080	-0.19	0.030	0.048	0.014	0.022
	Bluetooth	1Mbps	Right Side	10mm	0	2402	9.43	10.50	1.281	77.13	1.080	0.12	0.016	0.022	0.008	0.011
	Bluetooth	1Mbps	Top Side	10mm	0	2402	9.43	10.50	1.281	77.13	1.080	0.19	0.023	0.032	0.011	0.015

14.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
34	GSM850	GPRS (4 Tx slots)	Front	15mm	251	848.8	27.74	28.50	1.191	-0.01	0.520	0.619	0.403	0.480
	GSM850	GPRS (4 Tx slots)	Front	15mm	128	824.2	27.56	28.50	1.242	-0.01	0.370	0.459	0.289	0.359
	GSM850	GPRS (4 Tx slots)	Front	15mm	189	836.4	27.63	28.50	1.222	0.16	0.472	0.577	0.365	0.446
	GSM850	GPRS (4 Tx slots)	Back	15mm	251	848.8	27.74	28.50	1.191	0.04	0.460	0.548	0.355	0.423
	GSM1900	GPRS (4 Tx slots)	Front	15mm	810	1909.8	25.40	25.50	1.023	0.01	0.299	0.306	0.171	0.175
	GSM1900	GPRS (4 Tx slots)	Front	15mm	512	1850.2	25.10	25.50	1.096	0.12	0.282	0.309	0.162	0.178
35	GSM1900	GPRS (4 Tx slots)	Front	15mm	661	1880	25.17	25.50	1.079	0.07	0.480	0.518	0.280	0.302
	GSM1900	GPRS (4 Tx slots)	Back	15mm	810	1909.8	25.40	25.50	1.023	0.05	0.263	0.269	0.155	0.159

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	15mm	9400	1880	24.19	24.50	1.074	0.01	0.745	0.800	0.434	0.466
36	WCDMA II	RMC 12.2Kbps	Front	15mm	9262	1852.4	24.11	24.50	1.094	0	0.746	0.816	0.435	0.476
	WCDMA II	RMC 12.2Kbps	Front	15mm	9538	1907.6	23.92	24.50	1.143	0.01	0.638	0.729	0.370	0.423
	WCDMA II	RMC 12.2Kbps	Back	15mm	9400	1880	24.19	24.50	1.074	-0.05	0.690	0.741	0.411	0.441
	WCDMA IV	RMC 12.2Kbps	Front	15mm	1513	1752.6	24.04	24.50	1.112	-0.08	0.880	0.978	0.519	0.577
37	WCDMA IV	RMC 12.2Kbps	Front	15mm	1312	1712.4	23.77	24.50	1.183	-0.15	0.904	1.069	0.536	0.634
	WCDMA IV	RMC 12.2Kbps	Front	15mm	1413	1732.6	24.01	24.50	1.119	-0.04	0.954	1.068	0.528	0.591
	WCDMA IV	RMC 12.2Kbps	Back	15mm	1513	1752.6	24.04	24.50	1.112	0	0.796	0.885	0.479	0.533
	WCDMA IV	RMC 12.2Kbps	Back	15mm	1312	1712.4	23.77	24.50	1.183	0	0.805	0.952	0.487	0.576
	WCDMA IV	RMC 12.2Kbps	Back	15mm	1413	1732.6	24.01	24.50	1.119	0.05	0.830	0.929	0.501	0.561
	WCDMA V	RMC 12.2Kbps	Front	15mm	4182	836.4	24.34	25.00	1.164	-0.01	0.476	0.554	0.370	0.431
	WCDMA V	RMC 12.2Kbps	Front	15mm	4132	826.4	24.21	25.00	1.199	0.03	0.440	0.528	0.344	0.413
38	WCDMA V	RMC 12.2Kbps	Front	15mm	4233	846.6	24.28	25.00	1.180	0	0.495	0.584	0.385	0.454
	WCDMA V	RMC 12.2Kbps	Back	15mm	4182	836.4	24.34	25.00	1.164	0.02	0.451	0.525	0.348	0.405



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	15mm	18900	1880	23.95	24.50	1.135	0.09	0.728	0.826	0.423	0.480
39	LTE Band 2	20M	QPSK	1	0	Front	15mm	18700	1860	23.51	24.50	1.256	-0.03	0.714	0.897	0.417	0.524
	LTE Band 2	20M	QPSK	1	0	Front	15mm	19100	1900	23.84	24.50	1.164	0.01	0.727	0.846	0.419	0.488
	LTE Band 2	20M	QPSK	50	0	Front	15mm	18900	1880	23.22	23.50	1.067	-0.07	0.593	0.632	0.344	0.367
	LTE Band 2	20M	QPSK	100	0	Front	15mm	18900	1880	23.02	23.50	1.117	0.02	0.608	0.679	0.352	0.393
	LTE Band 2	20M	QPSK	1	0	Back	15mm	18900	1880	23.95	24.50	1.135	-0.08	0.559	0.634	0.331	0.376
	LTE Band 2	20M	QPSK	50	0	Back	15mm	18900	1880	23.22	23.50	1.067	-0.02	0.460	0.491	0.270	0.288
40	LTE Band 4	20M	QPSK	1	0	Front	15mm	20175	1732.5	23.75	24.50	1.189	0.01	0.782	0.929	0.469	0.557
	LTE Band 4	20M	QPSK	50	0	Front	15mm	20175	1732.5	22.86	23.50	1.159	0.01	0.640	0.742	0.380	0.440
	LTE Band 4	20M	QPSK	100	0	Front	15mm	20175	1732.5	22.78	23.50	1.180	0	0.637	0.752	0.375	0.443
	LTE Band 4	20M	QPSK	1	0	Back	15mm	20175	1732.5	23.75	24.50	1.189	0.05	0.736	0.875	0.445	0.529
	LTE Band 4	20M	QPSK	50	0	Back	15mm	20175	1732.5	22.86	23.50	1.159	-0.18	0.582	0.674	0.352	0.408
	LTE Band 4	20M	QPSK	100	0	Back	15mm	20175	1732.5	22.78	23.50	1.180	-0.14	0.662	0.781	0.399	0.471
41	LTE Band 5	10M	QPSK	1	0	Front	15mm	20525	836.5	23.64	24.50	1.219	0	0.420	0.512	0.328	0.400
	LTE Band 5	10M	QPSK	25	0	Front	15mm	20525	836.5	22.58	23.50	1.236	0.01	0.349	0.431	0.272	0.336
	LTE Band 5	10M	QPSK	1	0	Back	15mm	20525	836.5	23.64	24.50	1.219	0.01	0.402	0.490	0.311	0.379
	LTE Band 5	10M	QPSK	25	0	Back	15mm	20525	836.5	22.58	23.50	1.236	-0.04	0.334	0.413	0.257	0.318
	LTE Band 7	20M	QPSK	1	99	Front	15mm	21350	2560	23.77	24.50	1.183	0.04	0.248	0.293	0.119	0.141
	LTE Band 7	20M	QPSK	50	50	Front	15mm	21350	2560	22.81	23.50	1.172	0.04	0.209	0.245	0.100	0.117
	LTE Band 7	20M	QPSK	1	99	Back	15mm	21350	2560	23.77	24.50	1.183	-0.08	0.256	0.303	0.122	0.144
42	LTE Band 7	20M	QPSK	1	99	Back	15mm	20850	2510	23.54	24.50	1.247	-0.18	0.244	0.304	0.119	0.148
	LTE Band 7	20M	QPSK	1	99	Back	15mm	21100	2535	23.69	24.50	1.205	-0.12	0.250	0.301	0.122	0.147
	LTE Band 7	20M	QPSK	50	50	Back	15mm	21350	2560	22.81	23.50	1.172	-0.15	0.207	0.243	0.103	0.121
	LTE Band 12	10M	QPSK	1	0	Front	15mm	23095	707.5	23.56	24.50	1.242	-0.18	0.137	0.170	0.109	0.135
	LTE Band 12	10M	QPSK	25	25	Front	15mm	23095	707.5	22.31	23.50	1.315	-0.03	0.115	0.151	0.091	0.120
43	LTE Band 12	10M	QPSK	1	0	Back	15mm	23095	707.5	23.56	24.50	1.242	-0.03	0.147	0.183	0.116	0.144
	LTE Band 12	10M	QPSK	25	25	Back	15mm	23095	707.5	22.31	23.50	1.315	-0.01	0.125	0.164	0.099	0.130
	LTE Band 13	10M	QPSK	1	0	Front	15mm	23230	782	23.65	24.50	1.216	-0.07	0.300	0.365	0.235	0.286
	LTE Band 13	10M	QPSK	25	25	Front	15mm	23230	782	22.68	23.50	1.208	-0.03	0.250	0.302	0.197	0.238
44	LTE Band 13	10M	QPSK	1	0	Back	15mm	23230	782	23.65	24.50	1.216	-0.04	0.305	0.371	0.238	0.289
	LTE Band 13	10M	QPSK	25	25	Back	15mm	23230	782	22.68	23.50	1.208	-0.06	0.255	0.308	0.199	0.240
	LTE Band 25	20M	QPSK	1	0	Front	15mm	26340	1880	23.66	24.00	1.081	-0.04	0.673	0.728	0.391	0.423
45	LTE Band 25	20M	QPSK	1	0	Front	15mm	26140	1860	23.08	24.00	1.236	-0.02	0.624	0.771	0.364	0.450
	LTE Band 25	20M	QPSK	1	0	Front	15mm	26590	1905	23.48	24.00	1.127	0.04	0.629	0.709	0.365	0.411
	LTE Band 25	20M	QPSK	50	0	Front	15mm	26340	1880	22.68	23.00	1.076	-0.01	0.532	0.573	0.308	0.332
	LTE Band 25	20M	QPSK	1	0	Back	15mm	26340	1880	23.66	24.00	1.081	-0.12	0.535	0.579	0.325	0.351
	LTE Band 25	20M	QPSK	50	0	Back	15mm	26340	1880	22.68	23.00	1.076	-0.18	0.431	0.464	0.255	0.274
	LTE Band 66	20M	QPSK	1	0	Front	15mm	132322	1745	23.42	24.00	1.143	0.02	0.724	0.827	0.430	0.491
46	LTE Band 66	20M	QPSK	1	0	Front	15mm	132072	1720	23.21	24.00	1.199	-0.01	0.733	0.879	0.435	0.522
	LTE Band 66	20M	QPSK	1	0	Front	15mm	132572	1770	23.35	24.00	1.161	-0.01	0.672	0.780	0.398	0.462
	LTE Band 66	20M	QPSK	50	0	Front	15mm	132322	1745	22.34	23.00	1.164	0.01	0.572	0.666	0.339	0.395
	LTE Band 66	20M	QPSK	100	0	Front	15mm	132322	1745	22.29	23.00	1.178	-0.03	0.590	0.695	0.349	0.411
	LTE Band 66	20M	QPSK	1	0	Back	15mm	132322	1745	23.42	24.00	1.143	0.02	0.690	0.789	0.417	0.477
	LTE Band 66	20M	QPSK	50	0	Back	15mm	132322	1745	22.34	23.00	1.164	0.11	0.558	0.650	0.336	0.391



<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	1	2412	15.91	16.00	1.021	99.03	1.010	-0.14	0.045	0.046	0.024	0.025
47	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	6	2437	15.66	16.00	1.081	99.03	1.010	-0.03	0.047	0.051	0.026	0.028
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	11	2462	15.56	16.00	1.107	99.03	1.010	0.07	0.042	0.047	0.023	0.026
	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	1	2412	15.91	16.00	1.021	99.03	1.010	0.09	0.041	0.042	0.022	0.023
	WLAN5GHz	802.11a 6Mbps	Front	15mm	64	5320	16.95	17.00	1.012	94.87	1.054	-0.09	0.008	0.009	0.002	0.002
48	WLAN5GHz	802.11a 6Mbps	Back	15mm	64	5320	16.95	17.00	1.012	94.87	1.054	-0.04	0.100	0.107	0.034	0.036
	WLAN5GHz	802.11a 6Mbps	Back	15mm	56	5280	16.72	17.00	1.067	94.87	1.054	-0.07	0.087	0.098	0.029	0.033
	WLAN5GHz	802.11a 6Mbps	Front	15mm	100	5500	16.94	17.00	1.014	94.87	1.054	-0.06	0.011	0.012	0.003	0.003
	WLAN5GHz	802.11a 6Mbps	Back	15mm	100	5500	16.94	17.00	1.014	94.87	1.054	0.1	0.071	0.076	0.022	0.024
	WLAN5GHz	802.11a 6Mbps	Back	15mm	116	5580	16.89	17.00	1.026	94.87	1.054	0.04	0.080	0.087	0.027	0.029
	WLAN5GHz	802.11a 6Mbps	Back	15mm	132	5660	16.80	17.00	1.047	94.87	1.054	0.11	0.091	0.100	0.032	0.035
49	WLAN5GHz	802.11a 6Mbps	Back	15mm	144	5720	16.58	17.00	1.102	94.87	1.054	0.02	0.104	0.121	0.036	0.042
	WLAN5GHz	802.11a 6Mbps	Front	15mm	149	5745	16.78	17.00	1.052	94.87	1.054	-0.15	0.013	0.014	0.002	0.002
	WLAN5GHz	802.11a 6Mbps	Back	15mm	149	5745	16.78	17.00	1.052	94.87	1.054	-0.01	0.105	0.116	0.037	0.041
	WLAN5GHz	802.11a 6Mbps	Back	15mm	157	5785	16.71	17.00	1.069	94.87	1.054	0.04	0.106	0.119	0.036	0.041
50	WLAN5GHz	802.11a 6Mbps	Back	15mm	165	5825	16.65	17.00	1.084	94.87	1.054	0.01	0.107	0.122	0.038	0.043

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	Bluetooth	1Mbps	Front	15mm	0	2402	9.43	10.50	1.281	77.13	1.080	0.14	0.008	0.011	0.004	0.006
	Bluetooth	1Mbps	Back	15mm	0	2402	9.43	10.50	1.281	77.13	1.080	-0.16	0.009	0.013	0.006	0.008
	Bluetooth	1Mbps	Back	15mm	39	2441	8.76	10.50	1.494	77.13	1.080	-0.04	0.008	0.012	0.005	0.007
51	Bluetooth	1Mbps	Back	15mm	78	2480	8.81	10.50	1.477	77.13	1.080	-0.15	0.009	0.014	0.006	0.010

14.4 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	ON	512	1850.2	21.31	22.00	1.172	0.03	0.917		1.075
2nd	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	ON	512	1850.2	21.31	22.00	1.172	0.07	0.906	1.01	1.062
1st	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1413	1732.6	18.49	18.50	1.002	-0.03	1.140		1.143
2nd	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1413	1732.6	18.49	18.50	1.002	0.08	1.120	1.02	1.123

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			Notes
		Head	Body-worn	Hotspot	
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		
2.	GPRS/EDGE + WLAN2.4GHz	Yes*	Yes*	Yes	*VOIP applications are considered.
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	
4.	LTE + WLAN2.4GHz	Yes*	Yes*	Yes	*VOIP applications are considered.
5.	GSM Voice + Bluetooth	Yes^	Yes		^Bluetooth Tethering is considered.
6.	GPRS/EDGE + Bluetooth	Yes*^	Yes*	Yes^	*VOIP applications are considered. ^Bluetooth Tethering is considered.
7.	WCDMA+ Bluetooth	Yes^	Yes	Yes^	^Bluetooth Tethering is considered.
8.	LTE + Bluetooth	Yes*^	Yes*	Yes^	*VOIP applications are considered. ^Bluetooth Tethering is considered.
9.	GSM Voice + WLAN5GHz	Yes	Yes		
10.	GPRS/EDGE + WLAN5GHz	Yes*	Yes*		*VOIP applications are considered.
11.	WCDMA + WLAN5GHz	Yes	Yes		
12.	LTE + WLAN5GHz	Yes*	Yes*		*VOIP applications are considered.

General Note:

- In this report, the 10g SAR results which is submitted voluntarily.
- This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications.
- For all different cellular bands share the same antenna, and can't operating simultaneously.
- WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation < 1.6W/kg.
 - $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

15.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Right Cheek	0.515	0.247	0.189	0.072	0.76	0.70	0.59
		Right Tilted	0.278	0.203	0.122	0.054	0.48	0.40	0.33
		Left Cheek	0.561	0.730	0.515	0.190	1.29	1.08	0.75
		Left Tilted	0.269	0.471	0.368	0.147	0.74	0.64	0.42
	GSM1900	Right Cheek	0.142	0.247	0.189	0.072	0.39	0.33	0.21
		Right Tilted	0.068	0.203	0.122	0.054	0.27	0.19	0.12
		Left Cheek	0.532	0.730	0.515	0.190	1.26	1.05	0.72
		Left Tilted	0.067	0.471	0.368	0.147	0.54	0.44	0.21
WCDMA	WCDMA II	Right Cheek	0.387	0.247	0.189	0.072	0.63	0.58	0.46
		Right Tilted	0.192	0.203	0.122	0.054	0.40	0.31	0.25
		Left Cheek	0.712	0.730	0.515	0.190	1.44	1.23	0.90
		Left Tilted	0.147	0.471	0.368	0.147	0.62	0.52	0.29
	WCDMA IV	Right Cheek	0.460	0.247	0.189	0.072	0.71	0.65	0.53
		Right Tilted	0.225	0.203	0.122	0.054	0.43	0.35	0.28
		Left Cheek	0.812	0.730	0.515	0.190	1.54	1.33	1.00
		Left Tilted	0.193	0.471	0.368	0.147	0.66	0.56	0.34
	WCDMA V	Right Cheek	0.532	0.247	0.189	0.072	0.78	0.72	0.60
		Right Tilted	0.290	0.203	0.122	0.054	0.49	0.41	0.34
		Left Cheek	0.540	0.730	0.515	0.190	1.27	1.06	0.73
		Left Tilted	0.226	0.471	0.368	0.147	0.70	0.59	0.37



WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
LTE	LTE Band 2	Right Cheek	0.369	0.247	0.189	0.072	0.62	0.56	0.44
		Right Tilted	0.192	0.203	0.122	0.054	0.40	0.31	0.25
		Left Cheek	0.632	0.730	0.515	0.190	1.36	1.15	0.82
		Left Tilted	0.176	0.471	0.368	0.147	0.65	0.54	0.32
	LTE Band 4	Right Cheek	0.343	0.247	0.189	0.072	0.59	0.53	0.42
		Right Tilted	0.196	0.203	0.122	0.054	0.40	0.32	0.25
		Left Cheek	0.670	0.730	0.515	0.190	1.40	1.19	0.86
		Left Tilted	0.254	0.471	0.368	0.147	0.73	0.62	0.40
	LTE Band 5	Right Cheek	0.486	0.247	0.189	0.072	0.73	0.68	0.56
		Right Tilted	0.268	0.203	0.122	0.054	0.47	0.39	0.32
		Left Cheek	0.438	0.730	0.515	0.190	1.17	0.95	0.63
		Left Tilted	0.230	0.471	0.368	0.147	0.70	0.60	0.38
	LTE Band 7	Right Cheek	0.423	0.247	0.189	0.072	0.67	0.61	0.50
		Right Tilted	0.037	0.203	0.122	0.054	0.24	0.16	0.09
		Left Cheek	0.091	0.730	0.515	0.190	0.82	0.61	0.28
		Left Tilted	0.043	0.471	0.368	0.147	0.51	0.41	0.19
	LTE Band 12	Right Cheek	0.113	0.247	0.189	0.072	0.36	0.30	0.19
		Right Tilted	0.073	0.203	0.122	0.054	0.28	0.20	0.13
		Left Cheek	0.109	0.730	0.515	0.190	0.84	0.62	0.30
		Left Tilted	0.071	0.471	0.368	0.147	0.54	0.44	0.22
	LTE Band 13	Right Cheek	0.259	0.247	0.189	0.072	0.51	0.45	0.33
		Right Tilted	0.099	0.203	0.122	0.054	0.30	0.22	0.15
		Left Cheek	0.264	0.730	0.515	0.190	0.99	0.78	0.45
		Left Tilted	0.099	0.471	0.368	0.147	0.57	0.47	0.25
	LTE Band 25	Right Cheek	0.322	0.247	0.189	0.072	0.57	0.51	0.39
		Right Tilted	0.171	0.203	0.122	0.054	0.37	0.29	0.23
		Left Cheek	0.590	0.730	0.515	0.190	1.32	1.11	0.78
		Left Tilted	0.142	0.471	0.368	0.147	0.61	0.51	0.29
	LTE Band 66	Right Cheek	0.314	0.247	0.189	0.072	0.56	0.50	0.39
		Right Tilted	0.161	0.203	0.122	0.054	0.36	0.28	0.22
		Left Cheek	0.646	0.730	0.515	0.190	1.38	1.16	0.84
		Left Tilted	0.197	0.471	0.368	0.147	0.67	0.57	0.34

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
GSM	GSM850	Right Cheek	0.373	0.111	0.058	0.036	0.48	0.43	0.41
		Right Tilted	0.224	0.094	0.038	0.026	0.32	0.26	0.25
		Left Cheek	0.441	0.327	0.165	0.094	0.77	0.61	0.54
		Left Tilted	0.214	0.203	0.107	0.062	0.42	0.32	0.28
	GSM1900	Right Cheek	0.094	0.111	0.058	0.036	0.21	0.15	0.13
		Right Tilted	0.044	0.094	0.038	0.026	0.14	0.08	0.07
		Left Cheek	0.357	0.327	0.165	0.094	0.68	0.52	0.45
		Left Tilted	0.044	0.203	0.107	0.062	0.25	0.15	0.11
WCDMA	WCDMA II	Right Cheek	0.256	0.111	0.058	0.036	0.37	0.31	0.29
		Right Tilted	0.128	0.094	0.038	0.026	0.22	0.17	0.15
		Left Cheek	0.477	0.327	0.165	0.094	0.80	0.64	0.57
		Left Tilted	0.099	0.203	0.107	0.062	0.30	0.21	0.16
	WCDMA IV	Right Cheek	0.307	0.111	0.058	0.036	0.42	0.37	0.34
		Right Tilted	0.150	0.094	0.038	0.026	0.24	0.19	0.18
		Left Cheek	0.558	0.327	0.165	0.094	0.89	0.72	0.65
		Left Tilted	0.129	0.203	0.107	0.062	0.33	0.24	0.19
	WCDMA V	Right Cheek	0.389	0.111	0.058	0.036	0.50	0.45	0.43
		Right Tilted	0.235	0.094	0.038	0.026	0.33	0.27	0.26
		Left Cheek	0.423	0.327	0.165	0.094	0.75	0.59	0.52
		Left Tilted	0.171	0.203	0.107	0.062	0.37	0.28	0.23



WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
LTE	LTE Band 2	Right Cheek	0.239	0.111	0.058	0.036	0.35	0.30	0.28
		Right Tilted	0.128	0.094	0.038	0.026	0.22	0.17	0.15
		Left Cheek	0.422	0.327	0.165	0.094	0.75	0.59	0.52
		Left Tilted	0.117	0.203	0.107	0.062	0.32	0.22	0.18
	LTE Band 4	Right Cheek	0.232	0.111	0.058	0.036	0.34	0.29	0.27
		Right Tilted	0.125	0.094	0.038	0.026	0.22	0.16	0.15
		Left Cheek	0.454	0.327	0.165	0.094	0.78	0.62	0.55
		Left Tilted	0.139	0.203	0.107	0.062	0.34	0.25	0.20
	LTE Band 5	Right Cheek	0.385	0.111	0.058	0.036	0.50	0.44	0.42
		Right Tilted	0.217	0.094	0.038	0.026	0.31	0.26	0.24
		Left Cheek	0.345	0.327	0.165	0.094	0.67	0.51	0.44
		Left Tilted	0.187	0.203	0.107	0.062	0.39	0.29	0.25
	LTE Band 7	Right Cheek	0.213	0.111	0.058	0.036	0.32	0.27	0.25
		Right Tilted	0.020	0.094	0.038	0.026	0.11	0.06	0.05
		Left Cheek	0.045	0.327	0.165	0.094	0.37	0.21	0.14
		Left Tilted	0.020	0.203	0.107	0.062	0.22	0.13	0.08
	LTE Band 12	Right Cheek	0.092	0.111	0.058	0.036	0.20	0.15	0.13
		Right Tilted	0.045	0.094	0.038	0.026	0.14	0.08	0.07
		Left Cheek	0.087	0.327	0.165	0.094	0.41	0.25	0.18
		Left Tilted	0.052	0.203	0.107	0.062	0.26	0.16	0.11
	LTE Band 13	Right Cheek	0.208	0.111	0.058	0.036	0.32	0.27	0.24
		Right Tilted	0.083	0.094	0.038	0.026	0.18	0.12	0.11
		Left Cheek	0.210	0.327	0.165	0.094	0.54	0.38	0.30
		Left Tilted	0.083	0.203	0.107	0.062	0.29	0.19	0.15
	LTE Band 25	Right Cheek	0.212	0.111	0.058	0.036	0.32	0.27	0.25
		Right Tilted	0.111	0.094	0.038	0.026	0.21	0.15	0.14
		Left Cheek	0.394	0.327	0.165	0.094	0.72	0.56	0.49
		Left Tilted	0.096	0.203	0.107	0.062	0.30	0.20	0.16
	LTE Band 66	Right Cheek	0.213	0.111	0.058	0.036	0.32	0.27	0.25
		Right Tilted	0.103	0.094	0.038	0.026	0.20	0.14	0.13
		Left Cheek	0.439	0.327	0.165	0.094	0.77	0.60	0.53
		Left Tilted	0.106	0.203	0.107	0.062	0.31	0.21	0.17



15.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	4	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)		
GSM	GSM850	Front	0.654	0.084	0.036	0.74	0.69
		Back	0.630	0.187	0.048	0.82	0.68
		Left side	0.723			0.72	0.72
		Right side	0.883	0.091	0.022	0.97	0.91
		Top side		0.078	0.032	0.08	0.03
		Bottom side	0.210			0.21	0.21
	GSM1900	Front	0.384	0.084	0.036	0.47	0.42
		Back	0.380	0.187	0.048	0.57	0.43
		Left side	0.138			0.14	0.14
		Right side	0.009	0.091	0.022	0.10	0.03
		Top side		0.078	0.032	0.08	0.03
		Bottom side	1.075			1.08	1.08
WCDMA	WCDMA II	Front	0.456	0.084	0.036	0.54	0.49
		Back	0.401	0.187	0.048	0.59	0.45
		Left side	0.235			0.24	0.24
		Right side	0.018	0.091	0.022	0.11	0.04
		Top side		0.078	0.032	0.08	0.03
		Bottom side	1.002			1.00	1.00
	WCDMA IV	Front	0.588	0.084	0.036	0.67	0.62
		Back	0.514	0.187	0.048	0.70	0.56
		Left side	0.161			0.16	0.16
		Right side	0.014	0.091	0.022	0.11	0.04
		Top side		0.078	0.032	0.08	0.03
		Bottom side	1.143			1.14	1.14
	WCDMA V	Front	0.645	0.084	0.036	0.73	0.68
		Back	0.631	0.187	0.048	0.82	0.68
		Left side	0.659			0.66	0.66
		Right side	0.781	0.091	0.022	0.87	0.80
		Top side		0.078	0.032	0.08	0.03
		Bottom side	0.143			0.14	0.14
LTE	LTE Band 2	Front	0.509	0.084	0.036	0.59	0.55
		Back	0.410	0.187	0.048	0.60	0.46
		Left side	0.238			0.24	0.24
		Right side	0.015	0.091	0.022	0.11	0.04
		Top side		0.078	0.032	0.08	0.03
		Bottom side	1.027			1.03	1.03
	LTE Band 4	Front	0.487	0.084	0.036	0.57	0.52
		Back	0.418	0.187	0.048	0.61	0.47
		Left side	0.157			0.16	0.16
		Right side	0.017	0.091	0.022	0.11	0.04
		Top side		0.078	0.032	0.08	0.03
		Bottom side	1.066			1.07	1.07



WWAN Band		Exposure Position	1	2	4	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)		
LTE	LTE Band 5	Front	0.575	0.084	0.036	0.66	0.61
		Back	0.575	0.187	0.048	0.76	0.62
		Left side	0.635			0.64	0.64
		Right side	0.656	0.091	0.022	0.75	0.68
		Top side		0.078	0.032	0.08	0.03
		Bottom side	0.096			0.10	0.10
	LTE Band 7	Front	0.711	0.084	0.036	0.80	0.75
		Back	0.842	0.187	0.048	1.03	0.89
		Left side	0.142			0.14	0.14
		Right side	0.274	0.091	0.022	0.37	0.30
		Top side		0.078	0.032	0.08	0.03
		Bottom side	0.189			0.19	0.19
	LTE Band 12	Front	0.186	0.084	0.036	0.27	0.22
		Back	0.209	0.187	0.048	0.40	0.26
		Left side	0.181			0.18	0.18
		Right side	0.191	0.091	0.022	0.28	0.21
		Top side		0.078	0.032	0.08	0.03
		Bottom side	0.028			0.03	0.03
	LTE Band 13	Front	0.412	0.084	0.036	0.50	0.45
		Back	0.412	0.187	0.048	0.60	0.46
		Left side	0.435			0.44	0.44
		Right side	0.404	0.091	0.022	0.50	0.43
		Top side		0.078	0.032	0.08	0.03
		Bottom side	0.036			0.04	0.04
	LTE Band 25	Front	0.508	0.084	0.036	0.59	0.54
		Back	0.416	0.187	0.048	0.60	0.46
		Left side	0.237			0.24	0.24
		Right side	0.015	0.091	0.022	0.11	0.04
		Top side		0.078	0.032	0.08	0.03
		Bottom side	1.022			1.02	1.02
	LTE Band 66	Front	0.511	0.084	0.036	0.60	0.55
		Back	0.435	0.187	0.048	0.62	0.48
		Left side	0.155			0.16	0.16
		Right side	0.016	0.091	0.022	0.11	0.04
		Top side		0.078	0.032	0.08	0.03
		Bottom side	1.069			1.07	1.07



WWAN Band		Exposure Position	1	2	4	1+2 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	Bluetooth 10g SAR (W/kg)		
GSM	GSM850	Front	0.513	0.044	0.018	0.56	0.53
		Back	0.436	0.088	0.022	0.52	0.46
		Left side	0.490			0.49	0.49
		Right side	0.603	0.049	0.011	0.65	0.61
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.113			0.11	0.11
	GSM1900	Front	0.208	0.044	0.018	0.25	0.23
		Back	0.217	0.088	0.022	0.31	0.24
		Left side	0.080			0.08	0.08
		Right side	0.005	0.049	0.011	0.05	0.02
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.588			0.59	0.59
WCDMA	WCDMA II	Front	0.251	0.044	0.018	0.30	0.27
		Back	0.230	0.088	0.022	0.32	0.25
		Left side	0.139			0.14	0.14
		Right side	0.012	0.049	0.011	0.06	0.02
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.544			0.54	0.54
	WCDMA IV	Front	0.327	0.044	0.018	0.37	0.35
		Back	0.294	0.088	0.022	0.38	0.32
		Left side	0.098			0.10	0.10
		Right side	0.009	0.049	0.011	0.06	0.02
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.629			0.63	0.63
	WCDMA V	Front	0.506	0.044	0.018	0.55	0.52
		Back	0.435	0.088	0.022	0.52	0.46
		Left side	0.454			0.45	0.45
		Right side	0.536	0.049	0.011	0.59	0.55
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.078			0.08	0.08
LTE	LTE Band 2	Front	0.276	0.044	0.018	0.32	0.29
		Back	0.234	0.088	0.022	0.32	0.26
		Left side	0.141			0.14	0.14
		Right side	0.010	0.049	0.011	0.06	0.02
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.557			0.56	0.56
	LTE Band 4	Front	0.272	0.044	0.018	0.32	0.29
		Back	0.240	0.088	0.022	0.33	0.26
		Left side	0.095			0.10	0.10
		Right side	0.011	0.049	0.011	0.06	0.02
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.588			0.59	0.59



WWAN Band		Exposure Position	1	2	4	1+2 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	Bluetooth 10g SAR (W/kg)		
LTE	LTE Band 5	Front	0.452	0.044	0.018	0.50	0.47
		Back	0.445	0.088	0.022	0.53	0.47
		Left side	0.439			0.44	0.44
		Right side	0.453	0.049	0.011	0.50	0.46
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.051			0.05	0.05
	LTE Band 7	Front	0.325	0.044	0.018	0.37	0.34
		Back	0.390	0.088	0.022	0.48	0.41
		Left side	0.079			0.08	0.08
		Right side	0.138	0.049	0.011	0.19	0.15
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.083			0.08	0.08
	LTE Band 12	Front	0.150	0.044	0.018	0.19	0.17
		Back	0.165	0.088	0.022	0.25	0.19
		Left side	0.129			0.13	0.13
		Right side	0.135	0.049	0.011	0.18	0.15
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.016			0.02	0.02
	LTE Band 13	Front	0.299	0.044	0.018	0.34	0.32
		Back	0.294	0.088	0.022	0.38	0.32
		Left side	0.303			0.30	0.30
		Right side	0.281	0.049	0.011	0.33	0.29
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.021			0.02	0.02
	LTE Band 25	Front	0.278	0.044	0.018	0.32	0.30
		Back	0.236	0.088	0.022	0.32	0.26
		Left side	0.141			0.14	0.14
		Right side	0.010	0.049	0.011	0.06	0.02
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.554			0.55	0.55
	LTE Band 66	Front	0.284	0.044	0.018	0.33	0.30
		Back	0.248	0.088	0.022	0.34	0.27
		Left side	0.095			0.10	0.10
		Right side	0.011	0.049	0.011	0.06	0.02
		Top side		0.039	0.015	0.04	0.02
		Bottom side	0.598			0.60	0.60



15.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Front	0.619	0.051	0.014	0.011	0.67	0.63	0.63
		Back	0.548	0.042	0.122	0.014	0.59	0.67	0.56
	GSM1900	Front	0.518	0.051	0.014	0.011	0.57	0.53	0.53
		Back	0.269	0.042	0.122	0.014	0.31	0.39	0.28
WCDMA	WCDMA II	Front	0.816	0.051	0.014	0.011	0.87	0.83	0.83
		Back	0.741	0.042	0.122	0.014	0.78	0.86	0.76
	WCDMA IV	Front	1.069	0.051	0.014	0.011	1.12	1.08	1.08
		Back	0.952	0.042	0.122	0.014	0.99	1.07	0.97
	WCDMA V	Front	0.584	0.051	0.014	0.011	0.64	0.60	0.60
		Back	0.525	0.042	0.122	0.014	0.57	0.65	0.54
LTE	LTE Band 2	Front	0.897	0.051	0.014	0.011	0.95	0.91	0.91
		Back	0.634	0.042	0.122	0.014	0.68	0.76	0.65
	LTE Band 4	Front	0.929	0.051	0.014	0.011	0.98	0.94	0.94
		Back	0.875	0.042	0.122	0.014	0.92	1.00	0.89
	LTE Band 5	Front	0.512	0.051	0.014	0.011	0.56	0.53	0.52
		Back	0.490	0.042	0.122	0.014	0.53	0.61	0.50
	LTE Band 7	Front	0.293	0.051	0.014	0.011	0.34	0.31	0.30
		Back	0.304	0.042	0.122	0.014	0.35	0.43	0.32
	LTE Band 12	Front	0.170	0.051	0.014	0.011	0.22	0.18	0.18
		Back	0.183	0.042	0.122	0.014	0.23	0.31	0.20
	LTE Band 13	Front	0.365	0.051	0.014	0.011	0.42	0.38	0.38
		Back	0.371	0.042	0.122	0.014	0.41	0.49	0.39
	LTE Band 25	Front	0.771	0.051	0.014	0.011	0.82	0.79	0.78
		Back	0.579	0.042	0.122	0.014	0.62	0.70	0.59
	LTE Band 66	Front	0.879	0.051	0.014	0.011	0.93	0.89	0.89
		Back	0.789	0.042	0.122	0.014	0.83	0.91	0.80

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
GSM	GSM850	Front	0.480	0.028	0.003	0.006	0.51	0.48	0.49
		Back	0.423	0.023	0.043	0.010	0.45	0.47	0.43
	GSM1900	Front	0.302	0.028	0.003	0.006	0.33	0.31	0.31
		Back	0.159	0.023	0.043	0.010	0.18	0.20	0.17
WCDMA	WCDMA II	Front	0.476	0.028	0.003	0.006	0.50	0.48	0.48
		Back	0.441	0.023	0.043	0.010	0.46	0.48	0.45
	WCDMA IV	Front	0.634	0.028	0.003	0.006	0.66	0.64	0.64
		Back	0.576	0.023	0.043	0.010	0.60	0.62	0.59
	WCDMA V	Front	0.454	0.028	0.003	0.006	0.48	0.46	0.46
		Back	0.405	0.023	0.043	0.010	0.43	0.45	0.42
LTE	LTE Band 2	Front	0.524	0.028	0.003	0.006	0.55	0.53	0.53
		Back	0.376	0.023	0.043	0.010	0.40	0.42	0.39
	LTE Band 4	Front	0.557	0.028	0.003	0.006	0.59	0.56	0.56
		Back	0.529	0.023	0.043	0.010	0.55	0.57	0.54
	LTE Band 5	Front	0.400	0.028	0.003	0.006	0.43	0.40	0.41
		Back	0.379	0.023	0.043	0.010	0.40	0.42	0.39
	LTE Band 7	Front	0.141	0.028	0.003	0.006	0.17	0.14	0.15
		Back	0.148	0.023	0.043	0.010	0.17	0.19	0.16
	LTE Band 12	Front	0.135	0.028	0.003	0.006	0.16	0.14	0.14
		Back	0.144	0.023	0.043	0.010	0.17	0.19	0.15
	LTE Band 13	Front	0.286	0.028	0.003	0.006	0.31	0.29	0.29
		Back	0.289	0.023	0.043	0.010	0.31	0.33	0.30
	LTE Band 25	Front	0.450	0.028	0.003	0.006	0.48	0.45	0.46
		Back	0.351	0.023	0.043	0.010	0.37	0.39	0.36
	LTE Band 66	Front	0.522	0.028	0.003	0.006	0.55	0.53	0.53
		Back	0.477	0.023	0.043	0.010	0.50	0.52	0.49

Test Engineer : Tommy Chen Thomas Wang San Lin Wilson Lin Galen Chang and Nick Yu

16. Uncertainty Assessment

Pre KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [11] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.