




FCC RADIO TEST REPORT

FCC ID : PY7-75158T
Equipment : GSM/WCDMA/LTE Phone with BT, DTS/UNII
a/b/g/n/ac/ax, NFC and GNSS
Brand Name : Sony
Applicant : Sony Corporation
1-7-1 Konan, Minato-ku , Tokyo, Japan 108-0075
Manufacturer : Sony Corporation
1-7-1 Konan, Minato-ku , Tokyo, Japan 108-0075
Standard : FCC Part 15 Subpart C §15.225

The product was received on Feb. 03, 2026 and testing was performed from Mar. 05, 2026 to Apr. 09, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1. General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2. Test Configuration of Equipment Under Test.....	7
2.1 Descriptions of Test Mode.....	7
2.2 Connection Diagram of Test System	7
2.3 Table for Supporting Units	8
2.4 EUT Operation Test Setup	8
3. Test Results	9
3.1 AC Power Line Conducted Emissions Measurement	9
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement.....	11
3.3 Frequency Stability Measurement	12
3.4 Field Strength of Fundamental Emissions and Mask Measurement.....	13
3.5 Radiated Emissions Measurement.....	15
3.6 Antenna Requirements.....	18
4. List of Measuring Equipment	19
5. Measurement Uncertainty.....	20
Appendix A. Test Results of Conducted Emission Test	
Appendix B. Test Results of Near Field Test Items	
B1. Test Result of 20dB Spectrum Bandwidth	
B2. Test Result of Frequency Stability	
Appendix C. Test Results of Radiated Test Items	
C1. Test Result of Field Strength of Fundamental Emissions	
C2. Results of Radiated Emissions (9 kHz~30MHz)	
C3. Results of Radiated Emissions (30MHz~1GHz)	



History of this test report

Report No.	Version	Description	Issue Date
FR620304D	01	Initial issue of report	Jun. 17, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	4.83 dB under the limit at 1.05MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
	2.1049	99% OBW Spectrum Bandwidth	Pass	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 16.90 dB μ V/m at 13.56 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	8.81 dB under the limit at 30.00MHz
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Freda Wu

1. General Description

1.1 Product Feature of Equipment Under Test

Product Specification is subject to this standard	
General Specs	GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC and BDS/Galileo/GLONASS/GPS.
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass / BDS / Galileo: PIFA Antenna NFC: LOOP Antenna

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	0.27	SEABBAG0AWE0004B	RF conducted measurement
	0.27	SEABBAG0AWE00018	Radiated Spurious Emission
	0.27	SEABBAG0AWE0000A SEABBAG0AWE0008D	Conducted Emission

Specification of Accessory		
AC Adapter	Brand Name	Sony
	Model Name	XQZ-UC1
Earphone	Brand Name	Sony
	Model Name	MDR-EX15AP
USB Cable 1	Brand Name	Sony
	Model Name	XQZ-UB1
USB Cable 2	Brand Name	Sony
	Model Name	UCB20

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW1190 and TW3786

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. The Radiated Spurious Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ FCC Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.


Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in reader mode with NFC tag (four NFC type A, B, F, V) and without reading tag. Based on the highest field strength of fundamental and spurious emissions, the worst case type (type B) was recorded in this report.

The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and three receiving antenna orientations (parallel, perpendicular, and ground-parallel) for LOOP Antenna, and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

Test Cases	
AC Conducted Emission	Mode 1: NFC Link + USB Cable + Earphone + Adapter

2.2 Connection Diagram of Test System



Conduction Test Setup			
No.	Wireless Station	Connection Type	Test Mode
			1
A1	NFC	NFC Tx	X
No.	Power Source	Connection Type	1
B1	AC : 120V/60Hz	AC Power Cable	X
No.	Setup Peripherals	Connection Type	1
C1	Earphone	Earphone jack	X

Radiation Tx Test Setup				
No.	Wireless Station	Connection Type	Test Mode	
			1	2
A1	NFC Card	NFC		X
No.	Power Source	Connection Type	1	2
B1	AC : 120V/60Hz	AC Power Cable	X	X
No.	Setup Peripherals	Connection Type	1	2
C1	Earphone	Earphone jack	X	X

2.3 Table for Supporting Units

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Earphone	Sony	MDR-EX15AP	N/A	Unshielded, 1.2 m	N/A
2.	NFC Card	Winso	N/A	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The EUT is programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmitting signal (Power Level: Default) at 13.56MHz

For without reading tag mode is send commands to realize EUT in transmit mode.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

Note:

(1) with antenna

Remark: 13.56 MHz is the NFC RF fundamental signal.

(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20 dB and 99% emission bandwidth in the specific band 13.553~13.567 MHz.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max Hold Mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20 dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Near Field Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed by using a new battery.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT has transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 100 ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Near Field Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

Remark:

1. The field strength test result is in 3m test distance, follow test rules the test data use distance extrapolation factor and reported in this report at 30m test result.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)

3.4.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower is placed 3 meters far away from the turntable.
 2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
 3. The height of the receiving antenna is fixed at one meter above ground to find the maximum emissions field strength.
 4. For Fundamental emissions, use the receiver to measure QP reading.
 5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
 6. Compliance with the spectrum mask is tested with RBW set to 9 kHz.
- Note: Emission level (dB μ V/m) = 20 log Emission level (μ V/m).

3.4.4 Test Setup

For radiated test below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna is varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower is scanned (from 1 M to 4 M) and then the turntable is rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30 MHz, loop antenna has to be used for measurement and the recorded data shall be QP measured by receiver.
8. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.

3.5.5 Test Setup

For radiated test below 30MHz



For radiated test above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark:

1. There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.
2. After pre-scan three receiving antenna orientations parallel (horizontal), perpendicular(vertical), and ground-parallel for Loop Antenna, the worst case is receiving antenna parallel.



3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4. List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 06, 2026	Apr. 02, 2026~ Apr. 09, 2026	Jan. 05, 2027	Radiation (03CH07-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	35419 & 03	30MHz~1GHz	Apr. 21, 2025	Apr. 02, 2026~ Apr. 09, 2026	Apr. 20, 2026	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Mar. 16, 2026	Apr. 02, 2026~ Apr. 09, 2026	Mar. 15, 2027	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Sep. 30, 2025	Apr. 02, 2026~ Apr. 09, 2026	Sep. 29, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4 MY15682/4	30MHz to 18GHz	Feb. 19, 2026	Apr. 02, 2026~ Apr. 09, 2026	Feb. 18, 2027	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4	9kHz to 30MHz	Feb. 19, 2026	Apr. 02, 2026~ Apr. 09, 2026	Feb. 18, 2027	Radiation (03CH07-HY)
Antenna Mast	MF	MF-7802	N/A	Control Turn table	N/A	Apr. 02, 2026~ Apr. 09, 2026	N/A	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Apr. 02, 2026~ Apr. 09, 2026	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Apr. 02, 2026~ Apr. 09, 2026	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Apr. 02, 2026~ Apr. 09, 2026	N/A	Radiation (03CH07-HY)
Software	Audix	E3	RK-002396	N/A	N/A	Apr. 02, 2026~ Apr. 09, 2026	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Mar. 02, 2026	Apr. 02, 2026~ Apr. 09, 2026	Mar. 01, 2027	Radiation (03CH07-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 05, 2026	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 05, 2026	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2025	Mar. 05, 2026	Oct. 19, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 02, 2026	Mar. 05, 2026	Mar. 01, 2027	Conduction (CO07-HY)
Two-Line V- Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Mar. 05, 2026	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Oct. 21, 2025	Mar. 05, 2026	Oct. 20, 2026	Conduction (CO07-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 30, 2025	Mar. 30, 2026	Sep. 29, 2026	Near Field (TH05-HY)
DC Power Supply	GW Instek	GPE-2323	GEU871221	0V~64V ; 0A~6A	Apr. 14, 2025	Mar. 30, 2026	Apr. 13, 2026	Near Field (TH05-HY)
Temperature Chamber	ESPEC	SU-242	93000763	-30℃ ~95℃	Jan. 05, 2026	Mar. 30, 2026	Jan. 04, 2027	Near Field (TH05-HY)
Hygrometer	TECPEL	DTM-303A	TP224371	N/A	Jun. 16, 2025	Mar. 30, 2026	Jun. 15, 2026	Near Field (TH05-HY)

5. Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.3 dB
---	--------




Appendix A. Test Results of Conducted Emission Test

EUT Information

Report NO : 620304
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	39.23	56.00	16.77	L1	ON	20.2
0.150000	54.09	---	66.00	11.91	L1	ON	20.2
0.163500	---	32.22	55.28	23.06	L1	ON	20.1
0.163500	53.58	---	65.28	11.70	L1	ON	20.1
0.181500	---	30.40	54.42	24.02	L1	ON	20.1
0.181500	52.89	---	64.42	11.53	L1	ON	20.1
0.199500	---	31.48	53.63	22.15	L1	ON	20.1
0.199500	51.22	---	63.63	12.41	L1	ON	20.1
0.224250	---	28.54	52.66	24.12	L1	ON	20.1
0.224250	48.00	---	62.66	14.66	L1	ON	20.1
0.246750	---	25.27	51.87	26.60	L1	ON	20.1
0.246750	48.12	---	61.87	13.75	L1	ON	20.1
0.276000	---	26.10	50.94	24.84	L1	ON	20.1
0.276000	45.62	---	60.94	15.32	L1	ON	20.1
0.312000	---	25.38	49.92	24.54	L1	ON	20.0
0.312000	44.80	---	59.92	15.12	L1	ON	20.0
0.350250	---	22.53	48.96	26.43	L1	ON	20.0
0.350250	42.32	---	58.96	16.64	L1	ON	20.0
0.395250	---	22.89	47.95	25.06	L1	ON	20.0

0.395250	41.45	---	57.95	16.50	L1	ON	20.0
0.444750	---	19.80	46.97	27.17	L1	ON	20.0
0.444750	37.80	---	56.97	19.17	L1	ON	20.0
0.489750	---	16.76	46.17	29.41	L1	ON	20.0
0.489750	37.23	---	56.17	18.94	L1	ON	20.0
0.510000	---	20.56	46.00	25.44	L1	ON	20.0
0.510000	35.15	---	56.00	20.85	L1	ON	20.0
0.559500	---	19.47	46.00	26.53	L1	ON	20.0
0.559500	34.84	---	56.00	21.16	L1	ON	20.0
0.597750	---	20.83	46.00	25.17	L1	ON	20.0
0.597750	34.41	---	56.00	21.59	L1	ON	20.0
0.640500	---	15.93	46.00	30.07	L1	ON	20.0
0.640500	32.77	---	56.00	23.23	L1	ON	20.0
0.674250	---	17.97	46.00	28.03	L1	ON	20.0
0.674250	29.43	---	56.00	26.57	L1	ON	20.0
0.714750	---	17.03	46.00	28.97	L1	ON	20.0
0.714750	29.48	---	56.00	26.52	L1	ON	20.0
1.050000	---	36.84	46.00	9.16	L1	ON	20.0
1.050000	43.12	---	56.00	12.88	L1	ON	20.0
1.792500	---	20.29	46.00	25.71	L1	ON	20.0
1.792500	34.39	---	56.00	21.61	L1	ON	20.0
13.560000	---	53.49	50.00	-3.49	L1	ON	20.6
13.560000	55.30	---	60.00	4.70	L1	ON	20.6
18.690000	---	18.30	50.00	31.70	L1	ON	20.8
18.690000	25.02	---	60.00	34.98	L1	ON	20.8

EUT Information

Report NO : 620304
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	32.04	55.88	23.84	N	ON	20.1
0.152250	53.23	---	65.88	12.65	N	ON	20.1
0.163500	---	28.34	55.28	26.94	N	ON	20.1
0.163500	51.30	---	65.28	13.98	N	ON	20.1
0.181500	---	32.53	54.42	21.89	N	ON	20.1
0.181500	51.58	---	64.42	12.84	N	ON	20.1
0.201750	---	26.12	53.54	27.42	N	ON	20.1
0.201750	48.51	---	63.54	15.03	N	ON	20.1
0.222000	---	27.19	52.74	25.55	N	ON	20.1
0.222000	47.72	---	62.74	15.02	N	ON	20.1
0.258000	---	24.37	51.50	27.13	N	ON	20.1
0.258000	44.88	---	61.50	16.62	N	ON	20.1
0.291750	---	22.95	50.47	27.52	N	ON	20.0
0.291750	43.18	---	60.47	17.29	N	ON	20.0
0.341250	---	20.93	49.17	28.24	N	ON	20.0
0.341250	40.20	---	59.17	18.97	N	ON	20.0
0.395250	---	18.79	47.95	29.16	N	ON	20.0
0.395250	39.56	---	57.95	18.39	N	ON	20.0
0.433500	---	17.07	47.19	30.12	N	ON	20.0

0.433500	37.32	---	57.19	19.87	N	ON	20.0
0.489750	---	18.10	46.17	28.07	N	ON	20.0
0.489750	34.78	---	56.17	21.39	N	ON	20.0
0.539250	---	15.63	46.00	30.37	N	ON	20.0
0.539250	33.73	---	56.00	22.27	N	ON	20.0
1.050000	---	41.17	46.00	4.83	N	ON	20.0
1.050000	45.83	---	56.00	10.17	N	ON	20.0
1.902750	---	20.88	46.00	25.12	N	ON	20.0
1.902750	31.83	---	56.00	24.17	N	ON	20.0
13.560000	---	55.70	50.00	-5.70	N	ON	20.6
13.560000	57.75	---	60.00	2.25	N	ON	20.6

EUT Information

Report NO : 620304
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	25.26	50.00	24.74	L1	ON	20.6
13.560000	30.87	---	60.00	29.13	L1	ON	20.6

EUT Information

Report NO : 620304
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum





Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	25.38	50.00	24.62	N	ON	20.6
13.560000	30.30	---	60.00	29.70	N	ON	20.6

Appendix B. Test Results of Near Field Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode		Test Frequency (MHz)	
NFC Tx		13.56	
			
Date: 30.MAR.2026 09:27:20		Date: 30.MAR.2026 09:25:32	
20dB Bandwidth (kHz)	2.64	99% OccupiedBW(kHz)	2.24
Frequency range (MHz)	$f_L > 13.553$	13.55866	Test Result
	$f_H < 13.567$	13.56130	Complies

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

**B2. Test Result of Frequency Stability**


Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (°C)	Time (min)	Measurement Frequency (MHz)
3.89	13.559980	-20	0	13.560070
3.4	13.559980		2	13.560080
4.48	13.559980		5	13.560080
			10	13.560080
		-10	0	13.560070
			2	13.560070
			5	13.560060
			10	13.560070
		0	0	13.560060
			2	13.560060
			5	13.560060
			10	13.560060
		10	0	13.560040
			2	13.560040
			5	13.560040
			10	13.560040
		20	0	13.560010
			2	13.560010
			5	13.560000
			10	13.560000
		30	0	13.559980
			2	13.559980
			5	13.559960
			10	13.559970
		40	0	13.559930
			2	13.559920
			5	13.559930
			10	13.559920




Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (°C)	Time (min)	Measurement Frequency (MHz)
		50	0	13.559920
			2	13.559920
			5	13.559920
			10	13.559920
Max.Deviation (MHz)	-0.000020	Max.Deviation (MHz)		-0.000080
Max.Deviation (ppm)	-1.4749	Max.Deviation (ppm)		-5.8997
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS


Appendix C. Test Results of Radiated Test Items


C1. Test Result of Field Strength of Fundamental Emissions



**Note :**


- Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB) = $40 \log (30/3) = 40$ (dB)
- Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.




**Note :**


1. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB) = $40 \log (30/3) = 40$ (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.


C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)




Note :


1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
 EX.:
 For below 490kHz Distance extrapolation factor = $40 \log (300/3) = 80$ (dB)
 For 490kHz to 30MHz Distance extrapolation factor = $40 \log (30/3) = 40$ (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored




**Note :**


- The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
EX.:
For below 490kHz Distance extrapolation factor = $40 \log (300/3) = 80$ (dB)
For 490kHz to 30MHz Distance extrapolation factor = $40 \log (30/3) = 40$ (dB)
- Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
- 13.56 MHz is fundamental signal which can be ignored


C3. Results of Radiated Spurious Emissions (30MHz~1GHz)



**Note:**

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.



**Note:**

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as “-” means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.

————THE END————