FCC RF Test Report

APPLICANT	:	Sony Mobile Communications Inc.
EQUIPMENT	:	GSM/WCDMA/LTE Phone+Bluetooth, DTS/UNII a/b/g/n and NFC
BRAND NAME	:	Sony
FCC ID	:	PY7-PM0921
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The product was received on Oct. 07, 2015 and testing was completed on Dec. 29, 2015. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory 1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Modification of EUT 6
1.5 Testing Location 7
1.6 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Carrier Frequency Channel 8
2.2 Pre-Scanned RF Power 9
2.3 Test Mode 10
2.4 Connection Diagram of Test System 11
2.5 Support Unit used in test configuration and system 12
2.6 EUT Operation Test Setup 12
2.7 Measurement Results Explanation Example 12

3 TEST RESULT **13**

3.1 6dB and 99% Bandwidth Measurement 13
3.2 Output Power Measurement 15
3.3 Power Spectral Density Measurement 17
3.4 Conducted Band Edges and Spurious Emission Measurement 19
3.5 Radiated Band Edges and Spurious Emission Measurement 32
3.6 AC Conducted Emission Measurement 36
3.7 Antenna Requirements 40

4 LIST OF MEASURING EQUIPMENT **41**

5 UNCERTAINTY OF EVALUATION **43**

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED TEST RESULTS

APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR582708-02C	Rev. 01	Initial issue of report	Jan. 21, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.02 dB at 2484.240 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 17.80 dB at 0.158 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Remark: The FCC ID: PY7-PM0920 and FCC ID: PY7-PM0921 is similar device, in this report all the test result are referred to PY7-PM0920, Sporton Report No: FR5O0716C.

1 General Description

1.1 Applicant

Sony Mobile Communications Inc.
Nya Vattentornet, 22188 Lund, Sweden

1.2 Manufacturer

Sony Mobile Communications Inc.
1-8-15 Konan, Minato-ku, Tokyo, 108-0075, Japan

1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n NFC and GPS

Product Specification subjective to this standard	
Antenna Type / Gain	802.11b/g/n : PIFA Antenna with gain -3.00 dBi
HW Version	A
SW Version	33.2.B.0.19

<FR5O0716C>

EUT Information List				
IMEI	HW Version	SW Version	S/N	Performed Test Item
IMEI 1: 004402455537120	A	33.2.A.0.19	RQ3000D4EL	RF conducted measurement
IMEI 1 : 004402455535371			RQ3000D4PK	Radiated Spurious Emission
IMEI 1: 004402455535215			RQ3000D4J1	Conducted Emission

Accessory List	
AC Adapter 1	Model No. : UCH20
	Type No. : AC-0060-US
	S/N : 1215W43609270 (for radiated spurious emission) 1215W48600011 (for conducted emission)
Earphone	Model No. : MH410c
	Type No. : AG-1110
	S/N : 1541A8180036E76(for radiated spurious emission) 1541A8170036EC2 (for conducted emission)
Battery 1	Model No. : LIS1618ERPC
USB Cable 1	Model No. : EC803
	Type No. : AI-0404
	S/N : 153812AF5009094 (for radiated spurious emission) 153812AA503376C (for conducted emission)

Note:

1. Above EUT list and accessory list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test.
3. For other wireless features of this EUT, test report will be issued separately.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b mode				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	19.98	19.78	19.75	19.77

2.4GHz 802.11g mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	22.59	22.50	22.53	22.50	22.48	22.52	22.53	22.56

2.4GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	22.45	22.38	22.29	22.27	22.13	22.39	22.41	22.44

2.4GHz 802.11n HT40 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	22.56	21.72	21.81	21.67	21.77	22.41	22.52	22.55

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

<2.4GHz>

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + MP3 + Battery 1 + Earphone + USB Cable 1 (Charging from Adapter 1)

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Samsung	SBH20	PY7-RD0010	Unshielded, 0.75 m	N/A
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A of this test report.

Minimum 6dB Bandwidth



Date: 17.NOV.2015 19:48:43

Maximum 99% Occupied Bandwidth



Date: 29.NOV.2015 17:31:39

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r03 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.

Worst Case Power Density (dBm/3kHz)



Date: 17.NOV.2015 20:01:39

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	**Temperature :**	21~26℃
Test Band :	2.4GHz Low	**Relative Humidity :**	45~54%
Test Channel :	01	**Test Engineer :**	Luffy_Lin

WLAN 802.11b Channel 01

100kHz PSD reference Level



Date: 17.NOV.2015 19:49:46

Low Channel Plot



Date: 17.NOV.2015 19:50:03

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 19:50:20

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 19:50:28

Test Mode :	802.11b	**Temperature :**	21~26℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	45~54%
Test Channel :	06	**Test Engineer :**	Luffy_Lin

WLAN 802.11b Channel 06

100kHz PSD reference Level



Date: 17.NOV.2015 19:55:32

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 19:55:48

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 19:55:56

Test Mode :	802.11b	**Temperature :**	21~26℃
Test Band :	2.4GHz High	**Relative Humidity :**	45~54%
Test Channel :	11	**Test Engineer :**	Luffy_Lin

WLAN 802.11b Channel 11

100kHz PSD reference Level



Date: 17.NOV.2015 20:02:03

High Channel Plot



Date: 17.NOV.2015 20:02:23

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 20:02:42

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 20:02:50

Test Mode :	802.11g	**Temperature :**	21~26℃
Test Band :	2.4GHz Low	**Relative Humidity :**	45~54%
Test Channel :	01	**Test Engineer :**	Luffy_Lin

WLAN 802.11g Channel 01

100kHz PSD reference Level



Date: 17.NOV.2015 20:20:40

Low Channel Plot



Date: 17.NOV.2015 20:20:57

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 20:22:39

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 20:22:47

Test Mode :	802.11g	**Temperature :**	21~26℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	45~54%
Test Channel :	06	**Test Engineer :**	Luffy_Lin

WLAN 802.11g Channel 06

100kHz PSD reference Level



Date: 17.NOV.2015 20:28:03

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 20:29:18

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 20:29:26

Test Mode :	802.11g	**Temperature :**	21~26℃
Test Band :	2.4GHz High	**Relative Humidity :**	45~54%
Test Channel :	11	**Test Engineer :**	Luffy_Lin

WLAN 802.11g Channel 11

100kHz PSD reference Level



Date: 17.NOV.2015 20:33:49

High Channel Plot



Date: 17.NOV.2015 20:34:35

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 20:34:50

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 20:34:59

Test Mode :	802.11n HT20	**Temperature :**	21~26℃
Test Band :	2.4GHz Low	**Relative Humidity :**	45~54%
Test Channel :	01	**Test Engineer :**	Luffy_Lin

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Date: 17.NOV.2015 20:57:08

Low Channel Plot



Date: 17.NOV.2015 20:57:29

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 20:58:05

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 20:58:14

Test Mode :	802.11n HT20	**Temperature :**	21~26℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	45~54%
Test Channel :	06	**Test Engineer :**	Luffy_Lin

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level



Date: 17.NOV.2015 21:02:28

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 21:02:43

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 21:02:52

Test Mode :	802.11n HT20	**Temperature :**	21~26℃
Test Band :	2.4GHz High	**Relative Humidity :**	45~54%
Test Channel :	11	**Test Engineer :**	Luffy_Lin

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



Date: 17.NOV.2015 21:06:55

High Channel Plot



Date: 17.NOV.2015 21:08:09

Spurious Emission 30MHz~3GHz



Date: 17.NOV.2015 21:09:23

Spurious Emission 2GHz~25GHz



Date: 17.NOV.2015 21:09:31

Test Mode :	802.11n HT40	**Temperature :**	21~26℃
Test Band :	2.4GHz Low	**Relative Humidity :**	45~54%
Test Channel :	03	**Test Engineer :**	Luffy_Lin

WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level



Date: 29.NOV.2015 17:21:32

Low Channel Plot



Date: 29.NOV.2015 17:21:47

Spurious Emission 30MHz~3GHz



Date: 29.NOV.2015 17:21:59

Spurious Emission 2GHz~25GHz



Date: 29.NOV.2015 17:22:08

Test Mode :	802.11n HT40	**Temperature :**	21~26℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	45~54%
Test Channel :	06	**Test Engineer :**	Luffy_Lin

WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level



Date: 29.NOV.2015 17:30:32

Spurious Emission 30MHz~3GHz



Date: 29.NOV.2015 17:31:07

Spurious Emission 2GHz~25GHz



Date: 29.NOV.2015 17:31:16

Test Mode :	802.11n HT40	**Temperature :**	21~26℃
Test Band :	2.4GHz High	**Relative Humidity :**	45~54%
Test Channel :	09	**Test Engineer :**	Luffy_Lin

WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level



Date: 29.NOV.2015 17:16:34

High Channel Plot



Date: 29.NOV.2015 17:18:01

Spurious Emission 30MHz~3GHz



Date: 29.NOV.2015 17:18:12

Spurious Emission 2GHz~25GHz



Date: 29.NOV.2015 17:18:20

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μs)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	97.2	1390	0.72	1kHz
2.4GHz 802.11n HT20	97.04	1310	0.76	1kHz
2.4GHz 802.11n HT40	94.72	646	1.55	3kHz

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	22~23℃
Test Engineer :	Derreck Chen	**Relative Humidity :**	52~55%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + MP3 + Battery 1 + Earphone + USB Cable 1 (Charging from Adapter 1)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	47.8	Off	L1	19.6	17.8	65.6
0.182000	45.8	Off	L1	19.7	18.6	64.4
0.214000	39.4	Off	L1	19.7	23.6	63.0
0.270000	36.5	Off	L1	19.7	24.6	61.1
0.318000	35.5	Off	L1	19.7	24.3	59.8
0.398000	33.5	Off	L1	19.7	24.4	57.9
2.110000	31.3	Off	L1	19.6	24.7	56.0
13.990000	34.0	Off	L1	19.8	26.0	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	29.9	Off	L1	19.6	25.7	55.6
0.182000	30.6	Off	L1	19.7	23.8	54.4
0.214000	25.2	Off	L1	19.7	27.8	53.0
0.270000	25.0	Off	L1	19.7	26.1	51.1
0.318000	23.0	Off	L1	19.7	26.8	49.8
0.398000	20.9	Off	L1	19.7	27.0	47.9
2.110000	22.2	Off	L1	19.6	23.8	46.0
13.990000	26.4	Off	L1	19.8	23.6	50.0

Test Mode :	Mode 1	**Temperature :**	22~23℃
Test Engineer :	Derreck Chen	**Relative Humidity :**	52~55%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + MP3 + Battery 1 + Earphone + USB Cable 1 (Charging from Adapter 1)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	41.1	Off	N	19.7	23.3	64.4
0.214000	34.6	Off	N	19.7	28.4	63.0
0.270000	34.3	Off	N	19.7	26.8	61.1
0.358000	30.4	Off	N	19.7	28.4	58.8
0.414000	30.5	Off	N	19.6	27.1	57.6
1.558000	29.8	Off	N	19.6	26.2	56.0
13.366000	31.7	Off	N	19.8	28.3	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	27.0	Off	N	19.7	27.4	54.4
0.214000	22.6	Off	N	19.7	30.4	53.0
0.270000	25.1	Off	N	19.7	26.0	51.1
0.358000	24.4	Off	N	19.7	24.4	48.8
0.414000	23.3	Off	N	19.6	24.3	47.6
1.558000	23.6	Off	N	19.6	22.4	46.0
13.366000	23.8	Off	N	19.8	26.2	50.0

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1218006	300MHz~40GHz	Oct. 07, 2015	Nov. 06, 2015~ Nov. 29, 2015	Oct. 06, 2016	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Oct. 07, 2015	Nov. 06, 2015~ Nov. 29, 2015	Oct. 06, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jun. 18, 2015	Nov. 06, 2015~ Nov. 29, 2015	Jun. 17, 2016	Conducted (TH05-HY)
Hygrometer	Testo	608-H1	34897199	N/A	May 04, 2015	Nov. 06, 2015~ Nov. 29, 2015	May 03, 2016	Conducted (TH05-HY)
RF Cable	HARBOUR INDUSTRIES	LL142	Infinet CA3601-360 1-DLL	0.1MHz~40GHz	Mar. 06, 2015	Nov. 06, 2015~ Nov. 29, 2015	Mar. 05, 2016	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Oct. 28, 2015~ Dec. 29, 2015	Sep. 01, 2016	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 24, 2014	Oct. 28, 2015~ Nov. 17, 2015	Nov. 23, 2015	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 20, 2015	Nov. 21, 2015~ Dec. 29, 2015	Nov. 19, 2016	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 08, 2015	Oct. 28, 2015~ Dec. 29, 2015	Oct. 07, 2016	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Nov. 19, 2014	Oct. 28, 2015~ Nov. 17, 2015	Nov. 18, 2015	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Nov. 17, 2015	Nov. 21, 2015~ Dec. 29, 2015	Nov. 16, 2016	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 20, 2014	Oct. 28, 2015~ Nov. 17, 2015	Nov. 19, 2015	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 19, 2015	Nov. 21, 2015~ Dec. 29, 2015	Nov. 18, 2016	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1902247	1GHz~18GHz	Jul. 01, 2015	Oct. 28 2015~ Dec. 29, 2015	Jun. 30, 2016	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHZ	Sep. 24, 2015	Oct. 28, 2015~ Dec. 29, 2015	Sep. 23, 2016	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Feb. 02, 2015	Oct. 28, 2015~ Dec. 29, 2015	Feb. 01, 2016	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Oct. 28, 2015~ Dec. 29, 2015	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Oct. 28, 2015~ Dec. 29, 2015	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0-360 degree	N/A	Oct. 28, 2015~ Dec. 29, 2015	N/A	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D	35414	30MHz to 1GHz	Nov. 17, 2015	Nov. 21, 2015~ Dec. 29, 2015	Nov. 16, 2016	Radiation (03CH11-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 20, 2015	Oct. 28, 2015~ Dec. 29, 2015	Apr. 19, 2016	Radiation (03CH11-HY)
Preamplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Oct. 28, 2015~ Dec. 29, 2015	Jun. 01, 2016	Radiation (03CH11-HY)
Test Software	Audix	E3	6.2009-8-24	N/A	N/A	Oct. 28, 2015~ Dec. 29, 2015	N/A	Radiation (03CH11-HY)
Filter	Wainwright	WLKS1200-8SS	SN3	1.2G Low Pass	Oct. 01, 2015	Oct. 28, 2015~ Dec. 29, 2015	Sep. 30, 2016	Radiation (03CH11-HY)
Filter	Microwave	H3G018G1	SN477220	3.0G High Pass	Oct. 01, 2015	Oct. 28, 2015~ Dec. 29, 2015	Sep. 30, 2016	Radiation (03CH11-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 21, 2015	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Dec. 21, 2015	Aug. 25, 2016	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Apr. 20, 2015	Dec. 21, 2015	Apr. 19, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Dec. 21, 2015	Dec. 01, 2016	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 07, 2015	Dec. 21, 2015	Jan. 06, 2016	Conduction (CO05-HY)
Test Software	N/A	EMC32	8.40.0	N/A	N/A	Dec. 21, 2015	N/A	Conduction (CO05-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.26

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90

Appendix A. Conducted Test Results

Report Number : FR582708-02C

A1 - DTS Part

Test Engineer:	Luffy_Lin	Temperature:	21~26	°C
Test Date:	2015/11/06~2015/11/29	Relative Humidity:	45~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.70	9.08	0.50	Pass
11b	1Mbps	1	6	2437	13.25	10.08	0.50	Pass
11b	1Mbps	1	11	2462	12.80	9.60	0.50	Pass
11g	6Mbps	1	1	2412	17.55	15.72	0.50	Pass
11g	6Mbps	1	6	2437	18.10	16.28	0.50	Pass
11g	6Mbps	1	11	2462	17.50	15.72	0.50	Pass
HT20	MCS0	1	1	2412	18.25	16.36	0.50	Pass
HT20	MCS0	1	6	2437	18.60	17.28	0.50	Pass
HT20	MCS0	1	11	2462	18.25	16.12	0.50	Pass
HT40	MCS0	1	3	2422	35.80	35.12	0.50	Pass
HT40	MCS0	1	6	2437	36.70	35.92	0.50	Pass
HT40	MCS0	1	9	2452	36.00	35.12	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	19.44	30.00	-3.00	16.44	36.00	Pass
11b	1Mbps	1	6	2437	19.29	30.00	-3.00	16.29	36.00	Pass
11b	1Mbps	1	11	2462	19.98	30.00	-3.00	16.98	36.00	Pass
11g	6Mbps	1	1	2412	22.50	30.00	-3.00	19.50	36.00	Pass
11g	6Mbps	1	6	2437	21.80	30.00	-3.00	18.80	36.00	Pass
11g	6Mbps	1	11	2462	22.59	30.00	-3.00	19.59	36.00	Pass
HT20	MCS0	1	1	2412	21.62	30.00	-3.00	18.62	36.00	Pass
HT20	MCS0	1	6	2437	21.68	30.00	-3.00	18.68	36.00	Pass
HT20	MCS0	1	11	2462	22.45	30.00	-3.00	19.45	36.00	Pass
HT40	MCS0	1	3	2422	21.47	30.00	-3.00	18.47	36.00	Pass
HT40	MCS0	1	6	2437	22.56	30.00	-3.00	19.56	36.00	Pass
HT40	MCS0	1	9	2452	21.69	30.00	-3.00	18.69	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	16.68
11b	1Mbps	1	6	2437	0.00	16.65
11b	1Mbps	1	11	2462	0.00	16.99
11g	6Mbps	1	1	2412	0.12	14.60
11g	6Mbps	1	6	2437	0.12	14.57
11g	6Mbps	1	11	2462	0.12	14.85
HT20	MCS0	1	1	2412	0.13	13.42
HT20	MCS0	1	6	2437	0.13	13.48
HT20	MCS0	1	11	2462	0.13	13.88
HT40	MCS0	1	3	2422	0.24	11.97
HT40	MCS0	1	6	2437	0.24	12.99
HT40	MCS0	1	9	2452	0.24	11.91

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-6.40	-3.00	8.00	Pass
11b	1Mbps	1	6	2437	-7.11	-3.00	8.00	Pass
11b	1Mbps	1	11	2462	-5.72	-3.00	8.00	Pass
11g	6Mbps	1	1	2412	-10.94	-3.00	8.00	Pass
11g	6Mbps	1	6	2437	-9.90	-3.00	8.00	Pass
11g	6Mbps	1	11	2462	-9.38	-3.00	8.00	Pass
HT20	MCS0	1	1	2412	-11.96	-3.00	8.00	Pass
HT20	MCS0	1	6	2437	-10.75	-3.00	8.00	Pass
HT20	MCS0	1	11	2462	-11.93	-3.00	8.00	Pass
HT40	MCS0	1	3	2422	-14.63	-3.00	8.00	Pass
HT40	MCS0	1	6	2437	-16.19	-3.00	8.00	Pass
HT40	MCS0	1	9	2452	-14.23	-3.00	8.00	Pass

Appendix B. Radiated Spurious Emission

Test Engineer :	Bill Kuo, Ken Wu, and J.C. Liang	Temperature :	21~23°C
		Relative Humidity :	54~56%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		2380.02	52.06	-21.94	74	53.13	26.96	6.01	34.04	125	359	P	H
		2390	42.08	-11.92	54	43.1	27.01	6.01	34.04	125	359	A	H
	*	2412	102.39	-	-	103.33	27.06	6.04	34.04	125	359	P	H
	*	2412	99.95	-	-	100.89	27.06	6.04	34.04	125	359	A	H
													H
													H
		2365.89	52.1	-21.9	74	53.22	26.91	6.01	34.04	150	173	P	V
		2390	41.75	-12.25	54	42.77	27.01	6.01	34.04	150	173	A	V
	*	2412	98.72	-	-	99.66	27.06	6.04	34.04	150	173	P	V
	*	2412	96.25	-	-	97.19	27.06	6.04	34.04	150	173	A	V
													V
													V
802.11b CH 06 2437MHz		2367.42	53.28	-20.72	74	54.4	26.91	6.01	34.04	121	357	P	H
		2390	41.67	-12.33	54	42.69	27.01	6.01	34.04	121	357	A	H
	*	2437	101.87	-	-	102.7	27.16	6.04	34.03	121	357	P	H
	*	2437	99.42	-	-	100.25	27.16	6.04	34.03	121	357	A	H
		2484.64	53.36	-20.64	74	54.03	27.25	6.09	34.01	121	357	P	H
		2484.96	42.3	-11.7	54	42.97	27.25	6.09	34.01	121	357	A	H
		2387.67	52.91	-21.09	74	53.93	27.01	6.01	34.04	100	357	P	V
		2389.11	41.48	-12.52	54	42.5	27.01	6.01	34.04	100	357	A	V
	*	2437	94.14	-	-	94.97	27.16	6.04	34.03	100	357	P	V
	*	2437	91.58	-	-	92.41	27.16	6.04	34.03	100	357	A	V
		2487.68	53.06	-20.94	74	53.68	27.3	6.09	34.01	100	357	P	V
		2483.6	42.15	-11.85	54	42.82	27.25	6.09	34.01	100	357	A	V

802.11b CH 11 2462MHz	*	2462	103.09	-	-	103.84	27.2	6.07	34.02	119	359	P	H
	*	2462	100.6	-	-	101.35	27.2	6.07	34.02	119	359	A	H
		2486.92	54	-20	74	54.67	27.25	6.09	34.01	119	359	P	H
		2486.84	43.77	-10.23	54	44.44	27.25	6.09	34.01	119	359	A	H
													H
													H
	*	2462	99.38	-	-	100.13	27.2	6.07	34.02	102	173	P	V
	*	2462	96.81	-	-	97.56	27.2	6.07	34.02	102	173	A	V
		2487.96	53.76	-20.24	74	54.38	27.3	6.09	34.01	102	173	P	V
		2486.92	44.17	-9.83	54	44.84	27.25	6.09	34.01	102	173	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	38.19	-35.81	74	63.49	31.12	8.65	65.07	100	0	P	H
													H
													H
													H
		4824	36.13	-37.87	74	61.43	31.12	8.65	65.07	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	35.41	-38.59	74	60.53	31.21	8.69	65.02	100	0	P	H
		7311	40.05	-33.95	74	58.64	36.08	10.39	65.06	100	0	P	H
													H
													H
		4874	36.23	-37.77	74	61.35	31.21	8.69	65.02	100	0	P	V
		7311	40.18	-33.82	74	58.77	36.08	10.39	65.06	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	41.1	-32.9	74	65.99	31.29	8.79	64.97	100	0	P	H
		7386	43.62	-30.38	74	61.95	36.27	10.48	65.08	100	0	P	H
													H
													H
		4924	44.6	-29.4	74	69.49	31.29	8.79	64.97	100	0	P	V
		7386	41.18	-32.82	74	59.51	36.27	10.48	65.08	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2390	58.18	-15.82	74	59.2	27.01	6.01	34.04	255	19	P	H
		2390	45.27	-8.73	54	46.29	27.01	6.01	34.04	255	19	A	H
	*	2412	103.43	-	-	104.37	27.06	6.04	34.04	255	19	P	H
	*	2412	93.56	-	-	94.5	27.06	6.04	34.04	255	19	A	H
													H
													H
		2384.07	52.28	-21.72	74	53.35	26.96	6.01	34.04	107	358	P	V
		2389.83	43.06	-10.94	54	44.08	27.01	6.01	34.04	107	358	A	V
	*	2412	99.99	-	-	100.93	27.06	6.04	34.04	107	358	P	V
	*	2412	92.84	-	-	93.78	27.06	6.04	34.04	107	358	A	V
													V
													V
802.11g CH 06 2437MHz		2343.3	52.52	-21.48	74	53.75	26.87	5.95	34.05	168	184	P	H
		2389.92	43	-11	54	44.02	27.01	6.01	34.04	168	184	A	H
	*	2437	103.96	-	-	104.79	27.16	6.04	34.03	168	184	P	H
	*	2437	96.21	-	-	97.04	27.16	6.04	34.03	168	184	A	H
		2485.72	54.38	-19.62	74	55.05	27.25	6.09	34.01	168	184	P	H
		2485.4	44.46	-9.54	54	45.13	27.25	6.09	34.01	168	184	A	H
		2370.57	52.83	-21.17	74	53.9	26.96	6.01	34.04	100	355	P	V
		2386.41	42.17	-11.83	54	43.19	27.01	6.01	34.04	100	355	A	V
	*	2437	98.16	-	-	98.99	27.16	6.04	34.03	100	355	P	V
	*	2437	90.66	-	-	91.49	27.16	6.04	34.03	100	355	A	V
		2485.88	53.03	-20.97	74	53.7	27.25	6.09	34.01	100	355	P	V
		2485.24	42.76	-11.24	54	43.43	27.25	6.09	34.01	100	355	A	V

802.11g CH 11 2462MHz	*	2462	102.1	-	-	102.85	27.2	6.07	34.02	137	22	P	H
	*	2462	94.96	-	-	95.71	27.2	6.07	34.02	137	22	A	H
		2483.68	58.88	-15.12	74	59.55	27.25	6.09	34.01	137	22	P	H
		2483.52	46.07	-7.93	54	46.74	27.25	6.09	34.01	137	22	A	H
													H
													H
	*	2462	97.3	-	-	98.05	27.2	6.07	34.02	100	174	P	V
	*	2462	89.83	-	-	90.58	27.2	6.07	34.02	100	174	A	V
		2485.72	54.83	-19.17	74	55.5	27.25	6.09	34.01	100	174	P	V
		2485.76	44.23	-9.77	54	44.9	27.25	6.09	34.01	100	174	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	35.93	-38.07	74	61.23	31.12	8.65	65.07	100	0	P	H
													H
													H
													H
		4824	37.91	-36.09	74	63.21	31.12	8.65	65.07	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	38.39	-35.61	74	63.51	31.21	8.69	65.02	100	0	P	H
		7311	40.04	-33.96	74	58.63	36.08	10.39	65.06	100	0	P	H
													H
													H
		4874	39.52	-34.48	74	64.64	31.21	8.69	65.02	100	0	P	V
		7311	40.42	-33.58	74	59.01	36.08	10.39	65.06	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	36.82	-37.18	74	61.71	31.29	8.79	64.97	100	0	P	H
		7386	40.1	-33.9	74	58.43	36.27	10.48	65.08	100	0	P	H
													H
													H
		4924	39.85	-34.15	74	64.74	31.29	8.79	64.97	100	0	P	V
		7386	40.37	-33.63	74	58.7	36.27	10.48	65.08	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.47	60.74	-13.26	74	61.76	27.01	6.01	34.04	147	358	P	H
		2390	48	-6	54	49.02	27.01	6.01	34.04	147	358	A	H
	*	2412	102.6	-	-	103.54	27.06	6.04	34.04	147	358	P	H
	*	2412	95.34	-	-	96.28	27.06	6.04	34.04	147	358	A	H
													H
													H
		2389.83	58.79	-15.21	74	59.81	27.01	6.01	34.04	117	155	P	V
		2390	45.47	-8.53	54	46.49	27.01	6.01	34.04	117	155	A	V
	*	2412	98.44	-	-	99.38	27.06	6.04	34.04	117	155	P	V
	*	2412	91.34	-	-	92.28	27.06	6.04	34.04	117	155	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2355.72	52.21	-21.79	74	53.4	26.91	5.95	34.05	167	359	P	H
		2389.92	42.74	-11.26	54	43.76	27.01	6.01	34.04	167	359	A	H
	*	2437	102.26	-	-	103.09	27.16	6.04	34.03	167	359	P	H
	*	2437	94.52	-	-	95.35	27.16	6.04	34.03	167	359	A	H
		2484.24	53.71	-20.29	74	54.38	27.25	6.09	34.01	167	359	P	H
		2485.64	44.16	-9.84	54	44.83	27.25	6.09	34.01	167	359	A	H
		2388.93	52.88	-21.12	74	53.9	27.01	6.01	34.04	151	152	P	V
		2389.56	42.41	-11.59	54	43.43	27.01	6.01	34.04	151	152	A	V
	*	2437	100.39	-	-	101.22	27.16	6.04	34.03	151	152	P	V
	*	2437	92.44	-	-	93.27	27.16	6.04	34.03	151	152	A	V
		2492.8	52.67	-21.33	74	53.28	27.3	6.09	34	151	152	P	V
		2485.6	43.31	-10.69	54	43.98	27.25	6.09	34.01	151	152	A	V

802.11n HT20 CH 11 2462MHz	*	2462	102.58	-	-	103.33	27.2	6.07	34.02	140	359	P	H
	*	2462	94.24	-	-	94.99	27.2	6.07	34.02	140	359	A	H
		2484.12	59.96	-14.04	74	60.63	27.25	6.09	34.01	140	359	P	H
		2483.84	46.93	-7.07	54	47.6	27.25	6.09	34.01	140	359	A	H
													H
													H
	*	2462	99.93	-	-	100.68	27.2	6.07	34.02	144	150	P	V
	*	2462	91.54	-	-	92.29	27.2	6.07	34.02	144	150	A	V
		2483.76	57.85	-16.15	74	58.52	27.25	6.09	34.01	144	150	P	V
		2483.56	46.25	-7.75	54	46.92	27.25	6.09	34.01	144	150	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	36.4	-37.6	74	61.7	31.12	8.65	65.07	100	0	P	H
													H
													H
													H
		4824	37.42	-36.58	74	62.72	31.12	8.65	65.07	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	37.1	-36.9	74	62.22	31.21	8.69	65.02	100	0	P	H
		7311	39.78	-34.22	74	58.37	36.08	10.39	65.06	100	0	P	H
													H
													H
		4874	38.15	-35.85	74	63.27	31.21	8.69	65.02	100	0	P	V
		7311	40.16	-33.84	74	58.75	36.08	10.39	65.06	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	36.42	-37.58	74	61.31	31.29	8.79	64.97	100	0	P	H
		7386	40.49	-33.51	74	58.82	36.27	10.48	65.08	100	0	P	H
													H
													H
		4924	37.64	-36.36	74	62.53	31.29	8.79	64.97	100	0	P	V
		7386	40.25	-33.75	74	58.58	36.27	10.48	65.08	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2389.74	63.2	-10.8	74	64.22	27.01	6.01	34.04	149	3	P	H
		2390	50.63	-3.37	54	51.65	27.01	6.01	34.04	149	3	A	H
	*	2422	98.41	-	-	99.29	27.11	6.04	34.03	149	3	P	H
	*	2422	90.95	-	-	91.83	27.11	6.04	34.03	149	3	A	H
		2485.04	53.68	-20.32	74	54.35	27.25	6.09	34.01	149	3	P	H
		2485.48	43.98	-10.02	54	44.65	27.25	6.09	34.01	149	3	A	H
		2390	60.06	-13.94	74	61.08	27.01	6.01	34.04	137	154	P	V
		2389.65	47.72	-6.28	54	48.74	27.01	6.01	34.04	137	154	A	V
	*	2422	94.27	-	-	95.15	27.11	6.04	34.03	137	154	P	V
	*	2422	86.81	-	-	87.69	27.11	6.04	34.03	137	154	A	V
		2485.6	53.3	-20.7	74	53.97	27.25	6.09	34.01	137	154	P	V
		2485.64	43.73	-10.27	54	44.4	27.25	6.09	34.01	137	154	A	V
802.11n HT40 CH 06 2437MHz		2388.3	55.54	-18.46	74	56.56	27.01	6.01	34.04	169	4	P	H
		2390	44.92	-9.08	54	45.94	27.01	6.01	34.04	169	4	A	H
	*	2437	99.57	-	-	100.4	27.16	6.04	34.03	169	4	P	H
	*	2437	92.4	-	-	93.23	27.16	6.04	34.03	169	4	A	H
		2483.52	59.4	-14.6	74	60.07	27.25	6.09	34.01	169	4	P	H
		2483.96	46.98	-7.02	54	47.65	27.25	6.09	34.01	169	4	A	H
		2387.22	52.54	-21.46	74	53.56	27.01	6.01	34.04	147	151	P	V
		2389.56	43.45	-10.55	54	44.47	27.01	6.01	34.04	147	151	A	V
	*	2437	96.43	-	-	97.26	27.16	6.04	34.03	147	151	P	V
	*	2437	88.62	-	-	89.45	27.16	6.04	34.03	147	151	A	V
		2484.04	54.5	-19.5	74	55.17	27.25	6.09	34.01	147	151	P	V
		2483.84	44.78	-9.22	54	45.45	27.25	6.09	34.01	147	151	A	V

802.11n HT40 CH 09 2452MHz		2324.49	52.21	-21.79	74	53.5	26.82	5.95	34.06	167	3	P	H
		2389.92	42.96	-11.04	54	43.98	27.01	6.01	34.04	167	3	A	H
	*	2452	100.14	-	-	100.93	27.16	6.07	34.02	167	3	P	H
	*	2452	92.88	-	-	93.67	27.16	6.07	34.02	167	3	A	H
		2484	65	-9	74	65.67	27.25	6.09	34.01	167	3	P	H
		2484.24	50.98	-3.02	54	51.65	27.25	6.09	34.01	167	3	A	H
		2339.7	52.62	-21.38	74	53.85	26.87	5.95	34.05	152	149	P	V
		2359.86	42.98	-11.02	54	44.17	26.91	5.95	34.05	152	149	A	V
	*	2452	96.67	-	-	97.46	27.16	6.07	34.02	152	149	P	V
	*	2452	89.11	-	-	89.9	27.16	6.07	34.02	152	149	A	V
		2483.52	61.87	-12.13	74	62.54	27.25	6.09	34.01	152	149	P	V
		2483.8	47.53	-6.47	54	48.2	27.25	6.09	34.01	152	149	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		4844	35.33	-38.67	74	60.55	31.15	8.69	65.06	100	0	P	H
		7266	40.39	-33.61	74	59.1	36.01	10.34	65.06	100	0	P	H
													H
													H
		4844	35.48	-38.52	74	60.7	31.15	8.69	65.06	100	0	P	V
		7266	40.06	-33.94	74	58.77	36.01	10.34	65.06	100	0	P	V
													V
													V
802.11n HT40 CH 06 2437MHz		4874	35.77	-38.23	74	60.89	31.21	8.69	65.02	100	0	P	H
		7311	39.37	-34.63	74	57.96	36.08	10.39	65.06	100	0	P	H
													H
													H
		4874	36.27	-37.73	74	61.39	31.21	8.69	65.02	100	0	P	V
		7311	39.4	-34.6	74	57.99	36.08	10.39	65.06	100	0	P	V
													V
													V
802.11n HT40 CH 09 2452MHz		4904	36.4	-37.6	74	61.39	31.26	8.74	64.99	100	0	P	H
		7356	39.77	-34.23	74	58.2	36.2	10.44	65.07	100	0	P	H
													H
													H
		4904	36.49	-37.51	74	61.48	31.26	8.74	64.99	100	0	P	V
		7356	39.68	-34.32	74	58.11	36.2	10.44	65.07	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11b LF		141.51	33.45	-10.05	43.5	45.96	17.81	1.46	31.78			P	H
		202.26	36.12	-7.38	43.5	50.21	16.05	1.64	31.78	120	100	P	H
		212.25	34.41	-9.09	43.5	48.2	16.2	1.79	31.78			P	H
		517	25.46	-20.54	46	30.41	24.33	2.64	31.92			P	H
		756.4	29.14	-16.86	46	30.08	27.78	3.25	31.97			P	H
		960.8	33.32	-20.68	54	30.01	30.58	3.68	30.95			P	H
													H
													H
													H
													H
													H
													H
		38.1	34.53	-5.47	40	44.26	21.42	0.67	31.82	100	0	P	V
		63.48	33.69	-6.31	40	52.34	12.1	1.04	31.79			P	V
		199.56	34.49	-9.01	43.5	48.63	16	1.64	31.78			P	V
		590.5	26.64	-19.36	46	30.25	25.53	2.89	32.03			P	V
		752.9	29.14	-16.86	46	30.14	27.73	3.25	31.98			P	V
		953.8	32.98	-13.02	46	29.71	30.59	3.68	31			P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		100.47	25.64	-17.86	43.5	39.93	16.21	1.28	31.78	-	-	P	H
		158.79	28.34	-15.16	43.5	41.71	16.95	1.46	31.78	-	-	P	H
		199.83	32.64	-10.86	43.5	46.78	16	1.64	31.78	160	82	P	H
		514.2	26.51	-19.49	46	31.49	24.29	2.64	31.91	-	-	P	H
		731.9	29.2	-16.8	46	30.6	27.35	3.25	32	-	-	P	H
		911.1	34.2	-11.8	46	32.49	29.5	3.55	31.34	-	-	P	H
													H
													H
													H
													H
													H
													H
		63.21	33.98	-6.02	40	52.68	12.05	1.04	31.79	110	75	P	V
		123.42	23.83	-19.67	43.5	36.54	17.79	1.28	31.78	-	-	P	V
		199.83	31.46	-12.04	43.5	45.6	16	1.64	31.78	-	-	P	V
		542.2	25.69	-20.31	46	30.18	24.69	2.77	31.95	-	-	P	V
		839.7	30.54	-15.46	46	30.08	28.78	3.4	31.72	-	-	P	V
		956.6	33.41	-12.59	46	30.12	30.59	3.68	30.98	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		100.47	24.9	-18.6	43.5	39.19	16.21	1.28	31.78	-	-	P	H
		160.41	27.94	-15.56	43.5	41.36	16.9	1.46	31.78	-	-	P	H
		200.1	33.22	-10.28	43.5	47.36	16	1.64	31.78	200	170	P	H
		409.9	24.55	-21.45	46	31.36	22.59	2.41	31.81	-	-	P	H
		729.8	29.01	-16.99	46	30.47	27.29	3.25	32	-	-	P	H
		964.3	33.32	-20.68	54	29.99	30.57	3.68	30.92	-	-	P	H
													H
													H
													H
													H
													H
													H
		63.21	31.19	-8.81	40	49.89	12.05	1.04	31.79	115	50	P	V
		200.1	32.07	-11.43	43.5	46.21	16	1.64	31.78	-	-	P	V
		232.5	27.53	-18.47	46	40.37	17.14	1.79	31.77	-	-	P	V
		439.3	24.39	-21.61	46	30.71	23.11	2.41	31.84	-	-	P	V
		724.2	29.98	-16.02	46	31.66	27.19	3.14	32.01	-	-	P	V
		948.9	33.67	-12.33	46	30.46	30.57	3.68	31.04	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
2.4GHz 802.11n HT40 LF		100.74	24.66	-18.84	43.5	38.95	16.21	1.28	31.78	-	-	P	H
		146.1	27.91	-15.59	43.5	40.65	17.58	1.46	31.78	-	-	P	H
		201.18	32.99	-10.51	43.5	47.11	16.02	1.64	31.78	100	110	P	H
		490.4	24.86	-21.14	46	30.15	23.95	2.64	31.88	-	-	P	H
		752.2	29.67	-16.33	46	30.67	27.73	3.25	31.98	-	-	P	H
		937	32.98	-13.02	46	30.2	30.24	3.68	31.14	-	-	P	H
													H
													H
													H
													H
													H
													H
		63.48	31.04	-8.96	40	49.69	12.1	1.04	31.79	120	60	P	V
		198.48	32.26	-11.24	43.5	46.47	15.93	1.64	31.78	-	-	P	V
		234.12	26.85	-19.15	46	39.61	17.22	1.79	31.77	-	-	P	V
		492.5	25.34	-20.66	46	30.6	23.98	2.64	31.88	-	-	P	V
		728.4	29.15	-16.85	46	30.64	27.27	3.25	32.01	-	-	P	V
		896.4	32.44	-13.56	46	31.16	29.18	3.55	31.45	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Bill Kuo, Ken Wu, and J.C. Liang	**Temperature :**	21~23°C
		Relative Humidity :	54~56%

Note symbol

-L	**Low channel location**
-R	**High channel location**

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1	Horizontal	Vertical
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	 Site : 03CH11-HY Condition : FCC CLASS-B (AVG) 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.		

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 	

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.		

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH03 2422MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH09 2452MHz	
1	Horizontal	Vertical
Peak Avg.		

2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11b LF	
1	Horizontal	Vertical
QP / Peak		

2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11g LF	
1	Horizontal	Vertical
QP / Peak		

2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT20 LF	
1	Horizontal	Vertical
QP / Peak		

2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT40 LF	
1	Horizontal	Vertical
QP / Peak