

Prepared (also subject responsible if other)

SEM/CA/K Jeff Chlebowski / Michael Frink

Approved

Checked

SEM/CA/K (Jeff Chlebowski)

**Limited Internal
MARKING DRAWING**

No.

151 86 – KRC 114 16

Date

Rev

Reference

2003-05-06

PD5

Approved according to: 000 21 – LXE 107 42/1

Type 103 1011-BV.
Label

The label used for marking is defined in the Manufacturing Specification on the SVF 930 361/1.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88) for the KRH.

Print layout

Sony Ericsson trademark	Model Number	CD A number Marking of Origin
Type number GHY ¹ Y ² Y ³ fields		
Country approval mark 1	Country approval mark 2	
IMEI-numbers as barcode		
IMEI-numbers as characters		
Serial number as barcode		
Serial number as characters		
*UPC number as barcode		
*UPC num as characters	Prod / Repair wk as characters	
	Prod wk as barcode	
CE Marking		

SAMPLE* (FPO)


***Note: representative sample, text in image does not match required information for this product defined in table below.**

Definitions:

Sony Ericsson trademark	Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347.
Model number	The model number is T616 and shall be printed "T616"
Type number	The type number is AAB-1031011-BV and shall be printed "Type AAB-1031011-BV"
G-field	R-state identification of the CXC-module according to the Marking data 1/151 86 for the KRC.
H-field	R-state identification of the KRC according to the Marking data 1/151 86 for the KRC.
Y ¹ -field	R-state identification of the KRH according to the Marking data 1/151 86 for the KRC.
Y ² -field	KRH structure identification according to the Marking data 1/151 86 for the KRC.
Y ³ -field	R-state identification of the ROA according to the Marking data 1/151 86 for the KRC.

Prepared (also subject responsible if other)

SEM/CA/K Jeff Chlebowski / Michael Frink

Approved

SEM/CA/K (Jeff Chlebowski)

Checked

**Limited Internal
MARKING DRAWING**

No.

151 86 – KRC 114 16

Date

2003-05-06

Rev

PD5

Reference

Country approval
mark 1

Consist of text: FCC ID: PY7A1031011

Within a frame with height > 1,5 mm.

Country approval
mark 2

Consist of text: IC: 4170B-A1031011

IMEI number as bar code

See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -).

IMEI number as characters

The IMEI number has format:

01AAAAAA-BBBBBB-C

AAAAAA = 019700

BBBBBB = assigned serial number

C = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.

Serial number as bar code

According to Ericsson corporate standard 102 01 - 109.

Serial number as
characters

According to Ericsson group standard 0012-101.

Ericsson group factory number system according the Ericsson corporate standard 1120-101 Factory codes:

Linköping A61

AT&T Wireless product
number as bar code

IF APPLICABLE, meaning KRC product structure is /54 .

AT&T Wireless product
number as characters

IF APPLICABLE, meaning KRC product structure is /54. Product number 111111111111 (TBD).

Production week
(Prod wk)

The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard.

Repair week

The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwxx (R = repair, y = year, ww = week, xx = Revision eg. 1A)

Marking of origin

"Made in" statement should reflect the country of origin of the 1/KRC (i.e. Made in Malaysia).

CDA number

The number of the CDA file loaded including the R-state of the file, eg. CDA 102 122 R1A

Approval marks

1. According to 1424 - SVF 930 52
2. The notified body number from the type approval certificate, 0682. The print size (height) for the notified body number (e.g. 0682) and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement.



Prepared (also subject responsible if other)

SEM/CA/K Jeff Chlebowski / Michael Frink

Approved

Checked

SEM/CA/K (Jeff Chlebowski)

Limited Internal
MARKING DRAWING

No.

151 86 – KRC 114 16

Date

Rev

Reference

2003-05-06

PD5

Print regulations

The printing shall be well readable and permanent.

Typeface	OCR-B
Type size	min 1.1 mm
Line spacing	min 1.5 mm
Trademark	min 1.5 mm