

Confidential
MARKING DRAWING

1(3)

<i>Prepared</i>	<i>Date</i>	<i>Rev</i>	<i>Doc no.</i>
RT/SEM/CA/KA Christer Andersson	2005-07-07	A	1/151 86-DPY 101 1500
<i>Approved</i>	<i>Checked</i>		<i>File</i>
CA/KA (Christer Andersson)			

Marking Drawing T292a

Type AAA-1061011-BV = T292a

Label

The Label used for marking is defined in the Manufacturing Specification 1301-SVF 930 2239.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing for the KRH.

Print Layout

Sony Ericsson  IMEI : 00100300-123456-0  A6103.000 FCC ID: PY7-A1061011 Can IC: 4170B-A1061011

T292a DPY 1500 RXX AAA-106 1011-BV AAA Made in Malaysia 05/07/08

<i>Prepared</i>	<i>Date</i>	<i>Rev</i>	<i>Doc no.</i>
RT/SEM/CA/KA Christer Andersson	2005-07-07	A	1/151 86-DPY 101 1500
<i>Approved</i>	<i>Checked</i>		<i>File</i>
CA/KA (Christer Andersson)			

Line	Text
1.	Sony Ericsson Trademark
2.	IMEI Number as Bar Code
3.	IMEI Number as Characters
4.	Serial Number as Bar Code
5.	Serial Number as Characters
6.	Country Approval mark 1
7.	Country Approval mark 2.
8.	Model number, Reduced DPY number & r-state, Type approval number GHY1 fields.
9.	
10.	Marking of Origin Build week

Definitions:

Sony Ericsson trademark	Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347.
IMEI number as bar code	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -).
IMEI number as characters	The IMEI number has format: 01AAAAAA-BBBBBB-C AAAAAA = (see 1/151-86-KRH 101 295 latest rev for this information) BBBBBB = assigned serial number C = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Serial number as bar code	As desired by supplier (only actual number, with data identifier).
Serial number as characters	Supplier's identification for traceability of the KRH, as desired by the supplier.
Country approval mark 1	Consist of text: FCC ID: PY7-A1061011 <i>Within a frame</i> with height > 1,5 mm.
Country approval mark 2	Consist of text: IC: 4170B-A1061011

Confidential
MARKING DRAWING

3(3)

<i>Prepared</i>	<i>Date</i>	<i>Rev</i>	<i>Doc no.</i>
RT/SEM/CA/KA Christer Andersson	2005-07-07	A	1/151 86-DPY 101 1500
<i>Approved</i>	<i>Checked</i>		<i>File</i>
CA/KA (Christer Andersson)			

Model Number	The model number is T292a and shall be printed "T292a"
Reduced DPY	Reduced DPY-Number & r-state. The reduced DPY number leaves out the 3 digit number prefix (ex: DPY 101 1500 R1A would be printed DPY 1500 R1A)
Type Number	The type number is AAA 1061011-BV and shall be printed "AAA-1061011-BV"
G – Field	R-State identification of the CXC-module according to the Marking Data 1/151-86-KRH 101 295.
H-field	R-state identification of the KRH according to the Marking data 1/151-86-KRH 101 295.
Y ¹ -field	R-state identification of the ROA according to the Marking data 1/151-86-KRH 101 295.
Marking of origin	"Made in" statement should reflect the country of origin of the 1/KRH (i.e. Made in Malaysia).
Build Week	Build Week, in format year W XX, ie 05W18 is equal to build year 2005, Week 18.

Print regulations

The printing shall be well readable and permanent.

Typeface	OCR-B
Type size	min 1.1 mm
Line spacing	min 1.5 mm
Trademark	min 1.5 mm
Approval Marks	min 5.0 mm

Revision Table

Revision	Date	Reason
A	2005-07-07	Initial Release