

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

43(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked	C X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Appendix 4

Probe Calibration Certificates



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes	No. REP 2005 004 T292A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked C X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

ET3DV6 SN:1586

May 26, 2005

DASY - Parameters of Probe: ET3DV6 SN:1586**Sensitivity in Free Space^A****Diode Compression^B**

NormX	1.90 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP X	94 mV
NormY	1.84 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Y	94 mV
NormZ	1.89 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Z	94 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect**TSL 900 MHz Typical SAR gradient: 5 % per mm**

Sensor Center to Phantom Surface Distance	3.7 mm	4.7 mm
SAR _{ts} [%] Without Correction Algorithm	8.4	4.3
SAR _{ts} [%] With Correction Algorithm	0.1	0.2

TSL 1750 MHz Typical SAR gradient: 10 % per mm

Sensor Center to Phantom Surface Distance	3.7 mm	4.7 mm
SAR _{ts} [%] Without Correction Algorithm	12.2	8.2
SAR _{ts} [%] With Correction Algorithm	0.8	0.1

Sensor Offset

Probe Tip to Sensor Center 2.7 mm

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).

^B Numerical linearization parameter: uncertainty not required.





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes	No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

ET3DV6 SN:1586

May 26, 2005

Conversion Factor Assessment



f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
835	± 50 / ± 100	Head	41.5 ± 5%	0.90 ± 5%	0.62	1.76	6.58 ± 11.0% (k=2)
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.61	1.78	6.46 ± 11.0% (k=2)
1750	± 50 / ± 100	Head	40.1 ± 5%	1.37 ± 5%	0.59	2.26	5.29 ± 11.0% (k=2)
1900	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.56	2.50	5.10 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.66	2.22	4.58 ± 11.8% (k=2)
835	± 50 / ± 100	Body	55.2 ± 5%	0.97 ± 5%	0.54	1.96	6.51 ± 11.0% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.52	2.05	6.21 ± 11.0% (k=2)
1750	± 50 / ± 100	Body	53.4 ± 5%	1.49 ± 5%	0.55	2.76	4.71 ± 11.0% (k=2)
1900	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.56	2.76	4.61 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.68	2.13	4.26 ± 11.8% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes	No. REP 2005 004 T292A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked C X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

ET3DV6 SN:1587

May 26, 2005

DASY - Parameters of Probe: ET3DV6 SN:1587**Sensitivity in Free Space^A****Diode Compression^B**

NormX	2.05 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP X	95 mV
NormY	1.92 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Y	95 mV
NormZ	1.79 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Z	95 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect**TSL 900 MHz Typical SAR gradient: 5 % per mm**

Sensor Center to Phantom Surface Distance	3.7 mm	4.7 mm
SAR ₉₀ [%] Without Correction Algorithm	8.1	4.4
SAR ₉₀ [%] With Correction Algorithm	0.1	0.2

TSL 1750 MHz Typical SAR gradient: 10 % per mm

Sensor Center to Phantom Surface Distance	3.7 mm	4.7 mm
SAR ₉₀ [%] Without Correction Algorithm	12.4	8.5
SAR ₉₀ [%] With Correction Algorithm	0.5	0.1

Sensor Offset

Probe Tip to Sensor Center 2.7 mm

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).^B Numerical linearization parameter; uncertainty not required.





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes	No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

ET3DV6 SN:1587

May 26, 2005

Conversion Factor Assessment



f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
835	± 50 / ± 100	Head	41.5 ± 5%	0.90 ± 5%	0.60	1.76	6.78 ± 11.0% (k=2)
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.55	1.85	6.50 ± 11.0% (k=2)
1750	± 50 / ± 100	Head	40.1 ± 5%	1.37 ± 5%	0.50	2.53	5.45 ± 11.0% (k=2)
1900	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.47	2.71	5.05 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.58	2.40	4.55 ± 11.8% (k=2)
835	± 50 / ± 100	Body	55.2 ± 5%	0.97 ± 5%	0.51	1.97	6.65 ± 11.0% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.51	2.03	6.37 ± 11.0% (k=2)
1750	± 50 / ± 100	Body	53.4 ± 5%	1.49 ± 5%	0.48	2.94	4.74 ± 11.0% (k=2)
1900	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.50	3.13	4.57 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.53	2.51	4.16 ± 11.8% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

48(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Appendix 5

Measurement Uncertainty Budget



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Table 1a. Uncertainty Budget for System Performance Check (Dipole & flat phantom) DASY3 System

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1-g)	<i>c_i</i> (10-g)	1-g <i>u_i</i> (±%)	10-g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration (<i>k</i> =1)	E.2.1	4.8	N	1	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	8.3	R	1.73	1	1	4.8	4.8	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1.0	N	1	1	1	1.0	1.0	∞
Response Time	E.2.7	0.0	R	1.73	1	1	0.0	0.0	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance (corresponds to the mechanical constraints of the robot)	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	3.9	R	1.73	1	1	2.3	2.3	∞
Dipole									
Dipole Axis to Liquid Distance	8, E.4.2	1.0	R	1.73	1	1	0.6	0.6	∞
Input Power and SAR Drift Measurement	8, 6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty - shell thickness tolerance	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation	E.3.2	4.3	R	1.73	0.64	0.43	1.59	1.07	∞

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

50(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

from target values (5)									
Liquid Conductivity - measurement uncertainty (6)	E.3.3	6.20	R	1.73	0.64	0.43	2.29	1.54	∞
Liquid Permittivity - deviation from target values (5)	E.3.2	3.7	R	1.73	0.6	0.49	1.28	1.05	∞
Liquid Permittivity - measurement uncertainty (6)	E.3.3	6.08	R	1.73	0.6	0.49	2.11	1.72	∞
Combined Standard Uncertainty			RSS				10.61	10.31	
Expanded Uncertainty (95% C.L.)							21.22	20.62	



Sony Ericsson

REPORT

51(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Table 1b. Uncertainty Budget for System Performance Check (Dipole & flat phantom) DASY4 System

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1-g)	<i>c_i</i> (10-g)	1-g <i>u_i</i> (±%)	10-g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration (<i>k</i> =1)	E2.1	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Axial Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Hemispherical Isotropy	E.2.2	1.0	R	1.73	1	1	0.6	0.6	∞
Boundary Effect	E.2.3	4.7	R	1.73	1	1	2.7	2.7	∞
Linearity	E.2.4	1.0	R	1.73	1	1	0.6	0.6	∞
System Detection Limits	E.2.5	1.0	N	1	1	1	1.0	1.0	∞
Readout Electronics	E.2.6	0.8	R	1.73	1	1	0.5	0.5	∞
Response Time	E.2.7	2.6	R	1.73	1	1	1.5	1.5	∞
Integration Time	E.2.8	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance (corresponds to the mechanical constraints of the robot)	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1	1	0.6	0.6	∞
Dipole									
Dipole Axis to Liquid Distance	8, E.4.2	1.0	R	1.73	1	1	0.6	0.6	∞
Input Power and SAR Drift Measurement	8, 6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty - shell thickness tolerance	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation	E.3.2	4.3	R	1.73	0.64	0.43	1.59	1.07	∞

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

52(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

from target values (5)									
Liquid Conductivity - measurement uncertainty (6)	E.3.3	6.20	R	1.73	0.64	0.43	2.29	1.54	∞
Liquid Permittivity - deviation from target values (5)	E.3.2	3.7	R	1.73	0.6	0.49	1.28	1.05	∞
Liquid Permittivity - measurement uncertainty (6)	E.3.3	6.08	R	1.73	0.6	0.49	2.11	1.72	∞
Combined Standard Uncertainty			RSS				9.37	9.03	
Expanded Uncertainty (95% C.L.)							18.74	18.05	



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes	No. REP 2005 004 T292A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked C X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Table 2a: Uncertainty Budget for the Device Under Test with DASY3 System

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d, k)$	<i>f</i>	<i>g</i>	$h = c \times f / e$	$i = c \times g / e$	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	c_i (1-g)	c_i (10-g)	1-g u_i (±%)	10-g u_i (±%)	v_i
Measurement System									
Probe Calibration ($k=1$)	E2.1	4.8	N	1	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	8.3	R	1.73	1	1	4.8	4.8	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1.0	N	1	1	1	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1	1	0.5	0.5	∞
Integration Time	E.2.8	1.4	R	1.73	1	1	0.8	0.8	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance (corresponds to the mechanical constraints of the robot)	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	3.9	R	1.73	1	1	2.3	2.3	∞
Test sample Related									
Test Sample Positioning	E.4.2	1.0	N	1	1	1	1.2	1.2	4
Device Holder Uncertainty	E.4.1	2.0	R	1.73	1	1	0.7	0.7	4
Output Power Variation - SAR drift measurement (4)	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									



Sony Ericsson

REPORT

54(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values (5)	E.3.2	4.3	R	1.73	0.64	0.43	1.6	1.1	∞
Liquid Conductivity - measurement uncertainty (6)	E.3.3	6.20	R	1.73	0.64	0.43	2.3	1.5	∞
Liquid Permittivity - deviation from target values (5)	E.3.2	3.7	R	1.73	0.6	0.49	1.3	1.0	∞
Liquid Permittivity - measurement uncertainty (6)	E.3.3	6.08	R	1.73	0.6	0.49	2.1	1.7	∞
Combined Standard Uncertainty			RSS				10.73	10.42	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			K=2				21.45	20.84	



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Table 2b: Uncertainty Budget for the Device Under Test with DASY4 System

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d, k)$	<i>f</i>	<i>g</i>	$h = c \times f / e$	$i = c \times g / e$	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	c_i (1-g)	c_i (10-g)	1-g u_i (±%)	10-g u_i (±%)	v_i
Measurement System									
Probe Calibration ($k=1$)	E2.1	4.8	N	1	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1.0	N	1	1	1	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1	1	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1	1	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance (corresponds to the mechanical constraints of the robot)	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1	1	0.6	0.6	∞
Test sample Related									
Test Sample Positioning	E.4.2	1.0	N	1	1	1	1.2	1.2	4
Device Holder Uncertainty	E.4.1	2.0	R	1.73	1	1	0.7	0.7	4
Output Power Variation - SAR drift measurement (4)	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									



Sony Ericsson

REPORT

56(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values (5)	E.3.2	4.3	R	1.73	0.64	0.43	1.6	1.1	∞
Liquid Conductivity - measurement uncertainty (6)	E.3.3	6.20	R	1.73	0.64	0.43	2.3	1.5	∞
Liquid Permittivity - deviation from target values (5)	E.3.2	3.7	R	1.73	0.6	0.49	1.3	1.0	∞
Liquid Permittivity - measurement uncertainty (6)	E.3.3	6.08	R	1.73	0.6	0.49	2.1	1.7	∞
Combined Standard Uncertainty			RSS				9.46	9.12	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			K=2				18.91	18.23	



Sony Ericsson

REPORT

57(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Table 3a. Values for e'

Uncertainty Component	Tolerance ($\pm\%$)	Probability Distribution	Divisor	c_i	Standard Uncertainty ($\pm\%$)	v_i or v_{eff}
Repeatability (n repeats)	0.97	N	1	1	0.97	4
Network analyzer uncertainty sources	8.38	R	1.73	1	4.83	∞
Dielectric Error Sources	5.93	R	1.73	1	3.42	∞
Combined standard uncertainty					6.08	

Table 3b. Values for σ

Uncertainty Component	Tolerance ($\pm\%$)	Probability Distribution	Divisor	c_i	Standard Uncertainty ($\pm\%$)	v_i or v_{eff}
Repeatability (n repeats)	1.85	N	1	1	1.85	4
Network analyzer uncertainty sources	8.38	R	1.73	1	4.83	∞
Dielectric Error Sources	5.93	R	1.73	1	3.42	∞
Combined standard uncertainty					6.20	

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

58(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc

Appendix 6

Photographs of the Device Under Test

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

59(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



a. Front



b. Back



c. Side

Views of Device

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

60(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Front View



Back View

Front and Back views of carry accessory model ICE-25.

Exhibit 11

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

61(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Front View



Back View

Front and Back views of carry accessory model ICT-14.

Exhibit 11

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

62(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



View of Hands-free Accessory HPB-20

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

63(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Position of device against head phantom

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

64(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Position of device against head phantom in the tilted position

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

65(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Position of device against flat phantom using a 15mm spacer with hands free accessory (HPB-20).

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

66(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Position of device against flat phantom using a 15mm spacer with hands free accessory (HPB-20).

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

67(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	C	X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Position of device against flat phantom using carry accessory ICE25 with hands free accessory (HPB-20).

APPLICANT: Sony Ericsson Mobile Communications Inc.

FCC ID: **PY7A1061011**



Sony Ericsson

REPORT

68(68)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes		No. REP 2005 004 T292A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked	C X:\SAR Chamber\FCC reports\T292A\Final Reports\FCCT292A.doc



Position of device against flat phantom using carry accessory ICT14 with hands free accessory (HPB-20).