



Prepared (also subject responsible if other)

SEM/CVVGP, Leif Hedin

Approved

SEM/CVVGP, Leif Hedin

Checked

Company Internal
MARKING DRAWING
No.

1244-0569 Uen

Date

2011-04-19

Rev

1

Reference

3

WT13i, Mobile Phone label, ROW, made in...

1 General information

Mobile Phone label part no	1243-7744
Bar code	Print quality: according to COSMETIC GUIDELINE – Bar code labels document 1222-6072 Uen Quiet zone: No bar codes are allowed to be closer to a label edge than 4 mm!
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

MLCI= Main Label Content Information Document

2 Printing information

Content	Format
Line 1a (2,0/1,0)	Sony Ericsson stylized name.
Line 1b (2,0/16,0)	Graphics, height 1,5 mm. According to 1200-1925
Line 1c (2,0/21,0)	Model Name “WT13i” Marking of origin; “Made in Xxx” “Xxx” = actual country of production of the included telephone, in English
Line 2a (4,0/1,0)	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 2b (4,0/12,0)	Product number of the Sales Item in which the phone is packed, if applicable. “SI XXXX-XXXX”
Line 2c (4,0/17,0)	Text, height 1,2 mm.
Line 2d (4,0/23,5)	Location code of where the phone is flashed, if applicable, “XXX”
Line 3a (5,5/1,0)	Text, height 1,2 mm. Production week (flash), “yyWww” (yy = year, ww = week)
Line 3b (5,5/19,0)	Text, height 1,2 mm. Repair week, if applicable. “RyyWww” (yy = year, ww = week)
Line 4a (7,5/1,0)	Text, height 1,2 mm. “TYPE: AAB-1880032-BV” <i>According to Chapter 1 in MLCI.</i>
Line 4b (7,5/16,0)	Text, height 1,2 mm. HW & SW identification field, if applicable; “FFGG” According to Type-testing report under Product Model Specifying Documents
Line 5 (10,0/2,0)	Text, height 1,2 mm. “FCC ID: PY7A1880032” <i>According to Chapter 1 in MLCI.</i>
Line 6a (11,0/1,0)	Text, height 1,2 mm. “IC: 4170B-A1880032” <i>According to Chapter 1 in MLCI.</i>
Line 6b (11,0/1,0)	Text, height 1,2 mm. Line 5 in bar code, according to line 6a. As desired by supplier (e.g. only actual number).
Line 6c (11,0/1,0)	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 6d (11,0/1,0)	Text, height 1,5 mm. Supplier’s identification for trace-ability of the telephone, as desired by supplier (e.g. “S/N: Defined by supplier.



Prepared (also subject responsible if other)

SEM/CSVGP, Leif Hedin

Approved

SEM/CSVGP, Leif Hedin

Checked

Company Internal
MARKING DRAWING
No.

1244-0569

Date

2011-04-19

Rev

1

Reference

3

	nnn...." for serial number).	
Line 6b (1,0/15,0)	Actual electronic serial number (IMEI) of the mobile phone, "00000000-000000-0"	Text, height 1,5mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 7 (13,5/2,0)	Line 7 in bar code, according to line 6b. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 8a (19,0/1,0)	CE approval symbol, the NB-"0682" and "Alert Symbol" in one artwork	Graphics, height 5 mm. According to 1242-7470
Line 8b (19,0/31,0)	WEEE trashcan without bar symbol	Graphics, min. height 5mm, according to 1202-5537.

3 Layout

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1

Conceptual picture



double underlined = major changes since last revision.



Prepared by

Contents responsible if other than preparer

Label placement

To find the label follow these steps:

1. Remove the cover on the rear side of the product.
2. Remove the battery.
3. The label is located behind the battery.

