



Prepared (also subject responsible if other)

Yulin Cheng(28847649)

Approved

Yulin Cheng(28847649)

Checked

Company Internal
MARKING DRAWING
No.

1206-9778

Date

2007-12-13

Rev

1

Reference

31

Approved according to 000 21–LXE 107 42/1

Product Specification Becky, Made in

1 General information

Core Unit label part no	1202-5662
Bar code	Standard: according to Ericsson corporate standard 102 01–109 Uen Print quality: C, according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

MLCI= Main Label Content Information-document.

2 Printing information

	Content	Format
Line 1 (4,0/15,0)	Sony Ericsson stylized name.	Graphics, height 1,5 mm. According to 1200-1925.
Line 2 (6,5/12,5)	SIM card logo	Graphics, height 7,3 mm. According to 1200-9812. Rotated 90° counter-clockwise
Line 3a (8,0/15,0)	Product number without revision of the Sales Item in which the phone is packed, if applicable. “SI: XXXX-XXXX”	Text, height 1,2 mm.
Line 3b (8,0/30,0)	Model Name “Z770i”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 4a (11,0/2,0)	“TYPE: AAD-3052051-BV”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 4b (11,0/23,0)	HW & SW identification field, if applicable; “FG”	Text, height 1,2 mm. According to Type-testing report in BOM pos 1C.
Line 4c (11,0/29,5)	Location code of where the phone is flashed, if applicable, “XXX”	Text, height 1,2 mm.
Line 5a (14,0/2,0)	“FCC ID: PY7A3052051”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 5b (14,0/23,0)	Production week (flash), “yy’W’ww” (yy = year, ww = week)	Text, height 1,2 mm.
Line 6a (17,0/2,0)	“IC: 4170B-A3052051”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 6b (17,0/23,0))	Repair week, if applicable. “Ry’W’ww” (y = year, ww = week)	Text, height 1,2 mm.
Line 7 (20,0/2,0)	Line 8a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 8a (23,0/2,0)	Supplier’s identification for trace-ability of the telephone, as desired by supplier (e.g. “S/N: nnn....” for serial number).	Text, height 1,2 mm. Defined by supplier.



Prepared (also subject responsible if other)

Yulin Cheng(28847649)

Approved

Yulin Cheng(28847649)

Checked

Company Internal
MARKING DRAWING
No.

1206-9778

Date

2007-12-13

Rev

1

Reference


31

	Content	Format
Line 8b (23,0/19,0)	Actual electronic serial number (IMEI) of the Mobile Phone, "00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 9 (25,5/2,0)	Line 8b in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 10a (33,0/2,0)	CE approval symbol	Graphics, height 5 mm. According to 1202-5482.
Line 10b (33,0/10,0)	The notified body number "0682"	Text, height 1,2 mm.
Line 11 (37,0/2,0)	Marking of origin: "Xxx"= actual country of production of the included telephone, in English.	Text, height 1,2 mm.

3 Layout

The conceptual picture (for Zebra 90Xiii printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



double underlined = major changes since last revision.



Prepared (also subject responsible if other)

Yulin Cheng(28847649)

Approved

Yulin Cheng(28847649)

Checked

Company Internal
MARKING DRAWING
No.

1206-9778

Date

2007-12-13

Rev

1

Reference

31

3.2 Label placement

To find the label follow these steps:

1. Remove the cover on the rear side of the product.
2. Remove the battery.
3. The label is located behind the battery.

