Deutscher Akkreditierungs Rat

Accredited testing-laboratory

DAR registration number: DAT-P-176/94-D1

Federal Motor Transport Authority (KBA)
DAR registration number: KBA-P 00070-97

Recognized by the Federal Communications Commission
Anechoic chamber registration no.: 90462 (FCC)
Anechoic chamber registration no.: 3462C-1 (IC)
Certification ID: DE 0001
Accreditation ID: DE 0002

Accredited Bluetooth® Test Facility (BQTF)

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Cetecom ICT is under license

Test report no.	**:**	**1-1065-19-04/09**
Type identification	**:**	**AAD-3880029-BV**
Applicant	**:**	**Sony Ericsson Mobile Communications AB**
FCC ID	**:**	**PY7A3880029**
IC Certification No	**:**	**4170B-A3880029**
Test standards	**:**	**47 CFR Part 15**
		RSS - 210 Issue 7

Table of contents

1 General information 3
1.1 Notes 3
1.2 Testing laboratory 4
1.3 Details of applicant 4
1.4 Application details 4
2 Test standard/s 5
3 Technical tests 6
3.1 Details of manufacturer 6
3.1.1 Test item 6
3.1.2 Additional EUT information For IC Canada (appendix 2) 7
3.1.3 RF Technical Brief Cover Sheet acc. To RSS-102 8
3.1.4 EUT operating modes 9
3.1.5 Extreme conditions testing values 9
4 Summary of Measurement Results and list of all performed test cases 10
5 RF measurement testing 11
5.1 Description of test set-up 11
5.1.1 Radiated measurements 11
5.1.2 Conducted measurements 11
5.2 Referenced documents 12
5.3 Additional comments 12
5.4 Antenna gain 12
5.5 Carrier frequency separation §15.247(a)(1) 13
5.6 Number of hopping channels §15.247(a)(1) 14
5.7 Time of occupancy (dwell time) §15.247(a)(1)(iii) 15
5.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(e) 16
5.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1) 17
5.10 Maximum output power (conducted) § 15.247 (b)(1) 22
5.11 Max. peak output power (radiated) § 15.247 (b)(1) 27
5.12 Band-edge compliance of conducted emissions §15.247 (d) 28
5.13 Band-edge compliance of radiated emissions §15.205 36
5.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1) 39
5.15 Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1) 45
5.16 Spurious Emissions - radiated (Receiver) § 15.109 54
5.17 Spurious Emissions < 30 MHz - Transmitter radiated § 15.209 58
5.18 Conducted Emissions <30 MHz § 15.107/207 59
6 Test equipment and ancillaries used for tests 61
7 Photographs of the Test Set-up 63
8 Photographs of the EUT 65

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

Test laboratory manager:

2009-03-19	**Daniel Muyunga**	
Date	Name	Signature
2009-03-19	**Marco Bertolino**	M. Bertolino
Date	Name	Signature

Technical responsibility for area of testing:

2009-03-19	**Stefan Bös**	Stefan Bös
Date	Name	Signature

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10
66117 Saarbrücken
Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
e-mail: info@ICT.cetecom.de
Internet: http://www.cetecom-ict.de

State of accreditation: **The test laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025**
DAR registration number: DAT-P-176/94-D1

Accredited by: **Federal Motor Transport Authority (KBA)**
DAR registration number: KBA-P 00070-97

Testing location, if different from CETECOM ICT Services GmbH:

Name :
Street :
Town :
Country :
Phone :
Fax :

1.3 Details of applicant

Name:	**Sony Ericsson Mobile Communications AB**
Street:	**Mobilvägen 10**
Town:	**22188 Lund**
Country:	**Sweden**
Telephone:	**+46-46-19-3000**
Fax:	**+46-10-800-2441**
Contact:	**Mr. Peter Lindeborg**
E-mail:	**peter.lindeborg@sonyericsson.com**
Telephone:	**+46-10-802-43 68**

1.4 Application details

Date of receipt of order:	**2009-03-09**
Date of receipt of test item:	**2009-03-09**
Date of start test:	**2009-03-16**
Date of end test	**2009-03-19**
Persons(s) who have been present during the test:	**-/-**

2 Test standard/s

47 CFR Part 15	**2008-07**	**Title 47 of the Code of Federal Regulations; Chapter I-Federal Communications Commission subchapter A - general, Part 15-Radio frequency devices**
RSS - 210 Issue 7	**2007-06**	**Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment**

3 Technical tests

3.1 Details of manufacturer

Name:	**Sony Ericsson Mobile Communications AB**
Street:	**Mobilvägen 10**
Town:	**22188 Lund**
Country:	**Sweden**

3.1.1 Test item

Kind of test item	:	**Mobile Phone 850/900/1800/1900/UMTS FDD1 /HSDPA /BT2.0+EDR**
Type identification	:	**AAD-3880029-BV**
S/N serial number	:	**Rad.: BX900H9GQF, BX900H9G** **Cond.: BX900H9GQQ, BX900H9GQY**
HW hardware status	:	**A**
SW software status	:	**-/-**
Frequency Band [MHz]	:	**ISM 2.400 - 2.483,5**
Type of Modulation	:	**FHSS**
Number of channels	:	**79**
Antenna	:	**Integrated antenna**
Power Supply	:	**4.0 V by Li-Ion battery BST-39 and power supply**
Temperature Range	:	**-20 °C to +60 °C**

<u>GFSK</u>
Max. power radiated: 2.61 dBm
Max. power conducted: 5.43 dBm

<u>Pi/4 DQPSK</u>
Max. power radiated: 2.44 dBm
Max. power conducted: 5.28 dBm

<u>8DPSK</u>
Max. power radiated: 2.74 dBm
Max. power conducted: 5.53 dBm

FCC ID: PY7A3880029
IC: 4170B-A3880029

3.1.2 Additional EUT information For IC Canada (appendix 2)

IC Registration Number:	**4170B-A3880029**
Model Name:	**AAD-3880029-BV**
Manufacturer (complete Address):	**Sony Ericsson Mobile Communications AB Mobilvägen 10 22188 Lund Sweden**
Tested to Radio Standards Specification (RSS) No.:	**RSS-210 Issue 7**
Open Area Test Site Industry Canada Number:	**IC 3462C-1**
Frequency Range (or fixed frequency) [MHz]:	**2400 – 2483.5 MHz**
RF: Power [W] (max):	**GFSK: Rad. EIRP: 1.8 mW Conducted : 3.5 mW Pi/4 DQPSK: Rad. EIRP: 1.8 mW Conducted : 3.4 mW 8QPSK: Rad. EIRP: 1.9 mW Conducted : 3.6 mW**
Antenna Type:	**Integrated antenna**
Occupied Bandwidth (99% BW) [kHz]:	**GFSK: 932 Pi/4 DQPSK: 1335 8 DPSK: 1269**
Type of Modulation:	**GFSK, Pi/4 DQPSK, 8 DPSK**
Emission Designator (TRC-43):	**GFSK: 932KFXD Pi/4 DQPSK: 1M33GXD 8DPSK: 1M27GXD**
Transmitter Spurious (worst case) [dBµV/m in 10m]:	**23.0**
Receiver Spurious (worst case) [dBµV/m in 10m]:	**22.7**

ATTESTATION:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:

Test engineer: Daniel Muyunga Date: 2009-03-19

3.1.3 RF Technical Brief Cover Sheet acc. To RSS-102

All Fields must be completed with the requested information or the following codes: N/A for Not Applicable, N/P for Not Performed or N/V for Not Available. Where applicable, check appropriate box.

1. COMPANY NUMBER: **4170B-A3880029**

2. MODEL NUMBER: **AAD-3880029-BV**

3. MANUFACTURER: **Sony Ericsson Mobile Communications AB**

4. TYPE OF EVALUATION: **(c) RF Evaluation**

- Evaluated against exposure limits: General Public Use ☒ Controlled Use ☐
- Duty cycle used in evaluation: 99 %
- Standard used for evaluation: RSS-102 Issue 2 (2005-11)
- Measurement distance: 0.20 m
- RF value: 0.0037 V/m □ A/m □ W/m^2 ☒

Measured ☐ Computed ☐ Calculated ☒

Declaration of RF Exposure Compliance

ATTESTATION:

I attest that the information provided in this test report are correct; that a Technical Brief was prepared and the information it contains is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed and that the device meets the SAR and/or RF exposure limits of RSS-102.

Name: Daniel K. Muyunga, Dipl.-Ing. (FH)
Title: Engineer
Company: Cetecom ICT Services GmbH

3.1.4 EUT operating modes

EUT operating mode no.*)	Description of operating modes	Additional information
Op. 0	Normal mode	Normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

*) EUT operating mode no. is used to simplify the test plan

3.1.5 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T_{nom}	°C	**+23**
Nominal Humidity	H_{nom}	%	**35**
Nominal Power Source	V_{nom}	V	**4.0**

Type of power source: **by Li-Ion battery BST-39 and power supply**

Deviations from these values are reported in chapter 2

4 Summary of Measurement Results and list of all performed test cases

☒ **No deviations from the technical specifications were ascertained**

☐ There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	PASS	2009-03-19	-/-

Test Specification Clause	Test Case	Modulation	Pass	Fail	N/A	Not performed
None	Antenna Gain	GFSK	Yes			
§15.247(a1)	Carrier frequency separation	GFSK	Yes			
§15.247(a1)	Number of hopping channels	GFSK	Yes			
§15.247(a)(1)(iii)	Time of occupancy (dwell time)	--	Yes			
§15.247(e)	Power Spectral density (Hybrid system in Inquiry mode/Page scan)	--			Yes	
§15.247(a)(1)	Spectrum Bandwidth of a FHSS System / 20dB Bandwith	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (b)(1)	Maximum output power (conducted)	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (b)(1)	Max. peak output power (radiated)	GFSK	Yes			
§ 15.247 (d)	Band-edge compliance of conducted emissions	Widest modulation	Yes			
§ 15.205	Band-edge compliance of radiated emissions	Widest modulation	Yes			
§ 15.247 (d)	Spurious Emission - conducted (Transmitter)	GFSK	Yes			
§ 15.247 (d)	Spurious Emission - radiated (Transmitter) >30 MHz	GFSK	Yes			
§ 15.109	Spurious Emissions - radiated (Receiver)	GFSK	Yes			
§ 15.209	Spurious Emissions - radiated (Transmitter) <30 MHz	GFSK	Yes			
§ 15.107/207	Conducted Emissions <30 MHz	GFSK	Yes			

5 RF measurement testing

5.1 Description of test set-up

5.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63-4-2003 clause 4.2.
Antennas are confirmed with ANSI C63.2-1996 item 15.

9 kHz - 150 kHz: Quasi Peak measurement, 200 Hz Bandwidth, passive loop antenna.
150 kHz - 30 MHz: Quasi Peak measurement, 9 kHz Bandwidth, passive loop antenna.
30 MHz - 200 MHz: Quasi Peak measurement, 120 kHz Bandwidth, bi-conical antenna
200MHz - 1GHz: Quasi Peak measurement, 120 kHz Bandwidth, log periodic antenna
>1GHz: Average, RBW 1MHz, VBW 10 Hz, waveguide horn

All measurements are done in accordance with the Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems DA 00-705 and Appendix A “BLUETOOTH APPROVALS”
The EUT is powered by an external power supply with nominal voltage. The signalling is performed from outside the chamber with a signalling unit (CMU200 or other) by air link using signalling antenna.

5.1.2 Conducted measurements

The EUT’s RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



5.2 Referenced documents

None

5.3 Additional comments

None

5.4 Antenna gain

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

	low channel 2402 MHz	mid channel 2441 MHz	high channel 2480 MHz
Conducted power [dBm] Measured, GFSK modulation	4.77	5.43	5.31
Radiated power [dBm] Measured, GFSK modulation	2.03	2.57	2.61
Gain [dBi] Calculated	-2.74	-2.86	-2.70

5.5 Carrier frequency separation §15.247(a)(1)

Modulation: GFSK

Plot 1 of 1:



Result: Channel separation is: ~ 1 MHz

Limits:

Under normal test conditions only	Minimum 25 kHz or 20 dB Bandwidth of the hopping system

5.6 Number of hopping channels §15.247(a)(1)

Modulation: GFSK

Plot 1 of 2:



Plot 2 of 2:



Result: The number of hopping channels is: 79

Limits:

Under normal test conditions only	at least 15 non-overlapping channels

5.7 Time of occupancy (dwell time) §15.247(a)(1)(iii)

For Bluetooth devices:

The dwell time of 0.4 s within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is a follows:

Dwell time = time slot length * hop rate / number of hopping channels *31.6 s

Example for a DH1 packet (with a maximum length of one time slot)
Dwell time = 625 µs * 1600 1/s / 79 * 31.6 s = 0.4 s (in a 31.6 s period)

For multi-slot packet the hopping is reduced according to the length of the packet.
Example for a DH5 packet (with a maximum length of five time slots)
Dwell time = 5 * 625 µs * 1600 * 1/5 *1/s / 79 * 31.6 s = 0.4 s (in a 31.6 s period)

This is according the Bluetooth Core Specification V 1.1 & V 1.2 & V2.0 (+ critical errata) for all Bluetooth devices.
Therefore, all Bluetooth devices comply with the FCC dwell time requirement in the data mode.
This was checked during the Bluetooth Qualification tests.
The Dwell time in hybrid mode is approximately 2.6 ms (in a 12.8s period)

5.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(e)

Not applicable

Result: Power density: - dBm/Hz = - dBm / 3 kHz
Correction factor from dBm/Hz to dBm / 3 kHz is +34,8 dB

Limits:

Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

5.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1)

Plot 1: GFSK



Plot 2: GFSK



Plot 3: GFSK



Plot 4: Pi/4 DQPSK



Plot 5: Pi/4 DQPSK



Plot 6: Pi/4 DQPSK



Plot 7: 8DPSK



Plot 8: 8DPSK



Plot 9: 8DPSK



Result:

Modulation	**20 dB BANDWIDTH [kHz]**		
Frequency [MHz]	2402	2441	2480
GFSK	926	926	932
Pi/4 DQPSK	1335	1335	1335
8DPSK	1269	1269	1269
Measurement uncertainty	± 10 kHz		

RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000)
RBW: 10 kHz / VBW 10 kHz

Limits:

Under normal test conditions only	GFSK < 1000 kHz Pi/4 DQPSK < 1500 8DPSK < 1500

5.10 Maximum output power (conducted) § 15.247 (b)(1)

Plot 1: GFSK

Plot 2: GFSK

Plot 3: GFSK



Ref. Level Offset [dB]	Detector	Sweeptime [s]	Video BW [Hz]	RBW [Hz]
12.3	POS	5m	3M	3000000

Start Freq [Hz]	Stop Freq [Hz]	Tracem.	Found Peak [dBm]	Found Peak [Hz]
2.478G	2.482G	MAXH	5.312	2.48G

Plot 4: Pi/4 DQPSK



Ref. Level Offset [dB]	Detector	Sweeptime [s]	Video BW [Hz]	RBW [Hz]
12.1	POS	5m	3M	3000000

Start Freq [Hz]	Stop Freq [Hz]	Tracem.	Found Peak [dBm]	Found Peak [Hz]
2.401G	2.404G	MAXH	4.704	2.402G

Plot 5: Pi/4 DQPSK



Plot 6: Pi/4 DQPSK



Plot 7: 8DPSK



Ref. Level Offset [dB]	Detector	Sweeptime [s]	Video BW [Hz]	RBW [Hz]
12.1	POS	5m	3M	3000000

Start Freq [Hz]	Stop Freq [Hz]	Tracem.	Found Peak [dBm]	Found Peak [Hz]
2.401G	2.404G	MAXH	4.877	2.402G

Plot 8: 8DPSK



Ref. Level Offset [dB]	Detector	Sweeptime [s]	Video BW [Hz]	RBW [Hz]
12.4	POS	5m	3M	3000000

Start Freq [Hz]	Stop Freq [Hz]	Tracem.	Found Peak [dBm]	Found Peak [Hz]
2.439G	2.442G	MAXH	5.536	2.441G

Plot 9: 8DPSK



Results:

Modulation	**Max. peak output power [dBm]**		
Frequency [MHz]	2402	2441	2480
GFSK	4.77	5.43	5.31
Pi/4 DQPSK	4.70	5.28	5.14
8DPSK	4.87	5.53	5.44
Measurement uncertainty	± 2 dB		

RBW / VBW: 3 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt

5.11 Max. peak output power (radiated) § 15.247 (b)(1)

Modulation: GFSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T_{nom}	V_{nom}	2.03	2.57	2.61
Measurement uncertainty		± 3 dB		

RBW / VBW: 3 MHz

Modulation: Pi/4 DQPSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T_{nom}	V_{nom}	1.96	2.42	2.44
Measurement uncertainty		± 3 dB		

RBW / VBW: 3 MHz

Modulation:8PSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T_{nom}	V_{nom}	2.13	2.67	2.74
Measurement uncertainty		± 3 dB		

RBW / VBW: 3 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt

5.12 Band-edge compliance of conducted emissions §15.247 (d)

Modulation: GFSK

Plot 1 of 4 (hopping off, lowest frequency):



Plot 2 of 4 (hopping on, lowest frequency):



Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):



Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Modulation: Pi/4 DQPSK

Plot 1 of 4 (hopping off, lowest frequency):



Plot 2 of 4 (hopping on, lowest frequency):



Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):



Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Modulation: 8 DPSK

Plot 1 of 4 (hopping off, lowest frequency):



Plot 2 of 4 (hopping on, lowest frequency):

Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):



Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Limits:

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).

5.13 Band-edge compliance of radiated emissions §15.205

Modulation: GFSK

Plot 1: Restricted Bands low



Date: 16.MAR.2009 20:55:37

Plot 2: Restricted Bands high



Date: 16.MAR.2009 20:48:11

Modulation: Pi/4 DQPSK

Plot 1: Restricted Bands low



Date: 16.MAR.2009 20:51:39

Plot 2: Restricted Bands high



Date: 16.MAR.2009 20:48:37

Modulation: 8DPSK

Plot 1: Restricted Bands low



Date: 16.MAR.2009 20:50:57

Plot 2: Restricted Bands high



Date: 16.MAR.2009 20:49:09

5.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)

Modulation: GFSK

Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel



Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		4.77	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
2441		5.31	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
2480		5.25	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
Measurement uncertainty			± 3dB		

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Modulation: Pi/4 DQPSK

Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel



Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		4.31	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
2441		4.90	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
2480		4.77	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
Measurement uncertainty			± 3dB		

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Modulation: 8 DPSK

Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel



Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		4.42	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
2441		5.02	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
2480		4.86	30 dBm		Operating frequency
Found peaks not critical			-20 dBc		complies
					complies
Measurement uncertainty			± 3dB		

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.

5.15 Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1)

Modulation: 8DPSK

Plot 1: 0.03 - 1 GHz vertical/horizontal (lowest channel)

Common Information

EUT:	AAD-3880029-BV + CAA-0002001-BV (SN: 15 07W52 104209)
Serial Number:	S/N: BX900H9GNX
Test Description:	FCC part 15 B @ 10 m
Operating Conditions:	BT Tx Ch.: 00 + charging
Operator Name:	LNG
Comment:	Powerd by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
30.604500	10.9	15000.000	120.000	179.0	V	141.0	12.7	19.1	30.0
42.991000	13.5	15000.000	120.000	98.0	V	323.0	13.5	16.5	30.0
156.007250	22.8	15000.000	120.000	98.0	V	72.0	9.3	10.7	33.5
742.408000	21.0	15000.000	120.000	220.0	V	141.0	24.0	15.0	36.0
848.463150	21.9	15000.000	120.000	220.0	V	137.0	25.0	14.1	36.0
886.534850	22.5	15000.000	120.000	205.0	H	323.0	25.5	13.5	36.0

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3]
	@ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch
	FW 1.0
Antenna:	VULB 9163
	SN 9163-295, FW ---
	Correction Table (vertical): VULP6113
	Correction Table (horizontal): VULP6113
	Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower]
	@ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable]
	@ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 3 GHz vertical/horizontal (lowest channel)



Signal suppressed with a 2.4 GHz Band notch filter

Plot 3: 3 - 12 GHz vertical/horizontal (lowest channel)



Measured in 1 meter distance

Plot 4: 12 - 25 GHz vertical/horizontal (valid for all channels)



Plot 5: 0.03 - 1 GHz vertical/horizontal (middle channel)

Common Information

EUT:	AAD-3880029-BV + CAA-0002001-BV (SN: 15 07W52 104209)
Serial Number:	S/N: BX900H9GNX
Test Description:	FCC part 15 B @ 10 m
Operating Conditions:	BT Tx Ch.: 39 + charging
Operator Name:	LNG
Comment:	Powerd by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
46.006600	14.9	15000.000	120.000	98.0	V	55.0	13.4	15.1	30.0
53.963900	12.7	15000.000	120.000	129.0	V	290.0	13.2	17.3	30.0
55.001050	14.2	15000.000	120.000	220.0	V	119.0	13.1	15.8	30.0
156.001550	22.7	15000.000	120.000	98.0	V	105.0	9.3	10.8	33.5
695.883800	19.8	15000.000	120.000	138.0	H	19.0	22.9	16.2	36.0
747.881050	21.1	15000.000	120.000	220.0	V	41.0	24.1	14.9	36.0

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3]
	@ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch
	FW 1.0
Antenna:	VULB 9163
	SN 9163-295, FW ---
	Correction Table (vertical): VULP6113
	Correction Table (horizontal): VULP6113
	Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower]
	@ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable]
	@ GPIB0 (ADR 9), FW REV 3.12

Plot 6: 1 - 3 GHz vertical/horizontal (middle channel)



Signal suppressed with a 2.4 GHz Band notch filter

Plot 7: 3 - 12 GHz vertical/horizontal (middle channel)



Measured in 1 meter distance

Plot 8: 0.03 - 1 GHz vertical/horizontal (highest channel)

Common Information

EUT:	AAD-3880029-BV + CAA-0002001-BV (SN: 15 07W52 104209)
Serial Number:	S/N: BX900H9GNX
Test Description:	FCC part 15 B @ 10 m
Operating Conditions:	BT Tx Ch.: 78 + charging
Operator Name:	LNG
Comment:	Powerd by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
30.636000	11.0	15000.000	120.000	191.0	V	49.0	12.7	19.0	30.0
31.033500	10.8	15000.000	120.000	98.0	V	323.0	12.7	19.2	30.0
42.961600	12.6	15000.000	120.000	98.0	V	233.0	13.5	17.4	30.0
54.895150	10.6	15000.000	120.000	181.0	V	323.0	13.1	19.4	30.0
156.002150	23.0	15000.000	120.000	98.0	V	82.0	9.3	10.5	33.5
824.261350	22.5	15000.000	120.000	156.0	V	143.0	24.7	13.5	36.0

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3]
	@ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch
	FW 1.0
Antenna:	VULB 9163
	SN 9163-295, FW ---
	Correction Table (vertical): VULP6113
	Correction Table (horizontal): VULP6113
	Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower]
	@ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable]
	@ GPIB0 (ADR 9), FW REV 3.12

Plot 9: 1 - 4 GHz vertical/horizontal (highest channel)

Signal suppressed with a 2.4 GHz Band notch filter

Plot 10: 4 - 12 GHz vertical/horizontal (highest channel)



Measured in 1 meter distance

Results:

SPURIOUS EMISSIONS LEVEL (dBµV/m)								
2402 MHz			2441 MHz			2480 MHz		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
No peak detected Also see table below plots			No peak detected Also see table below plots			No peak detected Also see table below plots		
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz f ≥ 1GHz : RBW/VBW: 1 MHz

Limits: § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limits: § 15.209

Frequency [MHz]	Field strength [µV/m]	Measurement distance (m)
30 - 88	100 (40 dBµV/m)	3
88 - 216	150 (43.5 dBµV/m)	3
216 - 960	200 (46 dBµV/m)	3
above 960	500 (54 dBµV/m)	3

5.16 Spurious Emissions - radiated (Receiver) § 15.109

Plot 1: 0.03 - 1 GHz vertical/horizontal (receiver)

Common Information

EUT:	AAD-3880029-BV + CAA-0002001-BV (SN: 15 07W52 104209)
Serial Number:	S/N: BX900H9GNX
Test Description:	FCC part 15 B @ 10 m
Operating Conditions:	BT Rx mode + charging
Operator Name:	LNG
Comment:	Powerd by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
38.372650	9.9	15000.000	120.000	127.0	H	272.0	13.4	20.1	30.0
43.017200	12.8	15000.000	120.000	120.0	V	-3.0	13.5	17.2	30.0
54.256250	9.4	15000.000	120.000	220.0	H	288.0	13.1	20.6	30.0
75.056350	11.7	15000.000	120.000	220.0	V	197.0	9.5	18.3	30.0
156.012950	22.7	15000.000	120.000	98.0	V	69.0	9.3	10.8	33.5
763.712200	21.0	15000.000	120.000	220.0	H	323.0	24.2	15.0	36.0

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3]
	@ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch
	FW 1.0
Antenna:	VULB 9163
	SN 9163-295, FW ---
	Correction Table (vertical): VULP6113
	Correction Table (horizontal): VULP6113
	Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower]
	@ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable]
	@ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 – 3 GHz vertical/horizontal (receiver)



Plot 3: 3 - 12 GHz vertical/horizontal (receiver)



Measured at 1 meter distance

Plot 4: 12 - 25 GHz vertical/horizontal (receiver)



Results:

Spurious Emissions level [dBµV/m]		
f[MHz]	Detector	Level [dBµV/m]
No peak detected Also see table below plots		
Measurement uncertainty	±3 dB	

f < 1 GHz: RBW/VBW: 100 kHz f ≥ 1GHz : RBW/VBW: 1 MHz
See above plots

Measurement distance see table

Limits: § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100 (40 dBµV/m)	3
88 - 216	150 (43.5 dBµV/m)	3
216 - 960	200 (46 dBµV/m)	3
above 960	500 (54 dBµV/m)	3

5.17 Spurious Emissions < 30 MHz - Transmitter radiated § 15.209

Modulation: GFSK

Measured at 3 m distance.
Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:



Limits:

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dBµV/m	30

5.18 Conducted Emissions <30 MHz § 15.107/207

Modulation: GFSK

Plot 1: Neutral line, Transmitting



Plot 2: Phase line, Transmitting



Plot 3: Neutral line, Idle



Plot 4: Phase line, Idle



Limits:

Under normal test conditions only	See plots

6 Test equipment and ancillaries used for tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

All reported calibration intervals are calibrations according to the EN/ISO/IEC 17025 standard. These calibrations were performed from an accredited external calibration laboratory.
Additional to these calibrations the laboratory performed comparison measurements with other calibrated systems and performed a weekly chamber inspection.
All used devices are connected with a 10 MHz external reference.
According to the manufacturers' instruction is it possible to establish a calibration interval for the FSP unit of 24 month, if the device has an external 10 MHz reference.

Anechoic chamber A:

No.	Instrument/Ancillary	Manufacturer	Type	Serial-No.	Internal identification
	Radiated emission in chamber A				
A-1	Spectrum Analyzer	Rohde & Schwarz	ESU26	100037	300003555
A-2	Signal Generator	Rohde & Schwarz	SMR20B11	1104.0002.20	300003593
A-3	RF System Panel	Rohde & Schwarz	TS RSP	---	300003556
A-4	Relais Matrix	Rohde & Schwarz	PSN	860673/009	300001385
A-5	Horn Antenna	EMCO	3115	9709-5290	300000212
A-6	Bilog.-Log. Antenna	Schwarzbeck	VULB 9163	02/00	300003696
A-7	Notch Filter GSM 900	Wainwright	WRCD 901.9/903.1EE	9	---
A-8	Notch Filter GSM 1800	Wainwright	WRCD 1747/1748-5EE	1	---
A-9	Notch Filter GSM 1900	Wainwright	WRCB 1879.5/1880.5EE	9	---
A-10	Notch Filter GSM 850	Wainwright	WRCT 837-0.2/50-8EE	1	---
A-11	Notch Filter UMTS	Wainwright	WRCD 1800/2000-0.2/40-5EEK	2	---
A-12	Notch Filter ISM 2400	Wainwright	WRCG 2400/ 2483-2375/ 2505-50/10SS	26	---
A-13	High Pass Filter 1.1 GHz	Wainwright	WHK 1.1/15G-10SS	---	---
A-14	High Pass Filter 2.6 GHz	Wainwright	WHKX 2.6/18G-12SS	---	---
A-15	High Pass Filter 7 GHz	Wainwright	WHKX 7.0/18G-8SS	---	---
A-14	Amplifier	Miteq	AFS4-00201800-15-10P-6	US42-0050 2650-28-5A	300003204
A-16	Controller	Inn co	CO 2000	2020507	---
A-17	DC Power Supply	Hewlet Packard	HP6632A	---	300000924
A-18	Computer	F+W	---	---	300003303

System Rack Room 005 :

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	FSP 30	R&S	100886	300003575	25.08.2008	24	25.08.2010
2	CBT	R&S	100313	300003516	03.09.2008	24	03.09.2010
3	Switch Matrix	HP		300000929	n.a.		
4	Power Supply	HP	3041A00544	300002270	13.05.2007	36	13.05.2010
5	Signal Generator	R&S	836206/0092	300002680	30.05.2007	36	30.05.2010

Signalling Units:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	CBT	R&S	100313	300003516	03.09.2008	24	03.09.2010
2	CBT	R&S	100185	300003416	27.08.2008	24	27.08.2010
3	CMU-200	R&S	103992	300003231	04.06.2008	12	04.06.2009
4	CMU-200	R&S	106240	300003321	27.08.2008	24	27.08.2010
5	CMU-200	R&S	832221/0055	300002862	20.03.2008	24	20.03.2010

Anechoic chamber F:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Control Computer	F+W	FW0502032	300003303	-/-	-/-	-/-
2	Trilog Antenna VULB 9163	Schwarzbeck	295	300003787	01.04.2008	24	01.04.2010
3	Amplifier - 0518C-138	Veritech Micro-wave Inc.	-/-	-/-	-/-	-/-	-/-
4	Switch - 3488A	HP		300000368	-/-	-/-	-/-
5	EMI Test receiver - ESCI	R&S	100083	300003312	31.01.2007	24	31.01.2009
6	Turntable Controller - 1061 3M	EMCO	1218	300000661	-/-	-/-	-/-
7	Tower Controller 1051 Controller	EMCO	1262	300000625	-/-	-/-	-/-
8	Tower - 1051	EMCO	1262	300000625	-/-	-/-	-/-
10	Ultra Notch-Filter Rejected band Ch. 62	WRCD	9	-/-	-/-	-/-	-/-