



Prepared (also subject responsible if other)

SEM/CVVGP, Leif Hedin

Approved

SEM/CVVGP, Leif Hedin

Checked

Company Internal
MARKING DRAWING
No.

1229-5132 Uen

Date

2010-03-19

Rev

1

Reference

2

M1a, Mobile Phone label content, Made in...

1 General information

Mobile Phone label part no	1233-9922
Mobile Phone label content part no	1229-5131
Bar code	Print quality: according to COSMETIC GUIDELINE – Bar code labels document 1222-6072 Uen Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

MLCI= Main Label Content Information Document

2 Printing information

Content	Format
Line 1a (11,0/4,0) Sony Ericsson stylized name.	Graphics, height 1,5 mm. According to 1200-1925.
Line 1b (11,0/18,0) Model Name “ M1a”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 2 (13,0/4,0) Product number without revision of the Sales Item in which the phone is packed, if applicable. “SI XXXX-XXXX”	Text, height 1,2 mm.
Line 3a (15,0/4,0) “TYPE: AAD-3880062-BV”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 3b (15,0/20,0) HW & SW identification field, if applicable; “FFGG”	Text, height 1,2 mm. According to Type-testing report under specifying document in product model.
Line 3c (15,0/26,0) Location code of where the phone is flashed, if applicable, “XXX”	Text, height 1,2 mm.
Line 4a (17,0/4,0) “FCC ID: PY7A3880062”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 4b (17,0/20,0) Production week (flash), “yy’W’ww” (yy = year, ww = week)	Text, height 1,2 mm.



Prepared (also subject responsible if other)

SEM/CVVGP, Leif Hedin

Approved

SEM/CVVGP, Leif Hedin

Checked

Company Internal
MARKING DRAWING
No.

1229-5132 Uen

Date

2010-03-19

Rev

1

Reference

2

Line 5a (19,0/4,0)	"IC: 4170B-A3880062"	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 5b (19,0/20,0)	Repair week, if applicable. "Ry'W'ww" (y = year, ww = week)	Text, height 1,2 mm.
Line 6 (21,5/5,0)	Line 7a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 7a (23,5/4,0)	Supplier's identification for trace-ability of the telephone, as desired by supplier (e.g. "S/N: nnn...." for serial number).	Text, height 1,2 mm. Defined by supplier.
Line 7b (23,5/17,0)	Actual electronic serial number (IMEI) of the Mobile Phone, "00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 8 (26,0/5,0)	Line 7b in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 9a (32,5/4,0)	CE approval symbol	Graphics, height 5 mm. According to 1210-0131.
Line 9b (32,5/13,0)	The notified body number "0682"	Text, height 1,2 mm.
Line 9c (32,5/17,0)	"Alert Symbol"	Graphics, height 5 mm According to 1001-5859
Line 9d (32,5/32,0)	WEEE trashcan without bar symbol	Graphics, min. height 5mm, according to 1202-5537.
Line 10 (35,5/4,0)	Marking of origin: "Xxx"= actual country of production of the included telephone, in English.	Text, height 1,2 mm.
Line 11 (53,0/4,0)	SIM-Card logotype	Graphics, height 5 mm. Acc to 1210-0475 Rotated 90 degrees counter -clockwise



Prepared (also subject responsible if other)

SEM/CVVGP, Leif Hedin

Approved

SEM/CVVGP, Leif Hedin

Checked

Company Internal
MARKING DRAWING
No.

1229-5132 Uen

Date

2010-03-19

Rev

1


Reference

2

3 Layout

The conceptual picture (for Zebra 90XIII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



double underlined = major changes since last revision.

Prepared (also subject responsible if other)

SEM/CVVGP, Leif Hedin

Approved

SEM/CVVGP, Leif Hedin

Checked

Company Internal
MARKING DRAWING
No.

1229-5132 Uen

Date

2010-03-19

Rev

1

Reference

16

Label placement

To find the label follow these steps:

1. Remove the cover on the rear side of the product.
2. Remove the battery.
3. The label is located behind the battery.

