



Prepared (also subject responsible if other)

SEM/CVVGP, Anna Englund

Approved

SEM/CVVGP, Anna Englund

Checked

Company Internal
MARKING DRAWING
No.

1237-0987 Uen

Date

2010-12-02

Rev

1

Reference

9

R800a, Mobile Phone label, a-version, made in...

1 General information

Mobile Phone label part no	1233-5697
Mobile Phone label content part no	1237-0986
Bar code	Print quality: according to COSMETIC GUIDELINE – Bar code labels document 1222-6072 Uen Quiet zone: No bar codes are allowed to be closer to a label edge than 4 mm!
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

MLCI= Main Label Content Information Document

2 Printing information

Content	Format
Line 1a (7,0/6,0)	Sony Ericsson stylized name. Graphics, height 1,5 mm. According to 1200-1925
Line 1b (7,0/24,0)	Model Name “R800a” Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 2a (14,0/6,0)	Product number of the Sales Item in which the phone is packed, if applicable. “SI XXXX-XXXX” Text, height 1,2 mm.
Line 2b (14,0/24,0)	Location code of where the phone is flashed, if applicable, “XXX” Text, height 1,2 mm.
Line 3a (18,0/6,0)	“TYPE: AAD-3880087-BV” Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 3b (18,0/24,0)	HW & SW identification field, if applicable; “FFGG” Text, height 1,2 mm. According to Type-testing report under Product Model Specifying Documents
Line 4a (20,0/6,0)	“FCC ID: PY7A3880087” Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 4b (20,0/24,0)	Production week (flash), “yy’W’ww” (yy = year, ww = week) Text, height 1,2 mm.
Line 5a (22,0/6,0)	“IC: 4170B-A3880087” Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
Line 5b (22,0/24,0)	Repair week, if applicable. “Ryy’W’ww” (yy = year, ww = week) Text, height 1,2 mm.
Line 6 (28,0/6,0)	Line 6 in bar code, according to line 7a. As desired by supplier (e.g. only actual number). Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).



Prepared (also subject responsible if other)

SEM/CVVGP, Anna Englund

Approved

SEM/CVVGP, Anna Englund

Checked

Company Internal
MARKING DRAWING
No.

1237-0987 Uen

Date

2010-12-02

Rev

1

Reference

9

Line 7a (30,0/6,0)	Supplier's identification for trace-ability of the telephone, as desired by supplier (e.g. "S/N: nnn...." for serial number).	Text, height 1,5 mm. Defined by supplier.
Line 7b (30,0/20,0)	Actual electronic serial number (IMEI) of the mobile phone, "00000000-000000-0"	Text, height 1,5mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 8 (33,06,0)	Line 8 in bar code, according to line 7b. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 9a (47,0/4,0)	CE approval symbol, the NB-"0682" and "Alert Symbol" in one artwork	Graphics, height 5 mm. According to 1242-7470
Line 9b (47,0/33,5)	WEEE trashcan without bar symbol	Graphics, min. height 5mm, according to 1202-5537.
Line 10 (54,0/9,0)	A circle shaped hole in the drawing, already made in the label material	Ø=5 mm
Line 11 (58,0/3,0)	Marking of origin; "Made in Xxx" "Xxx" = actual country of production of the included telephone, in English	Text, height 1,2 mm.

3 Layout

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



double underlined = major changes since last revision.