

Prepared (also subject responsible if other)

LD/SEM/GUG/NB Håkan Sjöberg +46 46 193559

Approved

Checked

LD/SEM/GUG/NMC Mats Hansson

Company Internal
STATEMENT

No.

GUG/N03:241 Uen

Date

Rev

Reference

2003-07-24

A

Receiver

Federal Communication Commission

Application PY7AAB-1021011**Statement on output power**

For the FCC SAR and EMC (Part 24) measurements of Sony Ericsson phone T610, FCC ID PY7AAB-1021011, we have used two units since the testing took place at two different test houses.

The conducted output power was measured on both units at the Sony Ericsson SAR laboratory before the EMC unit was sent to Cetecom Saarbrücken for the EMC measurements. This was made in order to ensure that the output power was the same on both units.

Below follows the results of the different measurements:

Measurement results; SAR laboratory, Sony Ericsson

Unit	Channel 512	Channel 661	Channel 810
A6101TUXTK (SAR)	29,29 dBm	29,23 dBm	29,26 dBm
004601-01-351592-0 (EMC)	29,37 dBm	29,31 dBm	29,27 dBm

Measurement results; Cetecom, Saarbrücken

Unit	Channel 512	Channel 661	Channel 810
004601-01-351592-0 (EMC)	29,7 dBm	29,4 dBm	29,5 dBm

Based on results presented above, the reason for the difference of 0,4 dBm between the SAR and EMC report is due to measurement uncertainties between different test houses / test equipments.

Best regards,

Mats Hansson
Technical Manager
EMF & Safety
Type Approval Department