

Prepared (also subject responsible if other)

GBBA/SEM/BMD/V David Godfrey/Jose A. Rodrigo

Approved

Checked

GBBA/SEM/BMD/P Danny Bravo

Limited Internal
MARKING DRAWING

No.

151 86-KRD 102 325/01 Uen

Date

Rev

Reference

2003-04-01

PA2

Approved according to 1776-KRD 102 325-1

Marking Drawing GC79 Type FAE-1021011-BV

Label

The label used for marking is defined in the Manufacturing Specification on the media used.

Placing

The label shall be placed on the back of the PC card according to the Assembly Drawing (151 88) for the KRD.

Print layout

Printing area 38 x 26 mm.

Lines:

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9



Line 10
Line 11
Line 12

Prepared (also subject responsible if other)

GBBA/SEM/BMD/V David Godfrey/Jose A. Rodrigo

Approved

GBBA/SEM/BMD/P Danny Bravo

Checked

**Limited Internal
MARKING DRAWING**

No.

151 86-KRD 102 325/01 Uen

Date

2003-04-01

Rev

PA2

Reference

Definitions

Line	1a	Sony Ericsson trademark
	1b	Production Week as bar code
	2a	Approval marks (1,2)
	2b	Production Week as characters
	3	Industry Canada marking and GHY ₁ Y ₂ Y ₃ fields and FCC approval marking
	4	IMEI number as bar code
	5	IMEI number as characters
	6	Serial number as bar-code
	7	Serial number as characters
	8	UPC number as bar code
	9	UPC number as characters
	10	
	10	Product number, R-state
	11	Type number
	12a	Marking of origin
	12b	Product Name "GC79"

Sony Ericsson trademark	Sony Ericsson and the Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347. Height min. 3 mm.
Approval marks	1. CE Marking. According to 1424 - SVF 930 52. 2. The Notified Body number. It shall be 0682. The print size (height) for the notified body number and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement.
Local approval marks	This field shall be used for local approval marks in countries where special marking is required.
IMEI number as bar code	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -). Height 3.5 mm.
IMEI number as characters	The IMEI number has format: TAC1-TAC2-SNR-CD TAC1 = First six digits of the Type Approval code after assignment

Prepared (also subject responsible if other)

GBBA/SEM/BMD/V David Godfrey/Jose A. Rodrigo

Approved

Checked

GBBA/SEM/BMD/P Danny Bravo

**Limited Internal
MARKING DRAWING**

No.

151 86-KRD 102 325/01 Uen

Date

Rev

Reference

2003-04-01

PA2

from the Notified Body.

TAC2 = Last two digits of the Type
Approval code after assignment
from the Notified Body.

SNR = A serial number from 000 000 to
999 999.

CD = A check digit, from 0-9, calculated
according to the Luhn formula
(ISO/IEC 7812), GSM 02.16.

Serial number as bar
code

According to Ericsson corporate standard
102 01 - 109. Height 3.5 mm.

Serial number as
characters

According to Ericsson group standard
0012-101.
Ericsson group factory number system
according the Ericsson corporate standard
1120-101 Factory codes:
Tecom (Taiwan) S48

UPC number as bar
code

According to AT&T PM-100-1-03. Height
3.5 mm.

UPC number as
characters

According to AT&T PM-100-1-03.

Type number

The type number is FAE-1021011-BV and
shall be printed "TYPE FAE-1021011-BV".

FCC approval marking

FCC approval marking: consists of the text:

FCC ID: PY7F1021011

Within a frame with height > 1.5 mm.

Industry Canada marking

Industry Canada approval marking:
consists of text:

IC: 4170B-F1021011

G-field

R-state identification of the CXC-module
loaded in KRD according to the Marking
data 1/151 86 for the KRD.

H-field

R-state identification of the hardware
version used during the current Type
Approval according to the Marking data



Prepared (also subject responsible if other)

GBBA/SEM/BMD/V David Godfrey/Jose A. Rodrigo

Approved

Checked

GBBA/SEM/BMD/P Danny Bravo

Limited Internal
MARKING DRAWING

No.

151 86-KRD 102 325/01 Uen

Date

Rev

Reference

2003-04-01

PA2

1/151 86 for the KRD.

Y₁-field

R-state identification of the current KRD according to the Marking data 1/151 86 for the KRD.

Y₂-field

ROA structure identification of the KRD according to the Marking data 1/151 86 for the KRD.

Y₃-field

R-state identification of the ROA of the KRD according to the Marking data 1/151 86 for the KRD.

Production week as bar code

According to Ericsson corporate standard 102 01 - 109. Height 3.5 mm

Production week

The production week shall be given as yyWww (yy = year, ww = week)

KRD number

The KRD number for the product.

R-state

The R-state for the KRD according to the 1095 for the KRD.

Marking of origin

Marking of origin and shall be printed "Made by Sony Ericsson".

Printing regulations

Fontface:

OCR-B

Type size:

min. 1.3 mm

Line spacing:

min. 0.3 mm

Trade mark height:

min. 3 mm

Approval marks height:

min. 5 mm

Colour:

Black

Prepared (also subject responsible if other)

GBBA/SEM/BMD/V David Godfrey/Jose A. Rodrigo

Approved

Checked

GBBA/SEM/BMD/P Danny Bravo

**Limited Internal
MARKING DRAWING**

No.

151 86-KRD 102 325/01 Uen

Date

Rev

Reference

2003-04-01

PA2

Print layout for prototypes

Line 7 and 8 are replaced with text "NOT TYPE APPROVED". Text height min. 2 mm. Under this text the following fields should be put:

- Production week, Product number, R-state. Text height min. 1.3 mm.
- Text "Made by Sony Ericsson". Text height min. 1.3 mm.

Line 2 is replaced with text with alternative shown below. Type size min. 5 mm.

DEMO
PROTOTYPE 2A
PROTOTYPE 2B
PROTOTYPE 2C
etc.

Line 4, the field shall be filled with the **test** IMEI number.

The test IMEI number is: **004601-01-** and the SNR are between **430000 ---> 431999**

(the CD numer must be added)

LINES

1

2

3

4

5

6

7

8

Sony Ericsson
XXXXXXXXXX

XXXXXX-XX-XXXXXX-X

XXXXXXXXXX
NOT TYPE APPROVED
yyWww KRD 102 325 RXX Made by Sony Ericsson