



Prepared (also subject responsible if other)

SEM/BGULD, Mats Hörlin

Approved

SEM/BGULDC (Hans-Olov Hallin)

Checked

Company Internal
MARKING DRAWING
No.

151 86-SVV 107 540/13 Uen

Date

Rev

Reference

2006-06-28

PA1

10

W958c, KRH-label, TYPE: FAB-102 2012-BV, Made in...

1 General information

The format of the label is based on a label SVF 930 863 (33,0 x 20,0 mm).

If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.

All bar codes, when applicable, are according to Ericsson corporate standard 102 01–109 Uen. All bar codes shall fulfil minimum print quality C according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen. No bar codes are allowed to be closer to a label edge than 2 mm! (quiet zone).

“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88-) for the KRH.

2 Printing information

	Content	Format
Line 1 (14,0/2,0)	Simcard symbol	Graphics, height 11 mm. According to 1424-SVF 930 1468/1.
Line 2a (18,0/2,0)	Sony Ericsson stylized name.	Graphics, height 2,0 mm. According to 190 89–EN/LZT 108 5347
Line 2b (18,0/15,0)	Model name, “W958c”	Text, height 1,2 mm.
Line 2c (18,0/20,5)	Country approval mark 2 “IC: 4170B-FB022012”	Text, height 1,2 mm.
Line 3a (20,0/2,0)	Type number of the phone (KRH), “Type: FAB-1022012-BV”.	Text, height 1,2 mm.
Line 3b (20,0/17,0)	ROA and R-state identification field, “G ₁ G ₂ G ₃ HY ₁ Y ₂ Y ₃ ”	Text, height 1,2 mm. “G”, “H” and “Y”-field According to the Type approval report 174 52-SVV 107 404/13. This document will be found in the 1095- for this SVV.
Line 3c (20,0/25,0)	Production week (flash), “yy’W’ww” (yy = year, ww = week)	Text, height 1,2 mm.
Line 3d (20,0/30,0)	Location code of where the phone is flashed, if applicable, “FFF”	Text, height 1,2 mm.



Prepared (also subject responsible if other)

SEM/BGULD, Mats Hörlin

Approved

SEM/BGULDC (Hans-Olov Hallin)

Checked

Company Internal
MARKING DRAWING
No.

151 86-SVV 107 540/13 Uen

Date

Rev

Reference

2006-06-28

PA1

10

Line 4 (23,0/2,0)	Line 4a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 5a (24,5/0/2,0)	Supplier's identification for traceability of the telephone, as desired by supplier (e.g. "S/N: nnn...." For serial number).	Text, height 1,2 mm. Defined by supplier.
Line 5b (24,5/15,0)	Country approval mark 1 "FCC ID: PY7FB022012"	Text, height 1,2 mm.
Line 6 (27,5/2,0)	Line 6a in bar code (only actual number, without data identifier).	Bar code, height 4,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 7a (29,5/2,0)	Actual electronic serial number (IMEI) of the phone (KRH), "00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from the 1301-FAD 109 0112/1 document in the 1095- for the SVV. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 7b (29,5/21,0)	Product number of the DPY kit in which the phone is packed. Printed without "DPY 101" and R-state, "0000/000"	Text, height 1,2 mm.
Line 7c (29,5/28,0)	Repair week, if applicable. "Ry'W'ww" (y = year, ww = week)	Text, height 1,2 mm.
Line 8 (33,0/12,0)	Marking of origin. The line shall be printed as stated in chapter 3 in this document.	Text, height 1,2 mm.
Line 9a (35,5/2,0)	CE approval symbol.	Graphics, height 5 mm. According to 1424-SVF 930 52.
Line 9b (35,5/8,0)	The Notified body number. "0682"	Text, height 2,5 mm.
Line 9c (35,0/12,5)	"CMII ID: 2006CJXXXX"	Text, height 1,5 mm. Paragraph of two rows aligned from bottom row.
Line 9d (35,5/12,0)	Frame around the text in Line 9c	Line
Line 10a (43,0/2,0)	CCC-sticker with S&E.	Graphics, height 6,3 mm, width 8,0 mm. According to 1424-SVF 930 2413.
Line 10b (43,0/12,0)	GSM/GPRS 移动电话机 “索尼爱立信移动通信 产品(中国)有限公司”	Text, height 2 mm.



Prepared (also subject responsible if other)

SEM/BGULD, Mats Hörlin

Approved

SEM/BGULDC (Hans-Olov Hallin)

Checked

Company Internal
MARKING DRAWING
No.

151 86-SVV 107 540/13 Uen

Date

Rev

Reference

2006-06-28

PA1

10

3 Marking of Origin

3.1 Content

“Made in Xxx” in Chinese Simplified;
“Xxx” = actual country of production of the included telephone

“Made in China” in Chinese Simplified: 1424-SVF 930 1350/1
“Made in Japan” in Chinese Simplified: 1424-SVF 930 1350/19
“Made in Malaysia” in Chinese Simplified: 1424-SVF 930 1350/27
“Made in France” in Chinese Simplified: 1424-SVF 930 1350/28

4 Layout

The conceptual picture (for Zebra 90Xill printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

4.1 Conceptual picture

