SAR TEST REPORT

No. 2013SAR00133

For

Sony Mobile Communications AB

GSM/UMTS/LTE mobile phone

Type number: PM-0590-BV

Marketing name: C6916

With

Hardware Version: AP2

Software Version: 14.1.F.0.158 (Main antenna)

s_atp_honami_us_1_30_5_9_b (WLAN antenna)

FCC ID: PY7PM-0590

Issued Date: 2014-02-18

DAkkS
Deutsche
Akkreditierungsstelle
D-PL-12123-01-01

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of MIIT

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2079, Fax:+86(0)10-62304633 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

Revision Version

Report Number	Revision	Date	Memo
2013SAR00133	00	2013-10-14	Initial creation of test report
2013SAR00133	01	2013-11-11	Retest a part of power and SAR for WLAN 5G
2013SAR00133	02	2014-02-18	Retest the SAR value for WLAN 5G from ch.149 to ch.165 with 10mm

TABLE OF CONTENT

1 TEST LABORATORY 5

1.1 TESTING LOCATION 5
1.2 TESTING ENVIRONMENT 5
1.3 PROJECT DATA 5
1.4 SIGNATURE 5

2 STATEMENT OF COMPLIANCE 6

3 CLIENT INFORMATION 8

3.1 APPLICANT INFORMATION 8
3.2 MANUFACTURER INFORMATION 8

4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 9

4.1 ABOUT EUT 9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 9
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 10

5 TEST METHODOLOGY 10

5.1 APPLICABLE LIMIT REGULATIONS 10
5.2 APPLICABLE MEASUREMENT STANDARDS 10

6 SPECIFIC ABSORPTION RATE (SAR) 11

6.1 INTRODUCTION 11
6.2 SAR DEFINITION 11

7 TISSUE SIMULATING LIQUIDS 12

7.1 TARGETS FOR TISSUE SIMULATING LIQUID 12
7.2 DIELECTRIC PERFORMANCE 13

8 SYSTEM VERIFICATION 20

8.1 SYSTEM SETUP 20
8.2 SYSTEM VERIFICATION 21

9 MEASUREMENT PROCEDURES 22

9.1 TESTS TO BE PERFORMED 22
9.2 GENERAL MEASUREMENT PROCEDURE 23
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR 24
9.4 SAR MEASUREMENT FOR LTE 25
9.5 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR 26
9.6 POWER DRIFT 27

10 AREA SCAN BASED 1-G SAR 27

10.1 REQUIREMENT OF KDB 27
10.2 FAST SAR ALGORITHMS 27

11 CONDUCTED OUTPUT POWER 28

11.1 MANUFACTURING TOLERANCE 28
11.2 HOTSPOT 34
11.3 GSM MEASUREMENT RESULT 40
11.4 WCDMA MEASUREMENT RESULT 42
11.5 LTE MEASUREMENT RESULT 43
11.6 WI-FI AND BT MEASUREMENT RESULT 47

12 SIMULTANEOUS TX SAR CONSIDERATIONS 50

12.1 INTRODUCTION 50
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES 50
12.3 SAR MEASUREMENT POSITIONS 50
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS 51

13 EVALUATION OF SIMULTANEOUS 52

14 SAR TEST RESULT 53

14.1 SAR RESULTS FOR FAST SAR 53
14.2 SAR RESULTS FOR STANDARD PROCEDURE 66

15 SAR MEASUREMENT VARIABILITY 72

16 MEASUREMENT UNCERTAINTY 73

17 MAIN TEST INSTRUMENTS 77

ANNEX A GRAPH RESULTS 78

ANNEX B SYSTEM VERIFICATION RESULTS 144

ANNEX C SAR MEASUREMENT SETUP 166

ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM 172

ANNEX E EQUIVALENT MEDIA RECIPES 175

ANNEX F SYSTEM VALIDATION 176

ANNEX G PROBE CALIBRATION CERTIFICATE 177

ANNEX H DIPOLE CALIBRATION CERTIFICATE 199

1 Test Laboratory

1.1 Testing Location

Company Name:	TMC Beijing, Telecommunication Metrology Center of MIIT
Address:	No 52, Huayuan beilu, Haidian District, Beijing,P.R.China
Postal Code:	100191
Telephone:	+86-10-62304633
Fax:	+86-10-62304793

1.2 Testing Environment

Temperature:	18°C~25 °C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg

1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	September 15, 2013
Testing End Date:	February 17, 2014

1.4 Signature

Lin Xiaojun

(Prepared this test report)



Qi Dianyuan

(Reviewed this test report)

Xiao Li

Deputy Director of the laboratory

(Approved this test report)

2 Statement of Compliance

The maximum results of SAR found during testing for Sony Mobile Communications (China) Co. Ltd GSM/UMTS/LTE mobile phone PM-0590-BV / C6916 are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g (W/Kg)	Equipment Class
Head (Separation Distance 0mm)	GSM 850	0.72	PCE
	PCS 1900	0.26	
	UMTS FDD 2	0.36	
	UMTS FDD 4	0.39	
	UMTS FDD 5	0.61	
	LTE Band 4	0.27	
	LTE Band 17	0.20	
	WLAN 2.4&5.8 GHz	0.69	DTS
	WLAN 5 GHz	0.66	UNII
Hotspot (Separation Distance 10mm)	GSM 850	0.41	PCE
	PCS 1900	0.48	
	UMTS FDD 2	0.60	
	UMTS FDD 4	0.63	
	UMTS FDD 5	0.31	
	LTE Band 4	0.54	
	LTE Band 17	0.30	
	WLAN 2.4&5.8 GHz	0.61	DTS
	WLAN 5 GHz	/	UNII
Body-worn (Data) (Separation Distance 15mm)	GSM 850	1.23	PCE
	PCS 1900	0.82	
	UMTS FDD 2	0.99	
	UMTS FDD 4	1.25	
	UMTS FDD 5	0.80	
	LTE Band 4	0.99	
	LTE Band 17	0.32	
	WLAN 2.4&5.8 GHz	0.45	DTS
	WLAN 5 GHz	0.52	UNII
Body-worn (Speech) (Separation Distance 15mm)	GSM 850	0.53	PCE
	PCS 1900	0.58	
	UMTS FDD 2	0.99	
	UMTS FDD 4	1.23	
	UMTS FDD 5	0.58	
	LTE Band 4	/	
	LTE Band 17	/	
	WLAN 2.4&5.8 GHz	/	DTS
	WLAN 5 GHz	/	UNII

Note1: With regard to WLAN-5G, It can't use with hotspot function from ch.36 to ch.140 and can use with hotspot function from ch.149 to ch.165. So according to the client request, the WLAN-5G is tested with 15mm from ch.36 to ch.140 and with 10mm from ch.149 to ch.165.

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1999.
For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm for hotspot on and 15mm for hotspot off and speech between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.
The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.
The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.
The highest reported SAR value is obtained at the case of **(Table 2.1),** and the values are**: 1.25 W/kg (1g).**

Table 2.2: The sum of reported SAR values for main antenna and WiFi

	Position	GSM/WCDMA	WiFi (DTS)	Sum1	WiFi (UNII)	Sum2
Maximum reported SAR value for Head	Left hand, Touch cheek	0.70	0.69	**1.39**	0.66	**1.36**
	Right hand, Touch cheek	0.72	0.20	**0.92**	0.20	**0.92**
Maximum reported SAR value for Body	Front 15mm	1.23	0.07	**1.30**	0.10	**1.33**
	Rear 15mm	1.07	0.45	**1.52**	0.52	**1.59**
	Bottom 15mm	1.25	/	**/**	/	**/**
	Front 10mm	0.63	0.15	**0.78**	/	**/**
	Rear 10mm	0.60	0.61	**1.21**	/	**/**

Note1: Sum1 is GSM/WCDMA + WiFi (DTS). Sum2 is GSM/WCDMA + WiFi (UNII).

Table 2.3: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.72	0.83	**1.55**
Highest reported SAR value for Body	Front 15mm	1.23	0.28	**1.51**

BT* - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **1.59 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

PBA of hotspot power back off is not required as FCC's response of KDB inquiry, and there is one Main antenna working for the transmission of 2G/3G/4G, and neither voice nor data of 2G/3G/4G can transmit simultaneously with each other. Another specific BT/WLAN antenna is working for all transmission modes of BT/WLAN and any transmission mode of BT/WLAN cannot work simultaneously with each other. Main antenna and BT/WLAN antenna can work at the same time.

3 Client Information

3.1 Applicant Information

Company Name:	Sony Mobile Communications AB
Address /Post:	Sony Mobile R&D Center, No. 16, Guangshun South Street, Chaoyang District
City:	Beijing
Postal Code:	100102
Country:	China
Contact Person:	Ma, Gang
Telephone:	+86-10-58656312
Fax:	+86-10-58659049

3.2 Manufacturer Information

Company Name:	Sony Mobile Communications AB
Address /Post:	Sony Mobile R&D Center, No. 16, Guangshun South Street, Chaoyang District
City:	Beijing
Postal Code:	100102
Country:	China
Contact Person:	Ma, Gang
Telephone:	+86-10-58656312
Fax:	+86-10-58659049

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	GSM/UMTS/LTE mobile phone
Type name:	PM-0590-BV
Marketing Name:	C6916
Operating mode(s):	GSM 850/900/1800/1900, WCDMA 850/900/1700/1900/2100 BT, Wi-Fi (2.4G&5G), LTE Band 4/17
Tested Tx Frequency:	825 – 848.8 MHz (GSM 850)
	1850.2 – 1910 MHz (GSM 1900)
	826.4–846.6 MHz (WCDMA850 Band V)
	1712.4 – 1752.6 MHz (WCDMA 1700 Band IV)
	1852.4–1907.6 MHz (WCDMA1900 Band II)
	1720 – 1745 MHz (LTE Band 4)
	709 – 711 MHz (LTE Band 17)
	2412 – 2462 MHz (Wi-Fi 2.4G)
	5180 – 5825 MHz (Wi-Fi 5G)
GPRS/EGPRS Multislot Class:	12
GPRS capability Class:	B
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Accessories/Body-worn configurations:	Headset
Hotspot mode:	Support simultaneous transmission of hotspot and voice(or data)
Form factor:	145.7 mm × 73.9 mm

4.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	SN	HW	SW Version	Tested Band
EUT1	004402451406460	CB5A1U82TJ	AP2	14.1.F.0.158	GSM
EUT2	004402451406700	CB5A1U82SL	AP2	14.1.F.0.158	GSM
EUT3	004402451406692	CB5A1U82TO	AP2	14.1.F.0.158	UMTS
EUT4	004402451406676	CB5A1U82T6	AP2	14.1.F.0.158	UMTS
EUT5	004402451406684	CB5A1U82SZ	AP2	14.1.F.0.158	LTE
EUT6	004402451406742	CB5A1U82SU	AP2	14.1.F.0.158	LTE
EUT7	004402451406395	CB5A1U82T3	AP2	14.1.F.0.158	Main antenna (AP ON)
EUT8	004402451406452	CB5A1U82T8	AP2	14.1.F.0.158	Main antenna (AP ON)
EUT9	004402451399665	CB5A1U21M5	AP2	s_atp_honami_us_1_30_5_9_b	WLAN
EUT10	004402451398089	CB5A1U21KK	AP2	s_atp_honami_us_1_30_5_9_b	WLAN
EUT11	004402451398089	CB5A1U21KK	AP2	s_atp_honami_us_1_30_5_9_b	WLAN

*EUT ID: is used to identify the test sample in the lab internally.

Note: There are different software version between the SAR sample and the WLAN sample. Because the SAR sample is controlled to work by Digital Radio Communication tester, the WLAN sample is controlled to work by the terminal software installed on the PC.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	1276-0526	/	Sony Electronics(Wuxi)Co.,Ltd
AE2	Headset	MH750c	/	Cotron

*AE ID: is used to identify the test sample in the lab internally.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

KDB447498 D01: General RF Exposure Guidance v05r01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r01: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v02: SAR Measurement Procedures for 3G Devices

KDB941225 D05 SAR for LTE Devices v02r02: SAR Evaluation Considerations for LTE Devices

KDB941225 D06 Hotspot Mode SAR v01r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227: SAR measurement procedures for 802.112abg transmitters

KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01: SAR Measurement Requirements for 100 MHz to 6 GHz

KDB 865664 D02 RF Exposure Reporting v01r01: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt}\left(\frac{dW}{dm}\right) = \frac{d}{dt}\left(\frac{dW}{\rho dv}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg)
SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific head capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid

Frequency(MHz)	Liquid Type	Conductivity(σ)	± 5% Range	Permittivity(ε)	± 5% Range
750	Head	0.89	0.85～0.93	41.94	39.8～44.0
750	Body	0.96	0.91～1.01	55.5	52.7～58.3
835	Head	0.90	0.86～0.95	41.5	39.4～43.6
835	Body	0.97	0.92～1.02	55.2	52.4～58.0
1750	Head	1.37	1.30～1.44	40.08	38.1～42.1
1750	Body	1.49	1.42～1.56	53.4	50.7～56.1
1900	Head	1.40	1.33～1.47	40.0	38.0～42.0
1900	Body	1.52	1.44～1.60	53.3	50.6～56.0
2450	Head	1.80	1.71～1.89	39.2	37.2～41.2
2450	Body	1.95	1.85～2.05	52.7	50.1～55.3
5200	Head	4.66	4.43～4.89	35.99	34.19～37.79
5200	Body	5.30	5.04～5.56	49.0	46.6～51.4
5300	Head	4.76	4.52～5.00	35.87	34.08～37.66
5300	Body	5.42	5.15～5.69	48.9	46.46～51.34
5600	Head	5.07	4.82～5.32	35.53	33.75～37.31
5600	Body	5.77	5.48～6.06	48.5	46.08～50.92
5800	Head	5.27	5.01～5.53	35.3	33.5～37.1
5800	Body	6.00	5.70～6.30	48.2	45.8～50.6

7.2 Dielectric Performance

Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ε	Drift (%)	Conductivity σ (S/m)	Drift (%)
2013-09-18	Head	750 MHz	43.12	2.81	0.918	3.15
	Body	750 MHz	56.35	1.53	0.974	1.46
2013-09-15	Head	835 MHz	40.87	-1.52	0.913	1.44
	Body	835 MHz	54.62	-1.05	0.983	1.34
2013-09-17	Head	1750 MHz	40.97	2.22	1.366	-0.29
	Body	1750 MHz	52.31	-2.04	1.516	1.74
2013-09-16	Head	1900 MHz	39.07	-2.33	1.424	1.71
	Body	1900 MHz	51.96	-2.51	1.509	-0.72
2013-09-28	Head	2450 MHz	38.41	-2.02	1.824	1.33
	Body	2450 MHz	53.28	1.10	1.973	1.18
2013-09-29	Head	5200 MHz	36.79	2.22	4.563	-2.08
	Body	5200 MHz	50.83	3.73	5.154	-2.75
2013-09-30	Head	5800 MHz	35.49	0.54	5.359	1.69
	Body	5800 MHz	49.52	2.74	6.114	1.90
2013-11-07	Head	5300 MHz	36.14	0.75	4.706	-0.38
	Body	5300 MHz	50.3	2.86	5.333	-1.61
2013-11-07	Head	5600 MHz	35.5	-0.08	5.108	0.75
	Body	5600 MHz	49.65	2.37	5.809	0.68
2013-11-07	Head	5800 MHz	35.06	-0.68	5.371	1.92
	Body	5800 MHz	49.21	2.10	6.138	2.30
2014-02-16	Body	5800 MHz	47.4	-1.66	6.142	2.37

Note: The liquid temperature is 22.0 ℃



Picture 7-1: Liquid depth in the Head Phantom (750 MHz)

Picture 7-2: Liquid depth in the Flat Phantom (750 MHz)



Picture 7-3: Liquid depth in the Head Phantom (835 MHz)



Picture 7-4: Liquid depth in the Flat Phantom (835 MHz)



Picture 7-5: Liquid depth in the Head Phantom (1750 MHz)



Picture 7-6 Liquid depth in the Flat Phantom (1750MHz)



Picture 7-7: Liquid depth in the Head Phantom (1900 MHz)



Picture 7-8 Liquid depth in the Flat Phantom (1900MHz)



Picture 7-9 Liquid depth in the Head Phantom (2450MHz)



Picture 7-10 Liquid depth in the Flat Phantom (2450MHz)



Picture 7-11 Liquid depth in the Head Phantom (5GHz)



Picture 7-12 Liquid depth in the Flat Phantom (5GHz)

8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2013-09-18	750 MHz	5.56	8.52	5.48	8.28	-1.44%	-2.82%
2013-09-15	835 MHz	6.16	9.44	6.24	9.56	1.30%	1.27%
2013-09-17	1750 MHz	19.6	36.9	19.84	37.24	1.22%	0.92%
2013-09-16	1900 MHz	21.3	40.4	20.56	38.72	-3.47%	-4.16%
2013-09-28	2450 MHz	24.9	53.4	24.28	51.60	-2.49%	-3.37%
2013-09-29	5200 MHz	22.8	79.7	23.50	82.00	3.07%	2.89%
2013-09-30	5800 MHz	22.2	78.2	21.50	75.30	-3.15%	-3.71%
2013-11-07	5300 MHz	23.5	82.1	23.20	81.40	-1.28%	-0.85%
2013-11-07	5600 MHz	23.5	82.8	23.90	84.70	1.70%	2.29%
2013-11-07	5800 MHz	22.2	78.2	21.60	77.60	-2.70%	-0.77%

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2013-09-18	750 MHz	5.75	8.75	5.80	8.88	0.87%	1.49%
2013-09-15	835 MHz	6.20	9.40	6.36	9.64	2.58%	2.55%
2013-09-17	1750 MHz	20.6	38.2	20.04	36.96	-2.72%	-3.25%
2013-09-16	1900 MHz	21.9	41.3	21.52	40.40	-1.74%	-2.18%
2013-09-28	2450 MHz	23.4	50.4	23.92	51.20	2.22%	1.59%
2013-09-29	5200 MHz	21.0	74.9	20.60	73.50	-1.90%	-1.87%
2013-09-30	5800 MHz	20.5	74.5	21.10	77.30	2.93%	3.76%
2013-11-07	5300 MHz	21.4	76.1	20.80	74.40	-2.80%	-2.23%
2013-11-07	5600 MHz	22.1	79.9	21.50	77.80	-2.71%	-2.63%
2013-11-07	5800 MHz	20.5	74.5	21.00	75.30	2.44%	1.07%
2014-02-17	5800 MHz	20.5	74.5	20.10	74.00	-1.95%	-0.67%

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.

Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
b) all configurations for each device position in a), e.g., antenna extended and retracted, and
c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., N_c > 3), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1 Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe

tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	½·δ·ln(2) ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the area scan based *1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other

physical channel configurations (DPCCH & $DPDCH_n$), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1}:47/15 β_{ed2}:47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	3.0	2.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.0	0.0	21	81

Rel.8 DC-HSDPA (Cat 24)

SAR test exclusion for Rel.8 DC-HSDPA must satisfy the SAR test exclusion requirements of Rel.5 HSDPA. SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion.

9.4 SAR Measurement for LTE

SAR tests for LTE are performed with a base station simulator, Rohde & Rchwarz CMW500. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the CMW 500.

It is performed for conducted power and SAR based on the KDB941225 D05.

SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation
   Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.
2) QPSK with 50% RB allocation
   The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.
3) QPSK with 100% RB allocation
   For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

9.5 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.
Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

In order to testing the conducted power of WLAN, the DUT is controlled to transmit WLAN TX as maximum power by the terminal software installed on the PC. The procedure how to control is presented as blew:
1. Connect DUT and PC via the USB cable and check the port is opened.
2. Input the command "WLPU" to power on WLAN.
3. Input the command "WTFD" to firmware download.
4. Input the WBTX command to start transmit (i.e., WBTX=1,0,1,1500,25,0,12).
5. Input the command "WIDL" to stop transmit.
6. Input the command "WLPD" to power off WLAN.

9.6 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 14.2 to Table 14.65 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

When WLAN Hotspot mode is activated (AP ON), in all operating modes, the conducted output power will be reduced except WLAN-5G. When WLAN Hotspot mode is deactivated (AP OFF), the RF output power level return to their normal RF power level.

11.1 Manufacturing tolerance

When the hotspot mode is ON:

Table 11.1: GPRS and EGPRS

GSM 850 GPRS (GMSK)				
Channel		**251**	**190**	**128**
1 Txslot	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
2 Txslots	Target (dBm)	25	25	25
	Tune-up (dBm)	26	26	26
3 Txslots	Target (dBm)	24	24	24
	Tune-up (dBm)	25	25	25
4 Txslots	Target (dBm)	23	23	23
	Tune-up (dBm)	24	24	24
GSM 850 EGPRS (GMSK)				
Channel		**251**	**190**	**128**
1 Txslot	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
2 Txslots	Target (dBm)	25	25	25
	Tune-up (dBm)	26	26	26
3 Txslots	Target (dBm)	24	24	24
	Tune-up (dBm)	25	25	25
4 Txslots	Target (dBm)	23	23	23
	Tune-up (dBm)	24	24	24
GSM 850 EGPRS (8PSK)				
Channel		**251**	**190**	**128**
1 Txslot	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
2 Txslots	Target (dBm)	25	25	25
	Tune-up (dBm)	26	26	26
3 Txslots	Target (dBm)	24	24	24
	Tune-up (dBm)	25	25	25
4 Txslots	Target (dBm)	23	23	23
	Tune-up (dBm)	24	24	24
GSM 1900 GPRS (GMSK)				
Channel		**810**	**661**	**512**
1 Txslot	Target (dBm)	25	25	25
	Tune-up (dBm)	26.5	26.5	26.5

2 Txslots	Target (dBm)	22	22	22
	Tune-up (dBm)	23	23	23
3 Txslots	Target (dBm)	21	21	21
	Tune-up (dBm)	22	22	22
4 Txslots	Target (dBm)	20	20	20
	Tune-up (dBm)	21	21	21
GSM 1900 EGPRS (GMSK)				
Channel		**810**	**661**	**512**
1 Txslot	Target (dBm)	25	25	25
	Tune-up (dBm)	26.5	26.5	26.5
2 Txslots	Target (dBm)	22	22	22
	Tune-up (dBm)	23	23	23
3 Txslots	Target (dBm)	21	21	21
	Tune-up (dBm)	22	22	22
4 Txslots	Target (dBm)	20	20	20
	Tune-up (dBm)	21	21	21
GSM 1900 EGPRS (8PSK)				
Channel		**810**	**661**	**512**
1 Txslot	Target (dBm)	25.5	25.5	25.5
	Tune-up (dBm)	26.5	26.5	26.5
2 Txslots	Target (dBm)	22	22	22
	Tune-up (dBm)	23	23	23
3 Txslots	Target (dBm)	21	21	21
	Tune-up (dBm)	22	22	22
4 Txslots	Target (dBm)	20	20	20
	Tune-up (dBm)	21	21	21

Table 11.2: WCDMA

WCDMA 850 CS			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	19	19	19
Tune-up (dBm)	20	20	20
WCDMA 1700 CS			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	19	19	19
Tune-up (dBm)	19.5	19.5	19.5
WCDMA 1900 CS			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	18	18	18
Tune-up (dBm)	19	19	19

Table 11.3: LTE

Mode	Target (dBm)	Tune-up (dBm)
LTE Band 4	18	19
LTE Band 17	21	22

Note: When the hotspot mode is ON, MPR settings doesn't work.

Table 11.4: WiFi

Mode	Target (dBm)	Tune-up (dBm)
802.11 b	15	16
802.11 g	15	16
802.11 n (2.4GHz HT20)	15	16

When the hotspot mode is OFF:

Table 11.5: GSM Speech

GSM 850			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	33	33	33
Tune-up (dBm)	34	34	34
GSM 1900			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	30	30	30
Tune-up (dBm)	31.5	31.5	31.5

Table 11.6: GPRS and EGPRS

GSM 850 GPRS (GMSK)				
Channel		**251**	**190**	**128**
1 Txslot	Target (dBm)	33	33	33
	Tune-up (dBm)	34	34	34
2 Txslots	Target (dBm)	31	31	31
	Tune-up (dBm)	32	32	32
3 Txslots	Target (dBm)	30	30	30
	Tune-up (dBm)	31	31	31
4 Txslots	Target (dBm)	29	29	29
	Tune-up (dBm)	30	30	30
GSM 850 EGPRS (GMSK)				
Channel		**251**	**190**	**128**
1 Txslot	Target (dBm)	33	33	33
	Tune-up (dBm)	34	34	34
2 Txslots	Target (dBm)	31	31	31
	Tune-up (dBm)	32	32	32
3 Txslots	Target (dBm)	30	30	30
	Tune-up (dBm)	31	31	31
4 Txslots	Target (dBm)	29	29	29
	Tune-up (dBm)	30	30	30

GSM 850 EGPRS (8PSK)				
Channel		**251**	**190**	**128**
1 Txslot	Target (dBm)	27	27	27
	Tune-up (dBm)	28	28	28
2 Txslots	Target (dBm)	25	25	25
	Tune-up (dBm)	26	26	26
3 Txslots	Target (dBm)	24	24	24
	Tune-up (dBm)	25	25	25
4 Txslots	Target (dBm)	23	23	23
	Tune-up (dBm)	24	24	24
GSM 1900 GPRS (GMSK)				
Channel		**810**	**661**	**512**
1 Txslot	Target (dBm)	30	30	30
	Tune-up (dBm)	31.5	31.5	31.5
2 Txslots	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
3 Txslots	Target (dBm)	27	27	27
	Tune-up (dBm)	28	28	28
4 Txslots	Target (dBm)	26	26	26
	Tune-up (dBm)	27	27	27
GSM 1900 EGPRS (GMSK)				
Channel		**810**	**661**	**512**
1 Txslot	Target (dBm)	30	30	30
	Tune-up (dBm)	31.5	31.5	31.5
2 Txslots	Target (dBm)	28	28	28
	Tune-up (dBm)	29	29	29
3 Txslots	Target (dBm)	27	27	27
	Tune-up (dBm)	28	28	28
4 Txslots	Target (dBm)	26	26	26
	Tune-up (dBm)	27	27	27
GSM 1900 EGPRS (8PSK)				
Channel		**810**	**661**	**512**
1 Txslot	Target (dBm)	26	26	26
	Tune-up (dBm)	27	27	27
2 Txslots	Target (dBm)	24	24	24
	Tune-up (dBm)	25	25	25
3 Txslots	Target (dBm)	23	23	23
	Tune-up (dBm)	24	24	24
4 Txslots	Target (dBm)	22	22	22
	Tune-up (dBm)	23	23	23

Table 11.7: WCDMA

WCDMA 850 CS			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	23.5	23.5	23.5
Tune-up (dBm)	24.5	24.5	24.5
HSUPA (sub-test 1/5)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	23.5	23.5	23.5
Tune-up (dBm)	24.5	24.5	24.5
HSUPA (sub-test 2/3/4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	22.5	22.5	22.5
Tune-up (dBm)	23.5	23.5	23.5
DC-HSDPA (sub-test 1-4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	22.5	22.5	22.5
Tune-up (dBm)	23.5	23.5	23.5
WCDMA 1700 CS			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	24.5	24.5	24.5
Tune-up (dBm)	25.0	25.0	25.0
HSUPA (sub-test 1/5)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	24.5	24.5	24.5
Tune-up (dBm)	25.0	25.0	25.0
HSUPA (sub-test 2/3/4)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	23.5	23.5	23.5
Tune-up (dBm)	24.0	24.0	24.0
DC-HSDPA (sub-test 1-4)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	23.5	23.5	23.5
Tune-up (dBm)	25.0	25.0	25.0
WCDMA 1900 CS			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	23.0	23.0	23.0
Tune-up (dBm)	24.0	24.0	24.0
HSUPA (sub-test 1/5)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	23.0	23.0	23.0
Tune-up (dBm)	24.0	24.0	24.0

HSUPA (sub-test 2/3/4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22.0	22.0	22.0
Tune-up (dBm)	23.0	23.0	23.0
DC-HSDPA (sub-test 1-4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22.0	22.0	22.0
Tune-up (dBm)	23.0	23.0	23.0

Table 11.8: LTE

Mode	Target (dBm)	Tune-up (dBm)
LTE Band 4	23.0	24.0
LTE Band 17	23.0	24.0

LTE MPR will follow up 3GPP setting as below:

Modulation	Channel bandwidth / Transmission bandwidth (NRB)						MPR (dB)
	1.4MHz	3.0MHz	5MHz	10MHz	15MHz	20MHz	
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	0
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Table 11.9: Bluetooth

Bluetooth			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6	6	6
Tune-up (dBm)	13	13	13

Table 11.10: WiFi

Band	Mode	Data Rates (Mbps)	Target (dBm)	Tune-up (dBm)
2.4G	11b	1-11	19	20
	11g	6-36	17	18
		48	16	17
		54	15	16
	11n	MCS0-MCS4	17.5	18.5
		MCS5-MCS6	15	16
		MCS7	14	15
5G (UNII Low Band)	11a	6-36	16.5	17
		48	16	17
		54	15	16
	11n/ac (20M&40M)	MCS0-MCS4	16.5	17
		MCS5-MCS6	15	16
		MCS7	14	15

	11ac (80M)	MCS0-MCS4	16.5	17
		MCS5-MCS6	15	16
		MCS7	14	15
		MCS8	13	14
		MCS9	12	13
5G (Other Bands)	11a	6-36	17	18
		48	16	17
		54	15	16
	11n/ac (20M)	MCS0-MCS4	17.5	18.5
		MCS5-MCS6	15	16
		MCS7	14	15
	11n/ac (40M)	MCS0-MCS4	17	18
		MCS5-MCS6	15	16
		MCS7	14	15
	11ac (80M)	MCS0-MCS4	17	18
		MCS5-MCS6	15	16
		MCS7	14	15
		MCS8	13	14
		MCS9	12	13

11.2 Hotspot

There is power reduction enabled for all operating modes except WLAN-5G. The power reduction is enabled when the user enables hotspot mode via the manufacturer software. The tables below show the measured powers with hotspot.

Table 11.11: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	**190**	**128**		**251**	**190**	**128**
1 Txslot	27.76	27.89	27.96	-9.03dB	18.73	18.86	18.93
2 Txslots	24.85	24.91	24.94	-6.02dB	18.83	18.89	18.92
3Txslots	23.66	23.77	23.88	-4.26dB	19.40	19.51	19.62
4 Txslots	22.56	22.59	22.72	-3.01dB	**19.55**	**19.58**	**19.71**
GSM 850 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	**190**	**128**		**251**	**190**	**128**
1 Txslot	27.66	27.82	27.88	-9.03dB	18.63	18.79	18.85
2 Txslots	24.78	24.85	24.88	-6.02dB	18.76	18.83	18.86
3Txslots	23.60	23.71	23.80	-4.26dB	19.34	19.45	19.54
4 Txslots	22.48	22.53	22.66	-3.01dB	**19.47**	**19.52**	**19.65**
GSM 850 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	**190**	**128**		**251**	**190**	**128**
1 Txslot	27.17	27.23	27.30	-9.03dB	18.14	18.20	18.27
2 Txslots	24.75	24.78	24.87	-6.02dB	18.73	18.76	18.85
3Txslots	23.53	23.59	23.73	-4.26dB	19.27	19.33	19.47
4 Txslots	22.36	22.41	22.51	-3.01dB	**19.35**	**19.40**	**19.50**

PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	**661**	**512**		**810**	**661**	**512**
1 Txslot	25.28	25.36	25.48	-9.03dB	16.25	16.33	16.45
2 Txslots	21.63	21.75	21.86	-6.02dB	15.61	15.73	15.84
3Txslots	20.50	20.71	20.76	-4.26dB	16.24	16.45	16.50
4 Txslots	19.81	19.91	19.98	-3.01dB	**16.80**	**16.90**	**16.97**
PCS1900 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	**661**	**512**		**810**	**661**	**512**
1 Txslot	25.25	25.33	25.45	-9.03dB	16.22	16.30	16.42
2 Txslots	21.64	21.73	21.83	-6.02dB	15.62	15.71	15.81
3Txslots	20.48	20.68	20.74	-4.26dB	16.22	16.42	16.48
4 Txslots	19.81	19.92	19.98	-3.01dB	**16.80**	**16.91**	**16.97**
PCS1900 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	**661**	**512**		**810**	**661**	**512**
1 Txslot	25.39	25.45	25.49	-9.03dB	16.36	16.42	16.46
2 Txslots	21.73	21.90	21.90	-6.02dB	15.71	15.88	15.88
3Txslots	20.58	20.73	20.78	-4.26dB	16.32	16.47	16.52
4 Txslots	19.77	19.85	19.94	-3.01dB	**16.76**	**16.84**	**16.93**

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 4Txslots for GPRS and EGPRS.

Note: According to the KDB941225 D03, "when SAR tests for EDGE or EGPRS mode is necessary, GMSK modulation should be used".

Table 11.12: The conducted Power for WCDMA

Item	**band**	**FDDV result**		
	ARFCN	**4233 (846.6MHz)**	**4182 (836.4MHz)**	**4132 (826.4MHz)**
WCDMA	****	18.11	18.35	18.23
Item	**band**	**FDDIV result**		
	ARFCN	**1513 (1752.6MHz)**	**1412 (1732.4MHz)**	**1312 (1712.4MHz)**
WCDMA	****	18.17	18.09	18.22
Item	**band**	**FDDII result**		
	ARFCN	**9538 (1907.6MHz)**	**9400 (1880MHz)**	**9262 (1852.4MHz)**
WCDMA	****	17.63	17.73	17.78

Table 11.13: The conducted Power for LTE

Band 4							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1754.3	19	17.99	0	17.98	0
		1732.5	19	18.00	0	18.00	0
		1710.7	19	17.98	0	17.95	0
	1RB Middle (3)	1754.3	19	18.00	0	17.96	0
		1732.5	19	17.98	0	17.99	0
		1710.7	19	18.00	0	17.93	0
	1RB Low (0)	1754.3	19	18.00	0	17.91	0
		1732.5	19	17.99	0	17.98	0
		1710.7	19	17.96	0	17.93	0
	3RB High (3)	1754.3	19	18.00	0	17.99	0
		1732.5	19	17.96	0	18.00	0
		1710.7	19	17.99	0	17.94	0
	3RB Middle (1)	1754.3	19	18.00	0	18.00	0
		1732.5	19	17.92	0	17.95	0
		1710.7	19	18.00	0	17.99	0
	3RB Low (0)	1754.3	19	17.96	0	17.98	0
		1732.5	19	18.00	0	17.96	0
		1710.7	19	17.98	0	17.99	0
	6RB (0)	1754.3	19	17.96	0	17.97	0
		1732.5	19	17.98	0	17.95	0
		1710.7	19	18.00	0	18.00	0
3 MHz	1RB High (14)	1753.5	19	17.97	0	18.00	0
		1732.5	19	18.00	0	17.87	0
		1711.5	19	17.98	0	17.95	0
	1RB Middle (7)	1753.5	19	18.00	0	17.95	0
		1732.5	19	17.98	0	17.90	0
		1711.5	19	17.95	0	17.94	0
	1RB Low (0)	1753.5	19	17.97	0	17.93	0
		1732.5	19	17.96	0	17.97	0
		1711.5	19	17.99	0	17.98	0
	8RB High (7)	1753.5	19	17.90	0	17.98	0
		1732.5	19	17.97	0	17.97	0
		1711.5	19	18.00	0	17.99	0
	8RB Middle (4)	1753.5	19	17.99	0	17.97	0
		1732.5	19	17.96	0	17.95	0
		1711.5	19	17.95	0	18.00	0

	8RB Low (0)	1753.5	19	17.96	0	17.95	0
		1732.5	19	17.94	0	17.98	0
		1711.5	19	17.98	0	18.00	0
	15RB (0)	1753.5	19	17.94	0	18.00	0
		1732.5	19	17.93	0	17.98	0
		1711.5	19	17.99	0	17.99	0
5 MHz	1RB High (24)	1752.5	19	17.95	0	18.00	0
		1732.5	19	18.00	0	17.99	0
		1712.5	19	17.94	0	18.00	0
	1RB Middle (12)	1752.5	19	17.97	0	17.96	0
		1732.5	19	18.00	0	17.97	0
		1712.5	19	17.94	0	18.00	0
	1RB Low (0)	1752.5	19	17.91	0	17.99	0
		1732.5	19	17.95	0	17.95	0
		1712.5	19	17.97	0	18.00	0
	12RB High (13)	1752.5	19	17.92	0	17.98	0
		1732.5	19	17.96	0	17.98	0
		1712.5	19	17.99	0	18.00	0
	12RB Middle (6)	1752.5	19	17.88	0	17.92	0
		1732.5	19	17.89	0	17.91	0
		1712.5	19	17.94	0	17.97	0
	12RB Low (0)	1752.5	19	17.91	0	17.94	0
		1732.5	19	17.98	0	17.98	0
		1712.5	19	17.97	0	18.00	0
	25RB (0)	1752.5	19	17.95	0	17.95	0
		1732.5	19	17.96	0	17.99	0
		1712.5	19	17.97	0	17.94	0
10 MHz	1RB High (49)	1750	19	17.95	0	17.95	0
		1732.5	19	17.98	0	18.00	0
		1715	19	17.93	0	17.99	0
	1RB Middle (24)	1750	19	17.97	0	17.97	0
		1732.5	19	17.91	0	18.00	0
		1715	19	17.99	0	17.97	0
	1RB Low (0)	1750	19	17.97	0	17.96	0
		1732.5	19	17.96	0	17.94	0
		1715	19	17.98	0	17.96	0
	25RB High (25)	1750	19	17.94	0	17.95	0
		1732.5	19	18.00	0	17.99	0
		1715	19	17.99	0	18.00	0
	25RB Middle (12)	1750	19	17.98	0	17.99	0
		1732.5	19	17.97	0	17.96	0
		1715	19	18.00	0	18.00	0

	25RB Low (0)	1750	19	17.99	0	17.98	0
		1732.5	19	17.94	0	17.98	0
		1715	19	17.97	0	18.00	0
	50RB (0)	1750	19	17.92	0	17.93	0
		1732.5	19	18.00	0	17.99	0
		1715	19	18.00	0	17.97	0
15 MHz	1RB High (74)	1747.5	19	17.93	0	17.99	0
		1732.5	19	17.92	0	17.97	0
		1717.5	19	18.00	0	17.93	0
	1RB Middle (37)	1747.5	19	17.98	0	17.97	0
		1732.5	19	17.97	0	17.96	0
		1717.5	19	17.99	0	17.93	0
	1RB Low (0)	1747.5	19	17.98	0	17.92	0
		1732.5	19	17.98	0	17.87	0
		1717.5	19	17.98	0	17.93	0
	36RB High (38)	1747.5	19	17.96	0	17.97	0
		1732.5	19	18.00	0	17.96	0
		1717.5	19	17.99	0	18.00	0
	36RB Middle (19)	1747.5	19	17.97	0	17.98	0
		1732.5	19	17.94	0	17.98	0
		1717.5	19	17.98	0	18.00	0
	36RB Low (0)	1747.5	19	17.94	0	17.96	0
		1732.5	19	17.98	0	17.99	0
		1717.5	19	17.98	0	17.97	0
	75RB (0)	1747.5	19	18.00	0	17.97	0
		1732.5	19	17.96	0	17.99	0
		1717.5	19	17.99	0	18.00	0
20 MHz	1RB High (99)	1745	19	17.97	0	17.92	0
		1732.5	19	17.99	0	17.93	0
		1720	19	17.99	0	17.92	0
	1RB Middle (50)	1745	19	17.97	0	17.88	0
		1732.5	19	17.97	0	17.91	0
		1720	19	17.99	0	17.93	0
	1RB Low (0)	1745	19	17.98	0	17.96	0
		1732.5	19	18.00	0	17.97	0
		1720	19	17.99	0	17.94	0
	50RB High (50)	1745	19	17.98	0	17.96	0
		1732.5	19	17.99	0	17.97	0
		1720	19	17.99	0	17.97	0
	50RB Middle (25)	1745	19	17.96	0	17.97	0
		1732.5	19	17.99	0	17.98	0
		1720	19	17.99	0	17.98	0

	50RB Low (0)	1745	19	17.98	0	17.96	0
		1732.5	19	17.99	0	17.98	0
		1720	19	18.00	0	17.99	0
	100RB (0)	1745	19	17.96	0	17.97	0
		1732.5	19	17.98	0	17.96	0
		1720	19	18.00	0	17.99	0
Band 17							
Bandwidth (MHz)	RB allocation RB offset (Start RB)	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
				Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	713.5	22	21.32	0	21.55	0
		710	22	21.46	0	21.66	0
		706.5	22	21.55	0	21.75	0
	1RB Middle (12)	713.5	22	21.34	0	21.60	0
		710	22	21.53	0	21.73	0
		706.5	22	21.50	0	21.71	0
	1RB Low (0)	713.5	22	21.45	0	21.64	0
		710	22	21.50	0	21.73	0
		706.5	22	21.48	0	21.58	0
	12RB High (13)	713.5	22	21.31	0	20.82	0
		710	22	21.42	0	20.86	0
		706.5	22	21.49	0	21.09	0
	12RB Middle (6)	713.5	22	21.31	0	20.83	0
		710	22	21.38	0	20.83	0
		706.5	22	21.53	0	21.03	0
	12RB Low (0)	713.5	22	21.31	0	20.89	0
		710	22	21.42	0	20.89	0
		706.5	22	21.44	0	20.94	0
	25RB (0)	713.5	22	21.29	0	20.77	0
		710	22	21.30	0	20.83	0
		706.5	22	21.33	0	20.85	0
10 MHz	1RB High (49)	711	22	21.18	0	21.82	0
		710	22	21.26	0	20.92	0
		709	22	21.36	0	21.18	0
	1RB Middle (24)	711	22	21.35	0	21.88	0
		710	22	21.48	0	21.07	0
		709	22	21.45	0	21.21	0
	1RB Low (0)	711	22	21.33	0	21.87	0
		710	22	21.34	0	21.01	0
		709	22	21.31	0	21.12	0
	25RB High (25)	711	22	21.28	0	20.71	0
		710	22	21.33	0	20.86	0
		709	22	21.30	0	20.81	0

	25RB Middle (12)	711	22	21.36	0	20.84	0
		710	22	21.26	0	20.80	0
		709	22	21.34	0	20.84	0
	25RB Low (0)	711	22	21.30	0	20.82	0
		710	22	21.39	0	20.86	0
		709	22	21.37	0	20.81	0
	50RB (0)	711	22	21.20	0	20.65	0
		710	22	21.23	0	20.68	0
		709	22	21.32	0	20.68	0

The average conducted power for Wi-Fi is as following:

802.11b（dBm）

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1	14.90	14.85	14.73	14.66
6	15.52	15.63	15.55	15.30
11	15.76	15.58	15.45	15.37

802.11g（dBm）

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	15.35	15.20	15.00	14.80	14.50	14.28	14.02	14.11
6	15.75	15.65	15.54	15.36	14.98	14.73	14.49	14.31
11	15.92	15.82	15.69	15.47	15.25	15.00	14.61	14.56

802.11n（dBm）- HT20 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	15.55	15.48	15.34	15.11	14.95	14.93	14.77	14.25
6	15.85	15.79	15.70	15.49	15.40	15.35	15.10	14.62
11	15.95	15.89	15.66	15.67	15.48	15.28	15.22	14.70

11.3 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.14: The conducted power measurement results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	33.40	33.33	33.26
GSM 1900MHz	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	30.86	30.95	30.99

Table 11.15: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	**190**	**128**		**251**	**190**	**128**
1 Txslot	33.44	33.36	33.30	-9.03dB	24.41	24.33	24.27
2 Txslots	30.72	30.82	30.85	-6.02dB	24.70	24.80	24.83
3Txslots	29.64	29.63	29.67	-4.26dB	25.38	**25.37**	25.41
4 Txslots	28.40	28.33	28.44	-3.01dB	**25.39**	25.32	**25.43**
GSM 850 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	**190**	**128**		**251**	**190**	**128**
1 Txslot	33.47	33.39	33.33	-9.03dB	24.44	24.36	24.30
2 Txslots	30.72	30.84	30.87	-6.02dB	24.70	24.82	24.85
3Txslots	29.63	29.62	29.67	-4.26dB	**25.37**	**25.36**	**25.41**
4 Txslots	28.35	28.30	28.41	-3.01dB	25.34	25.29	25.40
GSM 850 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	**190**	**128**		**251**	**190**	**128**
1 Txslot	27.37	27.34	27.38	-9.03dB	18.34	18.31	18.35
2 Txslots	24.96	24.95	25.03	-6.02dB	18.94	18.93	19.01
3Txslots	23.79	23.81	23.90	-4.26dB	19.53	19.55	19.64
4 Txslots	22.63	22.65	22.72	-3.01dB	**19.62**	**19.64**	**19.71**
PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	**661**	**512**		**810**	**661**	**512**
1 Txslot	30.91	30.99	31.02	-9.03dB	21.88	21.96	21.99
2 Txslots	27.91	28.00	28.02	-6.02dB	21.89	21.98	22.00
3Txslots	26.88	27.01	26.94	-4.26dB	22.62	22.75	22.68
4 Txslots	25.76	25.91	25.87	-3.01dB	**22.75**	**22.90**	**22.86**
PCS1900 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	**661**	**512**		**810**	**661**	**512**
1 Txslot	30.90	30.99	31.02	-9.03dB	21.87	21.96	21.99
2 Txslots	27.89	27.97	28.01	-6.02dB	21.87	21.95	21.99
3Txslots	26.88	27.00	26.92	-4.26dB	22.62	22.74	22.66
4 Txslots	25.76	25.92	25.87	-3.01dB	**22.75**	**22.91**	**22.86**
PCS1900 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	**661**	**512**		**810**	**661**	**512**
1 Txslot	26.07	26.19	26.19	-9.03dB	17.04	17.16	17.16
2 Txslots	24.06	24.17	24.15	-6.02dB	18.04	18.15	18.13
3Txslots	22.92	23.08	23.10	-4.26dB	18.66	18.82	18.84
4 Txslots	21.82	21.93	21.97	-3.01dB	**18.81**	**18.92**	**18.96**

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 3&4Txslots for GSM850 and 4Txslots for PCS1900.

Note: According to the KDB941225 D03, "when SAR tests for EDGE or EGPRS mode is necessary, GMSK modulation should be used".

11.4 WCDMA Measurement result

Table 11.16: The conducted Power for WCDMA

Item	band	FDDV result		
	ARFCN	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)
WCDMA	\	24.27	24.22	24.30
HSUPA	1	23.15	23.42	23.39
	2	22.01	22.26	22.26
	3	22.98	23.14	23.42
	4	22.39	22.68	22.60
	5	24.18	24.17	24.45
DC-HSDPA	1	23.45	23.39	23.43
	2	23.38	23.30	23.31
	3	23.37	23.32	23.39
	4	23.35	23.28	23.30
Item	band	FDDIV result		
	ARFCN	1513 (1752.6MHz)	1412 (1732.4MHz)	1312 (1712.4MHz)
WCDMA	\	24.36	24.36	24.49
HSUPA	1	23.03	23.42	23.25
	2	22.08	22.14	22.11
	3	22.96	23.64	22.96
	4	22.46	22.46	22.56
	5	24.52	24.57	24.51
DC-HSDPA	1	24.08	24.06	23.97
	2	24.07	24.02	23.92
	3	24.10	23.98	24.00
	4	24.06	23.92	23.93
Item	band	FDDII result		
	ARFCN	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)
WCDMA	\	23.74	23.76	23.80
HSUPA	1	23.58	22.95	23.00
	2	21.35	21.87	21.79
	3	22.63	22.52	22.49
	4	21.72	22.08	22.26
	5	23.77	23.74	23.86

DC-HSDPA	**1**	22.99	22.91	22.85
	2	22.96	22.84	22.81
	3	23.00	22.88	22.87
	4	22.94	22.85	22.80

Note: HSUPA&DC-HSDPA body SAR for WCDMA850/1700/1900 are not required, because maximum average output power of each RF channel with HSUPA&DC-HSDPA active is not 1/4 dB higher than that measured without HSUPA&DC-HSDPA.

11.5 LTE Measurement result

Table 11.17: The conducted Power for LTE

Band 4							
Bandwidth (MHz)	RB allocation RB offset (Start RB)	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
				Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1754.3	24	23.86	0	22.67	1
		1732.5	24	23.85	0	22.71	1
		1710.7	24	23.88	0	22.52	1
	1RB Middle (3)	1754.3	24	23.85	0	22.64	1
		1732.5	24	23.84	0	22.68	1
		1710.7	24	23.79	0	22.47	1
	1RB Low (0)	1754.3	24	23.82	0	22.56	1
		1732.5	24	23.92	0	22.78	1
		1710.7	24	23.95	0	22.55	1
	3RB High (3)	1754.3	24	23.80	0	22.71	1
		1732.5	24	23.77	0	22.71	1
		1710.7	24	23.86	0	22.74	1
	3RB Middle (1)	1754.3	24	23.77	0	22.77	1
		1732.5	24	23.83	0	22.89	1
		1710.7	24	23.92	0	22.80	1
	3RB Low (0)	1754.3	24	23.78	0	22.71	1
		1732.5	24	23.88	0	22.85	1
		1710.7	24	23.93	0	22.86	1
	6RB (0)	1754.3	24	22.75	1	21.80	2
		1732.5	24	22.97	1	21.94	2
		1710.7	24	22.91	1	21.92	2
3 MHz	1RB High (14)	1753.5	24	23.83	0	22.64	1
		1732.5	24	23.80	0	22.56	1
		1711.5	24	23.79	0	22.57	1
	1RB Middle (7)	1753.5	24	23.77	0	22.60	1
		1732.5	24	23.80	0	22.66	1
		1711.5	24	23.80	0	22.68	1

	1RB Low (0)	1753.5	24	23.75	0	22.53	1
		1732.5	24	23.91	0	22.73	1
		1711.5	24	23.97	0	22.74	1
	8RB High (7)	1753.5	24	22.75	1	21.66	2
		1732.5	24	22.72	1	21.74	2
		1711.5	24	22.79	1	21.74	2
	8RB Middle (4)	1753.5	24	22.66	1	21.66	2
		1732.5	24	22.86	1	21.84	2
		1711.5	24	22.72	1	21.76	2
	8RB Low (0)	1753.5	24	22.67	1	21.65	2
		1732.5	24	22.84	1	21.83	2
		1711.5	24	22.79	1	21.72	2
	15RB (0)	1753.5	24	22.68	1	21.75	2
		1732.5	24	22.85	1	21.93	2
		1711.5	24	22.77	1	21.82	2
5 MHz	1RB High (24)	1752.5	24	23.83	0	22.85	1
		1732.5	24	23.89	0	22.84	1
		1712.5	24	23.87	0	22.88	1
	1RB Middle (12)	1752.5	24	23.73	0	22.73	1
		1732.5	24	23.85	0	22.82	1
		1712.5	24	23.77	0	22.77	1
	1RB Low (0)	1752.5	24	23.87	0	22.84	1
		1732.5	24	23.94	0	22.96	1
		1712.5	24	23.99	0	22.93	1
	12RB High (13)	1752.5	24	22.66	1	21.76	2
		1732.5	24	22.74	1	21.80	2
		1712.5	24	22.67	1	21.73	2
	12RB Middle (6)	1752.5	24	22.64	1	21.74	2
		1732.5	24	22.90	1	21.90	2
		1712.5	24	22.69	1	21.73	2
	12RB Low (0)	1752.5	24	22.63	1	21.68	2
		1732.5	24	22.87	1	21.95	2
		1712.5	24	22.73	1	21.84	2
	25RB (0)	1752.5	24	22.62	1	21.63	2
		1732.5	24	22.81	1	21.80	2
		1712.5	24	22.56	1	21.67	2
10 MHz	1RB High (49)	1750	24	23.78	0	22.53	1
		1732.5	24	23.75	0	22.64	1
		1715	24	23.88	0	22.64	1
	1RB Middle (24)	1750	24	23.73	0	22.54	1
		1732.5	24	23.77	0	22.57	1
		1715	24	23.75	0	22.58	1

	1RB Low (0)	1750	24	23.69	0	22.54	1
		1732.5	24	23.78	0	22.62	1
		1715	24	23.91	0	22.74	1
	25RB High (25)	1750	24	22.60	1	21.66	2
		1732.5	24	22.77	1	21.71	2
		1715	24	22.74	1	21.82	2
	25RB Middle (12)	1750	24	22.54	1	21.59	2
		1732.5	24	22.84	1	21.83	2
		1715	24	22.70	1	21.74	2
	25RB Low (0)	1750	24	22.58	1	21.61	2
		1732.5	24	22.78	1	21.87	2
		1715	24	22.63	1	21.65	2
	50RB (0)	1750	24	22.53	1	21.54	2
		1732.5	24	22.67	1	21.68	2
		1715	24	22.59	1	21.61	2
15 MHz	1RB High (74)	1747.5	24	23.74	0	22.54	1
		1732.5	24	23.77	0	22.63	1
		1717.5	24	23.66	0	22.52	1
	1RB Middle (37)	1747.5	24	23.69	0	22.52	1
		1732.5	24	23.78	0	22.61	1
		1717.5	24	23.80	0	22.66	1
	1RB Low (0)	1747.5	24	23.78	0	22.60	1
		1732.5	24	23.67	0	22.52	1
		1717.5	24	23.77	0	22.64	1
	36RB High (38)	1747.5	24	22.38	1	21.70	2
		1732.5	24	22.50	1	21.80	2
		1717.5	24	22.40	1	21.79	2
	36RB Middle (19)	1747.5	24	22.41	1	21.81	2
		1732.5	24	22.58	1	21.90	2
		1717.5	24	22.37	1	21.95	2
	36RB Low (0)	1747.5	24	22.57	1	21.56	2
		1732.5	24	22.76	1	21.73	2
		1717.5	24	22.64	1	21.61	2
	75RB (0)	1747.5	24	22.44	1	21.37	2
		1732.5	24	22.53	1	21.46	2
		1717.5	24	22.53	1	21.44	2
20 MHz	1RB High (99)	1745	24	23.73	0	22.62	1
		1732.5	24	23.79	0	22.57	1
		1720	24	23.77	0	22.62	1
	1RB Middle (50)	1745	24	23.74	0	22.50	1
		1732.5	24	23.69	0	22.65	1
		1720	24	23.75	0	22.57	1

	1RB Low (0)	1745	24	23.69	0	22.53	1
		1732.5	24	23.74	0	22.59	1
		1720	24	23.74	0	22.65	1
	50RB High (50)	1745	24	22.55	1	21.46	2
		1732.5	24	22.64	1	21.61	2
		1720	24	22.69	1	21.59	2
	50RB Middle (25)	1745	24	22.57	1	21.57	2
		1732.5	24	22.74	1	21.72	2
		1720	24	22.49	1	21.55	2
	50RB Low (0)	1745	24	22.60	1	21.63	2
		1732.5	24	22.62	1	21.64	2
		1720	24	22.54	1	21.58	2
	100RB (0)	1745	24	22.59	1	21.61	2
		1732.5	24	22.67	1	21.66	2
		1720	24	22.54	1	21.55	2
Band 17							
Bandwidth (MHz)	RB allocation RB offset (Start RB)	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
				Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	713.5	24	23.71	0	22.48	1
		710	24	23.96	0	22.91	1
		706.5	24	23.95	0	22.91	1
	1RB Middle (12)	713.5	24	23.76	0	22.49	1
		710	24	23.86	0	22.87	1
		706.5	24	23.92	0	22.87	1
	1RB Low (0)	713.5	24	23.73	0	22.46	1
		710	24	23.89	0	22.84	1
		706.5	24	23.84	0	22.74	1
	12RB High (13)	713.5	24	22.72	1	21.79	2
		710	24	22.72	1	21.88	2
		706.5	24	22.78	1	21.91	2
	12RB Middle (6)	713.5	24	22.78	1	21.87	2
		710	24	22.76	1	21.90	2
		706.5	24	22.82	1	21.90	2
	12RB Low (0)	713.5	24	22.83	1	21.87	2
		710	24	22.82	1	21.89	2
		706.5	24	22.79	1	21.88	2
	25RB (0)	713.5	24	22.66	1	21.61	2
		710	24	22.77	1	21.76	2
		706.5	24	22.81	1	21.87	2

10 MHz	1RB High (49)	711	24	23.72	0	22.55	1
		710	24	23.72	0	22.60	1
		709	24	23.77	0	22.56	1
	1RB Middle (24)	711	24	23.81	0	22.56	1
		710	24	23.80	0	22.66	1
		709	24	23.87	0	22.76	1
	1RB Low (0)	711	24	23.83	0	22.64	1
		710	24	23.86	0	22.67	1
		709	24	23.79	0	22.59	1
	25RB High (25)	711	24	22.73	1	21.77	2
		710	24	22.79	1	21.82	2
		709	24	22.78	1	21.82	2
	25RB Middle (12)	711	24	22.83	1	21.87	2
		710	24	22.75	1	21.77	2
		709	24	22.69	1	21.83	2
	25RB Low (0)	711	24	22.73	1	21.82	2
		710	24	22.70	1	21.78	2
		709	24	22.72	1	21.82	2
	50RB (0)	711	24	22.66	1	21.67	2
		710	24	22.68	1	21.75	2
		709	24	22.70	1	21.71	2

11.6 Wi-Fi and BT Measurement result

The output power of BT antenna is as following:

Mode	Conducted Power (dBm)		
	Channel 0 (2402MHz)	Channel 39 (2441MHz)	Channel 78 (2480MHz)
GFSK	7.78	8.84	8.09
EDR2M-4_DQPSK	6.38	7.33	6.59
EDR3M-8DPSK	6.47	7.35	6.59

The average conducted power for Wi-Fi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1	19.04	18.94	18.85	18.63
6	19.50	19.45	19.42	19.17
11	19.72	19.66	19.74	19.45

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	17.14	17.02	16.87	16.69	16.65	16.58	15.80	14.70
6	17.66	17.50	17.39	17.17	16.97	16.66	15.54	14.63
11	17.77	17.65	17.55	17.33	17.12	16.83	15.62	14.61

802.11n (dBm) - HT20 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	17.92	17.76	17.66	17.49	17.32	14.72	14.60	13.99
6	18.25	18.11	18.01	17.85	17.65	15.08	15.03	14.46
11	18.33	18.15	18.03	17.90	17.73	15.30	15.20	14.59

802.11a (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
36(5180 MHz)	16.82	16.80	16.75	16.59	16.38	16.23	15.97	14.59
40(5200 MHz)	16.63	16.61	16.47	16.32	16.21	16.02	16.04	14.66
44(5220 MHz)	16.83	16.77	16.71	16.37	16.15	16.08	16.29	14.69
48(5240 MHz)	16.70	16.64	16.58	16.45	16.34	16.18	16.40	14.74
52(5260 MHz)	17.40	17.49	17.45	17.38	17.18	16.90	16.50	14.84
56(5280 MHz)	17.42	17.53	17.47	17.34	17.23	16.98	16.54	14.95
60(5300 MHz)	17.62	17.52	17.53	17.40	17.25	16.98	16.52	14.84
64(5320 MHz)	17.60	17.57	17.56	17.43	17.31	17.08	16.63	15.02
100(5500 MHz)	17.75	17.67	17.70	17.58	17.39	17.18	16.70	15.10
104(5520 MHz)	17.86	17.80	17.77	17.64	17.52	17.26	16.74	15.24
108(5540 MHz)	17.94	17.95	17.91	17.80	17.66	17.46	16.74	15.40
112(5560 MHz)	17.85	17.89	17.82	17.71	17.39	17.30	16.71	15.28
116(5580 MHz)	17.81	17.73	17.72	17.62	17.47	17.22	16.74	15.17
120(5600 MHz)	17.96	17.88	17.83	17.70	17.57	17.37	16.87	15.24
124(5620 MHz)	17.91	17.87	17.77	17.66	17.53	17.31	16.79	15.11
128(5640 MHz)	17.96	17.96	17.86	17.75	17.57	17.37	16.84	15.16
132(5660 MHz)	17.89	17.88	17.82	17.80	17.72	17.52	16.87	15.15
136(5680 MHz)	17.93	17.90	17.83	17.69	17.45	17.33	16.85	15.26
140(5700 MHz)	17.97	17.93	17.87	17.78	17.65	17.41	16.99	15.28
149(5745 MHz)	17.79	17.87	17.76	17.70	17.53	17.24	16.97	15.00
153(5765 MHz)	17.69	17.71	17.71	17.63	17.41	17.10	16.70	14.90
157(5785 MHz)	17.39	17.36	17.30	17.23	17.13	16.99	16.50	14.79
161(5805 MHz	17.27	17.41	17.45	17.41	17.04	16.80	16.47	14.74
165(5825 MHz)	17.28	17.20	17.15	17.04	16.93	16.78	16.34	14.62

802.11n/ac (dBm) - HT20 (5G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
36(5180 MHz)	16.87	16.77	16.58	16.45	16.31	14.66	14.57	13.64
40(5200 MHz)	16.76	16.55	16.44	16.29	16.05	14.75	14.64	13.87
44(5220 MHz)	16.88	16.77	16.62	16.39	16.21	14.90	14.81	14.05
48(5240 MHz)	16.78	16.71	16.63	16.36	16.18	14.94	14.83	14.07
52(5260 MHz)	17.88	17.81	17.76	17.64	17.41	15.05	14.98	14.17
56(5280 MHz)	18.08	17.97	17.78	17.80	17.56	15.20	15.10	14.12
60(5300 MHz)	18.12	17.94	17.87	17.79	17.55	15.08	15.08	14.24

64(5320 MHz)	18.10	18.07	17.97	17.84	17.61	15.19	15.19	14.23
100(5500 MHz)	18.34	18.21	18.09	17.96	17.71	15.15	15.07	14.36
104(5520 MHz)	18.34	18.23	18.11	17.98	17.77	15.12	14.97	14.34
108(5540 MHz)	18.29	18.27	18.11	17.96	17.62	15.27	15.13	14.33
112(5560 MHz)	18.31	18.09	17.99	17.88	17.63	15.26	15.16	14.23
116(5580 MHz)	18.28	18.14	18.05	17.91	17.67	15.19	15.23	14.39
120(5600 MHz)	18.16	17.99	17.89	17.76	17.66	15.27	15.19	14.29
124(5620 MHz)	18.32	18.19	18.11	17.89	17.68	15.09	15.20	14.22
128(5640 MHz)	18.41	18.26	18.11	17.99	17.77	15.37	15.23	14.35
132(5660 MHz)	18.40	18.27	18.25	18.07	17.85	15.33	15.38	14.52
136(5680 MHz)	18.43	18.35	18.29	18.19	17.90	15.41	15.29	14.67
140(5700 MHz)	18.45	18.31	18.18	18.06	17.84	15.35	15.15	14.51
149(5745 MHz)	17.90	17.62	17.81	17.70	17.44	14.91	14.82	14.40
153(5765 MHz)	17.76	17.81	17.75	17.58	17.37	14.90	14.77	14.25
157(5785 MHz)	17.69	17.59	17.51	17.31	17.28	14.79	14.71	13.96
161(5805 MHz	17.59	17.61	17.56	17.39	17.29	14.82	14.73	13.91
165(5825 MHz)	17.62	17.58	17.47	17.37	17.32	14.67	14.62	13.74

802.11n/ac (dBm) - HT40 (5G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
38(5190 MHz)	16.72	16.53	16.31	16.09	15.82	15.52	15.35	14.45
46(5230 MHz)	16.84	16.64	16.17	15.87	15.68	15.46	15.35	14.53
54(5270 MHz)	17.94	17.75	17.97	17.79	17.89	15.67	15.56	14.70
62(5310 MHz)	17.98	17.88	18.00	17.85	17.93	15.95	15.87	14.91
102(5510 MHz)	17.94	17.75	17.97	17.82	17.91	15.86	15.81	14.93
110(5550 MHz)	17.90	17.69	17.90	17.70	17.88	15.86	15.76	14.78
118(5590 MHz)	17.71	17.50	17.80	17.60	17.71	15.51	15.43	14.53
126(5630 MHz)	17.80	17.46	17.84	17.66	17.77	15.53	15.44	14.62
134(5670 MHz)	17.92	17.87	17.95	17.87	17.99	15.76	15.69	14.75
151(5755 MHz)	17.90	17.72	17.93	17.77	17.79	15.63	15.56	14.57
159(5795 MHz)	17.77	17.55	17.76	17.56	17.59	15.58	15.47	14.39

802.11ac (dBm) – HT80 (5G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
42(5210 MHz)	16.31	16.16	16.08	16.02	15.84	15.43	15.33	14.33	13.43	12.58
58(5290 MHz)	17.85	17.70	17.93	17.90	17.74	15.64	15.55	14.50	13.62	12.64
106(5530 MHz)	17.94	17.83	17.93	17.86	17.75	15.85	15.78	14.66	13.79	12.86
122(5610 MHz)	17.93	17.86	17.85	17.73	17.63	15.70	15.63	14.57	13.64	12.74
155(5775 MHz)	17.90	17.82	17.86	17.80	17.77	15.50	15.44	14.50	13.44	12.51

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.
For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Picture 12.1 Antenna Locations

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	No	Yes	Yes	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Appendix A

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Picture 12.2 Power Thresholds

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
			dBm	mW	
Bluetooth	2.441	19	8.84	7.66	Yes
WLAN 2.4GHz (AP ON)	2.45	19	15.95	39.36	No
WLAN 2.4GHz (AP OFF)	2.45	19	19.74	94.19	No
WLAN 5GHz	5.745	12	18.45	69.98	No

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WiFi

	Position	GSM/WCDMA	WiFi (DTS)	Sum1	WiFi (UNII)	Sum2
Maximum reported SAR value for Head	Left hand, Touch cheek	0.70	0.69	**1.39**	0.66	**1.36**
	Right hand, Touch cheek	0.72	0.20	**0.92**	0.20	**0.92**
Maximum reported SAR value for Body	Front 15mm	1.23	0.07	**1.30**	0.10	**1.33**
	Rear 15mm	1.07	0.45	**1.52**	0.52	**1.59**
	Bottom 15mm	1.25	/	**/**	/	**/**
	Front 10mm	0.63	0.15	**0.78**	/	**/**
	Rear 10mm	0.60	0.61	**1.21**	/	**/**

Note1: Sum1 is GSM/WCDMA + WiFi (DTS). Sum2 is GSM/WCDMA + WiFi (UNII).

Table 13.2: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.72	0.83	**1.55**
Highest reported SAR value for Body	Front 15mm	1.23	0.28	**1.51**

BT* - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Mode/Band	F (GHz)	Position	Distance (mm)	Upper limit of power *		Estimated$_{1g}$ (W/kg)
				dBm	mW	
Bluetooth	2.441	Head	5	13	19.95	0.83
Bluetooth	2.441	Body	15	13	19.95	0.28

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[√f(GHz)/x] W/kg for test separation distances ≤ 50 mm;
where x = 7.5 for 1-g SAR.
When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:
According to the above tables, the sum of reported SAR values is < 1.6W/kg. So the simultaneous transmission SAR with volume scans is not required.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom.
The distance is 10mm for AP ON and 15mm for AP OFF and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-g SAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or more than 1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{Target} - P_{Measured})/10}$$

Where P_{Target} is the power of manufacturing upper limit;
$P_{Measured}$ is the measured power in chapter 11.

Table 14.1: Duty Cycle

AP OFF	**Duty Cycle**
Speech for GSM850/1900	1:8.3
GPRS&EGPRS for GSM850/1900	1:2.67 or 1:2
WCDMA850/1700/1900&LTE&WiFi	1:1
AP ON	**Duty Cycle**
GPRS&EGPRS for GSM850/1900	1:2
WCDMA850/1700/1900&LTE&WiFi	1:1

14.1 SAR results for Fast SAR

Table 14.2: SAR Values (GSM 850 MHz Band - Head) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	Left	Touch	/	33.40	34.0	0.345	**0.40**	0.500	**0.57**	0.07
836.6	190	Left	Touch	/	33.33	34.0	0.379	**0.44**	0.550	**0.64**	-0.10
824.2	128	Left	Touch	/	33.26	34.0	0.460	**0.55**	0.592	**0.70**	-0.12
836.6	190	Left	Tilt	/	33.33	34.0	0.257	**0.30**	0.328	**0.38**	-0.06
848.8	251	Right	Touch	/	33.40	34.0	0.366	**0.42**	0.535	**0.61**	-0.15
836.6	190	Right	Touch	/	33.33	34.0	0.393	**0.46**	0.574	**0.67**	-0.19
824.2	128	Right	Touch	Fig.1	33.26	34.0	0.467	**0.55**	0.607	**0.72**	-0.06
836.6	190	Right	Tilt	/	33.33	34.0	0.257	**0.30**	0.329	**0.38**	0.09

Table 14.3: SAR Values (GSM 850 MHz Band - Body) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	GPRS (4)	Front	/	28.40	30.0	0.661	**0.96**	0.853	**1.23**	0.14
836.6	190	GPRS (3)	Front	Fig.2	29.63	31.0	0.645	**0.88**	0.858	**1.18**	-0.10
824.2	128	GPRS (4)	Front	/	28.44	30.0	0.559	**0.80**	0.741	**1.06**	0.04
836.6	190	GPRS (3)	Rear	/	29.63	31.0	0.597	**0.82**	0.775	**1.06**	-0.10
836.6	190	GPRS (3)	Left	/	29.63	31.0	0.242	**0.33**	0.331	**0.45**	0.06
836.6	190	GPRS (3)	Right	/	29.63	31.0	0.294	**0.40**	0.405	**0.56**	0.03
836.6	190	GPRS (3)	Bottom	/	29.63	31.0	0.095	**0.13**	0.135	**0.19**	0.06
836.6	190	EGPRS (3)	Front	/	29.62	31.0	0.640	**0.88**	0.851	**1.17**	0.05
836.6	190	Speech	Front Headset	/	33.33	34.0	0.352	**0.41**	0.452	**0.53**	-0.10

Note1: The distance between the EUT and the phantom bottom is 15mm. Note2: The type of Headset is MH750c.

Table 14.4: SAR Values (GSM 850 MHz Band - Body) – AP ON

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.6	190	GPRS (4)	Front	/	22.59	24.0	0.183	**0.25**	0.258	**0.36**	0.08
848.8	251	GPRS (4)	Rear	/	22.56	24.0	0.189	**0.26**	0.269	**0.37**	0.02
836.6	190	GPRS (4)	Rear	Fig.3	22.59	24.0	0.232	**0.32**	0.298	**0.41**	-0.03
824.2	128	GPRS (4)	Rear	/	22.72	24.0	0.189	**0.25**	0.268	**0.36**	-0.13
836.6	190	GPRS (4)	Left	/	22.59	24.0	0.117	**0.16**	0.181	**0.25**	0.07
836.6	190	GPRS (4)	Right	/	22.59	24.0	0.127	**0.18**	0.187	**0.26**	0.08
836.6	190	GPRS (4)	Bottom	/	22.59	24.0	0.043	**0.06**	0.065	**0.09**	-0.03
836.6	190	EGPRS (4)	Rear	/	22.53	24.0	0.225	**0.32**	0.292	**0.41**	-0.13

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.5: SAR Values (GSM 1900 MHz Band - Head) – AP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	Left	Touch	/	30.86	31.5	0.094	**0.11**	0.168	**0.19**	0.16
1880	661	Left	Touch	/	30.95	31.5	0.130	**0.15**	0.229	**0.26**	0.11
1850.2	512	Left	Touch	Fig.4	30.99	31.5	0.136	**0.15**	0.234	**0.26**	0.11
1880	661	Left	Tilt	/	30.95	31.5	0.062	**0.07**	0.114	**0.13**	0.17
1909.8	810	Right	Touch	/	30.86	31.5	0.063	**0.07**	0.109	**0.13**	0.15
1880	661	Right	Touch	/	30.95	31.5	0.066	**0.07**	0.116	**0.13**	0.13
1850.2	512	Right	Touch	/	30.99	31.5	0.082	**0.09**	0.132	**0.15**	0.18
1880	661	Right	Tilt	/	30.95	31.5	0.022	**0.02**	0.042	**0.05**	0.11

Table 14.6: SAR Values (GSM 1900 MHz Band - Body) – AP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	661	GPRS (4)	Front	/	25.91	27.0	0.268	**0.34**	0.448	**0.58**	-0.03
1909.8	810	GPRS (4)	Rear	Fig.5	25.76	27.0	0.356	**0.47**	0.613	**0.82**	-0.17
1880	661	GPRS (4)	Rear	/	25.91	27.0	0.344	**0.44**	0.587	**0.75**	0.09
1850.2	512	GPRS (4)	Rear	/	25.87	27.0	0.335	**0.43**	0.573	**0.74**	-0.01
1880	661	GPRS (4)	Left	/	25.91	27.0	0.059	**0.08**	0.090	**0.12**	0.11
1880	661	GPRS (4)	Right	/	25.91	27.0	0.067	**0.09**	0.111	**0.14**	0.09
1880	661	GPRS (4)	Bottom	/	25.91	27.0	0.276	**0.35**	0.464	**0.60**	0.13
1909.8	810	EGPRS (4)	Rear	/	25.76	27.0	0.353	**0.47**	0.613	**0.82**	0.12
1909.8	810	Speech	Rear Headset	/	30.86	31.5	0.292	**0.34**	0.503	**0.58**	0.10

Note1: The distance between the EUT and the phantom bottom is 15mm. Note2: The type of Headset is MH750c.

Table 14.7: SAR Values (GSM 1900 MHz Band - Body) – AP ON

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	661	GPRS (4)	Front	/	19.91	21.0	0.136	**0.17**	0.250	**0.32**	0.15
1909.8	810	GPRS (4)	Rear	Fig.6	19.81	21.0	0.199	**0.26**	0.368	**0.48**	0.02
1880	661	GPRS (4)	Rear	/	19.91	21.0	0.178	**0.23**	0.328	**0.42**	0.09
1850.2	512	GPRS (4)	Rear	/	19.98	21.0	0.175	**0.22**	0.320	**0.40**	0.12
1880	661	GPRS (4)	Left	/	19.91	21.0	0.025	**0.03**	0.042	**0.05**	0.10
1880	661	GPRS (4)	Right	/	19.91	21.0	0.032	**0.04**	0.051	**0.07**	0.03
1880	661	GPRS (4)	Bottom	/	19.91	21.0	0.167	**0.21**	0.318	**0.41**	-0.17
1909.8	810	EGPRS (4)	Rear	/	19.81	21.0	0.193	**0.25**	0.357	**0.47**	0.18

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.8: SAR Values (WCDMA 850 MHz Band - Head) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
846.6	4233	Left	Touch	/	24.27	24.5	0.383	**0.40**	0.558	**0.59**	0.17
836.4	4182	Left	Touch	Fig.7	24.22	24.5	0.444	**0.47**	0.575	**0.61**	-0.08
826.4	4132	Left	Touch	/	24.30	24.5	0.354	**0.37**	0.514	**0.54**	0.10
836.4	4182	Left	Tilt	/	24.22	24.5	0.270	**0.29**	0.349	**0.37**	0.06
846.6	4233	Right	Touch	/	24.27	24.5	0.376	**0.40**	0.547	**0.58**	0.13
836.4	4182	Right	Touch	/	24.22	24.5	0.433	**0.46**	0.561	**0.60**	-0.19
826.4	4132	Right	Touch	/	24.30	24.5	0.360	**0.38**	0.524	**0.55**	-0.16
836.4	4182	Right	Tilt	/	24.22	24.5	0.257	**0.27**	0.326	**0.35**	0.04

Table 14.9: SAR Values (WCDMA 850 MHz Band - Body) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.4	4182	Front	/	24.22	24.5	0.547	**0.58**	0.706	**0.75**	-0.00
846.6	4233	Rear	Fig.8	24.27	24.5	0.582	**0.61**	0.754	**0.80**	0.14
836.4	4182	Rear	/	24.22	24.5	0.580	**0.62**	0.751	**0.80**	-0.01
826.4	4132	Rear	/	24.30	24.5	0.565	**0.59**	0.727	**0.76**	0.02
836.4	4182	Left	/	24.22	24.5	0.193	**0.21**	0.264	**0.28**	-0.07
836.4	4182	Right	/	24.22	24.5	0.232	**0.25**	0.317	**0.34**	-0.06
836.4	4182	Bottom	/	24.22	24.5	0.067	**0.07**	0.094	**0.10**	-0.01
846.6	4233	Rear Headset	/	24.27	24.5	0.428	**0.45**	0.551	**0.58**	-0.09

Note1: The distance between the EUT and the phantom bottom is 15mm. Note2: The type of Headset is MH750c

Table 14.10: SAR Values (WCDMA 850 MHz Band - Body) – AP ON

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.4	4182	Front	/	18.35	20.0	0.126	**0.18**	0.179	**0.26**	0.08
846.6	4233	Rear	/	18.11	20.0	0.133	**0.21**	0.190	**0.29**	-0.06
836.4	4182	Rear	Fig.9	18.35	20.0	0.165	**0.24**	0.214	**0.31**	0.01
826.4	4132	Rear	/	18.23	20.0	0.140	**0.21**	0.199	**0.30**	0.05
836.4	4182	Left	/	18.35	20.0	0.084	**0.12**	0.124	**0.18**	-0.09
836.4	4182	Right	/	18.35	20.0	0.092	**0.13**	0.135	**0.20**	0.01
836.4	4182	Bottom	/	18.35	20.0	0.029	**0.04**	0.045	**0.07**	-0.14

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.11: SAR Values (WCDMA 1700 MHz Band - Head) – APP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1752.6	1513	Left	Touch	/	24.36	25.0	0.164	**0.19**	0.257	**0.30**	0.19
1732.4	1412	Left	Touch	/	24.36	25.0	0.125	**0.14**	0.210	**0.24**	0.12
1712.4	1312	Left	Touch	/	24.49	25.0	0.087	**0.10**	0.145	**0.16**	0.16
1732.4	1412	Left	Tilt	/	24.36	25.0	0.045	**0.05**	0.073	**0.08**	0.15
1752.6	1513	Right	Touch	Fig.10	24.36	25.0	0.202	**0.23**	0.335	**0.39**	0.05
1732.4	1412	Right	Touch	/	24.36	25.0	0.165	**0.19**	0.282	**0.33**	0.13
1712.4	1312	Right	Touch	/	24.49	25.0	0.128	**0.14**	0.220	**0.25**	0.13
1732.4	1412	Right	Tilt	/	24.36	25.0	0.038	**0.04**	0.063	**0.07**	0.11

Table 14.12: SAR Values (WCDMA 1700 MHz Band - Body) – AP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1752.6	1513	Front	/	24.36	25.0	0.584	**0.68**	0.976	**1.13**	-0.00
1732.4	1412	Front	/	24.36	25.0	0.490	**0.57**	0.825	**0.96**	-0.04
1712.4	1312	Front	/	24.49	25.0	0.443	**0.50**	0.760	**0.85**	-0.02
1752.6	1513	Rear	/	24.36	25.0	0.544	**0.63**	0.921	**1.07**	-0.02
1732.4	1412	Rear	/	24.36	25.0	0.534	**0.62**	0.908	**1.05**	-0.02
1712.4	1312	Rear	/	24.49	25.0	0.449	**0.50**	0.767	**0.86**	-0.01
1732.4	1412	Left	/	24.36	25.0	0.110	**0.13**	0.165	**0.19**	0.19
1732.4	1412	Right	/	24.36	25.0	0.108	**0.13**	0.163	**0.19**	0.18
1752.6	1513	Bottom	Fig.11	24.36	25.0	0.616	**0.71**	1.08	**1.25**	0.08
1732.4	1412	Bottom	/	24.36	25.0	0.517	**0.60**	0.912	**1.06**	0.03
1712.4	1312	Bottom	/	24.49	25.0	0.446	**0.50**	0.785	**0.88**	0.04
1752.6	1513	Bottom Headset	/	24.36	25.0	0.608	**0.70**	1.06	**1.23**	0.12
1732.4	1412	Bottom Headset	/	24.36	25.0	0.528	**0.61**	0.927	**1.07**	0.03
1712.4	1312	Bottom Headset	/	24.49	25.0	0.438	**0.49**	0.772	**0.87**	0.05

Note1: The distance between the EUT and the phantom bottom is 15mm. Note2: The type of Headset is MH750c

Table 14.13: SAR Values (WCDMA 1700 MHz Band - Body) – AP ON

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1752.6	1513	Front	Fig.12	18.17	19.5	0.251	**0.34**	0.464	**0.63**	0.06
1732.4	1412	Front	/	18.09	19.5	0.231	**0.32**	0.430	**0.59**	-0.05
1712.4	1312	Front	/	18.22	19.5	0.189	**0.25**	0.353	**0.47**	-0.14
1732.4	1412	Rear	/	18.09	19.5	0.219	**0.30**	0.398	**0.55**	0.10
1732.4	1412	Left	/	18.09	19.5	0.034	**0.05**	0.052	**0.07**	0.15
1732.4	1412	Right	/	18.09	19.5	0.041	**0.06**	0.062	**0.09**	0.14
1732.4	1412	Bottom	/	18.09	19.5	0.216	**0.30**	0.425	**0.59**	-0.05

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.14: SAR Values (WCDMA 1900 MHz Band - Head) – AP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1907.6	9538	Left	Touch	/	23.74	24.0	0.161	**0.17**	0.285	**0.30**	0.19
1880	9400	Left	Touch	Fig.13	23.76	24.0	0.210	**0.22**	0.343	**0.36**	-0.16
1852.4	9262	Left	Touch	/	23.80	24.0	0.185	**0.19**	0.316	**0.33**	0.15
1880	9400	Left	Tilt	/	23.76	24.0	0.079	**0.08**	0.136	**0.14**	0.14
1907.6	9538	Right	Touch	/	23.74	24.0	0.168	**0.18**	0.296	**0.31**	0.18
1880	9400	Right	Touch	/	23.76	24.0	0.162	**0.17**	0.280	**0.30**	-0.17
1852.4	9262	Right	Touch	/	23.80	24.0	0.204	**0.21**	0.329	**0.34**	0.16
1880	9400	Right	Tilt	/	23.76	24.0	0.036	**0.04**	0.065	**0.07**	0.16

Table 14.15: SAR Values (WCDMA 1900 MHz Band - Body) – AP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1880	9400	Front	/	23.76	24.0	0.401	**0.42**	0.677	**0.72**	-0.11
1907.6	9538	Rear	/	23.74	24.0	0.540	**0.57**	0.932	**0.99**	0.06
1880	9400	Rear	/	23.76	24.0	0.512	**0.54**	0.878	**0.93**	0.05
1852.4	9262	Rear	/	23.80	24.0	0.495	**0.52**	0.851	**0.89**	-0.03
1880	9400	Left	/	23.76	24.0	0.094	**0.10**	0.151	**0.16**	0.04
1880	9400	Right	/	23.76	24.0	0.110	**0.12**	0.172	**0.18**	0.11
1907.6	9538	Bottom	/	23.74	24.0	0.523	**0.56**	0.914	**0.97**	0.03
1880	9400	Bottom	/	23.76	24.0	0.533	**0.56**	0.931	**0.98**	0.01
1852.4	9262	Bottom	/	23.80	24.0	0.517	**0.54**	0.904	**0.95**	0.17
1907.6	9538	Bottom Headset	Fig.14	23.74	24.0	0.545	**0.58**	0.936	**0.99**	0.01
1880	9400	Bottom Headset	/	23.76	24.0	0.512	**0.54**	0.869	**0.92**	0.16
1852.4	9262	Bottom Headset	/	23.80	24.0	0.479	**0.50**	0.810	**0.85**	-0.05

Note1: The distance between the EUT and the phantom bottom is 15mm. Note2: The type of Headset is MH750c

Table 14.16: SAR Values (WCDMA 1900 MHz Band - Body) – AP ON

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1880	9400	Front	/	17.73	19.0	0.192	**0.26**	0.346	**0.46**	0.02
1907.6	9538	Rear	/	17.63	19.0	0.239	**0.33**	0.439	**0.60**	0.15
1880	9400	Rear	Fig.15	17.73	19.0	0.247	**0.33**	0.451	**0.60**	0.10
1852.4	9262	Rear	/	17.78	19.0	0.230	**0.30**	0.420	**0.56**	0.15
1880	9400	Left	/	17.73	19.0	0.039	**0.05**	0.063	**0.08**	0.18
1880	9400	Right	/	17.73	19.0	0.048	**0.06**	0.076	**0.10**	-0.06
1880	9400	Bottom	/	17.73	19.0	0.212	**0.28**	0.400	**0.54**	0.04

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.17: SAR Values (LTE Band4 - Head) – AP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1732.5	20175	1RB_High	Left	Touch	/	23.79	24.0	0.160	**0.17**	0.257	**0.27**	0.12
1732.5	20175	1RB_High	Left	Tilt	/	23.79	24.0	0.070	**0.07**	0.114	**0.12**	0.14
1732.5	20175	1RB_High	Right	Touch	Fig.16	23.79	24.0	0.166	**0.17**	0.258	**0.27**	0.10
1732.5	20175	1RB_High	Right	Tilt	/	23.79	24.0	0.121	**0.13**	0.189	**0.20**	0.12
1732.5	20175	50RB_Mid	Left	Touch	/	22.74	23.0	0.116	**0.12**	0.188	**0.20**	0.19
1732.5	20175	50RB_Mid	Left	Tilt	/	22.74	23.0	0.046	**0.05**	0.082	**0.09**	0.11
1732.5	20175	50RB_Mid	Right	Touch	/	22.74	23.0	0.121	**0.13**	0.189	**0.20**	0.12
1732.5	20175	50RB_Mid	Right	Tilt	/	22.74	23.0	0.031	**0.03**	0.052	**0.06**	0.12

Note1: The LTE mode is QPSK_20MHz.

Table 14.18: SAR Values (LTE Band4 - Body) – AP OFF

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1732.5	20175	1RB_High	Front	/	23.79	24.0	0.425	**0.45**	0.714	**0.75**	-0.01
1745	20300	1RB_High	Rear	/	23.73	24.0	0.441	**0.47**	0.728	**0.77**	-0.01
1732.5	20175	1RB_High	Rear	/	23.79	24.0	0.485	**0.51**	0.815	**0.86**	0.01
1720	20050	1RB_High	Rear	/	23.77	24.0	0.392	**0.41**	0.654	**0.69**	-0.07
1732.5	20175	1RB_High	Left	/	23.79	24.0	0.105	**0.11**	0.158	**0.17**	0.17
1732.5	20175	1RB_High	Right	/	23.79	24.0	0.114	**0.12**	0.174	**0.18**	-0.05
1745	20300	1RB_High	Bottom	Fig.17	23.73	24.0	0.522	**0.56**	0.928	**0.99**	0.06

1732.5	20175	1RB_High	Bottom	/	23.79	24.0	0.496	**0.52**	0.881	**0.92**	0.05
1720	20050	1RB_High	Bottom	/	23.77	24.0	0.449	**0.47**	0.798	**0.84**	0.08
1732.5	20175	50RB_Mid	Front	/	22.74	23.0	0.308	**0.33**	0.517	**0.55**	0.12
1732.5	20175	50RB_Mid	Rear	/	22.74	23.0	0.347	**0.37**	0.585	**0.62**	-0.03
1732.5	20175	50RB_Mid	Left	/	22.74	23.0	0.078	**0.08**	0.118	**0.13**	-0.15
1732.5	20175	50RB_Mid	Right	/	22.74	23.0	0.078	**0.08**	0.117	**0.12**	0.18
1732.5	20175	50RB_Mid	Bottom	/	22.74	23.0	0.368	**0.39**	0.653	**0.69**	0.01
1745	20300	100RB	Bottom	/	22.59	23.0	0.369	**0.41**	0.653	**0.72**	0.04

Note1: The distance between the EUT and the phantom bottom is 15mm.

Note2: The LTE mode is QPSK_20MHz.

Table 14.19: SAR Values (LTE Band4 - Body) – AP ON

Ambient Temperature: 22.7 °C Liquid Temperature: 22.2 °C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1732.5	20175	1RB_Low	Front	Fig.18	18.00	19.0	0.229	**0.29**	0.427	**0.54**	-0.15
1732.5	20175	1RB_Low	Rear	/	18.00	19.0	0.231	**0.29**	0.415	**0.52**	-0.03
1732.5	20175	1RB_Low	Left	/	18.00	19.0	0.037	**0.05**	0.058	**0.07**	-0.18
1732.5	20175	1RB_Low	Right	/	18.00	19.0	0.040	**0.05**	0.062	**0.08**	0.16
1732.5	20175	1RB_Low	Bottom	/	18.00	19.0	0.208	**0.26**	0.405	**0.51**	-0.17
1720	20050	50RB_Low	Front	/	18.00	19.0	0.204	**0.26**	0.375	**0.47**	0.03
1720	20050	50RB_Low	Rear	/	18.00	19.0	0.215	**0.27**	0.392	**0.49**	-0.15
1720	20050	50RB_Low	Left	/	18.00	19.0	0.031	**0.04**	0.050	**0.06**	0.11
1720	20050	50RB_Low	Right	/	18.00	19.0	0.035	**0.04**	0.054	**0.07**	0.10
1720	20050	50RB_Low	Bottom	/	18.00	19.0	0.198	**0.25**	0.393	**0.49**	0.11

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

Table 14.20: SAR Values (LTE Band17 - Head) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
709	23780	1RB_Mid	Left	Touch	Fig.19	23.87	24.0	0.159	**0.16**	0.195	**0.20**	-0.14
709	23780	1RB_Mid	Left	Tilt	/	23.87	24.0	0.087	**0.09**	0.105	**0.11**	-0.18
709	23780	1RB_Mid	Right	Touch	/	23.87	24.0	0.154	**0.16**	0.190	**0.20**	0.15
709	23780	1RB_Mid	Right	Tilt	/	23.87	24.0	0.084	**0.09**	0.102	**0.11**	-0.18
711	23800	25RB_Mid	Left	Touch	/	22.83	23.0	0.131	**0.14**	0.160	**0.17**	-0.17
711	23800	25RB_Mid	Left	Tilt	/	22.83	23.0	0.072	**0.07**	0.087	**0.09**	0.15
711	23800	25RB_Mid	Right	Touch	/	22.83	23.0	0.122	**0.13**	0.151	**0.16**	-0.11
711	23800	25RB_Mid	Right	Tilt	/	22.83	23.0	0.067	**0.07**	0.081	**0.08**	0.08

Note1: The LTE mode is QPSK_10MHz.

Table 14.21: SAR Values (LTE Band17 - Body) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
709	23780	1RB_Mid	Front	/	23.87	24.0	0.195	**0.20**	0.244	**0.25**	-0.01
709	23780	1RB_Mid	Rear	Fig.20	23.87	24.0	0.244	**0.25**	0.306	**0.32**	0.01
709	23780	1RB_Mid	Left	/	23.87	24.0	0.116	**0.12**	0.155	**0.16**	-0.12
709	23780	1RB_Mid	Right	/	23.87	24.0	0.088	**0.09**	0.117	**0.12**	-0.05
709	23780	1RB_Mid	Bottom	/	23.87	24.0	0.016	**0.02**	0.023	**0.02**	-0.04
711	23800	25RB_Mid	Front	/	22.83	24.0	0.157	**0.21**	0.196	**0.26**	0.07
711	23800	25RB_Mid	Rear	/	22.83	24.0	0.195	**0.26**	0.245	**0.32**	-0.01
711	23800	25RB_Mid	Left	/	22.83	24.0	0.093	**0.12**	0.124	**0.16**	0.03
711	23800	25RB_Mid	Right	/	22.83	24.0	0.070	**0.09**	0.093	**0.12**	-0.01
711	23800	25RB_Mid	Bottom	/	22.83	24.0	0.013	**0.02**	0.018	**0.02**	-0.19

Note1: The distance between the EUT and the phantom bottom is 15mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.22: SAR Values (LTE Band17 - Body) – AP ON

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
710	23790	1RB_Mid	Front	/	21.48	22.0	0.149	**0.17**	0.188	**0.21**	-0.10
710	23790	1RB_Mid	Rear	Fig.21	21.48	22.0	0.211	**0.24**	0.269	**0.30**	0.03
710	23790	1RB_Mid	Left	/	21.48	22.0	0.088	**0.10**	0.119	**0.13**	0.03
710	23790	1RB_Mid	Right	/	21.48	22.0	0.045	**0.05**	0.063	**0.07**	-0.07
710	23790	1RB_Mid	Bottom	/	21.48	22.0	0.015	**0.02**	0.027	**0.03**	-0.12
710	23790	25RB_Low	Front	/	21.39	22.0	0.141	**0.16**	0.180	**0.21**	0.03
710	23790	25RB_Low	Rear	/	21.39	22.0	0.195	**0.22**	0.246	**0.28**	-0.03
710	23790	25RB_Low	Left	/	21.39	22.0	0.079	**0.09**	0.109	**0.13**	-0.08
710	23790	25RB_Low	Right	/	21.39	22.0	0.043	**0.05**	0.060	**0.07**	-0.03
710	23790	25RB_Low	Bottom	/	21.39	22.0	0.014	**0.02**	0.026	**0.03**	-0.05

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.23: SAR Values (Wi-Fi 802.11b - Head) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2462	11	Left	Touch	/	19.72	20.0	0.236	**0.25**	0.485	**0.52**	-0.16
2437	6	Left	Touch	Fig.22	19.50	20.0	0.303	**0.34**	0.614	**0.69**	-0.17
2412	1	Left	Touch	/	19.04	20.0	0.251	**0.31**	0.531	**0.66**	0.13
2462	11	Left	Tilt	/	19.72	20.0	0.106	**0.11**	0.236	**0.25**	-0.17
2462	11	Right	Touch	/	19.72	20.0	0.096	**0.10**	0.187	**0.20**	0.09
2462	11	Right	Tilt	/	19.72	20.0	0.062	**0.07**	0.131	**0.14**	0.05

Table 14.24: SAR Values (Wi-Fi 802.11b - Body) – AP OFF

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2462	11	Front	/	19.72	20.0	0.032	**0.03**	0.061	**0.07**	0.18
2462	11	Rear	/	19.72	20.0	0.158	**0.17**	0.311	**0.33**	0.17
2437	6	Rear	/	19.50	20.0	0.101	**0.11**	0.238	**0.27**	0.11
2412	1	Rear	Fig.23	19.04	20.0	0.186	**0.23**	0.358	**0.45**	-0.05
2462	11	Right	/	19.72	20.0	0.084	**0.09**	0.187	**0.20**	-0.05
2462	11	Top	/	19.72	20.0	0.020	**0.02**	0.037	**0.04**	0.15

Note1: The distance between the EUT and the phantom bottom is 15mm.

Table 14.25: SAR Values (Wi-Fi 802.11b - Body) – AP ON

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2462	11	Front	/	15.76	16.0	0.011	**0.01**	0.040	**0.04**	0.14
2462	11	Rear	/	15.76	16.0	0.171	**0.18**	0.379	**0.40**	-0.16
2437	6	Rear	Fig.24	15.52	16.0	0.210	**0.23**	0.458	**0.51**	0.14
2412	1	Rear	/	14.90	16.0	0.165	**0.21**	0.384	**0.49**	-0.16
2462	11	Right	/	15.76	16.0	0.047	**0.05**	0.102	**0.11**	0.09
2462	11	Top	/	15.76	16.0	0.013	**0.01**	0.025	**0.03**	0.09

Note1: The distance between the EUT and the phantom bottom is 10mm.