**CETECOM™****CETECOM ICT Services**
consulting - testing - certification >>>

TEST REPORT

Test report no.: 1-6965/13-16-15-A

Deutsche
Akkreditierungsstelle
D-PL-12076-01-01

Testing laboratory

CETECOM ICT Services GmbH

Untertuerkheimer Strasse 6 – 10

66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <http://www.cetecom.com>e-mail: ict@cetecom.com**Accredited Testing Laboratory:**

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-01

Area of Testing:

Radio Communications & EMC (RCE)

Applicant

Sony Mobile Communications AB

Nya Vattentornet

22188 Lund / SWEDEN

Phone: +46 46 19 30 00

Fax: -/-

Contact: Mikael Nilsson

e-mail: Micke.nilsson@sonymobile.com

Phone: +46 7 03 22 75 03

Manufacturer

Sony Mobile Communications AB

Nya Vattentornet

22188 Lund / SWEDEN

Test standard/s

47 CFR Part 15

Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item:**Smart Phone GPRS/EGPRS 850/900/1800/1900; UMTS HSPA FDDI/III/V; LTE FDD1/3/17/18; LTE TDD41; CDMA 2K BC0/BC6; WLAN b/g/n/a/ac; BT 4.0; RFID; A-GPS PY7PM-0750****FCC ID:****PY7PM-0750****Frequency:**UNII band 5150 MHz to 5725 MHz
(lowest channel 36 – 5180 MHz; highest channel 140 – 5700 MHz)**Technology tested:**

WLAN (OFDM/a – mode; n/ac HT20 / HT40 – mode and ac HT80 – mode)

Antenna:

Integrated antenna

Power supply:

3.7V DC by Li - polymer battery

Temperature range:

-30°C to +60°C

This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorised:

cn=Christoph Schneider, o=CETECOM ICT
Services GmbH, ou=SND-120402,
email=christoph.schneider@cetecom.com,
c=DE
2014.03.31 07:32:02 +02'00'Christoph Schneider
Expert

Test performed:

cn=Andreas Luckenbill, o=CETECOM ICT
Services GmbH, ou=LUC-111202,
email=andreas.luckenbill@cetecom.com,
c=DE
2014.03.31 07:29:07 +02'00'Andreas Luckenbill
Expert

1 Table of contents

1	Table of contents	2
2	General information	3
2.1	Notes and disclaimer	3
2.2	Application details.....	3
3	Test standard/s	3
3.1	Measurement guidance.....	3
4	Test environment.....	4
5	Test item	4
5.1	Additional information	4
6	Test laboratories sub-contracted	4
7	Description of the test setup	5
7.1	Radiated measurements in a semi-anechoic chamber	5
7.2	Radiated measurements in a fully anechoic chamber	6
7.3	Radiated measurements 12.75 GHz to 40 GHz	7
7.4	AC conducted	8
7.5	Conducted measurements	9
8	Summary of measurement results	10
9	Additional comments	11
10	Measurement results	12
10.1	Identify worst case datarate.....	12
10.2	Gain	13
10.3	Duty cycle	14
10.4	Maximum output power conducted	17
10.5	Power spectral density	20
10.6	Spectrum bandwidth – 26 dB bandwidth	22
10.7	Peak excursion measurements	24
10.8	Band edge compliance radiated.....	26
10.9	TX spurious emissions radiated.....	34
10.10	RX spurious emissions radiated	73
10.11	Spurious emissions radiated < 30 MHz	78
10.12	Spurious emissions conducted < 30 MHz	82
11	Test equipment and ancillaries used for tests	85
12	Observations	89
Annex A	Document history	90
Annex B	Further information.....	90
Annex C	Accreditation Certificate	91

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

The testing service provided by CETECOM ICT Services GmbH has been rendered under the current "General Terms and Conditions for CETECOM ICT Services GmbH".

CETECOM ICT Services GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM ICT Services GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM ICT Services GmbH test report include or imply any product or service warranties from CETECOM ICT Services GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM ICT Services GmbH.

All rights and remedies regarding vendor's products and services for which CETECOM ICT Services GmbH has prepared this test report shall be provided by the party offering such products or services and not by CETECOM ICT Services GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order:	2014-02-19
Date of receipt of test item:	2014-03-14
Start of test:	2014-03-15
End of test:	2014-03-26
Person(s) present during the test:	-/-

3 Test standard/s

Test standard	Date	Test standard description
47 CFR Part 15		Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

3.1 Measurement guidance

UNII: KDB 789033	2013-04	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E
------------------	---------	--

4 Test environment

Temperature:	T_{nom}	+22 °C during room temperature tests
	T_{max}	+60 °C during high temperature tests
	T_{min}	-30 °C during low temperature tests
Relative humidity content:		42 %
Barometric pressure:		not relevant for this kind of testing
Power supply:	V_{nom}	3.7 V DC by Li - polymer battery
	V_{max}	4.4 V
	V_{min}	3.3 V

5 Test item

Kind of test item	:	Smart Phone GPRS/EGPRS 850/900/1800/1900; UMTS HSPA FDDI/III/V; LTE FDD1/3/17/18; LTE TDD41; CDMA 2K BC0/BC6; WLAN b/g/n/a/ac; BT 4.0; RFID; A-GPS
Type identification	:	PY7PM-0750
S/N serial number	:	Rad. CB5126D6YF Cond. CB5126DB1G
HW hardware status	:	AP1
SW software status	:	RF test software
Frequency band [MHz]	:	UNII band 5150 MHz to 5725 MHz (lowest channel 36 – 5180 MHz; highest channel 140 – 5700 MHz)
Type of radio transmission	:	OFDM
Use of frequency spectrum	:	
Type of modulation	:	BPSK, QPSK, 16 – QAM, 64 – QAM and 256 – QAM
Number of channels	:	19
Antenna	:	Integrated antenna
Power supply	:	3.7 V DC by Li - polymer battery
Temperature range	:	-30°C to +60°C

5.1 Additional information

Test setup- and EUT-photos are included in test report: 1-6965/13-16-01_AnnexA
 1-6965/13-16-01_AnnexB
 1-6965/13-16-01_AnnexD

All conducted measurements performed by CETECOM ICT Services GmbH, Saarbrücken.
 All radiated measurements performed by CETECOM GmbH, Essen.


6 Test laboratories sub-contracted

None


7 Description of the test setup


7.1 Radiated measurements in a semi-anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.




7.2 Radiated measurements in a fully anechoic chamber



7.3 Radiated measurements 12.75 GHz to 40 GHz**Equipment table:**

Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom
Std. Gain Horn Antenna 12.4 to 18.0 GHz	639	Narda	8402	300000787
Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda	8205	300002442
Microwave System Amplifier, 0.5-26.5 GHz	83017A	HP Meßtechnik	00419	300002268
Std. Gain Horn Antenna 26.5-40.0 GHz	V637	Narda	7911	300001751
Broadband Low Noise Amplifier 18-50 GHz	CBL18503070-XX	CERNEX	19338	300004273
Spectrum Analyzer 20 Hz - 50 GHz	FSU50	R&S	200012	300003443
Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517


7.4 AC conducted



Equipment table:

Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom
MXE EMI Receiver 20 Hz bis 26,5 GHz	N9038A	Agilent Technologies	MY51210197	300004405
Isolating Transformer	MPL IEC625 Bus Regeltrenntravo	Erft	91350	300001155
Switch / Control Unit	3488A	HP Meßtechnik	*	300000199
Switch / Control Unit	3488A	HP Meßtechnik	2719A15013	300001168
Artificial Mains 9 kHz to 30 MHz	ESH3-Z5	R&S	828576/020	300001210

7.5 Conducted measurements



Equipment table:

Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom
Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517

8 Summary of measurement results



No deviations from the technical specifications were ascertained



There were deviations from the technical specifications ascertained

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15	Passed	2014-03-31	-/-

Test specification clause	Test case	Temperature conditions	Power source voltages	Pass	Fail	NA	NP	Results (max.)
-/-	Output power verification (conducted)	Nominal	Nominal	☐	☐	☐	☐	No passed / fail criteria!
-/-	Gain	Nominal	Nominal	☐	☐	☐	☐	No passed / fail criteria!
U-NII Part 15	Duty cycle	Nominal	Nominal	☐	☐	☐	☐	No passed / fail criteria!
§15.407(a)	Maximum output power (conducted & radiated)	Nominal	Nominal	☒	☐	☐	☐	complies
§15.407(a)	Power spectral density	Nominal	Nominal	☒	☐	☐	☐	complies
§15.407(a)	Spectrum bandwidth 26dB bandwidth	Nominal	Nominal	☒	☐	☐	☐	complies
§15.407(a)	Peak excursion measurements	Nominal	Nominal	☒	☐	☐	☐	complies
§15.205	Band edge compliance radiated	Nominal	Nominal	☒	☐	☐	☐	complies
§15.407(b)	TX spurious emissions radiated	Nominal	Nominal	☒	☐	☐	☐	complies
§15.109	RX spurious emissions radiated	Nominal	Nominal	☒	☐	☐	☐	complies
§15.209(a)	Spurious emissions radiated < 30 MHz	Nominal	Nominal	☒	☐	☐	☐	complies
§15.107(a) §15.207	Spurious emissions conducted emissions < 30 MHz	Nominal	Nominal	☒	☐	☐	☐	complies

Note: NA = Not Applicable; NP = Not Performed

9 Additional comments

Reference documents: None

Special test descriptions: None

Configuration descriptions: None

Test mode: ☐ No test mode available.

☒ Special software is used.
EUT is transmitting pseudo random data by itself

10 Measurement results

10.1 Identify worst case datarate

Measurement:

All modes of the EUT will be measured with an average powermeter to identify the maximum transmission power on low, mid and high channel. In the case that only one or two channels are available, only these will be measured.

In further tests only the identified worst case modulation scheme or bandwidth will be measured. Additional the band edge compliance test will be performed in the lowest and highest modulation scheme.

Measurement parameters:

Average Power Meter

Results:

Modulation	Modulation scheme / bandwidth						
Frequency	5180 MHz	5240 MHz	5260 MHz	5320 MHz	5500 MHz	-/-	5700 MHz
OFDM / a – mode	6Mbit/s	6Mbit/s	6Mbit/s	6Mbit/s	6Mbit/s	-/-	6Mbit/s
OFDM / n/ac – mode HT20	MCS6	MCS6	MCS6	MCS6	MCS6	-/-	MCS7
Frequency	5190 MHz	5230 MHz	5270 MHz	5310 MHz	5510 MHz	-/-	5670 MHz
OFDM / n/ac – mode HT40	MCS7	MCS7	MCS3	MCS3	MCS8	-/-	MCS7
Frequency	5210 MHz		5290 MHz		5530 MHz		-/-
OFDM / ac – mode HT80	MCS0		MCS9		MCS0		-/-

10.2 Gain

Description:

Measurement of the maximum output power conducted and radiated

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	5s
Resolution bandwidth:	3 MHz
Video bandwidth:	8 MHz / 10 MHz
Span:	See complete signal!
Trace-Mode:	Max Hold

Limits:

Antenna Gain
Maximum 6 dBi

Result:

OFDM Band 5150 MHz to 5250 MHz Channel	Gain		
	Lowest 5180 MHz	-/-	Highest 5240 MHz
Gain (declared by manufacturer)	-1.6	-/-	-1.4
Measurement uncertainty	± 3 dB		

OFDM Band 5250 MHz to 5350 MHz Channel	Gain		
	Lowest 5260 MHz	-/-	Highest 5320 MHz
Gain (declared by manufacturer)	-1.4	-/-	-1.6
Measurement uncertainty	± 3 dB		

OFDM Band 5470 MHz to 5725 MHz Channel	Gain		
	Lowest 5500 MHz	Middle 5600 MHz	Highest 5700 MHz
Gain (declared by manufacturer)	-2.7	-2.2	-2.2
Measurement uncertainty	± 3 dB		

Result: Passed



10.3 Duty cycle



Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	10 MHz
Video bandwidth:	10 MHz
Span:	Zero
Trace-Mode:	Video trigger / view / single sweep

Results:**Duty cycle and correction factor:**

OFDM / a – mode:	96.47 % duty cycle	=>	0.16 dB
OFDM / n – mode HT20:	96.24 % duty cycle	=>	0.17 dB
OFDM / n – mode HT40:	92.62 % duty cycle	=>	0.33 dB
OFDM / ac – mode HT80:	84.73 % duty cycle	=>	0.72 dB

Plots:**Plot 1:** duty cycle of the transmitter – OFDM / a – mode**Plot 2:** duty cycle of the transmitter – OFDM / n – mode HT20

Plot 3: duty cycle of the transmitter – OFDM / n – mode HT40**Plot 4:** duty cycle of the transmitter – OFDM / ac – mode HT80

10.4 Maximum output power conducted

Description:

Measurement of the maximum output power conducted and radiated

Measurement:

Measurement parameter	
Detector:	RMS
Sweep time:	60s
Resolution bandwidth:	1 MHz
Video bandwidth:	≥ 3 MHz
Span:	> EBW
Trace-Mode:	Max hold
Analyzer function	Band power / channel power Interval > 26 dB EBW

Limits:

Radiated output power	Conducted output power
Conducted power + 6dBi antenna gain	The lesser one of 50mW or 4 dBm + 10 log Bandwidth 5.150-5.250 GHz 250mW or 11 dBm + 10 log Bandwidth 5.250-5.350 GHz 250mW or 11 dBm + 10 log Bandwidth 5.470-5.725 GHz 1W or 17 dBm + 10 log Bandwidth 5.725-5.825 GHz (where Bandwidth is the 26dB Bandwidth [MHz])

Result: OFDM / a – mode

OFDM / a – mode Channel	Maximum output power conducted [dBm]			
	Lowest 5180 MHz	Highest 5240 MHz	Lowest 5260 MHz	Highest 5320 MHz
duty cycle correction included	12.96	13.14	13.18	13.05
Channel	Lowest 5500 MHz	Middle 5600 MHz	Highest 5700 MHz	-/-
duty cycle correction included	13.67	13.17	13.29	-/-
Measurement uncertainty	± 1 dB			

Result: Passed**Result: OFDM / n/ac – mode HT20**

OFDM / n/ac – mode HT20 Channel	Maximum output power conducted [dBm]			
	Lowest 5180 MHz	Highest 5240 MHz	Lowest 5260 MHz	Highest 5320 MHz
duty cycle correction included	13.10	13.25	13.33	13.20
Channel	Lowest 5500 MHz	Middle 5600 MHz	Highest 5700 MHz	-/-
duty cycle correction included	13.85	13.41	13.47	-/-
Measurement uncertainty	± 1 dB			

Result: Passed

Result: OFDM / n/ac – mode HT40

OFDM / n/ac – mode HT40 Channel	Maximum output power conducted [dBm]			
	Lowest 5190 MHz	Highest 5230 MHz	Lowest 5270 MHz	Highest 5310 MHz
duty cycle correction included	10.64	9.94	10.58	9.36
Channel	Lowest 5510 MHz	Middle 5590 MHz	Highest 5670 MHz	-/-
duty cycle correction included	8.47	8.34	8.22	-/-
Measurement uncertainty	± 1 dB			

Result: Passed**Result: OFDM / ac – mode HT80**

OFDM / ac – mode HT80 Channel	Maximum output power conducted [dBm]			
	Lowest 5210 MHz	Highest 5290 MHz	Lowest 5530 MHz	-/-
duty cycle correction included	7.78	7.52	7.54	-/-
Measurement uncertainty	± 1 dB			

Result: Passed

10.5 Power spectral density

Description:

Measurement of the power spectral density of a digital modulated system. The measurement is repeated at the lowest, middle and highest channel.

Measurement:

Measurement parameter	
Detector:	RMS
Sweep time:	60 s / 120 s
Resolution bandwidth:	1 MHz
Video bandwidth:	≥ 3 MHz
Span:	> EBW
Trace-Mode:	Max hold

Limits:

Power Spectral Density
power spectral density conducted ≤ 4 dBm in any 1 MHz band (band 5150 – 5250 MHz)
power spectral density conducted ≤ 11 dBm in any 1 MHz band (band 5250 – 5350 MHz)
power spectral density conducted ≤ 11 dBm in any 1 MHz band (band 5470 – 5725 MHz)
power spectral density conducted ≤ 17 dBm in any 1 MHz band (band 5725 – 5825 MHz)

Result: OFDM / a – mode

OFDM / a – mode Channel	Power Spectral density [dBm/MHz]	
	Lowest 5180 MHz	Highest 5240 MHz
incl. duty cycle correction	0.9	1.0
Channel	Lowest 5260 MHz	Highest 5320 MHz
	0.9	1.1
Channel	Lowest 5500 MHz	Highest 5700 MHz
	1.4	1.2
Measurement uncertainty	± 1 dB	

Result: Passed

Result: OFDM / n – mode HT20

OFDM / n – mode HT20 Channel	Power Spectral density [dBm/MHz]	
	Lowest 5180 MHz	Highest 5240 MHz
incl. duty cycle correction	0.7	0.8
Channel	Lowest 5260 MHz	Highest 5320 MHz
	0.8	1.0
Channel	Lowest 5500 MHz	Highest 5700 MHz
	1.4	1.5
Measurement uncertainty	± 1 dB	

Result: Passed**Result: OFDM / n – mode HT40**

OFDM / n – mode HT40	Power Spectral density [dBm/MHz]				
	Channel	Lowest 5190 MHz	Highest 5230 MHz	Lowest 5270 MHz	Highest 5310 MHz
incl. duty cycle correction		-2.6	-5.4	-3.5	-5.8
Channel	Lowest 5510 MHz		Highest 5670 MHz		
incl. duty cycle correction	-6.8		-6.9		
Measurement uncertainty	± 1 dB				

Result: Passed**Result: OFDM / ac – mode HT80**

OFDM / ac – mode HT80 Channel	Power Spectral density [dBm/MHz]			
	Lowest 5210 MHz	Highest 5290 MHz	Lowest 5530 MHz	
incl. duty cycle correction	-8.1	-8.5	-8.2	
Measurement uncertainty	± 1 dB			

Result: Passed

10.6 Spectrum bandwidth – 26 dB bandwidth

Description:

Measurement of the 26 dB bandwidth of the modulated signal.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1% EBW
Video bandwidth:	≥ RBW
Span:	> complete signal!
Trace-Mode:	Max hold

Limits:

Spectrum Bandwidth – 26 dB Bandwidth
-/-

Result: OFDM / a – mode

OFDM / a – mode Channel	26 dB BANDWIDTH [MHz]	
	Lowest 5180 MHz	Highest 5240 MHz
	21.9	21.8
Channel	Lowest 5260 MHz	Highest 5320 MHz
	21.8	21.9
Channel	Lowest 5500 MHz	Highest 5700 MHz
	22.0	22.0
Measurement uncertainty	± 1 MHz	

Result: **Passed**

Result: OFDM / n/ac – mode HT20

OFDM / n/ac – mode Channel	26 dB BANDWIDTH [MHz]	
	Lowest 5180 MHz	Highest 5240 MHz
	22.1	22.2
Channel	Lowest 5260 MHz	Highest 5320 MHz
	22.2	22.2
Channel	Lowest 5500 MHz	Highest 5700 MHz
	22.2	22.0
Measurement uncertainty	± 1 MHz	

Result: Passed**Result: OFDM / n/ac – mode HT40**

OFDM / n/ac – mode HT40	26 dB BANDWIDTH [MHz]			
	Lowest 5190 MHz	Highest 5230 MHz	Lowest 5270 MHz	Highest 5310 MHz
Channel	40.1	39.8	40.0	39.8
Channel	Lowest 5510 MHz		Highest 5670 MHz	
	40.2		40.0	
Measurement uncertainty	± 1 MHz			

Result: Passed**Result: OFDM / ac – mode HT80**

OFDM / ac – mode HT80 Channel	26 dB BANDWIDTH [MHz]			
	Lowest 5210 MHz	Highest 5290 MHz	Lowest 5530 MHz	-/-
	82.1	82.1	81.9	
Measurement uncertainty	$\pm$ RBW			

Result: Passed

10.7 Peak excursion measurements

Description:

Peak to average value.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	60 s / 120 s
Resolution bandwidth:	1 MHz
Video bandwidth:	≥ 3 MHz
Span:	> Complete signal
Trace-Mode:	Max hold

Limits:

Peak excursion value
Does not exceed 13 dB.

Results:

Modulation OFDM / a – mode	Peak excursion value		
	Channel	5180 MHz	5240 MHz
RMS		0.9	1.0
Peak		9.43	9.63
Peak excursion value		8.53	8.63
Channel		5260 MHz	5320 MHz
RMS		0.9	1.1
Peak		9.41	9.58
Peak excursion value		8.51	8.58
Channel		5500 MHz	5700 MHz
RMS		1.4	1.2
Peak		10.02	10.01
Peak excursion value		8.62	8.81
Measurement uncertainty	± 1 dB		

Result: Passed

Results:

Modulation OFDM / n/ac – mode	Peak excursion value		
	5180 MHz		5240 MHz
Channel			
RMS	0.7		0.8
Peak	10.39		10.45
Peak excursion value	9.69		9.65
Channel	5260 MHz		5320 MHz
RMS	0.8		1.0
Peak	10.69		10.59
Peak excursion value	9.89		9.59
Channel	5500 MHz		5700 MHz
RMS	1.4		1.5
Peak	11.25		11.2
Peak excursion value	9.85		9.7
Measurement uncertainty	± 1 dB		

Result: Passed**Results:**

Modulation OFDM / n/ac – mode HT40	Peak excursion value		
	5190 MHz	5230 MHz	5270 MHz
Channel			
RMS	-2.6	-5.4	-3.5
Peak	2.9	3.17	3.45
Peak excursion value	5.50	8.57	6.95
Channel	5310 MHz	5510 MHz	5670 MHz
RMS	-5.8	-6.8	-6.9
Peak	3.46	3.15	2.89
Peak excursion value	9.26	9.95	9.79
Measurement uncertainty	± 1 dB		

Result: Passed**Results:**

Modulation OFDM / ac – mode HT80	Peak excursion value		
	5210 MHz	5290 MHz	5530 MHz
Channel			
RMS	-8.1	-8.5	-8.2
Peak	2.66	1.80	2.21
Peak excursion value	10.76	10.30	10.41
Measurement uncertainty	± 1 dB		

Result: Passed

10.8 Band edge compliance radiated

Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to the lowest channel for the lower restricted band and to the highest channel for the upper restricted band. Measurement distance is 3m.

Measurement:



Measurement parameter	
Detector:	Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	1 MHz
Video bandwidth:	10 Hz / 1 MHz
Span:	See plots!
Trace-Mode:	Max Hold



Limits:


Band Edge Compliance Radiated
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
74 dB μ V/m PEAK 54 dB μ V/m AVG



Result:



Scenario	Band Edge Compliance Radiated [dB μ V/m]
band edge	< 74 dB μ V/m (AVG) < 54 dB μ V/m (PEAK)
Measurement uncertainty	± 3 dB



Plots:
Plot 1: lower band edge, vertical & horizontal polarization (a mode), channel 36, 6Mbps

Plot 2: upper band edge, vertical & horizontal polarization (a mode), channel 64, 6Mbps



Plot 3: lower band edge, vertical & horizontal polarization (ac HT 20 mode), channel 52, MCS6

Plot 4: lower band edge, vertical & horizontal polarization (ac HT 20 mode), channel 100, MCS6


Plot 5: upper band edge, vertical & horizontal polarization (ac HT 20 mode), channel 140, MCS7

Plot 6: lower band edge, vertical & horizontal polarization (ac HT 40 mode), channel 38, MCS7

Plot 7: upper band edge, vertical & horizontal polarization (ac HT 40 mode), channel 62, MCS3


Plot 8: lower band edge, vertical & horizontal polarization (ac HT 40 mode), channel 102, MCS8

Plot 9: upper band edge, vertical & horizontal polarization (ac HT 40 mode), channel 134, MCS7


Plot 10: lower band edge, vertical & horizontal polarization (ac HT 80 mode), channel 42, MCS0

Plot 11: upper band edge, vertical & horizontal polarization (ac HT 80 mode), channel 58, MCS9


Plot 12: lower band edge, vertical & horizontal polarization (ac HT 80 mode), channel 106, MCS0**Result:** Passed

10.9 TX spurious emissions radiated

Description:

Measurement of the radiated spurious emissions in transmit mode. The measurement is performed at lowest, middle and highest channel.

Measurement:

Measurement parameter	
Detector:	Quasi Peak below 1 GHz (alternative Peak) Peak above 1 GHz / RMS
Sweep time:	Auto
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 1 MHz
Video bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: ≥ 3 MHz / 10 Hz
Span:	30 MHz to 40 GHz
Trace-Mode:	Max Hold / Average with 100 counts + 20 log (1 / X) for duty cycle lower than 100 %

Limits:

TX Spurious Emissions Radiated		
§15.209		
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10
Above 960	54.0	3
§15.407		
Outside the restricted bands!	-27 dBm / MHz	

Results: OFDM / a – mode

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM a – mode								
Lowest 5180 MHz			Middle 5200 MHz			Highest 5240 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM a – mode								
Lowest 5260 MHz			Middle 5280 MHz			Highest 5320 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM a – mode								
Lowest 5500 MHz			Middle 5600 MHz			Highest 5700 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM a – mode								
Lowest 5745 MHz			Middle 5765 MHz			Highest 5805 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

Result: Passed

Results: OFDM / n – modeHT20

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM n – mode HT20								
Lowest 5180 MHz			Middle 5200 MHz			Highest 5240 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM n – mode HT20								
Lowest 5260 MHz			Middle 5280 MHz			Highest 5320 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM n – mode HT20								
Lowest 5500 MHz			Middle 5600 MHz			Highest 5700 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM n – mode HT20								
Lowest 5745 MHz			Middle 5765 MHz			Highest 5805 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

Result: Passed

Results: OFDM / n – modeHT40

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM n – mode HT40								
Lowest 5190 MHz			Middle 5230 MHz			Highest 5270 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM n – mode HT40								
Lowest 5310 MHz			Middle 5510 MHz			Highest 5590 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					


TX Spurious Emissions Radiated [dBμV/m] / dBm								
OFDM n – mode HT40								
Lowest 5670 MHz			Middle 5765 MHz			Highest 5795 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
No peaks found.			No peaks found.			No peaks found.		
Measurement uncertainty			± 3 dB					

Result: Passed**Note:**

Plots are added to show the behaviour of the EUT.

Plots: OFDM / a – mode**Plot 1:** 30 MHz to 1 GHz, channel 36, 5180 MHz, 6Mbps, vertical & horizontal polarization


01_FCC15.209_hor+vert_kipp

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
857.010000	29.7	1000.0	120.000	217.0	V	0.0	0.0	26.2	16.30	46.00
914.080000	30.4	1000.0	120.000	157.0	V	16.0	90.0	27.3	15.60	46.00
963.030000	31.3	1000.0	120.000	192.0	H	247.0	90.0	27.5	22.70	54.00

Plot 2: 1 GHz to 7GHz, channel 36, 5180 MHz, 6Mbps, vertical & horizontal polarization

00431_SM1_KP1_W LAN_FCC15407

**Final Result 2**


Frequency (MHz)	RMS (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)
4748.500000	37.3	100.0	1000.000	155.0	V	85.0	90.0	4.7	16.7
5388.500000	40.3	100.0	1000.000	155.0	H	89.0	0.0	5.7	13.7

(continuation of the "Final Result 2" table from column 10 ...)

Frequency (MHz)	Limit (dB μ V/m)	Comment
4748.500000	54.0	
5388.500000	54.0	


Plot 3: 7 GHz to 18 GHz, channel 36, 5180 MHz, 6Mbps, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 4: 18 GHz to 40 GHz, channel 36, 5180 MHz, 6Mbps, vertical & horizontal polarization

EMI Scan_18_40GHz_Pre



Plot 5: 30 MHz to 1 GHz, channel 64, 5320 MHz, 6Mbps, vertical & horizontal polarization


01_FCC15.209_hor+vert_kipp

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
919.740000	30.2	1000.0	120.000	182.0	H	48.0	90.0	27.1	15.80	46.00
962.670000	31.3	1000.0	120.000	291.0	V	352.0	90.0	27.5	22.70	54.00
984.130000	32.1	1000.0	120.000	165.0	V	188.0	0.0	27.8	21.90	54.00


Plot 6: 1 GHz to 7 GHz, 5320 MHz, channel 64, 6Mbps, vertical & horizontal polarization

00431_Sweep1_SM1_KP1_W LAN_FCC15407




Plot 7: 7 GHz to 18 GHz, channel 64, 5320 MHz, 6Mbps, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 8: 18 GHz to 40 GHz, channel 64, 5320 MHz, 6Mbps, vertical & horizontal polarization

EMI Scan_18_40GHz_Pre




Plots: OFDM / ac – mode HT20

Plot 1: 1 GHz to 7 GHz, channel 52 ,5260 MHz, MCS6, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407 (b)(2)




Plot 2: 7 GHz to 18 GHz, channel 52 ,5260 MHz, MCS6, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 3: 1 GHz to 7 GHz, channel 100, 5500 MHz, MCS6, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407 (b)(3)




Plot 4: 7 GHz to 18 GHz, channel 100, 5500 MHz, MCS6, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 5: 30 MHz to 1 GHz, channel 140, 5700 MHz, MCS7, vertical & horizontal polarization

01_FCC15.209_hor+vert_kipp

**Final Result 1**


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
727.450000	27.9	1000.0	120.000	284.0	H	84.0	90.0	24.3	18.10	46.00
973.100000	31.5	1000.0	120.000	198.0	V	0.0	0.0	27.7	22.50	54.00
987.560000	32.3	1000.0	120.000	259.0	V	335.0	90.0	27.9	21.70	54.00

Plot 6: 1 GHz to 7 GHz, channel 140, 5700 MHz, MCS7, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407(b)(3)




Plot 7: 7 GHz to 18 GHz, channel 140, 5700 MHz, MCS7, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 8: 18 GHz to 40 GHz, channel 140, 5700 MHz, MCS7, vertical & horizontal polarization

EMI Scan_18_40GHz_Pre




Plots: OFDM / ac – mode HT40

Plot 1: 1 GHz to 7 GHz, channel 38, 5190 MHz, MCS7, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407(b)(1)




Plot 2: 7 GHz to 18 GHz, channel 38, 5190 MHz, MCS7, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 3: 30 MHz to 1 GHz, channel 62, 5310 MHz, MCS3, vertical & horizontal polarization

01_FCC15.209_hor+vert_kipp

**Final Result 1**


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
48.580000	15.7	1000.0	120.000	227.0	V	305.0	90.0	14.1	24.30	40.00
680.580000	25.7	1000.0	120.000	116.0	V	0.0	90.0	23.5	20.30	46.00
907.200000	30.3	1000.0	120.000	225.0	H	182.0	0.0	27.1	15.70	46.00

Plot 4: 1 GHz to 7 GHz, channel 62, 5310 MHz, MCS3, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407(b)(2)




Plot 5: 7 GHz to 18 GHz, channel 62, 5310 MHz, MCS3, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 6: 18 GHz to 26 GHz, channel 62, 5310 MHz, MCS3, vertical & horizontal polarization

EMI Scan_18_40GHz_Pre




Plot 7: 1 GHz to 7 GHz, channel 102, 5510 MHz, MCS8, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407(b)(3)




Plot 8: 7 GHz to 18 GHz, channel 102, 5510 MHz, MCS8, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15247




Plot 9: 1 GHz to 7 GHz, channel 134, 5670 MHz, MCS7, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407 (b)(3)




Plot 10: 7 GHz to 18 GHz, channel 134, 5670 MHz, MCS7, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15407




Plot 11: 18 GHz to 40 GHz, channel 134, 5670 MHz, MCS7, vertical & horizontal polarization

EMI Scan_18_40GHz_Pre




Plots: OFDM / ac – mode HT80

Plot 12: 1 GHz to 7 GHz, channel 42, 5210 MHz, MCS0, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407(b)(1)




Plot 13: 7 GHz to 18 GHz, channel 42, 5210 MHz, MCS0, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15407




Plot 14: 30 MHz to 1 GHz, channel 58, 5290 MHz, MCS9, vertical & horizontal polarization

01_FCC15.209_hor+vert_kipp

**Final Result 1**


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
82.490000	12.2	1000.0	120.000	133.0	V	209.0	90.0	8.2	27.80	40.00
95.200000	11.8	1000.0	120.000	117.0	V	96.0	0.0	8.8	31.70	43.50
99.910000	10.9	1000.0	120.000	105.0	V	146.0	90.0	8.6	32.60	43.50
104.220000	8.3	1000.0	120.000	235.0	V	84.0	90.0	8.5	35.20	43.50
106.880000	10.4	1000.0	120.000	144.0	V	135.0	90.0	8.5	33.10	43.50

Plot 15: 1 GHz to 7 GHz, channel 58, 5290 MHz, MCS9, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407(b)(2)




Plot 16: 7 GHz to 18 GHz, channel 58, 5290 MHz, MCS9, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15407




Plot 17: 18 GHz to 40 GHz, channel 58, 5290 MHz, MCS9, vertical & horizontal polarization

EMI Scan_18_40GHz_Pre




Plot 18: 1 GHz to 7 GHz, channel 106, 5530 MHz, MCS0, vertical & horizontal polarization
00431_Sweep1_SM1_KP1_W LAN_FCC15407 (b)(3)



Plot 19: 7 GHz to 18 GHz, channel 106, 5530 MHz, MCS0, vertical & horizontal polarization

Sweep2_SM1_KP1_W LAN_FCC15407



10.10 RX spurious emissions radiated

Description:

Measurement of the radiated spurious emissions in idle/receive mode.

Measurement:

Measurement parameter	
Detector:	Quasi Peak below 1 GHz (alternative Peak) Peak above 1 GHz / RMS
Sweep time:	Auto
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 1 MHz
Video bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: ≥ 3 MHz / 10 Hz
Span:	30 MHz to 40 GHz
Trace-Mode:	Max Hold / Average with 100 counts + 20 log (1 / X) for duty cycle lower than 100 %

Limits:

RX Spurious Emissions Radiated		
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10
Above 960	54.0	3

Results:


RX Spurious Emissions Radiated [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
No critical peaks found		
Measurement uncertainty	± 3 dB	

Result: Passed

Note: The limit was recalculated with 20 dB / decade (Part 15.31) for all radiated spurious emissions 30 MHz to 1 GHz from 3 meter limit to a 10 meter distance. (40dB/decade for emissions < 30MHz)

Plot 1: 30 MHz to 1 GHz, channel 56, vertical & horizontal polarization


05_FCC15.109_hor+vert_kipp

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
49.950000	22.1	1000.0	120.000	105.0	V	243.0	90.0	13.6	17.9	40.0
873.930000	30.2	1000.0	120.000	360.0	V	0.0	0.0	26.7	15.8	46.0
922.740000	30.3	1000.0	120.000	184.0	V	311.0	90.0	27.1	15.7	46.0

Plot 2: 30 MHz to 1 GHz, channel 116, vertical & horizontal polarization


05_FCC15.109_hor+vert_kipp

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
884.210000	30.0	1000.0	120.000	368.0	H	241.0	0.0	26.7	16.0	46.0
950.690000	31.2	1000.0	120.000	105.0	V	155.0	90.0	27.5	14.8	46.0

Plot 3: 1 GHz to 16 GHz, channel 56, vertical & horizontal polarization


030442_FCC_Part15.109_Unint_Rad_Class_B_1G-20G_ESU40

**Final Result 2**

Frequency (MHz)	RMS (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
3520.200000	39.4	100.0	1000.000	V	88.0	90.0	1.5	14.6	54.0
5280.200000	37.4	100.0	1000.000	V	92.0	90.0	6.6	16.6	54.0

Plot 4: 1 GHz to 16 GHz, channel 116, vertical & horizontal polarization


030442_FCC_Part15.109_Unint_Rad_Class_B_1G-20G_ESU40

**Final Result 2**

Frequency (MHz)	RMS (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Azimuth (deg)	Elevation (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
3520.200000	39.3	100.0	1000.000	V	92.0	90.0	1.5	14.7	54.0
5280.200000	37.4	100.0	1000.000	V	88.0	90.0	6.6	16.6	54.0

Plot 5: 18 GHz to 30 GHz, channel 116, vertical & horizontal polarization

EMI Scan_18_30GHz_RX-Mode-Pre



10.11 Spurious emissions radiated < 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode and receive mode below 30 MHz. The EUT is set first to middle channel. This measurement is representative for all channels and modes. If peaks are found the lowest channel and the highest channel will be measured too. Then the EUT is set to receive or idle mode. The limits are recalculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

Limits:



Spurious Emissions Radiated < 30 MHz		
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Results:


Spurious Emissions Radiated < 30 MHz [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
No peaks detected		
Measurement uncertainty	± 3 dB	

Result: Passed


Note: The limit was recalculated with 20 dB / decade (Part 15.31) for all radiated spurious emissions 30 MHz to 1 GHz from 3 meter limit to a 10 meter distance. (40dB/decade for emissions < 30MHz)

Plots:**Plot 1:** 9 kHz to 30 MHz, a-mode, channel 36, 6Mbps, TX mode**Plot 2:** 9 kHz to 30 MHz, a-mode, channel 64, 6Mbps, TX mode


Plot 3: 9 kHz to 30 MHz, ac-mode HT20, channel 140, MCS7, TX mode



Plot 4: 9 kHz to 30 MHz, ac-mode HT40, channel 62, MCS3, TX mode



Plot 5: 9 kHz to 30 MHz, ac-mode HT80, channel 58, MCS9, TX mode



10.12 Spurious emissions conducted < 30 MHz

Description:

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. The EUT is set to middle channel. If peaks are found the lowest channel and the highest channel will be measured too. Both power lines, phase and neutral line, are measured. Found peaks are remeasured with average and quasi peak detection to show compliance to the limits.

Measurement:

Measurement parameter	
Detector:	Peak - Quasi Peak / Average
Sweep time:	Auto
Video bandwidth:	F > 150 kHz: 9 kHz
Resolution bandwidth:	F > 150 kHz: 100 kHz
Span:	150 kHz to 30 MHz
Trace-Mode:	Max Hold

Limits:



Spurious Emissions Conducted < 30 MHz		
Frequency (MHz)	Quasi-Peak (dB μ V/m)	Average (dB μ V/m)
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30.0	60	50

*Decreases with the logarithm of the frequency


Results:

Spurious Emissions Conducted < 30 MHz [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
No peaks found		
Measurement uncertainty	± 3 dB	


Result: Passed

Plots:**Plot 1:** 150 kHz to 30 MHz / phase Line, TX mode**Plot 2:** 150 kHz to 30 MHz / neutral Line, TX mode

Plot 3: 150 kHz to 30 MHz / phase Line, RX mode



Plot 4: 150 kHz to 30 MHz / neutral Line, RX mode



11 Test equipment and ancillaries used for tests

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Equipment from Cetecom ICT Services GmbH

No.	Lab / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	21.01.2014	21.01.2015
2	n. a.	Power Supply 0-20V, 0-5A	6632B	Agilent Technologies	GB42110541	400000562	vKI!	10.01.2013	10.01.2016
3	n. a.	PC-WLAN Tester	Intel Core i3 3220/3,3 GHz, Prozessor		2V2403033A 4523	300004589	ne		
4	n. a.	Teststand	Teststand Custom Sequence Editor	National Instruments GmbH		300004590	ne		

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vKI!	Attention: extended calibration interval	*)	next calibration ordered / currently in progress
NK!	Attention: not calibrated		

Equipment and Software of Cetecom GmbH

Used equipment "CTC"

The "Ref.-No" in the left column of the following tables allows the clear identification of the laboratory equipment.

Test software and firmware of equipment

Ref.-No	Equipment	Type	Serial-No.	Version of Firmware or Software during the test
001	EMI Test Receiver	ESS	825132/017	Firm.= 1.21 , OTP=2.0, GRA=2.0
012	Signal Generator (EMS-cond.)	SMY 01	839069/027	Firm.= V 2.02
013	Power Meter (EMS cond.)	NRVD	839111/003	Firm.= V 1.51
017	Digital Radiocommunication Tester	CMD 60 M	844365/014	Firmware = V 3.52 .22.01.99, DECT = D2.87 13.01.99
053	Audio Analyzer	UPA3	860612/022	Firm. V 4.3
119	RT Harmonics Analyzer dig. Flickermeter	B10	G60547	Firm.= V 3.1DHG
140	Signal Generator	SMHU	831314/006	Firm.= 3.21
261	Thermal Power Sensor	NRV-Z55	825083/0008	EPROM-Datum 02.12.04, SE EE 1 B
262	Power Meter	NRV-S	825770/0010	Firm.= 2.6

Ref.-No.	Equipment	Type	Serial-No.	Version of Firmware or Software during the test
263	Signal Generator	SMP 04	826190/0007	Firm.=3.21
264	Spectrum Analyzer	FSEK 30	826939/005	Bios=2.1, Analyzer= 3.20
295	Racal Digital Radio Test Set	6103	1572	UNIT Firmware= 4.04, SW-Main=4.04, SW-BBP=1.04, SW-DSP=1.02, Hardboot=1.02, Softboot=2.02
298	Univ. Radio Communication Tester	CMU 200	832221/091	R&S Test Firmware =3.53 /3.54 (current Testsoftw. f. all band used
323	Digital Radiocommunication Tester	CMD 55	825878/0034	Firm.= 3.52 .22.01.99
331	Climatic Test Chamber -40/+80 Grad	HC 4055	43146	TSI 1.53
335	CTC-EMS-Conducted	System EMS Conducted	-	EMC 32 V 8.52
340	Digital Radiocommunication Tester	CMD 55	849709/037	Firm.= 3.52 .22.01.99
355	Power Meter	URV 5	891310/027	Firm.= 1.31
365	10V Insertion Unit 50 Ohm	URV5-Z2	100880	Eprom Data = 31.03.08
366	Ultra Compact Simulator	UCS 500 M4	V0531100594	Firm. UCS 500=001925/3.06a02, rc=ISMIEC 4.10
371	Bluetooth Tester	CBT32	100153	CBT V5,30+ SW-Option K55, K57
377	EMI Test Receiver	ESCS 30	100160	Firm.= 2.30, OTP= 02.01, GRA= 02.36
378	Broadband RF Field Monitor	RadiSense III	03D00013SNO-08	Firm.= V.03D13
383	Signal Generator	SME 03	842 828 /034	Firm.= 4.61
389	Digital Multimeter	Keithley 2000	0583926	Firm. = A13 (Mainboard) A02 (Display)
392	Radio Communication Tester	MT8820A	6K00000788	Firm.= 4.50 #005, IPL=4.01#001, OS=4.02#001, GSM=4.41#013, W-CDMA= 4.54#004, scenario= 4.52#002
436	Univ. Radio Communication Tester	CMU 200	103083	R&S Test Firmware Base=5.14, Mess-Software= GSM:5.14 WCDMA:5.14 (current Testsoftw. F. all band
441	CTC-SAR-EMI Cable Loss	System EMI field (SAR)	-	EMC 32 Version 8.52
442	CTC-SAR-EMS	System EMS field (SAR)	-	EMC 32 Version 8.40
443	CTC-FAR-EMI-RSE	System CTC-FAR-EMI-RSE	-	Spuri 7.2.5 or EMC 32 Ver. 8.53
444	CTC-FAR-EMS field	System-EMS-Field (FAR)	-	EMC 32 Version 8.40
460	Univ. Radio Communication Tester	CMU 200	108901	R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw.,f. all band to be used,
489	EMI Test Receiver	ESU40	1000-30	Firmware=4.43 SP3, Bios=V5.1-16-3, Spec. =01.00
491	ESD Simulator dito	ESD dito	dito307022	V 2.30
524	Voltage Drop Simulator	VDS 200	0196-16	Software Nr: 000037 Version V4.20a01
526	Burst Generator	EFT 200 A	0496-06	Software Nr. 000034 Version V2.32
527	Micro Pulse Generator	MPG 200 B	0496-05	Software-Nr. 000030 Version V2.43
528	Load Dump Simulator	LD 200B	0496-06	Software-Nr. 000031 Version V2.35a01
546	Univ. Radio Communication Tester	CMU 200	106436	R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw.,f. all band to be used
547	Univ. Radio Communication Tester	CMU 200	835390/014	R&S Test Firmware Base=V5.1403 (current Testsoftw., f. all band used, GSM = 5.14 WCDMA: = 5.14
584	Spectrum Analyzer	FSU 8	100248	2.82_SP3
597	Univ. Radio Communication Tester	CMU 200	100347	R&S Test Firmware Base=5.01, GSM=5.02 WCDMA= not installed, Mainboard= µP1=V.850
598	Spectrum Analyzer	FSEM 30 (Reserve)	831259/013	Firmware Bios 3.40 , Analyzer 3.40 Sp 2
620	EMI Test Receiver	ESU 26	100362	4.43_SP3
642	Wideband Radio Communication Tester	CMW 500	126089	Setup V03.26, Test programm component V03.02.20

Single instruments and test systems

Ref.-No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
001	EMI Test Receiver	ESS	825132/017	Rohde & Schwarz	12 M	-	31.03.2014
005	AC - LISN (50 Ohm/50µH, test site 1)	ESH2-Z5	861741/005	Rohde & Schwarz	24/12 M	-	31.03.2014
007	Single-Line V-Network (50 Ohm/5µH)	ESH3-Z6	892563/002	Rohde & Schwarz	24/12 M	-	31.03.2014
009	Power Meter (EMS-radiated)	NRV	863056/017	Rohde & Schwarz	24 M	-	31.03.2015
016	Line Impedance Simulating Network	Op. 24-D	B6366	Spitzenberger+Spies	36 M	-	31.03.2016
020	Horn Antenna 18 GHz (Subst 1)	3115	9107-3699	EMCO	36/12 M	-	31.03.2014
021	Loop Antenna (H-Field)	6502	9206-2770	EMCO	36 M	-	31.03.2015
030	Loop Antenna (H-field)	HFH-Z2	879604/026	Rohde & Schwarz	36 M	-	31.03.2015
033	RF-current probe (100kHz-30MHz)	ESH2-Z1	879581/18	Rohde & Schwarz	24 M	-	31.03.2015
057	relay-switch-unit (EMS system)	RSU	494440/002	Rohde & Schwarz	pre-m	1a	
060	power amplifier (DC-2kHz)	PAS 5000	B6363	Spitzenberger+Spies	-	3	
066	notch filter (WCDMA; FDD1)	WRCT 1900/2200-5/40-10EEK	5	Wainwright GmbH	12 M	1g	30.06.2014
086	DC - power supply, 0 -10 A	LNG 50-10	-	Heinzinger Electronic	pre-m	2	
087	DC - power supply, 0 -5 A	EA-3013 S	-	Elektro Automatik	pre-m	2	
090	Helmholtz coil: 2x10 coils in series	-	-	RWTÜV	-	4	
091	USB-LWL-Converter	OLS-1	007/2006	Ing. Büro Scheiba	-	4	
099	passive voltage probe	ESH2-Z3	299.7810.52	Rohde & Schwarz	36 M	-	31.03.2015
100	passive voltage probe	Probe TK 9416	without	Schwarzbeck	36 M	-	31.03.2015
110	USB-LWL-Converter	OLS-1	-	Ing. Büro Scheiba	-	4	
119	RT Harmonics Analyzer dig. Flickermeter	B10	G60547	BOCONSULT	36 M	-	31.03.2016
134	horn antenna 18 GHz (Subst 2)	3115	9005-3414	EMCO	pre-m	-	31.03.2014
136	adjustable dipole antenna (Dipole 1)	3121C-DB4	9105-0697	EMCO	36 M	-	31.03.2015
140	Signal Generator	SMHU	831314/006	Rohde & Schwarz	24 M	-	31.03.2014
248	attenuator	SMA 6dB 2W	-	Radiall	pre-m	2	
249	attenuator	SMA 10dB 10W	-	Radiall	pre-m	2	
252	attenuator	N 6dB 12W	-	Radiall	pre-m	2	
256	attenuator	SMA 3dB 2W	-	Radiall	pre-m	2	
257	hybrid	4031C	04491	Narda	pre-m	2	
260	hybrid coupler	4032C	11342	Narda	pre-m	2	
261	Thermal Power Sensor	NRV-Z55	825083/0008	Rohde & Schwarz	24 M	-	31.03.2014
262	Power Meter	NRV-S	825770/0010	Rohde & Schwarz	24 M	-	31.03.2014
263	Signal Generator	SMP 04	826190/0007	Rohde & Schwarz	36 M	-	31.03.2016
264	Spectrum Analyzer	FSEK 30	826939/005	Rohde & Schwarz	12 M	-	31.03.2014
265	peak power sensor	NRV-Z33, Model 04	840414/009	Rohde & Schwarz	24 M	-	31.03.2014
266	peak power sensor	NRV-Z31, Model 04	843383/016	Rohde & Schwarz	24 M	-	31.03.2014
267	notch filter GSM 850	WRCA 800/960-6EEK	9	Wainwright GmbH	pre-m	2	
270	termination	1418 N	BB6935	Weinschel	pre-m	2	
271	termination	1418 N	BE6384	Weinschel	pre-m	2	
272	attenuator (20 dB) 50 W	Model 47	BF6239	Weinschel	pre-m	2	
273	attenuator (10 dB) 100 W	Model 48	BF9229	Weinschel	pre-m	2	
274	attenuator (10 dB) 50 W	Model 47 (10 dB) 50 W	BG0321	Weinschel	pre-m	2	
275	DC-Block	Model 7003 (N)	C5129	Weinschel	pre-m	2	
276	DC-Block	Model 7006 (SMA)	C7061	Weinschel	pre-m	2	
279	power divider	1515 (SMA)	LH855	Weinschel	pre-m	2	
287	pre-amplifier 25MHz - 4GHz	AMF-2D-100M4G-35-10P	379418	Miteq	12 M	1c	30.06.2014
291	high pass filter GSM 850/900	WHJ 2200-4EE	14	Wainwright GmbH	12 M	1c	30.06.2014
298	Univ. Radio Communication Tester	CMU 200	832221/091	Rohde & Schwarz	pre-m	3	
300	AC LISN (50 Ohm/50µH, 1-phase)	ESH3-Z5	892 239/020	Rohde & Schwarz	24/12 M	-	31.03.2014
301	attenuator (20 dB) 50W, 18GHz	47-20-33	AW0272	Lucas Weinschel	pre-m	2	
302	horn antenna 40 GHz (Meas 1)	BBHA9170	155	Schwarzbeck	36 M	-	31.03.2014
303	horn antenna 40 GHz (Subst 1)	BBHA9170	156	Schwarzbeck	36 M	-	31.03.2014
331	Climatic Test Chamber -40/+80 Grad	HC 4055	43146	Heraeus Vötsch	24 M	-	30.11.2014
341	Digital Multimeter	Fluke 112	81650455	Fluke	24 M	-	31.03.2014
342	Digital Multimeter	Voltcraft M-4660A	IB 255466	Voltcraft	24 M	-	31.03.2015
347	laboratory site	radio lab.	-	-	-	5	
348	laboratory site	EMI conducted	-	-	-	5	
354	DC - Power Supply 40A	NGPE 40/40	448	Rohde & Schwarz	pre-m	2	
355	Power Meter	URV 5	891310/027	Rohde & Schwarz	24 M	-	31.03.2014
356	power sensor	NRV-Z1	882322/014	Rohde & Schwarz	24 M	-	31.03.2015
357	power sensor	NRV-Z1	861761/002	Rohde & Schwarz	24 M	-	31.03.2015
371	Bluetooth Tester	CBT32	100153	R&S	24 M	-	31.03.2014
373	Single-Line V-Network (50 Ohm/5µH)	ESH3-Z6	100535	Rohde & Schwarz	24/12 M	-	31.03.2014
376	Horn Antenna 6 GHz	BBHA9120 E	BBHA 9120 E 179	Schwarzbeck	12 M	-	31.03.2014
377	EMI Test Receiver	ESCS 30	100160	Rohde & Schwarz	12 M	-	31.03.2014
389	Digital Multimeter	Keithley 2000	0583926	Keithley	24 M	-	31.03.2015
392	Radio Communication Tester	MT8820A	6K00000788	Anritsu	12 M	-	31.03.2014
431	Model 7405	Near-Field Probe Set	9305-2457	EMCO	-	4	

Ref.-No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
436	Univ. Radio Communication Tester	CMU 200	103083	Rohde & Schwarz	12 M	-	31.03.2014
441	CTC-SAR-EMI Cable Loss	System EMI field (SAR) Cable	-	CETECOM	12 M	5	31.10.2014
443	CTC-FAR-EMI-RSE	System CTC-FAR-EMI-RSE	-	ETS-Lindgren / CETECOM	12 M	5	15.07.2014
448	notch filter WCDMA_FDD II	WRCT 1850.0/2170.0-5/40-	5	Wainwright Instruments GmbH	12 M	1c	30.06.2014
449	notch filter WCDMA FDD V	WRCT 824.0/894.0-5/40-8SSK	1	Wainwright	12 M	1c	30.06.2014
454	Oscilloscope	HM 205-3	9210 P 29661	Hameg	-	4	
456	DC-Power supply 0-5 A	EA 3013 S	207810	Elektro Automatik	pre-m	2	
459	DC -Power supply 0-5 A , 0-32 V	EA-PS 2032-50	910722	Elektro Automatik	pre-m	2	
460	Univ. Radio Communication Tester	CMU 200	108901	Rohde & Schwarz	12 M	-	31.03.2014
463	Universal source	HP3245A	2831A03472	Agilent	-	4	
466	Digital Multimeter	Fluke 112	89210157	Fluke USA	24 M	-	31.03.2014
467	Digital Multimeter	Fluke 112	89680306	Fluke USA	24 M	-	31.03.2014
468	Digital Multimeter	Fluke 112	90090455	Fluke USA	24 M	-	31.03.2014
477	ReRadiating GPS-System	AS-47	-	Automotive Cons. Fink	-	3	
480	power meter (Fula)	NRVS	838392/031	Rohde & Schwarz	24 M	-	31.03.2015
482	filter matrix	Filter matrix SAR 1	-	CETECOM (Brl)	-	1d	
484	pre-amplifier 2,5 - 18 GHz	AMF-5D-02501800-25-10P	1244554	Miteq	12 M	-	30.06.2014
487	System CTC NSA-Verification SAR-EMI	System EMI field (SAR) NSA	-	ETS Lindgren / CETECOM	24 M	-	30.06.2015
489	EMI Test Receiver	ESU40	1000-30	Rohde & Schwarz	12 M	-	31.03.2014
502	band reject filter	WRCG 1709/1786-1699/1796-	SN 9	Wainwright	pre-m	2	
503	band reject filter	WRCG 824/849-814/859-	SN 5	Wainwright	pre-m	2	
512	notch filter GSM 850	WRCA 800/960-02/40-6EEK	SN 24	Wainwright	12 M	1c	30.06.2014
517	relais switch matrix	HF Relais Box Keithley	SE 04	Keithley	pre-m	2	
523	Digital Multimeter	L4411A	MY46000154	Agilent	24 M	-	31.03.2015
529	6 dB Broadband resistive power divider	Model 1515	LH 855	Weinschel	pre-m	2	
530	10 dB Broadband resistive power divider	R 416110000	LOT 9828	-	pre-m	2	
546	Univ. Radio Communication Tester	CMU 200	106436	R&S	12 M	-	31.03.2014
547	Univ. Radio Communication Tester	CMU 200	835390/014	Rohde & Schwarz	12 M	-	31.03.2014
548	Digital-Barometer	GBP 2300	without	Greisinger GmbH	36 M	-	30.06.2015
549	Log.Per-Antenna	HL025	1000060	Rohde & Schwarz	36/12 M	-	31.03.2015
552	high pass filter 2,8-18GHz	WHKX 2.8/18G-10SS	4	Wainwright	12 M	1c	30.06.2014
558	System CTC FAR S-VSWR	System CTC FAR S-VSWR	-	CTC	24 M	-	31.07.2015
574	Biconilog Hybrid Antenna	BTA-L	980026L	Frankonia	36/12 M	-	31.03.2016
584	Spectrum Analyzer	FSU 8	100248	Rohde & Schwarz	24 M	-	31.03.2014
597	Univ. Radio Communication Tester	CMU 200	100347	Rohde & Schwarz	12 M	-	31.03.2014
598	Spectrum Analyzer	FSEM 30 (Reserve)	831259/013	Rohde & Schwarz	24 M	-	13.01.2015
600	power meter	NRVD (Reserve)	834501/018	Rohde & Schwarz	24 M	-	31.03.2015
601	medium-sensitivity diode sensor	NRV-Z5 (Reserve)	8435323/003	Rohde & Schwarz	24 M	-	31.03.2015
602	peak power sensor	NRV-Z32 (Reserve)	835080	Rohde & Schwarz	24 M	-	31.03.2015
608	UltraLog-Antenna	HL 562	830547/009	Rohde & Schwarz	36/12 M	-	31.03.2014
611	DC power supply	E3632A	KR 75305854	Agilent	pre-m	2	
612	DC power supply	E3632A	MY 40001321	Agilent	pre-m	2	
613	Attenuator	R416120000 20dB 10W	Lot. 9828	Radiall	pre-m	2	
616	Digitalmultimeter	Fluke 177	88900339	Fluke	24 M	-	31.03.2014
617	Power Splitter/Combiner	ZFSC-2-2-S+	S F987001108	Mini Circuits	-	2	
618	Power Splitter/Combiner	50PD-634	600994	JFW Industries USA	-	2	
619	Power Splitter/Combiner	50PD-634	600995	JFW Industries, USA	-	3	
620	EMI Test Receiver	ESU 26	100362	Rohde-Schwarz	12 M	-	01.03.2014
621	Step Attenuator 0-139 dB	RSP	100017	Rohde & Schwarz	pre-m	2	
625	Generic Test Load USB	Generic Test Load USB	-	CETECOM	-	2	
627	data logger	OPUS 1	201.0999.9302.6.4.1.43	G. Luft GmbH	24 M	-	30.05.2014
634	Spectrum Analyzer	FSM (HF-Unit)	826188/010	Rohde & Schwarz	pre-m	2	
636	Thermal Imaging camera	Ti32	Ti32-12060213	Fluke Corporation	24 M	-	31.07.2014
637	High Speed HDMI with Ethernet 1m	HDMI cable with Ethernet 1m	-	KogiLink	-	2	
638	HDMI Kabel with Ethernet 1,5 m flach	HDMI cable with Ethernet	-	Reichelt	-	2	
640	HDMI cable 2m rund	HDMI cable 2m rund	-	Reichelt	-	2	
641	HDMI cable with Ethernet	Certified HDMI cable with	-	PureLink	-	2	
642	Wideband Radio Communication Tester	CMW 500	126089	Rohde&Schwarz	24 M	-	31.03.2014
644	Amplifierer	ZX60-2534M+	SN865701299	Mini-Circuits	-	-	
670	Univ. Radio Communication Tester	CMU 200	106833	Rohde & Schwarz	12 M	-	31.03.2014
671	DC-power supply 0-5 A	EA-3013S	-	Elektro Automatik	pre-m	2	
678	Power Meter	NRP	101638	Rohde&Schwarz	pre-m	-	

Ref- No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
683	Spectrum Analyzer	FSU 26	200571	Rohde & Schwarz	12 M	-	26.11.2014
686	Field Analyzer	EHP-200A	160WX30702	Narda Safety Test Solutions	24 M	-	18.07.2015
687	Signal Generator	SMF 100A	102073	Rohde&Schwarz	12 M	-	27.11.2014
688	Pre Amp	JS-18004000-40-8P	1750117	Miteq	pre-m	-	

12 Observations

No observations exceeding those reported with the single test cases have been made.

Annex A Document history

Version	Applied changes	Date of release
	Initial release	2014-03-28
-A	Editorial changes	2014-03-31

Annex B Further information**Glossary**


AVG	-	Average
DUT	-	Device under test
EMC	-	Electromagnetic Compatibility
EN	-	European Standard
EUT	-	Equipment under test
ETSI	-	European Telecommunications Standard Institute
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	Not applicable
PP	-	Positive peak
QP	-	Quasi peak
S/N	-	Serial number
SW	-	Software

Annex C Accreditation Certificate

Front side of certificate



Back side of certificate



Note:

The current certificate including annex is published on our website (see link below) or may be received from CETECOM ICT Services on request.

<http://www.cetecom.com/eu/de/cetecom-group/europa/deutschland-saarbruecken/akkreditierungen.html>