



FCC PART 15C&IC TEST REPORT No. 2013TAR841

for

Sony Mobile Communications AB

GSM/WCDMA/LTE Mobile Phone

Type: PM-0762-BV

FCC ID: PY7PM-0762

with

Hardware Version: a

Software Version: s_atp_tianchi_1_0_14_6

Issued Date: 2014-01-15



DAR accreditation (DIN EN ISO/IEC 17025): No. D-PL-12123-01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629B

Note: The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No.18A, Kangding Street, Beijing Economical Development Area, Beijing, China 100176

Tel:+86(0)10-67857376, Fax:+86(0)10-67857376 Email:welcome@emcite.com. www.emcite.com

CONTENTS

CONTENTS	2
1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT.....	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. GENERAL DESCRIPTION.....	6
4. REFERENCE DOCUMENTS	7
4.1. DOCUMENTS SUPPLIED BY APPLICANT	7
4.2. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS	9
6.1. SUMMARY OF TEST RESULTS.....	9
6.2. STATEMENTS.....	10
6.3. TEST CONDITIONS	10
7. TEST EQUIPMENTS UTILIZED	11
A.1. MEASUREMENT METHOD	12
A.2. PEAK OUTPUT POWER	13
A.2.1 Antenna gain	13
A.2.2 Conducted Output Power	13
A.2.3 Radiated Output Power	13
A.3. FREQUENCY BAND EDGES - CONDUCTED.....	14
A.4. CONDUCTED EMISSION	21
A.5. RADIATED EMISSION.....	45
A.6. TIME OF OCCUPANCY (DWEIL TIME)	66
A.7. 20DB BANDWIDTH.....	76
A.8. CARRIER FREQUENCY SEPARATION	82
A.9. NUMBER OF HOPPING CHANNELS.....	84
A.10. AC POWERLINE CONDUCTED EMISSION	88
A.11.RECEIVER RADIATION EMISSION	91

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No.18A, Kangding Street, Beijing Economical Development Area,
Beijing, China
Postal Code: 100176
Telephone: 00861067857376
Fax: 00861067857376

1.2. Testing Environment


Normal Temperature: 15-35℃
Extreme Temperature: -20/+55℃
Relative Humidity: 30-60%
Air Pressure 990hPa-1040hPa

Note: The climatic requirements above are general exclude the special requirements for dedicated test environments listed in section 5 and some specific test cases in other parts of this report.

1.3. Project data

Project Leader: Zi Xiaogang
Testing Start Date: 2013-12-26
Testing End Date: 2014-01-07


1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Sony Mobile Communications (China) Co. Ltd
Address /Post: Sony Mobile R&D Center, No. 16, Guangshun South Street,
Chaoyang District
City: Beijing
Postal Code: 100102
Country: China
Contact Person: Ma, Gang
Telephone: +86-10-58656312
Fax: +86-10-58659049

2.2. Manufacturer Information

Company Name: Sony Mobile Communications AB
Address /Post: Mobilvägen, 22188 Lund, Sweden
City: Lund
Postal Code: 22188
Country: Sweden
Contact Person: Nilsson, Mikael
Telephone: +46 703 227503
Fax: +46 706 127385

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM 850/900/1800/1900 quad bands, GPRS, EDGE, WCDMA FDD bands 1/5/8, HSDPA, HSUPA, LTE FDD bands 1/3/5/7/8/20, Bluetooth (EDR and 4.0), ANT+, WLAN (802.11 a/b/g/n), NFC, FM, GPS mobile phone
Type	PM-0762-BV
FCC ID	PY7PM-0762
Frequency Range	ISM 2400MHz~2483.5MHz
Type of Modulation	GFSK/ $\pi/4$ DQPSK/8DPSK
Number of Channels	79
GSM Frequency Band	GSM 850/900/1800/1900
UMTS Frequency Band	FDD Band 1 / FDD Band 5 / FDD Band 8
LTE Frequency Band	FDD Band 1 / FDD Band 3 / FDD Band 5 / FDD Band 7 / FDD Band 8 / FDD Band 20
Antenna	Integrated
MAX Radiated Power	8.74dBm EIRP(8DPSK)
MAX Conducted Power	10.93dBm (8DPSK)
Power Supply	3.7V DC

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	S/N	HW Version	SW Version
N12	004402451819175	CB512686S5	a	s_atp_tianchi_1_0_14_6
N10	004402451819274	CB512686FD	a	s_atp_tianchi_1_0_14_6

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Revision
AE1	Travel Charger	4413W18511285	1
AE2	Vehicle Charger	122914030172794	1
AE3	USB Cable	131307D20BE8904	1

AE1

Commercial name	EP880
Type	AC-0400-EU
Manufacturer	SALCOMP
Length of cable	98.5 cm (length of USB cable)

AE2

Type	CAA-0003013
Manufacturer	Sony Mobile

Length of cable	98.5 cm (the length of USB cable)
AE3	
Commercial name	EC801
Type	AI-0401
Manufacturer	Sony Mobile
Length of cable	98.5 cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/WCDMA/LTE Mobile Phone with integrated antenna and inbuilt battery.

The EUT supports GSM 850/900/1800/1900MHz bands, WCDMA FDD bands 1/5/8 and LTE FDD bands 1/3/5/7/8/20. It supports GPRS service with multi-slots class 33 and EGPRS service with multi-slots class 33. The HSDPA and HSUPA (Cat 6) features are also supported.

It has MP3, camera, USB memory, Mobile High-Definition Link (MHL), FM radio, GPS receiver, NFC, Bluetooth (EDR and Bluetooth 4.0), ANT+, WLAN (802.11 a/b/g/n) and Wi-Fi hotspot functions. For WLAN 802.11n, it supports 20MHz and 40MHz bandwidths on both 2.4GHz band and 5GHz/5.8GHz band.

It includes normal option: USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

	FCC CFR 47, Part 15, Subpart C:	
	15.205 Restricted bands of operation;	10-1-12
FCC Part15	15.209 Radiated emission limits, general requirements;	Edition
	15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	
FCC Part 2	Frequency Allocations and Radio Treaty Matters;	10-1-12
	General Rules and Regulations	Edition
ANSI C63.10	American National Standard for Testing Unlicensed Wireless Devices	2009
	Spectrum Management and Telecommunications - Radio Standards Specification	
RSS - Gen Issue3	General Requirements and Information for the Certification of Radiocommunication Equipment	2010-12
RSS -210 Issue8	Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment	2010-12

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room/ conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Fully-anechoic chamber2 (8.6 meters×6.1 meters×3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 1 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

Fully-anechoic chamber3 (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	> 2 MΩ
Ground system resistance	< 0.5 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz

Additional Humidity Requirements for Electrostatic Discharge Test: Min. = 30%, Max. = 60%.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Modulation	Sub-clause of Part15C	IC	Verdict
Peak Output Power (Conducted)	GFSK/	15.247 (b)(1)	RSS-210 A8.4 (2)	P
	$\pi/4$ DQPSK			P
	8DPSK			P
Peak Output Power(Radiated)	GFSK	15.247 (b)(1)	RSS-210 A8.4 (2)	P
Antenna Gain	GFSK/	None		P
Frequency Band Edges	GFSK	15.247 (d)	RSS-210 A8.5	P
	$\pi/4$ DQPSK			P
	8DPSK			P
Conducted Emission	GFSK	15.247 (d)	RSS-210 A8.5	P
	$\pi/4$ DQPSK			P
	8DPSK			P
Radiated Emission	GFSK	15.247(d),15.205, 15.209,15.109	RSS-210 A8.5	P
	$\pi/4$ DQPSK			P
	8DPSK			P
Time of Occupancy (Dwell Time)	GFSK	15.247 (a) (1)(iii)	RSS-210 A8.1 (4)	P
	$\pi/4$ DQPSK			P
	8DPSK			P
20dB Bandwidth	GFSK	15.247 (a)(1)	RSS-210 A8.1 (1)	P
	$\pi/4$ DQPSK			P
	8DPSK			P
Carrier Frequency Separation	GFSK	15.247 (a)(1)	RSS-210 A8.1 (2)	P
	$\pi/4$ DQPSK			P
	8DPSK			P
Number of hopping channels	GFSK	15.247 (a)(1)(iii)	RSS-210 A8.1 (4)	P
	$\pi/4$ DQPSK			P
	8DPSK			P
AC Powerline Conducted Emission	GFSK	15.107, 15.207	RSS-Gen 7.2.2	P

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by TMC
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

The test cases as listed in section 6.1 of this report for the EUT specified in section 3 was performed by TMC and according to the standards or reference documents listed in section 4.2

The EUT met all requirements of the standards or reference documents.

This report only deals with the Bluetooth including EDR functions among the features described in section 3.

6.3. Test Conditions

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage
V min	Low Voltage
V max	High Voltage
H nom	Norm Humidity
A nom	Norm Air Pressure

For this report, all the test case listed above are tested under Normal Temperature and Normal Voltage, and also under norm humidity, the specific conditions as following:

Temperature	T nom	25°C
Voltage	V nom	3.7V
Humidity	H nom	38%
Air Pressure	A nom	1010hPa

7. Test Equipments Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Vector Signal Analyzer	FSU26	200030	Rohde & Schwarz	2014-06-12
2	Bluetooth Tester	CBT32	100649	Rohde & Schwarz	2014-02-03

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	2014-11-05
2	EMI Antenna	VULB 9163	9163482	Schwarzbeck	2014-02-17
3	EMI Antenna	3117	00119024	EMCO	2014-02-03
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	2014-06-30
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	2014-06-30
6	Bluetooth Tester	CBT	100153	Rohde & Schwarz	2014-09-15
7	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	2014-03-17
8	Pre-amplifier(18GHz)	SCU18	1005277	Rohde & Schwarz	/
9	Pre-amplifier(26.5GHz)	SCU26	1006788	Rohde & Schwarz	/

Anechoic chamber

Fully anechoic chamber by Frankonia German.

Note : The pre amplifiers is calibrated with routes calibration every time before test, therefore no need for the calibration date.


ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements


The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;



A.2. Peak Output Power

Measurement Limit:

Standard	Limit (dBm)
FCC Part 15.247(b)(1)/ / RSS-210 A8.4 (2)	< 30

The measurement is made according to ANSI C63.10.

Measurement Results:

A.2.1 Antenna gain

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the EUT.

Antenna gain = GFSK (Radiated) - GFSK (Conducted)

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz
GFSK (Conducted)	8.31	9.70	6.98
GFSK (Radiated)	6.70	7.51	6.01
Gain(dBi)	-1.61	-2.19	-0.97

Conclusion: PASS

A.2.2 Conducted Output Power

Peak(RBW=VBW=2MHz; SPAN=5MHz; Detector: Peak)

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
GFSK (dBm)	8.31	9.70	6.98	P
$\pi/4$ DQPSK (dBm)	9.31	10.62	7.98	P
8DPSK (dBm)	9.64	10.93	8.28	P

Measurement Uncertainty: ± 1.17 dB

Conclusion: PASS

A.2.3 Radiated Output Power

Peak(RBW=VBW=8MHz; SPAN=8MHz; Detector: Peak)

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
GFSK (dBm)	6.70	7.51	6.01	P
$\pi/4$ DQPSK * (dBm)	7.70	8.43	7.02	P
8DPSK * (dBm)	8.03	8.74	7.31	P

Note:* These values are calculated with the antenna gain

Measurement Uncertainty: ± 1.98 dB

Conclusion: PASS

A.3. Frequency Band Edges - Conducted

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d) RSS-210 A8.4(2)	<-20 Note: The measurement results are calculated as power measured in any 100KHz bandwidth outside the frequency band in dBm minus power measured in the 100 kHz bandwidth within the band that contains the highest level of the desired power

The measurement is made according to ANSI C63.10.

Measurement Result:

For GFSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.1	-57.07	P
	Hopping ON	Fig.2	-59.77	P
78	Hopping OFF	Fig.3	-61.91	P
	Hopping ON	Fig.4	-63.79	P

For $\pi/4$ DQPSK


Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.5	-56.25	P
	Hopping ON	Fig.6	-55.80	P
78	Hopping OFF	Fig.7	-63.54	P
	Hopping ON	Fig.8	-62.26	P

For 8DPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.9	-55.72	P
	Hopping ON	Fig.10	-57.98	P
78	Hopping OFF	Fig.11	-63.72	P
	Hopping ON	Fig.12	-62.29	P


Conclusion: PASS

Test graphs as below




Date: 23.DEC.2013 17:02:10

Fig.1. Frequency Band Edges: GFSK, Channel 0, Hopping Off




Date: 23.DEC.2013 17:04:30

Fig.2. Frequency Band Edges: GFSK, Channel 0, Hopping On




Date: 23.DEC.2013 17:02:28

Fig.3. Frequency Band Edges: GFSK, Channel 78, Hopping Off




Date: 23.DEC.2013 17:06:32

Fig.4. Frequency Band Edges: GFSK, Channel 78, Hopping On




Date: 23.DEC.2013 17:23:40

Fig.5. Frequency Band Edges: $\pi/4$ DQPSK, Channel 0, Hopping Off




Date: 23.DEC.2013 17:26:00

Fig.6. Frequency Band Edges: $\pi/4$ DQPSK, Channel 0, Hopping On




Date: 23.DEC.2013 17:23:58

Fig.7. Frequency Band Edges: $\pi/4$ DQPSK, Channel 78, Hopping Off




Date: 23.DEC.2013 17:28:03

Fig.8. Frequency Band Edges: $\pi/4$ DQPSK, Channel 78, Hopping On




Date: 23.DEC.2013 17:45:14

Fig.9. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off




Date: 23.DEC.2013 17:47:34

Fig.10. Frequency Band Edges: 8DPSK, Channel 0, Hopping On



Date: 23.DEC.2013 17:45:31

Fig.11. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off



Date: 23.DEC.2013 17:49:36

Fig.12. Frequency Band Edges: 8DPSK, Channel 78, Hopping On

A.4. Conducted Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d) RSS-210 A8.5	20dB below peak output power in 100 kHz bandwidth

The measurement is made according to ANSI C63.10

Measurement Results:

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.13	P
	30 MHz ~ 1 GHz	Fig.14	P
	1 GHz ~ 3 GHz	Fig.15	P
	3 GHz ~ 10 GHz	Fig.16	P
	10 GHz ~ 26 GHz	Fig.17	P
Ch 39 2441 MHz	Center Frequency	Fig.18	P
	30 MHz ~ 1 GHz	Fig.19	P
	1 GHz ~ 3 GHz	Fig.20	P
	3 GHz ~ 10 GHz	Fig.21	P
	10 GHz ~ 26 GHz	Fig.22	P
Ch 78 2480 MHz	Center Frequency	Fig.23	P
	30 MHz ~ 1 GHz	Fig.24	P
	1 GHz ~ 3 GHz	Fig.25	P
	3 GHz ~ 10 GHz	Fig.26	P
	10 GHz ~ 26 GHz	Fig.27	P

For $\pi/4$ DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.28	P
	30 MHz ~ 1 GHz	Fig.29	P
	1 GHz ~ 3 GHz	Fig.30	P
	3 GHz ~ 10 GHz	Fig.31	P
	10 GHz ~ 26 GHz	Fig.32	P
Ch 39 2441 MHz	Center Frequency	Fig.33	P
	30 MHz ~ 1 GHz	Fig.34	P
	1 GHz ~ 3 GHz	Fig.35	P
	3 GHz ~ 10 GHz	Fig.36	P
	10 GHz ~ 26 GHz	Fig.37	P
Ch 78 2480 MHz	Center Frequency	Fig.38	P
	30 MHz ~ 1 GHz	Fig.39	P


	1 GHz ~ 3 GHz	Fig.40	P
	3 GHz ~ 10 GHz	Fig.41	P
	10 GHz ~ 26 GHz	Fig.42	P

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.43	P
	30 MHz ~ 1 GHz	Fig.44	P
	1 GHz ~ 3 GHz	Fig.45	P
	3 GHz ~ 10 GHz	Fig.46	P
	10 GHz ~ 26 GHz	Fig.47	P
Ch 39 2441 MHz	Center Frequency	Fig.48	P
	30 MHz ~ 1 GHz	Fig.49	P
	1 GHz ~ 3 GHz	Fig.50	P
	3 GHz ~ 10 GHz	Fig.51	P
	10 GHz ~ 26 GHz	Fig.52	P
Ch 78 2480 MHz	Center Frequency	Fig.53	P
	30 MHz ~ 1 GHz	Fig.54	P
	1 GHz ~ 3 GHz	Fig.55	P
	3 GHz ~ 10 GHz	Fig.56	P
	10 GHz ~ 26 GHz	Fig.57	P


Conclusion: PASS

Test graphs as below




Date: 23.DEC.2013 17:06:51

Fig.13. Conducted spurious emission: GFSK, Channel 0,2402MHz




Date: 23.DEC.2013 17:07:08

Fig.14. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz




Date: 23.DEC.2013 17:07:40

Fig.15. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz




Date: 23.DEC.2013 17:07:56

Fig.16. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz




Date: 23.DEC.2013 17:08:13

Fig.17. Conducted spurious emission: GFSK, Channel 0, 10GHz - 26GHz




Date: 23.DEC.2013 17:08:30

Fig.18. Conducted spurious emission: GFSK, Channel 39, 2441MHz




Date: 23.DEC.2013 17:08:46

Fig.19. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz




Date: 23.DEC.2013 17:09:18

Fig.20. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz




Date: 23.DEC.2013 17:09:34

Fig.21. Conducted spurious emission: GFSK, Channel 39, 3GHz – 10GHz




Date: 23.DEC.2013 17:09:51

Fig.22. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz




Date: 23.DEC.2013 17:10:08

Fig.23. Conducted spurious emission: GFSK, Channel 78, 2480MHz




Date: 23.DEC.2013 17:10:24

Fig.24. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz




Date: 23.DEC.2013 17:10:56

Fig.25. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz




Date: 23.DEC.2013 17:11:12

Fig.26. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz




Date: 23.DEC.2013 17:11:29

Fig.27. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz




Date: 23.DEC.2013 17:28:21

Fig.28. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0,2402MHz




Date: 23.DEC.2013 17:28:38

Fig.29. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 30MHz - 1GHz




Date: 23.DEC.2013 17:29:10

Fig.30. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 1GHz - 3GHz




Date: 23.DEC.2013 17:29:26

Fig.31. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 3GHz - 10GHz




Date: 23.DEC.2013 17:29:43

Fig.32. Conducted spurious emission: $\pi/4$ DQPSK, Channel 0, 10GHz - 26GHz




Date: 23.DEC.2013 17:30:00

Fig.33. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 2441MHz




Date: 23.DEC.2013 17:30:16

Fig.34. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 30MHz - 1GHz




Date: 23.DEC.2013 17:30:48

Fig.35. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 1GHz - 3GHz




Date: 23.DEC.2013 17:31:04

Fig.36. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 3GHz - 10GHz



Date: 23.DEC.2013 17:31:21

Fig.37. Conducted spurious emission: $\pi/4$ DQPSK, Channel 39, 10GHz – 26GHz



Ref 11.2 dBm * Att 5 dB

* RBW 100 kHz Marker 1 [T1] -44.78 dBm
 * VBW 300 kHz
 SWT 100 ms 165.240384615 MHz

Offset 1.2 dB


D1 -16.58 dBm

1

Start 30 MHz 97 MHz/ Stop 1 GHz


Date: 23.DEC.2013 17:31:54

Fig.39. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 30MHz - 1GHz




Date: 23.DEC.2013 17:32:26

Fig.40. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 1GHz - 3GHz




Date: 23.DEC.2013 17:32:42

Fig.41. Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 3GHz - 10GHz




Date: 23.DEC.2013 17:32:59

Fig.42. Fig.30 Conducted spurious emission: $\pi/4$ DQPSK, Channel 78, 10GHz - 26GHz




Date: 23.DEC.2013 17:49:55

Fig.43. Conducted spurious emission: 8DPSK, Channel 0, 2402MHz




Date: 23.DEC.2013 17:50:12

Fig.44. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz




Date: 23.DEC.2013 17:50:43

Fig.45. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz




Date: 23.DEC.2013 17:51:00

Fig.46. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz




Date: 23.DEC.2013 17:51:17

Fig.47. Conducted spurious emission: 8DPSK, Channel 0, 10GHz - 26GHz




Date: 23.DEC.2013 17:51:33

Fig.48. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz




Date: 23.DEC.2013 17:51:50

Fig.49. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz




Date: 23.DEC.2013 17:52:21

Fig.50. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz




Date: 23.DEC.2013 17:52:38

Fig.51. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz




Date: 23.DEC.2013 17:52:55

Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Date: 23.DEC.2013 17:53:11

Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz




Date: 23.DEC.2013 17:53:28

Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Date: 23.DEC.2013 17:53:59

Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz



Date: 23.DEC.2013 17:54:16

Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz



Date: 23.DEC.2013 17:54:33

Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

A.5. Radiated Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209 RSS-210 A8.5	Listed as follows

Frequency (MHz) Field strength	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100	3
88–216	150	3
216–960	200	3
Above 960	500	3

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
0.009-30	100KHz/300KHz	5
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

Measurement Results:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and

including the gain of receive antenna, the gain of the preamplifier, the cable los.
The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}}$$

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	30 MHz ~ 1 GHz	Fig.58	P
	1 GHz ~ 3 GHz	Fig.59	P
	3 GHz ~ 18 GHz	Fig.60	P
Ch 39 2441 MHz	9 kHz ~ 30 MHz	Fig.61	P
	30 MHz ~ 1 GHz	Fig.62	P
	1 GHz ~ 3 GHz	Fig.63	P
	3 GHz ~ 18 GHz	Fig.64	P
Ch 78 2480 MHz	30 MHz ~ 1 GHz	Fig.65	P
	1 GHz ~ 3 GHz	Fig.66	P
	3 GHz ~ 18 GHz	Fig.67	P
Power	2.38GHz~2.4GHz---L	Fig.68	P
Power	2.45GHz~2.5GHz---H	Fig.69	P
For all channels	18 GHz ~ 26 GHz	Fig.70	P

For π/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	30 MHz ~ 1 GHz	Fig.71	P
	1 GHz ~ 3 GHz	Fig.72	P
	3 GHz ~ 18 GHz	Fig.73	P
Ch 39 2441 MHz	30 MHz ~ 1 GHz	Fig.74	P
	1 GHz ~ 3 GHz	Fig.75	P
	3 GHz ~ 18 GHz	Fig.76	P
Ch 78 2480 MHz	30 MHz ~ 1 GHz	Fig.77	P
	1 GHz ~ 3 GHz	Fig.78	P
	3 GHz ~ 18 GHz	Fig.79	P
Power	2.38GHz~2.4GHz---L	Fig.80	P
Power	2.45GHz~2.5GHz---H	Fig.81	P
For all channels	18 GHz ~ 26 GHz	Fig.82	P

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	30 MHz ~ 1 GHz	Fig.83	P
	1 GHz ~ 3 GHz	Fig.84	P
	3 GHz ~ 18 GHz	Fig.85	P
Ch 39	30 MHz ~ 1 GHz	Fig.86	P

2441 MHz	1 GHz ~ 3 GHz	Fig.87	P
	3 GHz ~ 18 GHz	Fig.88	P
Ch 78 2480 MHz	30 MHz ~ 1 GHz	Fig.89	P
	1 GHz ~ 3 GHz	Fig.90	P
	3 GHz ~ 18 GHz	Fig.91	P
Power	2.38GHz~2.4GHz---L	Fig.92	P
Power	2.45GHz~2.5GHz---H	Fig.93	P
For all channels	18 GHz ~ 26 GHz	Fig.94	P

Note: Only worst case result is given.

Test graphs as below:




Fig.58. Radiated emission: GFSK, Channel 0, 30 MHz - 1 GHz




Fig.59. Radiated emission: GFSK, Channel 0, 1 GHz - 3 GHz




Fig.60. Radiated emission: GFSK, Channel 0, 3 GHz - 18 GHz




Fig.61. Radiated emission: GFSK, Channel 39, 9 kHz - 30 MHz




Fig.62. Radiated emission: GFSK, Channel 39, 30 MHz - 1 GHz




Fig.63. Radiated emission: GFSK, Channel 39, 1 GHz - 3 GHz




Fig.64. Radiated emission: GFSK, Channel 39, 3 GHz - 18 GHz




Fig.65. Radiated emission: GFSK, Channel 78, 30 MHz - 1 GHz




Fig.66. Radiated emission: GFSK, Channel 78, 1 GHz - 3 GHz




Fig.67. Radiated emission: GFSK, Channel 78, 3 GHz - 18 GHz




Fig.68. Radiated emission (Power): GFSK, low channel




Fig.69. Radiated emission (Power) GFSK, high channel




Fig.70. Radiated emission: GFSK, 18 GHz - 26 GHz




Fig.71. Radiated emission: $\pi/4$ DQPSK, Channel 0, 30 MHz - 1 GHz




Fig.72. Radiated emission: $\pi/4$ DQPSK, Channel 0, 1 GHz - 3 GHz




Fig.73. Radiated emission: $\pi/4$ DQPSK, Channel 0, 3 GHz - 18 GHz




Fig.74. Radiated emission: $\pi/4$ DQPSK, Channel 39, 30 MHz - 1 GHz




Fig.75. Radiated emission: $\pi/4$ DQPSK, Channel 39, 1 GHz - 3 GHz




Fig.76. Radiated emission: $\pi/4$ DQPSK, Channel 39, 3 GHz - 18 GHz




Fig.77. Radiated emission: $\pi/4$ DQPSK, Channel 78, 30 MHz - 1 GHz




Fig.78. Radiated emission: $\pi/4$ DQPSK, Channel 78, 1 GHz - 3 GHz




Fig.79. Radiated emission: $\pi/4$ DQPSK, Channel 78, 3 GHz - 18 GHz




Fig.80. Radiated emission (Power): $\pi/4$ DQPSK, low channel




Fig.81. Radiated emission (Power): $\pi/4$ DQPSK, high channel




Fig.82. Radiated emission: $\pi/4$ DQPSK, 18 GHz - 26 GHz




Fig.83. Radiated emission: 8DPSK, Channel 0, 30 MHz - 1 GHz




Fig.84. Radiated emission: 8DPSK, Channel 0, 1 GHz - 3 GHz




Fig.85. Radiated emission: 8DPSK, Channel 0, 3 GHz - 18 GHz




Fig.86. Radiated emission: 8DPSK, Channel 39, 30 MHz - 1 GHz




Fig.87. Radiated emission: 8DPSK, Channel 39, 1 GHz - 3 GHz




Fig.88. Radiated emission: 8DPSK, Channel 39, 3 GHz - 18 GHz




Fig.89. Radiated emission: 8DPSK, Channel 78, 30 MHz - 1 GHz




Fig.90. Radiated emission: 8DPSK, Channel 78, 1 GHz - 3 GHz




Fig.91. Radiated emission: 8DPSK, Channel 78, 3 GHz - 18 GHz




Fig.92. Radiated emission (Power): 8DPSK, low channel




Fig.93. Radiated emission (Power): 8DPSK, high channel




Fig.94. Radiated emission: 8DPSK, 18 GHz - 26 GHz

A.6. Time of Occupancy (Dwell Time)

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii) RSS-210 A8.1 (4)	< 400

The measurement is made according to ANSI C63.10

Measurement Result:

For GFSK

Channel	Packet	Dwell Time (ms)		Conclusion
39	DH1	Fig.95	111.57	P
		Fig.96		
	DH3	Fig.97	191.40	P
		Fig.98		
	DH5	Fig.99	174.52	P
		Fig.100		

For $\pi/4$ DQPSK


Channel	Packet	Dwell Time (ms)		Conclusion
39	DH1	Fig.101	113.10	P
		Fig.102		
	DH3	Fig.103	165.53	P
		Fig.104		
	DH5	Fig.105	186.15	P
		Fig.106		

For 8DPSK

Channel	Packet	Dwell Time (ms)		Conclusion
39	DH1	Fig.107	109.58	P
		Fig.108		
	DH3	Fig.109	165.00	P
		Fig.110		
	DH5	Fig.111	163.18	P
		Fig.112		


Conclusion: PASS

Test graphs as below:




Date: 23.DEC.2013 17:12:56

Fig.95. Time of occupancy (Dwell Time): Channel 39, GFSK-DH1




Date: 23.DEC.2013 17:12:44

Fig.96. Number of Transmissions Measurement: Channel 39, GFSK-DH1




Date: 23.DEC.2013 17:14:16

Fig.97. Time of occupancy (Dwell Time): Channel 39, GFSK-DH3




Date: 23.DEC.2013 17:14:05

Fig.98. Number of Transmissions Measurement: Channel 39, GFSK-DH3




Date: 23.DEC.2013 17:15:32

Fig.99. Time of occupancy (Dwell Time): Channel 39, GFSK-DH5




Date: 23.DEC.2013 17:15:20

Fig.100. Number of Transmissions Measurement: Channel 39, GFSK-DH5




Date: 23.DEC.2013 17:34:26

Fig.101. Time of occupancy (Dwell Time): Channel 39, $\pi/4$ DQPSK -DH1




Date: 23.DEC.2013 17:34:14

Fig.102. Number of Transmissions Measurement: Channel 39, $\pi/4$ DQPSK -DH1




Date: 23.DEC.2013 17:35:47

Fig.103. Time of occupancy (Dwell Time): Channel 39, $\pi/4$ DQPSK -DH3




Date: 23.DEC.2013 17:35:35

Fig.104. Number of Transmissions Measurement: Channel 39, $\pi/4$ DQPSK -DH3




Date: 23.DEC.2013 17:37:06

Fig.105. Time of occupancy (Dwell Time): Channel 39, $\pi/4$ DQPSK -DH5




Date: 23.DEC.2013 17:36:54

Fig.106. Number of Transmissions Measurement: Channel 39, $\pi/4$ DQPSK -DH5




Date: 23.DEC.2013 17:55:59

Fig.107. Time of occupancy (Dwell Time): Channel 39, 8DPSK-DH1




Date: 23.DEC.2013 17:55:48

Fig.108. Number of Transmissions Measurement: Channel 39, 8DPSK -DH1




Date: 23.DEC.2013 17:57:18

Fig.109. Time of occupancy (Dwell Time): Channel 39, 8DPSK -DH3




Date: 23.DEC.2013 17:57:06

Fig.110. Number of Transmissions Measurement: Channel 39, 8DPSK -DH3



Date: 23.DEC.2013 17:58:13

Fig.111. Time of occupancy (Dwell Time): Channel 39, 8DPSK -DH5



Date: 23.DEC.2013 17:58:02

Fig.112. Number of Transmissions Measurement: Channel 39, 8DPSK -DH5

A.7. 20dB Bandwidth

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

The measurement is made according to ANSI C63.10

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.113	870.19	NA
39	Fig.114	870.19	NA
78	Fig.115	870.19	NA

For $\pi/4$ DQPSK


Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.116	1293.27	NA
39	Fig.117	1264.42	NA
78	Fig.118	1274.04	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.119	1288.46	NA
39	Fig.120	1264.42	NA
78	Fig.121	1278.85	NA


Conclusion: NA

Test graphs as below:




Date: 23.DEC.2013 17:16:06

Fig.113. 20dB Bandwidth: GFSK, Channel 0




Date: 23.DEC.2013 17:16:38

Fig.114. 20dB Bandwidth: GFSK, Channel 39




Date: 23.DEC.2013 17:17:10

Fig.115. 20dB Bandwidth: GFSK, Channel 78




Date: 23.DEC.2013 17:37:40

Fig.116. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 0




Date: 23.DEC.2013 17:38:12

Fig.117. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 39




Date: 23.DEC.2013 17:38:43

Fig.118. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78




Date: 23.DEC.2013 17:58:46

Fig.119. 20dB Bandwidth: 8DPSK, Channel 0



Date: 23.DEC.2013 17:59:18

Fig.120. 20dB Bandwidth: 8DPSK, Channel 39



Date: 23.DEC.2013 17:59:50

Fig.121. 20dB Bandwidth: 8DPSK, Channel 78

A.8. Carrier Frequency Separation

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1) RSS-210 A8.1 (2)	over 25 kHz or $(2/3) * 20\text{dB bandwidth}$

The measurement is made according to ANSI C63.10

* Comment: This limit should be over 25 kHz or $(2/3) * 20\text{dB bandwidth}$, whichever is greater.

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)	Conclusion
39	Fig.122	P

For $\pi/4$ DQPSK

Channel	Carrier frequency separation (kHz)	Conclusion
39	Fig.123	P

For 8DPSK


Channel	Carrier frequency separation (kHz)	Conclusion
39	Fig.124	P

Conclusion: PASS

Test graphs as below:


Date: 23.DEC.2013 17:19:14

Fig.122. Carrier frequency separation measurement: GFSK, Channel 39



Date: 23.DEC.2013 17:40:48

Fig.123. Carrier frequency separation measurement: $\pi/4$ DQPSK, Channel 39



Date: 23.DEC.2013 18:01:54

Fig.124. Carrier frequency separation measurement: 8DPSK, Channel 39

A.9. Number of Hopping Channels

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii) RSS-210 A8.1 (4)	At least 15 non-overlapping channels

The measurement is made according to ANSI C63.10

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.125	79	P
40~78	Fig.126		

For $\pi/4$ DQPSK


Channel	Number of hopping channels		Conclusion
0~39	Fig.127	79	P
40~78	Fig.128		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.129	79	P
40~78	Fig.130		


Conclusion: PASS

Test graphs as below:




Date: 23.DEC.2013 17:21:18

Fig.125. Number of hopping frequencies: GFSK, Channel 0 - 39




Date: 23.DEC.2013 17:23:21

Fig.126. Number of hopping frequencies: GFSK, Channel 40 - 78




Date: 23.DEC.2013 17:42:52

Fig.127. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 0 - 39




Date: 23.DEC.2013 17:44:54

Fig.128. Number of hopping frequencies: $\pi/4$ DQPSK, Channel 40 - 78



Date: 23.DEC.2013 18:03:59

Fig.129. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Date: 23.DEC.2013 18:06:01

Fig.130. Number of hopping frequencies: 8DPSK, Channel 40 - 78

A.10. AC Powerline Conducted Emission

Test Condition

Voltage (V)	Frequency (Hz)
120	60

The measurement is made according to ANSI C63.10

Measurement Method:

The EUT is connected to the travel adapter, and travel adapter is connected to the LISN directly. EUT is under test mode, and the modulation method is GFSK.

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Bluetooth (Average Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	


NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: PASS

Please refer to **ANNEX B** for test setup photo.

Test graphs as below:

Traffic




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
1.338000	40.7	GND	N	9.7	15.3	56.0
1.383000	45.1	GND	L1	9.7	10.9	56.0
1.428000	45.7	GND	L1	9.7	10.3	56.0
1.486500	41.0	GND	L1	9.7	15.0	56.0
1.531500	44.8	GND	L1	9.7	11.2	56.0
1.581000	42.2	GND	L1	9.7	13.8	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.460500	38.6	GND	L1	9.8	8.0	46.7
0.874500	35.5	GND	L1	9.7	10.5	46.0
0.969000	38.5	GND	L1	9.7	7.5	46.0
1.338000	34.2	GND	L1	9.7	11.8	46.0
1.428000	37.5	GND	L1	9.7	8.5	46.0
1.626000	32.0	GND	L1	9.7	14.0	46.0

Idle:



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
1.320000	40.2	GND	L1	9.7	15.8	56.0
1.383000	44.7	GND	L1	9.7	11.3	56.0
1.423500	44.6	GND	L1	9.7	11.4	56.0
1.473000	44.6	GND	L1	9.7	11.4	56.0
1.518000	41.6	GND	L1	9.7	14.4	56.0
1.576500	45.3	GND	L1	9.7	10.7	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.460500	38.6	GND	L1	9.8	8.1	46.7
0.919500	36.2	GND	L1	9.7	9.8	46.0
1.018500	35.4	GND	L1	9.7	10.6	46.0
1.383000	35.4	GND	L1	9.7	10.6	46.0
1.477500	38.0	GND	L1	9.7	8.0	46.0
1.576500	33.8	GND	L1	9.7	12.2	46.0

A.11.RECEIVER RADIATION EMISSION**Reference**

FCC: CFR Part 15.109, 2.1053/ RSS-Gen 7.2.2

A.11.1 Method of Measurement

The measurement procedure in ANSI C63.10-2009 is used. The EUT is placed on a 80cm height non-conductive table locating on the center of turntable. From 30MHz-1GHz, the measurement distance is 10m. For frequency range above 1GHz, the measurement distance is 3m.

The EUT is measured with travel charger and the operating mode is idle without CMU200's signaling.

A.11.2 Method of Measurement


Frequency of Emission (MHz)	Limit (dB μ V/m)	Measurement Distance (m)
30-88	30	10
88-216	33.5	10
216-960	36	10
960-1000	44	10
>1000	54	3

A. 11.3 Measurement results

IF bandwidth: 120 kHz

Idle Mode: 30MHz-1GHz


Normal RE_30M-1GHz_10m



RBW / VBW 1 MHz

Idle Mode: 1GHz-3GHz


Normal RE_1G-3GHz



RBW / VBW 1 MHz

Idle Mode: 3GHz-18GHz

Normal RE_3G-18GHz



*****END OF REPORT*****