

Appendix 5. Simulated Tissues

The body mixture consists of water, Polysorbate (Tween 20) and salt. Visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

Ingredient (% by weight)	Frequency 750/835/850/900 MHz	
	Head	Body
De-Ionized Water	52.87	71.30
Polysorbate 20	46.10	28.00
Salt	1.03	0.70

Ingredient (% by weight)	Frequency 1800/1900 MHz	
	Head	Body
De-Ionized Water	55.40	71.50
Polysorbate 20	44.22	28.00
Salt	0.38	0.50

Ingredient (% by weight)	Frequency 2450/2600 MHz	
	Head	Body
De-Ionized Water	55.75 ⁽¹⁾	71.70
Polysorbate 20	45.25 ⁽¹⁾	28.00
Salt	0.00	0.30

Stimulating Liquid for 3700 MHz to 5800 MHz are supplied and manufactured by SPEAG

Ingredient (% by weight)	Frequency
	3700 - 5800 MHz Head / Body
De-Ionized Water	~78.00
Mineral Oil	~11.00
Emulsifiers	~9.00
Additives and Salt	~2.00

Note(s):

- As per the recipe provided by National Physical Laboratory, the 2450 MHz Head Fluid recipe is mixed to the total percentage of weight is by 101.0 %.

Appendix 6. System Check and Dielectric Parameters

Dielectric Property Measurements: The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

System Performance Check: Prior to the assessment, the system was verified in the flat region of the phantom, 900 MHz, 1900 MHz, 2450 MHz and 5.0 GHz dipoles were used. A forward power of 250 mW was applied to the 900 MHz, 1900 MHz, 2450 MHz dipoles and 100 mW was applied to 5.0 GHz dipole and the system was verified to a tolerance of $\pm 5\%$ for the 900MHz, 1900MHz, 2450 MHz and 5.0 GHz dipoles.

The applicable verification normalised to 1 Watt.

System Check 900 Head								
Date: 23/06/2014								
Validation Dipole and Serial Number: D900V2 SN: 035								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	23.0°C	23.9°C	ϵ_r	41.50	42.95	3.49	5.00
				σ	0.97	0.97	0.21	5.00
				1g SAR	10.50	10.00	-4.76	5.00
				10g SAR	6.69	6.48	-3.14	5.00
Date: 23/06/2014								
Validation Dipole and Serial Number: D900V2 SN: 035								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	23.0°C	21.9°C	ϵ_r	41.50	41.51	0.02	5.00
				σ	0.97	0.94	-3.09	5.00
				1g SAR	10.50	10.04	-4.38	5.00
				10g SAR	6.69	6.52	-2.54	5.00

System Check 900 Body**Date: 23/06/2014****Validation Dipole and Serial Number: D900V2 SN: 035**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	22.0°C	20.4°C	ϵ_r	55.00	54.44	-1.02	5.00
				σ	1.05	1.00	-4.62	5.00
				1g SAR	10.40	10.28	-1.15	5.00
				10g SAR	6.73	6.76	0.45	5.00

Date: 02/06/2014**Validation Dipole and Serial Number: D900V2 SN: 035**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	23.0°C	22.0°C	ϵ_r	55.00	52.88	-3.85	5.00
				σ	1.05	1.07	1.86	5.00
				1g SAR	10.40	10.60	1.92	5.00
				10g SAR	6.73	6.84	1.63	5.00

System Check 1900 Head**Date: 23/06/2014****Validation Dipole and Serial Number: D1900V2 SN: 537**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	23.0°C	23.0°C	ϵ_r	40.00	39.26	-1.85	5.00
				σ	1.40	1.33	-4.77	5.00
				1g SAR	39.80	39.08	-1.81	5.00
				10g SAR	20.70	20.20	-2.42	5.00

Date: 25/06/2014**Validation Dipole and Serial Number :D1900V2 SN: 537**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	23.0°C	22.0°C	ϵ_r	40.00	39.26	-1.85	5.00
				σ	1.40	1.33	-4.77	5.00
				1g SAR	39.80	39.20	-1.51	5.00
				10g SAR	20.70	20.32	-1.84	5.00

System Check 1900 Body**Date: 23/06/2014****Validation Dipole and Serial Number: D1900V2 SN: 537**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	23.0°C	22.0°C	ϵ_r	53.30	52.75	-1.03	5.00
				σ	1.52	1.51	-0.42	5.00
				1g SAR	40.20	42.00	4.48	5.00
				10g SAR	21.1	22.08	4.64	5.00

Date: 26/06/2014**Validation Dipole and Serial Number: D1900V2 SN: 537**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	23.0°C	23.0°C	ϵ_r	53.30	41.62	0.29	5.00
				σ	1.52	1.50	-1.53	5.00
				1g SAR	40.20	42.00	4.48	5.00
				10g SAR	21.1	21.80	3.32	5.00

System Check 2450 Head**Date: 23/06/2014****Validation Dipole and Serial Number: D2450V2 SN: 701**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	2450	23.0°C	22.0°C	ϵ_r	39.20	39.05	-0.38	5.00
				σ	1.80	1.83	1.48	5.00
				1g SAR	53.40	53.20	-0.37	5.00
				10g SAR	24.7	24.64	-0.24	5.00

System Check 2450 Body**Date: 23/06/2014****Validation Dipole and Serial Number: D2440V2 SN: 701**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2450	23.0°C	22.0°C	ϵ_r	52.70	51.99	-1.35	5.00
				σ	1.95	2.02	3.44	5.00
				1g SAR	51.40	52.00	1.17	5.00
				10g SAR	23.90	23.84	-0.25	5.00

System Check 5200 Head								
Date: 24/06/2014 Validation Dipole and Serial Number: D5GHzV2 SN: 1016								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5200	24.0°C	24.0°C	ϵ_r	35.99	35.16	-2.31	5.00
				σ	4.66	4.78	2.47	5.00
				1g SAR	77.40	78.00	0.78	5.00
				10g SAR	22.3	22.30	0.00	5.00
System Check 5500 Head								
Date: 24/06/2014 Validation Dipole and Serial Number: D5GHzV2 SN: 1016								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5500	24.0°C	24.0°C	ϵ_r	35.60	34.68	-2.58	5.00
				σ	4.96	5.07	2.20	5.00
				1g SAR	84.80	84.00	-0.94	5.00
				10g SAR	24.1	23.50	-2.49	5.00
System Check 5800 Head								
Date: 24/06/2014 Validation Dipole and Serial Number: D5GHzV2 SN: 1016								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5800	24.0°C	24.0°C	ϵ_r	35.30	34.18	-3.17	5.00
				σ	5.27	5.38	2.05	5.00
				1g SAR	76.90	79.90	3.90	5.00
				10g SAR	22.00	22.40	1.82	5.00

System Check 5200 Body								
Date: 23/06/2014 Validation Dipole and Serial Number: D5GHzV2 SN: 1016								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5200	24.0°C	23.0°C	ϵ_r	49.01	49.35	0.69	5.00
				σ	5.30	5.31	0.18	5.00
				1g SAR	73.10	70.30	-3.83	5.00
				10g SAR	20.40	20.30	-0.49	5.00
System Check 5500 Body								
Date: 23/06/2014 Validation Dipole and Serial Number: D5GHzV2 SN: 1016								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5500	24.0°C	22.0°C	ϵ_r	48.60	48.31	-0.60	5.00
				σ	5.65	5.71	1.13	5.00
				1g SAR	79.00	81.50	3.16	5.00
				10g SAR	21.9	22.80	4.11	5.00
System Check 5800 Body								
Date: 23/06/2014 Validation Dipole and Serial Number: D5GHzV2 SN: 1016								
Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5800	24.0°C	24.0°C	ϵ_r	48.20	47.55	-1.35	5.00
				σ	6.00	6.17	2.90	5.00
				1g SAR	73.20	72.30	-1.23	5.00
				10g SAR	20.20	20.00	-0.99	5.00

Appendix 7. measurement Uncertainty Table

Measurement uncertainty tables for technologies tested.

A.7.1. Uncertainty -GSM 850 / UMTS FDD 5 / LTE Band 17 Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.510	2.510	normal (k=1)	1.0000	1.0000	2.510	2.510	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.950	2.950	normal (k=1)	1.0000	0.6400	1.888	1.888	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.840	2.840	normal (k=1)	1.0000	0.6000	1.704	1.704	5
	Combined standard uncertainty			t-distribution			9.58	9.58	>500
	Expanded uncertainty			k = 1.96			18.77	18.77	>500

A.7.2. Uncertainty Rate-GSM / GPRS / EDGE 850 / UMTS FDD 5 / LTE Band 17 Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		v _i or v _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration /Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.510	2.510	normal (k=1)	1.0000	1.0000	2.510	2.510	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.000	2.000	normal (k=1)	1.0000	0.6400	1.280	1.280	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	1.560	1.560	normal (k=1)	1.0000	0.6000	0.936	0.936	5
	Combined standard uncertainty			t-distribution			9.37	9.37	>500
	Expanded uncertainty			k = 1.96			18.36	18.36	>500

A.7.3. Uncertainty -PCS 1900 / UMTS FDD 2 Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		v _i or v _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with Regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.490	2.490	normal (k=1)	1.0000	1.0000	2.490	2.490	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	3.560	3.560	normal (k=1)	1.0000	0.6400	2.278	2.278	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.620	2.620	normal (k=1)	1.0000	0.6000	1.572	1.572	5
	Combined standard uncertainty			t-distribution			9.63	9.63	>500
	Expanded uncertainty			k = 1.96			18.88	18.88	>500

A.7.4. Uncertainty -PCS / GPRS / EDGE 1900 / UMTS FDD 2 Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		v _i or v _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	1.860	1.860	normal (k=1)	1.0000	1.0000	1.860	1.860	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.610	2.610	normal (k=1)	1.0000	0.6400	1.670	1.670	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.140	2.140	normal (k=1)	1.0000	0.6000	1.284	1.284	5
	Combined standard uncertainty			t-distribution			9.32	9.32	>500
	Expanded uncertainty			k = 1.96			18.26	18.26	>500

A.7.5. Uncertainty –Wi-Fi 2450 MHz Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		v _i or v _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.180	2.180	normal (k=1)	1.0000	1.0000	2.180	2.180	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	1.840	1.840	normal (k=1)	1.0000	0.6400	1.178	1.178	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.030	2.030	normal (k=1)	1.0000	0.6000	1.218	1.218	5
	Combined standard uncertainty			t-distribution			9.25	9.25	>500
	Expanded uncertainty			k = 1.96			18.13	18.13	>500

A.7.6. Uncertainty – Wi-Fi 2450 MHz Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		v _i or v _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.440	2.440	normal (k=1)	1.0000	1.0000	2.440	2.440	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.260	2.260	normal (k=1)	1.0000	0.6400	1.446	1.446	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.150	2.150	normal (k=1)	1.0000	0.6000	1.290	1.290	5
	Combined standard uncertainty			t-distribution			9.36	9.36	>500
	Expanded uncertainty			k = 1.96			18.35	18.35	>500

A.7.7. Uncertainty -Wi-Fi 5GHz Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		v _i or v _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.550	6.550	normal (k=1)	1.0000	1.0000	6.550	6.550	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.380	2.380	normal (k=1)	1.0000	1.0000	2.380	2.380	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	5.000	5.000	normal (k=1)	1.0000	0.6400	3.200	3.200	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	5.000	5.000	normal (k=1)	1.0000	0.6000	3.000	3.000	5
	Combined standard uncertainty			t-distribution			10.48	10.48	>250
	Expanded uncertainty			k = 1.96			20.53	20.53	>250

A.7.8. Uncertainty -Wi-Fi 5GHz Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.550	6.550	normal (k=1)	1.0000	1.0000	6.550	6.550	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	1.960	1.960	normal (k=1)	1.0000	1.0000	1.960	1.960	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	4.370	4.370	normal (k=1)	1.0000	0.6400	2.797	2.797	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	4.270	4.270	normal (k=1)	1.0000	0.6000	2.562	2.562	5
	Combined standard uncertainty			t-distribution			10.15	10.15	>450
	Expanded uncertainty			k = 1.96			19.90	19.90	>450

Appendix 8. 3G Test set-up

3G (12.K RMC / HSDPA / HSUPA) setup

To switch from 2G to 3G, on the system config screen choose Format Switch and select WCDMA. The Call Setup Screen as shown in figure 1 pops up.

Call Setup Screen									
Call Control	Active Cell Operating Mode							Call Params	
Operating Mode	UE Information IMSI: IMEI(SU): (---) Power Class:							Cell Power	
Active Cell								-35.00	
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCCH TX Power: -11.55 dBm							dBm/3.84 MHz	
								Channel Type	
	Call Processing Status Current Service Type: None RIM Status: None GMM State: None Current DPCH Offset: 0 chips							12.2k RMC	
Originate Call								Paging Service	
	HSUPA Information Rep EDCH Cat/Ext: Unrep/Unrep Last received E-TFCI: ---- Throughput: ---- kbps Acks Transmitted: ----							RB Test Mode	
Paging Parameters ▾								HSPA Parameters	
	HSDPA Information Cur UE HS-DSCH Cat: ---- Block Error Ratio: ---- % Throughput: ---- kbps Blocks Transmitted: ----							34.121 Preset Call Configs ▾	
Handovers								Channel (UARFCN) Params	
	Active Cell Idle							Sys Type: UTRA FDD	
Clear UE Info									
1 of 5	IntRef							1 of 3	

Figure 1: 3G Call Setup Screen

For a 12.2k RMC call follow the steps below.

8.1. Steps for 12.2k RMC

1. Ensure that the Operating Mode of the cell is off before setting up the instrument.
2. On the Call Setup Screen, under Call Parameters, press the button against Cell Power. The Cell Power value is set to about -35dBm to account for all the losses and ensure sufficient signal strength to the EUT.
3. The Channel Type is selected to 12.2k RMC. Press button against Channel (VARFCN) Params select the correct Downlink Channel for the required UMTS FDD Band.
4. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. Under HSDPA Parameters on page 1, press HSDPA Uplink parameters and set the Delta ACK, Delta NACK, Delta CQI values to 8. Under HSDPA Params itself, press HSDPA RB Test Mode Setup button and then the HSDPA RB Test Mode Settings and change HS-DSCH Data Pattern to All Ones.

Call Setup Screen																
Call Control	Active Cell Operating Mode							HSDPA Parms								
	UE Information IMSI: IMEI(SV): (---) Power Class:							HSDPA RB Test Mode Setup								
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm															
	HSDPA Uplink Parameters							UE Category Parameters ▾								
	<table border="1"> <thead> <tr> <th>Value</th> </tr> </thead> <tbody> <tr> <td>DeltaACK</td> </tr> <tr> <td>DeltaNACK</td> </tr> <tr> <td>DeltaCQI</td> </tr> <tr> <td>Ack-Nack Repetition Factor</td> </tr> <tr> <td>CQI Feedback Cycle (k)</td> </tr> <tr> <td>CQI Repetition Factor</td> </tr> </tbody> </table>							Value	DeltaACK	DeltaNACK	DeltaCQI	Ack-Nack Repetition Factor	CQI Feedback Cycle (k)	CQI Repetition Factor	MAC-(e)hs Parameters ▾	
	Value															
	DeltaACK															
	DeltaNACK															
	DeltaCQI															
	Ack-Nack Repetition Factor															
	CQI Feedback Cycle (k)															
CQI Repetition Factor																
							HSDPA Uplink Parameters ▾									
							Return									
Close Menu																
			Active Cell				Sys Type: UTRA FDD									
			Idle													
			IntRef						1 of 2							

Figure 2: HSDPA Parameters

5. On the Call Setup Screen, under Call Parameters, on page 2, check if the DL DTCH Data is set to All Ones. On page 3, ensure that the Receiver is set to Manual. On page 3 itself, under UL CL Power Ctrl Parameters, UL CL Power Ctrl Mode is set to All Up Bits.

Call Setup Screen										
Call Control	Active Cell Operating Mode							Call Parms		
Operating Mode								DL DTCH Data		
Active Cell								All Ones		
	UE Information IMSI: IMEI(SV): (---) Power Class:							RLC Reestablish		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm									
	Originate Call								Auto	
	Paging Parameters ▾	Call Processing Status Current Service Type: None RAI Status: None GMM State: None Current DPCH Offset: 0 chips							Call Limit State	
Handovers								Off		
Clear UE Info	HSUPA Information Rep EDCH Cat/Ext: Unrep/Unrep Last received E-TFCI: ---- Throughput: ---- kbps Acks Transmitted: ----							Call Drop Timer		
	HSDPA Information Cur UE HS-DSCH Cat: ---- Block Error Ratio: ---- % Throughput: ---- kbps Blocks Transmitted: ----							On		
								SRB Parameters ▾		
			Active Cell				Sys Type: UTRA FDD			
			Idle							
			IntRef						2 of 3	
1 of 5										

Figure 3: DL DTCH Data Parms

Call Setup Screen																									
Call Control	Active Cell Operating Mode							Call Parm																	
	UE Information IMSI: IMEI(SV): Power Class:							UE Target Power -5 dBm																	
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm							UL CL Power Ctrl Parameters																	
	UL CL Power Ctrl Parameters <table border="1"> <thead> <tr> <th>UL CL Power Ctrl Mode</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>UL CL Power Ctrl Algorithm</td> <td>All Up bits</td> </tr> <tr> <td>UL CL Power Ctrl Stepsize</td> <td>Two</td> </tr> <tr> <td></td> <td>1 dB</td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td></td> <td></td> </tr> </tbody> </table>							UL CL Power Ctrl Mode	Value	UL CL Power Ctrl Algorithm	All Up bits	UL CL Power Ctrl Stepsize	Two		1 dB									Send Step Up TPC Bit Pattern	
	UL CL Power Ctrl Mode	Value																							
	UL CL Power Ctrl Algorithm	All Up bits																							
	UL CL Power Ctrl Stepsize	Two																							
		1 dB																							
							Send Step Down TPC Bit Pattern																		
							Receiver Control																		
Close Menu																									
Active Cell Idle							Sys Type: UTRA FDD																		
IntRef							3 of 3																		

Figure 4: UL CL Power Ctrl Parameters

6. On the Call Setup Screen, under Call Control, page 2, Cell Parameters, it is ensured that PS Domain information is kept as Absent for RMC.

Call Setup Screen																											
Call Control	Active Cell Operating Mode							Call Parm																			
	UE Information IMSI: IMEI(SV): Power Class:							Cell Power -35.00 dBm/3.84 MHz																			
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm							Channel Type 12.2k RMC																			
	Cell Parameters <table border="1"> <thead> <tr> <th>Cell Parameters</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>BCCH Update Page</td> <td>Inhibit</td> </tr> <tr> <td>PS Domain Information</td> <td>Absent</td> </tr> <tr> <td>MCC (Mobile Country Code)</td> <td>1</td> </tr> <tr> <td>MNC (Mobile Network Code)</td> <td>1</td> </tr> <tr> <td>MNC (Mobile Network Code) Length</td> <td>Auto</td> </tr> <tr> <td>LAC (Local Area Code)</td> <td>1</td> </tr> <tr> <td>RAC (Routing Area Code)</td> <td>1</td> </tr> <tr> <td>Cell Identity</td> <td>1</td> </tr> </tbody> </table>							Cell Parameters	Value	BCCH Update Page	Inhibit	PS Domain Information	Absent	MCC (Mobile Country Code)	1	MNC (Mobile Network Code)	1	MNC (Mobile Network Code) Length	Auto	LAC (Local Area Code)	1	RAC (Routing Area Code)	1	Cell Identity	1	Paging Service RB Test Mode	
	Cell Parameters	Value																									
	BCCH Update Page	Inhibit																									
	PS Domain Information	Absent																									
	MCC (Mobile Country Code)	1																									
	MNC (Mobile Network Code)	1																									
	MNC (Mobile Network Code) Length	Auto																									
LAC (Local Area Code)	1																										
RAC (Routing Area Code)	1																										
Cell Identity	1																										
							HSPA Parameters																				
							34,121 Preset Call Configs																				
							Channel (UARFCN) Parm																				
Close Menu																											
Active Cell Idle							Sys Type: UTRA FDD																				
IntRef							1 of 3																				

Figure 5: Cell Parameters

7. On the same page under Uplink Parameters the maximum Uplink Transmit Power is made 24dBm. Uplink DPCH Bc/Bd Control Settings are kept at Auto for RMC. These vary according for HSDPA and HSUPA as per the values given in KDB 941225 D01 SAR test for 3G devices v02.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parm		
Additional Screens	UE Information IMSI: IMEI(SV): Power Class: (--)						Cell Power		
							-35.00		
Cell Parameters	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm						dBm/3.84 MHz		
							Channel Type		
Generator Info	Uplink Parameters PRACH Preambles: 64 PRACH Ramping Cycles(MAX): 2 Available Subchannels (Bit Mask): 000000000001 Uplink DPCH Scrambling Code: 0 Uplink DPCH Bc/Bd Control: Auto Manual Uplink DPCH Bc: 8 Manual Uplink DPCH Bd: 15 Maximum Uplink Transmit Power Level: 24 dBm Value						12.2k RNC		
							Paging Service		
Uplink Parameters	Uplink Parameters PRACH Preambles: 64 PRACH Ramping Cycles(MAX): 2 Available Subchannels (Bit Mask): 000000000001 Uplink DPCH Scrambling Code: 0 Uplink DPCH Bc/Bd Control: Auto Manual Uplink DPCH Bc: 8 Manual Uplink DPCH Bd: 15 Maximum Uplink Transmit Power Level: 24 dBm						RB Test Mode		
							HSPA Parameters		
UE Rep Meas	Uplink Parameters PRACH Preambles: 64 PRACH Ramping Cycles(MAX): 2 Available Subchannels (Bit Mask): 000000000001 Uplink DPCH Scrambling Code: 0 Uplink DPCH Bc/Bd Control: Auto Manual Uplink DPCH Bc: 8 Manual Uplink DPCH Bd: 15 Maximum Uplink Transmit Power Level: 24 dBm						34,121 Preset Call Configs		
							Channel (UARFCN) Parm		
Close Menu	Uplink Parameters PRACH Preambles: 64 PRACH Ramping Cycles(MAX): 2 Available Subchannels (Bit Mask): 000000000001 Uplink DPCH Scrambling Code: 0 Uplink DPCH Bc/Bd Control: Auto Manual Uplink DPCH Bc: 8 Manual Uplink DPCH Bd: 15 Maximum Uplink Transmit Power Level: 24 dBm						RB Test Mode		
							HSPA Parameters		
2 of 5	Uplink Parameters PRACH Preambles: 64 PRACH Ramping Cycles(MAX): 2 Available Subchannels (Bit Mask): 000000000001 Uplink DPCH Scrambling Code: 0 Uplink DPCH Bc/Bd Control: Auto Manual Uplink DPCH Bc: 8 Manual Uplink DPCH Bd: 15 Maximum Uplink Transmit Power Level: 24 dBm						34,121 Preset Call Configs		
							Channel (UARFCN) Parm		
Active Cell Idle Sys Type: UTRA FDD									
IntRef									
1 of 3									

Figure 6: Uplink Parameters

8. On page 3 under Call Control, for the RB Test Mode setup, Asymmetric RMC CN Domain is ensured to be in CS Domain for RMC call.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parm		
	UE Information IMSI: IMEI(SV): Power Class: (--)						Cell Power		
							-35.00		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm						dBm/3.84 MHz		
							Channel Type		
	RB Test Mode Settings Uplink DTCH RMC CRC Presence: Present Uplink Dummy DCCH Data: Off UE Loopback Type: Type 1 Asymmetric RMC Loopback Messaging: Close/Open Asymmetric RMC CN Domain: CS Domain Value						12.2k RNC		
							Paging Service		
Voice Call	RB Test Mode Settings Uplink DTCH RMC CRC Presence: Present Uplink Dummy DCCH Data: Off UE Loopback Type: Type 1 Asymmetric RMC Loopback Messaging: Close/Open Asymmetric RMC CN Domain: CS Domain						RB Test Mode		
							HSPA Parameters		
Close Menu	RB Test Mode Settings Uplink DTCH RMC CRC Presence: Present Uplink Dummy DCCH Data: Off UE Loopback Type: Type 1 Asymmetric RMC Loopback Messaging: Close/Open Asymmetric RMC CN Domain: CS Domain						34,121 Preset Call Configs		
							Channel (UARFCN) Parm		
3 of 5	RB Test Mode Settings Uplink DTCH RMC CRC Presence: Present Uplink Dummy DCCH Data: Off UE Loopback Type: Type 1 Asymmetric RMC Loopback Messaging: Close/Open Asymmetric RMC CN Domain: CS Domain						RB Test Mode		
							HSPA Parameters		
Active Cell Idle Sys Type: UTRA FDD									
IntRef									
1 of 3									

Figure 7: RB Test Mode Settings

9. After the test set has been set up, change the cell Operating Mode to Active Cell and originate a call.

8.2. Steps for 12.2k RMC + HSDPA/HSUPA

1. Most of the steps to be followed are as in the case of 12.2k RMC however, some of the settings need to be changed. The Channel Type is changed to 12.2k RMC+HSDPA or 12.2k RMC+HSUPA as required.
2. For HSDPA and HSUPA, the settings remain same as the case for RMC but the PS Domain is made Present for Cell Parameters (Figure 5) and RB Test Mode Setup (Figure 7).
3. The following tables taken from FCC 3G SAR procedures (KDB 941225 D01 SAR test for 3G devices v02) below were applied to the Agilent 8960 series 10 wireless communications test set which supports 3G / HSDPA release 5 / HSUPA release 6.

Sub-test 1 Setup for Release 5 HSDPA

Sub-test	β_c	β_d	B_d (SF)	$\beta_{cl} \beta_d$	$\beta_{hs}^{(1)}$	SM (dB) ⁽²⁾
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 ⁽³⁾	15/15 ⁽³⁾	64	12/15 ⁽³⁾	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Rightarrow A_{HS} = \beta_{hs}/\beta_c = 30/15 \Rightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for $\beta_{cl} \beta_d = 12/15$, $B_{hs}/\beta_c = 24/15$

Note 3: For subtest 2 the $\beta_{cl} \beta_d$ ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$

Sub-test 5 Setup for Release 6 HSUPA

Sub-test	β_c	β_d	B_d (SF)	$\beta_{cl} \beta_d$	$\beta_{hs}^{(1)}$	B_{oc}	B_{od}	B_{od} (SF)	B_{od} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	31/15	$B_{d1}: 47/15$ $B_{d2}: 47/15$	4	1	2.0	1.0	15	92
4	2/15	15/15	64	2/15	2/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	24/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Rightarrow A_{HS} = \beta_{hs}/\beta_c = 30/15 \Rightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for $\beta_{cl} \beta_d = 12/15$, $B_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH AND E-DPCCH for the MPR is based on the relative CM difference.

Note 3: For subtest 1 the $\beta_{cl} \beta_d$ ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the $\beta_{cl} \beta_d$ ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: B_{od} can not be set directly; it is set by Absolute Grant Value.

Call Setup Screen									
Call Control	Active Cell Operating Mode							Serving Grant	
Operating Mode	UE Information INSI: INEI(SU): (---) Power Class: UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm Call Processing Status Current Service Type: Mono RM Status: Abs Single Shot AG GMM State: Index 18: (95/15)^2 Current DPCCH Index 19: (106/15)^2 Index 20: (119/15)^2 Index 21: (134/15)^2 Index 22: (150/15)^2 Index 23: (168/15)^2 HSUPA Information Rep EDCH Cat/Power Class: 1 Last received Throughput: 0 kbps Acks Transmitted: 0							AG Mode	
Active Cell								Single Shot	
								Single Shot AG	
								21: (134/15)^2	
Originate Call								Send Single Shot Absolute Grant	
								RB Setup AG	
Paging Parameters								33: 4(134/15)^2	
Handovers								AG Pattern Parameters	
Clear UE Info								Return	
	Active Cell Idle Sys Type: UTRA FDD								
1 of 5	IntRef							1 of 2	

Call Setup Screen									
Call Control	Active Cell Operating Mode							Call Params	
Additional Screens	UE Information INSI: INEI(SU): (---) Power Class: UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -22.58 dBm Uplink Parameters PRACH Preambles: 64 PRACH Ramping Cycles(NMAX): 2 Available Subchannels (Bit Mask): 000000000001 Uplink DPCCH Scrambling Code: 0 Uplink DPCCH Bc/Bd Control: Manual Manual Uplink DPCCH Bc: 2 Manual Uplink DPCCH Bd: 15 Maximum Uplink Transmit Power Level: 24 dBm							Cell Power	
Cell Parameters								-35.00 dBm/3.84 MHz	
Generator Info								Channel Type	
								12.2k + HSDPA	
								Paging Service	
								RB Test Mode	
Uplink Parameters								HSPA Parameters	
UE Rep Params								34.121 Preset Call Configs	
Close Menu								Channel (UARFCN) Params	
	Cell Off Sys Type: UTRA FDD								
2 of 5	IntRef							1 of 3	

4. For HSUPA the Serving Grant Parameter needs to be set. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. On the new screen that pops up, press HSUPA and Serving Grant. The Serving Grant is set according to the table for HSPA in the KDB (AG Index). The correct AG is chosen from the Single Shot AG. Consecutively, the RG Setup AG is set as per the ratio set on Single Shot AG.

Call Setup Screen									
Call Control	Active Cell Operating Mode							Serving Grant	
Operating Mode	UE Information INSI: INEI(SV): (---) Power Class:							AG Mode	
Active Cell								Single Shot	
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm							Single Shot AG	
								31: 6(168/15)^2	
Originate Call	Call Processing Status Current Service Type: None RIM Status: None GMM State: None Current DPCH Offset: 0 chips							Send Single Shot Absolute Grant	
Paging Parameters	HSUPA Information Rep EDCH Cat/Ext: Unrep/Unrep Last received E-TFCI: ---- Throughput: ---- kbps Acks Transmitted: ----							RB Setup AG	
								37: 6(168/15)^2	
Handovers	HSDPA Information Cur UE HS-DSCH Cat: ---- Block Error Ratio: ---- % Throughput: ---- kbps Blocks Transmitted: ----							AG Pattern Parameters	
Clear UE Info	Active Cell Idle							Return	
	Sys Type: UTRA FDD								
1 of 5				IntRef					1 of 2

Figure 8: Serving Grant Example