

Appendix 5. Simulated Tissues

The body mixture consists of water, Polysorbate (Tween 20) and salt. Visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

Ingredient (% by weight)	Frequency 750/835/850/900 MHz	
	Head	Body
De-Ionized Water	52.87	71.30
Polysorbate 20	46.10	28.00
Salt	1.03	0.70

Ingredient (% by weight)	Frequency 1800/1900 MHz	
	Head	Body
De-Ionized Water	55.40	71.50
Polysorbate 20	44.22	28.00
Salt	0.38	0.50

Ingredient (% by weight)	Frequency 2450/2600 MHz	
	Head	Body
De-Ionized Water	55.75 ⁽¹⁾	71.70
Polysorbate 20	45.25 ⁽¹⁾	28.00
Salt	0.00	0.30

Stimulating Liquid for 3700 MHz to 5800 MHz are supplied and manufactured by SPEAG

Ingredient (% by weight)	Frequency
	3700 - 5800 MHz Head / Body
De-Ionized Water	~78.00
Mineral Oil	~11.00
Emulsifiers	~9.00
Additives and Salt	~2.00

Note(s):

- As per the recipe provided by National Physical Laboratory, the 2450 MHz Head Fluid recipe is mixed to the total percentage of weight is by 101.0 %.

Appendix 6. System Check and Dielectric Parameters

Dielectric Property Measurements: The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

System Performance Check: Prior to the assessment, the system was verified in the flat region of the phantom, 750 MHz, 900 MHz, 1800 MHz, 1900 MHz, 2450 MHz, 2600 MHz and 5.0 GHz dipoles were used. A forward power of 250 mW was applied to the 750 MHz, 900 MHz, 1800 MHz, 1900 MHz, 2450 MHz, 2600 MHz dipoles and 100 mW was applied to 5.0 GHz dipole and the system was verified to a tolerance of $\pm 5\%$ for the 900MHz, 1800MHz, 1900MHz, 2450 MHz, 2600 MHz and 5.0 GHz dipoles.

The applicable verification normalised to 1 Watt.

System Check 750 Head

Date: 02/07/2014

Validation Dipole and Serial Number: D750V3 SN: 1011

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	750	23.1°C	22.4°C	ϵ_r	41.96	41.77	-0.45	5.00
				σ	0.89	0.85	-3.98	5.00
				1g SAR	8.48	8.48	0.00	5.00
				10g SAR	5.57	5.68	1.97	5.00

System Check 750 Body

Date: 03/07/2014

Validation Dipole and Serial Number: D750V3 SN: 1011

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	750	22.7°C	22..7°C	ϵ_r	55.55	53.67	-3.39	5.00
				σ	0.96	0.94	-2.45	5.00
				1g SAR	8.84	8.72	-1.36	5.00
				10g SAR	5.84	5.88	0.68	5.00

System Check 900 Head

Date: 30/06/2014

Validation Dipole and Serial Number: D900V2 SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	23.0°C	22.°C	ϵ_r	41.50	41.83	0.80	5.00
				σ	0.97	0.96	-1.34	5.00
				1g SAR	10.50	10.36	-1.33	5.00
				10g SAR	6.69	6.76	1.05	5.00

Date: 03/07/2014

Validation Dipole and Serial Number: D900V2 SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	22.6.0°C	22.4°C	ϵ_r	41.50	40.91	-1.42	5.00
				σ	0.97	0.95	-1.60	5.00
				1g SAR	10.50	10.08	-4.00	5.00
				10g SAR	6.69	6.52	-2.54	5.00

System Check 900 Body

Date: 30/06/2014

Validation Dipole and Serial Number: D900V2 SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	23.0°C	22.6°C	ϵ_r	55.00	53.42	-2.87	5.00
				σ	1.05	1.01	-3.62	5.00
				1g SAR	10.40	10.52	1.15	5.00
				10g SAR	6.73	6.88	2.23	5.00

Date: 03/07/2014

Validation Dipole and Serial Number: D900V2 SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	23.0°C	22.5°C	ϵ_r	55.00	53.75	-2.27	5.00
				σ	1.05	1.07	2.24	5.00
				1g SAR	10.40	10.08	-3.08	5.00
				10g SAR	6.73	6.52	-3.12	5.00

System Check 1800 Head

Date: 30/06/2014

Validation Dipole and Serial Number: D1800V2 SN: 2d009

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1800	24.0°C	23.2°C	ϵ_r	40.00	38.38	-4.05	5.00
				σ	1.40	1.38	-1.14	5.00
				1g SAR	37.30	36.92	-1.02	5.00
				10g SAR	19.70	19.84	0.71	5.00

System Check 1800 Body

Date: 30/06/2014

Validation Dipole and Serial Number :D1800V2 SN: 2d009

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1800	24.0°C	22.7°C	ϵ_r	53.30	50.81	-4.67	5.00
				σ	1.52	1.57	3.09	5.00
				1g SAR	36.50	35.96	-1.48	5.00
				10g SAR	19.50	19.48	-0.10	5.00

System Check 1900 Head

Date: 30/06/2014

Validation Dipole and Serial Number: D1900V2 SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	23.0°C	23.8°C	ϵ_r	40.00	39.68	-0.80	5.00
				σ	1.40	1.34	-4.32	5.00
				1g SAR	39.80	39.36	-1.11	5.00
				10g SAR	20.70	20.44	-1.26	5.00

Date: 30/06/2014

Validation Dipole and Serial Number: D1900V2 SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	23.0°C	23.8°C	ϵ_r	40.00	39.14	-2.15	5.00
				σ	1.40	1.34	-4.10	5.00
				1g SAR	39.80	39.64	-0.40	5.00
				10g SAR	20.70	20.52	-0.87	5.00

System Check 1900 Body

Date: 30/06/2014

Validation Dipole and Serial Number: D1900V2 SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	23.0°C	22.4°C	ϵ_r	53.30	53.40	0.19	5.00
				σ	1.52	1.53	0.63	5.00
				1g SAR	40.20	41.20	2.49	5.00
				10g SAR	21.1	21.44	1.61	5.00

Date: 30/06/2014

Validation Dipole and Serial Number: D1900V2 SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	23.0°C	24.0°C	ϵ_r	53.30	53.02	-0.53	5.00
				σ	1.52	1.47	-3.40	5.00
				1g SAR	40.20	39.60	-1.49	5.00
				10g SAR	21.1	20.84	-1.23	5.00

Date: 03/07/2014

Validation Dipole and Serial Number: D1900V2 SN: 540

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	23.0°C	24.0°C	ϵ_r	53.30	52.30	-1.88	5.00
				σ	1.52	1.49	-1.88	5.00
				1g SAR	40.20	38.96	-3.08	5.00
				10g SAR	21.1	20.16	-4.45	5.00

System Check 2450 Head

Date: 30/06/2014

Validation Dipole and Serial Number: D2450V2 SN: 701

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	2450	24.0°C	23.3°C	ϵ_r	39.20	39.84	1.63	5.00
				σ	1.80	1.81	0.42	5.00
				1g SAR	53.40	54.00	1.12	5.00
				10g SAR	24.70	24.72	0.08	5.00

System Check 2450 Body

Date: 07/07/2014

Validation Dipole and Serial Number: D2440V2 SN: 701

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2450	23.5°C	23.3°C	ϵ_r	52.70	50.78	-3.64	5.00
				σ	1.95	2.04	4.56	5.00
				1g SAR	51.40	51.60	0.39	5.00
				10g SAR	23.90	23.64	-1.09	5.00

System Check 2600 Head**Date: 01/07/2014****Validation Dipole and Serial Number: D2600V2 SN: 1046**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	2600	23.3°C	23.5°C	ϵ_r	39.00	39.35	0.90	5.00
				σ	1.96	1.98	0.82	5.00
				1g SAR	57.60	60.00	4.17	5.00
				10g SAR	25.80	26.48	2.64	5.00

System Check 2600 Body**Date: 03/07/2014****Validation Dipole and Serial Number: D2600V2 SN: 1046**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2600	23.0°C	22.5°C	ϵ_r	52.50	51.12	-2.63	5.00
				σ	2.16	2.21	2.38	5.00
				1g SAR	56.80	59.20	4.23	5.00
				10g SAR	25.20	25.72	2.06	5.00

Date: 07/07/2014**Validation Dipole and Serial Number: D2600V2 SN: 1046**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2600	23.0°C	22.5°C	ϵ_r	52.50	51.09	-2.69	5.00
				σ	2.16	2.90	1.58	5.00
				1g SAR	56.80	56.80	0.00	5.00
				10g SAR	25.20	24.44	-3.02	5.00

System Check 5200 Head

Date: 01/07/2014

Validation Dipole and Serial Number: D5GHzV2 SN: 1016

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5200	24.0°C	23.5°C	ϵ_r	35.99	36.31	0.89	5.00
				σ	4.66	4.69	0.74	5.00
				1g SAR	77.40	75.90	-1.94	5.00
				10g SAR	22.30	21.90	-1.79	5.00

Date: 01/07/2014

Validation Dipole and Serial Number: D5GHzV2 SN: 1016

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5500	22.0	23.5°C	ϵ_r	35.60	35.89	0.81	5.00
				σ	4.96	5.03	1.40	5.00
				1g SAR	84.80	82.40	-2.83	5.00
				10g SAR	24.10	23.40	-2.90	5.00

Date: 01/07/2014

Validation Dipole and Serial Number: D5GHzV2 SN: 1016

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5800	22.0	23.5°C	ϵ_r	35.30	35.60	0.85	5.00
				σ	5.27	5.36	1.68	5.00
				1g SAR	76.90	78.50	-2.08	5.00
				10g SAR	22.00	22.50	2.27	5.00

System Check 5200 Body

Date: 30/06/2014

Validation Dipole and Serial Number: D5GHzV2 SN: 1016

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5200	23.5°C	22.0°C	ϵ_r	49.01	49.01	0.00	5.00
				σ	5.30	5.15	-2.87	5.00
				1g SAR	73.10	69.60	-4.79	5.00
				10g SAR	20.40	19.90	-2.45	5.00

Date: 30/06/2014

Validation Dipole and Serial Number: D5GHzV2 SN: 1016

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5500	23.5	22.0°C	ϵ_r	48.60	48.46	-0.29	5.00
				σ	5.65	5.64	-0.22	5.00
				1g SAR	79.00	76.60	-2.91	5.00
				10g SAR	21.90	21.70	-0.91	5.00

Date: 30/06/2014

Validation Dipole and Serial Number: D5GHzV2 SN: 1016

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5800	23.5	22.0°C	ϵ_r	48.20	47.75	-0.93	5.00
				σ	6.00	6.13	2.14	5.00
				1g SAR	75.20	73.20	2.73	5.00
				10g SAR	20.20	21.10	4.46	5.00

Appendix 7. Measurement Uncertainty Table

Measurement uncertainty tables for technologies tested.

A.7.1. GSM 850 / UMTS FDD 5 / LTE Band 5 / LTE Band 17 Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.510	2.510	normal (k=1)	1.0000	1.0000	2.510	2.510	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.950	2.950	normal (k=1)	1.0000	0.6400	1.888	1.888	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.840	2.840	normal (k=1)	1.0000	0.6000	1.704	1.704	5
	Combined standard uncertainty			t-distribution			9.58	9.58	>500
	Expanded uncertainty			k = 1.96			18.77	18.77	>500

A.7.2. GSM / GPRS / EDGE 850 / UMTS FDD 5 / LTE Band 5 / LTE Band 17 Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration /Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.510	2.510	normal (k=1)	1.0000	1.0000	2.510	2.510	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.000	2.000	normal (k=1)	1.0000	0.6400	1.280	1.280	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	1.560	1.560	normal (k=1)	1.0000	0.6000	0.936	0.936	5
	Combined standard uncertainty			t-distribution			9.37	9.37	>500
	Expanded uncertainty			k = 1.96			18.36	18.36	>500

A.7.3. UMTS FDD 4 / LTE Band 4 Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration/ Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.440	2.440	normal (k=1)	1.0000	1.0000	2.440	2.440	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.120	2.120	normal (k=1)	1.0000	0.6400	1.357	1.357	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.270	2.270	normal (k=1)	1.0000	0.6000	1.362	1.362	5
	Combined standard uncertainty			t-distribution			9.41	9.41	>500
	Expanded uncertainty			k = 1.96			18.45	18.45	>500

A.7.4. UMTS FDD 4 / LTE Band 4 Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration/ Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.460	2.460	normal (k=1)	1.0000	1.0000	2.460	2.460	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.210	2.210	normal (k=1)	1.0000	0.6400	1.414	1.414	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.150	2.150	normal (k=1)	1.0000	0.6000	1.290	1.290	5
	Combined standard uncertainty			t-distribution			9.42	9.42	>500
	Expanded uncertainty			k = 1.96			18.45	18.45	>500

A.7.5. PCS 1900 / UMTS FDD 2 / LTE Band 2 Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with Regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.490	2.490	normal (k=1)	1.0000	1.0000	2.490	2.490	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	3.560	3.560	normal (k=1)	1.0000	0.6400	2.278	2.278	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.620	2.620	normal (k=1)	1.0000	0.6000	1.572	1.572	5
	Combined standard uncertainty			t-distribution			9.63	9.63	>500
	Expanded uncertainty			k = 1.96			18.88	18.88	>500

A.7.6. PCS / GPRS / EDGE 1900 / UMTS FDD 2 / LTE Band 2 Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	1.730	1.730	Rectangular	1.7321	1.0000	0.999	0.999	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	1.860	1.860	normal (k=1)	1.0000	1.0000	1.860	1.860	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.610	2.610	normal (k=1)	1.0000	0.6400	1.670	1.670	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.140	2.140	normal (k=1)	1.0000	0.6000	1.284	1.284	5
	Combined standard uncertainty			t-distribution			9.32	9.32	>500
	Expanded uncertainty			k = 1.96			18.26	18.26	>500

A.7.7. LTE Band 7 / Wi-Fi 2450 MHz Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.180	2.180	normal (k=1)	1.0000	1.0000	2.180	2.180	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	1.840	1.840	normal (k=1)	1.0000	0.6400	1.178	1.178	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.030	2.030	normal (k=1)	1.0000	0.6000	1.218	1.218	5
	Combined standard uncertainty			t-distribution			9.25	9.25	>500
	Expanded uncertainty			k = 1.96			18.13	18.13	>500

A.7.8. LTE Band 7 / Wi-Fi 2450 MHz Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.000	6.000	normal (k=1)	1.0000	1.0000	6.000	6.000	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.440	2.440	normal (k=1)	1.0000	1.0000	2.440	2.440	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	2.260	2.260	normal (k=1)	1.0000	0.6400	1.446	1.446	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	2.150	2.150	normal (k=1)	1.0000	0.6000	1.290	1.290	5
	Combined standard uncertainty			t-distribution			9.36	9.36	>500
	Expanded uncertainty			k = 1.96			18.35	18.35	>500

A.7.9. Wi-Fi 5GHz Head Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		u _i or u _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.550	6.550	normal (k=1)	1.0000	1.0000	6.550	6.550	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	2.380	2.380	normal (k=1)	1.0000	1.0000	2.380	2.380	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	5.000	5.000	normal (k=1)	1.0000	0.6400	3.200	3.200	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	5.000	5.000	normal (k=1)	1.0000	0.6000	3.000	3.000	5
	Combined standard uncertainty			t-distribution			10.48	10.48	>250
	Expanded uncertainty			k = 1.96			20.53	20.53	>250

A.7.10. Wi-Fi 5GHz Body Configuration 1g

Type	Source of uncertainty	+ Value	- Value	Probability Distribution	Divisor	C _i (1g)	Standard Uncertainty		U _i or U _{eff}
							+ u (%)	- u (%)	
B	Probe calibration	6.550	6.550	normal (k=1)	1.0000	1.0000	6.550	6.550	∞
B	Axial Isotropy	0.250	0.250	normal (k=1)	1.0000	1.0000	0.250	0.250	∞
B	Hemispherical Isotropy	1.300	1.300	normal (k=1)	1.0000	1.0000	1.300	1.300	∞
B	Spatial Resolution	0.500	0.500	Rectangular	1.7321	1.0000	0.289	0.289	∞
B	Boundary Effect	0.769	0.769	Rectangular	1.7321	1.0000	0.444	0.444	∞
B	Linearity	0.600	0.600	Rectangular	1.7321	1.0000	0.346	0.346	∞
B	Detection Limits	0.200	0.200	Rectangular	1.7321	1.0000	0.115	0.115	∞
B	Readout Electronics	0.160	0.160	normal (k=1)	1.0000	1.0000	0.160	0.160	∞
B	Response Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	Integration Time	0.000	0.000	Rectangular	1.7321	1.0000	0.000	0.000	∞
B	RF Ambient conditions	3.000	3.000	Rectangular	1.7321	1.0000	1.732	1.732	∞
B	Probe Positioner Mechanical Restrictions	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Probe Positioning with regard to Phantom Shell	2.850	2.850	Rectangular	1.7321	1.0000	1.645	1.645	∞
B	Extrapolation and integration / Maximum SAR evaluation	5.080	5.080	Rectangular	1.7321	1.0000	2.933	2.933	∞
A	Test Sample Positioning	1.960	1.960	normal (k=1)	1.0000	1.0000	1.960	1.960	10
A	Device Holder uncertainty	0.154	0.154	normal (k=1)	1.0000	1.0000	0.154	0.154	10
B	Phantom Uncertainty	4.000	4.000	Rectangular	1.7321	1.0000	2.309	2.309	∞
B	Drift of output power	5.000	5.000	Rectangular	1.7321	1.0000	2.887	2.887	∞
B	Liquid Conductivity (target value)	5.000	5.000	Rectangular	1.7321	0.6400	1.848	1.848	∞
A	Liquid Conductivity (measured value)	4.370	4.370	normal (k=1)	1.0000	0.6400	2.797	2.797	5
B	Liquid Permittivity (target value)	5.000	5.000	Rectangular	1.7321	0.6000	1.732	1.732	∞
A	Liquid Permittivity (measured value)	4.270	4.270	normal (k=1)	1.0000	0.6000	2.562	2.562	5
	Combined standard uncertainty			t-distribution			10.15	10.15	>450
	Expanded uncertainty			k = 1.96			19.90	19.90	>450

Appendix 8. 3G Test set-up

3G (12.K RMC / HSDPA / HSUPA) setup

To switch from 2G to 3G, on the system config screen choose Format Switch and select WCDMA. The Call Setup Screen as shown in figure 1 pops up.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Params		
Operating Mode	UE Information IMSI: IMEI(SV): (---) Power Class:						Cell Power		
Active Cell							-35.00		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm						dBm/3.84 MHz		
							Channel Type		
	Call Processing Status Current Service Type: None MM Status: None GMM State: None Current DPCH Offset: 0 chips						12.2k RMC		
Originate Call							Paging Service		
	HSUPA Information Rep EDCH Cat/Ext: Unrep/Unrep Last received E-TFCI: ---- Throughput: ---- kbps Acks Transmitted: ----						RB Test Mode		
							HSPA Parameters		
Paging Parameters ▾	HSDPA Information Cur UE HS-DSCH Cat: ---- Block Error Ratio: ---- % Throughput: ---- kbps Blocks Transmitted: ----						34.121 Preset Call Configs ▾		
							Channel (UARFCN) Params		
Handovers	Active Cell Idle						Sys Type: UTRA FDD		
Clear UE Info	IntRef						1 of 3		
1 of 5									

Figure 1: 3G Call Setup Screen

For a 12.2k RMC call follow the steps below.

8.1. Steps for 12.2k RMC

1. Ensure that the Operating Mode of the cell is off before setting up the instrument.
2. On the Call Setup Screen, under Call Parameters, press the button against Cell Power. The Cell Power value is set to about -35dBm to account for all the losses and ensure sufficient signal strength to the EUT.
3. The Channel Type is selected to 12.2k RMC. Press button against Channel (UARFCN) Params select the correct Downlink Channel for the required UMTS FDD Band.
4. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. Under HSDPA Parameters on page 1, press HSDPA Uplink parameters and set the Delta ACK, Delta NACK, Delta CQI values to 8. Under HSDPA Params itself, press HSDPA RB Test Mode Setup button and then the HSDPA RB Test Mode Settings and change HS-DSCH Data Pattern to All Ones.

Call Setup Screen									
Call Control	Active Cell Operating Mode						HSDPA Parms		
	UE Information IMSI: IMEI(SV): (---) Power Class:						HSDPA RB Test Mode Setup		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm								
	HSDPA Uplink Parameters						Value		
	DeltaACK						8		
	DeltaNACK						8		
	DeltaCQI						8		
	Ack-Nack Repetition Factor						1		
	CQI Feedback Cycle (k)						2 ms		
	CQI Repetition Factor						1		
	Close Menu							Return	
		Active Cell				Sys Type: UTRA FDD			
		Idle							
		IntRef						1 of 2	

Figure 2: HSDPA Parameters

5. On the Call Setup Screen, under Call Parameters, on page 2, check if the DL DTCH Data is set to All Ones. On page 3, ensure that the Receiver is set to Manual. On page 3 itself, under UL CL Power Ctrl Parameters, UL CL Power Ctrl Mode is set to All Up Bits.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parms		
Operating Mode							DL DTCH Data		
Active Cell	UE Information IMSI: IMEI(SV): (---) Power Class:						All Ones		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm						RLC Reestablish		
							Auto		
Originate Call	Call Processing Status Current Service Type: None MM Status: None GMM State: None Current DPCH Offset: 0 chips						Call Limit State		
Paging Parameters							Off		
Handovers	HSUPA Information Rep EDCH Cat/Ext: Unrep/Unrep Last received E-TFCI: ---- Throughput: ---- kbps Acks Transmitted: ----						Call Drop Timer		
	HSDPA Information Cur UE HS-DSCH Cat: ---- Block Error Ratio: ---- % Throughput: ---- kbps Blocks Transmitted: ----						On		
Clear UE Info							SRB Parameters		
		Active Cell				Sys Type: UTRA FDD			
		Idle							
		IntRef						2 of 3	
1 of 5									

Figure 3: DL DTCH Data Parms

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parm		
	UE Information IMSI: IMEI(SU): Power Class: (--)						UE Target Power -5 dBm		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCCH TX Power: -11.55 dBm						UL CL Power Ctrl Parameters		
	UL CL Power Ctrl Parameters Value						Send Step Up TPC Bit Pattern		
	UL CL Power Ctrl Mode All Up bits						Send Step Down TPC Bit Pattern		
	UL CL Power Ctrl Algorithm Two						Receiver Control		
	UL CL Power Ctrl Stepsize 1 dB								
Close Menu									
		Active Cell		Sys Type: UTRA FDD					
		Idle							
		IntRef							
						3 of 3			

Figure 4: UL CL Power Ctrl Parameters

6. On the Call Setup Screen, under Call Control, page 2, Cell Parameters, it is ensured that PS Domain information is kept as Absent for RMC.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parm		
Additional Screens Cell Parameters Generator Info Uplink Parameters UE Rep Neas Close Menu	UE Information IMSI: IMEI(SU): Power Class: (--)						Cell Power -35.00		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCCH TX Power: -11.55 dBm						dBm/3.84 MHz		
	Cell Parameters Value						Channel Type 12.2k RMC		
	BCCH Update Page Inhibit						Paging Service RB Test Mode		
	PS Domain Information Absent						HSPA Parameters		
	NCC (Mobile Country Code) 1						34,121 Preset Call Configs		
	NMC (Mobile Network Code) 1						Channel (UARFCN) Parm		
	NMC (Mobile Network Code) Length Auto								
	LAC (Local Area Code) 1								
	RAC (Routing Area Code) 1								
Cell Identity 1									
		Active Cell		Sys Type: UTRA FDD					
		Idle							
		IntRef							
						1 of 3			

Figure 5: Cell Parameters

7. On the same page under Uplink Parameters the maximum Uplink Transmit Power is made 24dBm. Uplink DPCH Bc/Bd Control Settings are kept at Auto for RMC. These vary according for HSDPA and HSUPA as per the values given in KDB 941225 D01 SAR test for 3G devices v02.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parns		
Additional Screens	UE Information IMSI: IMEI(SV): Power Class:						Cell Power		
							-35.00		
Cell Parameters							dBm/3.84 MHz		
							Channel Type		
							12.2k RMC		
Generator Info	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm						Paging Service		
							RB Test Mode		
Uplink Parameters	Uplink Parameters				Value				
	PRACH Preambles				64		HSPA Parameters		
	PRACH Ramping Cycles(MAX)				2				
	Available Subchannels (Bit Mask)				000000000001				
	UE Rep Meas	Uplink DPCH Scrambling Code				0		34,121 Preset Call Configs	
Uplink DPCH Bc/Bd Control				Auto					
Close Menu	Manual Uplink DPCH Bc				8		Channel (UARFCN) Parns		
	Manual Uplink DPCH Bd				15				
	Maximum Uplink Transmit Power Level				24 dBm				
	Active Cell				Sys Type: UTRA FDD				
	Idle								
2 of 5				IntRef					1 of 3

Figure 6: Uplink Parameters

8. On page 3 under Call Control, for the RB Test Mode setup, Asymmetric RMC CN Domain is ensured to be in CS Domain for RMC call.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parns		
	UE Information IMSI: IMEI(SV): Power Class:						Cell Power		
							-35.00		
							dBm/3.84 MHz		
							Channel Type		
							12.2k RMC		
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm						Paging Service		
							RB Test Mode		
	RB Test Mode Settings				Value				
	Uplink DTCH RMC CRC Presence				Present		HSPA Parameters		
	Uplink Dummy DCCH Data				Off				
UE Loopback Type				Type 1					
Voice Call	Asymmetric RMC Loopback Messaging				Close/Open		34,121 Preset Call Configs		
	Asymmetric RMC CN Domain				CS Domain				
Close Menu							Channel (UARFCN) Parns		
	Active Cell				Sys Type: UTRA FDD				
	Idle								
3 of 5				IntRef					1 of 3

Figure 7: RB Test Mode Settings

9. After the test set has been set up, change the cell Operating Mode to Active Cell and originate a call.

8.2. Steps for 12.2k RMC + HSDPA/HSUPA

1. Most of the steps to be followed are as in the case of 12.2k RMC however, some of the settings need to be changed. The Channel Type is changed to 12.2k RMC+HSDPA or 12.2k RMC+HSUPA as required.

2. For HSDPA and HSUPA, the settings remain same as the case for RMC but the PS Domain is made Present for Cell Parameters (Figure 5) and RB Test Mode Setup (Figure 7).
3. The following tables taken from FCC 3G SAR procedures (KDB 941225 D01 SAR test for 3G devices v02) below were applied to the Agilent 8960 series 10 wireless communications test set which supports 3G / HSDPA release 5 / HSUPA release 6.

Sub-test 1 Setup for Release 5 HSDPA

Sub-test	β_c	β_d	B_d (SF)	$\beta_c \beta_d$	$\beta_{hs}^{(1)}$	SM (dB) ⁽²⁾
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 ⁽³⁾	15/15 ⁽³⁾	64	12/15 ⁽³⁾	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for $\beta_c \beta_d = 12/15$, $B_{hs}/\beta_c = 24/15$

Note 3: For subtest 2 the $\beta_c \beta_d$ ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$

Sub-test 5 Setup for Release 6 HSUPA

Sub-test	β_c	β_d	B_d (SF)	$\beta_c \beta_d$	$\beta_{hs}^{(1)}$	B_{oc}	B_{od}	B_{od} (SF)	B_{od} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	31/15	$B_{dl1}: 47/15$ $B_{dl2}: 47/15$	4	1	2.0	1.0	15	92
4	2/15	15/15	64	2/15	2/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	24/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for $\beta_c \beta_d = 12/15$, $B_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH AND E-DPCCH for the MPR is based on the relative CM difference.

Note 3: For subtest 1 the $\beta_c \beta_d$ ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the $\beta_c \beta_d$ ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: B_{od} can not be set directly; it is set by Absolute Grant Value.

Call Setup Screen									
Call Control		Active Cell Operating Mode						Serving Grant	
Operating Mode		UE Information INSI: INEI(SV): (---) Power Class:						AG Mode	
Active Cell								Single Shot	
Originate Call		UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm						Single Shot AG	
								21: (134/15)^2	
Paging Parameters		Call Processing Status Current Service Type: None MM Status: Abs Single Shot AG GMM State: Index 18: (95/15)^2 Current DPCCH: Index 19: (106/15)^2 HSUPA In: Index 20: (119/15)^2 Rep EDCH Cat: Index 21: (134/15)^2 Last received: Index 22: (150/15)^2 Throughput: Index 23: (168/15)^2 Acks Transmitted:						Send Single Shot Absolute Grant	
Handovers		Information DPCCH Cat: ---- Ratio: ---- % : ---- kbps Transmitted: ----						RB Setup AG	
Clear UE Info		Active Cell Idle Sys Type: UTRA FDD						AG Pattern Parameters	
1 of 5		IntRef						Return	
								1 of 2	

Call Setup Screen									
Call Control		Active Cell Operating Mode						Call Params	
Additional Screens		UE Information INSI: INEI(SV): (---) Power Class:						Cell Power	
Cell Parameters								-35.00	
Generator Info		UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -22.58 dBm						dBm/3.84 MHz	
Uplink Parameters								Channel Type	
Uplink Parameters		Uplink Parameters PRACH Preambles: 64 PRACH Ramping Cycles(MAX): 2 Available Subchannels (Bit Mask): 000000000001 Uplink DPCCH Scrambling Code: 0 Uplink DPCCH Bc/Bd Control: Manual Manual Uplink DPCCH Bc: 2 Manual Uplink DPCCH Bd: 15 Maximum Uplink Transmit Power Level: 24 dBm						12.2k + HSDPA	
UE Rep Params								Paging Service	
Close Menu		Cell Off Sys Type: UTRA FDD						RB Test Mode	
2 of 5		IntRef						HSPA Parameters	
								34.121 Preset Call Configs	
								Channel (UARFCN) Params	
								1 of 3	

4. For HSUPA the Serving Grant Parameter needs to be set. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. On the new screen that pops up, press HSUPA and Serving Grant. The Serving Grant is set according to the table for HSPA in the KDB (AG Index). The correct AG is chosen from the Single Shot AG. Consecutively, the RG Setup AG is set as per the ratio set on Single Shot AG.

Call Setup Screen									
Call Control	Active Cell Operating Mode							Serving Grant	
Operating Mode	UE Information IMSI: IMEI(SV): Power Class:							AG Mode	
Active Cell								Single Shot	
								Single Shot AG	
								31: 6(168/15)^2	
	UE Expected Open Loop Transmit Power Initial PRACH TX Power: -60.00 dBm Initial DPCH TX Power: -11.55 dBm								
Originate Call								Send Single Shot Absolute Grant	
	Call Processing Status Current Service Type: None MM Status: None GMM State: None Current DPCH Offset: 0 chips							RB Setup AG	
Paging Parameters ▾								37: 6(168/15)^2	
Handovers	HSUPA Information Rep EDCH Cat/Ext: Unrep/Unrep Last received E-TFCI: ---- Throughput: ---- kbps Acks Transmitted: ----				HSDPA Information Cur UE HS-DSCH Cat: ---- Block Error Ratio: ---- % Throughput: ---- kbps Blocks Transmitted: ----			AG Pattern Parameters ▾	
Clear UE Info								Return	
			Active Cell			Sys Type: UTRA FDD			
			Idle						
1 of 5				IntRef					1 of 2

Figure 8: Serving Grant Example

Appendix 9. CAT24 Test set-up

A.9.1. Establish a DC-HSDPA RB Test Mode Connection with DL 42Mbps

RB (radio bearer) test mode is a special, defined-channel configuration designed to simplify the testing environment. Since W-CDMA is an incredibly flexible system, defined radio bearers, called RMCs (reference measurement channels) simplify which configurations need to be tested for RF performance.

RB test mode provides the ability to set up a standalone channel configuration originating from the 8960 via call-processing. The direction of the call setup is always from the 8960 to the UE. This is the typical RF test that is used throughout the lifecycle of a device's design process. Using RB test mode is attractive to device manufacturers because it does not require extra software to control the UE. In this type of call connection, the radio bearer (within the 8960) essentially controls the UE during test.

A.9.1.1 Configure 8960

1. Press **Operating Mode (F1)**, select **Cell Off** operating mode.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parm		
Operating Mode	UE Information						Cell Power		
Cell Off	INIS:		Power Class:		Detected PRACH Sig: ----		-75.00		
	INEI(SV):		---				dBm/3.84 MHz		
	Called Party Number:						Channel Type		
	UE Expected Open Loop Transmit Power						12.2k RNC		
	Init PRACH TX Pow: -22.70 dBm			Init DPCCH TX Pow: -11.55 dBm			Paging Service		
Originate Call	Current Service Type						RB Test Mode		
	None								
Paging Parameters	Call Processing Status						HSPA Parameters		
	RRC State:		Operating Mode		Per State: Off				
	MM Status:		Active Cell		Mode State: Off				
	GMM State:		FDD Test		Offset: 0 chips				
Handovers	HSPA In		Cell Off		Information		34.121 Preset Call Configs		
	UE Rep E-DCH				SCH Cat: 14				
	Last Happy Bit				Ratio: ---- %				
Clear UE Info	Throughput:				kbps		Channel (UARFCN) Parm		
	ACKs Transmitt				mitted: ----				
	Background		Cell Off		Sys Type: UTRA FDD				
					Logging: No Conn				
1 of 5			IntRef Offset				1 of 3		

2. Set the **Channel type** to **12.2k + HSDPA**.

3. Set the downlink channel code. In order to achieve the 42 Mbps maximum downlink throughput, you have to set up 15 HS-PDSCHs which will possibly cause a code collision.

To easily configure the downlink 15 HS-PDSCH for a maximum throughput, use the code preset to configure the code channels for both the serving cell and the secondary serving cell.

Select **Call Control 2 of 6** -> **Generator Info (F3)** -> **Downlink Channel Configs (F4)** -> **DL Chan code Preset Configs (F5)**, choose **34.121 Tables E.6.2.3,4 (HSDPA 15 HS-PDSCHs)**.

Set the **Conn S-CCPCH Cfg** to **Off** to avoid the code collision.

To see the channel code allocation for the serving cell and the secondary serving cell, select **Additional Gen Info Screens (F1)** -> **DC-HSDPA DL Code Chan Info (F4)**.

Call Setup Screen									
Screen Ctrl	DC-HSDPA DL Code Channel Information							Call Parms	
DL Code Channel Info Screen	Serving Cell Primary Scrambling Code: 0							Cell Power	
	Secondary Serving Cell Primary Scrambling Code: 2							-75.00	
Generated Power Info Screen	Channel	Serving Cell DL Chan Info			Sec Cell DL Chan Info			dBm/3.84 MHz	
	Channel	Level (dB)	Current	Desired	OVSF	Chan Code	Level (dB)	Current	Desired
OCNS Info Screen	CPICH:	Off	-3.30	256	0	Off	Off	256	0
	P-CCPCH/SCH:	Off	-5.30	256	1	Off	Off	256	1
DC-HSDPA DL Code Chan Info	S-CCPCH:	Off	-10.30	64	2	Off	Off	256	2
	PICH:	Off	-8.30	256	2	Off	Off	256	2
Return	AICH:	Off	-9.30	256	3	Off	Off	256	3
	(F-)DPCH:	Off	Off	128	7	Off	Off	128	7
Channel (UARFCN) Parms	E-AGCH:	Off	Off	256	42	Off	Off	256	42
	E-HICH:	Off	Off	128	22	Off	Off	128	22
34,121 Preset Call Configs	E-AGCH:	Off	Off	128	22	Off	Off	128	22
	HS-SCCH 1:	Off	Off	128	2	Off	Off	128	2
HSPA Parameters	HS-SCCH 2:	Off	Off	128	3	Off	Off	128	3
	HS-SCCH 3:	Off	Off	128	3	Off	Off	128	3
Cell Off	HS-SCCH 4:	Off	Off	128	3	Off	Off	128	3
	HS-PDSCHs:	Off	Off	16	1-15	Off	Off	16	1-15
Sys Type: UTRA FDD	Comp OCNS:	Off	Off	128	WCDMA	Off	Off	128	HSDPA
	Logging: No Conn								
DBUS-INT		IntRef		Offset		1 of 3			

4. Configure DC-HSDPA parameters to achieve the Maximum Downlink Data Rate:

First of all, you must know the maximum data rate of the device under test according to its category and the key factors to achieve the maximum data rate. In this lab, you use a category 24 device whose maximum data rate is 42 Mbps when DC-HSDPA is configured.

a) Set up the HSDPA RB Test Mode Parameters

Path: Call Parms 1 of 3 -> HSPA Parameters (F10) -> HSDPA Parameters (F10) -> HSDPA RB Test Mode Setup (F8) -> HSDPA RB Test Mode Settings (F8).

- RB Test HS-DSCH Configuration Type = User Defined
- RB Test User Defined HS-DSCH MAC entity = MAC-ehs (Note 1)
- RB Test User Defined HARQ Processes = 6 (Note 2)
- RB Test User Defined UE IR Buffer Allocation = Implicit
- RB Test User Defined DC-HSDPA State = On
- RB Test Mode DC-HSDPA DPCH Loopback State = On

Note 1: DC-HSDPA requires MAC-ehs. You must set the MAC entity to MAC-ehs before setting the DC-HSDPA state)

Note 2: To restrict the amount of soft memory that can be allocated to a single HARQ process (and thus limit the amount of data that has to be transferred across the UE's internal data buses) the specifications require that when setting up a DC-HSDPA call with the implicit HARQ memory partitioning the network must configure 6, 7, or 8 HARQ processes per cell. For the explicit HARQ memory partitioning case, the number of HARQ processes can be 1 through 8, but the memory size for each HARQ process cannot be greater than the number of soft channel bits for an implicit memory partitioning with 6 processes per HS-DSCH channel.

b) Set up the Serving Cell Parameters

Path: F10

- RB Test User Defined 64QAM State = On
- RB Test User Defined Active HS-PDSCHs = 15
- RB Test User Def Transport Block Size Index = 62
- RB Test User Defined Modulation Type = 64QAM
- RB Test User Defined Inter-TTI Interval = 1

c) Set up the Secondary Serving Cell Parameters

Path: F11

- RB Test User Def Secondary Cell 64QAM State = On
- RBTM User Def Sec Cell Active HS-PDSCHs = 15

- RBTM User Def Sec Cell TB Size Index = 62
- RBTM User Def Sec Cell Modulation Type = 64QAM
- RBTM User Def Sec Cell Inter-TTI Interval = 1

d) Set the **Secondary Serving Cell Power (dBm/3.84 MHz)** to **-25 dBm/3.84 MHz**

Path: Return (**F12**) -> HSDPA Parms 2 of 2 -> Secondary Serv Cell Parms (**F10**)

e) Set the **Cell power** to **-25 dBm/3.84 MHz**

Path: CALL SETUP -> **F7**

f) Set the HSDPA Conn DL Channel Levels

Path: CALL SETUP -> Call Control 2 of 6 -> Generator Info (**F3**) -> Downlink Channel Levels (**F3**) -> Connected DL Channel Levels (**F3**) -> **F3**

- HSDPA Cell 1 Connected CPICH Level = -8
- HSDPA Cell 1 Connected P-CCPCH/SCH Level = -20
- HSDPA Cell 1 Connected PICH Level = off
- HSDPA Cell 1 Connected DPCH Level = -30
- HSDPA Cell 1 Connected HS-PDSCH Level (Sum) = -1 dBm
- HSDPA Cell 1 Connected HS-SCCH 1 to 4 Level = -20,-20,off,off
- Secondary Cell HSDPA Conn CPICH Level = -8
- Secondary Cell HSDPA Conn PCCPCH/SCH Level = -20
- Secondary Cell HSDPA Conn PICH Level = off
- Secondary Cell HSDPA Conn HS-PDSCHs Lvl (Sum) = -1 dBm
- Secondary Cell HSDPA Conn HS-SCCH 1 to 4 Level = -20,-20,off,off

5. Set the **Operating Mode (F1)** to **Active Cell**.

A.9.1.2. Power on the UE and Set up the Connection

Power on the device, and then wait for it to camp on 8960. You should be able to see the following screen.

Press and then wait for the call setup screen. You should be able to see the following:

Call Setup Screen									
Call Control		Active Cell Operating Mode						Call Parms	
Operating Mode		UE Information						Cell Power	
Active Cell		IMSI: 001012345678901			Power Class: 4			-25.00	
		IMEI(SV):352358040214948(---)			Detected PRACH Sig: 0			dBm/3.84 MHz	
		Called Party Number:						Channel Type	
		UE Expected Open Loop Transmit Power						12.2k + HSDPA	
		Init PRACH TX Pou: -60.00 dBm			Init DPCH TX Pou: -11.55 dBm			Paging Service	
Originate Call		Current Service Type						RB Test Mode	
		None							
Paging Parameters		Call Processing Status						HSPA Parameters	
		RRC State: Idle		Soft Handover State: Off		Compressed Mode State: Off		34.121 Preset Call Configs	
		MM Status: None		Cur DPCH Offset: 0 chips					
		GMM State: Attached							
Handovers		HSUPA Information			HSDPA Information			Channel (UARFCN) Parms	
		Rep EDCH Cat/Ext: 6/Unrep			Cur UE HS-DSCH Cat: 24				
		Last Happy Bit: None			Block Error Ratio: ---- %				
		Throughput: ---- kbps			Throughput: ---- kbps				
Clear UE Info		ACKs Transmitted: ----			Blocks Transmitted: ----				
		Active Cell				Sys Type: UTRA FDD			
		Idle				Logging: No Conn			
1 of 6		DBUS-INT		IntRef		Offset		1 of 3	

The UE reports HSDPA categories to 8960, which represents its maximum data rate capability. DC-HSDPA requires UE categories 21 to 24.

The GMM state must be **Attached**, otherwise you cannot establish a HSDPA connection.

2. Originate the Connection

a) Now, Originate an RB Test call with DC-HSDPA by pressing „**F3**“ from the main Call Setup screen.

b) After a connection is set up, you will be able to see the throughput from the HSDPA Information window. Press the **Measurement Reset** key to reset the calculation.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Params		
Operating Mode	UE Information						Cell Power		
Active Cell	INSI: 001012345678901		Power Class: 4		INEI(SV):352358040214948(---)		Detected PRACH Sig: 0		-25.00
	Called Party Number:						dBm/3.84 MHz		
	UE Expected Open Loop Transmit Power						Channel Type		
	Init PRACH TX Pou: -60.00 dBm		Init DPCCH TX Pou: -11.55 dBm				12.2k + HSDPA		
End Call	Current Service Type						Paging Service		
	RB Test Mode - HSDPA						RB Test Mode		
	Call Processing Status								
Paging Parameters	RRC State: CELL_DCH		Soft Handover State: Off		MM Status: None		Compressed Mode State: Off		HSPA Parameters
	GMM State: Attached		Cur DPCH Offset: 0 chips						
Handovers	HSUPA Information			HSDPA Information			34.121 Preset Call Configs		
	Rep EDCH Cat/Ext: 6/Unrep			Cur UE HS-DSCH Cat: 24					
	Last Happy Bit: None			Block Error Ratio: 0 %					
	Throughput: ---- kbps			Throughput: 42101 kbps					
Clear UE Info	ACKs Transmitted: ----			Blocks Transmitted: 115500			Channel (UARFCN) Params		
	Active Cell Connected						Sys Type: UTRA FDD		
							Logging: No Conn		
1 of 6	DBUS-INT	IntRef	Offset						1 of 3

Now you can also check the connected DC-HSDPA downlink channel levels.

Path: CALL SETUP->Call Control 2 of 6 -> Generator Info (F3) -> Additional Gen Info Screens (F1) ->DC-HSDPA DL Code Chan Info (F4).

Call Setup Screen										
Screen Ctrl	DC-HSDPA DL Code Channel Information								Call Params	
DL Code Channel Info Screen	Serving Cell Primary Scrambling Code: 0						Cell Power		-25.00	
	Secondary Serving Cell Primary Scrambling Code: 2						dBm/3.84 MHz			
Generated Power Info Screen	Channel	Serving Cell DL Chan Info				Sec Cell DL Chan Info				Channel Type
		Level (dB)	Current	Desired	OVSF	Chan Code	Level (dB)	Current	Desired	
OCNS Info Screen	CPICH:	-8.00	-8.00	256	0	-8.00	-8.00	256	0	Paging Service
	P-CCPCH/SCH:	-20.00	-20.00	256	1	-20.00	-20.00	256	1	
DC-HSDPA DL Code Chan Info	S-CCPCH:	Off	Off	64	2	Off	Off	256	2	RB Test Mode
	PICH:	Off	Off	256	2	Off	Off	256	2	
	AICH:									HSPA Parameters
	(F-)DPCH:	-30.00	-30.00	128	7					
	E-AGCH:	Off	Off	256	42					34.121 Preset Call Configs
	E-HICH:	Off	Off	128	22					
	E-RGCH:	Off	Off	128	22					Channel (UARFCN) Params
	HS-SCCH 1:	-20.00	-20.00	128	2	-20.00	-20.00	128	2	
	HS-SCCH 2:	-20.00	-20.00	128	3	-20.00	-20.00	128	3	1 of 3
	HS-SCCH 3:									
Return	HS-SCCH 4:									
	HS-PDSCHs:	-1.00	-1.00	16	1-15	-1.00	-1.00	16	1-15	
	Comp OCNS:	-17.91	-17.91	128	HSDPA	-17.65	-17.65	128	HSDPA	
	Active Cell Connected						Sys Type: UTRA FDD			
							Logging: No Conn			
	DBUS-INT	IntRef	Offset							

A.9.2. Activate/ Deactivate the Secondary Serving Cell

Once a DC-HSDPA connection is established, 8960 can control the UE to start or stop monitoring the secondary serving cell using HS-SCCH orders. The HS-SCCH orders can be sent on either the serving or secondary serving cell.

A.9.2.1 Deactivate the Secondary Serving Cell

1. Setup the Deactivate Secondary Cell Parameter

Path: CALL SETUP->Call Control 6 of 6 -> HS-SCCH Order (F3) -> Deactivate Secondary Cell (F2)

In this lab you set it to deactivate the secondary serving cell from the serving cell.

- Deactivate Secondary Cell HS-SCCH Order From = Serving Cell

Press **Send Deactivate Secondary Cell (F5)**

Press Measurement Reset key and see the throughput has dropped to 21 Mbps or so, like the figure below:

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parm		
Operating Mode	UE Information						Cell Power		
Active Cell	IMSI: 001012345678901 Power Class: 4 IMEI(SV):352358040214948(--) Detected PRACH Sig: 0 Called Party Number:						-25.00 dBm/3.84 MHz		
	UE Expected Open Loop Transmit Power						Channel Type		
	Init PRACH TX Pou: -60.00 dBm Init DPCH TX Pou: -11.55 dBm						12.2k + HSDPA		
End Call	Current Service Type						Paging Service		
	RB Test Mode - HSDPA						RB Test Mode		
Paging Parameters	Call Processing Status						HSPA Parameters		
	RRC State: CELL_DCH Soft Handover State: Off MM Status: None Compressed Mode State: Off GMM State: Attached Cur DPCH Offset: 0 chips						34.121 Preset Call Configs		
Handovers	HSDPA Information HSDPA Information Rep EDCH Cat/Ext: 6/Unrep Cur UE HS-DSCH Cat: 24 Last Happy Bit: None Block Error Ratio: 0 % Throughput: ---- kbps Throughput: 21088 kbps ACKs Transmitted: ---- Blocks Transmitted: 35000						Channel (UARFCN) Parm		
Clear UE Info	Active Cell Connected Sys Type: UTRA FDD Logging: No Conn								
1 of 6	DBUS-INT	IntRef	Offset				1 of 3		

You can see more on the DC-HSDPA Information screen.

Path: CALL SETUP->Call Control 2 of 6 -> Additional Screens (F1) -> HSDPA Information (F4) -> DC-HSDPA Information (F4).

Call Setup Screen									
Screen Ctrl	DC-HSDPA Information								Call Parm
Channel (UARFCN) Info	Secondary Serving Cell Status								Cell Power
	Current Secondary Serving Cell Status: Configured-Inactive								-25.00
									dBm/3.84 MHz
HSPA Information	DC-HSDPA Information								Channel Type
									12.2k + HSDPA
E-TFCI Recording Information									Paging Service
									RB Test Mode
HSDPA Information									HSPA Parameters
Clear UE Info									34.121 Preset Call Configs
Return									Channel (UARFCN) Parm
	Active Cell Connected				Sys Type: UTRA FDD				
					Logging: No Conn				
1 of 2		DBUS-INT		IntRef	Offset				1 of 3

A.9.2.2 Re-activate the Secondary Serving Cell

Now you can activate the secondary serving cell by pressing back to the HS-SCCH Order menu.

Path: CALL SETUP->Call Control 6 of 6 -> HS-SCCH Order (F3)

Press **Send Activate Secondary Cell (F1)**.

Press the Measurement Reset key and see the throughput has increased to 42 Mbps. When you look at the DC-HSDPA Information screen, you can see the secondary serving cell is set up again.

Call Setup Screen									
Screen Ctrl	DC-HSDPA Information						Call Params		
Channel (UARFCN) Info	Secondary Serving Cell Status						Cell Power		
	Current Secondary Serving Cell Status: Configured-Active						-25.00		
HSPA Information	DC-HSDPA Information						dBm/3.84 MHz		
							Channel Type		
E-TFCI Recording Information							12.2k + HSDPA		
							Paging Service		
HSDPA Information							RB Test Mode		
							HSPA Parameters		
Clear UE Info							34.121 Preset Call Configs		
							Channel (UARFCN) Params		
Return							1 of 3		
1 of 2									
				Active Cell		Sys Type: UTRA FDD			
				Connected		Logging: No Conn			
				DBUS-INT		IntRef Offset			

When DC-HSDPA is active, the HBLER measurement can also be used to perform receiver testing. 3GPP TS 34.121-1 sections 6.3C and 6.3D are supported and can be set up and tested as described in an appendix in another document, DC-HSDPA User Guide.