

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15CBT_RM-1127_07.docx	Date of Report:	28-Aug-2015
Number of pages:	49	Customer's Contact person:	Tero Huhtala
Testing laboratory:	TCC Microsoft Beijing Laboratory Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550	Customer:	Microsoft P.O. Box 403 Visiokatu 4 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880
FCC listing no.:	975940		
IC recognition no.:	661AH-1		
Tested devices/ accessories:	Phone RM-1127 / Cover CC-3097 / Battery Samsung BL-T5A / AC-Charger AC-18U / Headset WH-108		
FCC ID:	PYARM-1127	IC:	-
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2014), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards, RSS-210 (Issue 8, December 2010). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Microsoft.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Jia Dongsheng, Manager

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	15-Jun-2015
Testing completed	26-Aug-2015
The customer's contact person	Tero Huhtala
Test Plan referred to	T:\Projects\RM-1128\TestPlan\RS_testplan_RM-1128.xlsm
Notes	-
Document name	FCC15CBT_RM-1127_07.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WCDMA/WLAN/Bluetooth

The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-1128	004402742351913	1510	-	01065.00000.15265.37000	500110
Cover	CC-3097	-	-	-	-	500128
Battery	Samsung BL-T5A	5241525213V10205754;0670778	PWB Ver.1.1	-	-	500117
AC-Charger	AC-18U	418715115100100658;0675735	-	-	-	500122
Headset	WH-108	-	-	-	-	500103
Phone	RM-1128	004402742351970	1510	-	01065.00000.15265.37000	500100
Cover	CC-3097	-	-	-	-	500127
Battery	Samsung BL-T5A	5241525213V10200063;0670778	PWB Ver.1.1	-	-	500101
AC-Charger	AC-18U	4818715115100100661;0675735	-	-	-	500124
Headset	WH-108	-	-	-	-	500121

1.2. Summary of Test Results

Bluetooth:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4(2)	Conducted peak output power	PASSED
15.247(d), 15.205(b)	A8.5	Band edge compliance of RF emissions	PASSED
15.247(d)	A8.5	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8.5	Spurious radiated emissions	PASSED
15.207	7.2.4	AC powerline conducted emissions	PASSED
15.247(a)(1)	A8.1(a)	20dB(bandwidth)	PASSED
15.247(a)(1)	A8.1(b)	Carrier frequency separation	PASSED
15.247(a)(1)(iii)	A8.1(d)	Number of hopping frequencies	PASSED
15.247(a)(1)(iii)	A8.1(d)	Time of occupancy	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Microsoft Laboratory.

The test results of PYARM-1128 are re-used for certification of the PYARM-1127. The table above indicates the results, which will be re-used.

CONTENTS


1. Summary for FCC Part 15C Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4(2))	5
2.1. Test Setup	5
2.2. Test method and limit	5
2.3. Bluetooth Test results	6
3. Band edge compliance of RF emissions (FCC 15.247(d), 15.205(b), RSS-210 A8.5)	9
3.2. Test method and limit	9
3.3. Bluetooth test results	10
4. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)	18
4.1. Test Setup	18
4.2. Test method and limit	18
4.3. Bluetooth Test results	19
5. Spurious radiated emissions (FCC 15.247(d), 15.209, RSS-210 A8.5)	22
5.2. Test method and limit	22
5.3. Bluetooth test results	24
6. AC powerline conducted emissions (FCC §15.207, RSS-210 7.2.4)	27
6.1. Test Setup	27
6.2. Test method and limit	27
6.3. Bluetooth Test results	29
7. 20dB(bandwidth) (FCC §15.247(a)(1), RSS-210 A8.1(a))	31
7.1. Test Setup	31
7.2. Test method and limit	31
7.3. Bluetooth Test results	33
8. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1(b))	37
8.1. Test Setup	37
8.2. Test method and limit	37
8.3. Bluetooth Test results	39

9. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1(d))	40
9.1. Test Setup	40
9.2. Test method and limit	40
9.3. Bluetooth Test results	42
10. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1(d))	43
10.1. Test Setup	43
10.2. Test method and limit	43
10.3. Bluetooth Test results	45
11. Test Equipment	47
11.1. Conducted measurements	47
11.2. Radiated measurements	47

2. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4(2))

EUT with DUT number	RM-1128, DUT 500110
Accessories with DUT numbers	CC-3097, DUT 500128; Samsung BL-T5A, DUT 500117; AC-18U, DUT 500122; WH-108, DUT 500103
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Test was in conducted RF2 system.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21/57/100.1
Date of measurements	10-Jul-2015
Measured by	Dou Rubo

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for conducted peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5 5725 - 5850	≤ 1	≤ 30

2.3. Bluetooth Test results


2.3.1 GFSK modulation, PRBS packet type

Channel / f_c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	9.46	8.831	PASSED
40 / 2442	10.73	11.83	PASSED
78 / 2480	8.96	7.87	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 3 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 3 MHz, VBW: 3 MHz)




Channel 78 / 2480 MHz (Peak detector, RBW: 3 MHz, VBW: 3 MHz)




2.3.2 8DPSK modulation, PRBS packet type

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
0 / 2402	10.6	11.482	PASSED
40 / 2442	11.78	15.066	PASSED
78 / 2480	10.06	10.139	PASSED


Channel 0 / 2402 MHz (Peak detector, RBW: 3 MHz, VBW: 3 MHz)



Channel 40 / 2442 MHz (Peak detector, RBW: 3 MHz, VBW: 3 MHz)




Channel 78 / 2480 MHz (Peak detector, RBW: 3 MHz, VBW: 3 MHz)



3. Band edge compliance of RF emissions (FCC 15.247(d), 15.205(b), RSS-210 A8.5)

EUT with DUT number	RM-1128, DUT 500100
Accessories with DUT numbers	CC-3097, DUT 500127; Samsung BL-T5A, DUT 500101; AC-18U, DUT 500124; WH-108, DUT 500121
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/50/99.6
Date of measurements	13-Jul-2015
Measured by	Dou Rubo

3.1.1 Test setup



3.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).


Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit
Below 2390 and above 2483.5	54 dBuV/m (avg) and 74 dBuV/m (pk)
2390 - 2400	-20 dBc (pk)

3.3. Bluetooth test results

3.3.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2387	57.71	767.803	56.95	0.76	PASSED
2400	70.91	3510.347	0	70.91	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	44.29	163.776	43.53	0.76	PASSED

Hopping on. Low end.




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2386	57.74	770.46	56.98	0.76	PASSED
2400	68.85	2770.129	0	68.85	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	44.29	163.776	43.53	0.76	PASSED

Channel 78 / 2480 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2495	59.69	965.384	57.94	1.75	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2495	45.7	192.752	43.95	1.75	PASSED

Hopping on. High end.



Peak (RBW: 1 MHz, VBW: 1 MHz)


Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2486	59.12	903.129	57.37	1.75	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2495	45.7	192.752	43.95	1.75	PASSED

3.3.2 8DPSK modulation, PRBS packet type

Channel 0 / 2402 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2389	58.19	811.521	57.43	0.76	PASSED
2400	74.43	5266.838	0	74.43	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	44.29	163.776	43.53	0.76	PASSED

Hopping on. Low end.




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2387	57.84	780.189	57.08	0.76	PASSED
2400	73.82	4911.34	73.06	0.76	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	44.29	163.776	43.53	0.76	PASSED

Channel 78 / 2480 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2484	60.37	1043.758	58.62	1.75	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2484	47.89	247.942	46.14	1.75	PASSED

Hopping on. High end.



Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2492	59.84	981.974	58.09	1.75	PASSED


Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2484	46.32	206.99	44.57	1.75	PASSED

4. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-1128, DUT 500110
Accessories with DUT numbers	CC-3097, DUT 500128; Samsung BL-T5A, DUT 500117; AC-18U, DUT 500122; WH-108, DUT 500103
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Test was in conducted RF2 system.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21/57/100.1
Date of measurements	10-Jul-2015
Measured by	Dou Rubo

4.1. Test Setup



4.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

4.3. Bluetooth Test results

4.3.1 GFSK modulation, PRBS packet type


Channel 0 / 2402 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4803.792	-44.97	PASSED
7248.802	-48.88	PASSED


Channel 40 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4883.633	-46.56	PASSED
7283.533	-49.81	PASSED

Channel 78 / 2480 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4959.481	-48.20	PASSED
7396.108	-49.08	PASSED

4.3.2 8DPSK modulation, PRBS packet type


Channel 0 / 2402 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4803.792	-46.78	PASSED
7238.623	-48.81	PASSED


Channel 40 / 2442 MHz



Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4884.431	-46.99	PASSED
7343.413	-48.57	PASSED

Channel 78 / 2480 MHz




Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
4995.808	-46.79	PASSED
7440.419	-47.19	PASSED

5. Spurious radiated emissions (FCC 15.247(d), 15.209, RSS-210 A8.5)

EUT with DUT number	RM-1128, DUT 500100
Accessories with DUT numbers	CC-3097, DUT 500127 ; Samsung BL-T5A, DUT 500101; AC-18U, DUT 500124; WH-108, DUT 500121
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/50/99.6
Date of measurements	13-Jul-2015
Measured by	Gao Sherina

5.1.1 Test setup



5.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210 as follows:
The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement is made up to 10th harmonic of the EUT highest TX channel.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
30 - 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

5.3. Bluetooth test results

5.3.1 GFSK modulation, PRBS packet type

Channel 0 / 2402 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4803.7	58.17	810.028	56.77	1.4	74	15.81	PASSED
7206	52.33	413.523	42.13	10.2	95	42.9	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4803.7	44.56	169.044	43.16	1.4	54	9.42	PASSED
7206	38.66	85.704	28.46	10.2	---	---	PASSED

Channel 40 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
31.86	28.04	25.235	33.84	-5.8	40	11.96	PASSED
31.888	28.02	25.177	33.92	-5.9	40	11.98	PASSED
31.98	28.11	25.439	34.01	-5.9	40	11.89	PASSED
36.076	24.92	17.62	33.52	-8.6	40	15.08	PASSED
36.082	24.83	17.438	33.43	-8.6	40	15.17	PASSED
39.009	23.56	15.066	34.06	-10.5	40	16.44	PASSED
39.723	20.93	11.13	31.93	-11	40	19.07	PASSED
48.549	20.24	10.28	37.24	-17	40	19.76	PASSED
228.827	30.66	34.119	46.36	-15.7	46	15.36	PASSED
942.317	32.97	44.514	34.17	-1.2	46	13.05	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4881.8	43.8	154.882	42	1.8	74	30.18	PASSED
7318.3	49.94	314.051	39.04	10.9	74	24.04	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4881.8	31.07	35.768	29.27	1.8	54	22.91	PASSED
7318.3	36.73	68.628	25.83	10.9	54	17.25	PASSED

Channel 78 / 2480 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4959.7	56.42	662.217	54.82	1.6	74	17.56	PASSED
7441.3	50.72	343.558	39.72	11	74	23.26	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4959.7	42.95	140.443	41.35	1.6	54	11.03	PASSED
7441.3	37.48	74.817	26.48	11	54	16.5	PASSED

5.3.2 8DPSK modulation, PRBS packet type

Channel 0 / 2402 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4804	57.19	723.602	55.79	1.4	74	16.79	PASSED
7206	50.36	329.61	40.16	10.2	95	44.87	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4804	43.85	155.776	42.45	1.4	54	10.13	PASSED
7206	37.28	73.114	27.08	10.2	---	---	PASSED

Channel 40 / 2442 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
31.8	28.28	25.942	34.08	-5.8	40	11.72	PASSED
31.98	28.05	25.264	33.95	-5.9	40	11.95	PASSED
32.908	25.3	18.408	31.8	-6.5	40	14.7	PASSED
35.572	27.29	23.147	35.49	-8.2	40	12.71	PASSED
35.776	26.58	21.33	34.98	-8.4	40	13.42	PASSED
38.949	24.29	16.387	34.79	-10.5	40	15.71	PASSED
49.593	21.85	12.374	39.65	-17.8	40	18.15	PASSED
50.649	20.18	10.209	38.58	-18.4	40	19.82	PASSED
228.797	30.56	33.729	46.26	-15.7	46	15.46	PASSED
942.317	32.88	44.055	34.08	-1.2	46	13.14	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4881.3	43.94	157.398	42.14	1.8	74	30.04	PASSED
7319.8	50.14	321.366	39.24	10.9	74	23.84	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4881.3	31.06	35.727	29.26	1.8	54	22.92	PASSED
7319.8	36.72	68.549	25.82	10.9	54	17.26	PASSED

Channel 78 / 2480 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4960.2	53.61	479.181	52.01	1.6	74	20.37	PASSED
7440.8	51.06	357.273	40.06	11	74	22.92	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4960.2	39.1	90.157	37.5	1.6	54	14.88	PASSED
7440.8	37.52	75.162	26.52	11	54	16.46	PASSED

6. AC powerline conducted emissions (FCC §15.207, RSS-210 7.2.4)

EUT with DUT number	RM-1128, DUT 500100
Accessories with DUT numbers	CC-3097, DUT 500127 ; Samsung BL-T5A, DUT 500101; AC-18U, DUT 500124; WH-108, DUT 500121
Operation Voltage [V] / [Hz]	115/60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22/65/100.1
Date of measurements	23-Jul-2015
Measured by	Dou Rubo

6.1. Test Setup



6.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

The measurement is made according to Public notice DA 00-705 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

6.3. Bluetooth Test results

6.3.1 GFSK modulation, PRBS packet type

Channel 40 / 2442 MHz



QuasiPeak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.765	39.59	N	PASSED
0.77	39.69	N	PASSED
0.87	39.85	N	PASSED
0.93	40.02	N	PASSED
0.985	40.47	N	PASSED
1.37	38.79	N	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.515	30.69	N	PASSED
0.69	30.13	N	PASSED
0.925	29.91	N	PASSED
1.325	31.21	N	PASSED
1.335	31.15	N	PASSED
1.385	30.71	N	PASSED

6.3.2 8DPSK modulation, PRBS packet type

Channel 40 / 2442 MHz



QuasiPeak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.605	40.92	N	PASSED
0.875	39.87	N	PASSED
0.995	40.03	N	PASSED
1.155	39.61	N	PASSED


Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.515	30.13	N	PASSED
0.935	30.7	N	PASSED
1.165	30.2	N	PASSED
1.335	31.16	N	PASSED

7. 20dB(bandwidth) (FCC §15.247(a)(1), RSS-210 A8.1(a))

EUT with DUT number	RM-1128, DUT 500110
Accessories with DUT numbers	CC-3097, DUT 500128; Samsung BL-T5A, DUT 500117; AC-18U, DUT 500122; WH-108, DUT 500103
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Test was in conducted RF2 system.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/58/100.5
Date of measurements	10-Jul-2015
Measured by	Dou Rubo

7.1. Test Setup



7.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for 20 dB bandwidth measurements


Limit [MHz]
N/A

7.3. Bluetooth Test results


7.3.1 GFSK modulation, PRBS packet type

Channel / f _c [MHz]	20 dB bandwidth [kHz]
0 / 2402	712
40 / 2442	709.1
78 / 2480	709.1


0 / 2402



40 / 2442




78 / 2480




7.3.2 8DPSK modulation, PRBS packet type

Channel / f_c [MHz]	20 dB bandwidth [kHz]
0 / 2402	1299.6
40 / 2442	1296.7
78 / 2480	1296.7


0 / 2402



40 / 2442




78 / 2480



8. Carrier frequency separation (FCC §15.247(a)(1), RSS-210 A8.1(b))

EUT with DUT number	RM-1128, DUT 500110
Accessories with DUT numbers	CC-3097, DUT 500128; Samsung BL-T5A, DUT 500117; AC-18U, DUT 500122; WH-108, DUT 500103
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Test was in conducted RF2 system.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/58/100.5
Date of measurements	10-Jul-2015
Measured by	Dou Rubo

8.1. Test Setup



8.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for carrier frequency separation measurements


Limit [MHz]
≥ 0.025 or $2/3$ of the 20 dB bandwidth

8.3. Bluetooth Test results

8.3.1 GFSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
998.6	PASSED


Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



8.3.2 8DPSK modulation, PRBS packet type

Carrier frequency separation [kHz]	Result
998.6	PASSED


Hopping on, carrier frequency separation of channels 39 / 2441 MHz and 40 / 2442 MHz



9. Number of hopping frequencies (FCC §15.247(a)(1)(iii), RSS-210 A8.1(d))

EUT with DUT number	RM-1128, DUT 500110
Accessories with DUT numbers	CC-3097, DUT 500128; Samsung BL-T5A, DUT 500117; AC-18U, DUT 500122; WH-108, DUT 500103
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Test was in conducted RF2 system.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/58/100.5
Date of measurements	10-Jul-2015
Measured by	Gao Sherina

9.1. Test Setup



9.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for number of hopping frequencies measurements


Limit [number]
≥ 15

9.3. Bluetooth Test results

9.3.1 GFSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
78	PASSED


Hopping on, number of hopping frequencies



9.3.2 8DPSK modulation, PRBS packet type

Measured number of hopping frequencies	Result
78	PASSED


Hopping on, number of hopping frequencies



10. Time of occupancy (FCC §15.247(a)(1)(iii), RSS-210 A8.1(d))

EUT with DUT number	RM-1128, DUT 500110
Accessories with DUT numbers	CC-3097, DUT 500128; Samsung BL-T5A, DUT 500117; AC-18U, DUT 500122; WH-108, DUT 500103
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Test was in conducted RF2 system.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	23/58/100.5
Date of measurements	10-Jul-2015
Measured by	Dou Rubo

10.1. Test Setup



10.2. Test method and limit

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

The measurement is made according to Public notice DA 00-705 and IC standard RSS-210.

The total time of occupancy is get by multiplying the measured number of transmissions occurred during 31.6 second period with the duration of one transmission.

Limits for time of occupancy measurements


Limit [s]
≤ 0.4

10.3. Bluetooth Test results


10.3.1 GFSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [ms]	Time of occupancy [s]	Result
99	2.899	0.287	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz




Hopping on, duration of one transmission, channel 40 / 2442 MHz




10.3.2 8DPSK modulation, PRBS packet type

Measured number of transmissions	Duration of one transmission [ms]	Time of occupancy [s]	Result
74	2.91	0.215	PASSED

Hopping on, number of transmissions, channel 40 / 2442 MHz



Hopping on, duration of one transmission, channel 40 / 2442 MHz



11. Test Equipment

11.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCHW0020	DC Power supply	HP6632B	HP	22/24/27, 15C
BJPCPT0040	Receiver	ESCS30	R&S	15C, 15B
BJPCPT0069	LISN 50 μ H	ESH3-Z5	R&S	15C, 15B
BJPCTC0323	Signal Generator	SMR 27	R&S	22/24/27, 15C, 15B
BJPCPT0073	Signal Generator	SMR 20	R&S	22/24/27, 15C, 15B
BJPCPT0191	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C, 15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C, 15R
BJPCTC0017	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0062	AC Power source	6812B	HP	15C, 15B
BJPCTC0067	Bluetooth Tester	CBT	R&S	22/24/27, 15C
BJPCTC0082	Humidity and Temperature Sensor	175-H2	Testo	15B, 15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B, 15C
BJPCTC0089	Temperature Test chamber	VT4002	Votsch industrietechnik	22/24/27, 15C
BJPCTC0090	FSP spectrum analyzer	FSP30	R&S	22/24/27, 15C
BJPCTC0094	GPIO-RS232 convertor	GPIO-RS232	NI	22/24/27, 15C
BJPCTC0112	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0127	AC Power source	SOYI-500VA	SOYI	15B, 15C
BJPCTC0128	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27, 15B, 15C
BJPCTC0129	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27, 15B, 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27, 15B, 15C
BJPCTC0136	Communication antenna	JXTXLB-880-NF	A-INFOMW	15B, 15C
BJPCTC0306	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0305	GPIO converter	GPIO-RS232	NI	22/24/27, 15C
BJPCTC0304	Spectrum Analyser	FSV30	R&S	22/24/27, 15C
BJPCTC0309	GPIO-RS232 convertor	RS232	NI	22/24/27, 15C
BJPCTC0307	Dual channel battery/charger simulator	2306	KEITHLEY	22/24/27, 15C
BJPCTC0308	Dual channel battery/charger simulator	2306	KEITHLEY	22/24/27, 15C
BJPCTC0352	Signal Generator 20GHz	MG3692B	Anritsu	22/24/27, 15C
BJBDATC0169	Temperature Test chamber	VT4002	Votsch	22/24/27, 15C
BJPCTC0334	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0342	Communication Tester	CMU200	R&S	15B, 15C
BJPCTC0343	Power Splitter	1167A	Agilent	EN300328
BJPCTC0344	Power Splitter	1167A	Agilent	EN300328
BJPCTC0345	Power Splitter	1167A	Agilent	EN300328
BJPCTC0346	Attenuator	8496A	Agilent	EN300328
BJPCTC0347	Directional Coupler	4226-20	Narda	EN300328
BJPCTC0348	Signal generator	E4438C	Agilent	EN300328
BJPCTC0336	Signal Generator	SMP22	R&S	22/24/27, 15C
BJPCTC0357	Signal Generator	SMB100A	R&S	-

11.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCPT0072	Receiver	ESIB26	R&S	22/24/27, 15C, 15B
BJPCPT0150	High Pass Filter	WHKS1200-10SS	Wainwright	22/24/27, 15C, 15B
BJPCPT0151	Band Reject Filter	WRCD1880/2000-0.2/40-5SSK	Wainwright	24, 15B
BJPCPT0154	Band Reject Filter	WRCT2402/2480-2400/2483.5-30-20SS	Wainwright	15C, 15B
BJPCPT0166	Antenna	VUBA 9117	Swarzbeck	22/24/27
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C, 15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C, 15R
BJPCTC0007	Antenna	HL562	R&S	22/24/27, 15C, 15B
BJPCTC0029	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0034	Band Reject Filter	WRCT 800/880-0.2/40-5SSK	Wainwright	22, 15B
BJPCTC0049	Preamplifier	Blma 0118-1A-Bt	Bonn	22/24/27, 15C, 15B
BJPCTC0055	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0058	Bluetooth Tester	CBT	R&S	15C, 15B
BJPCTC0062	AC Power source	6812B	Hp	15C, 15B
BJPCTC0064	Band Reject Filter	WRCG1877/1883-1870/1890-40/6SS	Wainwright	24, 15B
BJPCTC0071	Multi-Device Controller	2090	EMCO	22/24/27, 15C, 15B
BJPCTC0072	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	ETS	22/24/27, 15C, 15B
BJPCTC0073	MAST	Model-TR/POL	ETS	22/24/27, 15C, 15B
BJPCTC0074	MAST	Model 2070-2	ETS	22/24/27, 15C, 15B
BJPCTC0075	Turntable	Model 2188	ETS-EMCO	22/24/27, 15C, 15B
BJPCTC0081	Humidity and Temperature Sensor	175-H2	Testo	15B, 15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B, 15C
BJPCTC0124	Attenuator	SA18N200W-40	Fairview Microwave	-
BJPCTC0125	Loop Antenna	HFH2-Z2	R&S	15C
BJPCTC0126	Tripod	FHU-Z	R&S	15C
BJPCTC0128	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0129	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27 15B 15C
BJPCTC0133	Open Switch and contril unit	OSP 150	R&S	15B, 15C
BJPCTC0134	Open Switch and contril unit	OSP 150	R&S	15B, 15C
BJPCTC0135	Open Switch and contril unit	OSP 130	R&S	15B, 15C
BJPCTC0136	Communication antenna	JXTXLB-880-NF	A-INFOMW	15B 15C
BJPCTC0171	Broad-band Horn Antenna	BBHA9120 D	SCHWARZBECK MESS - ELEKTRONIK	22/24/27, 15C, 15B
BJPCTC0310	Horn Antenna	QSH20SMA	Q-par	22/24/27, 15C, 15B
BJPCTC0311	Horn Antenna	QSH18SMA	Q-par	22/24/27, 15C, 15B
BJPCTC0312	Relay Switch Unit	-	-	22/24/27, 15C, 15B
BJPCTC0313	High Pass Filter	WHKX1.0/15G-12SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0314	High Pass Filter	WHKX8.0/18G-88SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0315	High Pass Filter	WHKX3.0/18G-12SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0316	Preamplifier	AMT-5F-18002550-25-108	-	22/24/27, 15C, 15B
BJPCTC0317	Preamplifier	AMF-6D-02001800-29-20P	-	22/24/27, 15C, 15B
BJPCTC0350	Preamplifier	AMF-4D-01000800-30-29P	Miteq	22/24/27, 15C, 15B
BJPCTC0324	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
BJPCTC0329	Relay Switch Unit	-	-	22/24/27, 15C, 15B
BJPCTC0334	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0342	Communication Tester	CMU200	R&S	15B, 15C

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCTC0349	Preamplifier	AMF-4D-01000800-30-79P	Miteg	22/24/27, 15C, 15B
BJPCTC0350	Preamplifier	AMF-4D-01000800-30-29P	Miteg	22/24/27, 15C, 15B
BJPCTC0351	Preamplifier	AFS4-00101800	-	22/24/27, 15C, 15B
BJPCTC0113	Receiver	ESI B26	R&S	22/24/27, 15B, 15C