



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180400312002
Page: 1 of 7

SAR Evaluation Report

Application No.: SZEM1804003120CR
Applicant: Summer Infant, Inc
Address of Applicant: 1275 Park East Drive, Woonsocket, Rhode Island, United States
Manufacturer: EXVISION INDUSTRIES LIMITED
Address of Manufacturer: NO21, NANXING 3RD ROAD, NANFANG IND PARK, BEIZHA, HUMEN, DONGGUAN, CHINA P.R.C.
Factory: EXVISION INDUSTRIES LIMITED
Address of Factory: NO21, NANXING 3RD ROAD, NANFANG IND PARK, BEIZHA, HUMEN, DONGGUAN, CHINA P.R.C.
Equipment Under Test (EUT):
EUT Name: Audio Baby Monitor
Model No.: 36004R
FCC ID: PZK-36004R
Trade mark: SUMMER
Standard(s) : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2018-04-23
Date of Test: 2018-04-27 to 2018-05-15
Date of Issue: 2018-05-18

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



**SGS-CSTC Standards Technical Services Co., Ltd
Shenzhen Branch.**

Report No.: SZEM180400312002
Page: 2 of 7

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-05-18		Original

Authorized for issue by:			
			
		Leo Li /Project Engineer	
			
		Eric Fu /Reviewer	



**SGS-CSTC Standards Technical Services Co., Ltd
Shenzhen Branch.**

Report No.: SZEM180400312002
Page: 3 of 7

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF EUT	4
4.2 TEST LOCATION	5
4.3 TEST FACILITY	5
4.4 DEVIATION FROM STANDARDS.....	6
4.5 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7



**SGS-CSTC Standards Technical Services Co., Ltd
Shenzhen Branch.**

Report No.: SZEM180400312002
Page: 4 of 7

4 General Information

4.1 General Description of EUT

Power supply:	Ni-MH battery : 3.6V 800mAh rechargeable battery Adapter Model:P6 0750500 Input:AC 100~240V 50/60Hz 250mA Output:DC 7.5V 500mA
Cable:	DC cable: 195cm unshielded
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Gain	0 dBi
Antenna Type	PIFA
Channel Spacing	3.375 MHz
Number of Channels	19
Modulation Type	GFSK
Operation Frequency	2410.875 MHz to 2471.626 MHz



SGS-CSTC Standards Technical Services Co., Ltd Shenzhen Branch.

Report No.: SZEM180400312002
Page: 5 of 7

4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



**SGS-CSTC Standards Technical Services Co., Ltd
Shenzhen Branch.**

Report No.: SZEM180400312002
Page: 6 of 7

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Max. Average power (including tune-up tolerance) is 5.73 dBm on the lowest channel 2.410875 GHz (*)
5.73 dBm logarithmic terms convert to numeric result is nearly 3.74 mW

According to the formula, calculate the test exclusion thresholds:

$$\text{General RF Exposure} = \frac{(\text{Max. Average Power of channel, including tune-up tolerance, mW}) \cdot \sqrt{f(\text{GHz})}}{(\text{min. test separation distance, mm})}$$
$$\text{General RF Exposure} = (3.74 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.410875 \text{ GHz}} = 1.16 \quad (1)$$

SAR requirement:

$$S = 3.0 \quad (2)$$

$$(1) < (2)$$

So the SAR report is not required.

(*) Max. power refer to Report No.:SZEM180400312001

- End of the Report -