

CETECOM ICT Services GmbH

Radio Satellite Communication

Untertürkheimer Straße 6-10 . D-66117 Saarbrücken

Telefon: +49 (0)681 598-9100

Telefax: -9075

RSC14

issue test report consist of 74 Pages

Page 1 (74)



TTI-P-G166/98

Accredited Bluetooth™ Test Facility (BQTF)

Test report no.:5_3682-A/00
FCC Part 2, 15, 90
MC9600 G2

CETECOM – ICT Services GmbH
Untertürkheimerstr. 6-10
66117 Saarbrücken, Germany

Telephone: + 49 (0) 681 / 598-0
Fax: + 49 (0) 681 / 9075

Table of Contents

1 General information

1.1 Notes

1.2 Testing laboratory

1.3 Details of applicant

1.4 Application details

1.5 Test item

1.6 Test standards

2 Technical test

2.1 Summary of test results

2.2 Test report

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Telephone : + 49 681 598 - 9100

Telefax : + 49 681 598 - 9075

E-mail : Michael.Berg@ict.cetecom.de

Internet : www.cetecom.de

Accredited testing laboratory

DAR-registration number : TTI-P-G 166/98-20

Accredited Bluetooth™ Test Facility (BQTF)

[BLUETOOTH is a trademark owned by Bluetooth SIG, Inc. and licensed to CETECOM](#)

1.3 Details of applicant

Name : EADS Defence and Security Networks
Street : Rue J.P Timbaud-MS01, BP 26
City : F78392 Bois d'Arcy Cedex
Country : France
Telephone : +33 1 34 60 88 94
Telefax : +33 1 34 60 78 98
Contact : Yann Lebail
Telephone : +33 1 34 60 88 94

1.4 Application details

Date of receipt of application : 12.06.01
Date of receipt of test item : 11.07.01
Date of test : 16.-20.07.01

1.5 Test item

Type of equipment : **PMR Radio Base Station**
Type designation : **MC9600 BS8 G2**
Manufacturer : applicant
Street :
City :
Country :
Serial number : see photographs
Additional informations: :
Frequency : 440 - 490 MHz
Type of modulation : 12K0F1D
Number of channels : 4000
Antenna : N-socket
Power supply : 48V DC
Output power : 19.45 W
Type of equipment : Temperature range : -20°C - +50°C

1.6 Test standards: FCC Part 2, 15, 90

2 Technical test

2.1 Summary of test results

The radiated measurements were performed vertically and horizontal

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

Final verdict : PASS

Technical responsibility for area of testing :

26.07.01 RSC 8411 Berg M.



Date	Section	Name	Signature
------	---------	------	-----------

Technical responsibility for area of testing :

26.07.01 RSC8414 Ames H.



Date	Section	Name	Signature
------	---------	------	-----------

2.2 Testreport

TEST REPORT

Testreport no. : 5_3682-A/00

TEST REPORT REFERENCE

LIST OF MEASUREMENTS

PARAMETER TO BE MEASURED	PAGE
RF Power Vs. DC Power Input SUBCLAUSE § 2.993	7
OCCUPIED BANDWIDTH §2.989	8
PEAK OUTPUT POWER SUBCLAUSE § 2.1046	18
CONDUCTED SPURIOUS EMISSIONS § 2.991	29
CONDUCTED SPURIOUS EMISSIONS§ 2.991	30
RADIATED SPURIOUS EMISSION §2.993	31
FREQUENCY STABILITY Vs. TEMPERATURE § 2.995	35
FREQUENCY STABILITY Vs. VOLTAGE § 2.991	37
TRANSIENT FREQUENCY BEHAVIOR §90.214	40
RECEIVER SPURIOUS RADIATION § 15.209	46
RECEIVER SPURIOUS EMISSIONS (conducted) § 15.209	47
TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS	52
Photographs of the equipment	54

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RF Power Vs. DC Power Input**SUBCLAUSE § 2.993**

Power (W)					
Frequency	440 MHz	450 MHz	460 MHz	470 MHz	490 MHz
Low power	59.52	61.44	62.40	63.84	63.36
High power	195.36	199.68	195.84	210.24	211.68
Measurement uncertainty	± 3 %				

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

-

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 8 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C


Relative humidity : 43%

OCCUPIED BANDWIDTH §2.989

440 MHz (max. power)



Marker 1 [T1] RBW 100 Hz RF Att 40 dB
 -36.73 dBm VBW 100 Hz
 42.7 dBm 439.98486974 MHz SWT 58 s Unit dBm



Date: 16.JUL.2001 10:56:20

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
 (for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 9 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

OCCUPIED BANDWIDTH


§2.989

450 MHz (max. power)



Ref Lvl
42.9 dBm

RBW	100 Hz	RF Att	40 dB
VBW	100 Hz		
SWT	58 s	Unit	dBm



Date: 16.JUL.2001 11:05:11

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 10 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

OCCUPIED BANDWIDTH


§2.989

460 MHz (max. power)



Ref Lvl
42.8 dBm

RBW	100 Hz	RF Att	40 dB
VBW	100 Hz		
SWT	58 s	Unit	dBm



Date: 16.JUL.2001 11:09:24

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 11 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

OCCUPIED BANDWIDTH


§2.989

470 MHz (max. power)



Ref Lvl
41.8 dBm

RBW 100 Hz RF Att 40 dB
VBW 100 Hz
SWT 58 s Unit dBm



Date: 16.JUL.2001 11:13:32

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 12 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

OCCUPIED BANDWIDTH

§2.989

490 MHz (max. power)



Marker 1 [T1]

RBW 100 Hz RF Att 40 dB

Ref Lvl -39.08 dBm

VBW 100 Hz


41.7 dBm

489.98342936 MHz

SWT 58 s

Unit

dBm



Date: 16.JUL.2001 11:17:46

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 13 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C


Relative humidity : 43%

OCCUPIED BANDWIDTH

§2.989

440 MHz (min. power)


 Ref Lvl 30.1 dBm
 RBW 100 Hz RF Att 30 dB
 VBW 100 Hz
 SWT 58 s Unit dBm



Date: 16. JUL. 2001 13:14:59

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 14 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C


Relative humidity : 43%

OCCUPIED BANDWIDTH

§2.989

450 MHz (min. power)

 Marker 1 [T1] RBW 100 Hz RF Att 30 dB
 Ref Lvl -44.39 dBm VBW 100 Hz
 30.6 dBm 449.98929108 MHz SWT 58 s Unit dBm



Date: 16.JUL.2001 13:27:03

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 15 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

OCCUPIED BANDWIDTH


§2.989

460 MHz (min. power)



Ref Lvl
30.8 dBm

RBW	100 Hz	RF Att	30 dB
VBW	100 Hz		
SWT	58 s	Unit	dBm



Date: 16.JUL.2001 13:32:27

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 16 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C


Relative humidity : 43%

OCCUPIED BANDWIDTH

§2.989

470 MHz (min. power)


 Marker 1 [T1] RBW 100 Hz RF Att 20 dB
 Ref Lvl -46.18 dBm VBW 100 Hz
 30 dBm 469.98838928 MHz SWT 58 s Unit dBm



Date: 16.JUL.2001 13:34:59

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 17 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C


Relative humidity : 43%

OCCUPIED BANDWIDTH

§2.989

490 MHz (min. power)


 Marker 1 [T1] RBW 100 Hz RF Att 20 dB
 Ref Lvl -43.55 dBm VBW 100 Hz
 29.2 dBm 489.98974198 MHz SWT 58 s Unit dBm



Date: 16.JUL.2001 13:38:39

measured with normal Test modulation : Pseudo random data stream max. 8kBit/s

LIMITS

SUBCLAUSE § 90.210

Emission Mask D – 12.5 kHz channel bandwidth

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

PEAK OUTPUT POWER SUBCLAUSE § 2.1046 (conducted)

TEST CONDITIONS			OUTPUT POWER (W)				
			440	450	460	470	490
Frequency (MHz)							
T _{nom} (23)° C	V _{nom} (48)V	Max	18.50	19.45	19.17	15.31	14.66
		Min	1.03	1.15	1.20	0.99	0.83
Maximum deviation from output power under extreme test conditions (dBc)			not applicable		not applicable		not applicable
Measurement uncertainty			±3dB				

RBW / VBW : 100 kHz

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 19 (74)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

440 MHz (max. power)



Date: 16.JUL.2001 10:51:21

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 20 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

450 MHz (max. power)



Ref Lvl
52.9 dBm

Marker 1 [T1]

42.89 dBm

449.98748747 MHz


RBW 100 kHz

VBW 100 kHz

SWT 5 ms

RF Att 50 dB

Unit dBm



Date: 16.JUL.2001 11:02:44

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 21 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

460 MHz (max. power)



Marker 1 [T1]

RBW 100 kHz RF Att 50 dB

Ref Lvl 42.83 dBm

VBW 100 kHz


52.9 dBm

459.98545842 MHz

SWT 5 ms

Unit

dBm



Date: 16. JUL. 2001 11:06:53

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 22 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

470 MHz (max. power)



Marker 1 [T1]

RBW 100 kHz RF Att 50 dB

Ref Lvl 41.85 dBm

VBW 100 kHz


52.8 dBm

469.98388026 MHz

SWT 5 ms

Unit

dBm



Date: 16.JUL.2001 11:11:09

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 23 (74)

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

490 MHz (max. power)


 Marker 1 [T1] RBW 100 kHz RF Att 50 dB
 Ref Lvl 41.66 dBm VBW 100 kHz
 51.8 dBm 489.98342936 MHz SWT 5 ms Unit dBm



Date: 16.JUL.2001 11:15:05

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 24 (74)

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

440 MHz (min. power)


 Marker 1 [T1] RBW 100 kHz RF Att 40 dB
 Ref Lvl 30.11 dBm VBW 100 kHz
 40 dBm 439.99312375 MHz SWT 5 ms Unit dBm



Date: 16. JUL. 2001 13:13:21

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 25 (74)

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

450 MHz (min. power)


 Ref Lvl 40.1 dBm
 Marker 1 [T1] 30.59 dBm
 449.98929108 MHz
 RBW 100 kHz RF Att 40 dB
 VBW 100 kHz
 SWT 5 ms Unit dBm



Date: 16.JUL.2001 13:22:33

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 26 (74)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

460 MHz (min. power)



Date: 16.JUL.2001 13:30:58

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 27 (74)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

470 MHz (min. power)



Date: 16.JUL.2001 13:33:32

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 28 (74)

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23° C

Relative humidity : 43%

Peak output power (conducted)

490 MHz (min. power)


 Marker 1 [T1] RBW 100 kHz RF Att 30 dB
 Ref Lvl 29.21 dBm VBW 100 kHz
 40 dBm 489.98974198 MHz SWT 5 ms Unit dBm



Date: 16.JUL.2001 13:36:26

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 29 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

CONDUCTED SPURIOUS EMISSIONS § 2.991

EMISSION LIMITATIONS					
f (MHz)		amplitude of emission (dBm)	limit max. allowed emmission power	actual attenuation below frequency of operation (dB)	results
No peaks found					
Measurement uncertainty		± 3dB			

RBW : 100 kHz VBW: 1 MHz

LIMITS

SUBCLAUSE § 2.991

Conducted spurious emissions shall be attenuated below the maximum level of emission of the carrier frequency in accordance with the following formula:

For 12.5 kHz channel bandwidth :

$$\text{Spurious attenuation in dB} = 50 + 10 \log_{10} (\text{Power output in watt})$$

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 30 (74)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

CONDUCTED SPURIOUS EMISSIONS § 2.991

Worst case measurement with 8 channels maximum power



Date: 16. JUL. 2001 11:40:22

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RADIATED SPURIOUS EMISSION §2.993

EMISSION LIMITATIONS					
f (MHz)	polarization	amplitude of emission (dBµV/m) QUASIPeAK	amplitude of emission (dBµV/m) average	limit max. allowed emission power (dBµV/m)	results
CH 1 – CH8					
31.04	H	QP	27.8	40.0	Complies
31.04	V	QP	30.8	40.0	Complies
Measurement uncertainty			± 3dB		

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RADIATED SPURIOUS EMISSIONS

Horizontal, 8 channels max power



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.209

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RADIATED SPURIOUS EMISSIONS

Vertical, 8 channels max power



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.209

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RADIATED SPURIOUS EMISSIONS

Vertical / Horizontal, 8 channels max power



f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.209

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

FREQUENCY STABILITY Vs. TEMPERATURE § 2.995

Temperature [° C]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
-30°	19	440	0,000000432	0,0432
-20°	19	440	0,000000432	0,0432
-10°	19	440	0,000000432	0,0432
0,0°	19	440	0,000004318	0,0432
+10°	19	440	0,000004318	0,0432
+20°	20	440	0,000004545	0,0455
+30°	20	440	0,000004545	0,0455
+40°	20	440	0,000004545	0,0455
+50°	20	440	0,000004545	0,0455
+60°	20	440	0,000004545	0,0455

Temperature [° C]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
-30°	20	450	0,000000444	0,0444
-20°	20	450	0,000000444	0,0444
-10°	20	450	0,000000444	0,0444
0,0°	20	450	0,000004444	0,0444
+10°	20	450	0,000004444	0,0444
+20°	20	450	0,000004444	0,0444
+30°	20	450	0,000004444	0,0444
+40°	20	450	0,000004444	0,0444
+50°	20	450	0,000004444	0,0444
+60°	20	450	0,000000444	0,0444

Temperature [° C]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
-30°	20	460	0,000000435	0,0435
-20°	20	460	0,000000435	0,0435
-10°	20	460	0,000000435	0,0435
0,0°	20	460	0,000004348	0,0435
+10°	20	460	0,000004348	0,0435
+20°	20	460	0,000004348	0,0435
+30°	20	460	0,000004348	0,0435
+40°	21	460	0,000004565	0,0457
+50°	21	460	0,000004565	0,0457
+60°	21	460	0,000004565	0,0457

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23° C

Relative humidity : 43%

FREQUENCY STABILITY Vs. TEMPERATURE § 2.995

Temperature [° C]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
-30°	21	470	0,000000447	0,0447
-20°	21	470	0,000000447	0,0447
-10°	21	470	0,000000447	0,0447
0,0°	21	470	0,000004468	0,0447
+10°	21	470	0,000004468	0,0447
+20°	21	470	0,000004468	0,0447
+30°	21	470	0,000004468	0,0447
+40°	22	470	0,000004681	0,0468
+50°	22	470	0,000004681	0,0468
+60°	22	470	0,000004681	0,0468

Temperature [° C]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
-30°	22	490	0,000000449	0,0449
-20°	22	490	0,000000449	0,0449
-10°	22	490	0,000000449	0,0449
0,0°	22	490	0,000004490	0,0449
+10°	22	490	0,000004490	0,0449
+20°	22	490	0,000004490	0,0449
+30°	22	490	0,000004490	0,0449
+40°	22	490	0,000004490	0,0449
+50°	22	490	0,000004490	0,0449
+60°	22	490	0,000004490	0,0449



LIMITS

SUBCLAUSE § 90.213

Temperature – Frequency Stability of 0.0005% from -30 to +60 °C

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

FREQUENCY STABILITY Vs. VOLTAGE § 2.991

nom. Voltage	nom. Voltage	Voltage [V]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
0,85	48	40,80	20	440	0,00000045	0,0455
0,88		42,24	20	440	0,00000045	0,0455
0,90		43,20	20	440	0,00000045	0,0455
0,93		44,64	20	440	0,00000045	0,0455
0,95		45,60	20	440	0,00000045	0,0455
0,98		47,04	20	440	0,00000045	0,0455
1,00		48,00	20	440	0,00000045	0,0455
1,03		49,44	20	440	0,00000045	0,0455
1,05		50,40	20	440	0,00000045	0,0455
1,08		51,84	20	440	0,00000045	0,0455
1,10		52,80	20	440	0,00000045	0,0455
1,13		54,24	20	440	0,00000045	0,0455
1,15		55,20	20	440	0,00000045	0,0455

nom. Voltage	nom. Voltage	Voltage [V]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
0,85	48	40,80	20	450	0,00000044	0,0444
0,88		42,24	20	450	0,00000044	0,0444
0,90		43,20	20	450	0,00000044	0,0444
0,93		44,64	20	450	0,00000044	0,0444
0,95		45,60	20	450	0,00000044	0,0444
0,98		47,04	20	450	0,00000044	0,0444
1,00		48,00	20	450	0,00000044	0,0444
1,03		49,44	20	450	0,00000044	0,0444
1,05		50,40	20	450	0,00000044	0,0444
1,08		51,84	20	450	0,00000044	0,0444
1,10		52,80	20	450	0,00000044	0,0444
1,13		54,24	20	450	0,00000044	0,0444
1,15		55,20	20	450	0,00000044	0,0444

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

FREQUENCY STABILITY Vs. VOLTAGE § 2.991

nom. Voltage	nom. Voltage	Voltage [V]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
0,85	48	40,80	20	460	0,00000043	0,0435
0,88		42,24	20	460	0,00000043	0,0435
0,90		43,20	20	460	0,00000043	0,0435
0,93		44,64	20	460	0,00000043	0,0435
0,95		45,60	20	460	0,00000043	0,0435
0,98		47,04	20	460	0,00000043	0,0435
1,00		48,00	20	460	0,00000043	0,0435
1,03		49,44	20	460	0,00000043	0,0435
1,05		50,40	20	460	0,00000043	0,0435
1,08		51,84	20	460	0,00000043	0,0435
1,10		52,80	20	460	0,00000043	0,0435
1,13		54,24	21	460	0,00000046	0,0457
1,15		55,20	21	460	0,00000046	0,0457

nom. Voltage	nom. Voltage	Voltage [V]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
0,85	48	40,80	21	470	0,00000045	0,0447
0,88		42,24	21	470	0,00000045	0,0447
0,90		43,20	21	470	0,00000045	0,0447
0,93		44,64	21	470	0,00000045	0,0447
0,95		45,60	21	470	0,00000045	0,0447
0,98		47,04	21	470	0,00000045	0,0447
1,00		48,00	21	470	0,00000045	0,0447
1,03		49,44	21	470	0,00000045	0,0447
1,05		50,40	21	470	0,00000045	0,0447
1,08		51,84	21	470	0,00000045	0,0447
1,10		52,80	21	470	0,00000045	0,0447
1,13		54,24	21	470	0,00000045	0,0447
1,15		55,20	21	470	0,00000045	0,0447

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

FREQUENCY STABILITY Vs. VOLTAGE § 2.991

nom. Voltage	nom. Voltage	Voltage [V]	Frequency error [Hz]	Frequency [MHz]	Error in %	Error in ppm
0,85	48	40,80	22	490	0,00000045	0,0449
0,88		42,24	22	490	0,00000045	0,0449
0,90		43,20	22	490	0,00000045	0,0449
0,93		44,64	22	490	0,00000045	0,0449
0,95		45,60	22	490	0,00000045	0,0449
0,98		47,04	22	490	0,00000045	0,0449
1,00		48,00	22	490	0,00000045	0,0449
1,03		49,44	22	490	0,00000045	0,0449
1,05		50,40	22	490	0,00000045	0,0449
1,08		51,84	22	490	0,00000045	0,0449
1,10		52,80	22	490	0,00000045	0,0449
1,13		54,24	22	490	0,00000045	0,0449
1,15		55,20	22	490	0,00000045	0,0449



LIMITS

SUBCLAUSE § 90.213

Power Supply Voltage – Frequency Stability of 0.0005% from 85% to 115% of nominal voltage

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23°C

Relative humidity : 43%


TRANSIENT FREQUENCY BEHAVIOR §90.214

440 MHz

hp awaiting trigger



hp awaiting trigger



REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

07, 64, 66 -68

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23°C

Relative humidity : 43%


TRANSIENT FREQUENCY BEHAVIOR §90.214

450 MHz

hp awaiting trigger



hp awaiting trigger



REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

07, 64, 66 -68

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23°C

Relative humidity : 43%


TRANSIENT FREQUENCY BEHAVIOR §90.214

460 MHz

hp awaiting trigger



hp awaiting trigger



REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

07, 64, 66-68

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23° C

Relative humidity : 43%


TRANSIENT FREQUENCY BEHAVIOR §90.214

470 MHz

hp stopped



hp awaiting trigger



REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

07, 64, 66 -68

Equipment under test : MC9600 BS8 G2


Ambient temperature : 23°C

Relative humidity : 43%


TRANSIENT FREQUENCY BEHAVIOR §90.214

490 MHz

hp awaiting trigger



hp awaiting trigger



REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

07, 64, 66-68

Equipment under test : MC9600 BS8 G2**Ambient temperature** : 23° C**Relative humidity** : 43%

This measurements are done in accordance with TEST SET-UP PROCEDURES used for Submitted Data.(2.2.19 of the TIA/EIA 603, specifically the triggering level was set in a different manner, as described in the TEST SET-UP PROCEDURES used for Submitted Data).

LIMITS**SUBCLAUSE § 90.214**

Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels			
	Maximum frequency difference	150 to 174 MHz	421 to 512 MHz
t₁	±12.5 kHz	5.0 ms	10.0 ms
t₂	±6.25 kHz	20.0 ms	25.0 ms
t₃	±12.5 kHz	5.0 ms	10.0ms

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

07, 64 , 66 -68

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RECEIVER SPURIOUS RADIATION

§ 15.209

Radiated

SPURIOUS EMISSIONS LEVEL (µV/m)								
CH 1 – CH 8								
f (MHz)	Detector Polarisation	Level (µV/m)	f (MHz)	Detector	Level (µV/m)	f (MHz)	Detector	Level (µV/m)
31.8	QP / H	31.5						
31.5	QP / V	28.7						
456.59	QP / H	38.6						
456.59	QP / V	38.0						
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1 GHz : RBW/VBW: 1 MHz

Measurement distance see table

Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 47 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%


RECEIVER SPURIOUS EMISSIONS (conducted)

§ 15.209



Ref Lvl
87 dBµV

RBW 100 kHz RF Att 10 dB
VBW 100 kHz
SWT 250 ms Unit dBµV



Date: 16. JUL. 2001 12:48:36

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1 GHz : RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 5_3682-A/00

Issue Date: 05.03.01

Page 48 (74)

Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%


RECEIVER SPURIOUS EMISSIONS (conducted)

§ 15.209



Ref Lvl
87 dBµV

RBW 100 kHz RF Att 10 dB
VBW 100 kHz
SWT 1 s Unit dBµV



Date: 16. JUL. 2001 12:49:17

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RECEIVER SPURIOUS RADIATION

§ 15.209



f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RECEIVER SPURIOUS RADIATION

§ 15.209



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : MC9600 BS8 G2

Ambient temperature : 23° C

Relative humidity : 43%

RECEIVER SPURIOUS RADIATION

§ 15.209



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	8566 A	Hewlett-Packard	1925A00257
02	Analyzer Display	8566 A	Hewlett-Packard	1925A00860
03	Oscilloscope	7633	Tektronix	230054
04	Radio Analyzer	CMTA 54	Rohde & Schwarz	894 043/010
05	System Power Supply	6038 A	Hewlett-Packard	2848A07027
06	Signal Generator	8111 A	Hewlett-Packard	2215G00867
07	Signal Generator	8662 A	Hewlett-Packard	2224A01012
08	Funktionsgenerator	AFGU	Rohde & Schwarz	862 480/032
09	Regeltrenntrafo	MPL	Erft	91350
10	Netznachbildung	NNLA 8120	Schwarzbeck	8120331
11	Relais-Matrix	PSU	Rohde & Schwarz	893 285/020
12	Power-Meter	436 A	Hewlett-Packard	2101A12378
13	Power-Sensor	8484 A	Hewlett-Packard	2237A10156
14	Power-Sensor	8482 A	Hewlett-Packard	2237A00616
15	Modulationsmeter	9008	Racal-Dana	2647
16	Frequenzzähler	5340 A	Hewlett-Packard	1532A03899
17	Absorber Schirmkabine	---	MWB	87400/002
18	Spectrum Analyzer	85660 B	Hewlett-Packard	2747A05306
19	Analyzer Display	85662 A	Hewlett-Packard	2816A16541
20	Quasi Peak Adapter	85650 A	Hewlett-Packard	2811A01131
21	RF-Preselector	85685 A	Hewlett-Packard	2833A00768
22	Biconical Antenne	3104	Emco	3758
23	Log. Per. Antenne	3146	Emco	2130
24	Double Ridge Horn	3115	Emco	3088
25	EMI-Testreceiver	ESAI	Rohde & Schwarz	863 180/013
26	EMI-Analyzer-Display	ESAI-D	Rohde & Schwarz	862 771/008
27	Biconical Antenne	HK 116	Rohde & Schwarz	888 945/013
28	Log. Per. Antenne	HL 223	Rohde & Schwarz	825 584/002
29	Relais-Switch-Unit	RSU	Rohde & Schwarz	375 339/002
30	Highpass	HM985955	FSY Microwave	001
31	Amplifier	P42-GA29	Tron-Tech	B 23602
32	Absorber Schirmkabine		Frankonia	
33	Steuerrechner	PSM 7	Rohde & Schwarz	834 621/004
34	EMI Test Receiver	ESMI	Rohde & Schwarz	827 063/010
35	EMI Test Receiver	Display	Rohde & Schwarz	829 808/010

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
36	Controler	HD 100	Deisel	100/322/93
37	Relais Matrix	PSN	Rohde & Schwarz	829 065/003
38	Control Unit	GB 016 A2	Rohde & Schwarz	344 122/008
39	Relais Switch Unit	RSU	Rohde & Schwarz	316 790/001
40	Power Supply	6032A	Hewlett Packard	2846A04063
41	Spektrum Monitor	EZM	Rohde & Schwarz	883 720/006
42	Meßempfänger	ESH 3	Rohde & Schwarz	890 174/002
43	Meßempfänger	ESVP	Rohde & Schwarz	891 752/005
44	Biconi Ant. 20-300MHz	HK 116	Rohde & Schwarz	833 162/011
45	Logper Ant. 0.3-1 GHz	HL 223	Rohde & Schwarz	832 914/010
46	Amplifier 0.1-4 GHz	AFS4	Miteq Inc.	206461
47	Logper Ant. 1-18 GHz	HL 024 A2	Rohde & Schwarz	342 662/002
48	Polarisationsnetzwerk	HL 024 Z1	Rohde & Schwarz	341 570/002
49	Double Ridge G Horn Antenne 1-26.5 GHz	3115	EMCO	9107-3696
50	Microw. Sys. Amplifier 0.5- 26.5 GHz	8317A	Hewlett Packard	3123A00105
51	Audio Analyzer	UPD	Rohde & Schwarz	1030.7500.04
52	Steuerrechner	PSM 7	Rohde & Schwarz	883 086/026
53	DC V-Netzwerk	ESH3-Z6	Rohde & Schwarz	861 406/005
54	DC V-Netzwerk	ESH3-Z6	Rohde & Schwarz	893 689/012
55	AC 2 Phasen V-Netzwerk	ESH3-Z5	Rohde & Schwarz	861 189/014
56	AC 2 Phasen V-Netzwerk	ESH3-Z5	Rohde & Schwarz	894 981/019
57	AC-3 Phasen V-Netzwerk	ESH2-Z5	Rohde & Schwarz	882 394/007
58	Stromversorgung	6032A	Rohde & Schwarz	2933A05441
59	HF-Test Empfänger	ESVP.52	Rohde & Schwarz	881 487/021
60	Spectrum Monitor	EZM	Rohde & Schwarz	883 086/026
61	HF-Test Empfänger	ESH3	Rohde & Schwarz	881 515/002
62	Relais Matrix	PSU	Rohde & Schwarz	882 943/029
63	Relais Matrix	PSU	Rohde & Schwarz	828 628/007
64	Spectrum Analyzer	FSIQ 26	Rohde & Schwarz	119.6001.27
65	Spectrum Analyzer	HP 8565E	Hewlett Packard	3473A00773
66	Bidirektionalkoppler	DC 3010	Amplifier res.	12306
67	Oscilloscope	54502A	HP	2934A01917
68	Radiocommunic.Analyz.	4040	Schlumberger	1725117

Photographs of the equipment

