

## MPE Analysis Report

The Equipment-Under-Test (EUT) M10 is a BluOS STREAMING AMPLIFIER. The EUT contains both WLAN (WiFi) and Bluetooth modules. The Bluetooth module has Bluetooth 4.0 BLE and Bluetooth 3.0 features. The EUT can accept analog audio signal, digital audio signal and wireless audio signal via Bluetooth devices. The EUT has internal power amplifiers and loudspeaker. The EUT is powered by 100-120VAC, 200-240VAC. The NFC is a 13.56MHz passive tag only.

### WiFi Module

Antenna Type: Internal, Integral

Antenna Gain: 2dBi

B mode: product tolerance +/-3dB

Nominal conducted power

| Frequency (MHz) |      | Output in dBm |
|-----------------|------|---------------|
| Low             |      | 17.11         |
| Channel:        | 2412 |               |
| Middle          |      | 17.20         |
| Channel:        | 2437 |               |
| High            |      | 17.21         |
| Channel:        | 2462 |               |

G mode: product tolerance +/-3dB

Nominal conducted power

| Frequency (MHz) |      | Output in dBm |
|-----------------|------|---------------|
| Low             |      | 19.34         |
| Channel:        | 2412 |               |
| Middle          |      | 19.89         |
| Channel:        | 2437 |               |
| High            |      | 19.91         |
| Channel:        | 2462 |               |

NHT20: product tolerance +/-3dB

Nominal conducted power

| Frequency (MHz) |      | Output in dBm |
|-----------------|------|---------------|
| Low             |      | 18.11         |
| Channel:        | 2412 |               |
| Middle          |      | 18.76         |
| Channel:        | 2437 |               |
| High            |      | 18.91         |
| Channel:        | 2462 |               |

## INTERTEK TESTING SERVICE

NHT40: product tolerance +/-3dB

Nominal conducted power

|                 | Frequency (MHz) | Output in dBm |
|-----------------|-----------------|---------------|
| Low Channel:    | 2422            | 18.69         |
| Middle Channel: | 2437            | 19.01         |
| High Channel:   | 2452            | 19.11         |

AC20: product tolerance +/-3dB

Nominal conducted power

|  | Frequency (MHz) | Conducted output power in dBm |
|--|-----------------|-------------------------------|
|  | 5180            | 4.6                           |
|  | 5200            | 4.3                           |
|  | 5240            | 4.2                           |
|  | 5745            | 4.8                           |
|  | 5785            | 2.8                           |
|  | 5825            | 1.6                           |

AC40: product tolerance +/-3dB

Nominal conducted power

|  | Frequency (MHz) | Conducted output power in dBm |
|--|-----------------|-------------------------------|
|  | 5190            | 4.1                           |
|  | 5230            | 4.2                           |
|  | 5755            | 4.3                           |
|  | 5795            | 2.5                           |

AC80 product tolerance +/-3dB

Nominal conducted power

|  | Frequency (MHz) | Conducted output power in dBm |
|--|-----------------|-------------------------------|
|  | 5210            | 5.3                           |
|  | 5775            | 4.3                           |

A mode: product tolerance +/-3dB

Nominal conducted power

|  | Frequency (MHz) | Conducted output power in dBm |
|--|-----------------|-------------------------------|
|  | 5180            | 7.6                           |
|  | 5200            | 6.5                           |
|  | 5240            | 6.0                           |
|  | 5745            | 7.1                           |
|  | 5785            | 4.4                           |
|  | 5825            | 3.8                           |

## INTERTEK TESTING SERVICE

NHT20: product tolerance +/-3dB

Nominal conducted power

| Frequency (MHz) | Conducted output power in dBm |
|-----------------|-------------------------------|
| 5180            | 4.5                           |
| 5200            | 3.9                           |
| 5240            | 4.1                           |
| 5745            | 4.7                           |
| 5785            | 3.5                           |
| 5825            | 2.2                           |

NHT40: product tolerance +/-3dB

Nominal conducted power

| Frequency (MHz) | Conducted output power in dBm |
|-----------------|-------------------------------|
| 5190            | 4.0                           |
| 5230            | 4.1                           |
| 5755            | 4.6                           |
| 5795            | 3.5                           |

### Bluetooth Module

Antenna Type: Internal, Integral

Antenna Gain: 2dBi

Bluetooth 3.0 and Bluetooth 4.0 BLE

EIRP range is 0dBm to 8dBm

Modulation type: GFSK

FCC ID: Q2O-NADM10

IC: 152B-NADM10

For Maximum Permissible Exposure (MPE) evaluation of the unit, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65 and meet the requirement listed in KDB447498.

1) For the Bluetooth portion of the unit, the measured powers among all the measured channels were within its production tolerance. The antenna gain is 2 dBi = 1.58 (num gain) and its maximum source-based time-averaging duty factor is 100%. From these data and its operating configuration, the exposed power density at a distance (R) of **Error! Reference source not found.**cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\begin{aligned} &\text{The EIRP radiated power} \\ &= 8 \text{ dBm} \\ &= 6.31 \text{ mW} \end{aligned}$$

$$\begin{aligned} &\text{The radiated (EIRP) source-based time-averaging output power} \\ &= (6.31 * 1) \text{ mW} \\ &= 6.31 \text{ mW} \end{aligned}$$

$$\begin{aligned} &\text{The power density at } \mathbf{Error! Reference source not found.} \text{cm} \\ &= 6.31 / 4\pi R^2 \\ &= 0.00126 \text{ mW cm}^{-2} \end{aligned}$$

2) For the WiFi portion of the unit, the measured powers among all the measured channels were within its production tolerance. The antenna gain is 2 dBi = 1.58 (num gain) and its maximum source-based time-averaging duty factor is 100%. From these data and its operating configuration, the exposed power density at a distance (R) of **Error! Reference source not found.**cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\begin{aligned} &\text{The EIRP radiated power} \\ &= \text{conducted power (with maximum tolerance) + antenna gain} \\ &= (19.91 + 3) + 2 \text{ dBm} \\ &= 24.91 \text{ dBm (309.74 mW)} \end{aligned}$$

$$\begin{aligned} &\text{The radiated (EIRP) source-based time-averaging output power} \\ &= (309.74 * 1) \text{ mW} \\ &= 309.74 \text{ mW} \end{aligned}$$

$$\begin{aligned} &\text{The power density at 20 cm from the antenna} \\ &= \text{EIRP} / 4\pi R^2 \\ &= 0.06165 \text{ mW cm}^{-2} \end{aligned}$$

In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 mWcm-2 for general population and uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons. The following RF exposure statement is proposed to be included in the user manual:

**“ FCC RF Radiation Exposure Statement**

**Caution: To maintain compliance with the FCC’s RF exposure guidelines, place the Internet Music System at least 20cm from nearby persons.”**

In addition, for this product with multiple transmitter and antenna (Bluetooth and WiFi), the requirement of Simultaneous Transmission evaluation has also been considered and has complied with the following conditions of the worse case;

$$MPE1/Limit1 + MPE2/Limit2 \leq 1$$

Thus,

$$\begin{array}{lcl} 0.00126/1 & + & 0.06165/1 \\ \text{Bluetooth} & & \text{WiFi} \end{array} = 0.06291$$

It is concluded that no Simultaneous Transmission evaluation is required.