

FCC Test Report

Product Name : TracKing V5

Trade Name : Thermo King

Model No. : TKV5

FCC ID : Q37TKV5

Applicant : Thermo King Corporation

Address : 314 West 90th Street, Minneapolis, MN USA 55420

Date of Receipt : Aug. 24, 2021

Issued Date : Nov. 12, 2021

Report No. : 2181021R-E3032110108

Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

The test report shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd.

Test Report Certification



Product Name : TracKing V5
Applicant : Thermo King Corporation
Address : 314 West 90th Street, Minneapolis, MN USA 55420
Manufacturer : Thermo King Corporation
Address : 314 West 90th Street, Minneapolis, MN USA 55420
Trade Name : Thermo King
Model No. : TKV5
FCC ID : Q37TKV5
EUT Voltage : DC 14.2V
Testing Voltage : DC 14.2V
Applicable Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10: 2013
Laboratory Name : Hsin Chu Laboratory
Address : No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu
County 310, Taiwan, R.O.C.
TEL: +886-3-582-8001 / FAX: +886-3-582-8958
Test Result : Complied

Documented By :



(Carol Tsai / Senior Engineering Adm. Specialist)

Approved By :



(Louis Hsu / Deputy Manager)

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	Nov. 12, 2021

TABLE OF CONTENTS

Description	Page
1. General Information	6
1.1 EUT Description	6
1.2 Test Mode	7
1.3 Comments and Remarks	7
1.4 Tested System Details	8
1.5 Configuration of tested System	8
1.6 EUT Operation of during Test	9
1.7 Test Facility	9
1.8 List of Test Equipment	11
1.9 Uncertainty	12
1.10 Duty Cycle	13
2. Maximum Conducted Output Power	14
2.1 Test Setup	14
2.2 Test Limit	14
2.3 Test procedures	14
2.4 Test Specification	14
2.5 Test Result of Maximum Conducted Output Power	15
3. Radiated Emission	16
3.1 Test Setup	16
3.2 Test Limit	17
3.3 Test Procedure	17
3.4 Test Specification	17
3.5 Test Result of Radiated Emissions (30MHz~1GHz)	18
3.6 Test Result of Radiated Emissions (1GHz~10 th Harmonic)	19
4. Antenna Port Conducted Emission	23
4.1 Test Setup	23
4.2 Test Limit	23
4.3 Test Procedure	23
4.4 Test Specification	23
4.5 Test Result of Antenna Port Conducted Emission	24
5. Radiated Emission Band Edge	27
5.1 Test Setup	27
5.2 Test Limit	27
5.3 Test Procedure	27
5.4 Test Specification	27
5.5 Test Result of Radiated Emission Band Edge	28
6. Occupied Bandwidth & DTS Bandwidth	34
6.1 Test Setup	34
6.2 Test Limit	34
6.3 Test Procedures	34
6.4 Test Specification	34
6.5 Test Result of Occupied Bandwidth	35
6.6 Test Result of DTS Bandwidth	37

7.	Maximum Power Spectral Density	39
7.1	Test Setup.....	39
7.2	Test Limit	39
7.3	Test Procedures.....	39
7.4	Test Specification.....	39
7.5	Test Result of Maximum Power Spectral Density.....	40
Appendix A.....		42
	Test Result of Radiated Emissions Co-location.....	42
Appendix B.....		44
	Test Setup Photograph	44

1. General Information

1.1 EUT Description

Product Name	TrackKing V5
Trade Name	Thermo King
Model No.	TKV5
Frequency Range	1Mbps: 2402~2480MHz 2Mbps: 2402~2480MHz
Channel Number	1Mbps: 40 Channels 2Mbps: 40 Channels
Type of Modulation	GFSK

Antenna Information				
Ant.	Trade Name	Model No.	Type	Gain (dBi)
0	N/A	N/A	PCB	2.80

GFSK (1Mbps/2Mbps)

Working Frequency of Each Channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	10	2422 MHz	20	2442 MHz	30	2462 MHz
01	2404 MHz	11	2424 MHz	21	2444 MHz	31	2464 MHz
02	2406 MHz	12	2426 MHz	22	2446 MHz	32	2466 MHz
03	2408 MHz	13	2428 MHz	23	2448 MHz	33	2468 MHz
04	2410 MHz	14	2430 MHz	24	2450 MHz	34	2470 MHz
05	2412 MHz	15	2432 MHz	25	2452 MHz	35	2472 MHz
06	2414 MHz	16	2434 MHz	26	2454 MHz	36	2474 MHz
07	2416MHz	17	2436 MHz	27	2456 MHz	37	2476 MHz
08	2418 MHz	18	2438 MHz	28	2458 MHz	38	2478 MHz
09	2420 MHz	19	2440 MHz	29	2460 MHz	39	2480 MHz

Note:

1. Regards to the frequency band operation; the lowest 、middle and highest frequency of channel were selected to perform the test, and then shown on this report.
2. The above EUT information is declared by the manufacturer.

1.2 Test Mode

DEKRA has verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Test Mode	Mode 1: Transmit
-----------	------------------

Test Items	Test Mode	Modulation	Channel	Result
AC Power Line Conducted Emission	It was supplied power by DC-Powered for EUT. It's not necessary to apply to AC Power Line Conducted Emission test.			
Maximum Conducted Output Power	Mode 1	GFSK (1Mbps)	00/19/39	Pass
		GFSK (2Mbps)	00/19/39	Pass
Radiated Emission Below 1GHz	Mode 1	GFSK (2Mbps)	39	Pass
Radiated Emission Above 1GHz	Mode 1	GFSK (1Mbps)	00/19/39	Pass
		GFSK (2Mbps)	00/19/39	Pass
Antenna Port Conducted Emission	Mode 1	GFSK (1Mbps)	00/19/39	Pass
		GFSK (2Mbps)	00/19/39	Pass
Radiated Emission Band Edge	Mode 1	GFSK (1Mbps)	00/19/39	Pass
		GFSK (2Mbps)	00/19/39	Pass
Occupied Bandwidth & DTS Bandwidth	Mode 1	GFSK (1Mbps)	00/19/39	Pass
		GFSK (2Mbps)	00/19/39	Pass
Maximum Power Spectral Density	Mode 1	GFSK (1Mbps)	00/19/39	Pass
		GFSK (2Mbps)	00/19/39	Pass

Note:

1. Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. For below 1 GHz radiated emission have performed all modes of operation were investigated and the worst-case emissions are reported.
3. The EUT was performed at X axis and Z axis position for radiated emission and band edge tests. The worst case was found at Z axis, so the measurement will follow this same test configuration.
4. The EUT could be applied with Bluetooth function and WWAN function; therefore Co-location Maximum Permissible Exposure (Please refer to DEKRA Report No.: 2181021R-E3032410101) and Radiated Emission Co-location (Please refer to Appendix A) tests are added for simultaneously transmit between Bluetooth function and WWAN function. <Simultaneous Transmission Analysis Mode: 1. Bluetooth function + WWAN WCDMA function, 2. Bluetooth function + WWAN LTE function>

1.3 Comments and Remarks


The product specification and testing instructions for the EUT declared in the report are provided by the manufacturer who will take all responsibilities for the accuracy.

1.4 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
1 Notebook	DELL	Latitude E6320	8611271467	N/A	AC in: Non-Shielded, 1.8m DC out: Shielded, 1.9m and with a core
2 Power Supply	Topward	6303D	8095908	N/A	Non-Shielded, 1.8m

1.5 Configuration of tested System



1.6 EUT Operation of during Test

1	Set the EUT as shown.
2	Execute the control software bgtool
3	Configure test mode, test channel and data rate.
4	Let the EUT start sending transmit continuously.
5	Verify that device is working properly

1.7 Test Facility

Ambient conditions in the laboratory:

Items	Test Item	Actually	Tested by	Test Date	Test Site
Temperature (°C)	Maximum Peak Conducted Output Power	25	Clemens Fang	2021/9/3	SR12-H
Humidity (%RH)		66			
Temperature (°C)	Radiated Emission	24.7	Ling Chen	2021/8/31	CB2-H
Humidity (%RH)		56			
Temperature (°C)	Antenna Port Conducted Emission	25	Clemens Fang	2021/9/3 ~ 2021/9/11	SR12-H
Humidity (%RH)		61 ~ 66			
Temperature (°C)	Radiated Emission Band Edge	24.7	Ling Chen	2021/8/31	CB2-H
Humidity (%RH)		56			
Temperature (°C)	Occupied Bandwidth & DTS Bandwidth	25	Clemens Fang	2021/9/3	SR12-H
Humidity (%RH)		66			
Temperature (°C)	Maximum Power Spectral Density	25	Clemens Fang	2021/9/3	SR12-H
Humidity (%RH)		66			

Note: Test site information refers to Laboratory Information.

Laboratory Information

USA : **FCC Registration Number: TW3024**
Canada : **CAB identifier : TW3024**

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our Web site: <http://www.dekra.com.tw>

If you have any comments, please don't hesitate to contact us. Our test sites as below:

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
Address	1. No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. 2. No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.
Phone number	1. +886-3-582-8001 2. +886-3-582-8001
Fax number	1. +886-3-582-8958 2. +886-3-582-8958
Email address	info.tw@dekra.com
Website	http://www.dekra.com.tw
Note: Test site number for address 1 includes SR2-H. Test site number for address 2 includes CB2-H, CB3-H, CB4-H, SR10-H and SR12-H.	

1.8 List of Test Equipment

CB2-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Signal Analyzer	R&S	FSVA40	101455	2020/10/12	2021/10/11
Signal & Spectrum Analyzer	R&S	FSV40	101049	2021/03/31	2022/03/30
Signal Analyzer	R&S	FSVA40	101435	2021/06/04	2022/06/03
EXA Signal Analyzer	Keysight	N9010A	MY51440132	2021/01/25	2022/01/24
Trilog Broadband Antenna	Schwarzbeck	VULB 9168	1272	2021/08/20	2022/08/19
Bilog Antenna	Teseq	CBL6112D	23191	2021/02/26	2022/02/25
Horn Antenna	Schwarzbeck	BBHA 9120D	639	2021/05/17	2022/05/16
Horn Antenna	Schwarzbeck	BBHA 9170	202	2020/12/16	2021/12/15
Pre-Amplifier	EMCI	EMC01820I	980365	2021/05/28	2022/05/27
Pre-Amplifier	EMEC	EM01G18GA	060741	2021/07/02	2022/07/01
Pre-Amplifier	DEKRA	AP-400C	201801231	2020/11/16	2021/11/15
Wideband Radio Communication Tester	R&S	CMW500	106071	2021/01/27	2022/01/26
Wireless Conn. Tseter	R&S	CMW500	157118	2021/07/07	2022/07/06
Coaxial Cable(13m)	Huber+Suhner	SF104	CB2-H	2021/08/17	2022/08/16
Radiated Software	AUDIX	e3 V9	CB2-H	N/A	N/A

SR12-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
High Speed Peak Power Meter Dual Input	Anritsu	ML2496A	1602004	2020/11/30	2021/11/29
Pulse Power Sensor	Anritsu	MA2411B	1531043	2020/11/30	2021/11/29
EXA Signal Analyzer	Keysight	N9010A	MY51440132	2021/01/25	2022/01/24
Pulse Power Sensor	Anritsu	MA2411B	1531044	2020/11/30	2021/11/29
Power Meter	Keysight	8990B	MY51000248	2021/05/21	2022/05/20
Power Sensor	Keysight	N1923A	MY57240005	2021/05/21	2022/05/20
Spectrum Analyzer	Keysight	N9030B	MY57140404	2021/05/14	2022/05/13
Spectrum Analyzer	Keysight	N9010B	MY57110159	2021/03/29	2022/03/28
Wideband Radio Communication Tester	R&S	CMW500	106071	2021/01/27	2022/01/26
Wireless Conn. Tseter	R&S	CMW500	157118	2021/07/07	2022/07/06
Spectrum Analyzer	Agilent	N9010A	US47140172	2021/05/28	2022/05/27
Signal & Spectrum Analyzer	R&S	FSV40	101049	2021/03/31	2022/03/30

Note: All equipment upon which need to calibrated are with calibration period of 1 year.


1.9 Uncertainty

Uncertainties have been calculated according to the DEKRA internal document with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Test item	Uncertainty
Maximum Conducted Output Power	± 1.16 dB
Radiated Emission	30MHz~1GHz as ± 3.4 dB 1GHz~26.5GHz as ± 3.46 dB
Antenna Port Conducted Emission	± 1.27 dB
Radiated Emission Band Edge	± 3.46 dB
Occupied Bandwidth & DTS Bandwidth	± 637 Hz
Maximum Power Spectral Density	± 2.11 dB


1.10 Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
GFSK (1Mbps)	2.125	2.500	85.00%	0.71	0.471
GFSK (2Mbps)	1.070	1.875	57.07%	2.44	0.935



2. Maximum Conducted Output Power

2.1 Test Setup



2.2 Test Limit

The Maximum Conducted Output Power shall be less 1 Watt.

2.3 Test procedures

The EUT was setup according to ANSI C63.10: 2013; tested according to DTS test procedure of KDB 558074 D01 v05r02 for compliance to FCC 47CFR 15.247 requirements.

2.4 Test Specification

According to FCC Part 15 Subpart C Paragraph 15.247.


2.5 Test Result of Maximum Conducted Output Power

Modulation	Channel	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
GFSK (1Mbps)	00	2402	11.100	≤ 30.00	Pass
	19	2440	8.160	≤ 30.00	Pass
	39	2480	8.380	≤ 30.00	Pass
GFSK (2Mbps)	00	2402	11.110	≤ 30.00	Pass
	19	2440	9.690	≤ 30.00	Pass
	39	2480	9.130	≤ 30.00	Pass


3. Radiated Emission

3.1 Test Setup


9kHz~30MHz



30MHz~1GHz



Above 1GHz



3.2 Test Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limit in paragraph 15.209, whichever is the lesser attenuation.

Frequency (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	20 log (2400/F(kHz))	300
0.490 – 1.705	24000/F(kHz)	20 log (24000/F(kHz))	30
1.705 - 30	30	29.5	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Remarks:

1. Field strength (dBuV/m) = 20 log Field strength (uV/m)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

3.3 Test Procedure

The EUT was setup according to ANSI C63.10: 2013 and tested according to DTS test procedure of KDB 558074 D01V05r02 for compliance to FCC 47CFR 15.247 requirements.

The EUT and its simulators are placed on a turn table which is 0.8 or 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

On any frequency or frequencies from 9kHz(include The the lowest oscillator frequency generated within the device up to the 10th harmonic) to 1000 MHz, the limit shown are based on measuring equipment employing a quasi-peak detector function and on any frequency or frequencies above 1000 MHz the radiated limit shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.


The bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

3.4 Test Specification

According to FCC Part 15 Subpart C Paragraph 15.247.

3.5 Test Result of Radiated Emissions (30MHz~1GHz)

Site :CB2-H
Condition :3m Horizontal
Mode :2M_TX_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBm	dBm	dB	dBm	dB	
1	154.645	34.34	43.50	-9.16	39.83	-5.49	QP
2	243.012	33.56	46.00	-12.44	37.30	-3.74	QP
3	300.048	36.91	46.00	-9.09	38.83	-1.92	QP
4	399.376	36.92	46.00	-9.08	35.75	1.17	QP
5	521.111	39.56	46.00	-6.44	36.15	3.41	QP
6	637.220	35.28	46.00	-10.72	29.98	5.30	QP

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line

Site :CB2-H
Condition :3m Vertical
Mode :2M_TX_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBm	dBm	dB	dBm	dB	
1	144.266	33.73	43.50	-9.77	38.44	-4.71	QP
2	336.617	34.02	46.00	-11.98	34.92	-0.90	QP
3	477.170	38.80	46.00	-7.20	35.87	2.93	QP
4	533.042	39.70	46.00	-6.30	35.82	3.88	QP
5	642.361	36.24	46.00	-9.76	30.97	5.27	QP
6	872.833	31.70	46.00	-14.30	24.12	7.58	QP

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line

3.6 Test Result of Radiated Emissions (1GHz~10th Harmonic)


Site :CB2-H
Condition :3m Horizontal
Mode :BLE_1M_TX_2402MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4884.000	48.83	74.00	-25.17	62.66	-13.83	Peak
2	7206.000	63.92	74.00	-10.08	68.66	-4.74	Peak
3	9608.000	53.56	74.00	-20.44	55.95	-2.39	Peak
4	12010.000	49.40	54.00	-4.60	48.74	0.66	Average
5	12018.000	61.66	74.00	-12.34	61.00	0.66	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.


Site :CB2-H
Condition :3m Vertical
Mode :BLE_1M_TX_2402MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4884.000	49.29	74.00	-24.71	63.12	-13.83	Peak
2	7206.000	65.64	74.00	-8.36	70.38	-4.74	Peak
3	9608.000	53.58	74.00	-20.42	55.97	-2.39	Peak
4	12010.000	53.62	54.00	-0.38	52.96	0.66	Average
5	12018.000	66.00	74.00	-8.00	65.34	0.66	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.


Site :CB2-H
Condition :3m Horizontal
Mode :BLE_1M_TX_2440MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4880.000	45.95	74.00	-28.05	59.49	-13.54	Peak
2	7320.000	49.09	54.00	-4.91	53.68	-4.59	Average
3	7320.000	58.22	74.00	-15.78	62.81	-4.59	Peak
4	9760.000	53.43	74.00	-20.57	55.46	-2.03	Peak
5	12200.000	44.55	54.00	-9.45	43.93	0.62	Average
6	12200.000	58.20	74.00	-15.80	57.58	0.62	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.


Site :CB2-H
Condition :3m Vertical
Mode :BLE_1M_TX_2440MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4880.000	46.11	74.00	-27.89	59.65	-13.54	Peak
2	7320.000	53.42	54.00	-0.58	58.01	-4.59	Average
3	7320.000	61.04	74.00	-12.96	65.63	-4.59	Peak
4	9760.000	54.11	74.00	-19.89	56.14	-2.83	Peak
5	12200.000	47.21	54.00	-6.79	46.59	0.62	Average
6	12200.000	59.48	74.00	-14.52	58.86	0.62	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_1M_TX_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	4960.000	45.67	74.00	-28.33	58.90	-13.23	Peak
2	7440.000	49.81	54.00	-4.19	54.25	-4.44	Average
3	7440.000	58.44	74.00	-15.56	62.88	-4.44	Peak
4	9920.000	55.35	74.00	-18.65	56.99	-1.64	Peak
5	12400.000	53.89	74.00	-20.11	53.31	0.58	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_1M_TX_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	4960.000	46.85	74.00	-27.15	60.08	-13.23	Peak
2	7440.000	53.78	54.00	-0.22	58.22	-4.44	Average
3	7440.000	63.82	74.00	-10.18	68.26	-4.44	Peak
4	9920.000	59.17	74.00	-14.83	60.81	-1.64	Peak
5	12400.000	45.58	54.00	-8.42	45.00	0.58	Average
6	12400.000	54.03	74.00	-19.97	53.45	0.58	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_2M_TX_2402MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	4884.000	48.14	74.00	-25.86	61.97	-13.83	Peak
2	7206.000	63.28	74.00	-10.72	68.02	-4.74	Peak
3	9608.000	54.13	74.00	-19.87	56.52	-2.39	Peak
4	12010.000	49.56	54.00	-4.44	48.90	0.66	Average
5	12010.000	60.71	74.00	-13.29	60.05	0.66	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_2M_TX_2402MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	4884.000	49.24	74.00	-24.76	63.07	-13.83	Peak
2	7206.000	64.59	74.00	-9.41	69.33	-4.74	Peak
3	9608.000	54.06	74.00	-19.94	56.45	-2.39	Peak
4	12010.000	53.93	54.00	-0.07	53.27	0.66	Average
5	12010.000	65.98	74.00	-8.02	65.32	0.66	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_2M_TX_2402MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	4880.000	48.68	74.00	-25.32	62.22	-13.54	Peak
2	7320.000	50.21	54.00	-3.79	54.80	-4.59	Average
3	7320.000	60.84	74.00	-13.16	65.43	-4.59	Peak
4	9760.000	55.64	74.00	-18.36	57.67	-2.03	Peak
5	12200.000	48.22	54.00	-5.78	47.60	0.62	Average
6	12200.000	56.35	74.00	-17.65	55.73	0.62	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_2M_TX_2402MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	4880.000	49.39	74.00	-24.61	62.93	-13.54	Peak
2	7320.000	53.70	54.00	-0.30	58.29	-4.59	Average
3	7320.000	63.74	74.00	-10.26	68.33	-4.59	Peak
4	9760.000	55.59	74.00	-18.41	57.62	-2.03	Peak
5	12200.000	49.12	54.00	-4.88	48.50	0.62	Average
6	12200.000	58.79	74.00	-15.21	58.17	0.62	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_2M_TX_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	44.26	74.00	-29.74	57.49	-13.23	Peak
2	7440.000	47.82	54.00	-6.18	52.26	-4.44	Average
3	7440.000	58.93	74.00	-15.07	63.37	-4.44	Peak
4	9920.000	52.42	74.00	-21.58	54.06	-1.64	Peak
5	12400.000	50.72	74.00	-23.28	50.14	0.58	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_2M_TX_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	45.18	74.00	-28.82	58.41	-13.23	Peak
2	7440.000	51.70	54.00	-2.30	56.14	-4.44	Average
3	7440.000	61.98	74.00	-12.02	66.42	-4.44	Peak
4	9920.000	52.75	74.00	-21.25	54.39	-1.64	Peak
5	12400.000	46.30	54.00	-7.70	45.72	0.58	Average
6	12400.000	57.35	74.00	-16.65	56.77	0.58	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

4. Antenna Port Conducted Emission

4.1 Test Setup



4.2 Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limit. If the transmitter complies with the conducted power limit based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limit specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limit specified in §15.209(a) (see §15.205(c)).

4.3 Test Procedure


The EUT was setup according to ANSI C63.10: 2013 and tested according to DTS test procedure of KDB 558074 D01 V05r02 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.



4.4 Test Specification

According to FCC Part 15 Subpart C Paragraph 15.247.



4.5 Test Result of Antenna Port Conducted Emission





GFSK (2Mbps) / 2402 MHz




GFSK (2Mbps) / 2440 MHz




GFSK (2Mbps) / 2480 MHz




GFSK (1Mbps) / 2402 MHz (Band Edge)


Date: 3.SEP.2021 14:27:22

GFSK (1Mbps) / 2480 MHz (Band Edge)

Date: 3.SEP.2021 14:33:11

GFSK (2Mbps) / 2402 MHz (Band Edge)


Date: 3.SEP.2021 14:47:07

GFSK (2Mbps) / 2480 MHz (Band Edge)

Date: 3.SEP.2021 14:52:44

5. Radiated Emission Band Edge

5.1 Test Setup



5.2 Test Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limit in paragraph 15.209, whichever is the lesser attenuation.

5.3 Test Procedure

The EUT was setup according to ANSI C63.10: 2013 and tested according to FHSS test procedure of FCC KDB 558074 D01 v05r02 for compliance to FCC 47CFR 15.247 requirements.

The EUT and its simulators are placed on a turn table which is 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.


Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

5.4 Test Specification

According to FCC Part 15 Subpart C Paragraph 15.247.

5.5 Test Result of Radiated Emission Band Edge


Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_1M_2402MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2382.800	62.03	74.00	-11.97	48.59	13.44	Peak
2	2401.800	107.48	-----	-----	93.92	13.56	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.


Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_1M_2402MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2363.600	43.20	54.00	-10.80	29.88	13.32	Average
2	2402.000	107.00	-----	-----	93.44	13.56	Average

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.


Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_1M_2402MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2387.600	63.04	74.00	-10.96	49.57	13.47	Peak
2	2401.800	108.18	-----	-----	94.62	13.56	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.


Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_1M_2402MHz
Test By :Ling



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2363.600	44.12	54.00	-9.88	30.80	13.32	Average
2	2402.000	107.70	-----	-----	94.14	13.56	Average

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_1M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2382.400	59.70	74.00	-14.30	46.26	13.44	Peak
2	2440.000	107.83	-----	-----	94.04	13.79	Peak
3	2483.600	57.53	74.00	-16.47	43.46	14.07	Peak

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_1M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2389.600	32.98	54.00	-21.02	19.50	13.48	Average
2	2440.000	107.37	-----	-----	93.58	13.79	Average
3	2500.000	33.45	54.00	-20.55	19.28	14.17	Average

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_1M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2382.200	59.42	74.00	-14.58	45.98	13.44	Peak
2	2440.000	109.76	-----	-----	95.97	13.79	Peak
3	2483.800	55.88	74.00	-18.12	41.81	14.07	Peak

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_1M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2387.800	32.84	54.00	-21.16	19.37	13.47	Average
2	2440.000	109.29	-----	-----	95.50	13.79	Average
3	2488.000	33.55	54.00	-20.45	19.46	14.09	Average

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_1M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	2480.000	109.56	74.00	-4.45	95.52	14.04	Peak
2	2499.200	69.55	74.00	-4.45	55.38	14.17	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_1M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	2480.000	109.13	74.00	-2.52	95.09	14.04	Average
2	2483.600	51.48	54.00	-2.52	37.41	14.07	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_1M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	2480.000	109.36	74.00	-3.78	95.32	14.04	Peak
2	2499.200	70.22	74.00	-3.78	56.05	14.17	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_1M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	2480.000	108.90	74.00	-2.65	94.86	14.04	Average
2	2483.600	51.35	54.00	-2.65	37.28	14.07	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_2M_2482MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2382.600	62.73	74.00	-11.27	49.29	13.44	Peak
2	2401.600	107.29	74.00	33.29	93.74	13.55	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_2M_2482MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2363.600	41.41	54.00	-12.59	28.09	13.32	Average
2	2402.000	105.58	54.00	51.58	92.02	13.56	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_2M_2482MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2382.400	62.08	74.00	-11.92	48.64	13.44	Peak
2	2401.600	106.81	74.00	32.81	93.26	13.55	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_2M_2482MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2363.600	41.32	54.00	-12.68	28.00	13.32	Average
2	2402.000	105.07	54.00	51.07	91.51	13.56	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_2M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2382.400	57.67	74.00	-16.33	44.23	13.44	Peak
2	2439.800	108.12	-----	-----	94.33	13.79	Peak
3	2483.600	54.83	74.00	-19.17	40.76	14.07	Peak

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_2M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2389.800	32.83	54.00	-21.17	19.35	13.48	Average
2	2440.000	106.44	-----	-----	92.65	13.79	Average
3	2498.400	33.60	54.00	-20.40	19.43	14.17	Average

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_2M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2382.800	59.80	74.00	-14.20	46.36	13.44	Peak
2	2440.200	109.62	-----	-----	95.82	13.80	Peak
3	2483.800	56.29	74.00	-17.71	42.22	14.07	Peak

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_2M_2440MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2389.200	32.69	54.00	-21.31	19.21	13.48	Average
2	2440.000	107.88	-----	-----	94.09	13.79	Average
3	2490.000	33.46	54.00	-20.54	19.35	14.11	Average

Note:

1. Level = Read level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_2M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2479.800	106.55	-----	-----	92.51	14.04	Peak
2	2483.600	65.85	74.00	-8.15	51.78	14.07	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Horizontal
Mode :BLE_TX_2M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.200	104.80	-----	-----	90.76	14.04	Average
2	2483.600	53.04	54.00	-0.96	38.97	14.07	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_2M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.200	107.13	-----	-----	93.09	14.04	Peak
2	2483.600	66.47	74.00	-7.53	52.40	14.07	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :CB2-H
Condition :3m Vertical
Mode :BLE_TX_2M_2480MHz
Test By :Ling




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.200	105.48	-----	-----	91.44	14.04	Average
2	2483.600	53.98	54.00	-0.02	39.91	14.07	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna - Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

6. Occupied Bandwidth & DTS Bandwidth

6.1 Test Setup



6.2 Test Limit

The 6 dB bandwidth: ≥ 500 kHz.

Occupied Bandwidth: NA

6.3 Test Procedures

The EUT was setup according to ANSI C63.10: 2013; tested according to DTS test procedure of KDB 558074 D01 V05r02 for compliance to FCC 47CFR 15.247 requirements.


6.4 Test Specification

According to FCC Part 15 Subpart C Paragraph 15.247.


6.5 Test Result of Occupied Bandwidth

Modulation	Channel	Frequency (MHz)	Measure Level (MHz)	Limit (MHz)
GFSK (1Mbps)	00	2402	1.028	-
	19	2440	1.028	-
	39	2480	1.028	-
GFSK (2Mbps)	00	2402	2.097	-
	19	2440	2.102	-
	39	2480	2.112	-


GFSK (1Mbps) / 2402 MHz




GFSK (1Mbps) / 2440 MHz




GFSK (1Mbps) / 2480 MHz




GFSK (2Mbps) / 2402 MHz



GFSK (2Mbps) / 2440 MHz




GFSK (2Mbps) / 2480 MHz




6.6 Test Result of DTS Bandwidth

Modulation	Channel	Frequency (MHz)	Measure Level (MHz)	Limit (MHz)	Result
GFSK (1Mbps)	00	2402	0.634	≥ 0.500	Pass
	19	2440	0.634	≥ 0.500	Pass
	39	2480	0.634	≥ 0.500	Pass
GFSK (2Mbps)	00	2402	1.098	≥ 0.500	Pass
	19	2440	1.103	≥ 0.500	Pass
	39	2480	1.103	≥ 0.500	Pass


GFSK (1Mbps) / 2402 MHz




GFSK (1Mbps) / 2440 MHz




GFSK (1Mbps) / 2480 MHz




GFSK (2Mbps) / 2402 MHz



GFSK (2Mbps) / 2440 MHz




GFSK (2Mbps) / 2480 MHz



7. Maximum Power Spectral Density

7.1 Test Setup



7.2 Test Limit

The peak power spectral density conducted from the intentional radiated to the antenna shall not be greater than +8dBm in any 3kHz band during any time interval of continuous transmission.

7.3 Test Procedures






The EUT was setup according to ANSI C63.10: 2013; tested according to DTS test procedure of KDB 558074 D01 V05r02 for compliance to FCC 47CFR 15.247 requirements.

7.4 Test Specification

According to FCC Part 15 Subpart C Paragraph 15.247

7.5 Test Result of Maximum Power Spectral Density

Modulation	Channel	Frequency (MHz)	Measure Value (dBm/3kHz)	Limit (dBm/3kHz)	Result
GFSK (1Mbps)	00	2402	-8.950	≤ 8.000	Pass
	19	2440	-8.770	≤ 8.000	Pass
	39	2480	-8.520	≤ 8.000	Pass
GFSK (2Mbps)	00	2402	-7.550	≤ 8.000	Pass
	19	2440	-8.800	≤ 8.000	Pass
	39	2480	-9.360	≤ 8.000	Pass

GFSK (1Mbps) / 2402 MHz**GFSK (1Mbps) / 2440 MHz****GFSK (1Mbps) / 2480 MHz****GFSK (2Mbps) / 2402 MHz****GFSK (2Mbps) / 2440 MHz****GFSK (2Mbps) / 2480 MHz**