TEST REPORT

Equipment Under Test : Bluetooth Dongle
Model No. : YBU-1200

Applicant : Yasing Technology Corp
Address of Applicant : 1F No.50, Ta Hsueh Rd.,Hsinchu 300,Taiwan R.O.C.

Standards:

FCC Part 15 subpart C

In the configuration tested, the EUT complied with the standards specified above.

Remarks:

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Taiwan E&E Services or testing done by SGS Taiwan E&E Services in connection with distribution or use of the product described in this report must be approved by SGS Taiwan E&E Services in writing.

Tested by : Alex Hsieh **Date : May. 15, 2003**

Approved by : Robert Chang **Date : Jun 20, 2003**

Contents

1. General Information
1.1 Testing Laboratory 3
1.2 Details of Applicant 3
1.3 Description of EUT(s) 3
1.4 Operation Procedure 4
1.5 Testing Method 4

2. Summary of Results 6
3. Instruments List 7
4. Measurements 8
4.1 Conducted Limits 8
4.2 Radiated emission Limits, general requirement 11
4.3 Channel Spacing 18
4.4 20db bandwidth / No. of channels 19
4.5 Average time of Occupancy 24
4.6 Peak output power 29
4.7 Band-edge emission 33
4.8 Spurious Emission under 25Ghz 35

APPENDIX
Photographs of Test Setup 47
Photographs of EUT 48-49

1. General Information

1.1 Testing Laboratory

SGS Taiwan Ltd. (FCC Registration number: 573967)
1F, No. 134, Wukung Road, Wuku industrial zone
Taipei county , Taiwan , R.O.C.
Telephone : +886-2-2299-3279
Fax : +886-2-2298-2698
Internet : http://www.sgs.com.tw

1.2 Details of Applicant

Applicant : Yasing Technology Corp
Address of Applicant: 1F No.50, Ta Hsueh Rd.,Hsinchu 300, Taiwan R.O.C.
Contact: Mr. Eric Deng
Telephone: +886-3-5750500

1.3 Description of EUT(s)

1	Product name	Bluetooth Dongle
2	Product ID	YBU-1200
3	Supply Voltage	USB Power Supply 5V±10%
4	Antenna Gain	1 dBi
5	Carrier Frequency	2402MHz to 2480MHz
6	Modulation Method	GFSK,1Mbps,0.5BT Gaussian
7	Hopping	1600hops/sec, 1MHz channel space
8	Output Interface	USB
9	Operation Temperature	-20 to +60 degree
10	Compliant	Bluetooth Specification Ver1.1

1.4 Operation Procedure

The Bluetooth is a FHSS system, and the output power and operating frequency are NOT End-user adjustable. Applicant offer a engineering software “BlueSuite” installed on PC to control the EUT. Setting of the software parameters are set as default. Operating frequency are set as testing required. The output power is set as Ext=255, Int=55 (at max. power). Inside the BlueSuite software, there is a BlueTest to control EUT hopping on or off. We select “Txdata1” (which modulated by pseudo-random sequence)and assign the transmit channel(as below). When the EUT is required to transmit in hopping on mode. We select “Txdata2”

The lowest operating frequency within Bluetooth specification is 2402Mhz, and highest operating frequency is 2480Mhz. So the frequency above are used as the lowest and highest frequency in the testing, and the middle frequency is set as 2441Mhz.

1.5 Testing Method

The testing standard follows CFR 47, Part 15.247 and ANSI C63.4 1992, and measurement method according to Public Notice DA00-705 (March 2000).

The Testing procedure is as following:
a. The EUT was plug in the USB port of PC and placed on the top of a rotating table 0.8 meters above the ground at a 3m chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna.
c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:
1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1

MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.
4. During the Output power testing, the manufacturer attach a test fixture which is a short cable that replace the antenna. So we use conducted method to measure the power. Hence the EIRP is the output power plus the antenna gain in dBi. Due to cable loss, the real value will equal to measured value(show on the instrument) add cable loss.

2.Summary of Results

subclause	Parameter to be measures	Verdict	Page
15.207	Conducted Limits	*PASS*	8
15.209	Radiated emission Limits, general requirement	*PASS*	11
15.247(a)(1)	Channel Spacing	*PASS*	18
15.247(a)(1)(ii)	20db bandwidth / No. of channels	*PASS*	19
15.247(a)(1)(ii)	Average Time of Occupacy	*PASS*	24
15.247(b)(1)	Peak Output power	*PASS*	29
15.247(c)	Band-Edge Emission	*PASS*	33
15.247(c)	Spurious Emission under 25Ghz	*PASS*	35

3. Instruments List

Instrument	Model	Serial number	Calibration date
Desktop PC	HP Pavillion 723D	N/A	N/A
Spectrum Analyzer	Agilent E7405A	US40240202	Jun 01, 2002
Spectrum Analyzer	R&S FSP 40	100034	Mar. 27, 2003
Antenna	Schwarzbeck BBHA9170A	184/185	July 01, 2002
Antenna	Schwarzbeck BBHA9120A	309/320	July 01, 2002
Antenna	Schwarzbeck VULB9163	152	July 01, 2002
Signal generator	R&S SMR 40	100210	Feb. 11, 2003
EMC Analyzer	HP 8594EM	3624A00203	Dec. 13, 2002
EMI Test Receiver	R&S ESCS 30	828985/004	Oct. 11, 2002
Transient Limiter	HP 11947A	3107A02062	Jul. 24, 2002
L.I.S.N	Rolf-Heine NNB-2/16Z	99012	Oct. 08, 2002

4. Measurements

4.1 Conducted Limits SUBCLAUSE 15.207

Line

Product Name: Bluetooth dongle Test Date: May,26,2003

Model No.: YBU-1200 Tester : Gallon

Test Mode: Operation Mode Temperature: 26 ℃

Test Result: PASS Humidity: 57 %

Main Terminals:L

FREQ MHz	QP1 dBuV	AVG1 dBuV	Factor	QP2 dBuV	AVG2 dBuV	QP Limit	AV Limit	QP Offset	AV Offset
0.15	28.8	12.5	3.00	31.80	15.50	66.00	56.00	-34.20	-40.50
0.17	25.1	17.4	2.96	28.06	20.36	65.04	55.04	-36.98	-34.68
0.2	22	12.8	2.90	24.90	15.70	63.61	53.61	-38.71	-37.91
0.28	30.4	27.5	2.82	33.22	30.32	60.91	50.91	-27.69	-20.59
0.49	20.3	14.7	2.91	23.21	17.61	56.19	46.19	-32.98	-28.58
1.3	16.4	10.9	2.89	19.29	13.79	56.00	46.00	-36.71	-32.21

1." -" denotes the emission level was - 10 dB beneth the Average limit,so nothing need to re-check anymore.

2. QP1/ AVG1 value means the QP/AV reading without the factor.

3. QP2/AVG2 value means the QP/AV final reading with the factor.

Neural

Product Name: Bluetooth dongle Test Date: May,26,2003

Model No.: YBU-1200 Tester : Gallon

Test Mode: Operation Mode Temperature: 26 ℃

Test Result: PASS Humidity: 57 %

Main
Terminals:N

FREQ MHz	QP1 dBuV	AVG1 dBuV	Factor	QP2 dBuV	AVG2 dBuV	QP Limit	AV Limit	QP Offset	AV Offset
0.17	29.7	17.6	2.96	32.66	20.56	65	55.04	-32.4	-34.48
0.21	26.80	17.30	2.89	29.69	20.19	63.27	53.27	-33.58	-33.08
0.28	32.40	29.80	2.82	35.22	32.62	60.91	50.91	-25.69	-18.29
0.45	19.10	13.80	2.95	22.05	16.75	56.93	46.93	-34.88	-30.18
1.31	16.00	10.60	2.89	18.89	13.49	56.00	46.00	-37.11	-32.51
2.35	16.50	11.10	3.11	19.61	14.21	56.00	46.00	-36.39	-31.79

1." -" denotes the emission level was - 10 dB beneth the Average limit,so nothing need to re-check anymore.

2. QP1/ AVG1 value means the QP/AV reading without the factor.

3. QP2/AVG2 value means the QP/AV final reading with the factor.

4.1.1 Limits (EN55022)

Frequency range Mhz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

4.2 Radiated emission Limits, general requirement SUBCLAUSE 15.209

1. Transmit at 2402Mhz, The Spectrum setting : RBW=120Khz , VBW=120Khz, **Vertical**



Freq(Mhz)	Level (dbuV/m)	Over Limit (db)	Limit Line (dbuV/m)	Read level (dbuV)	Antenna factor(db/m)	Cable loss (db)
30.00	33.14	-6.86	40.0	21.68	11.08	0.38
72.68	31.49	-8.51	40.0	23.90	6.95	0.64
109.54	30.07	-13.43	43.5	18.27	11.04	0.76
156.10	28.00	-15.50	43.5	19.30	7.82	0.88

202.66	33.30	-10.20	43.5	21.94	10.36	1.00
740.04	38.40	-7.60	46.0	15.18	20.91	2.31

2. Transmit at 2402Mhz, The Spectrum setting : RBW=120Khz , VBW=120Khz, **Horizontal**



Freq(Mhz)	Level (dbuV/m)	Over Limit (db)	Limit Line (dbuV/m)	Read level (dbuV)	Antenna factor(db/m)	Cable loss (db)
109.54	28.77	-14.73	43.5	16.96	11.04	0.76
146.40	25.79	-17.71	43.5	17.53	7.41	0.86
185.20	31.87	-11.63	43.5	21.16	9375	0.85

202.66	33.18	-10.32	43.5	21.82	10.36	1.00
239.52	29.75	-16.25	46.0	16.59	12.08	1.09
728.40	39.15	-6.85	46.0	16.37	20.50	2.28

3. Transmit at 2441Mhz, The Spectrum setting : RBW=120Khz , VBW=120Khz, **Vertical**



Freq(Mhz)	Level (dbuV/m)	Over Limit (db)	Limit Line (dbuV/m)	Read level (dbuV)	Antenna factor(db/m)	Cable loss (db)
74.62	30.29	-9.61	40.0	23.12	6.62	0.65
156.10	28.11	-15.39	43.5	19.41	7.82	0.88

202.66	29.52	-13.98	43.5	18.16	10.36	1.00
515.00	34.51	-11.49	46.0	15.17	17.46	1.89
850.62	39.78	-6.22	46.0	15.61	21.67	2.51

4. Transmit at 2441Mhz, The Spectrum setting : RBW=120Khz , VBW=120Khz,**Horizontal**



Freq(Mhz)	Level (dbuV/m)	Over Limit (db)	Limit Line (dbuV/m)	Read level (dbuV)	Antenna factor(db/m)	Cable loss (db)
109.54	28.83	-14.67	43.5	17.02	11.04	0.76

185.20	32.06	-11.44	43.5	21.36	9.75	0.95
202.66	33.48	-10.02	43.5	22.12	10.36	1.00
629.46	37.65	-8.35	46.0	16.04	19.49	2.13
763.32	39.16	-6.84	46.0	15.89	20.91	2.36
899.12	39.73	-6.27	46.0	15.00	22.16	2.57

5. Transmit at 2480Mhz, The Spectrum setting : RBW=120Khz , VBW=120Khz, **Vertical**



Freq(Mhz)	Level (dbuV/m)	Over Limit (db)	Limit Line (dbuV/m)	Read level (dbuV)	Antenna factor(db/m	Cable loss (db)

					)	
74.62	31.00	-9.00	40.0	23.74	6.62	0.65
109.54	30.09	-13.41	43.5	18.28	11.04	0.76
154.16	28.56	-14.94	43.5	19.98	7.71	0.88
187.14	28.20	-15.30	43.5	17.31	9.94	0.96
202.66	31.24	-12.26	43.5	19.88	10.36	1.00
652.74	37.41	-8.59	46.0	15.69	19.57	2.16

6. Transmit at 2480Mhz, The Spectrum setting : RBW=120Khz , VBW=120Khz,**Horizontal**



Freq(Mhz)	Level (dbuV/m)	Over Limit (db)	Limit Line (dbuV/m)	Read level (dbuV)	Antenna factor(db/m)	Cable loss (db)
47.46	27.50	-12.50	40.0	14.84	12.15	0.51
109.54	28.80	-14.70	43.5	16.99	11.04	0.76
185.20	31.38	-12.12	43.5	20.68	9.75	0.95
202.66	32.50	-11.00	43.5	21.14	10.36	1.00
602.30	37.17	-8.83	46.0	15.75	19.32	2.09
879.72	40.19	-5.81	46.0	15.53	22.12	2.54

4.2.1 Limits

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

4.3 Channel Spacing SUBCLAUSE15.247(a)(1)





4.4 No. of carrier frequency / 20db Bandwidth

SUBCLAUSE15.247(a)(1)(ii)



Number of channels = 79

Split the whole frequency band into two.


Agilent 14:54:15 May 2, 2003
Ref 80 dBµV/m
•Atten 0 dB
Peak
Log
10
dB/
Start
2.401000000 GHz
W1 S2
S3 FC
A
Start 2.401 GHz
•Res BW 120 kHz
•VBW 300 kHz
Stop 2.441 GHz
•Sweep 60 s (401 pts)
Freq/Channel
Center Freq
2.42100000 GHz
Start Freq
2.40100000 GHz
Stop Freq
2.44100000 GHz
CF Step
4.00000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Scale Type
Log Lin


Agilent 14:55:48 May 2, 2003
Ref 80 dBµV/m
•Atten 0 dB
Peak
Log
10
dB/
Stop
2.481000000 GHz
W1 S2
S3 FC
A
Start 2.441 GHz
•Res BW 120 kHz
•VBW 300 kHz
Stop 2.481 GHz
•Sweep 60 s (401 pts)
Freq/Channel
Center Freq
2.46100000 GHz
Start Freq
2.44100000 GHz
Stop Freq
2.48100000 GHz
CF Step
4.00000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Scale Type
Log Lin

20dB bandwidth at lowest (2402Mhz), middle(2441Mhz), highest channel(2480Mhz)



Channel bandwidth = 780 KHZ



Channel bandwidth =815 KHZ



Channel bandwidth =810 KHZ

4.5 Average Time of Occupancy SUBCLAUSE15.247(a)(1)(ii)


Agilent 11:44:31 Jul 3, 2003
Mkr1 137.5 ms
77.1 dBµV/m
Ref 107 dBµV/m
Atten 10 dB
Peak
Log
10
dB/
Marker
137.5000000 ms
77.1 dBµV/m
V1 S2
S3 FC
A AA
Center 2.402 GHz
Res BW 1 MHz
VBW 3 MHz
Span 0 Hz
Sweep 1 s (401 pts)
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2


Agilent 11:53:53 Jul 3, 2003
Mkr1 Δ -420 µs
0.681 dB
Ref 107 dBµV/m
Atten 10 dB
Peak
Log
10
dB/
Marker Δ
-420.0000000 µs
0.681 dB
Center 2.402 GHz
Res BW 1 MHz
VBW 3 MHz
Span 0 Hz
Sweep 4 ms (401 pts)
Marker Trace Type X Axis Amplitude
1R (1) Time 2.15 ms 76.71 dBµV/m
1Δ (1) Time -420 µs 0.681 dB
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2
No Peak Found


Agilent 11:46:05 Jul 3, 2003
Mkr1 727.5 ms
76.9 dBµV/m
Ref 107 dBµV/m
Atten 10 dB
Peak
Log
10
dB/
Marker
727.5000000 ms
76.9 dBµV/m
V1 S2
S3 FC
A AA
Center 2.441 GHz
Res BW 1 MHz
VBW 3 MHz
Span 0 Hz
Sweep 1 s (401 pts)
Peak Search
Meas Tools
Next Peak
Next Pk Right
Next Pk Left
Min Search
Pk-Pk Search
More
1 of 2


Agilent 11:52:10 Jul 3, 2003
Mkr1 Δ -410 µs
0.412 dB
Ref 107 dBµV/m
Atten 10 dB
Peak
Log
10
dB/
Marker Δ
-410.0000000 µs
0.412 dB
Center 2.441 GHz
Res BW 1 MHz
VBW 3 MHz
Span 0 Hz
Sweep 4 ms (401 pts)
Marker Trace Type X Axis Amplitude
1R (1) Time 2.13 ms 76.61 dBµV/m
1Δ (1) Time -410 µs 0.412 dB
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2
No Peak Found


Agilent 11:46:37 Jul 3, 2003
Mkr1 430 ms
75.51 dBµV/m
Ref 107 dBµV/m
Atten 10 dB
Peak
Log
10
dB/
Marker
430.0000000 ms
75.51 dBµV/m
V1 S2
S3 FC
A AA
Center 2.48 GHz
Res BW 1 MHz
VBW 3 MHz
Span 0 Hz
Sweep 1 s (401 pts)
Peak Search
Meas Tools
Next Peak
Next Pk Right
Next Pk Left
Min Search
Pk-Pk Search
More
1 of 2


Agilent 11:51:22 Jul 3, 2003
Mkr1 Δ -410 µs
0.584 dB
Ref 107 dBµV/m
Atten 10 dB
Peak
Log
10
dB/
Marker Δ
-410.0000000 µs
0.584 dB
Center 2.48 GHz
Res BW 1 MHz
VBW 3 MHz
Span 0 Hz
Sweep 4 ms (401 pts)
Marker Trace Type X Axis Amplitude
1R (1) Time 2.13 ms 75.2 dBµV/m
1Δ (1) Time -410 µs 0.584 dB
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2
No Peak Found

4.5.1 calculation

At channel 2401, 2441and 2480Mhz, there are 1 bursts in 1 sec. Time period of each burst is 420 μSec(worst case). So the occupacy time within 30 second is 420 x 10 x 30 = 126000 μSec = 126 mSec = 0.126 Sec.

4.5.2 Limits

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

The EUT comply with the requirement in Sec 15.247(a)(1) that use at least 75 hopping frequencies. The maximum 20dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

4.6 Peak output Power SUBCLAUSE15.247(b)(1)

Transmitter transmit at lowest channel (2402Mhz)



The Power (ERP) = Output power + cable loss + antenna gain

= -4.64 dbm + 2.7 db+ 1 dBi = -0.94 dbm

Transmitter transmit at middle channel (2441Mhz)



The Power (ERP) = Output power + cable loss + antenna gain

= -3.73 dbm + 2.7 db+ 1 dBi = -0.03 dbm

Transmitter transmit at highest channel (2480Mhz)



The Power (ERP) = Output power + cable loss + antenna gain

= -5.77 dbm + 2.7 db+ 1 dBi = -2.07 dbm

So the max power happens at 2441Mhz , which equals to –0.03 dbm = 1 mW

Limits:

For frequency hopping systems operating in the 2400-2483.5 MHz band employing At least 75 hopping channels, all frequency hopping systems in the 5725-5850MHZ Band, and all direct sequence systems: 1 Watt.

4.7 Band Edge emission SUBCLAUSE15.247(c)


Agilent 11:06:27 Jul 3, 2003
Mkr1 Δ -2.41 MHz
-32.17 dB
Ref 67.99 dBμV/m Atten 5 dB Ext PG 30 dB
Peak
Log
10
dB/
DI
30.4
dBμV/m
Marker Δ
-2.410000 MHz
-32.17 dB
Start 2.398 GHz
Stop 2.403 GHz
*Res BW 100 kHz
VBW 100 kHz
*Sweep 40 ms (401 pts)
Marker Trace Type X Axis Amplitude
1R (1) Freq 2.40283 GHz 50.43 dBμV/m
1Δ (1) Freq -2.41 MHz -32.17 dB
2 (1) Freq 2.39960 GHz 17.7 dBμV/m
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2
A:\BB9120D.ANT file loaded



	Lower bandedge	Upper bandedge
Bandedge difference from main channel	**32.17 db**	**30.12 db**

4.7.1 Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, and it must comply with the limit in 15.209.

4.8 Spurious Emission under 25Ghz (from 1Ghz) SUBCLAUSE15.247(c)

1. Transmit at 2402Mhz
1Ghz – 18Ghz , Vertical



18Ghz – 25Ghz , Vertical



1Ghz – 18Ghz , Horizontal



18Ghz – 25Ghz , Horizontal



2. Transmit at 2441Mhz
1Ghz – 18Ghz , Vertical



18Ghz – 25Ghz , Vertical



1Ghz – 18Ghz , Horizontal



18Ghz – 25Ghz , Horizontal



3. Transmit at 2480Mhz
1Ghz – 18Ghz , Vertical



18Ghz – 25Ghz , Vertical



1Ghz – 18Ghz , Horizontal



18Ghz – 25Ghz , Horizontal



APPENDIX: Photographs of Test Setup

(The Photos are saved separately)

APPENDIX : Photographs of EUT

Internal Photos

(The Photos are saved separately)

External Photos

(The Photos are saved separately)