



MPE/RF EXPOSURE TEST REPORT

FCC CFR 47 Part 1.1310

REPORT No.: RDWN64-U2_MPE Rev A

Company: Radwin Ltd.

Model Name: RADWIN JET DUO 5.x/5.x GHz

MPE/RF EXPOSURE TEST REPORT

Company: Radwin Ltd.

Model: RADWIN JET DUO 5.x/5.x GHz

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: RDWN64-U2_MPE Rev A

This report supersedes: NONE

Applicant: Radwin Ltd.
27 Habarzel Street
Tel Aviv, 6971039
Israel

Issue Date: 12th September 2019

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

The calculations in the table below use the highest conducted power value together with the *highest* antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels. The Radio System, can transmit simultaneously, but not on same channel.

Outdoor System – Professional Installation

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
5150-5250	7.0	5.01	28.75	749.89	0.748	5.00	11.96
5150-5250	7.0	5.01	28.69	739.61	0.737	5.00	11.79
5725 - 5850	9.0	7.94	26.97	497.74	0.787	5.00	12.57
5725- 5850	9.0	7.94	26.77	475.34	0.751	5.00	12.01

The following assessments are worst case exposure conditions where the RADWIN JET DUO 5.x/5.x GHz contains 2 radio modules:- 2 x 5GHz 802.11 with both radios transmitting simultaneously;-

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance for Summation (cm)	Power Density Limit (mW/cm ²) E _{ref}	Power Density (mW/cm ²) @5cm	Summation E _i /E _{ref} @ 20 cm
5725 - 5850	9.0	7.94	26.97	497.74				
5725- 5850	9.0	7.94	26.77	475.34				
EIRP TOTAL (mW/EIRP) :				7726.3	20 cm distance Total Evaluation:			1.54 mW/cm²

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits – Professional Installation

FCC §1.1310 Table 1
 1500 to 100,000MHz = 5 mW/cm²



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com