



MPE/RF EXPOSURE REPORT

FCC CFR 47 Part 1.1310

Report No.: RDWN73-U2_FCC_MPE Rev A

Company: Radwin

Model Name: NEO, NEO DUO

MPE/RF EXPOSURE REPORT

Company Name: Radwin

Model Name: NEO, NEO DUO

To: FCC CFR 47 Part 1.1310

Report Serial No.: RDWN73-U2_FCC_MPE Rev A

This report supersedes: NONE

Applicant: Radwin
27 Habarzel Street
Tel Aviv, 6971039
Israel

Issue Date: 19th April 2021

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d (\text{mW/cm}^2) = \text{EIRP} / (4 * \pi * d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ { (G (\text{dBi}) / 10)}$$

These calculations represent worst case in terms of the exposure levels.

Limits for Occupational/Controlled Exposure for professional installation: 5 mW/cm²

Non-Beamforming

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm ²) @ Safe Distance
5150.0 - 5250.0	10.00	10.00	25.75	375.84	0.748	5.00	7.734	5.00
5250.0-5350.0	10.00	10.00	19.91	97.95	0.195	5.00	3.948	5.00
5470.0-5725.0	10.00	10.00	19.87	97.05	0.193	5.00	3.930	5.00
5725.0 - 5850.0	11.00	12.59	24.98	314.77	0.788	5.00	7.942	5.00

Beamforming

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm ²) @ Safe Distance
5150.0 - 5250.0	16.00	39.81	19.95	98.86	0.783	5.00	7.91	5.00
5250.0-5350.0	16.00	39.81	13.88	24.43	0.194	5.00	3.93	5.00
5470.0-5725.0	16.00	39.81	13.93	24.72	0.196	5.00	3.96	5.00
5725.0 - 5850.0	17.00	50.12	18.93	78.16	0.779	5.00	7.90	5.00

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

The following assessments are worst case exposure conditions where the RADWIN NEO DUO contains 2 radio modules:- 2 x 5GHz 802.11 with both radios transmitting simultaneously;-

Non-BeamForming

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²) E _{ref}	Min Calculated safe distance for Limit (cm)	Summation E _i /E _{ref} @ 20 cm
5150.0 - 5250.0	16.00	39.81	19.95	98.86	0.748	5.00	7.734	0.748
5725.0 - 5850.0	17.00	50.12	18.93	78.16	0.788	5.00	7.942	0.788
EIRP TOTAL (mW/EIRP) :				7721.15	20 cm distance Total Evaluation:			1.54 mW/cm²

BeamForming

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)	Summation E _i /E _{ref} @ 20 cm
5150.0 - 5250.0	16.00	39.81	19.95	98.86	0.783	5.00	7.91	0.783
5725.0 - 5850.0	17.00	50.12	18.93	78.16	0.779	5.00	7.90	0.779
EIRP TOTAL (mW/EIRP) :				7852.9195	20 cm distance Total Evaluation:			1.56 mW/cm²

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 5mW / cm² from 1.310 Table 1



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com