



REGULATORY COMPLIANCE REPORT

FCC CFR 47 Part 1.1310

Report No.: RDWN97-U3 Rev A (FCC MPE)

Company: Radwin Ltd.

Model Name: RADWIN 2000 EC00, RADWIN 2000 EI00,
RADWIN 2000 E CON EC00, RADWIN 2000 E INT EI00

REGULATORY COMPLIANCE REPORT

Company Name: Radwin Ltd.

Model Name: RADWIN 2000 EC00, RADWIN 2000 EI00,
RADWIN 2000 E CON EC00, RADWIN 2000 E INT EI00

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: RDWN97-U3 Rev A (FCC MPE)

This report supersedes: NONE

Applicant: Radwin Ltd.
27 Habarzel Street
Tel Aviv, 6971039
Israel

Issue Date: 11th June 2024

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



TESTING CERT #2381.01

MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = $EIRP / (4 * \pi * d^2)$

$EIRP = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

Because the EUT belongs to the Occupational/Controlled Exposure the limit of power density is 5 mW/cm².

The calculations in the table below use the highest conducted power values (with respect to the limit for the BW mode) together with the highest antenna gains per antenna type (Panel Antenna and Dish Antenna) specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
4900-5000	22.0	158.49	23.47	222.33	7.01	5.0	23.68
4900-5000	32.0	1584.89	23.47	222.33	70.1	5.0	74.89

From the above assessment the minimum separation distance is **75 cm** per the requirements of FCC Title 47 subpart §1.1310 for Occupational/Controlled Exposure limits.

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310 for Occupational/Controlled Exposure.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com