



FCC RF Test Report

APPLICANT : CIPHERLAB CO. LTD.
EQUIPMENT : Mobile Computer
BRAND NAME : CIPHERLAB
MODEL NAME : RK96
FCC ID : Q3N-RK96
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Oct. 21, 2025 ~ Jan. 04, 2026

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (Shenzhen)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	9
1.6 Testing Location	10
1.7 Test Software.....	10
1.8 Applicable Standards.....	11
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	12
2.1 Carrier Frequency and Channel	12
2.2 Test Mode.....	13
2.3 Connection Diagram of Test System.....	15
2.4 Support Unit used in test configuration and system	16
2.5 EUT Operation Test Setup	16
2.6 Measurement Results Explanation Example.....	16
3 TEST RESULT	17
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	17
3.2 Maximum Conducted Output Power Measurement	19
3.3 Power Spectral Density Measurement	27
3.4 Unwanted Emissions Measurement	30
3.5 AC Conducted Emission Measurement.....	35
3.6 Antenna Requirements	37
4 LIST OF MEASURING EQUIPMENT	38
5 MEASUREMENT UNCERTAINTY	39
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR532510E	Rev. 01	Initial issue of report	Jan. 06, 2026



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.09 dB at 5639.06 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 16.50 dB at 0.454 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

CIPHERLAB CO. LTD.

12F., 333, DunHua S. Rd., Sec. 2, Taipei, Taiwan 10669

1.2 Manufacturer

CIPHERLAB CO. LTD.

12F., 333, DunHua S. Rd., Sec. 2, Taipei, Taiwan 10669

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Computer
Brand Name	CIPHERLAB
Model Name	RK96
FCC ID	Q3N-RK96
SN Code	Conducted: GO12580000169 Conduction: G012580000139 Radiation: AS2580001892
HW Version	V1.02
SW Version	RK96.22.20250915
EUT Stage	DVT

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	MIMO <Ant. 1 + 2> <5180 MHz ~ 5240 MHz> 802.11a : 15.33 dBm / 0.0341 W 802.11n HT20 : 15.69 dBm / 0.0371 W 802.11n HT40 : 18.53 dBm / 0.0713 W 802.11ac VHT20: 15.56 dBm / 0.0360 W 802.11ac VHT40: 18.44 dBm / 0.0698 W 802.11ac VHT80: 19.05 dBm / 0.0804 W 802.11ac VHT160: 19.00 dBm / 0.0794 W 802.11ax HE20: 15.88 dBm / 0.0387 W 802.11ax HE40: 18.52 dBm / 0.0711 W 802.11ax HE80: 19.08 dBm / 0.0809 W 802.11ax HE160: 19.04 dBm / 0.0802 W 802.11be EHT20: 16.05 dBm / 0.0403 W 802.11be EHT40: 18.62 dBm / 0.0728 W 802.11be EHT80: 19.11 dBm / 0.0815 W 802.11be EHT160: 19.09 dBm / 0.0811 W <5260 MHz ~ 5320 MHz> 802.11a : 22.40 dBm / 0.1738 W 802.11n HT20 : 21.27 dBm / 0.1340 W 802.11n HT40 : 21.52 dBm / 0.1419 W 802.11ac VHT20: 21.20 dBm / 0.1318 W 802.11ac VHT40: 21.48 dBm / 0.1406 W 802.11ac VHT80: 21.41 dBm / 0.1384 W 802.11ax HE20: 21.36 dBm / 0.1368 W 802.11ax HE40: 21.57 dBm / 0.1435 W 802.11ax HE80: 21.45 dBm / 0.1396 W 802.11be EHT20: 21.52 dBm / 0.1419 W 802.11be EHT40: 21.66 dBm / 0.1466 W 802.11be EHT80: 21.56 dBm / 0.1432 W <5500 MHz ~ 5720 MHz > 802.11a : 22.55 dBm / 0.1799 W 802.11n HT20 : 21.42 dBm / 0.1387 W 802.11n HT40 : 21.73 dBm / 0.1489 W 802.11ac VHT20: 21.32 dBm / 0.1355 W 802.11ac VHT40: 21.68 dBm / 0.1472 W 802.11ac VHT80: 21.64 dBm / 0.1459 W 802.11ac VHT160: 20.63 dBm / 0.1156 W 802.11ax HE20: 21.56 dBm / 0.1432 W 802.11ax HE40: 21.77 dBm / 0.1503 W 802.11ax HE80: 21.68 dBm / 0.1472 W 802.11ax HE160: 20.69 dBm / 0.1172 W 802.11be EHT20: 21.73 dBm / 0.1489 W 802.11be EHT40: 21.89 dBm / 0.1545 W 802.11be EHT80: 21.77 dBm / 0.1503 W 802.11be EHT160: 20.72 dBm / 0.1180 W <5745 MHz ~ 5825 MHz>



	802.11a : 22.85 dBm / 0.1928 W 802.11n HT20 : 22.98 dBm / 0.1986 W 802.11n HT40 : 21.20 dBm / 0.1318 W 802.11ac VHT20: 21.90 dBm / 0.1549 W 802.11ac VHT40: 21.14 dBm / 0.1300 W 802.11ac VHT80: 21.46 dBm / 0.1400 W 802.11ax HE20: 21.99 dBm / 0.1581 W 802.11ax HE40: 21.54 dBm / 0.1426 W 802.11ax HE80: 21.50 dBm / 0.1413 W 802.11be EHT20: 22.06 dBm / 0.1607 W 802.11be EHT40: 21.58 dBm / 0.1439 W 802.11be EHT80: 21.58 dBm / 0.1439 W
99% Occupied Bandwidth	<5180 MHz ~ 5240 MHz> 802.11a : 17.814 MHz 802.11n HT20 : 18.906 MHz 802.11n HT40 : 37.340 MHz 802.11ac VHT80 : 77.256 MHz 802.11ac VHT160 : 160.56 MHz 802.11be EHT20: 19.222 MHz 802.11be EHT40: 38.476 MHz 802.11be EHT80: 77.896 MHz 802.11be EHT160: 161.200 MHz <5260 MHz ~ 5320 MHz> 802.11a : 20.818 MHz 802.11n HT20 : 20.014 MHz 802.11n HT40 : 39.572 MHz 802.11ac VHT80 : 77.016 MHz 802.11be EHT20: 19.454 MHz 802.11be EHT40: 39.092 MHz 802.11be EHT80: 78.904 MHz <5500 MHz ~ 5720 MHz> 802.11a : 21.434 MHz 802.11n HT20 : 21.774 MHz 802.11n HT40 : 37.804 MHz 802.11ac VHT80 : 78.312 MHz 802.11ac VHT160 : 160.91 MHz 802.11be EHT20: 19.518 MHz 802.11be EHT40: 39.100 MHz 802.11be EHT80: 79.176 MHz 802.11be EHT160: 165.650 MHz <5745 MHz ~ 5825 MHz> 802.11a : 19.062 MHz 802.11n HT20 : 19.530 MHz 802.11n HT40 : 38.204 MHz 802.11ac VHT80 : 77.752 MHz 802.11be EHT20: 19.478 MHz 802.11be EHT40: 38.740 MHz 802.11be EHT80: 79.144 MHz

Antenna Type / Gain	<5180 MHz ~ 5240 MHz> <Ant. 1> : Monopole(LDS) Antenna with gain 3.38 dBi <Ant. 2> : Monopole(LDS) Antenna with gain 2.97 dBi <5260 MHz ~ 5320 MHz> <Ant. 1> : Monopole(LDS) Antenna with gain 3.5 dBi <Ant. 2> : Monopole(LDS) Antenna with gain 2.19 dBi <5500 MHz ~ 5720 MHz> <Ant. 1> : Monopole(LDS) Antenna with gain 2.11 dBi <Ant. 2> : Monopole(LDS) Antenna with gain 2.11 dBi <5745 MHz ~ 5825 MHz> <Ant. 1> : Monopole(LDS) Antenna with gain 1.75 dBi <Ant. 2> : Monopole(LDS) Antenna with gain 1.68 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) 802.11be : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM / 4096QAM)

Note:

1. The Ant.1/ Ant.2 in this report correspond to Ant.7/ Ant.8 in the antenna report.
2. WLAN MIMO support CDD mode.
3. For WLAN SISO/MIMO mode, the whole testing has assessed only MIMO mode by referring to their higher conducted power.
4. For 802.11n/11ac mode, the whole testing has assessed only 802.11n HT20/HT40 by referring to the higher output power for conducted test items.
5. For 802.11ax/11be mode, the whole testing has assessed only 802.11be EHT20/ EHT40/ EHT80/ EHT160 by referring to their higher conducted power.
6. 802.11ax/be support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) test output power/PSD, the full RU PSD > partial RU, therefore the full RU perform full, and partial RU verify bandedge/spurious.
7. 802.11be support small size RU, Large size RU and Puncturing modes as below, and these partial RU Power/PSD less than full RU, therefore these partial RU only assess Power Density/RSE.

<Small size RU 52+26 Tone>:

Bandwidth	Tones		Index		For test modes configure
20MHz	26	52	1	38	1
20MHz	52	26	38	4	2
20MHz	52	26	39	7	3

<Small size RU 106+26 Tone>:

Bandwidth	Tones		Index		For test modes configure
20MHz	106	26	53	4	1
20MHz	26	106	4	54	2

<Large size RU 484+242 tone> & <80M BW Puncturing 20MHz>:

Bandwidth	Tones		Index		For test modes configure
80MHz	242	484	62	66	1
80MHz	242	484	61	66	2
80MHz	484	242	65	64	3
80MHz	484	242	65	63	4

<Large size RU 996+484 tone> & <160M BW Puncturing 40MHz>:

Bandwidth	Tones		Index		For test modes configure
160MHz	484-Left	996-Right	66-Left	67-Right	1
160MHz	484-Left	996-Right	65-Left	67-Right	2
160MHz	996-Left	484-Right	67-Left	66-Right	3
160MHz	996-Left	484-Right	67-Left	65-Right	4

<Large size RU 996+484+242 tone> & <160M BW Puncturing 20MHz>:

Bandwidth	Tones			Index			For test modes configure
160MHz	242-Left	484-Left	996-Right	62-Left	66-Left	67-Right	1
160MHz	242-Left	484-Left	996-Right	61-Left	66-Left	67-Right	2
160MHz	484-Left	242-Left	996-Right	65-Left	64-Left	67-Right	3
160MHz	484-Left	242-Left	996-Right	65-Left	63-Left	67-Right	4
160MHz	996-Left	242-Right	484-Right	67-Left	62-Right	66-Right	5
160MHz	996-Left	242-Right	484-Right	67-Left	61-Right	66-Right	6
160MHz	996-Left	484-Right	242-Right	67-Left	65-Right	64-Right	7
160MHz	996-Left	484-Right	242-Right	67-Left	65-Right	63-Right	8

Only the worse cases are shown in this report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH03-KS	CN1257	314309

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Note: Test data subcontracted: conducted test case in section 3.1~3.3 of this report

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH03-KS	AUDIX	E3	210616
2.	CO01-KS	AUDIX	E3	6.2009-8-24



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2020

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210	50 ^{##}	5250
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290	-	-
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700
Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640
	-	-	114 ^{##}	5570

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 [#]	5690	144	5720
	142*	5710	-	-

Note:

1. The above Frequency and Channel in "*" are 40MHz bandwidth.
2. The above Frequency and Channel in "[#]" are 80MHz bandwidth.
3. The above Frequency and Channel in "^{##}" are 160MHz bandwidth.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11be EHT20	MCS0
802.11be EHT40	MCS0
802.11be EHT80	MCS0
802.11be EHT160	MCS0

AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter)
Remark: For Radiated Test Cases, The tests were performance with Adapter and USB Cable	

RSE Co-location mode
Bluetooth-LE_GSKF CH38 2478MHz + WIFI 802.11be EHT40 CH151 5755MHz
WIFI 802.11b CH01 2412MHz + 802.11be EHT40 CH151 5755MHz



Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		20M BW	20M BW	20M BW	20M BW
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		40M BW	40M BW	40M BW	40M BW
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		80M BW	80M BW	80M BW	80M BW
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	122	-
Straddle		-	-	138	-


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		160M BW		160M BW	160M BW
M	Middle	50		114	-

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	Shielded cable DC O/P 1.8m, Unshielded AC I/P cable 1.8m
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.73 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.73 + 10 = 14.73 \text{ (dB)}
 \end{aligned}$$



3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 & ANSI C63.10-2020 clause 12.5.1 for 6dB BW and 12.5.2 for 26dB BW and 6.9.3 for 99% occupied bandwidth measurements.

☒	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	1. Set RBW = shall be in the range of 1% to 5% of the emission bandwidth. 2. Set the VBW > RBW. 3. Detector = Peak. 4. Trace mode = max hold 5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%. 6. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) $\geq 3 * RBW$. 7. Measure and record the results in the test report.
☒	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	1. Set RBW = 100 kHz. 2. Set the VBW $\geq 3 \times RBW$. 3. Detector = Peak. 4. Trace mode = max hold 5. Measure the maximum width of the emission that is 6 dB down from the peak of the emission. 6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log_{10} B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.
4. For MIMO mode, the measure-and-sum technique should be used for measuring the in-band transmit power of a device.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup





3.2.5 Test Result of Maximum Conducted Output Power

UNII-1																
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	36	Full	5180	0.04	0.04	12.45	11.56	15.04	24.00		3.38		Pass	13
11a	6Mbps	2	44	Full	5220	0.04	0.04	12.09	11.53	14.83	24.00		3.38		Pass	13
11a	6Mbps	2	48	Full	5240	0.04	0.04	12.52	12.10	15.33	24.00		3.38		Pass	13.5
HT20	MCS0	2	36	Full	5180	0.01	0.02	12.61	12.04	15.34	24.00		3.38		Pass	13.5
HT20	MCS0	2	44	Full	5220	0.01	0.02	12.45	12.11	15.29	24.00		3.38		Pass	13.5
HT20	MCS0	2	48	Full	5240	0.01	0.02	12.79	12.56	15.69	24.00		3.38		Pass	14
HT40	MCS0	2	38	Full	5190	0.01	0.02	15.34	14.68	18.03	24.00		3.38		Pass	16
HT40	MCS0	2	46	Full	5230	0.01	0.02	15.76	15.27	18.53	24.00		3.38		Pass	16.5
VHT20	MCS0	2	36	Full	5180	0.01	0.01	12.52	11.92	15.24	24.00		3.38		Pass	13.5
VHT20	MCS0	2	44	Full	5220	0.01	0.01	12.34	12.01	15.19	24.00		3.38		Pass	13.5
VHT20	MCS0	2	48	Full	5240	0.01	0.01	12.71	12.39	15.56	24.00		3.38		Pass	14
VHT40	MCS0	2	38	Full	5190	0.01	0.01	15.23	14.61	17.95	24.00		3.38		Pass	16
VHT40	MCS0	2	46	Full	5230	0.01	0.01	15.66	15.18	18.44	24.00		3.38		Pass	16.5
VHT80	MCS0	2	42	Full	5210	0.02	0.01	16.37	15.68	19.05	24.00		3.38		Pass	17
VHT160	MCS0	2	50	Full	5250	0.01	0.02	16.28	15.67	19.00	24.00		3.38		Pass	17
HE20	MCS0	2	36	Full	5180	0.02	0.02	12.77	12.15	15.48	24.00		3.38		Pass	13.5
				26/0		0.02	0.02	2.01	1.35	4.70	24.00		3.38		Pass	4
				52/37		0.02	0.02	6.22	5.56	8.91	24.00		3.38		Pass	7
				106/53		0.02	0.02	8.28	9.11	11.73	24.00		3.38		Pass	9.5
			44	Full	5220	0.02	0.02	12.59	12.24	15.42	24.00		3.38		Pass	13.5
			48	Full	5240	0.02	0.02	12.96	12.78	15.88	24.00		3.38		Pass	14
HE40	MCS0	2	38	Full	5190	0.02	0.01	15.34	14.69	18.04	24.00		3.38		Pass	16
			46	Full	5230	0.01	0.01	15.75	15.26	18.52	24.00		3.38		Pass	16.5
HE80	MCS0	2	42	Full	5210	0.01	0.02	16.39	15.72	19.08	24.00		3.38		Pass	17
HE160	MCS0	2	50	Full	5250	0.01	0.01	16.31	15.72	19.04	24.00		3.38		Pass	17

UNII-1																
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
EHT20	MCS0	2	36	Full	5180	0.01	0.01	12.96	12.27	15.64	24.00	3.38	Pass	13.5		
				26/0		0.01	0.01	2.04	1.41	4.75	24.00	3.38	Pass	4		
				52/37		0.01	0.01	6.29	5.64	8.99	24.00	3.38	Pass	7		
				106/53		0.01	0.01	8.31	9.20	11.79	24.00	3.38	Pass	9.5		
			44	Full	5220	0.01	0.01	12.77	12.38	15.59	24.00	3.38	Pass	13.5		
			48	Full	5240	0.01	0.01	13.12	12.96	16.05	24.00	3.38	Pass	14		
EHT40	MCS0	2	38	Full	5190	0.01	0.01	15.42	14.78	18.13	24.00	3.38	Pass	16		
			46	Full	5230	0.01	0.01	15.84	15.36	18.62	24.00	3.38	Pass	16.5		
EHT80	MCS0	2	42	Full	5210	0.01	0.02	16.41	15.77	19.11	24.00	3.38	Pass	17		
EHT160	MCS0	2	50	Full	5250	0.02	0.01	16.37	15.78	19.09	24.00	3.38	Pass	17		



UNII-2A																	
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2			
11a	6Mbps	2	52	Full	5260	0.04	0.04	19.56	19.13	22.36	23.98	3.50	26.99	Pass	20.5		
11a	6Mbps	2	60	Full	5300	0.04	0.04	19.36	19.26	22.32	23.98	3.50	26.99	Pass	20.5		
11a	6Mbps	2	64	Full	5320	0.04	0.04	19.45	19.32	22.40	23.98	3.50	26.99	Pass	20.5		
HT20	MCS0	2	52	Full	5260	0.01	0.02	18.37	18.14	21.27	23.98	3.50	26.99	Pass	19.5		
HT20	MCS0	2	60	Full	5300	0.01	0.02	18.19	18.13	21.17	23.98	3.50	26.99	Pass	19.5		
HT20	MCS0	2	64	Full	5320	0.01	0.02	18.21	18.18	21.20	23.98	3.50	26.99	Pass	19.5		
HT40	MCS0	2	54	Full	5270	0.01	0.02	18.73	18.27	21.52	23.98	3.50	26.99	Pass	19.5		
HT40	MCS0	2	62	Full	5310	0.01	0.02	18.42	18.24	21.34	23.98	3.50	26.99	Pass	19.5		
VHT20	MCS0	2	52	Full	5260	0.01	0.01	18.31	18.07	21.20	23.98	3.50	26.99	Pass	19.5		
VHT20	MCS0	2	60	Full	5300	0.01	0.01	18.11	18.06	21.10	23.98	3.50	26.99	Pass	19.5		
VHT20	MCS0	2	64	Full	5320	0.01	0.01	18.15	18.04	21.11	23.98	3.50	26.99	Pass	19.5		
VHT40	MCS0	2	54	Full	5270	0.01	0.01	18.70	18.21	21.48	23.98	3.50	26.99	Pass	19.5		
VHT40	MCS0	2	62	Full	5310	0.01	0.01	18.33	18.19	21.28	23.98	3.50	26.99	Pass	19.5		
VHT80	MCS0	2	58	Full	5290	0.02	0.01	18.51	18.29	21.41	23.98	3.50	26.99	Pass	19.5		
HE20	MCS0	2	52	Full	5260	0.02	0.02	18.50	18.21	21.36	23.98	3.50	26.99	Pass	19.5		
			60	Full	5300	0.02	0.02	18.32	18.21	21.27	23.98	3.50	26.99	Pass	19.5		
			64	Full	5320	0.02	0.02	18.33	18.25	21.30	23.98	3.50	26.99	Pass	19.5		
				26/8		0.02	0.02	8.02	8.25	11.15	23.98	3.50	26.99	Pass	9.5		
				52/40		0.02	0.02	10.49	11.70	14.15	23.98	3.50	26.99	Pass	12.5		
				106/54		0.02	0.02	13.55	14.98	17.33	23.98	3.50	26.99	Pass	15.5		
HE40	MCS0	2	54	Full	5270	0.02	0.01	18.79	18.31	21.57	23.98	3.50	26.99	Pass	19.5		
			62	Full	5310	0.02	0.01	18.49	18.29	21.40	23.98	3.50	26.99	Pass	19.5		
HE80	MCS0	2	58	Full	5290	0.01	0.02	18.53	18.34	21.45	23.98	3.50	26.99	Pass	19.5		

UNII-2A																	
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2			
EHT20	MCS0	2	52	Full	5260	0.01	0.01	18.65	18.36	21.52	23.98		3.50		26.99	Pass	19.5
			60	Full	5300	0.01	0.01	18.49	18.37	21.44	23.98		3.50		26.99	Pass	19.5
			64	Full	5320	0.01	0.01	18.48	18.40	21.45	23.98		3.50		26.99	Pass	19.5
				26/8		0.01	0.01	8.08	8.34	11.22	23.98		3.50		26.99	Pass	9.5
				52/40		0.01	0.01	10.56	11.79	14.23	23.98		3.50		26.99	Pass	12.5
				106/54		0.01	0.01	13.61	15.03	17.39	23.98		3.50		26.99	Pass	15.5
EHT40	MCS0	2	54	Full	5270	0.01	0.01	18.87	18.41	21.66	23.98		3.50		26.99	Pass	19.5
			62	Full	5310	0.01	0.01	18.58	18.40	21.50	23.98		3.50		26.99	Pass	19.5
EHT80	MCS0	2	58	Full	5290	0.01	0.02	18.67	18.42	21.56	23.98		3.50		26.99	Pass	19.5



UNII-2C																	
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2			
11a	6Mbps	2	100	Full	5500	0.04	0.04	19.48	19.27	22.39	23.98	2.11	26.99	Pass	20.5		
11a	6Mbps	2	116	Full	5580	0.04	0.04	19.37	18.70	22.06	23.98	2.11	26.99	Pass	20		
11a	6Mbps	2	140	Full	5700	0.04	0.04	18.96	17.99	21.51	23.98	2.11	26.99	Pass	19.5		
11a	6Mbps	2	144	Full	5720	0.04	0.04	19.96	19.08	22.55	23.98	2.11	26.99	Pass	20.5		
HT20	MCS0	2	100	Full	5500	0.01	0.02	18.40	18.24	21.33	23.98	2.11	26.99	Pass	19.5		
HT20	MCS0	2	116	Full	5580	0.01	0.02	18.63	18.19	21.42	23.98	2.11	26.99	Pass	19.5		
HT20	MCS0	2	140	Full	5700	0.01	0.02	18.67	18.12	21.41	23.98	2.11	26.99	Pass	19.5		
HT20	MCS0	2	144	Full	5720	0.01	0.02	18.58	18.13	21.37	23.98	2.11	26.99	Pass	19.5		
HT40	MCS0	2	102	Full	5510	0.01	0.02	18.66	18.45	21.57	23.98	2.11	26.99	Pass	19.5		
HT40	MCS0	2	110	Full	5550	0.01	0.02	18.77	18.67	21.73	23.98	2.11	26.99	Pass	19.5		
HT40	MCS0	2	134	Full	5670	0.01	0.02	18.77	18.16	21.49	23.98	2.11	26.99	Pass	19.5		
HT40	MCS0	2	142	Full	5710	0.01	0.02	18.84	18.14	21.52	23.98	2.11	26.99	Pass	19.5		
VHT20	MCS0	2	100	Full	5500	0.01	0.01	18.34	18.12	21.24	23.98	2.11	26.99	Pass	19.5		
VHT20	MCS0	2	116	Full	5580	0.01	0.01	18.51	18.10	21.32	23.98	2.11	26.99	Pass	19.5		
VHT20	MCS0	2	140	Full	5700	0.01	0.01	18.50	18.05	21.29	23.98	2.11	26.99	Pass	19.5		
VHT20	MCS0	2	144	Full	5720	0.01	0.01	18.43	18.06	21.26	23.98	2.11	26.99	Pass	19.5		
VHT40	MCS0	2	102	Full	5510	0.01	0.01	18.61	18.40	21.52	23.98	2.11	26.99	Pass	19.5		
VHT40	MCS0	2	110	Full	5550	0.01	0.01	18.73	18.60	21.68	23.98	2.11	26.99	Pass	19.5		
VHT40	MCS0	2	134	Full	5670	0.01	0.01	18.73	18.11	21.45	23.98	2.11	26.99	Pass	19.5		
VHT40	MCS0	2	142	Full	5710	0.01	0.01	18.80	18.09	21.47	23.98	2.11	26.99	Pass	19.5		
VHT80	MCS0	2	106	Full	5530	0.02	0.01	18.86	18.39	21.64	23.98	2.11	26.99	Pass	19.5		
VHT80	MCS0	2	122	Full	5610	0.02	0.01	18.87	18.33	21.62	23.98	2.11	26.99	Pass	19.5		
VHT80	MCS0	2	138	Full	5690	0.02	0.01	18.88	18.13	21.53	23.98	2.11	26.99	Pass	19.5		
VHT160	MCS0	2	114	Full	5570	0.01	0.02	17.76	17.48	20.63	23.98	2.11	26.99	Pass	18.5		
HE20	MCS0	2	100	Full	5500	0.02	0.02	18.53	18.35	21.45	23.98	2.11	26.99	Pass	19.5		
				26/0		0.02	0.02	8.51	8.47	11.50	23.98	2.11	26.99	Pass	9.5		
				52/37		0.02	0.02	11.50	11.65	14.59	23.98	2.11	26.99	Pass	12.5		
				106/53		0.02	0.02	14.66	15.03	17.86	23.98	2.11	26.99	Pass	15.5		
			116	Full	5580	0.02	0.02	18.79	18.31	21.56	23.98	2.11	26.99	Pass	19.5		
			140	Full	5700	0.02	0.02	18.80	18.15	21.49	23.98	2.11	26.99	Pass	19.5		
				26/8		0.02	0.02	10.42	9.22	12.87	23.98	2.11	26.99	Pass	10		
				52/40		0.02	0.02	12.69	11.95	15.35	23.98	2.11	26.99	Pass	13		
				106/54		0.02	0.02	16.00	15.01	18.54	23.98	2.11	26.99	Pass	16		
			144	Full	5720	0.02	0.02	18.71	18.16	21.45	23.98	2.11	26.99	Pass	19.5		
HE40	MCS0	2	102	Full	5510	0.02	0.01	18.72	18.49	21.62	23.98	2.11	26.99	Pass	19.5		
			110	Full	5550	0.02	0.01	18.83	18.69	21.77	23.98	2.11	26.99	Pass	19.5		
			134	Full	5670	0.02	0.01	18.84	18.18	21.53	23.98	2.11	26.99	Pass	19.5		
			142	Full	5710	0.02	0.01	18.90	18.16	21.56	23.98	2.11	26.99	Pass	19.5		



HE80	MCS0	2	106	Full	5530	0.01	0.02	18.89	18.43	21.68	23.98	2.11	26.99	Pass	19.5
			122	Full	5610	0.01	0.02	18.90	18.38	21.66	23.98	2.11	26.99	Pass	19.5
			138	Full	5690	0.01	0.02	18.90	18.17	21.56	23.98	2.11	26.99	Pass	19.5
HE160	MCS0	2	114	Full	5570	0.01	0.01	17.81	17.53	20.69	23.98	2.11	26.99	Pass	18.5

UNII-2C																	
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2			
EHT20	MCS0	2	100	Full	5500	0.01	0.01	18.68	18.50	21.60	23.98	2.11	26.99	26.99	Pass	19.5	
				26/0		0.01	0.01	8.59	8.57	11.59	23.98	2.11	26.99	26.99	Pass	9.5	
				52/37		0.01	0.01	11.61	11.79	14.71	23.98	2.11	26.99	26.99	Pass	12.5	
				106/53		0.01	0.01	14.75	15.16	17.97	23.98	2.11	26.99	26.99	Pass	15.5	
			116	Full	5580	0.01	0.01	18.96	18.46	21.73	23.98	2.11	26.99	26.99	Pass	19.5	
			140	Full	5700	0.01	0.01	18.95	18.16	21.58	23.98	2.11	26.99	26.99	Pass	19.5	
				26/8		0.01	0.01	10.47	9.29	12.93	23.98	2.11	26.99	26.99	Pass	10	
				52/40		0.01	0.01	12.77	12.04	15.43	23.98	2.11	26.99	26.99	Pass	13	
				106/54		0.01	0.01	16.08	15.13	18.64	23.98	2.11	26.99	26.99	Pass	16	
			144	Full	5720	0.01	0.01	18.99	18.18	21.62	23.98	2.11	26.99	26.99	Pass	19.5	
EHT40	MCS0	2	102	Full	5510	0.01	0.01	18.83	18.59	21.73	23.98	2.11	26.99	26.99	Pass	19.5	
			110	Full	5550	0.01	0.01	18.96	18.79	21.89	23.98	2.11	26.99	26.99	Pass	19.5	
			134	Full	5670	0.01	0.01	18.93	18.23	21.61	23.98	2.11	26.99	26.99	Pass	19.5	
			142	Full	5710	0.01	0.01	18.99	18.19	21.62	23.98	2.11	26.99	26.99	Pass	19.5	
EHT80	MCS0	2	106	Full	5530	0.01	0.02	18.97	18.54	21.77	23.98	2.11	26.99	26.99	Pass	19.5	
			122	Full	5610	0.01	0.02	18.99	18.46	21.74	23.98	2.11	26.99	26.99	Pass	19.5	
			138	Full	5690	0.01	0.02	18.98	18.21	21.62	23.98	2.11	26.99	26.99	Pass	19.5	
EHT160	MCS0	2	114	Full	5570	0.02	0.01	17.87	17.55	20.72	23.98	2.11	26.99	26.99	Pass	18.5	



UNII-3																
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	149	Full	5745	0.04	0.04	20.45	19.13	22.85	30.00	1.75	Pass	20.5		
11a	6Mbps	2	157	Full	5785	0.04	0.04	20.22	19.00	22.66	30.00	1.75	Pass	20.5		
11a	6Mbps	2	165	Full	5825	0.04	0.04	19.93	19.05	22.52	30.00	1.75	Pass	20.5		
HT20	MCS0	2	149	Full	5745	0.01	0.02	20.51	19.35	22.98	30.00	1.75	Pass	20.5		
HT20	MCS0	2	157	Full	5785	0.01	0.02	20.24	19.02	22.68	30.00	1.75	Pass	20.5		
HT20	MCS0	2	165	Full	5825	0.01	0.02	19.85	19.00	22.46	30.00	1.75	Pass	20.5		
HT40	MCS0	2	151	Full	5755	0.01	0.02	18.20	18.17	21.20	30.00	1.75	Pass	19.5		
HT40	MCS0	2	159	Full	5795	0.01	0.02	18.08	18.07	21.09	30.00	1.75	Pass	19.5		
VHT20	MCS0	2	149	Full	5745	0.01	0.01	19.50	18.18	21.90	30.00	1.75	Pass	19.5		
VHT20	MCS0	2	157	Full	5785	0.01	0.01	18.74	18.11	21.45	30.00	1.75	Pass	19.5		
VHT20	MCS0	2	165	Full	5825	0.01	0.01	18.82	18.06	21.47	30.00	1.75	Pass	19.5		
VHT40	MCS0	2	151	Full	5755	0.01	0.01	18.14	18.11	21.14	30.00	1.75	Pass	19.5		
VHT40	MCS0	2	159	Full	5795	0.01	0.01	18.03	18.02	21.04	30.00	1.75	Pass	19.5		
VHT80	MCS0	2	155	Full	5775	0.02	0.01	18.75	18.12	21.46	30.00	1.75	Pass	19.5		
HE20	MCS0	2	149	Full	5745	0.02	0.02	19.57	18.30	21.99	30.00	1.75	Pass	19.5		
HE20	MCS0	2	149	26/0	5745	0.02	0.02	9.26	8.18	11.76	30.00	1.75	Pass	9		
HE20	MCS0	2	149	52/37	5745	0.02	0.02	12.22	11.27	14.78	30.00	1.75	Pass	12.5		
HE20	MCS0	2	149	106/53	5745	0.02	0.02	15.60	14.29	18.00	30.00	1.75	Pass	15.5		
HE20	MCS0	2	157	Full	5785	0.02	0.02	18.81	18.17	21.51	30.00	1.75	Pass	19.5		
HE20	MCS0	2	165	Full	5825	0.02	0.02	18.88	18.15	21.54	30.00	1.75	Pass	19.5		
HE20	MCS0	2	165	26/8	5825	0.02	0.02	7.41	6.74	10.10	30.00	1.75	Pass	8.5		
HE20	MCS0	2	165	52/40	5825	0.02	0.02	10.88	10.32	13.62	30.00	1.75	Pass	12		
HE20	MCS0	2	165	106/54	5825	0.02	0.02	14.21	13.58	16.92	30.00	1.75	Pass	15		
HE40	MCS0	2	151	Full	5755	0.02	0.01	18.81	18.22	21.54	30.00	1.75	Pass	19.5		
HE40	MCS0	2	159	Full	5795	0.02	0.01	18.50	18.13	21.33	30.00	1.75	Pass	19.5		
HE80	MCS0	2	155	Full	5775	0.01	0.02	18.79	18.17	21.50	30.00	1.75	Pass	19.5		



UNII-3																
Mod.	Data Rate	NTX	CH.	RU Config	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail	Power Setting
						Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2		
EHT20	MCS0	2	149	Full	5745	0.01	0.01	19.66	18.34	22.06	30.00	1.75		Pass	19.5	
EHT20	MCS0	2	149	26/0	5745	0.01	0.01	9.34	8.30	11.86	30.00	1.75		Pass	9	
EHT20	MCS0	2	149	52/37	5745	0.01	0.01	12.29	11.39	14.87	30.00	1.75		Pass	12.5	
EHT20	MCS0	2	149	106/53	5745	0.01	0.01	15.69	14.37	18.09	30.00	1.75		Pass	15.5	
EHT20	MCS0	2	157	Full	5785	0.01	0.01	18.87	18.24	21.58	30.00	1.75		Pass	19.5	
EHT20	MCS0	2	165	Full	5825	0.01	0.01	18.92	18.25	21.61	30.00	1.75		Pass	19.5	
EHT20	MCS0	2	165	26/8	5825	0.01	0.01	7.47	6.85	10.18	30.00	1.75		Pass	8.5	
EHT20	MCS0	2	165	52/40	5825	0.01	0.01	10.97	10.39	13.70	30.00	1.75		Pass	12	
EHT20	MCS0	2	165	106/54	5825	0.01	0.01	14.28	13.69	17.01	30.00	1.75		Pass	15	
EHT40	MCS0	2	151	Full	5755	0.01	0.01	18.85	18.27	21.58	30.00	1.75		Pass	19.5	
EHT40	MCS0	2	159	Full	5795	0.01	0.01	18.54	18.21	21.39	30.00	1.75		Pass	19.5	
EHT80	MCS0	2	155	Full	5775	0.01	0.02	18.85	18.26	21.58	30.00	1.75		Pass	19.5	

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

For devices operating in the bands UNII-1/2A/2C

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW $\geq$ 3 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

For devices operating in the band UNII-3

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500KHz (or 300 kHz if the SA can't set RBW=500KHz).
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- If the SA can't set RBW=500KHz, then add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.


Method (a) or UNII-1/2A/2C: Measure and sum the spectra across the outputs.

The total final Power Spectral Density is the bin-by-bin summation to obtain the combined spectrum. For the device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

Method (b) for UNII-3: Measure and sum spectral maxima across the outputs.

The measurement on each individual output were performed with the same span and number on each individual output. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz .

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz . Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz .

- (2) For transmitters operating in the 5.725-5.85 GHz band:
- 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log (d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = GANT + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(\text{NANT}/\text{NSS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $\text{NANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain GANT is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>

	Ant. 1 (dBi)	Ant. 2 (dBi)	DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
UNII-1	3.38	2.97	3.38	6.19	0.00	0.19
UNII-2A	3.50	2.19	3.50	5.88	0.00	0.00
UNII-2C	2.11	2.11	2.11	5.12	0.00	0.00
UNII-3	1.75	1.68	1.75	4.73	0.00	0.00

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 10, 2025	Oct. 21, 2025~Nov. 19, 2025	Oct. 09, 2026	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2025	Oct. 21, 2025~Nov. 19, 2025	Apr. 17, 2026	Radiation (03CH03-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Oct. 21, 2025~Nov. 19, 2025	Aug. 09, 2026	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Nov. 23, 2024	Oct. 21, 2025~Nov. 19, 2025	Nov. 22, 2025	Radiation (03CH03-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251982	1GHz~18GHz	Aug. 22, 2025	Oct. 21, 2025~Nov. 19, 2025	Aug. 21, 2026	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101116	18GHz~40GHz	Oct. 18, 2025	Oct. 21, 2025~Nov. 19, 2025	Oct. 17, 2026	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 02, 2025	Oct. 21, 2025~Nov. 19, 2025	Jul. 01, 2026	Radiation (03CH03-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 02, 2025	Oct. 21, 2025~Nov. 19, 2025	Jan. 01, 2026	Radiation (03CH03-KS)
high gain Amplifier	EM	EM01G18GA	060834	1Ghz~18Ghz	Dec. 02, 2024	Oct. 21, 2025~Nov. 19, 2025	Dec. 01, 2025	Radiation (03CH03-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 02, 2025	Oct. 21, 2025~Nov. 19, 2025	Jan. 01, 2026	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 21, 2025~Nov. 19, 2025	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 21, 2025~Nov. 19, 2025	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 21, 2025~Nov. 19, 2025	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2025	Nov. 09, 2025	Apr. 15, 2026	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Jul. 03, 2025	Nov. 09, 2025	Jul. 02, 2026	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 24, 2024	Nov. 09, 2025	Dec. 23, 2025	Conduction (CO01-KS)
AC Power Source	Ouhan	APW-130NYT	202201040060	AC 0V~300V,45Hz~1000Hz	Apr. 16, 2025	Nov. 09, 2025	Apr. 15, 2026	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Oct. 28, 2025~Jan. 04, 2026	Apr. 01, 2026	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 25, 2024	Oct. 28, 2025~Jan. 04, 2026	Dec. 24, 2025	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 24, 2025		Dec. 23, 2026	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct. 14, 2025	Oct. 28, 2025~Jan. 04, 2026	Oct. 13, 2026	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Conducted Power Spectral Density	±1.32 dB
Frequency	±1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.20 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.88 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.32 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 25 °C, 45 %RH

Test Date: 2025.10.28-2026.1.4

Test Engineer: Wen Shiwei

Emission Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]
11A-CDD	Ant1	5180	23.30	5168.60	5191.90
	Ant2	5180	22.80	5168.60	5191.40
	Ant1	5220	23.80	5207.80	5231.60
	Ant2	5220	22.50	5208.80	5231.30
	Ant1	5240	24.00	5227.60	5251.60
	Ant2	5240	23.10	5228.10	5251.20
	Ant1	5260	40.60	5240.10	5280.70
	Ant2	5260	49.80	5237.30	5287.10
	Ant1	5300	38.40	5279.10	5317.50
	Ant2	5300	23.90	5288.10	5312.00
	Ant1	5320	36.00	5303.10	5339.10
	Ant2	5320	24.80	5307.90	5332.70
	Ant1	5500	24.30	5487.60	5511.90
	Ant2	5500	42.30	5478.70	5521.00
	Ant1	5580	24.50	5568.00	5592.50
	Ant2	5580	35.60	5563.10	5598.70
	Ant1	5700	24.00	5687.80	5711.80
	Ant2	5700	43.10	5677.70	5720.80
	Ant1	5720	38.60	5701.70	5740.30
	Ant2	5720	40.30	5697.90	5738.20
	Ant1	5745	37.30	5724.00	5761.30
	Ant2	5745	39.70	5725.90	5765.60
	Ant1	5785	37.50	5765.90	5803.40
	Ant2	5785	36.30	5767.40	5803.70
	Ant1	5825	24.80	5812.80	5837.60
	Ant2	5825	25.00	5812.20	5837.20
11N20MIMO	Ant1	5180	24.80	5167.40	5192.20
	Ant2	5180	24.20	5167.70	5191.90
	Ant1	5220	24.50	5207.80	5232.30
	Ant2	5220	23.80	5208.00	5231.80
	Ant1	5240	23.80	5227.90	5251.70
	Ant2	5240	24.70	5227.20	5251.90
	Ant1	5260	42.50	5237.70	5280.20
	Ant2	5260	49.30	5235.00	5284.30
	Ant1	5300	38.40	5279.60	5318.00



	Ant2	5300	33.50	5280.40	5313.90
	Ant1	5320	37.60	5299.00	5336.60
	Ant2	5320	24.70	5307.80	5332.50
	Ant1	5500	24.90	5487.50	5512.40
	Ant2	5500	43.80	5476.40	5520.20
	Ant1	5580	25.40	5567.20	5592.60
	Ant2	5580	35.10	5559.10	5594.20
	Ant1	5700	28.70	5683.50	5712.20
	Ant2	5700	42.90	5679.90	5722.80
	Ant1	5720	24.40	5707.60	5732.00
	Ant2	5720	25.90	5706.20	5732.10
	Ant1	5745	39.40	5721.00	5760.40
	Ant2	5745	41.20	5724.90	5766.10
	Ant1	5785	34.90	5765.50	5800.40
	Ant2	5785	37.90	5767.80	5805.70
	Ant1	5825	25.50	5812.00	5837.50
	Ant2	5825	25.00	5812.90	5837.90
11N40MIMO	Ant1	5190	46.20	5166.60	5212.80
	Ant2	5190	45.40	5167.80	5213.20
	Ant1	5230	45.40	5207.20	5252.60
	Ant2	5230	46.40	5206.60	5253.00
	Ant1	5270	86.60	5224.40	5311.00
	Ant2	5270	47.00	5246.60	5293.60
	Ant1	5310	46.60	5286.60	5333.20
	Ant2	5310	46.60	5287.40	5334.00
	Ant1	5510	46.60	5486.80	5533.40
	Ant2	5510	65.00	5478.20	5543.20
	Ant1	5550	46.80	5526.80	5573.60
	Ant2	5550	71.60	5518.00	5589.60
	Ant1	5670	46.00	5646.60	5692.60
	Ant2	5670	76.60	5626.20	5702.80
	Ant1	5710	45.80	5686.60	5732.40
	Ant2	5710	72.80	5674.40	5747.20
	Ant1	5755	64.40	5723.40	5787.80
	Ant2	5755	77.20	5713.40	5790.60
	Ant1	5795	46.80	5772.20	5819.00
	Ant2	5795	50.00	5768.60	5818.60
11AC80MIMO	Ant1	5210	88.00	5166.00	5254.00
	Ant2	5210	88.40	5166.00	5254.40
	Ant1	5290	108.40	5226.80	5335.20
	Ant2	5290	88.00	5246.80	5334.80
	Ant1	5530	88.40	5486.40	5574.80



	Ant2	5530	144.40	5455.60	5600.00
	Ant1	5610	104.00	5565.60	5669.60
	Ant2	5610	92.40	5564.80	5657.20
	Ant1	5690	88.40	5645.20	5733.60
	Ant2	5690	120.80	5613.20	5734.00
	Ant1	5775	91.60	5728.20	5819.80
	Ant2	5775	91.20	5731.00	5822.20
11AC160MIMO	Ant1	5250	336.80	5046.00	5382.80
	Ant2	5250	181.60	5159.60	5341.20
	Ant1	5570	182.40	5480.40	5662.80
	Ant2	5570	492.00	5263.60	5755.60
11BE20MIMO	Ant1	5180	24.20	5167.60	5191.80
	Ant2	5180	23.50	5167.80	5191.30
	Ant1	5220	23.10	5208.30	5231.40
	Ant2	5220	22.90	5208.80	5231.70
	Ant1	5240	24.00	5228.20	5252.20
	Ant2	5240	23.80	5227.70	5251.50
	Ant1	5260	29.20	5246.10	5275.30
	Ant2	5260	24.70	5247.20	5271.90
	Ant1	5300	24.20	5287.70	5311.90
	Ant2	5300	23.10	5288.40	5311.50
	Ant1	5320	23.10	5308.70	5331.80
	Ant2	5320	23.40	5308.40	5331.80
	Ant1	5500	23.60	5488.00	5511.60
	Ant2	5500	31.60	5483.80	5515.40
	Ant1	5580	23.50	5568.10	5591.60
	Ant2	5580	23.50	5568.40	5591.90
	Ant1	5700	25.10	5686.50	5711.60
	Ant2	5700	23.90	5687.90	5711.80
	Ant1	5720	23.60	5708.50	5732.10
	Ant2	5720	23.80	5708.20	5732.00
	Ant1	5745	25.20	5731.50	5756.70
	Ant2	5745	23.10	5733.30	5756.40
	Ant1	5785	24.90	5772.30	5797.20
	Ant2	5785	23.00	5773.30	5796.30
	Ant1	5825	23.80	5813.20	5837.00
	Ant2	5825	23.60	5813.30	5836.90
11BE40MIMO	Ant1	5190	44.80	5167.40	5212.20
	Ant2	5190	44.40	5167.20	5211.60
	Ant1	5230	46.20	5207.00	5253.20
	Ant2	5230	45.20	5207.00	5252.20
	Ant1	5270	68.80	5237.60	5306.40



	Ant2	5270	59.60	5248.00	5307.60
	Ant1	5310	54.20	5282.20	5336.40
	Ant2	5310	44.60	5288.00	5332.60
	Ant1	5510	45.60	5487.40	5533.00
	Ant2	5510	73.40	5464.40	5537.80
	Ant1	5550	58.40	5527.80	5586.20
	Ant2	5550	69.20	5517.00	5586.20
	Ant1	5670	58.40	5647.40	5705.80
	Ant2	5670	67.00	5630.20	5697.20
	Ant1	5710	47.20	5687.80	5735.00
	Ant2	5710	72.60	5673.40	5746.00
	Ant1	5755	71.00	5717.20	5788.20
	Ant2	5755	64.40	5726.60	5791.00
	Ant1	5795	57.80	5770.20	5828.00
	Ant2	5795	45.40	5772.00	5817.40
11BE80MIMO	Ant1	5210	87.60	5165.60	5253.20
	Ant2	5210	86.40	5167.20	5253.60
	Ant1	5290	124.00	5213.60	5337.60
	Ant2	5290	88.80	5246.00	5334.80
	Ant1	5530	88.00	5487.20	5575.20
	Ant2	5530	138.00	5450.80	5588.80
	Ant1	5610	87.20	5565.60	5652.80
	Ant2	5610	86.40	5565.20	5651.60
	Ant1	5690	90.40	5641.60	5732.00
	Ant2	5690	131.20	5612.80	5744.00
	Ant1	5775	135.20	5684.60	5819.80
	Ant2	5775	86.00	5731.80	5817.80
11BE160MIMO	Ant1	5250	404.80	5023.60	5428.40
	Ant2	5250	380.00	5034.00	5414.00
	Ant1	5570	367.20	5364.40	5731.60
	Ant2	5570	458.40	5273.20	5731.60



Test Graphs

