

# TEST REPORT



Certification # 1367-01

Laboratory ID

PRODUCT SAFETY ENGINEERING, INC.  
12955 Bellamy Brothers Boulevard  
Dade City, Florida 33525 USA  
PH (352) 588-2209 FX (352) 588-2544

Submitter ID

WorldWide Widget Works  
7024 Creek Place Drive  
Killeen, TX 76549

Report Issue Date: 11 Jul 03

Sample S/N: None

Sample Receipt Date: May 02, 2003

Test Report Number: 03F261B

Model Designation: TracBack

Product Description: 1.637 MHz  
Transmitter

Sample Test Date: see data sheets

Marketing Approval \_\_\_\_\_

Description of non-standard test method or test practice: *None*

Estimated Measurement Uncertainty: *Not Applicable*

Special limitations of use: *None*

**Traceability: *reference standards of measurement have been calibrated by a competent body using standards traceable to the NIST.***

According to testing performed at Product Safety Engineering, Inc., the above-mentioned unit is in compliance with the electromagnetic compatibility requirements defined in regulations indicated on page (3) of the test report. The test results contained herein relate only to the model(s) identified above. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Project Engineer, I hereby declare that the equipment tested as specified above conforms to the requirements indicated on page (3) of the test report.

Signature

Name David Foerstner

Title Engineering Group Leader

Date 07 JUL 03

**Reviewed by:**

Approved Signatory

Date 11 Jul 03

This report may only be reproduced in full with written permission from Product Safety Engineering, Inc.

Test Report Number 03F261B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525  
Tel (352) 588-2209 Fax (352) 588-2544

## DIRECTORY - EMISSIONS

|                                        |                     | Page(s) |
|----------------------------------------|---------------------|---------|
| <b>A) Documentation</b>                |                     |         |
| Test report                            |                     | 1 - 10  |
| Directory                              |                     | 2       |
| Test Regulations                       |                     | 3       |
| General Remarks                        |                     | 10      |
| Test-setups (Photos)                   |                     | 11 - 12 |
| <b>B) Test data</b>                    |                     |         |
| Conducted emissions                    | 10/150 kHz - 30 MHz | 5, 9    |
| Radiated emissions                     | 10 kHz - 30 MHz     | 5, 9    |
| Radiated emissions                     | 30 MHz - 1000 MHz   | 6, 9    |
| Interference power                     | 30 MHz - 300 MHz    | 6, 9    |
| Equivalent Radiated emissions          | 1 GHz - 18 GHz      | 7, 9    |
| Antenna Disturbance Voltage            | 30 MHz - 1,000 MHz  | 7, 9    |
| <b>C) Appendix A</b>                   |                     |         |
| Test Equipment Calibration Information |                     | A2      |
| Test Data Sheets                       |                     | A3 - A4 |
| <b>D) Appendix B</b>                   |                     |         |
| System Under Test Description          |                     | B2 - B4 |
| <b>E) Appendix C</b>                   |                     |         |
| Measurement Protocol                   |                     | C1 - C2 |

Test Report Number 03F261B

## EMISSIONS TEST REGULATIONS :

The emissions tests were performed according to following regulations:

- ☐ - EN 50081-1 : 1992
- ☐ - EN 50081-2 : 1995
  
- ☐ - EN 55011 : 1998 / A1:1999
  - ☐ - Group 1
  - ☐ - Group 2
  - ☐ - Class A
  - ☐ - Class B
- ☐ - EN 55013 : 1990 / A12:1994 / A13:1996 / A14:1999
  
- ☐ - EN 55014 : 1993 / A1:1997
  - ☐ - Household appliances and similar
  - ☐ - Portable tools
  - ☐ - Semiconductor devices
  
- ☐ - EN 55022 : 1998
  - ☐ - Class A
  - ☐ - Class B
- ☐ - AS/NZS 3548:1995
  - ☐ - Class A
  - ☐ - Class B
- ☐ - ICES-003
  - ☐ - Class A
  - ☐ - Class B
- ☐ - CNS 13438
  - ☐ - Class A
  - ☐ - Class B
- ☐ - VCCI : 1999
  - ☐ - Class A
  - ☐ - Class B
- ☒ - FCC Part 15
  - ☐ - Class A
  - ☒ - Class B
  - ☒ - Certification
  - ☐ - Verification
  - ☐ - Declaration of Conformity
  
- ☐ - FCC Part 18

Test Report Number 03F261B

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525  
Tel (352) 588-2209 Fax (352) 588-2544

**Environmental conditions during testing:**

|                       | LAB   | OATS    |
|-----------------------|-------|---------|
| Temperature: *        | _____ | : _____ |
| Relative Humidity: ** | _____ | : _____ |

\* The ambient temperature during the testing was within the range of (50° - 104° F) unless indicted above.

\*\* The humidity levels during the testing was within the range of (10% - 90%) relative humidity unless indicated above.

Power supply system : 9 Volts DC Hz INTERNAL BATTERY

**Sign Explanations:**

- ☐ - not applicable
- ☒ - applicable

*Test Report Number 03F261B*

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525  
Tel (352) 588-2209 Fax (352) 588-2544

## Emissions Test Conditions: CONDUCTED EMISSIONS (Interference Voltage)

The *CONDUCTED EMISSIONS (INTERFERENCE VOLTAGE)* measurements were performed at the following test location:

☒ - Test not applicable

- ☐ - Darby Test Site (Open Area Test Site)
- ☐ - Darby Laboratory

### Test equipment used :

|                            | Model Number | Manufacturer       | Description        | Serial Number  |
|----------------------------|--------------|--------------------|--------------------|----------------|
| <input type="checkbox"/> - | 8028-50      | Solar              | 50 $\Omega$ LISN   | 829012, 829022 |
| <input type="checkbox"/> - | 3825/2       | Solar              | 50 $\Omega$ LISN   | 924840         |
| <input type="checkbox"/> - | EMC-30       | Electro-Metrics    | EMI Receiver       | 191            |
| <input type="checkbox"/> - | 8566B        | Hewlett-Packard    | Spectrum Analyzer  | 2421A00526     |
| <input type="checkbox"/> - | 85650A       | Hewlett-Packard    | Quasi-Peak Adapter | 2043A00209     |
| <input type="checkbox"/> - | 85662A       | Hewlett Packard    | Analyzer Display   | 2403A07352     |
| <input type="checkbox"/> - | 8028-50      | Solar              | 50 $\Omega$ LISN   | 903725, 903726 |
| <input type="checkbox"/> - | FCC-TLISN-T4 | Fisher Custom Com. | Telecom ISN        | 20072          |

## Emissions Test Conditions: RADIATED EMISSIONS (Magnetic Field)

The *RADIATED EMISSIONS (MAGNETIC FIELD)* measurements were performed at the following test location:

- ☒ - Darby Test Site (Open Area Test Site)
- ☐ -
- ☐ -

### at a test distance of :

- ☒ - 3 meters
- ☐ - 30 meters

☐ - Test not applicable

### Test equipment used :

|                                       | Model Number | Manufacturer     | Description          | Serial Number |
|---------------------------------------|--------------|------------------|----------------------|---------------|
| <input type="checkbox"/> -            | 96005        | Eaton            | Log Periodic Antenna | 1099          |
| <input type="checkbox"/> -            | BIA-25       | Electro-Metrics  | Biconical Antenna    | 4283          |
| <input checked="" type="checkbox"/> - | 8566B        | Hewlett-Packard  | Spectrum Analyzer    | 2421A00526    |
| <input checked="" type="checkbox"/> - | 85662A       | Hewlett-Packard  | Analyzer Display     | 2403A07352    |
| <input checked="" type="checkbox"/> - | 85650A       | Hewlett-Packard  | Quasi-Peak Adapter   | 2043A00209    |
| <input type="checkbox"/> -            | ALR-30M      | Electro-Metrics  | Loop Antenna         | 824           |
| <input type="checkbox"/> -            | 8447D        | Hewlett Packard  | Preamplifier         | 2944A06832    |
| <input type="checkbox"/> -            | EMC-30       | Electro-Metrics  | EMI Receiver         | 191           |
| <input checked="" type="checkbox"/> - | ALA-130/A    | Antenna Research | Loop Antenna         | 106           |

Test Report Number 03F261B

## Emissions Test Conditions: RADIATED EMISSIONS (Electric Field)

The *RADIATED EMISSIONS (ELECTRIC FIELD)* measurements, in the frequency range of 30 MHz-1000 MHz, were tested in a horizontal and vertical polarization at the following test location :

☐ - Test not applicable

- ☒ - Darby Site (Open Area Test Site)
- ☐ - Darby Lab
- ☐ -

at a test distance of :

- ☒ - 3 meters
- ☐ - 10 meters
- ☐ - 30 meters

Test equipment used :

| Model Number                                 | Manufacturer    | Description          | Serial Number |
|----------------------------------------------|-----------------|----------------------|---------------|
| <input checked="" type="checkbox"/> - 96005  | Eaton           | Log Periodic Antenna | 1099          |
| <input checked="" type="checkbox"/> - BIA-25 | Electro-Metrics | Biconical Antenna    | 4283          |
| <input checked="" type="checkbox"/> - 8566B  | Hewlett-Packard | Spectrum Analyzer    | 2421A00526    |
| <input checked="" type="checkbox"/> - 85662A | Hewlett-Packard | Analyzer Display     | 2403A07352    |
| <input checked="" type="checkbox"/> - 85650A | Hewlett-Packard | Quasi-Peak Adapter   | 2043A00209    |
| <input checked="" type="checkbox"/> - 8447D  | Hewlett-Packard | Preamplifier (26dB)  | 2944A06832    |
| <input type="checkbox"/> - EMC-30            | Electro-Metrics | EMI Receiver         | 191           |
| <input type="checkbox"/> - 8568B             | Hewlett Packard | Spectrum Analyzer    | 2407A03213    |
| <input type="checkbox"/> - 85650A            | Hewlett Packard | Quasi-Peak Adapter   | 2043A00358    |
| <input type="checkbox"/> - 85662A            | Hewlett Packard | Analyzer Display     | 2340A05806    |
| <input type="checkbox"/> - LPA30             | Electro-Metrics | Log Periodic         | 2280          |
| <input type="checkbox"/> - BIA 30            | Electro-Metrics | Biconical Antenna    | 3852          |

## Emissions Test Conditions): INTERFERENCE POWER

The *INTERFERENCE POWER* measurements were performed by using the absorbing clamp on the mains and interface cables in the frequency range 30 MHz - 300 MHz at the following test location :

☒ - Test not applicable

- ☐ - Darby Lab
- ☐ -

Test equipment used :

| Model Number                      | Manufacturer    | Description        | Serial Number |
|-----------------------------------|-----------------|--------------------|---------------|
| <input type="checkbox"/> - MDS-21 | Rhode&Schwarz   | Absorbing Clamp    | 8608447020    |
| <input type="checkbox"/> - 8566B  | Hewlett-Packard | Spectrum Analyzer  | 2421A00526    |
| <input type="checkbox"/> - 85662A | Hewlett-Packard | Analyzer Display   | 2403A07352    |
| <input type="checkbox"/> - 85650A | Hewlett-Packard | Quasi-Peak Adapter | 2043A00209    |
| <input type="checkbox"/> - 8447D  | Hewlett-Packard | Amplifier (26 dB)  | 2944A06832    |
| <input type="checkbox"/> - EMC-30 | Electro-Metrics | EMI Receiver       | 191           |

Test Report Number 03F261B

The *EQUIVALENT RADIATED EMISSIONS* measurements in the frequency range      GHz -      GHz      were performed in a horizontal and vertical polarization at the following test location :

- ☐ - Darby Test Site (Open Area Test Site)
- ☐ -
- ☐ -
- ☐ -

at a test distance of:

- ☐ - 1 meters
- ☐ - 3 meters
- ☐ - 10 meters

■ - Test not applicable

**Test equipment used :**

| Model Number                      | Manufacturer      | Description             | Serial Number |
|-----------------------------------|-------------------|-------------------------|---------------|
| <input type="checkbox"/> - 8566B  | Hewlett-Packard   | Spectrum Analyzer       | 2421A00526    |
| <input type="checkbox"/> - 85662A | Hewlett-Packard   | Analyzer Display        | 2403A07352    |
| <input type="checkbox"/> - 85650A | Hewlett-Packard   | Quasi-Peak Adapter      | 2043A00209    |
| <input type="checkbox"/> - 8449B  | Hewlett-Packard   | Preamplifier            | 3008A00320    |
| <input type="checkbox"/> - 3115   | Electro-Mechanics | Double Ridge Guide Horn | 3810          |

The *ANTENNA TERMINAL DISTURBANCE VOLTAGE* in the frequency range 30 MHz - 1,000 MHz were performed.

- ☐ - Darby Test Site (Open Area Test Site)
- ☐ - Laboratory
- ☐ -
- ☐ -

■ - Test not applicable

| Model Number                           | Manufacturer    | Description                 | Serial Number |
|----------------------------------------|-----------------|-----------------------------|---------------|
| <input type="checkbox"/> - 2F9-3C4-3C5 | Wavecom         | UHF PAL TV Modulator        | 185879        |
| <input type="checkbox"/> - 2F1-3C4-3C5 | Wavecom         | VHF PAL TV Modulator        | 157728        |
| <input type="checkbox"/> - A-8000      | IFR             | Spectrum Analyzer           | 1306          |
| <input type="checkbox"/> - 8648B       | Hewlett-Packard | Signal Generator            | 3623A01433    |
| <input type="checkbox"/> - 8648B       | Hewlett-Packard | Signal Generator            | 3623A01477    |
| <input type="checkbox"/> - LMV-182A    | Leader          | RMS Milli-Voltmeter         | 8010091       |
| <input type="checkbox"/> - 3202        | Krhon-Hite      | Active filter               | 5899          |
| <input type="checkbox"/> - FMT115      | Leaming         | FM Modulator                | NONE          |
| <input type="checkbox"/> - 371         | UDT             | Optical power meter         | 06657         |
| <input type="checkbox"/> - TSG95       | Tektronix       | PAL video / Audio generator | B028883       |
| <input type="checkbox"/> -             |                 |                             |               |

Test Report Number 03F261B

## Equipment Under Test (EUT) Test Operation Mode - Emission tests :

The device under test was operated under the following conditions during emissions testing:

- ☐ - Standby
- ☐ - Test program (H - Pattern)
- ☐ - Test program (color bar)
- ☐ - Test program (customer specific)
- ☒ - Practice operation
- ☐ - Normal Operating Mode
- ☐ -

### Configuration of the device under test:

- ☒ - See System Under Test Information in Appendix B

### Rationale for EUT setup / configuration:

*ANSI C63.4, FCC PART 15.209, PART 15.219*

---

---

---

---

---

Test Report Number 03F261B

## Emission Test Results:

### FCC Part 15 section 15.219 Total Input Power

The requirements are ☒ - MET ☐ - NOT MET

Minimum limit margin 19.0 mW

Remarks: Total input power to final radio frequency stage shall not exceed 100 milliwatts

### Radiated emissions (magnetic field) 10 kHz - 30 MHz

The requirements are ☒ - MET ☐ - NOT MET

Minimum limit margin 6.6 dB at 9.82 MHz

Remarks:

### Radiated emissions (electric field) 30 MHz - 1000 MHz

The requirements are ☒ - MET ☐ - NOT MET

Minimum limit margin 26.6 dB at 33.0 MHz

Remarks:

### Interference Power at the mains and interface cables 30 MHz - 300 MHz

The requirements are Per FCC Part 15.219 ☐ - MET ☐ - NOT MET

Minimum limit margin dB at MHz

Remarks:

### Radiated emissions GHz - GHz

The requirements are ☐ - MET ☐ - NOT MET

Minimum limit margin dB at GHz

Remarks:

### Antenna Terminal Disturbance Voltage 30 MHz - 1,000 MHz

The requirements are ☐ - MET ☐ - NOT MET

Minimum limit margin dB at MHz

Remarks:

Test Report Number 03F261B

**GENERAL REMARKS:**

Radiated limits used were taken from FCC Part 15.219.

Limits were adjusted to 3 meter distance using FCC Part 15.31 (f) (2)

The EUT was tested in (3) orthogonal positions.

The value of "R37" was changed from (100) ohms to (22) ohms prior to testing.

**SUMMARY:**

The requirements according to the technical regulations are

■ - met

□ - **not** met.

The device under test does

■ - fulfill the general approval requirements mentioned on page 3.

□ - **not** fulfill the general approval requirements mentioned on page 3.

Testing Start Date                      May 16, 2003

Testing End Date:                      June 23, 2003

- PRODUCT SAFETY ENGINEERING INC -

*Test Report Number 03F261B*

Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525  
Tel (352) 588-2209 Fax (352) 588-2544

Test-setup photo(s):

Conducted emission 450/150 kHz - 30 MHz

N/A

*Test Report Number 03F261B*

**Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525**  
**Tel (352) 588-2209 Fax (352) 588-2544**

Test-setup photo(s):  
Radiated emission 1.6 MHz - 1000 MHz



*Test Report Number 03F261B*

**Product Safety Engineering, Inc 12955 Bellamy Brothers Blvd. Dade City, FL 33525**  
**Tel (352) 588-2209 Fax (352) 588-2544**

Page 12 of 12

# **APPENDIX**

## **A**

### **Test Equipment Calibration Information & Test Data Sheets**

## TEST EQUIPMENT CALIBRATION INFORMATION

| Manufacturer      | Model     | Description                  | Serial Number | Cal Due  |
|-------------------|-----------|------------------------------|---------------|----------|
| Hewlett Packard   | 8566B     | Spectrum Analyzer            | 2421A00526    | 08/22/03 |
| Hewlett Packard   | 85662A    | Display                      | 2403A07352    | 08/22/03 |
| Hewlett Packard   | 85650A    | Quasi-Peak Adapter           | 2043A00209    | 08/22/03 |
| Hewlett Packard   | 8447D     | Preamplifier 0.1 - 1,000 MHz | 2944A06832    | 11/13/03 |
| Hewlett Packard   | 8568B     | Spectrum Analyzer            | 2407A03213    | 08/22/03 |
| Hewlett Packard   | 85662A    | Display                      | 2340A05806    | 08/22/03 |
| Hewlett Packard   | 85650A    | Quasi-Peak Adapter           | 2043A00358    | 08/22/03 |
| Hewlett Packard   | 8447D     | Preamplifier 0.1 - 1,000 MHz | 2944A06901    | 08/02/03 |
| Hewlett Packard   | 8447D     | Preamplifier 0.1 - 1,000 MHz | 1937A03247    | 07/19/03 |
| Hewlett Packard   | 8449B     | Preamplifier 1 - 26.5 GHz    | 3008A00320    | 11/08/03 |
| Hewlett Packard   | 8648B     | Signal Generator             | 3443U00312    | 04/25/03 |
| Hewlett Packard   | 8672A     | Signal Generator             | 2211A02426    | 11/14/03 |
| Eaton             | 96005     | Log Periodic Antenna         | 1099          | 01/24/04 |
| Electro-Metrics   | LPA 30    | Log Periodic Antenna         | 2280          | 12/06/03 |
| Electro-Metrics   | BIA 30    | Biconical Antenna            | 3852          | 12/05/03 |
| Electro-Metrics   | BIA 25    | Biconical Antenna            | 4283          | 01/22/04 |
| Electro-Mechanics | 3115      | Double Ridge Guide Ant.      | 3810          | 11/07/03 |
| Electro-Metrics   | ALR30M    | Magnetic Loop Antenna        | 824           | 12/12/03 |
| Solar             | 8012      | LISN                         | 924840        | 12/29/03 |
| Solar             | 8028      | LISN                         | 829012/809022 | 12/19/03 |
| Solar             | 8028      | LISN                         | 903725/903726 | 11/18/03 |
| Schwartzbeck      | MDS-21    | Absorbing Clamp              | 02581         | 09/13/03 |
| Leader            | LFG1310   | Function Generator           | 8060233       | 04/23/03 |
| Holaday Ind.      | HI 4422   | Isotropic Probe              | 90310         | 05/22/03 |
| IFR Systems       | A-8000    | Spectrum Analyzer            | 1306          | 11/13/03 |
| Fischer Custom    | F-33-1    | RF Current Probe             | 360           | 11/20/03 |
| Electro-Metrics   | EMC-30    | EMI Receiver                 | 191           | 04/24/04 |
| Boonton           | 4220A     | RF Power Meter               | 204103AA      | 11/08/03 |
| Boonton           | 51011     | RF Power Meter               | 28823         | 11/08/03 |
| Antenna Research  | ALA-130/A | Loop Antenna                 | 106           | 03/14/04 |

## PRODUCT EMISSIONS

PRODUCT SAFETY ENGINEERING

PRODUCT SAFETY ENGINEERING

Data File: TRACBACK FCC-B BIC 5-16-2003

| No | EMISSION         | SPEC<br>LIMIT | MEASUREMENTS |       |      | POL | SITE |     | CORR<br>FACTOR | COMMENTS |
|----|------------------|---------------|--------------|-------|------|-----|------|-----|----------------|----------|
|    | FREQUENCY<br>MHz |               | ABS          | dLIM  | MODE |     | HGT  | AZM |                |          |
|    |                  |               |              |       |      |     | cm   | deg | dB             |          |
| 1  | 33.04            | 40.0          | 13.4         | -26.6 | PK   | V   | 100  | 90  |                |          |
| 2  | 51.20            | 40.0          | 11.2         | -28.8 | PK   | V   | 100  | 90  |                |          |
| 3  | 62.59            | 40.0          | 13.1         | -26.9 | PK   | V   | 100  | 270 |                |          |
| 4  | 122.29           | 43.5          | 15.1         | -28.4 | PK   | V   | 100  | 180 |                |          |
| 5  | 214.91           | 43.5          | 13.8         | -29.7 | PK   | V   | 100  | 225 |                |          |
| 6  | 216.22           | 46.0          | 3.7          | -42.3 | PK   | V   | 100  | 315 |                |          |
| 7  | 444.85           | 46.0          | 19.4         | -26.6 | PK   | V   | 100  | 225 |                |          |

A3

# World Wide Widget

## Intentional Radiator Emissions

Measured @ 3 Meters

| Frequency (MHz) | Spec Limit (dB $\mu$ V/M) | ACF   | CL  | Measurement (dB $\mu$ V/M) | $\Delta$ Limit |
|-----------------|---------------------------|-------|-----|----------------------------|----------------|
| 1.637           | 63.3                      | -8.2  | 0.5 | 52.5                       | -10.8          |
| 3.274           | 32.5                      | -10.3 | 0.5 | 24.2                       | -8.3           |
| 4.911           | 32.5                      | -9.2  | 0.5 | 22.6                       | -9.9           |
| 6.548           | 32.5                      | -7.8  | 0.5 | 24.0                       | -8.5           |
| 8.185           | 32.5                      | -6.4  | 0.5 | 24.2                       | -8.3           |
| 9.822           | 32.5                      | -4.6  | 0.5 | 25.9                       | -6.6           |
| 11.459          | 32.5                      | -3.7  | 0.5 | 24.6                       | -7.9           |
| 13.096          | 32.5                      | -2.4  | 0.5 | 24.8                       | -7.7           |
| 14.733          | 32.5                      | -1.0  | 0.5 | 24.6                       | -7.9           |
| 16.370          | 32.5                      | -0.7  | 0.5 | 22.2                       | -10.3          |

## Total Input Power & Harmonics

Total Input Power to final Radio Frequency Stage per FCC Part 15.219 was measured to be 81.0 mW which is 19 mW below the allowable 100 mW limit. We then measured the field strength of the fundamental and found it to be (52.5) dB $\mu$ V/m at (3) meters. This amplitude is below the limit stated in the general radiated emissions (15.209). Once the field strength of the fundamental was established, the harmonics were each measured and compared to a limit which was set at (20) dB below the measured fundamental level.

Magnetic loop antenna is active and includes a preamplifier.

# **APPENDIX**

## **B**

### **System Under Test Description**

## **SYSTEM COMPONENTS**

\*\*\*\*\*

DEVICE TYPE: EUT, WORLD WIDE WIDGET TRACBACK

\*\*\*\*\*

## INTERFACE CABLES

\*\*\*\*\*

DEVICE TYPE: EUT            **NONE**

SHIELD:

LENGTH:

CONNECTOR TYPE:

PORT:

\*\*\*\*\*

## AC LINE CORDS

\*\*\*\*\*

DEVICE TYPE: EUT            NONE

SHIELD:

LENGTH:

CONNECTOR TYPE:

\*\*\*\*\*

# **APPENDIX**

## **C**

### **Measurement Protocol**

The test methodology followed during the collection of the data included within this technical report was ANSI C63.4:1992.

The EUT was powered with (120) VAC / (60) Hz during the collection of data included within.

The data is compared to the FCC Part 15 Class B limits.

The "EMI" instrumentation is capable of calculating the final emission level based on the following formula:

Level at the receiver (dB $\mu$ V) + Antenna Correction Factor (dB/M) + Cable Loss (dB) - Preamp Gain (dB) = Actual Level in dB $\mu$ V/M.

The sample calculation below is based on the actual test data collected:

|                |   |                    |              |            |
|----------------|---|--------------------|--------------|------------|
| Observed Level |   | <b>39.9</b>        | dB $\mu$ V   |            |
| ACF            | + | <b>12.0</b>        | dB/M         |            |
| Cable Loss     | + | <b>0.7</b>         | dB           |            |
| Preamp Gain    | - | <b><u>26.0</u></b> | dB           |            |
| Actual Level   |   | <b>26.6</b>        | dB $\mu$ V/M | @ 33.0 MHz |

**Please have a company official review this report and sign.**

---