SPORTON International Inc.
No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	**Bluetake Technology Co., Ltd.**
Applicant Address	5F, No.27, Lane 155, Sec.3, Pei-shen road, Shen-keng Shiang, Taipei, Taiwan 222
FCC ID	**Q5TBT007EX0510**
Manufacturer's company	**Bluetake Technology Co., Ltd.**
Manufacturer Address	5F, No.27, Lane 155, Sec.3, Pei-shen road, Shen-keng Shiang, Taipei, Taiwan 222

Product Name	Bluetooth Class1 EDR USB Adapter
Brand Name	BLUETAKE
Model Name	BT007Ex
Test Rule Part(s)	47 CFR Part 15 Subpart C. 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Receive Date	Nov. 4, 2005
Test Date	Nov. 9, 2005
Submission Type	Original Equipment

Statement

The test result in this report refers exclusively to the presented test model / sample.
Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.
The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Lab Code: 200079-0

Table of Contents

1. CERTIFICATE OF COMPLIANCE 1

2. SUMMARY OF THE TEST RESULT 2

3. GENERAL INFORMATION 3

3.1. Product Details 3
3.2. Table for Filed Antenna 3
3.3. Table for Carrier Frequencies 3
3.4. Table for Test Modes 4
3.5. Table for Testing Locations 4
3.6. Table for Supporting Units 4
3.7. Table for Parameters of Test Software Setting 4
3.8. Test Configurations 5

4. TEST RESULT 7

4.1. AC Power Line Conducted Emissions Measurement 7
4.2. Maximum Peak Output Power Measurement 11
4.3. Hopping Channel Separation Measurement 13
4.4. Number of Hopping Frequency Measurement 18
4.5. Dwell Time Measurement 20
4.6. Radiated Emissions Measurement 27
4.7. Band Edge Emissions Measurement 39
4.8. Antenna Requirements 42

5. LIST OF MEASURING EQUIPMENTS 43

6. SPORTON COMPANY PROFILE 45

6.1. Test Location 45

7. CERTIFICATE OF NVLAP ACCREDITATION 46

APPENDIX A. PHOTOGRAPHS OF EUT ..... A1 ~ A5

APPENDIX B. TEST PHOTOS ..... B1 ~ B4

APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE ..... C1 ~ C3

History of This Test Report

Original Issue Date: Nov. 10, 2005

Report No.: FR5O2623

■ No additional attachment.

□ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

1. CERTIFICATE OF COMPLIANCE

Product Name	:	Bluetooth Class1 EDR USB Adapter
Brand Name	:	BLUETAKE
Model Name	:	BT007Ex
Applicant	:	Bluetake Technology Co., Ltd.
Test Rule Part(s)	:	47 CFR Part 15 Subpart C. 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 4, 2005 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Wayne Hsu / Supervisor
Sporton International Inc.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	17.64 dB
4.2	15.247(b)(1)	Maximum Peak Conducted Output Power	Complies	19.81 dB
4.3	15.247(a)(1)	Hopping Channel Separation	Complies	-
4.4	15.247(b)(1)	Number of Hopping Frequency	Complies	-
4.5	15.247(a)(1)	Dwell Time	Complies	-
4.6	15.247(d)	Radiated Emissions	Complies	6.40 dB
4.7	15.247(d)	Band Edge Emissions	Complies	11.52dB
4.8	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.26dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.5dB	Confidence levels of 95%
Hopping Channel Separation / Dwell Time	±6.25×10-7	Confidence levels of 95%
Radiated Emissions / Band Edge Emissions	±3.72dB	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Radio Type	Intentional Transceiver
Power Type	5V DC from host
Interface Type	USB
Modulation	FHSS (GFSK / QPSK /8PSK)
Data Rate (Mbps)	GFSK: 1 ; QPSK: 2 ; 8PSK: 3
Frequency Range	2400 ~ 2483.5MHz
Channel Number	79
Channel Band Width (99%)	1164 kHz
Conducted Output Power	10.19 dBm
Carrier Frequencies	Please refer to section 3.3
Antenna	Please refer to section 3.2

3.2. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Printed Antenna	NA	0

3.3. Table for Carrier Frequencies

Freqeuncy Band	Channel No.	Frequency
2400~2483.5MHz	0	2402 MHz
	1	2403 MHz
	:	:
	38	2440 MHz
	39	2441 MHz
	40	2442 MHz
	:	:
	77	2479 MHz
	78	2480 MHz

3.4. Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Conducted Emissions	Normal Link	3 Mbps	Hopping 0~78	1
Max. Conducted Output Power	8PSK	3 Mbps	0/39/78	NA
Hopping Channel Separation	8PSK	3 Mbps	0~1/39~40/77~78	NA
Number of Hopping Frequency	8PSK	3 Mbps	0~78	NA
Dwell Time	DH1/DH3/DH5	3 Mbps	0/39/78	NA
Radiated Emissions Below 1GHz	8PSK	3 Mbps	39	1
Radiated Emissions Above 1GHz Band Edge Emissions	8PSK	3 Mbps	0/39/78	1

3.5. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.6. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	PP01L	DoC
Modem	ACEEX	DM-1414	IFAXDM1414
Printer	EPSON	LQ-300	DoC

3.7. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g

Test Software Version	ART		
Frequency	2402 MHz	2441 MHz	2480 MHz
Power Parameters	80	82	84

3.8. Test Configurations

3.8.1. Radiation Emissions Test Configuration



1. DC power line, 1.5m, No-shielding

3.8.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For a Low-power Radio-frequency Device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



1. If cables, which hang closer than 40 cm to the horizontal metal groundplane, cannot be shortened to appropriate length, the excess shall be folded back and forth forming a bundle 30 cm to 40 cm long.
2. Excess mains cord shall be bundled in the centre or shortened to appropriate length.
3. EUT is connected to one artificial mains network (AMN). All AMNs and ISNs may alternatively be connected to a vertical reference plane or metal wall.
4. All other units of a system are powered from a second AMN. A multiple outlet strip can be used for multiple mains cords.
5. AMN and ISN are 80 cm from the EUT and at least 80 cm from other units and other metal planes.
6. Mains cords and signal cables shall be positioned for their entire lengths, as far as possible, at 40 cm from the vertical reference plane.
7. Cables of hand operated devices, such as keyboards, mouses, etc. shall be placed as for normal usage.
8. Peripherals shall be placed at a distance of 10 cm from each other and from the controller, except for the monitor which, if this is an acceptable installation practice, shall be placed directly on the top of the controller.
9. I/O signal cable intended for external connection.
10. The end of the I/O signal cables which are not connected to an AE may be terminated, if required, using correct terminating impedance.
11. If used, the current probe shall be placed at 0,1 m from the ISN.

4.1.5. Test Deviation

There are no deviations with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	66%
Test Engineer	Stan Peng	Phase	Line
Configuration	Normal Mode		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15160	32.38	-23.53	55.91	30.28	1.90	0.20	AVERAGE
2 @	0.15160	48.27	-17.64	65.91	46.17	1.90	0.20	QP
3	0.26442	37.31	-23.98	61.29	36.35	0.76	0.20	QP
4	0.26442	26.67	-24.62	51.29	25.71	0.76	0.20	AVERAGE
5	0.37512	29.85	-28.54	58.39	29.15	0.50	0.20	QP
6	0.37512	19.80	-28.59	48.39	19.10	0.50	0.20	AVERAGE
7	2.110	15.65	-30.35	46.00	15.23	0.22	0.20	AVERAGE
8	2.110	23.59	-32.41	56.00	23.17	0.22	0.20	QP
9	10.452	25.69	-24.31	50.00	25.00	0.30	0.39	AVERAGE
10	10.452	31.47	-28.53	60.00	30.78	0.30	0.39	QP
11	16.055	19.72	-30.28	50.00	19.02	0.30	0.40	AVERAGE
12	16.055	25.40	-34.60	60.00	24.70	0.30	0.40	QP

Temperature	24°C	Humidity	66%
Test Engineer	Stan Peng	Phase	Neutral
Configuration	Normal Mode		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15650	45.04	-20.61	65.65	42.77	2.07	0.20	QP
2	0.15650	30.53	-25.12	55.65	28.26	2.07	0.20	AVERAGE
3	0.21851	34.41	-28.46	62.88	33.10	1.11	0.20	QP
4	0.21851	17.41	-35.46	52.88	16.10	1.11	0.20	AVERAGE
5	0.26442	37.11	-24.18	61.29	36.01	0.90	0.20	QP
6	0.26442	28.37	-22.92	51.29	27.27	0.90	0.20	AVERAGE
7	1.560	21.44	-34.56	56.00	21.03	0.30	0.11	QP
8	1.560	13.39	-32.61	46.00	12.98	0.30	0.11	AVERAGE
9	2.012	12.09	-33.91	46.00	11.59	0.30	0.20	AVERAGE
10	2.012	20.41	-35.59	56.00	19.91	0.30	0.20	QP
11	10.790	31.54	-28.46	60.00	30.78	0.36	0.40	QP
12	10.790	26.53	-23.47	50.00	25.77	0.36	0.40	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Peak Output Power Measurement

4.2.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There are no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Peak Output Power

Temperature	22°C	Humidity	62%
Test Engineer	Stan Peng	Configurations	FHSS (8PSK)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
0	2402 MHz	10.15	30.00	Complies
39	2441 MHz	10.19	30.00	Complies
78	2480 MHz	10.13	30.00	Complies

4.3. Hopping Channel Separation Measurement

4.3.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

4.3.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 300 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
3. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There are no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Hopping Channel Separation

Temperature	22°C	Humidity	62%
Test Engineer	Stan Peng	Configurations	FHSS (8PSK)

Frequency	Ch. Separation (MHz)	20dB Bandwidth (kHz)	99% Occupied Bandwidth (kHz)	Result
2402 MHz	1.00	1206.00	1164.00	Complies
2441 MHz	1.00	1203.00	1143.00	Complies
2480 MHz	1.00	1209.00	1158.00	Complies

Ch. Separation Limits: >20dB bandwidth or >2/3 of 20dB bandwidth

20 dB Bandwidth Plot on Channel 0 / 2402 MHz



Date: 29.OCT.2005 20:48:50

20 dB Bandwidth Plot on Channel 39 / 2441 MHz



Date: 29.OCT.2005 20:51:39

20 dB Bandwidth Plot on Channel 78 / 2480 MHz



Date: 29.OCT.2005 20:53:03

Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz



Date: 29.OCT.2005 20:48:43

Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 29.OCT.2005 20:51:32

Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 29.OCT.2005 20:55:37

4.4. Number of Hopping Frequency Measurement

4.4.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were utilised.
3. Observe frequency hopping in 2400MHz~2483.5MHz, there are at least 75 non-overlapping channels.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There are no deviations with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Number of Hopping Frequency

Temperature	22℃	Humidity	62%
Test Engineer	Stan Peng	Configurations	FHSS (8PSK)

Modulation Type	Channel No.	Frequency (MHz)	Hopping Ch. (Channels)	Min. Limit (Channels)	Test Result
GFSK	0 ~ 78	2402 ~ 2480	79	75	Complies

Number of Hopping Channel Plot on Channel 0~78 / 2402 MHz ~ 2480 MHz



Date: 29.OCT.2005 20:50:36

4.5. Dwell Time Measurement

4.5.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.5.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	0 MHz
RB	1000 kHz
VB	1000 kHz
Detector	Peak
Trace	Single Trigger

4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser
2. Set RBW of spectrum analyzer to 1000kHz and VBW to 1000kHz.
3. Use a video trigger with the trigger level set to enable triggering only on full pulses.
4. Sweep Time is more than once pulse time.
5. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
6. Measure the maximum time duration of one single pulse.
7. Set the EUT for DH5, DH3 and DH1 packet transmitting.
8. Measure the maximum time duration of one single pulse.
9. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds
10. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
11. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.

4.5.4. Test Setup Layout



4.5.5. Test Deviation

There are no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Dwell Time

Temperature	22°C	Humidity	62%
Test Engineer	Stan Peng	Configurations	FHSS (8PSK)

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402 MHz	3.0900	0.3296	0.4000	Complies
DH3	2402 MHz	1.8300	0.2928	0.4000	Complies
DH1	2402 MHz	0.5650	0.1808	0.4000	Complies
DH5	2441 MHz	3.1000	0.3307	0.4000	Complies
DH3	2441 MHz	1.5300	0.2448	0.4000	Complies
DH1	2441 MHz	0.5750	0.1840	0.4000	Complies
DH5	2480 MHz	3.1000	0.3307	0.4000	Complies
DH3	2480 MHz	1.8300	0.2928	0.4000	Complies
DH1	2480 MHz	0.5700	0.1824	0.4000	Complies

DH5 Dwell Time Plot on Channel 0 / 2402 MHz



Date: 29.OCT.2005 20:43:57

DH3 Dwell Time Plot on Channel 0 / 2402 MHz



Date: 29.OCT.2005 20:43:18

DH1 Dwell Time Plot on Channel 0 / 2402 MHz



Date: 29.OCT.2005 20:40:19

DH5 Dwell Time Plot on Channel 39 / 2441 MHz



Date: 29.OCT.2005 20:44:24

DH3 Dwell Time Plot on Channel 39 / 2441 MHz



Date: 29.OCT.2005 20:42:52

DH1 Dwell Time Plot on Channel 39 / 2441 MHz



Date: 29.OCT.2005 20:40:51

DH5 Dwell Time Plot on Channel 78 / 2480 MHz



Date: 29.OCT.2005 20:44:52

DH3 Dwell Time Plot on Channel 78 / 2480 MHz



Date: 29.OCT.2005 20:42:12

DH1 Dwell Time Plot on Channel 78 / 2480 MHz



Date: 29.OCT.2005 20:41:25

4.6. Radiated Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100KHz / 100KHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.6.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1m.

Distance extrapolation factor = 20 log (specific distanc [3m] / test distance [1m]) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

4.6.5. Test Deviation

There are no deviations with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	21℃	Humidity	65%
Test Engineer	Leo Hung	Configurations	Channel 39

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	21°C	Humidity	65%
Test Engineer	Leo Hung	Configurations	Channel 39

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	257.950	34.32	-11.68	46.00	50.56	12.63	2.48	31.35	Peak	---	---
2 @	388.900	34.10	-11.90	46.00	47.15	15.40	2.63	31.08	Peak	---	---
3 @	453.890	36.59	-9.41	46.00	48.10	16.48	2.93	30.92	Peak	---	---
4 @	499.480	33.19	-12.81	46.00	43.67	17.18	3.28	30.94	Peak	---	---
5 @	515.970	33.00	-13.00	46.00	43.16	17.46	3.27	30.88	Peak	---	---
6 @	801.150	35.08	-10.92	46.00	41.36	20.10	3.80	30.18	Peak	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	257.950	35.94	-10.06	46.00	52.17	12.63	2.48	31.35	Peak	---	---
2 @	388.900	38.60	-7.40	46.00	51.65	15.40	2.63	31.08	Peak	---	---
3 @	450.980	39.02	-6.98	46.00	50.58	16.44	2.92	30.92	Peak	---	---
4 @	517.910	39.60	-6.40	46.00	49.73	17.48	3.26	30.87	Peak	---	---
5 @	644.980	36.34	-9.66	46.00	44.51	18.72	3.45	30.34	Peak	---	---
6 @	879.720	36.91	-9.09	46.00	42.02	20.69	4.06	29.86	Peak	---	---

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.

4.6.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	21°C	Humidity	65%
Test Engineer	Leo Hung	Configurations	Channel 0

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	1601.947	45.72	-8.28	54.00	49.13	25.92	5.38	34.72	AVERAGE	---	---
2	1602.011	49.03	-24.97	74.00	52.44	25.92	5.38	34.72	PEAK	---	---
3	4803.640	55.76	-18.24	74.00	47.04	32.81	11.07	35.17	PEAK	---	---
4 @	4804.048	40.90	-13.10	54.00	32.18	32.81	11.07	35.17	AVERAGE	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	1601.923	40.52	-33.48	74.00	43.94	25.92	5.38	34.72	PEAK	---	---
2	1602.019	33.47	-20.53	54.00	36.88	25.92	5.38	34.72	AVERAGE	---	---
3 @	4803.968	42.48	-11.52	54.00	33.77	32.81	11.07	35.17	AVERAGE	---	---
4	4803.968	58.64	-15.36	74.00	49.93	32.81	11.07	35.17	PEAK	---	---

Temperature	21°C	Humidity	65%
Test Engineer	Leo Hung	Configurations	Channel 39

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	1628.029	44.13	-9.87	54.00	47.35	26.13	5.38	34.73	AVERAGE	---	---
2	1628.029	47.19	-26.81	74.00	50.41	26.13	5.38	34.73	PEAK	---	---
3	4881.167	52.07	-21.93	74.00	43.22	32.88	11.12	35.15	PEAK	---	---
4 @	4882.128	40.35	-13.65	54.00	31.50	32.88	11.12	35.15	AVERAGE	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	1628.029	38.89	-15.11	54.00	42.11	26.13	5.38	34.73	AVERAGE	---	---
2	1628.029	43.56	-30.44	74.00	46.77	26.13	5.38	34.73	PEAK	---	---
3	4881.944	57.04	-16.96	74.00	48.19	32.88	11.12	35.15	PEAK	---	---
4 @	4882.072	41.63	-12.37	54.00	32.78	32.88	11.12	35.15	AVERAGE	---	---

Temperature	21°C	Humidity	65%
Test Engineer	Leo Hung	Configurations	Channel 78

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	1653.974	44.67	-9.33	54.00	47.73	26.23	5.45	34.74	AVERAGE	---	---
2	1653.974	47.22	-26.78	74.00	50.28	26.23	5.45	34.74	PEAK	---	---
3 @	4959.992	39.82	-14.18	54.00	30.82	32.97	11.17	35.14	AVERAGE	---	---
4	4960.272	51.37	-22.63	74.00	42.37	32.97	11.17	35.14	PEAK	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	1653.974	34.06	-19.94	54.00	37.12	26.23	5.45	34.74	AVERAGE	---	---
2	1653.974	40.70	-33.30	74.00	43.76	26.23	5.45	34.74	PEAK	---	---
3 @	4959.928	41.61	-12.39	54.00	32.61	32.97	11.17	35.14	AVERAGE	---	---
4	4959.928	51.20	-22.80	74.00	42.20	32.97	11.17	35.14	PEAK	---	---

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.

4.7. Band Edge Emissions Measurement

4.7.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100 KHz /100 KHz for Peak

4.7.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the freqeuncy range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.7.7. Test Result of Band Edge Emissions

For Emission in Restricted Band

Temperature	21°C	Humidity	65%
Test Engineer	Leo Hung	Configurations	Channel 0, 78

Channel 0

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2390.000	56.23	-17.77	74.00	20.63	28.88	6.72	0.00	PEAK	---	---
2	2390.000	26.49	-27.51	54.00	-9.11	28.88	6.72	0.00	Average	---	---

Channel 78

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
3 @	2483.500	62.48	-11.52	74.00	26.56	28.98	6.94	0.00	Peak	---	---
4	2483.500	27.04	-26.96	54.00	-8.88	28.98	6.94	0.00	Average	---	---

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Receiving maximum band edge emissions are Vertical Polarization /Horizontal Polarization.

For Emission not in Restricted Band

Low Band Edge Plot on Channel 0 / 2402 MHz



Date: 29.OCT.2005 20:49:33

High Band Edge Plot on Channel 78 / 2480 MHz



Date: 29.OCT.2005 20:53:45

4.8. Antenna Requirements

4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.8.2. Antenna Connector Construction

Please refer to section 3.2 in this test report, all antenna connectors comply with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Feb. 16, 2005	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	2001/004	9kHz – 30MHz	Apr. 20, 2005	Conduction (CO04-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	99041	9kHz – 30MHz	May. 05, 2005	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2005	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	Jun. 16, 2005	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100019	9KHZ~40GHz	Jul. 21, 2005	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	18667	9KHz ~ 2GHz	Jan. 10, 2005	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1GHz ~ 26.5GHz	May 31, 2005	Radiation (03CH03-HY)
Biconical Antenna	SCHWARZBECK	VHBB 9124	301	30MHz ~ 200MHz	Jul. 22, 2005	Radiation (03CH03-HY)
Log Antenna	SCHWARZBECK	VUSLP 9111	221	200MHz ~ 1GHz	Jul. 22, 2005	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 22, 2005	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz ~ 1GHz	Feb. 22, 2005	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz ~ 40GHz	Dec.01, 2004	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum analyzer	R&S	FSP40	100116	9kHz ~ 40GHx	Jan. 28, 2005	Conducted (TH01-HY)
Power meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 06, 2005	Conducted (TH01-HY)
Power sensor	R&S	NRV-Z55	100049	DC ~ 40GHz	Jul. 06, 2005	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Apr. 28, 2005	Conducted (TH01-HY)
AC power source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Apr. 21, 2005	Conducted (TH01-HY)
DC power source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Nov. 28, 2004	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2005	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Jan. 01, 2005	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Jan. 01, 2005	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS1012	CO38515	100MHz / 1GS/s	Apr. 15, 2005	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Dec. 31, 2004	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Amplifier	MITEQ	AMF-6F-260400	923364	26.5GHz ~ 40GHz	Jan. 05, 2004*	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9kHz ~ 30MHz	May. 24, 2004*	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz ~ 40GHz	Jun. 09, 2004*	Radiation (03CH03-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 02, 2005	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

6. SPORTON COMPANY PROFILE

SPORTON Lab. was established in 1986 with one shielded room: the first private EMI test facility, offering local manufacturers an alternative EMI test familial apart from ERSO. In 1988, one 3M and 10M/3M open area test site were setup and also obtained official accreditation from FCC, VCCI and NEMKO. In 1993, a Safety laboratory was founded and obtained accreditation from UL of USA, CSA of Canada and TUV (Rhineland & PS) of Germany. In 1995, one EMC lab, including EMI and EMS test facilities was setup. In 1997, SPORTON Group has provided financial expense to relocate the headquarter to Orient Scientific Park in Taipei Hsien to offer more comprehensive, more qualified and better service to local suppliers and manufactures. In 1999, Safety Group and Component Group were setup. In 2001, SPORTON has established 3M/10M chamber in Hwa Ya Technology Park.

6.1. Test Location

SHIJR	ADD	:	6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C.
	TEL	:	02-2696-2468
	FAX	:	02-2696-2255
HWA YA	ADD	:	No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
	TEL	:	03-327-3456
	FAX	:	03-318-0055
LINKOU	ADD	:	No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C
	TEL	:	02-2601-1640
	FAX	:	02-2601-1695
DUNGHU	ADD	:	No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C.
	TEL	:	02-2631-4739
	FAX	:	02-2631-9740
JUNGHE	ADD	:	7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C.
	TEL	:	02-8227-2020
	FAX	:	02-8227-2626
NEIHU	ADD	:	4Fl., No. 339, Hsin Hu 2nd Rd., Taipei 114, Taiwan, R.O.C.
	TEL	:	02-2794-8886
	FAX	:	02-2794-9777
JHUBEI	ADD	:	No.8, Lane 728, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.
	TEL	:	03-656-9065
	FAX	:	03-656-9085

7. CERTIFICATE OF NVLAP ACCREDITATION

United States Department of Commerce
National Institute of Standards and Technology

NVLAP®

ISO/IEC 17025:1999
ISO 9002:1994

Certificate of Accreditation

DEPARTMENT OF COMMERCE ★ UNITED STATES OF AMERICA ★

SPORTON INTERNATIONAL, INC.
TAIPEI HSIEN 221
TAIWAN

is recognized by the National Voluntary Laboratory Accreditation Program for satisfactory compliance with criteria set forth in NIST Handbook 150:2001, all requirements of ISO/IEC 17025:1999, and relevant requirements of ISO 9002:1994. Accreditation is awarded for specific services, listed on the Scope of Accreditation, for:

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS

December 31, 2005
Effective through

For the National Institute of Standards and Technology
NVLAP Lab Code: 200079-0

NVLAP-01C (06-01)