



RADIO TEST REPORT

Test Report No. : 10377588H-A-R1

Applicant : OMRON HEALTHCARE Co., Ltd.
Type of Equipment : Activity Monitor
Model No. : HJA-750C
FCC ID : Q6ZHJA750C
Test regulation : FCC Part 15 Subpart C: 2014
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This report is a revised version of 10377588H-A. 10377588H-A is replaced with this report.

Date of test: June 16 and 22, 2014

Representative test engineer:

K. Kawamura

Keisuke Kawamura

Engineer

Consumer Technology Division

Approved by:

Takayuki Shimada

Takayuki Shimada

Engineer

Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
<http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429

CONTENTS	PAGE
SECTION 1: Customer information.....	4
SECTION 2: Equipment under test (E.U.T.).....	4
SECTION 3: Test specification, procedures & results.....	5
SECTION 4: Operation of E.U.T. during testing.....	8
SECTION 5: Radiated Spurious Emission	9
SECTION 6: Antenna Terminal Conducted Tests.....	10
APPENDIX 1: Data of EMI test.....	11
6dB Bandwidth	11
Maximum Peak Output Power	13
Radiated Spurious Emission	15
Conducted Spurious Emission	19
Power Density	22
99%Occupied Bandwidth	24
APPENDIX 2: Test instruments	25
APPENDIX 3: Photographs of test setup	26
Radiated Spurious Emission	26
Worst Case Position (Horizontal: Z-axis/ Vertical:Y-axis)	27

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 1: Customer information

Company Name	:	OMRON HEALTHCARE Co., Ltd.
Address	:	53 Kunotsubo, Terado-cho, Muko, Kyoto 617-0002 Japan
Telephone Number	:	+81-75-925-2045
Facsimile Number	:	+81-75-925-2046
Contact Person	:	Toshiaki Yuasa

***Remarks:**

OMRON HEALTHCARE Co., Ltd. designates Hashimoto Electronic Industry as manufacturer of the product (Activity Monitor).

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment	:	Activity Monitor
Model No.	:	HJA-750C
Serial No.	:	Refer to Section 4, Clause 4.2
Rating	:	DC 3.0V
Receipt Date of Sample	:	June 16, 2014
Country of Mass-production	:	Japan
Condition of EUT	:	Production prototype
		(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	:	No Modification by the test lab

2.2 Product Description

General Specification

Clock frequency(ies) in the system	:	32.768kHz, 2.7MHz, 32MHz
------------------------------------	---	--------------------------

Radio Specification

Bluetooth (Low Energy)

Radio Type	:	Transceiver
Frequency of Operation	:	2402-2480MHz
Modulation	:	GFSK
Bandwidth & Channel Spacing	:	1MHz & 2MHz
Power Supply (radio part input)	:	DC 2.5V
Antenna type	:	$\lambda/4$ Monopole Antenna
Antenna Gain	:	2.5dBi

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C: 2014, final revised on May 1, 2014 and effective June 2, 2014

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.247 Operation within the bands 902-928MHz,
2400-2483.5MHz, and 5725-5850MHz

3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.4:2003 7. AC powerline Conducted Emission measurements ----- IC: RSS-Gen 7.2.4	FCC: Section 15.207 ----- IC: RSS-Gen 7.2.4	N/A	N/A*1)	-
6dB Bandwidth	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" ----- IC: RSS-Gen 4.6.2	FCC: Section 15.247(a)(2) ----- IC: RSS-210 A8.2(a)	See data.	Complied	Conducted
Maximum Peak Output Power	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" ----- IC: RSS-Gen 4.8	FCC: Section 15.247(b)(3) ----- IC: RSS-210 A8.4(4)		Complied	Conducted
Power Density	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" ----- IC: -	FCC: Section 15.247 (e) ----- IC: RSS-210 A8.2(b)		Complied	Conducted
Spurious Emission Restricted Band Edges	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" ----- IC: RSS-Gen 4.9	FCC: Section15.247(d) ----- IC: RSS-210 A8.5 RSS-Gen 7.2.3	8.8dB 9920.000MHz, AV, Vert./Hori.	Complied	Conducted/ Radiated

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

* In case any questions arise about test procedure, ANSI C63.4: 2003 is also referred.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

FCC 15.31 (e)

The test was performed with the New Battery (DC3.0V) and the stable voltage was supplied to the EUT during the tests. Therefore, the EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because it is soldered on the circuit board. Therefore the equipment complies with the requirement of 15.203.

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	IC: RSS-Gen 4.6.1	IC: RSS-Gen 4.6.1	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room (semi-anechoic chamber)	Radiated emission						
	(3m*)(+dB)				(1m*)(+dB)		(0.5m*)(+dB)
	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	1GHz -10GHz	10GHz -18GHz	18GHz -26.5GHz	26.5GHz -40GHz
No.1	4.0dB	5.1dB	5.0dB	5.1dB	6.0dB	4.9dB	4.3dB
No.2	3.9dB	5.2dB	5.0dB	4.9dB	5.9dB	4.7dB	4.2dB
No.3	4.3dB	5.1dB	5.2dB	5.2dB	6.0dB	4.8dB	4.2dB
No.4	4.6dB	5.2dB	5.0dB	5.2dB	6.0dB	5.7dB	4.2dB

*3m/1m/0.5m = Measurement distance

Power meter (+dB)	
Below 1GHz	Above 1GHz
0.7dB	1.5dB

Antenna terminal conducted emission and Power density (+dB)			Antenna terminal conducted emission (+dB)		Channel power (+dB)
Below 1GHz	1GHz-3GHz	3GHz-18GHz	18GHz-26.5GHz	26.5GHz-40GHz	
1.5dB	1.7dB	2.8dB	2.8dB	2.9dB	2.6dB

Radiated emission test(3m)

The data listed in this test report has enough margin, more than the site margin.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0
 4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
 Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.0 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Data of EMI, Test instruments, and Test set up

Refer to APPENDIX.

UL Japan, Inc.
Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
 Telephone : +81 596 24 8999
 Facsimile : +81 596 24 8124


SECTION 4: Operation of E.U.T. during testing

4.1 Operating Mode(s)

Bluetooth Low Energy (BT LE): Transmitting (Tx), Payload: PRBS9

Test Item	Operating Mode	Tested frequency
6dB Bandwidth Maximum Peak Output Power Power Density Spurious Emission Restricted Band Edges 99% Occupied Bandwidth	BT LE	2402MHz 2440MHz 2480MHz
*Transmitting duty was 100% on all tests. *Power of the EUT was set by the software as follows; Power settings: 0dBm Software: SMartRF studio7 1.16.0 *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.		

4.2 Configuration and peripherals



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

Description of EUT

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Activity Monitor	HJA-750C	FT-12 *1) 002 *2)	Hashimoto Electronic Industry	EUT

*1) Used for Radiated Emission test

*2) Used for Antenna Terminal conducted test

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	Signal Cable	0.04	Unshielded	Unshielded	*1)

*1) The cable was used as test jig and will not be included in the package of production model.
There was no influence on Spurious emission test.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Radiated Spurious Emission

Test Procedure

It was measured based on "11.0 Emissions in non-restricted frequency bands" of "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 (Issued on April 9, 2013)".

EUT was placed on a urethane platform of nominal size, 0.5m by 1.0m, raised 0.8m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

The height of the measuring antenna varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	Below 30MHz	30MHz to 300MHz	300MHz to 1GHz	Above 1GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn

In any 100kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20dBc was applied to the frequency over the limit of FCC 15.209 / Table 5 of RSS-Gen 7.2.5(IC) and outside the restricted band of FCC15.205 / Table 3 of RSS-Gen 7.2.2 (IC).

Frequency	Below 1GHz	Above 1GHz		20dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120kHz(T/R)	RBW: 1MHz VBW: 3MHz	Average Power Method: 12.2.5.1 *1) RBW: 1MHz VBW: 3MHz Trace: Free Run Detector: Power Averaging (RMS)	RBW: 100kHz VBW: 300kHz (S/A)
Test Distance	3m	3m (below 10GHz), 1m *2) (above 10GHz)		3m (below 10GHz), 1m *2) (above 10GHz)

*1) Average Power Measurement was performed based on 6.0 & 12.2.5 of "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 (Issued on April 9, 2013)"

*2) Distance Factor: $20 \times \log(3.0\text{m}/1.0\text{m}) = 9.5\text{dB}$

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 30M-26.5GHz
Test data : APPENDIX
Test result : Pass

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 6: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
6dB Bandwidth	3MHz	100kHz	300kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth	Enough width to display 20dB Bandwidth	1 to 3% of Span	Three times of RBW	Auto	Sample	Clear write	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/ Average *1)	-	Power Meter (Sensor: 50MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3kHz	10kHz	116msec	Peak	Max Hold	Spectrum Analyzer *2)
Conducted Spurious Emission *3)	9kHz to 150kHz	200Hz	620Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150kHz to 30MHz	9.1kHz	27kHz				

*1) Reference data
*2) Section 10.2 Method PKPSD (peak PSD) of "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 (Issued on April 9, 2013)".
*3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.
Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart.(9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=9.1kHz)

The test results and limit are rounded off to two decimals place, so some differences might be observed.

Test data : APPENDIX
Test result : Pass

APPENDIX 1: Data of EMI test

6dB Bandwidth

Test place	Ise EMC Lab. No.7 Measurement Room
Report No.	10377588H
Date	06/16/2014
Temperature/ Humidity	21 deg. C / 59% RH
Engineer	Shinya Watanabe
Mode	LE Tx

Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
2402	0.666	>500
2440	0.676	>500
2480	0.678	>500

UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

6dB Bandwidth



Maximum Peak Output Power

Test place : Ise EMC Lab. No.7 Measurement Room
Report No. : 10377588H
Date : 06/16/2014
Temperature/ Humidity : 21 deg. C / 59% RH
Engineer : Shinya Watanabe
Mode : LE Tx

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2402	-9.78	0.40	10.00	0.62	1.15	30.00	1000	29.38
2440	-10.37	0.40	10.00	0.03	1.01	30.00	1000	29.97
2480	-10.83	0.40	10.00	-0.43	0.91	30.00	1000	30.43

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Average Output Power (Reference data for RF Exposure)

Test place Ise EMC Lab. No.7 Measurement Room
Report No. 10377588H
Date 06/16/2014
Temperature/ Humidity 21 deg. C / 59% RH
Engineer Shinya Watanabe
Mode LE Tx

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2402	-10.45	0.40	10.00	-0.05	0.99	30.00	1000	30.05
2440	-11.09	0.40	10.00	-0.69	0.85	30.00	1000	30.69
2480	-11.95	0.40	10.00	-1.55	0.70	30.00	1000	31.55

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. : 10377584H
Date : 06/22/2014
Temperature/ Humidity : 22deg. C / 60% RH
Engineer : Keisuke Kawamura
Mode : LE Tx 2402MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	64.651	QP	22.8	7.3	7.6	32.2	-	5.5	40.0	34.5	
Hori	136.651	QP	22.1	14.3	8.5	32.1	-	12.8	43.5	30.7	
Hori	245.099	QP	22.1	17.2	9.5	32.0	-	16.8	46.0	29.2	
Hori	397.999	QP	21.9	17.5	10.5	31.9	-	18.0	46.0	28.0	
Hori	529.832	QP	21.9	18.6	11.4	32.0	-	19.9	46.0	26.1	
Hori	613.833	QP	22.0	19.6	11.9	32.0	-	21.5	46.0	24.5	
Hori	2390.000	PK	48.8	26.8	3.1	32.7	-	46.0	73.9	27.9	
Hori	2400.000	PK	50.0	26.8	3.1	32.7	-	47.2	73.9	26.7	
Hori	4804.000	PK	40.2	30.6	5.1	31.8	-	44.1	73.9	29.8	
Hori	7206.000	PK	40.8	35.9	6.6	32.7	-	50.6	73.9	23.3	
Hori	9608.000	PK	41.1	38.4	7.0	33.3	-	53.2	73.9	20.7	
Hori	2390.000	AV	40.9	26.8	3.1	32.7	0.0	38.1	53.9	15.8	
Hori	4804.000	AV	31.7	30.6	5.1	31.8	0.0	35.6	53.9	18.3	
Hori	7206.000	AV	33.0	35.9	6.6	32.7	0.0	42.8	53.9	11.1	
Hori	9608.000	AV	32.6	38.4	7.0	33.3	0.0	44.7	53.9	9.2	
Vert	64.651	QP	23.4	7.3	7.6	32.2	-	6.1	40.0	33.9	
Vert	136.651	QP	22.1	14.3	8.5	32.1	-	12.8	43.5	30.7	
Vert	245.099	QP	22.1	17.2	9.5	32.0	-	16.8	46.0	29.2	
Vert	397.999	QP	21.9	17.5	10.5	31.9	-	18.0	46.0	28.0	
Vert	529.832	QP	21.9	18.6	11.4	32.0	-	19.9	46.0	26.1	
Vert	613.833	QP	22.0	19.6	11.9	32.0	-	21.5	46.0	24.5	
Vert	2390.000	PK	48.0	26.8	3.1	32.7	-	45.2	73.9	28.7	
Vert	2400.000	PK	48.4	26.8	3.1	32.7	-	45.6	73.9	28.3	
Vert	4804.000	PK	40.0	30.6	5.1	31.8	-	43.9	73.9	30.0	
Vert	7206.000	PK	40.6	35.9	6.6	32.7	-	50.4	73.9	23.5	
Vert	9608.000	PK	40.0	38.4	7.0	33.3	-	52.1	73.9	21.8	
Vert	2390.000	AV	39.9	26.8	3.1	32.7	0.0	37.1	53.9	16.8	
Vert	4804.000	AV	32.0	30.6	5.1	31.8	0.0	35.9	53.9	18.0	
Vert	7206.000	AV	33.0	35.9	6.6	32.7	0.0	42.8	53.9	11.1	
Vert	9608.000	AV	32.6	38.4	7.0	33.3	0.0	44.7	53.9	9.2	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB
26.5GHz-40GHz 20log(3.0m/0.5m)=15.6dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2402.000	PK	96.5	26.8	3.1	32.7	93.7	-	-	Carrier
Hori	2400.000	PK	50.0	26.8	3.1	32.7	47.2	73.7	26.5	
Vert	2402.000	PK	95.8	26.8	3.1	32.7	93.0	-	-	Carrier
Vert	2400.000	PK	48.4	26.8	3.1	32.7	45.6	73.0	27.4	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. : 10377584H
Date : 06/22/2014
Temperature/ Humidity : 22deg. C / 60% RH
Engineer : Keisuke Kawamura
Mode : LE Tx 2440MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	64.651	QP	22.8	7.3	7.6	32.2	-	5.5	40.0	34.5	
Hori	136.651	QP	22.1	14.3	8.5	32.1	-	12.8	43.5	30.7	
Hori	245.099	QP	22.1	17.2	9.5	32.0	-	16.8	46.0	29.2	
Hori	397.999	QP	21.9	17.5	10.5	31.9	-	18.0	46.0	28.0	
Hori	529.832	QP	21.9	18.6	11.4	32.0	-	19.9	46.0	26.1	
Hori	613.833	QP	22.0	19.6	11.9	32.0	-	21.5	46.0	24.5	
Hori	4880.000	PK	40.2	30.8	5.2	31.7	-	44.5	73.9	29.4	
Hori	7320.000	PK	40.8	35.9	6.6	32.7	-	50.6	73.9	23.3	
Hori	9760.000	PK	41.1	38.7	7.1	33.4	-	53.5	73.9	20.4	
Hori	4880.000	AV	31.7	30.8	5.2	31.7	0.0	36.0	53.9	17.9	
Hori	7320.000	AV	33.0	35.9	6.6	32.7	0.0	42.8	53.9	11.1	
Hori	9760.000	AV	32.6	38.7	7.1	33.4	0.0	45.0	53.9	8.9	
Vert	64.651	QP	23.4	7.3	7.6	32.2	-	6.1	40.0	33.9	
Vert	136.651	QP	22.1	14.3	8.5	32.1	-	12.8	43.5	30.7	
Vert	245.099	QP	22.1	17.2	9.5	32.0	-	16.8	46.0	29.2	
Vert	397.999	QP	21.9	17.5	10.5	31.9	-	18.0	46.0	28.0	
Vert	529.832	QP	21.9	18.6	11.4	32.0	-	19.9	46.0	26.1	
Vert	613.833	QP	22.0	19.6	11.9	32.0	-	21.5	46.0	24.5	
Vert	4880.000	PK	40.0	30.8	5.2	31.7	-	44.3	73.9	29.6	
Vert	7320.000	PK	40.6	35.9	6.6	32.7	-	50.4	73.9	23.5	
Vert	9760.000	PK	40.0	38.7	7.1	33.4	-	52.4	73.9	21.5	
Vert	4880.000	AV	32.0	30.8	5.2	31.7	0.0	36.3	53.9	17.6	
Vert	7320.000	AV	33.0	35.9	6.6	32.7	0.0	42.8	53.9	11.1	
Vert	9760.000	AV	32.6	38.7	7.1	33.4	0.0	45.0	53.9	8.9	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB
 26.5GHz-40GHz 20log(3.0m/0.5m)=15.6dB

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 10377584H
Date 06/22/2014
Temperature/ Humidity 22deg. C / 60% RH
Engineer Keisuke Kawamura
Mode LE Tx 2480MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	64.651	QP	22.8	7.3	7.6	32.2	-	5.5	40.0	34.5	
Hori	136.651	QP	22.1	14.3	8.5	32.1	-	12.8	43.5	30.7	
Hori	245.099	QP	22.1	17.2	9.5	32.0	-	16.8	46.0	29.2	
Hori	397.999	QP	21.9	17.5	10.5	31.9	-	18.0	46.0	28.0	
Hori	529.832	QP	21.9	18.6	11.4	32.0	-	19.9	46.0	26.1	
Hori	613.833	QP	22.0	19.6	11.9	32.0	-	21.5	46.0	24.5	
Hori	2483.500	PK	50.8	26.9	3.1	32.7	-	48.1	73.9	25.8	
Hori	4960.000	PK	40.2	30.9	5.2	31.7	-	44.6	73.9	29.3	
Hori	7440.000	PK	40.8	35.9	6.6	32.7	-	50.6	73.9	23.3	
Hori	9920.000	PK	41.1	38.9	7.1	33.5	-	53.6	73.9	20.3	
Hori	2483.500	AV	44.7	26.9	3.1	32.7	0.0	42.0	53.9	11.9	
Hori	4960.000	AV	31.7	30.9	5.2	31.7	0.0	36.1	53.9	17.8	
Hori	7440.000	AV	33.0	35.9	6.6	32.7	0.0	42.8	53.9	11.1	
Hori	9920.000	AV	32.6	38.9	7.1	33.5	0.0	45.1	53.9	8.8	
Vert	64.651	QP	23.4	7.3	7.6	32.2	-	6.1	40.0	33.9	
Vert	136.651	QP	22.1	14.3	8.5	32.1	-	12.8	43.5	30.7	
Vert	245.099	QP	22.1	17.2	9.5	32.0	-	16.8	46.0	29.2	
Vert	397.999	QP	21.9	17.5	10.5	31.9	-	18.0	46.0	28.0	
Vert	529.832	QP	21.9	18.6	11.4	32.0	-	19.9	46.0	26.1	
Vert	613.833	QP	22.0	19.6	11.9	32.0	-	21.5	46.0	24.5	
Vert	2483.500	PK	48.9	26.9	3.1	32.7	-	46.2	73.9	27.7	
Vert	4960.000	PK	40.0	30.9	5.2	31.7	-	44.4	73.9	29.5	
Vert	7440.000	PK	40.6	35.9	6.6	32.7	-	50.4	73.9	23.5	
Vert	9920.000	PK	40.0	38.9	7.1	33.5	-	52.5	73.9	21.4	
Vert	2483.500	AV	44.8	26.9	3.1	32.7	0.0	42.1	53.9	11.8	
Vert	4960.000	AV	32.0	30.9	5.2	31.7	0.0	36.4	53.9	17.5	
Vert	7440.000	AV	33.0	35.9	6.6	32.7	0.0	42.8	53.9	11.1	
Vert	9920.000	AV	32.6	38.9	7.1	33.5	0.0	45.1	53.9	8.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB
26.5GHz-40GHz 20log(3.0m/0.5m)=15.6dB

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Burst rate confirmation

Test place

Report No.

Date

Temperature/ Humidity

Engineer

Mode

Ise EMC Lab. No.3 Semi Anechoic Chamber


10377584H

06/22/2014

22deg. C / 60% RH

Keisuke Kawamura


LE Tx



Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Measurement Room
Report No.	10377588H
Date	06/16/2014
Temperature/ Humidity	21 deg. C / 59% RH
Engineer	Shinya Watanabe
Mode	LE Tx

LE Tx 2402MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator [dB]	Antenna Gain [dBi]	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]
9.94	-101.6	0.40	10.0	2.5	-88.7	300.0	6.0	-27.4	47.7
299	-91.9	0.40	10.0	2.5	-79.0	300.0	6.0	-17.8	18.1

$E = \text{EIRP} - 20\log(D) + \text{Ground bounce} + 104.8 [\text{dBuV/m}]$

$\text{EIRP} = \text{Reading} + \text{Cable Loss} + \text{Attenuator} + \text{Antenna Gain}$

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Measurement Room
Report No.	10377588H
Date	06/16/2014
Temperature/ Humidity	21 deg. C / 59% RH
Engineer	Shinya Watanabe
Mode	LE Tx

LE Tx 2440MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator [dB]	Antenna Gain [dBi]	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]
11.70	-99.7	0.40	10.0	2.5	-86.8	300.0	6.0	-25.6	46.2
2961	-91.5	0.01	10.0	2.5	-79.0	300.0	6.0	-17.7	-1.8

$E = \text{EIRP} - 20 \log(D) + \text{Ground bounce} + 104.8 [\text{dBuV/m}]$

$\text{EIRP} = \text{Reading} + \text{Cable Loss} + \text{Attenuator} + \text{Antenna Gain}$

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Test place : Ise EMC Lab. No.7 Measurement Room
Report No. : 10377588H
Date : 06/16/2014
Temperature/ Humidity : 21 deg. C / 59% RH
Engineer : Shinya Watanabe
Mode : LE Tx

LE Tx 2480MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator [dB]	Antenna Gain [dBi]	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]
12.41	-100.4	0.40	10.0	2.5	-87.5	300.0	6.0	-26.2	45.7
250	-91.1	0.40	10.0	2.5	-78.2	300.0	6.0	-16.9	19.6

$E = \text{EIRP} - 20 \log(D) + \text{Ground bounce} + 104.8 [\text{dBuV/m}]$

$\text{EIRP} = \text{Reading} + \text{Cable Loss} + \text{Attenuator} + \text{Antenna Gain}$

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Power Density

Test place Ise EMC Lab. No.7 Measurement Room
Report No. 10377588H
Date 06/16/2014
Temperature/ Humidity 21 deg. C / 59% RH
Engineer Shinya Watanabe
Mode LE Tx

Freq.	Reading	Cable Loss	Atten.	Result	Limit	Margin
[MHz]	[dBm]	[dB]	[dB]	[dBm]	[dBm]	[dB]
2402.00	-21.36	0.40	10.00	-10.96	8.00	18.96
2440.00	-23.01	0.40	10.07	-12.54	8.00	20.54
2480.00	-22.94	0.40	10.07	-12.47	8.00	20.47

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999


Facsimile : +81 596 24 8124

Power Density



99%Occupied Bandwidth

Test place Ise EMC Lab. No.7 Measurement Room
Report No. 10377588H
Date 06/16/2014
Temperature/ Humidity 21 deg. C / 59% RH
Engineer Shinya Watanabe
Mode LE Tx



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

APPENDIX 2: Test instruments

EMI test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MOS-34	Thermo-Hygrometer	Custom	CTH-201	3401	AT	2014/02/20 * 12
MRENT-112	Spectrum Analyzer	Agilent	E4440A	MY48250080	AT	2013/10/04 * 12
MPM-08	Power Meter	Anritsu	ML2495A	6K00003338	AT	2013/10/15 * 12
MPSE-11	Power sensor	Anritsu	MA2411B	011737	AT	2013/10/15 * 12
MAT-22	Attenuator(10dB) 1-18GHz	Orient Microwave	BX10-0476-00	-	AT	2014/03/13 * 12
MAEC-03	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	RE	2014/02/27 * 12
MOS-13	Thermo-Hygrometer	Custom	CTH-180	1301	RE	2014/02/20 * 12
MJM-16	Measure	KOMELON	KMC-36	-	RE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE	-
MRENT-114	Spectrum Analyzer	Agilent	E4440A	MY46187105	RE	2013/11/11 * 12
MTR-08	Test Receiver	Rohde & Schwarz	ESCI	100767	RE	2013/08/20 * 12
MBA-03	Biconical Antenna	Schwarzbeck	BBA9106	1915	RE	2013/10/13 * 12
MLA-03	Logperiodic Antenna	Schwarzbeck	USLP9143	174	RE	2013/10/13 * 12
MCC-51	Coaxial cable	UL Japan	-	-	RE	2013/07/23 * 12
MAT-70	Attenuator(6dB)	Agilent	8491A-006	MY52460153	RE	2014/04/14 * 12
MPA-13	Pre Amplifier	SONOMA INSTRUMENT	310	260834	RE	2014/03/14 * 12
MHA-20	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	258	RE	2014/05/26 * 12
MCC-167	Microwave Cable	Junkosha	MWX221	1404S374(1m) / 1405S074(5m)	RE	2014/05/26 * 12
MPA-11	MicroWave System Amplifier	Agilent	83017A	MY39500779	RE	2014/03/24 * 12
MHA-16	Horn Antenna 15-40GHz	Schwarzbeck	BBHA9170	BBHA9170306	RE	2014/05/26 * 12
MHF-25	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	RE	2013/09/01 * 12

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item: RE: Radiated Emission

AT: Antenna Terminal Conducted test

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124