Variant FCC SAR Test Report

APPLICANT	:	ZTE CORPORATION
EQUIPMENT	:	cdma2000 Digital Mobile Handset
BRAND NAME	:	ZTE
MODEL NAME	:	V8000
FCC ID	:	Q78-V8000
STANDARD	:	FCC 47 CFR Part 2 (2.1093) ANSI/IEEE C95.1-1992 IEEE 1528-2003 FCC OET Bulletin 65 Supplement C (Edition 01-01)

This is a variant report which is only valid together with the original test report. The product was received on Jun. 25, 2012 and completely tested on Jul. 09, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai

Jones Tsai / Manager

Testing Laboratory 1190

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

Table of Contents

1. Statement of Compliance **4**
2. Administration Data **5**
2.1 Testing Laboratory 5
2.2 Applicant 5
2.3 Manufacturer 5
2.4 Application Details 5
3. General Information **6**
3.1 Description of Equipment Under Test (EUT) 6
3.2 Product Photos 7
3.3 Applied Standard 7
3.4 Device Category and SAR Limits 7
3.5 Test Conditions 7
4. Specific Absorption Rate (SAR) **8**
4.1 Introduction 8
4.2 SAR Definition 8
5. SAR Measurement System **9**
5.1 E-Field Probe 10
5.2 Data Acquisition Electronics (DAE) 10
5.3 Robot 11
5.4 Measurement Server 11
5.5 Phantom 12
5.6 Device Holder 12
5.7 Data Storage and Evaluation 13
5.8 Test Equipment List 15
6. Tissue Simulating Liquids **16**
7. SAR Measurement Evaluation **17**
7.1 Purpose of System Performance check 17
7.2 System Setup 17
7.3 Validation Results 18
8. EUT Testing Position **19**
8.1 Define two imaginary lines on the handset 19
8.2 Cheek Position 20
8.3 Tilted Position 20
8.4 Body Worn Position 21
9. Measurement Procedures **22**
9.1 Spatial Peak SAR Evaluation 22
9.2 Area & Zoom Scan Procedures 22
9.3 Volume Scan Procedures 23
9.4 SAR Averaged Methods 23
9.5 Power Drift Monitoring 23
10. SAR Test Configurations **24**
10.1 Exposure Positions Consideration 24
10.2 Conducted RF Output Power (Unit: dBm) 25
11. SAR Test Results **27**
11.1 Test Records for Head SAR Test 27
11.2 Test Records for Hotspot SAR Test 28
11.3 Test Records for Body-worn SAR Test 29
11.4 Simultaneous Multi-band Transmission Analysis 30
12. Uncertainty Assessment **32**
13. References **34**
Appendix A. Plots of System Performance Check
Appendix B. Plots of SAR Measurement
Appendix C. DASY Calibration Certificate
Appendix D. Product Photos
Appendix E. Test Setup Photos
Appendix F. Product Equality Declaration

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA222301-01	Rev. 01	This is a variant report for V8000. The product equality declaration could be referred to Appendix F. All test cases were performed on original report which can be referred to SPORTON Report Number FA222301. Based on the original test report, only the worst case was verified for WWAN SAR and retest WLAN SAR for the differences.	Jul. 26, 2012

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **ZTE CORPORATION DUT: cdma2000 Digital Mobile Handset; Brand Name: ZTE; Model Name: V8000** are as follows.

<Standalone SAR>

Band	Position	SAR_{1g} (W/kg)
CDMA2000 BC0	Head	0.583
CDMA2000 BC15	Head	0.684
CDMA2000 BC1	Head	0.424
WLAN 2.4G	Head	0.041
CDMA2000 BC0	Hotspot (1 cm)	1.160
CDMA2000 BC15	Hotspot (1 cm)	1.040
CDMA2000 BC1	Hotspot (1 cm)	0.841
WLAN 2.4G	Hotspot (1 cm)	0.077
Bluetooth	Hotspot (1 cm)	0.016
CDMA2000 BC0	Body-worn (1 cm)	1.160
CDMA2000 BC15	Body-worn (1 cm)	1.060
CDMA2000 BC1	Body-worn (1 cm)	0.841
WLAN 2.4G	Body-worn (1 cm)	0.077

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).

2. Administration Data

2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958

2.2 Applicant

Company Name	ZTE CORPORATION
Address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P. R. China

2.3 Manufacturer

Company Name	ZTE CORPORATION
Address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, P. R. China

2.4 Application Details

Date of Receipt of Application	Jun. 25, 2012
Date of Start during the Test	Jul. 06, 2012
Date of End during the Test	Jul. 09, 2012

3. General Information

3.1 Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT	cdma2000 Digital Mobile Handset
Brand Name	ZTE
Model Name	V8000
FCC ID	Q78-V8000
MEID Code	268435461001651330
Tx Frequency	CDMA2000 BC0 : 824.70 MHz ~ 848.31 MHz CDMA2000 BC1 : 1851.25 MHz ~ 1908.75 MHz CDMA2000 BC15 : 1711.25 ~ 1753.75 MHz WLAN2.4G: 2412 MHz ~ 2462 MHz Bluetooth : 2402 MHz ~ 2480 MHz
Rx Frequency	CDMA2000 BC0 : 869.70 MHz ~ 893.31 MHz CDMA2000 BC1 : 1931.25 MHz ~ 1988.75 MHz CDMA2000 BC15 : 2111.25 ~ 2153.75 MHz WLAN2.4G: 2412 MHz ~ 2462 MHz Bluetooth : 2402 MHz ~ 2480 MHz
Maximum Average Output Power to Antenna	CDMA2000 BC0 : 24.12 dBm CDMA2000 BC1 : 23.77 dBm CDMA2000 BC15 : 24.10 dBm 802.11b : 12.72 dBm 802.11g : 11.98 dBm 802.11n (BW 20MHz) (2.4GHz) : 11.87 dBm Bluetooth: 9.65 dBm
Antenna Type	WWAN: Fixed Internal Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna
HW Version	QB8655-02A_V1DMB_B
SW Version	V8000_CKT_1.72
Type of Modulation	CDMA2000 : QPSK 802.11b : DSSS (BPSK / QPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Identical Prototype
Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	

3.2 Product Photos

Please refer to Appendix D.

3.3 Applied Standard

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 447498 D01 v04
- FCC KDB 648474 D01 v01r05
- FCC KDB 941225 D01 v02
- FCC KDB 941225 D06 v01
- FCC KDB 248227 D01 v01r02

3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

3.5 Test Conditions

3.5.1 Ambient Condition

Ambient Temperature	20 to 24 ℃
Humidity	< 60 %

3.5.2 Test Configuration

The device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during all tests.

For WLAN SAR testing, WLAN engineering testing software installed on the EUT can provide continuous transmitting RF signal.

4. Specific Absorption Rate (SAR)

4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\mathbf{SAR} = \frac{\mathbf{d}}{\mathbf{dt}}\left(\frac{\mathbf{dW}}{\mathbf{dm}}\right) = \frac{\mathbf{d}}{\mathbf{dt}}\left(\frac{\mathbf{dW}}{\boldsymbol{\rho}\mathbf{dv}}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\mathbf{SAR} = \mathbf{C}\left(\frac{\boldsymbol{\delta}\mathbf{T}}{\boldsymbol{\delta}\mathbf{t}}\right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\mathbf{SAR} = \frac{\boldsymbol{\sigma}|\mathbf{E}|^2}{\boldsymbol{\rho}}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

5. SAR Measurement System



Fig 5.1 SPEAG DASY System Configurations

The DASY system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY software
- Remove control with teach pendant and additional circuitry for robot safety such as warming lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Component details are described in in the following sub-sections.

5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

5.1.1 E-Field Probe Specification

< ES3DV3 Probe >

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	 **Fig 5.2 Photo of ES3DV3**
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 µW/g to 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than ± 10%. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.
The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

Fig 5.3 Photo of DAE

5.3 Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ±0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

Fig 5.4 Photo of DASY5

5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.

Fig 5.5 Photo of Server for DASY5

5.5 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet
Measurement Areas	Left Hand, Right Hand, Flat Phantom

Fig 5.6 Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

5.6 Device Holder

<Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\varepsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

Fig 5.7 Device Holder

5.7 Data Storage and Evaluation

5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software：

Probe parameters：	- Sensitivity	$Norm_i$, a_{i0}, a_{i1}, a_{i2}
	- Conversion factor	$ConvF_i$
	- Diode compression point	dcp_i
Device parameters：	- Frequency	f
	- Crest factor	cf
Media parameters：	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as：

$$\mathbf{V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}}$$

with V_i = compensated signal of channel i, (i = x, y, z)
U_i = input signal of channel i, (i = x, y, z)
cf = crest factor of exciting field (DASY parameter)
dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated：

E-field Probes：$\mathbf{E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}}$

H-field Probes：$\mathbf{H_i = \sqrt{V_i} \cdot \frac{a_{i0}+a_{i1}f+a_{i2}f^2}{f}}$

with V_i = compensated signal of channel i, (i = x, y, z)
$Norm_i$ = sensor sensitivity of channel i, (i = x, y, z), μV/(V/m)^2 for E-field Probes
ConvF = sensitivity enhancement in solution
a_{ij} = sensor sensitivity factors for H-field probes
f = carrier frequency [GHz]
E_i = electric field strength of channel i in V/m
H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude)：

$$\mathbf{E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}}$$

The primary field data are used to calculate the derived field units.

$$\mathbf{SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}}$$

with SAR = local specific absorption rate in mW/g
E_{tot} = total field strength in V/m
σ = conductivity in [mho/m] or [Siemens/m]
ρ = equivalent tissue density in g/cm^3

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 12, 2011	Sep. 11, 2012
SPEAG	Data Acquisition Electronics	DAE4	1303	Nov. 10, 2011	Nov. 09, 2012
SPEAG	835MHz System Validation Kit	D835V2	4d091	Nov. 18, 2011	Nov. 17, 2012
SPEAG	1750MHz System Validation Kit	D1750V2	1023	Jun. 20, 2012	Jun. 19, 2013
SPEAG	1900MHz System Validation Kit	D1900V2	5d118	Nov. 21, 2011	Nov. 20, 2012
SPEAG	2450MHz System Validation Kit	D2450V2	736	Jul. 25, 2011	Jul. 24, 2012
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1670	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1671	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio Communication Analyzer	MT8820C	6201091028	Jun. 10, 2012	Jun. 09, 2013
Agilent	Base Station	E5515C	MY50267224	Dec. 29, 2011	Dec. 28, 2012
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	Apr. 13, 2012	Apr. 12, 2013
R&S	Signal Generator	SMR40	100455	Dec. 30, 2011	Dec. 29, 2012
Agilent	Power Meter	E4416A	MY45101555	Aug. 23, 2011	Aug. 22, 2012
Agilent	Power Sensor	E9327A	MY44421198	Aug. 23, 2011	Aug. 22, 2012
R&S	Spectrum Analyzer	FSP30	101400	Jun. 01, 2012	May 31, 2013

Table 5.1 Test Equipment List

Note: The calibration certificate of DASY can be referred to appendix C of this report.

6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.

Fig 6.1 Photo of Liquid Height for Head SAR

Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ε_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7

Table 6.1 Recipes of Tissue Simulating Liquid

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

The following table shows the measuring results for simulating liquid.

Freq. (MHz)	Liquid Type	Temp. (℃)	Conductivity (σ)	Permittivity (ε_r)	Conductivity Target (σ)	Permittivity Target (ε_r)	Delta (σ) (%)	Delta (ε_r) (%)	Limit (%)	Date
835	Head	21.5	0.914	41.826	0.90	41.5	1.56	0.79	±5	Jul. 06, 2012
835	Body	21.4	0.977	54.379	0.97	55.2	0.72	-1.49	±5	Jul. 06, 2012
1750	Head	21.6	1.381	40.83	1.40	40.0	-1.36	2.08	±5	Jul. 06, 2012
1750	Body	21.5	1.512	55.273	1.52	53.3	-0.53	3.70	±5	Jul. 06, 2012
1900	Head	21.6	1.417	39.706	1.40	40.0	1.21	-0.73	±5	Jul. 06, 2012
1900	Body	21.7	1.519	53.569	1.52	53.3	-0.07	0.50	±5	Jul. 06, 2012
2450	Head	21.4	1.82	39.753	1.80	39.2	1.11	1.41	±5	Jul. 09, 2012
2450	Body	21.3	1.951	53.859	1.95	52.7	0.05	2.20	±5	Jul. 09, 2012

Table 6.2 Measuring Results for Simulating Liquid

7. SAR Measurement Evaluation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

7.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

7.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Fig 7.1 System Setup for System Evaluation

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 24 dBm (250 mW) before dipole is connected.

Fig 7.2 Photo of Dipole Setup

7.3 Validation Results

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %. Table 7.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Measurement Date	Frequency (MHz)	Liquid Type	Targeted SAR_{1g} (W/kg)	Measured SAR_{1g} (W/kg)	Normalized SAR_{1g} (W/kg)	Deviation (%)
Jul. 06, 2012	835	Head	9.40	2.47	9.88	5.11
Jul. 06, 2012	835	Body	9.42	2.39	9.56	1.49
Jul. 06, 2012	1750	Head	36.2	9.52	38.08	5.19
Jul. 06, 2012	1750	Body	36.8	9.61	38.44	4.46
Jul. 06, 2012	1900	Head	40.3	9.26	37.04	-8.09
Jul. 06, 2012	1900	Body	41.8	10.6	42.40	1.44
Jul. 09, 2012	2450	Head	54.8	13.2	52.80	-3.65
Jul. 09, 2012	2450	Body	52.3	13	52.00	-0.57

Table 7.1 Target and Measurement SAR after Normalized

8. EUT Testing Position

This EUT was tested in seven different positions. They are right cheek, right tilted, left cheek, left tilted, front of the EUT with phantom 1 cm gap, back of the EUT with phantom 1 cm gap, Right Side of the EUT with phantom 1 cm gap as illustrated below:

8.1 Define two imaginary lines on the handset

(a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.

(b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.

(c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Fig 9.1 Illustration for Handset Vertical and Horizontal Reference Lines

8.2 Cheek Position

(a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 9.2).



Fig 9.2 Illustration for Cheek Position

8.3 Tilted Position

(a) To position the device in the "cheek" position described above.

(b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 9.3).



Fig 9.3 Illustration for Tilted Position

8.4 Body Worn Position

(a) To position the device parallel to the phantom surface with either keypad up or down.
(b) To adjust the device parallel to the flat phantom.
(c) To adjust the distance between the device surface and the flat phantom to 1 cm or holster surface.



Fig 9.4 Illustration for Body Worn Position

<EUT Setup Photos>

Please refer to Appendix E for the test setup photos.

9. Measurement Procedures

The measurement procedures are as follows:

(a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
(b) Keep EUT to radiate maximum output power or 100% duty factor (if applicable)
(c) Measure output power through RF cable and power meter.
(d) Place the EUT in the positions as Appendix E demonstrates.
(e) Set scan area, grid size and other setting on the DASY software.
(f) Measure SAR results for the highest power channel on each testing position.
(g) Find out the largest SAR result on these testing positions of each band
(h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

(a) Power reference measurement
(b) Area scan
(c) Zoom scan
(d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

(a) Extraction of the measured data (grid and values) from the Zoom Scan
(b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
(c) Generation of a high-resolution mesh within the measured volume
(d) Interpolation of all measured values form the measurement grid to the high-resolution grid
(e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
(f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

9.3 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.4 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

9.5 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

10. SAR Test Configurations

10.1 Exposure Positions Consideration



10.2 Conducted RF Output Power (Unit: dBm)

<CDMA2000>

Band	CDMA2000 BC0			CDMA2000 BC1			CDMA2000 BC15		
Channel	1013	384	777	25	600	1175	25	425	875
Frequency (MHz)	824.70	836.52	848.31	1851.25	1880.00	1908.75	1711.25	1731.25	1753.75
1xRTT RC1+SO55	24.10	24.04	24.01	23.71	23.69	23.68	23.78	23.90	23.88
1xRTT RC3+SO55	24.12	24.06	24.03	23.77	23.67	23.62	23.80	23.92	23.89
1xRTT RC3+SO32 (+ F-SCH)	24.11	24.05	24.04	23.71	23.68	23.69	23.79	23.91	23.87
1xRTT RC3+SO32(+SCH)	24.10	24.03	24.02	23.75	23.73	23.61	23.78	23.90	23.88
1xEVDO RTAP 153.6K	24.09	24.02	24.04	23.75	23.75	23.64	23.99	24.10	24.09
1xEVDO RETAP 4096K	24.10	24.01	24.00	23.76	23.76	23.66	23.97	24.09	24.08

Note:

1. According to KDB 941225 D01, Head SAR for RC1+SO55 is not required because the maximum average output power of RC1 is less than 1/4 dB higher than RC3+SO55.
2. Referring to KDB 941225 D01, the CDMA Handset Body-worn SAR tests based on RC3+SO32. RC1, RTAP (REV 0), and RETAP (Rev A) power are all less than 1/4 dB higher than RC3, thus SAR tests in these mode are not necessary.
3. Referring to KDB 941225 D01, in Hotspot mode EUT is treated as data device and SAR is tested with RTAP 153.6kbps (Ev-Do). If RC3+SO32 power is less than 1/4dB higher than Ev-Do, SAR tests with RC3+SO32 setting are not necessary.

<WLAN 2.4GHz>

Mode	Channel	Frequency (MHz)	Average power (dBm)			
			Data Rate (bps)			
			1M	2M	5.5M	11M
802.11b	CH 01	2412	11.40	11.34	11.60	11.39
	CH 06	2437	12.12	11.96	12.09	12.11
	CH 11	2462	12.72	12.64	12.71	12.65

Mode	Channel	Frequency (MHz)	Average power (dBm)							
			Data Rate (bps)							
			6M	9M	12M	18M	24M	36M	48M	54M
802.11g	CH 01	2412	10.87	10.86	10.83	10.72	10.86	10.77	10.81	10.82
	CH 06	2437	11.51	11.43	11.38	11.40	11.48	11.34	11.30	11.33
	CH 11	2462	11.98	11.88	11.94	11.90	11.95	11.94	11.96	11.78

Mode	Channel	Frequency (MHz)	Average power (dBm)							
			Data Rate (bps)							
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n 20M	CH 01	2412	10.77	10.69	10.66	10.71	10.67	10.74	10.76	10.67
	CH 06	2437	11.40	11.39	11.20	11.33	11.19	11.35	11.27	11.29
	CH 11	2462	11.87	11.83	11.79	11.85	11.83	11.80	11.85	11.80

Note:

1. Per KDB 248227, choose the highest output power channel to test SAR and determine further SAR exclusion
2. Per KDB 248227, 11g and 11n output power is less than 1/4 dB higher than 11b mode, thus the SAR can be excluded.
3. For each frequency band, testing at higher data rates and higher order modulations is not requirement when the maximum average output power for each of these configurations is less than 1/4 dB higher than those measured at the lowest data rate.

<Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power (dBm)								
			Data Rate								
			DH1	DH3	DH5	2DH1	2DH3	2DH5	3DH1	3DH3	3DH5
Bluetooth	CH 00	2402 MHz	8.15	8.12	8.05	5.88	6.08	5.99	6.07	6.08	5.97
	CH 39	2441 MHz	9.36	9.40	9.29	7.33	7.32	7.36	7.32	7.30	7.39
	CH 78	2480 MHz	9.65	9.64	9.53	7.36	7.43	7.41	7.47	7.48	6.10

11. SAR Test Results

11.1 Test Records for Head SAR Test

<CDMA2000>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Output Power (dBm)	Power Drift (dB)	SAR_{1g} (W/kg)
1	CDMA2000 BC0	RC3 SO55	Right Cheek	1013	824.70	24.12	-0.17	0.583
2	CDMA2000 BC15	RC3 SO55	Left Cheek	425	1731.25	23.92	0.07	0.684
3	CDMA2000 BC1	RC3 SO55	Left Cheek	25	1851.25	23.77	-0.1	0.424

Note: Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<WLAN>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Output Power (dBm)	Power Drift (dB)	SAR_{1g} (W/kg)
4	**WLAN2.4G**	**802.11b**	**Right Cheek**	**11**	**2462**	**12.72**	**0.13**	**0.041**
5	WLAN2.4G	802.11b	Right Tilted	11	2462	12.72	0.17	0.00929
6	WLAN2.4G	802.11b	Left Cheek	11	2462	12.72	0.16	0.040
7	WLAN2.4G	802.11b	Left Tilted	11	2462	12.72	0.09	0.009

Note: Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

11.2 Test Records for Hotspot SAR Test

<CDMA2000>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Output Power (dBm)	Power Drift (dB)	SAR_{1g} (W/kg)
8	CDMA2000 BC0	RTAP 153.6	Back	1	1013	824.70	24.09	-0.08	1.060
9	**CDMA2000 BC0**	**RTAP 153.6**	**Back**	**1**	**384**	**836.52**	**24.02**	**0.07**	**1.160**
10	CDMA2000 BC0	RTAP 153.6	Back	1	777	848.31	24.04	0.18	1.010
14	CDMA2000 BC15	RTAP 153.6	Back	1	25	1711.25	23.99	0.01	1.000
15	**CDMA2000 BC15**	**RTAP 153.6**	**Back**	**1**	**425**	**1731.25**	**24.10**	**0.02**	**1.040**
16	CDMA2000 BC15	RTAP 153.6	Back	1	875	1753.75	24.09	0.14	1.010
20	CDMA2000 BC1	RTAP 153.6	Back	1	25	1851.25	23.75	-0.07	0.812
21	**CDMA2000 BC1**	**RTAP 153.6**	**Back**	**1**	**600**	**1880**	**23.75**	**0.06**	**0.841**
22	CDMA2000 BC1	RTAP 153.6	Back	1	1175	1908.75	23.64	0.01	0.612

Note:

1. Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<WLAN>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Output Power (dBm)	Power Drift (dB)	SAR_{1g} (W/kg)
26	WLAN2.4G	802.11b	Front	1	11	2462	12.72	0.15	0.012
27	**WLAN2.4G**	**802.11b**	**Back**	**1**	**11**	**2462**	**12.72**	**0.08**	**0.077**
28	WLAN2.4G	802.11b	Right Side	1	11	2462	12.72	0.13	0.035

Note:

1. Per KDB 941225 D06, for EUT dimension ≥ 9cm*5cm, the test distance is 1cm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
2. Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

<Bluetooth>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Output Power (dBm)	Power Drift (dB)	SAR_{1g} (W/kg)
30	**Bluetooth**	**-**	**Back**	**1**	**78**	**2480**	**9.65**	**-0.10**	**0.016**

Note:

1. Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

11.3 Test Records for Body-worn SAR Test

<CDMA2000>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Output Power (dBm)	Headset	Power Drift (dB)	SAR_{1g} (W/kg)
8	CDMA2000 BC0	RTAP 153.6	Back	1	1013	824.70	24.09	-	-0.08	1.06
9	**CDMA2000 BC0**	**RTAP 153.6**	**Back**	**1**	**384**	**836.52**	**24.02**	**-**	**0.07**	**1.16**
10	CDMA2000 BC0	RTAP 153.6	Back	1	777	848.31	24.04	-	0.18	1.01
11	CDMA2000 BC0	RC3 SO32	Back	1	1013	824.70	24.11	V	0.03	0.756
12	CDMA2000 BC0	RC3 SO32	Back	1	384	836.52	24.05	V	-0.12	0.914
13	CDMA2000 BC0	RC3 SO32	Back	1	777	848.31	24.04	V	-0.08	0.794
14	CDMA2000 BC15	RTAP 153.6	Back	1	25	1711.25	23.99	-	0.01	1.000
15	CDMA2000 BC15	RTAP 153.6	Back	1	425	1731.25	24.10	-	0.02	1.040
16	CDMA2000 BC15	RTAP 153.6	Back	1	875	1753.75	24.09	-	0.14	1.010
17	CDMA2000 BC15	RC3 SO32	Back	1	25	1711.25	23.79	V	-0.05	1.030
18	**CDMA2000 BC15**	**RC3 SO32**	**Back**	**1**	**425**	**1731.25**	**23.91**	**V**	**0.01**	**1.060**
19	CDMA2000 BC15	RC3 SO32	Back	1	875	1753.75	23.87	V	-0.05	1.010
20	CDMA2000 BC1	RTAP 153.6	Back	1	25	1851.25	23.75	-	-0.07	0.812
21	**CDMA2000 BC1**	**RTAP 153.6**	**Back**	**1**	**600**	**1880**	**23.75**	**-**	**0.06**	**0.841**
22	CDMA2000 BC1	RTAP 153.6	Back	1	1175	1908.75	23.64	-	0.01	0.612
23	CDMA2000 BC1	RC3 SO32	Back	1	25	1851.25	23.71	V	-0.14	0.796
24	CDMA2000 BC1	RC3 SO32	Back	1	600	1880	23.68	V	-0.13	0.789
25	CDMA2000 BC1	RC3 SO32	Back	1	1175	1908.75	23.69	V	-0.09	0.576

Note:

1. Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.
2. "V" in the headset column means the headset is plugged during SAR testing.

<WLAN>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Output Power (dBm)	Headset	Power Drift (dB)	SAR_{1g} (W/kg)
26	WLAN2.4G	802.11b	Front	1	11	2462	12.72	-	0.15	0.012
27	**WLAN2.4G**	**802.11b**	**Back**	**1**	**11**	**2462**	**12.72**	**-**	**0.08**	**0.077**
29	WLAN2.4G	802.11b	Back	1	11	2462	12.72	V	0.15	0.073

Note:

1. Per KDB 248227, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.
2. "V" in the headset column means the headset is plugged during SAR testing.

11.4 Simultaneous Multi-band Transmission Analysis

No.	Applicable Simultaneous Transmission Combination
1.	CDMA2000 + Bluetooth
2.	CDMA2000 + WLAN 2.4G
3.	CDMA2000 + Bluetooth + WLAN 2.4G

Note:
1. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. Per KDB 648474 D01, the simultaneous transmission SAR for CDMA2000 and WLAN was not required, because the SAR summation (Head: 0.993 W/kg; Body: 1.237 W/kg) is less than 1.6 W/kg.
3. Per KDB 648474 D01, the simultaneous transmission SAR for CDMA2000 and Bluetooth was not required, because the SAR summation (Head: 0.684 W/kg; Body: 1.176 W/kg) is less than 1.6 W/kg.
4. Per KDB 648474 D01, the simultaneous transmission SAR for CDMA2000, WLAN and Bluetooth was not required, because the SAR summation (Head: 0.993 W/kg; Body: 1.253 W/kg) is less than 1.6 W/kg.

<Head SAR>

Position	WWAN			WLAN		Max. SAR Summation
	WWAN Band	Plot No	Max. WWAN SAR (W/kg)	Plot No	Max. WLAN SAR (W/kg)	
Right Cheek	CDMA2000 BC0	1	0.583	4	0.041	**0.993**
Right Tilted	-	-	-	5	0.00929	**0.00929**
Left Cheek	CDMA2000 BC15	2	0.684	6	0.040	**0.724**
	CDMA2000 BC1	3	0.424	6	0.040	**0.464**
Left Tilted	-	-	-	7	0.009	**0.009**

Note:
1. The maximum SAR summation is calculated based on the same configuration and test position.
2. When stand-alone 1-g SAR is not required for a transmitter or antenna, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements
3. If 1g-SAR scalar summation < 1.6W/kg, simultaneous SAR measurement is not necessary.
4. If 1g-SAR summation > 1.6W/kg, SPLSR calculation is necessary.

<Hotspot SAR>

Position	WWAN			WLAN		Bluetooth		Max. SAR Summation
	WWAN Band	Plot No	Max. WWAN SAR (W/kg)	Plot No	Max. WLAN SAR (W/kg)	Plot No	Max. Bluetooth SAR (W/kg)	
Front	-	-	-	26	0.012	-	-	**0.012**
Back	CDMA2000 BC0	9	1.160	27	0.077	30	0.016	**1.253**
	CDMA2000 BC15	15	1.040	27	0.077	30	0.016	**1.133**
	CDMA2000 BC1	21	0.841	27	0.077	30	0.016	**0.934**
Right Side	-	-	-	28	0.035	-	-	**0.035**

Note:
1. The maximum SAR summation is calculated based on the same configuration and test position.
2. When stand-alone 1-g SAR is not required for a transmitter or antenna, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements
3. If 1g-SAR scalar summation < 1.6W/kg, simultaneous SAR measurement is not necessary.
4. If 1g-SAR summation > 1.6W/kg, SPLSR calculation is necessary.

<Body-worn SAR>

Position	WWAN			WLAN		Bluetooth		Max. SAR Summation
	WWAN Band	Plot No	Max. WWAN SAR (W/kg)	Plot No	Max. WLAN SAR (W/kg)	Plot No	Max. Bluetooth SAR (W/kg)	
Front	-	-	-	26	0.012	-	-	**0.012**
Back	CDMA2000 BC0	9	1.160	27	0.077	30	0.016	**1.253**
	CDMA2000 BC15	15	1.04	27	0.077	30	0.016	**1.133**
	CDMA2000 BC1	21	0.841	27	0.077	30	0.016	**0.934**
Back (with Headset)	CDMA2000 BC0	12	0.914	29	0.073	-	-	**0.987**
	CDMA2000 BC15	18	1.060	29	0.073	-	-	**1.133**
	CDMA2000 BC1	23	0.796	29	0.073	-	-	**0.869**

Note:

1. The maximum SAR summation is calculated based on the same configuration and test position.
2. When stand-alone 1-g SAR is not required for a transmitter or antenna, its SAR is considered zero in the 1-g SAR summing process to determine simultaneous transmission SAR evaluation requirements
3. If 1g-SAR scalar summation < 1.6W/kg, simultaneous SAR measurement is not necessary.
4. If 1g-SAR summation > 1.6W/kg, SPLSR calculation is necessary.

Test Engineer： Kat Yin

12. Uncertainty Assessment

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 12.1

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor[(a)]	1/k[(b)]	$1/\sqrt{3}$	$1/\sqrt{6}$	$1/\sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) κ is the coverage factor

Table 12.1 Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						**± 22.0 %**	**± 21.5 %**

Table 12.2 Uncertainty Budget of DASY for frequency range 300 MHz to 3 GHz

13. References

[1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”

[2] ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992

[3] IEEE Std. 1528-2003, “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, December 2003

[4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), “Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields”, June 2001

[5] SPEAG DASY System Handbook

[6] FCC KDB 248227 D01 v01r02, “SAR Measurement Procedures for 802.11 a/b/g Transmitters”, May 2007

[7] FCC KDB 447498 D01 v04, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, November 2009

[8] FCC KDB 447498 D02 v02, “SAR Measurement Procedures for USB Dongle Transmitters”, November 2009

[9] FCC KDB 616217 D01 v01r01, “SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens”, November 2009

[10] FCC KDB 616217 D03 v01, “SAR Evaluation Considerations for Laptop/Notebook/Netbook and Tablet Computers”, November 2009

[11] FCC KDB 648474 D01 v01r05, “SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas”, September 2008

[12] FCC KDB 941225 D01 v02, “SAR Measurement Procedures for 3G Devices – CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA”, October 2007

[13] FCC KDB 941225 D02 v02 "3GPP R6 HSPA and R7 HSPA+ SAR Guidance", December 2009.

[14] FCC KDB 941225 D03 v01, “Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE”, December 2008

[15] FCC KDB 941225 D04 v01, “Evaluating SAR for GSM/(E)GPRS Dual Transfer Mode”, January 27 2010

[16] FCC KDB 941225 D05 v01, “SAR Test Considerations for LTE Handsets and Data Modems”, December 15 2010

[17] FCC KDB 941225 D06 v01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", April 2011

[18] FCC KDB 388624 D02, "Permit But Ask List", December 2011

Appendix A. Plots of System Performance Check

The plots are shown as follows.

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

System Check_Head_835MHz_120706

DUT: D835V2-SN:4d091

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1
Medium: HSL_835_120706 Medium parameters used: f = 835 MHz; σ = 0.914 mho/m; ε_r = 41.826; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.04, 6.04, 6.04); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 2.66 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 54.148 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 3.748 mW/g
SAR(1 g) = 2.47 mW/g; SAR(10 g) = 1.62 mW/g
Maximum value of SAR (measured) = 2.67 mW/g



0 dB = 2.67 mW/g = 8.53 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

System Check_Body_835MHz_120706

DUT: D835V2-SN:4d091

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 835 MHz; σ = 0.977 mho/m; ε_r = 54.379; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 2.60 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 51.846 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 3.633 mW/g
SAR(1 g) = 2.39 mW/g; SAR(10 g) = 1.56 mW/g
Maximum value of SAR (measured) = 2.59 mW/g



0 dB = 2.59 mW/g = 8.27 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

System Check_Head_1750MHz_120706

DUT: D1750V2-SN:1023

Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1
Medium: HSL_1800_120706 Medium parameters used: f = 1750 MHz; σ = 1.381 mho/m; ε_r = 40.83; ρ = 1000 kg/m^3
Ambient Temperature：23.6 ℃; Liquid Temperature：21.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(5.32, 5.32, 5.32); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 11.5 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 88.738 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 17.778 mW/g
SAR(1 g) = 9.52 mW/g; SAR(10 g) = 4.97 mW/g
Maximum value of SAR (measured) = 10.8 mW/g



0 dB = 10.8 mW/g = 20.67 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

System Check_Body_1750MHz_120706

DUT: D1750V2-SN:1023

Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1750 MHz; σ = 1.512 mho/m; ε_r = 55.273; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 11.5 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 85.908 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 17.662 mW/g
SAR(1 g) = 9.61 mW/g; SAR(10 g) = 5.01 mW/g
Maximum value of SAR (measured) = 10.9 mW/g



0 dB = 10.9 mW/g = 20.75 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

System Check_Head_1900MHz_120706

DUT: D1900V2-SN:5d118

Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1
Medium: HSL_1900_120706 Medium parameters used: f = 1900 MHz; σ = 1.417 mho/m; ε_r = 39.706; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(5.14, 5.14, 5.14); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 11.0 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 86.787 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 17.104 mW/g
SAR(1 g) = 9.26 mW/g; SAR(10 g) = 4.82 mW/g
Maximum value of SAR (measured) = 10.4 mW/g



0 dB = 10.4 mW/g = 20.34 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

System Check_Body_1900MHz_120706

DUT: D1900V2-SN:5d118

Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1900 MHz; σ = 1.519 mho/m; ε_r = 53.569; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 12.4 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 88.882 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 19.317 mW/g
SAR(1 g) = 10.6 mW/g; SAR(10 g) = 5.5 mW/g
Maximum value of SAR (measured) = 11.9 mW/g



0 dB = 11.9 mW/g = 21.51 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

System Check_Head_2450MHz_120709

DUT: D2450V2-SN:736

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1
Medium: HSL_2450_120709 Medium parameters used: f = 2450 MHz; σ = 1.82 mho/m; ε_r = 39.753; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.52, 4.52, 4.52); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 15.1 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 89.443 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 29.101 mW/g
SAR(1 g) = 13.2 mW/g; SAR(10 g) = 5.9 mW/g
Maximum value of SAR (measured) = 15.0 mW/g



0 dB = 15.0 mW/g = 23.52 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

System Check_Body_2450MHz_120709

DUT: D2450V2-SN:736

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1
Medium: MSL_2450_120709 Medium parameters used: f = 2450 MHz; σ = 1.951 mho/m; ε_r = 53.859; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Pin=250mW/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 14.7 mW/g

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 82.505 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 28.742 mW/g
SAR(1 g) = 13 mW/g; SAR(10 g) = 5.86 mW/g
Maximum value of SAR (measured) = 14.8 mW/g



0 dB = 14.8 mW/g = 23.41 dB mW/g

Appendix B. Plots of SAR Measurement

The plots are shown as follows.

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

01 CDMA2000 BC0_RC3 SO55_Right Cheek_Ch1013

DUT: 222301-01

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: HSL_835_120706 Medium parameters used: f = 824.7 MHz; σ = 0.905 mho/m; ε_r = 41.923; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.04, 6.04, 6.04); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.607 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.195 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.717 mW/g
SAR(1 g) = 0.583 mW/g; SAR(10 g) = 0.444 mW/g
Maximum value of SAR (measured) = 0.604 mW/g



0 dB = 0.604 mW/g = -4.38 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

01 CDMA2000 BC0_RC3 SO55_Right Cheek_Ch1013_2D

DUT: 222301-01

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: HSL_835_120706 Medium parameters used: f = 824.7 MHz; σ = 0.905 mho/m; ε_r = 41.923; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.04, 6.04, 6.04); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.607 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.195 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.717 mW/g
SAR(1 g) = 0.583 mW/g; SAR(10 g) = 0.444 mW/g
Maximum value of SAR (measured) = 0.604 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

02 CDMA2000 BC15_RC3 SO55_Left Cheek_Ch425

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1731.25 MHz;Duty Cycle: 1:1
Medium: HSL_1800_120706 Medium parameters used: f = 1731.25 MHz; σ = 1.363 mho/m; ε_r = 40.888; ρ = 1000 kg/m^3
Ambient Temperature：23.6 ℃; Liquid Temperature：21.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(5.32, 5.32, 5.32); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.696 mW/g

Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.233 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.070 mW/g
SAR(1 g) = 0.684 mW/g; SAR(10 g) = 0.409 mW/g
Maximum value of SAR (measured) = 0.749 mW/g



0 dB = 0.749 mW/g = -2.51 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

02 CDMA2000 BC15_RC3 SO55_Left Cheek_Ch425_2D

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1731.25 MHz;Duty Cycle: 1:1
Medium: HSL_1800_120706 Medium parameters used: f = 1731.25 MHz; σ = 1.363 mho/m; ε_r = 40.888; ρ = 1000 kg/m^3
Ambient Temperature：23.6 ℃; Liquid Temperature：21.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(5.32, 5.32, 5.32); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.696 mW/g

Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.233 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.070 mW/g
SAR(1 g) = 0.684 mW/g; SAR(10 g) = 0.409 mW/g
Maximum value of SAR (measured) = 0.749 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

03 CDMA2000 BC1_RC3 SO55_Left Cheek_Ch25

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: HSL_1900_120706 Medium parameters used: f = 1851.25 MHz; σ = 1.372 mho/m; ε_r = 39.872; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(5.14, 5.14, 5.14); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.454 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.945 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.661 mW/g
SAR(1 g) = 0.424 mW/g; SAR(10 g) = 0.265 mW/g
Maximum value of SAR (measured) = 0.464 mW/g



0 dB = 0.464 mW/g = -6.67 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

03 CDMA2000 BC1_RC3 SO55_Left Cheek_Ch25_2D

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: HSL_1900_120706 Medium parameters used: f = 1851.25 MHz; σ = 1.372 mho/m; ε_r = 39.872; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.6 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(5.14, 5.14, 5.14); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.454 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.945 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.661 mW/g
SAR(1 g) = 0.424 mW/g; SAR(10 g) = 0.265 mW/g
Maximum value of SAR (measured) = 0.464 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

04 802.11b_Right Cheek_Ch11

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: HSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.833 mho/m; ε_r = 39.712; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.52, 4.52, 4.52); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0428 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.827 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.087 mW/g
SAR(1 g) = 0.041 mW/g; SAR(10 g) = 0.020 mW/g
Maximum value of SAR (measured) = 0.0480 mW/g



0 dB = 0.0480 mW/g = -26.38 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

04 802.11b_Right Cheek_Ch11_2D

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: HSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.833 mho/m; ε_r = 39.712; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.52, 4.52, 4.52); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0428 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.827 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.087 mW/g
SAR(1 g) = 0.041 mW/g; SAR(10 g) = 0.020 mW/g
Maximum value of SAR (measured) = 0.0480 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

05 802.11b_Right Tilted_Ch11

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: HSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.833 mho/m; ε_r = 39.712; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.52, 4.52, 4.52); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0166 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.427 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 0.017 mW/g
SAR(1 g) = 0.00929 mW/g; SAR(10 g) = 0.00431 mW/g
Maximum value of SAR (measured) = 0.0105 mW/g



0 dB = 0.0105 mW/g = -39.58 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

06 802.11b_Left Cheek_Ch11

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: HSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.833 mho/m; ε_r = 39.712; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.52, 4.52, 4.52); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0391 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.902 V/m; Power Drift = 0.16 dB
Peak SAR (extrapolated) = 0.106 mW/g
SAR(1 g) = 0.040 mW/g; SAR(10 g) = 0.018 mW/g
Maximum value of SAR (measured) = 0.0445 mW/g



0 dB = 0.0445 mW/g = -27.03 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

07 802.11b_Left Tilted_Ch11

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: HSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.833 mho/m; ε_r = 39.712; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.52, 4.52, 4.52); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0164 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.396 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 0.014 mW/g
SAR(1 g) = 0.009 mW/g; SAR(10 g) = 0.00402 mW/g
Maximum value of SAR (measured) = 0.00993 mW/g



0 dB = 0.00993 mW/g = -40.06 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

08 CDMA2000 BC0_RTAP 153.6_Back_1.0cm_Ch1013

DUT: 222301-01

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 825 MHz; σ = 0.967 mho/m; ε_r = 54.454; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.12 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 32.006 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.440 mW/g
SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.765 mW/g
Maximum value of SAR (measured) = 1.11 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 32.006 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.475 mW/g
SAR(1 g) = 0.813 mW/g; SAR(10 g) = 0.501 mW/g
Maximum value of SAR (measured) = 0.894 mW/g



0 dB = 0.894 mW/g = -0.97 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

09 CDMA2000 BC0_RTAP 153.6_Back_1.0cm_Ch384

DUT: 222301-01

Communication System: CDMA2000; Frequency: 836.52 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 837 MHz; σ = 0.979 mho/m; ε_r = 54.364; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch384/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.21 mW/g

Ch384/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 33.253 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.559 mW/g
SAR(1 g) = 1.16 mW/g; SAR(10 g) = 0.839 mW/g
Maximum value of SAR (measured) = 1.21 mW/g

Ch384/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 33.253 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.663 mW/g
SAR(1 g) = 0.913 mW/g; SAR(10 g) = 0.554 mW/g
Maximum value of SAR (measured) = 1.01 mW/g



0 dB = 1.01 mW/g = 0.09 dB mW/g

09 CDMA2000 BC0_RTAP 153.6_Back_1.0cm_Ch384_2D

DUT: 222301-01

Communication System: CDMA2000; Frequency: 836.52 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 837 MHz; σ = 0.979 mho/m; ε_r = 54.364; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch384/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.21 mW/g

Ch384/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 33.253 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.559 mW/g
SAR(1 g) = 1.16 mW/g; SAR(10 g) = 0.839 mW/g
Maximum value of SAR (measured) = 1.21 mW/g

Ch384/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 33.253 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.663 mW/g
SAR(1 g) = 0.913 mW/g; SAR(10 g) = 0.554 mW/g
Maximum value of SAR (measured) = 1.01 mW/g


1g/10g Averaged SAR
SAR;Zoom Scan:Value Along Z, X=2, Y=2
Markers
mW/g
1.2
1.1
1.0
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0.0
0.005
0.010
0.015
0.020
0.025
0.030
0.035
m

10 CDMA2000 BC0_RTAP 153.6_Back_1.0cm_Ch777

DUT: 222301-01

Communication System: CDMA2000; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 848.31 MHz; σ = 0.989 mho/m; ε_r = 54.264; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch777/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.06 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.775 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 1.370 mW/g
SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.729 mW/g
Maximum value of SAR (measured) = 1.06 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.775 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 1.469 mW/g
SAR(1 g) = 0.811 mW/g; SAR(10 g) = 0.490 mW/g
Maximum value of SAR (measured) = 0.909 mW/g



0 dB = 0.909 mW/g = -0.83 dB mW/g

11 CDMA2000 BC0_RC3 SO32_Back_1.0cm_Ch1013_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 825 MHz; σ = 0.967 mho/m; ε_r = 54.454; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch1013/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.833 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.964 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 1.045 mW/g
SAR(1 g) = 0.756 mW/g; SAR(10 g) = 0.538 mW/g
Maximum value of SAR (measured) = 0.796 mW/g

Ch1013/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.964 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 1.334 mW/g
SAR(1 g) = 0.724 mW/g; SAR(10 g) = 0.416 mW/g
Maximum value of SAR (measured) = 0.802 mW/g



0 dB = 0.802 mW/g = -1.92 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

12 CDMA2000 BC0_RC3 SO32_Back_1.0cm_Ch384_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 836.52 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 837 MHz; σ = 0.979 mho/m; ε_r = 54.364; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch384/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.04 mW/g

Ch384/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.475 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 1.722 mW/g
SAR(1 g) = 0.914 mW/g; SAR(10 g) = 0.507 mW/g
Maximum value of SAR (measured) = 1.03 mW/g

Ch384/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.475 V/m; Power Drift = -0.12 dB
Peak SAR (extrapolated) = 1.078 mW/g
SAR(1 g) = 0.735 mW/g; SAR(10 g) = 0.507 mW/g
Maximum value of SAR (measured) = 0.771 mW/g



0 dB = 0.771 mW/g = -2.26 dB mW/g

13 CDMA2000 BC0_RC3 SO32_Back_1.0cm_Ch777_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 848.31 MHz;Duty Cycle: 1:1
Medium: MSL_835_120706 Medium parameters used: f = 848.31 MHz; σ = 0.989 mho/m; ε_r = 54.264; ρ = 1000 kg/m^3
Ambient Temperature：23.4 ℃; Liquid Temperature：21.4 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch777/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.883 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.776 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.511 mW/g
SAR(1 g) = 0.794 mW/g; SAR(10 g) = 0.435 mW/g
Maximum value of SAR (measured) = 0.895 mW/g

Ch777/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.776 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 0.987 mW/g
SAR(1 g) = 0.638 mW/g; SAR(10 g) = 0.431 mW/g
Maximum value of SAR (measured) = 0.665 mW/g



0 dB = 0.665 mW/g = -3.54 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

14 CDMA2000 BC15_RTAP 153.6_Back_1.0cm_Ch25

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1711.25 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1711.25 MHz; σ = 1.47 mho/m; ε_r = 55.336; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.21 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 12.389 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 1.692 mW/g
SAR(1 g) = 1 mW/g; SAR(10 g) = 0.579 mW/g
Maximum value of SAR (measured) = 1.11 mW/g



0 dB = 1.11 mW/g = 0.91 dB mW/g

15 CDMA2000 BC15_RTAP 153.6_Back_1.0cm_Ch425

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1731.25 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1731.25 MHz; σ = 1.491 mho/m; ε_r = 55.304; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.24 mW/g

Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.685 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 1.783 mW/g
SAR(1 g) = 1.04 mW/g; SAR(10 g) = 0.603 mW/g
Maximum value of SAR (measured) = 1.12 mW/g



0 dB = 1.12 mW/g = 0.98 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

16 CDMA2000 BC15_RTAP 153.6_Back_1.0cm_Ch875

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1753.75 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1754 MHz; σ = 1.516 mho/m; ε_r = 55.266; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.22 mW/g

Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.295 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 1.726 mW/g
SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.590 mW/g
Maximum value of SAR (measured) = 1.08 mW/g



0 dB = 1.08 mW/g = 0.67 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

17 CDMA2000 BC15_RC3 SO32_Back_1.0cm_Ch25_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1711.25 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1711.25 MHz; σ = 1.47 mho/m; ε_r = 55.336; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.25 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.927 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 1.743 mW/g
SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.596 mW/g
Maximum value of SAR (measured) = 1.09 mW/g



0 dB = 1.09 mW/g = 0.75 dB mW/g

18 CDMA2000 BC15_RC3 SO32_Back_1.0cm_Ch425_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1731.25 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1731.25 MHz; σ = 1.491 mho/m; ε_r = 55.304; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.29 mW/g

Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.290 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 1.804 mW/g
SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.613 mW/g
Maximum value of SAR (measured) = 1.13 mW/g



0 dB = 1.13 mW/g = 1.06 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

18 CDMA2000 BC15_RC3 SO32_Back_1.0cm_Ch425_Headset_2D

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1731.25 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1731.25 MHz; σ = 1.491 mho/m; ε_r = 55.304; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch425/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.29 mW/g

Ch425/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 11.290 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 1.804 mW/g
SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.613 mW/g
Maximum value of SAR (measured) = 1.13 mW/g



19 CDMA2000 BC15_RC3 SO32_Back_1.0cm_Ch875_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1753.75 MHz;Duty Cycle: 1:1
Medium: MSL_1800_120706 Medium parameters used: f = 1754 MHz; σ = 1.516 mho/m; ε_r = 55.266; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.87, 4.87, 4.87); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch875/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.23 mW/g

Ch875/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.048 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 1.751 mW/g
SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.591 mW/g
Maximum value of SAR (measured) = 1.08 mW/g



0 dB = 1.08 mW/g = 0.67 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

20 CDMA2000 BC1_RTAP 153.6_Back_1.0cm_Ch25

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1851.25 MHz; σ = 1.461 mho/m; ε_r = 53.588; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.957 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.149 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 1.387 mW/g
SAR(1 g) = 0.812 mW/g; SAR(10 g) = 0.474 mW/g
Maximum value of SAR (measured) = 0.897 mW/g



0 dB = 0.897 mW/g = -0.94 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

21 CDMA2000 BC1_RTAP 153.6_Back_1.0cm_Ch600

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1880 MHz; σ = 1.498 mho/m; ε_r = 53.575; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch600/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.953 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.358 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.460 mW/g
SAR(1 g) = 0.841 mW/g; SAR(10 g) = 0.485 mW/g
Maximum value of SAR (measured) = 0.918 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.358 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.190 mW/g
SAR(1 g) = 0.668 mW/g; SAR(10 g) = 0.391 mW/g
Maximum value of SAR (measured) = 0.762 mW/g



0 dB = 0.762 mW/g = -2.36 dB mW/g

21 CDMA2000 BC1_RTAP 153.6_Back_1.0cm_Ch600_2D

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1880 MHz; σ = 1.498 mho/m; ε_r = 53.575; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch600/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.953 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.358 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.460 mW/g
SAR(1 g) = 0.841 mW/g; SAR(10 g) = 0.485 mW/g
Maximum value of SAR (measured) = 0.918 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.358 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.190 mW/g
SAR(1 g) = 0.668 mW/g; SAR(10 g) = 0.391 mW/g
Maximum value of SAR (measured) = 0.762 mW/g


1g/10g Averaged SAR
SAR;Zoom Scan:Value Along Z, X=2, Y=1
Markers
mW/g
0.0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
0.005
0.010
0.015
0.020
0.025
0.030
0.035
m

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

22 CDMA2000 BC1_RTAP 153.6_Back_1.0cm_Ch1175

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1908.75 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1909 MHz; σ = 1.528 mho/m; ε_r = 53.554; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch1175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.682 mW/g

Ch1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 6.488 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 1.053 mW/g
SAR(1 g) = 0.612 mW/g; SAR(10 g) = 0.358 mW/g
Maximum value of SAR (measured) = 0.672 mW/g



0 dB = 0.672 mW/g = -3.45 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

23 CDMA2000 BC1_RC3 SO32_Back_1.0cm_Ch25_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1851.25 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1851.25 MHz; σ = 1.461 mho/m; ε_r = 53.588; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch25/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.996 mW/g

Ch25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.493 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 1.354 mW/g
SAR(1 g) = 0.796 mW/g; SAR(10 g) = 0.464 mW/g
Maximum value of SAR (measured) = 0.855 mW/g



0 dB = 0.855 mW/g = -1.36 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

24 CDMA2000 BC1_RC3 SO32_Back_1.0cm_Ch600_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1880 MHz; σ = 1.498 mho/m; ε_r = 53.575; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch600/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.968 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.884 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 1.353 mW/g
SAR(1 g) = 0.789 mW/g; SAR(10 g) = 0.467 mW/g
Maximum value of SAR (measured) = 0.864 mW/g

Ch600/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.884 V/m; Power Drift = -0.13 dB
Peak SAR (extrapolated) = 1.136 mW/g
SAR(1 g) = 0.646 mW/g; SAR(10 g) = 0.397 mW/g
Maximum value of SAR (measured) = 0.730 mW/g



0 dB = 0.730 mW/g = -2.73 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 06.07.2012

25 CDMA2000 BC1_RC3 SO32_Back_1.0cm_Ch1175_Headset

DUT: 222301-01

Communication System: CDMA2000; Frequency: 1908.75 MHz;Duty Cycle: 1:1
Medium: MSL_1900_120706 Medium parameters used: f = 1909 MHz; σ = 1.528 mho/m; ε_r = 53.554; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch1175/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.672 mW/g

Ch1175/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.713 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.952 mW/g
SAR(1 g) = 0.576 mW/g; SAR(10 g) = 0.348 mW/g
Maximum value of SAR (measured) = 0.631 mW/g

Ch1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 8.713 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 0.962 mW/g
SAR(1 g) = 0.572 mW/g; SAR(10 g) = 0.344 mW/g
Maximum value of SAR (measured) = 0.630 mW/g



0 dB = 0.630 mW/g = -4.01 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

26 802.11b_Front_1.0cm_Ch11

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: MSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.977 mho/m; ε_r = 53.795; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (71x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0202 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 0.888 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.029 mW/g
SAR(1 g) = 0.012 mW/g; SAR(10 g) = 0.00516 mW/g
Maximum value of SAR (measured) = 0.0145 mW/g



0 dB = 0.0145 mW/g = -36.77 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

27 802.11b_Back_1.0cm_Ch11

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: MSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.977 mho/m; ε_r = 53.795; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0914 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.368 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.172 mW/g
SAR(1 g) = 0.077 mW/g; SAR(10 g) = 0.035 mW/g
Maximum value of SAR (measured) = 0.0862 mW/g



0 dB = 0.0862 mW/g = -21.29 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

27 802.11b_Back_1.0cm_Ch11_2D

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: MSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.977 mho/m; ε_r = 53.795; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0914 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.368 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.172 mW/g
SAR(1 g) = 0.077 mW/g; SAR(10 g) = 0.035 mW/g
Maximum value of SAR (measured) = 0.0862 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

28 802.11b_Right Side_1.0cm_Ch11

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: MSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.977 mho/m; ε_r = 53.795; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (41x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0386 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 2.584 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.077 mW/g
SAR(1 g) = 0.035 mW/g; SAR(10 g) = 0.016 mW/g
Maximum value of SAR (measured) = 0.0394 mW/g



0 dB = 0.0394 mW/g = -28.09 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

29 802.11b_Back_1.0cm_Ch11_Headset

DUT: 222301-01

Communication System: WIFI; Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: MSL_2450_120709 Medium parameters used: f = 2462 MHz; σ = 1.977 mho/m; ε_r = 53.795; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch11/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0893 mW/g

Ch11/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.466 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.153 mW/g
SAR(1 g) = 0.073 mW/g; SAR(10 g) = 0.035 mW/g
Maximum value of SAR (measured) = 0.0844 mW/g



0 dB = 0.0844 mW/g = -21.47 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

30 BT_Back_1.0cm_Ch78

DUT: 222301-01

Communication System: Bluetooth; Frequency: 2480 MHz;Duty Cycle: 1:3.12
Medium: MSL_2450_120709 Medium parameters used: f = 2480 MHz; σ = 2.002 mho/m; ε_r = 53.643; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch78/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0231 mW/g

Ch78/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.623 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.034 mW/g
SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00741 mW/g
Maximum value of SAR (measured) = 0.0182 mW/g



0 dB = 0.0182 mW/g = -34.80 dB mW/g

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 09.07.2012

30 BT_Back_1.0cm_Ch78_2D

DUT: 222301-01

Communication System: Bluetooth; Frequency: 2480 MHz;Duty Cycle: 1:3.12
Medium: MSL_2450_120709 Medium parameters used: f = 2480 MHz; σ = 2.002 mho/m; ε_r = 53.643; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：21.3 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.28, 4.28, 4.28); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

Ch78/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.0231 mW/g

Ch78/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 1.623 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.034 mW/g
SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00741 mW/g
Maximum value of SAR (measured) = 0.0182 mW/g