

FCC RF EXPOSURE REPORT

FCC ID: Q78-ZXHNHS320

Project No. : 1704C225
Equipment : WIRELESS HD IP CAMERA
Model : HS320
Applicant : ZTE Corporation
**Address : ZTE Plaza, Hi-Tech Park, Nanshan District,
Shenzhen, Guangdong, China**

**According: : FCC Guidelines for Human Exposure IEEE
C95.1 & FCC Part 2.1091**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	PCB	N/A	0.87

TEST RESULTS

EUT :	WIRELESS HD IP CAMERA	Model Name :	HS320
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		

2.4G WIFI

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0.87	1.2218	24.50	281.8383	0.06854	1	Complies

Note: the calculated distance is 20 cm.