



FCC Test Report

Test report no.: EMC_471FCC15.247_2003

FCC Part 15.247 for FHSS systems / CANADA RSS-210

Model: (Earlite™ 1100)

FCC ID: Q7R101



TTI-P-G 081/94-A0

Accredited according to **ISO/IEC 17025**



FCC listed # 101450

IC recognized # 3925

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecomusa.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686

Board of Directors: Dr. Harald Ansorge, Dr. Klaus Matkey, Hans Peter May

Table of Contents

1	General information
1.1	Notes
1.2	Testing laboratory
1.3	Details of applicant
1.4	Application details
1.5	Test item
1.6	Test standards
2	Technical test
2.1	Summary of test results
2.2	Test report
1	General information
1.1	Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc USA.

TEST REPORT PREPARED BY:

EMC Engineer: Harpreet Sidhu

1.2 Testing laboratory
CETECOM Inc.
411 Dixon Landing Road, Milpitas, CA-95035, USA
Phone: +1 408 586 6200 Fax: +1 408 586 6299
E-mail: lothar.schmidt@cetecomusa.com
Internet: www.cetecom.com

1.3 Details of applicant

Name : STEP Communications
Street : 625 River Oaks Parkway
City / Zip Code : San Jose / 95134
Country : USA
Contact : Dinesh Chatkara
Telephone : +1 510 673 0899
Tele-fax : +1 775 261 0970
e-mail : dinesh@stepcommunications.com

1.4 Application details

Date of receipt test item : 2003-05-22
Date of test : 2003-05-22/30, 2003-07-15

1.5 Test item

Manufacturer : Windigo Systems
Street Address : 2210 O'Toole Ave #200
City / Zip code : San Jose / 95131
Country : USA
Marketing Name : Earlite™ 1100
Model No. : Earlite™ 1100
Description : [Bluetooth Headset](#)
FCC-ID : Q7R101

Additional information

Frequency : 2402MHz – 2480MHz
Type of modulation : GFSK
Number of channels : 79
Antenna : Embedded
Power supply : Battery (AC adaptor)
HW / SW version : 2.0A / 1.49
Output power : 3.97dBm (2.5mW) conducted peak power
Extreme temp. Tolerance : 0°C-45°C

1.6 Test standards: FCC Part 15 §15.247 (DA00-705) / RSS 210

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

2 Technical test**2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests
Performed

Final Verdict:
(only “passed” if all single measurements are “passed”)

Passed

Technical responsibility for area of testing:

2003-07-24 EMC & Radio

Siegfried Lehmann
(Technical Manager)



Date

Section

Name

Signature

Responsible for test report and project leader:

2003-07-24 EMC & Radio

Harpreet Sidhu (EMC Engineer)



Date

Section

Name

Signature

2.2 Test report

TEST REPORT


**Test report no.: EMC_471FCC15.247_2003
(Model: Earlite™ 1100)**

TEST REPORT REFERENCE

LIST OF MEASUREMENTS		PAGE
CARRIER FREQUENCY SEPERATION	§15.247(a)	7
NUMBER OF HOPPING CHANNELS	§15.247(a)	8
TIME OF OCCUPANCY (DWELL TIME)	§15.247(a)	12
SPECTRUM BANDWIDTH OF FHSS SYSTEM	§15.247(a)	15
POWER SPECTRAL DENSITY	§15.247 (d)	19
MAXIMUM PEAK OUTPUT POWER	§ 15.247 (b) (1)	23
BAND EDGE COMPLIANCE	§15.247 (c)	31
EMISSION LIMITATIONS	§ 15.247 (c) (1)	35
CONDUCTED EMISSIONS	§ 15.107/207	49
RECEIVER SPURIOUS RADIATION	§ 15.209	50
TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS		56
BLOCK DIAGRAMS		57

CARRIER FREQUENCY SEPERATION

§15.247(a)



Date: 30.MAY.2003 09:31:54


NUMBER OF HOPPING CHANNELS

§15.247(a)

The number of hopping channels is 79 (see next 4 plots)


The right red line corresponds to the left red line from the next plot.

Plot 1: Total 23




Date: 22.MAY.2003 10:48:28

Plot 2: Total 25




Date: 22.MAY.2003 10:50:58

Plot 3: Total 20



Date: 22.MAY.2003 10:53:24

Plot 4: Total 11



Date: 22.MAY.2003 10:54:40

TIME OF OCCUPANCY (DWELL TIME)


§15.247(a)

DH1 – Packet

The system makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 79 channels. So you have each channel 10.13 times per second and so for 30 seconds you have 303.9 times of appearance.

Each Tx-time per appearance is 420.84µs.

So we have $303.9 * 420.84\mu s = 127.89ms$ per 30 seconds.



Date: 22.MAY.2003 10:35:23

TIME OF OCCUPANCY (DWELL TIME)


§15.247(a)

DH3 – Packet

A DH3 Packets need 3 time slots for transmit and 1 for receiving, then the system makes worst case 400 hops per second with 79 channels. So you have each channel 5.1 times per second and so for 30 seconds you have 153 times of appearance.

Each Tx-time per appearance is 1.683ms.

So we have $153 * 1.683\text{ms} = 257.5\text{ms}$ per 30 seconds.



Date: 22.MAY.2003 10:39:30

TIME OF OCCUPANCY (DWELL TIME)


§15.247(a)

DH5 – Packet

At DH5 Packets you need 5 time slots for transmit and 1 for receiving, then the system makes worst case 266,7 hops per second with 79 channels. So you have each channel 3.36 times per second and so for 30 seconds you have 100.8 times of appearance.

Each Tx-time per appearance is 2.927ms.

So we have $100.8 * 2.927\text{ms} = 295.04\text{ms}$ per 30 seconds.



Date: 22.MAY.2003 10:43:09

SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth**§15.247(a)**

TEST CONDITIONS		20 dB BANDWIDTH (kHz)		
Frequency (MHz)		2402	2441	2480
$T_{nom}(23)^{\circ}C$	$V_{nom}(0)VDC$	873.75	917.83	873.75


RBW / VBW as provided in the "Measurement Guidelines" (DA 00-705, March 30, 2000)

LIMIT**SUBCLAUSE §15.247(a) (1)****The maximum 20dB bandwidth shall be at maximum 1000 KHz**

SPECTRUM BANDWIDTH OF FHSS SYSTEM 20 dB bandwidth

§15.247(a)

Lowest Channel: 2402MHz




Date: 22.MAY.2003 10:02:05

SPECTRUM BANDWIDTH OF FHSS SYSTEM 20 dB bandwidth

§15.247(a)

Mid Channel: 2441MHz




Date: 22.MAY.2003 10:03:45

SPECTRUM BANDWIDTH OF FHSS SYSTEM
20 dB bandwidth

§15.247(a)

Highest Channel: 2480MHz



Date: 22.MAY.2003 10:05:21

POWER SPECTRAL DENSITY**§15.247 (d)**

TEST CONDITIONS		POWER SPECTRAL DENSITY (dBm)		
Frequency (MHz)		2402	2441	2480
T _{nom} (23)°C	V _{nom} ()VDC	-8.38	-7.56	-9.88

LIMIT**SUBCLAUSE §15.247(d)**


The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band

ANALYZER SETTINGS: RBW=3KHz, VBW=3KHz

POWER SPECTRAL DENSITY

§15.247(d)

Lowest Channel: 2402MHz




Date: 22.MAY.2003 11:08:35

POWER SPECTRAL DENSITY

§15.247(d)

Middle Channel: 2441MHz




Date: 22.MAY.2003 11:09:57

POWER SPECTRAL DENSITY

§15.247(d)

Highest Channel: 2480MHz



Date: 22.MAY.2003 11:11:06

**MAXIMUM PEAK OUTPUT POWER
(conducted)****§ 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
Frequency (MHz)		2402	2441	2480
T _{nom} (23)°C	V _{nom} ()VDC	3.44	3.97	3.49
Measurement uncertainty		±0.5dBm		

RBW / VBW: 3 MHz


LIMIT**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)

Lowest Channel: 2402MHz




Date: 22.MAY.2003 10:07:21

PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)

Mid Channel: 2441MHz




Date: 22.MAY.2003 10:08:20

PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)

Highest Channel: 2480MHz



Date: 22.MAY.2003 10:09:12

**MAXIMUM PEAK OUTPUT POWER
(RADIATED)****§ 15.247 (b) (1)****EIRP:**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
Frequency (MHz)		2402	2441	2480
T _{nom} (23)°C	V _{nom} ()VDC	-7.29	-4.83	-3.51
Measurement uncertainty		±0.5dBm		

RBW/VBW: 3 MHz

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

LIMIT**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

PEAK OUTPUT POWER (RADIATED)


§15.247 (b) (1)

Lowest Channel: 2402MHz

SWEEP TABLE: "EIRP BT low channel"

Short Description: EIRP Bluetooth channel-2402MHz

Start	Stop	Detector	Meas.	IF
Frequency	Frequency		Time	BW
2.397GHz	2.407GHz	MaxPeak	Coupled	3 MHz



PEAK OUTPUT POWER (RADIATED)


§15.247 (b) (1)

Mid Channel: 2441MHz

SWEEP TABLE: "EIRP BT Mid channel"

Short Description: EIRP Bluetooth channel-2441MHz

Start	Stop	Detector	Meas.	IF
Frequency	Frequency		Time	BW
2.436GHz	2.446GHz	MaxPeak	Coupled	3 MHz



PEAK OUTPUT POWER (RADIATED)


§15.247 (b) (1)

Highest Channel: 2480MHz

SWEEP TABLE: "EIRP BT High channel"

Short Description: EIRP Bluetooth channel-2480MHz

Start	Stop	Detector	Meas.	IF
Frequency	Frequency		Time	BW
2.475GHz	2.485GHz	MaxPeak	Coupled	3 MHz



BAND EDGE COMPLIANCE

§15.247 (c)


Low frequency section (spurious in the restricted band 2310 – 2390 MHz)

Average Measurement

(This plot is valid for both Hopping ON & OFF)

Operating condition : Tx at 2402MHz
 SWEEP TABLE : "FCC15.247 LBE_AVG"
 Short Description : FCC15.247 BT Low-band-edge
 Limit Line : 54dBμV

Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.31 GHz	2.412 GHz	MaxPeak	Coupled	1 MHz	10Hz	#326 horn (dBi)



BAND EDGE COMPLIANCE

§15.247 (c)


Low frequency section (spurious in the restricted band 2310 – 2390 MHz)

Peak Measurement

(This plot is valid for both Hopping ON & OFF)

Operating condition : Tx at 2402MHz
 SWEEP TABLE : "FCC15.247 LBE_Pk"
 Short Description : FCC15.247 BT Low-band-edge
 Limit Line : 74dBμV

Start Frequency	Stop Frequency	Detector	Meas. Bandw.	RBW	VBW	Transducer
2.31 GHz	2.412 GHz	MaxPeak	Coupled	1 MHz	1MHz	#326 horn (dBi)



BAND EDGE COMPLIANCE

§15.247 (c)


High frequency section (spurious in the restricted band 2483.5 – 2500 MHz)

Average Measurement

(This plot is valid for both Hopping ON & OFF)

Operating condition : Tx at 2480MHz
SWEEP TABLE : "FCC15.247 HBE_AVG"
Short Description : FCC15.247 BT High-band-edge
Limit Line : 54dBμV

Start	Stop	Detector	Meas.	RBW	VBW	Transducer
Frequency	Frequency	Time	Bandw.			
2.462 GHz	2.5 GHz	MaxPeak	Coupled	1 MHz	10Hz	#326 horn (dBi)



BAND EDGE COMPLIANCE

§15.247 (c)


High frequency section (spurious in the restricted band 2483.5 – 2500 MHz)

Peak Measurement

(This plot is valid for both Hopping ON & OFF)

Operating condition : Tx at 2480MHz
 SWEEP TABLE : "FCC15.247 HBE_PK"
 Short Description : FCC15.247 BT High-band-edge
 Limit Line : 74dBμV

Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.462 GHz	2.5 GHz	MaxPeak	Coupled	1 MHz	1MHz	#326 horn (dBi)



EMISSION LIMITATIONS
Transmitter (Conducted)
LIMITS**§ 15.247 (c) (1)**

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions that fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


NOTE: Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Lowest Channel (2402MHz): 9KHz - 25GHz

NOTE: The peak above the limit line is the carrier frequency.




Date: 30.MAY.2003 09:25:13

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Mid Channel (2441MHz): 9KHz - 25GHz

NOTE: The peak above the limit line is the carrier frequency.




Date: 30.MAY.2003 09:26:28

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Highest Channel (2480MHz): 9KHz - 25GHz

NOTE: The peak above the limit line is the carrier frequency.



Date: 30.MAY.2003 09:28:29

EMISSION LIMITATIONS
Transmitter (Radiated)

§ 15.247 (c) (1)

LIMITS

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions that fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

NOTE:

1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 25 GHz very short cable connections to the antenna was used to minimize the noise level.
2. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.
3. All measurements are done in peak mode unless specified with plots.

Results for the radiated measurements below 30MHz according § 15.33

Frequency	Measured values	Remarks
9KHz – 30MHz	No emissions found, caused by the EUT	This is valid for all the tested channels

EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)**

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

Transmit at Lowest channel Frequency 2402MHz			
Frequency (MHz)	Level (dBµV/m)		
	Peak	Quasi-Peak	Average
Transmit at Middle channel Frequency 2441MHz			
Frequency (MHz)	Level (dBµV/m)		
	Peak	Quasi-Peak	Average
Transmit at Highest channel Frequency 2480MHz			
Frequency (MHz)	Level (dBµV/m)		
	Peak	Quasi-Peak	Average

EMISSION LIMITATIONS - Radiated (Transmitter)


§ 15.247 (c) (1)

30MHz – 1GHz

Note:

1. This plot is valid for low, mid & high channels (worst-case plot)
2. Peaks at 603.44MHz, 675.37MHz and 863.92MHz are ambient signals resulting due to loose cable.

SWEEP TABLE:		"BT Spuri hi 30-1G"			
Short Description:		Bluetooth 30MHz-1GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency		Time	VBW	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186



EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

Lowest Channel (2402MHz): 1GHz – 3GHz

NOTE: The peak above the limit is the carrier frequency.

SWEEP TABLE:

Short Description:

"BT Spuri hi 1-3G"

Bluetooth Spurious 1-3GHz

Start Stop

Detector

Meas.

RBW

Transducer

Frequency

Frequency

Time

Bandw.

VBW

1.0 GHz

3.0 GHz

MaxPeak

Coupled

1 MHz


#326 horn (dBi)

Marker:

2.402805611 GHz

98.2 dBµV/m

Level [dBµV/m]




EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

Lowest Channel (2402MHz): 3GHz – 18GHz

SWEEP TABLE:		"BT Spuri hi 3-18G"			
Short Description:		Bluetooth Spurious 3-18 GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
3.0 GHz	18.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter)
Middle Channel (2441MHz): 1GHz – 3GHz

§ 15.247 (c) (1)

NOTE: The peak above the limit is the carrier frequency.

SWEEP TABLE:		"BT Spuri hi 1-3G"			
Short Description:		Bluetooth Spurious 1-3GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
1.0 GHz	3.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter)

Middle Channel (2441MHz): 3GHz – 18GHz

§ 15.247 (c) (1)

NOTE: The peak above the limit is the carrier frequency.

SWEEP TABLE:		"BT Spuri hi 3-18G"			
Short Description:		Bluetooth Spurious 3-18GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
3.0 GHz	18.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

Highest Channel (2480MHz): 1GHz – 3GHz

NOTE: The peak above the limit is the carrier frequency.

SWEEP TABLE:

"BT Spuri hi 1-3G"

Short Description:

Bluetooth Spurious 1-3GHz

Start Stop

Detector

Meas.

RBW

Transducer

Frequency Frequency

Time

Bandw.

VBW

1.0 GHz 3.0 GHz

MaxPeak

Coupled

1 MHz


#326 horn (dBi)

Marker:

2.482965932 GHz

98.39 dBµV/m


Level [dBµV/m]



EMISSION LIMITATIONS - Radiated (Transmitter)
Highest Channel (2480MHz): 3GHz – 18GHz

§ 15.247 (c) (1)

SWEEP TABLE:		"BT Spuri hi 3-18G"			
Short Description:		Bluetooth Spurious 3-18GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
3.0 GHz	18.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

18GHz – 25GHz

Note: This plot is valid for low, mid & high channels (worst-case plot)

SWEEP TABLE:		"BT Spuri hi 18-25G"			
Short Description:		Bluetooth Spurious 18-25GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
18 GHz	25 GHz	MaxPeak	Coupled	1 MHz	#141 horn (dBi)



CONDUCTED EMISSIONS

§ 15.107/207

Measured with AC/DC power adapter

Power Adapter model: UE06W-060100SPA1

Technical specification: 15.107 / 15.207 (Revised as of August 20, 2002)


Limit

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

ANALYZER SETTINGS: RBW = 10KHz

VBW = 10KHz



Power Adapter model: GW-TR-008X

Technical specification: 15.107 / 15.207 (Revised as of August 20, 2002)

Limit

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50


* Decreases with logarithm of the frequency

ANALYZER SETTINGS: RBW = 10KHz

VBW = 10KHz

MEASUREMENT RESULT: "test_fin QP"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150000	53.00	0.0	66	13.0	L1	GND
0.270000	56.40	0.0	61	4.7	N	GND
0.400000	46.00	0.0	58	11.9	N	GND
0.530000	43.60	0.0	56	12.4	L1	GND
0.665000	42.50	0.0	56	13.5	L1	GND
1.065000	40.80	0.0	56	15.2	L1	GND



RECEIVER SPURIOUS RADIATION**§ 15.209****Limits**

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

NOTE:

1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 25 GHz very short cable connections to the antenna was used to minimize the noise level.
2. All measurements are done in peak mode unless specified with the plots.

RECEIVER SPURIOUS RADIATION

§ 15.209

30MHz – 1GHz


SWEEP TABLE:

"BT Spuri hi 30-1G"

Short Description:

Bluetooth 30MHz-1GHz

Start	Stop	Detector	Meas. Time	RBW	Transducer
Frequency	Frequency			VBW	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186



RECEIVER SPURIOUS RADIATION

1GHz – 3GHz

§ 15.209


SWEEP TABLE:

Short Description:

"BT Spuri hi 1-3G"

Bluetooth Spurious 1-3GHz

Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
1.0 GHz	3.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)



RECEIVER SPURIOUS RADIATION
3GHz – 18GHz

§ 15.209

SWEEP TABLE:

"BT Spuri hi 3-18G"

Short Description:

Bluetooth Spurious 3-18 GHz

Start Stop

Detector

Meas.

RBW

Transducer

Frequency Frequency

Time

Bandw.

VBW


3.0 GHz 18.0 GHz

MaxPeak

Coupled

1 MHz

#326 horn (dBi)




RECEIVER SPURIOUS RADIATION

18GHz – 25GHz


§ 15.209

SWEEP TABLE:		"BT Spuri hi 18-25G"			
Short Description:		Bluetooth Spurious 18-25GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
18.0 GHz	25 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)



TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	ESIB 40	Rohde & Schwarz	100107
02	Spectrum Analyzer	FSEM 30	Rohde & Schwarz	826880/010
03	Biconilog Antenna	3141	EMCO	0005-1186
04	Horn Antenna (700M-18GHz)	SAS-200/571	AH Systems	325
05	Horn Antenna (18-26.5GHz)	3160-09	EMCO	1240
06	2-3GHz Band reject filter	BRM50701	Microtronics	6
07	Pre-Amplifier	TS-ANA	Rohde & Schwarz	--
08	Pre-Amplifier	JS4-00102600	Miteq	00616

BLOCK DIAGRAMS**Conducted Testing**

Radiated Testing

ANECHOIC CHAMBER

