Product Name:	Bluetooth Data Suite
Model Number:	MA-700
Applicant:	MOBILE ACTION TECHNOLOGY INC. 5F., No. 205-3, Sec. 3, Beishin Rd., Shindian City, Taipei, Taiwan
Date of Receipt:	May 05, 2003
Finished date of Test:	May 26, 2003
Applicable Standards:	47 CFR Part 15, Subpart C, 15.247 ANSI C63.4:1992 DA-00-705

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Checked By : Sunyou Chen , Date: 5/29/2003
(Sunyou Chen)

Approved By : J H , Date: 5/29/2003
(Johnson Ho, Director)

NVLAP

Lab Code: 200099-0

TABLE OF CONTENTS

1. DOCUMENT POLICY AND TEST STATEMENT 4
1.1 DOCUMENT POLICY 4
1.2 TEST STATEMENT 4
2. DESCRIPTION OF EUT AND TEST MODE 5
2.1 GENERAL DESCRIPTION OF EUT 5
2.2 DESCRIPTION OF SUPPORT UNIT 6
2.3 DESCRIPTION OF TEST MODE 6
3. DESCRIPTION OF APPLIED STANDARDS 7
4 TECHNICAL CHARACTERISTICS TEST 8
4.1 CONDUCTED EMISSION TEST 8
4.1.1 LIMIT 8
4.1.2 TEST EQUIPMENT 8
4.1.3 TEST SETUP 9
4.1.4 TEST PROCEDURE 9
4.1.5 EUT OPERATING CONDITION 9
4.1.6 TEST RESULT 10
4.2 CHANNEL SEPARATION TEST 11
4.2.1 LIMIT 11
4.2.2 TEST EQUIPMENT 11
4.2.3 TEST SET-UP 11
4.2.4 TEST PROCEDURE 11
4.2.5 EUT OPERATING CONDITION 11
4.2.6 TEST RESULT 12
4.3 QUANTITY OF HOPPING CHANNEL TEST 15
4.3.1 LIMIT 15
4.3.2 TEST EQUIPMENT 15
4.3.3 TEST SET-UP 15
4.3.4 TEST PROCEDURE 15
4.3.5 EUT OPERATING CONDITION 15
4.3.6 TEST RESULT 16
4.4 TIME OF OCCUPANCY (DWELL TIME) 17
4.4.1 LIMIT 17
4.4.2 TEST EQUIPMENT 17
4.4.3 TEST SET-UP 17
4.4.4 TEST PROCEDURE 17
4.4.5 EUT OPERATING CONDITION 17
4.4.6 TEST RESULT 18
4.5 PEAK POWER TEST 20
4.5.1 LIMIT 20
4.5.2 TEST EQUIPMENT 20

4.5.3 TEST SET-UP 21
4.5.4 TEST PROCEDURE 21
4.5.5 EUT OPERATING CONDITION 21
4.5.6 TEST RESULT 21
4.6 BAND EDGE TEST 25
4.6.1 LIMIT 25
4.6.2 TEST EQUIPMENT 25
4.6.3 TEST SET-UP 26
4.6.4 TEST PROCEDURE 27
4.6.5 EUT OPERATING CONDITION 27
4.6.6 TEST RESULT 27
4.7 SPURIOUS RADIATED EMISSION TEST 29
4.7.1 LIMIT 29
4.7.2 TEST EQUIPMENT 30
4.7.3 TEST SET-UP 31
4.7.4 TEST PROCEDURE 32
4.7.5 EUT OPERATING CONDITION 32
4.7.6 TEST RESULT 33
5. ANTENNA APPLICATION 37
5.1 ANTENNA REQUIREMENT 37
5.2 RESULT 37
6. PHOTOS OF TESTING 38
7. TERMS OF ABRIVATION 40

1. DOCUMENT POLICY AND TEST STATEMENT

1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.

1.2 TEST STATEMENT

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- AC power source, 120 VAC/60 Hz, was used during the test.

2. DESCRIPTION OF EUT AND TEST MODE

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth Data Suite
MODEL NO.	MA-700
POWER SUPPLY	5Vdc from USB port of PC system
CABLE	N/A
I/O PORT	USB interface
FREQUENCY BAND	2.402~2.4835GHz
CARRIER FREQUENCY	CH0: 2402MHz~CH78: 2480MHz
NUMBER OF CHANNEL	79
CHANNEL SPACING	1MHz
RATED RF OUTPUT POWER	+2dBm
I.F. & L.O.	I.F.: 0MHz, L.O.:2402~2480MHz
MODULATION TYPE	GFSK
BIT RATE OF TRANSMISSION	1Mbps
ANTENNA TYPE	Integrated antenna
ANTENNA GAIN	+0.5 dBi

NOTE： For more detailed features, please refer to the manufacturer' s specification or User' s Manual of EUT.

2.2 DESCRIPTION OF SUPPORT UNIT

The transmitter part of EUT was tested with a PC system and configured by the requirement of ANSI C63.4. All interface ports were connected to the appropriate support units via specific cables. The support units and cables are listed below.

NO	DEVICE	BRAND	MODEL #	FCC ID / DOC	CABLE
1.	Notebook	DELL	PP01L/ 3F438A01	DOC	1.8m unshielded AC power cable 1.8m unshielded DC power cable
2	PRINTER	EPSON	P310B	DOC	1.5m unshielded power cord 1.2m shielded data cable
3	MODEM	DATATRONICS	1200CK	E2050V1200CK	1.5m unshielded DC power cable 1.2m shielded data cable

NOTE ： For the actual test configuration, please refer to the photos of testing.

2.3 DESCRIPTION OF TEST MODE

79 channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency(MHz)
0	2402
39	2441
78	2480

NOTE ：

1. Below 1 GHz, the channel 0, 39, and 78 were pre-tested in chamber. The channel 78, worst case one, was chosen for conducted and radiated emission test.
2. Above 1 GHz, the channel 0, 39 and 78 were tested individually

3. DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and to be connected with a PC system for normal use. According to the specifications provided by the applicant, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C, 15.247

ANSI C63.4:1992

DA-00-705

All tests have been performed and recorded as the above standards.

4 TECHNICAL CHARACTERISTICS TEST

4.1 CONDUCTED EMISSION TEST

4.1.1 LIMIT

Frequency (MHz)	Class A (dBμV)		Class B (dBμV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE：

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST EQUIPMENT

The following test equipment was used for the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 kHz TO 30 MHz	ROHDE & SCHWARZ	ESHS30/ 826003/008	JUL. 2003 R&S
LISN (for EUT)	50 μH, 50 ohm	SOLAR ELECTRONICS	8012-50-R-24-BNC / 924839	JUN. 2003 ETC
LISN (for Peripheral)	50μH, 50 ohm	SOLAR ELECTRONICS	9252-50-R-24-BNC / 951318	JUN. 2003 ETC
50 ohm TERMINATOR	50 ohm	HP	11593A/ 2	JUN. 2003 ETC
COAXIAL CABLE	3m	SUNCITY	J400/ 3M	JUL. 2003 SRT
ISOLATION TRANSFORMER	N/A	APC	AFC-11015/ F102040016	N/A
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 771	N/A
GROUND PLANE	2.3M (H) x 2.4M (W)	SRT	N/A	APR. 2004 SRT
GROUND PLANE	2.4M (H) x 2.4M (W)	SRT	N/A	APR. 2004 SRT

NOTE： The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.1.3 TEST SETUP



NOTE:

1. The EUT was put on a wooden table with 0.8m height above ground plane, and 0.4m away from reference ground plane (> 2mx2m).
2. For the actual test configuration, please refer to the photos of testing.
3. The serial no. of the LISN connected to EUT is 951318.
4. The serial no. of the LISN connected to support units is 924839.

4.1.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm/50µH as specified. All readings were quasi-peak and average values with 10 kHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. Both lines of the power mains of EUT were measured and the cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

4.1.5 EUT OPERATING CONDITION

Set the EUT under transmission condition continuously at a specific channel frequency.

Under Windows XP ran “EMI TEST” program, PC sent "H" pattern or accessed the following peripherals：

- RS232 (modem)
- Printer
- FDD
- HDD

4.1.6 TEST RESULT

Temperature:	25 °C	Humidity:	55 %RH
Ferquency Range:	0.15 – 30 MHz	Test Mode:	CH78
Receiver Detector:	Q.P. and AV.	Tested By:	Chris Hsieh

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dBμV)		Emission Level (dBμV)		Limit (dBμV)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.177	0.20	44.4	41.5	44.6	41.7	64.6	54.6	-20.0	-12.9
0.298	0.20	28.0	25.8	28.2	26.0	60.3	50.3	-32.1	-24.3
3.845	0.28	30.2	29.1	30.5	29.4	56.0	46.0	-25.5	-16.6
4.314	0.30	24.7	21.7	25.0	22.0	56.0	46.0	-31.0	-24.0
15.084	0.50	23.3	20.5	23.8	21.0	60.0	50.0	-36.2	-29.0
18.877	0.58	26.0	23.1	26.6	23.7	60.0	50.0	-33.4	-26.3

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dBμV)		Emission Level (dBμV)		Limit (dBμV)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.173	0.20	44.5	41.5	44.7	41.7	64.8	54.8	-20.1	-13.1
0.470	0.20	26.3	22.8	26.5	23.0	56.5	46.5	-30.0	-23.5
3.611	0.26	30.3	19.7	30.6	20.0	56.0	46.0	-25.4	-26.0
4.197	0.30	24.6	16.7	24.9	17.0	56.0	46.0	-31.1	-29.0
15.435	0.51	25.5	17.8	26.0	18.3	60.0	50.0	-34.0	-31.7
22.463	0.65	30.9	27.4	31.5	28.0	60.0	50.0	-28.5	-22.0

NOTE :

1. Measurement uncertainty is less than 2dB
2. Emission level = Reading valus + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. "*": Measurement does not apply for this frequency.
5. Margin value = Emission level - Limit
6. The emission of other frequencies were very low against the limit.
7. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

4.2 CHANNEL SEPARATION TEST

4.2.1 LIMIT

FCC Part15, Subpart C Section 15.247(a)(1) . Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

FREQUENCY RANGE (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz

4.2.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test：

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2004 R & S

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.2.3 TEST SET-UP

The EUT was connected to a spectrum through a 50Ω RF cable.

4.2.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.
Printed out the test result from the spectrum by hard copy function.

4.2.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.2.6 TEST RESULT

Temperature:	25°C	Humidity:	50%RH
Spectrum Detector:	PK	Tested by	Chris Hsieh
Test Result	PASS		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	SEPARATION READ VALUE (kHz)	SEPARATION LIMIT (kHz)
0	2402	1000.000	>25kHz
39	2441	1000.000	>25kHz
78	2480	1000.000	>25kHz

CH0:



CH39:


*RBW 100 kHz
*VBW 100 kHz
*SWT 100 ms
Delta 2 [T1]
0.01 dB
1.000000000 MHz
Ref 10 dBm
*Att 20 dB
10 Offset 1.2 dB
Marker 1 [T1]
1.66 dBm
1 PK
VIEW
LVL
Center 2.4405 GHz
200 kHz/
Span 2 MHz
Date: 5.AUG.2003 18:36:36

CH78:


*RBW 100 kHz
*VBW 100 kHz
*SWT 100 ms
Delta 2 [T1]
-0.03 dB
1.000000000 MHz
Ref 10 dBm
*Att 20 dB
10 Offset 1.2 dB
Marker 1 [T1]
1.62 dBm
1 PK
VIEW
LVL
Center 2.4795 GHz
200 kHz/
Span 2 MHz
Date: 5.AUG.2003 18:34:47

4.3 QUANTITY OF HOPPING CHANNEL TEST

4.3.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	Limit (Quantity of Hopping Channel)			
	20dB bandwidth <250kHZ	20dB bandwidth >250kHZ	20dB bandwidth <1MHz	20dB bandwidth >1MHz
902-928	50	25	NA	NA
2400-2483.5	NA	NA	75	15
5725-5850	NA	NA	75	NA

4.3.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2004 R & S

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST SET-UP

The EUT was connected to a spectrum through a 50Ω RF cable.

4.3.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.
Printed out the test result from the spectrum by hard copy function.

4.3.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.3.6 TEST RESULT

Temperature:	25°C	Humidity:	50%RH
Spectrum Detector:	PK	Tested by	Chris Hsieh
Test Result	PASS		

HOPPING CHANNEL FREQUENCY RANGE	QUANTITY OF HOPPING CHANNEL READ VALUE	QUANTITY OF HOPPING CHANNEL LIMIT
2402~2480	79	75

CH0-CH78



4.4 Time of occupancy (Dwell Time)

4.4.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	LIMIT (ms)		
	20dB bandwidth <250kHZ(50Channel)	20dB bandwidth >250kHZ(25Channel)	20dB bandwidth <1MHz(75Channel)
902-928	400(20s)	400(10s)	NA
2400-2483.5	NA	NA	400(30s)
5725-5850	NA	NA	400(30s)

NOTE: The “ ()” is all channel’ s average time of occupancy.

4.4.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2004 R & S

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

4.4.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.
Printed out the test result from the spectrum by hard copy function.

4.4.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.4.6 TEST RESULT

Temperature:	25°C	Humidity:	50%RH
Spectrum Detector:	PK	Tested by	Chris Hsieh
Test Result	PASS		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	Average time of occupancy READ VALUE (ms)	Average time of occupancy LIMIT (ms)
0	2402.00	1.272	400
39	2441.00	1.244	400
78	2480.00	1.260	400

CH0:



Ch39:


RBW 100 kHz
*VBW 100 kHz
SWT 2 ms
Delta 2 [T1]
2.06 dB
1.244000 ms
Ref 10 dBm
*Att 20 dB
10 Offset 1.2 dB
Marker 1 [T1]
-78.42 dBm
1 AP
VIEW
SGL
LVL
Center 2.441 GHz
200 µs/

CH78:


RBW 100 kHz
*VBW 100 kHz
SWT 2 ms
Delta 2 [T1]
-1.90 dB
1.260000 ms
Ref 10 dBm
*Att 20 dB
10 Offset 1.2 dB
Marker 1 [T1]
-77.29 dBm
1 AP
VIEW
SGL
LVL
Center 2.48 GHz
200 µs/

4.5 PEAK POWER TEST

4.5.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	LIMIT (W)				
	Quantity of Hopping Channel	50	25	15	75
902-928		1(30dBm)	0.125(21dBm)	NA	NA
2400-2483.5		NA	NA	0.125(21dBm)	1(30dBm)
5725-5850		NA	NA	NA	1(30dBm)

4.5.2 TEST EQUIPMENT

The following test equipment was used during the test：

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2004 R & S
POWER METER	N/A	BOONTON	4232A/ 29001	MAY 2003 ETC
POWER SENSOR	DC-18GHz 0.3μW-100mW 50Ω	BOONTON	51011-EMC/ 31184	JUN. 2003 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

4.5.4 TEST PROCEDURE

The EUT was operating in hopping mode or could control its channel.
Printed out the test result from the spectrum by hard copy function.
Recorded the read value of the power meter.

4.5.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.5.6 TEST RESULT

Temperature:	25°C	Humidity:	50%RH
Spectrum Detector:	PK	Tested by	Chris Hsieh
Test Result	PASS		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)
0	2402.00	2.6	30
39	2441.00	2.2	30
78	2480.00	2.1	30

CH0:


Ref 18.2 dBm
Att 20 dB
Offset 1.2 dB
RBW 1 MHz
VBW 1 MHz
SWT 100 ms
Marker 1 [T1]
2.50 dBm
2.402000000 GHz
1 PK
VIEW
LVL
Center 2.402 GHz
1 MHz/
Span 10 MHz
Tx Channel
Bandwidth
9 MHz
Power
3.64 dBm

CH39:


Ref 10.2 dBm
*Att 20 dB
*RBW 1 MHz
*VBW 1 MHz
*SWT 100 ms
Marker 1 [T1]
1.54 dBm
2.441000000 GHz
Offset 1.2 dB
1 PK
VIEW
LVL
Center 2.441 GHz
1 MHz/
Span 10 MHz
Tx Channel
Bandwidth
9 MHz
Power
2.61 dBm

CH78:


Ref 10.2 dBm
*Att 20 dB
Offset 1.2 dB
*RBW 1 MHz
*VBW 1 MHz
*SWT 100 ms
Marker 1 [T1]
1.38 dBm
2.480000000 GHz
1 PK
VIEW
LVL
Center 2.48 GHz
1 MHz/
Span 10 MHz
Tx Channel
Bandwidth
9 MHz
Power
2.47 dBm

4.6 BAND EDGE TEST

4.6.1 LIMIT

FCC Part15, Subpart C Section 15.247. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

OPERATING FREQUENCY RANGE (MHz)	SPURIOUS EMISSION FREQUENCY (MHz)	LIMIT	
		Peak power ration to emission(dBc)	Emission level(dBuV/m)
902-928	<902	>20	NA
	>928	>20	NA
	960-1240	NA	54
2400-2483.5	<2400	>20	NA
	>2483.5-2500	NA	54
5725-5850	<5350-5460	NA	54
	<5725	>20	NA
	>5850	>20	NA

4.6.2 TEST EQUIPMENT

The following test equipment was used during the test：

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR.2004 R & S
SPECTRUM	9KHz-26.5GHz	HP	8953E/ 3710A03220	MAY 2003 ETC
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB	HP	8449B/ 3008A01019	DEC.2003 ETC
HORN ANTENNA	1GHz to 18GHz	EMCO	3115/ 9602-4681	DEC.2003 ETC
OATS	3 - 10 M measurement	SRT	SRT-1	MAY 2003

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST SET-UP

FOR RF CONDUCTED TEST (dBc)



The EUT was connected to the spectrum through a 50Ω RF cable.

FOR RADIATED EMISSION TEST



NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.

4.6.4 TEST PROCEDURE

1. The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.
2. The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

4.6.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.6.6 TEST RESULT

Temperature:	25°C	Humidity:	60%RH
Spectrum Detector:	PK & AV	Tested by	Chris Hsieh
Test Result	PASS		

1.Conducted test

Frequency (MHz)	PEAK POWER OUTPUT (dBm)	Emission read Value(dBm)	Result of Band edge (dBc)	Band edge LIMIT (dBc)
<2400	2.64	-29.51	32.15	>20dBc
>2483.5	1.53	-34.19	35.72	>20dBc

2.Radiated emision test

Frequency (MHz)	Antenna polarization (H/V)	PEAK POWER OUTPUT (dBuV/m)	Emission read Value(dBuV/m)	Band edge LIMIT (dBuV/m)
<2400	V	56.5	37.0	54
>2483.5	V	57.7	35.5	54

<2400MHz:



>2483.5MHz



4.7 SPURIOUS RADIATED EMISSION TEST

4.7.1 LIMIT

FCC Part15, Subpart C Section 15.209 limit of radiated emission for frequency below1000MHz. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (dBmV/m)
30 - 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

NOTE : 1. In the emission tables above , the tighter limit applies at the band edges.
2. Distance refers to the distance between measuring instrument , antenna , and the closest point of any part of the device or system.

FCC Part 15, Section15.35(b) limit of radiated emission for frequency above 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

FUNDAMENTAL FREQUENCY (MHz)	FILED STRENGTH OF FUNDAMENTAL (dBuV/m) (at 3m)		FIELD STRENGTH OF HARMONICS (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
902-928	114	94	74.0	54.0
2400-2483.5	114	94	74.0	54.0
5725-5875	114	94	74.0	54.0
24000-24250	128	108	88	68

4.7.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test：

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 kHz TO 2750 MHz	ROHDE & SCHWARZ	ESCS30/ 830245/012	AUG. 2003 R&S
SPECTRUM	9KHz-26.5GHz	HP	8953E/ 3710A03220	MAY. 2003 ETC
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB	HP	8449B/ 3008A01019	DEC. 2003 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/9701-1124	JUL. 2003 ETC
HORN ANTENNA	1GHz to 18GHz	EMCO	3115/ 9602-4681	DEC. 2003 ETC
OATS	3 - 10 M measurement	SRT	SRT-1	APR. 2004 SRT

NOTE:

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.
2. The Open Area Test Site (SRT-1) is registered by FCC with No. 90957 and VCCI with No. R-1081.
3. The Open Area Test Site (SRT-2) is registered by FCC with No. 98458 and VCCI with No. R-1168.

4.7.3 TEST SET-UP



NOTE :

3. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
4. For the actual test configuration, please refer to the photos of testing.

4.7.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

4.7.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.7.6 TEST RESULT

Temperature:	25°C	Humidity:	50%RH
Ferquency Range:	30 – 1000 MHz	Test mode:	CH78
Receiver Detector:	Q.P. or AV.	Measured Distance:	3m
Tested by:	Chris Hsieh		

Antenna Polarization：Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	EL(m)	AZ(°)
85.6640	1.10	8.20	21.5	30.8	40.0	-9.2	183.6	2.6
141.6640	1.42	8.43	22.5	32.3	43.5	-11.2	163.3	2.6
282.5611	1.92	13.82	26.3	42.0	46.0	-4.0	224.6	2.3
433.6629	2.57	16.70	23.6	42.9	46.0	-3.1	188.6	2.0
566.8210	3.27	19.68	18.3	41.3	46.0	-4.7	192.6	1.9
701.0058	2.73	21.70	14.5	38.9	46.0	-7.1	180.0	1.8

Antenna Polarization：Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	EL(m)	AZ(°)
65.8200	1.02	8.35	22.5	31.9	40.0	-8.1	200.0	1.2
114.9932	1.29	8.42	27.5	37.2	43.5	-6.3	230.0	1.0
138.6200	1.40	8.36	26.8	36.6	43.5	-6.9	185.6	1.6
357.1192	2.23	15.53	22.1	39.9	46.0	-6.2	159.2	1.8
401.2300	2.70	16.31	20.5	39.5	46.0	-6.5	144.6	2.0
433.6628	2.57	16.70	21.2	40.5	46.0	-5.5	176.2	2.0

NOTE : 1. Measurement uncertainty is less than +/-4dB
2. "*": Measurement does not apply for this frequency.
3. Emissiom Level = Reading Value + Ant. Factor + Cable Loss
4. The field strength of other emission frequencies were very low against the limit.

Temperature:	23°C	Humidity:	50%RH
Ferquency Range:	1 – 25 GHz	Test mode:	Ch0
Receiver Detector:	PK. or AV.	Measured Distance:	3m
Tested by:	Chris Hsieh		

Antenna Polarization：Horizontal

Freq./MHz	Cable Loss (dB)	Ant. Fact. (dB)	Reading (dBuV)		Emission (dBuV/m)		Limit Line (dBuV/m)		Margin (dBuV/m)		AZ (o)	EL (m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2402.00(F)	-32.16	28.54	90.8	57.0	87.1	53.4	N/A	N/A	N/A	N/A	33	1.78
2432.80	-32.21	28.06	44.8	*	40.7	*	74.0	54.0	-33.3	*	33	1.78
4804.00	-30.46	33.63	46.7	*	49.8	*	74.0	54.0	-24.2	*	0	1.2
7206.00	-28.94	36.28	48.3	*	55.6	*	74.0	54.0	-18.4	*	0	1.2

Antenna Polarization：Vertical

Freq/MHz	Cable Loss (dB)	Ant. Fact. (dB)	Reading (dBuV)		Emission (dBuV/m)		Limit Line (dBuV/m)		Margin (dBuV/m)		AZ (o)	EL (m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2402.00(F)	-32.16	28.00	92.1	60.7	88.0	56.5	N/A	N/A	N/A	N/A	352	1.8
2417.90	-32.19	28.03	46.9	*	42.7	*	74.0	54.0	-31.3	*	352	1.8
4804.00	-30.46	33.63	46.3	*	49.4	*	74.0	54.0	-24.6	*	0	1.2
7206.00	-28.88	36.25	48.4	*	55.8	*	74.0	54.0	-18.2	*	0	1.2

NOTE : 1. Measurement uncertainty is less than +/-4dB
2. "*": Measurement does not apply for this frequency.
3. Emissiom Level = Reading Value + Ant. Factor + Cable Loss
4. The field strength of other emission frequencies were very low against the limit.
5.(F):The field stregth of fundamental frequency.

Temperature:	23°C	Humidity:	50%RH
Ferquency Range:	1 – 25 GHz	Test mode:	Ch39
Receiver Detector:	PK. or AV.	Measured Distance:	3m
Tested by:	Chris Hsieh		

Antenna Polarization：Horizontal

Freq./MHz	Cable Loss (dB)	Ant. Fact. (dB)	Reading (dBuV)		Emission (dBuV/m)		Limit Line (dBuV/m)		Margin (dBuV/m)		AZ (o)	EL (m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2441.00(F)	-32.22	28.62	89.2	62.1	85.6	58.5	N/A	N/A	N/A	N/A	40.2	1.75
2416.00	-32.19	28.03	45.5	*	41.4	*	74.0	54.0	-32.6	*	40.2	1.78
4882.00	-30.27	33.70	45.2	*	48.7	*	74.0	54.0	-25.3	*	0	1.2
7323.00	-29.05	36.36	48.5	*	55.8	*	74.0	54.0	-18.2	*	0	1.2

Antenna Polarization：Vertical

Freq./MHz	Cable Loss (dB)	Ant. Fact. (dB)	Reading (dBuV)		Emission (dBuV/m)		Limit Line (dBuV/m)		Margin (dBuV/m)		AZ (o)	EL (m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2441.00	-32.22	28.08	93.2	60.3	89.0	56.2	N/A	N/A	N/A	N/A	353	1.13
2390.19	-32.20	27.98	47.2	*	43.0	*	74.0	54.0	-31.0	*	0	1.2
4882.00	-30.26	33.71	44.9	*	48.4	*	74.0	54.0	-25.6	*	0	1.2
7323.00	-29.04	36.36	47.9	*	55.2	*	74.0	54.0	-18.8	*	0	1.2

NOTE : 1. Measurement uncertainty is less than +/-4dB
2. "*": Measurement does not apply for this frequency.
3. Emissiom Level = Reading Value + Ant. Factor + Cable Loss
4. The field strength of other emission frequencies were very low against the limit.
5.(F):The field stregth of fundamental frquency.

Temperature:	23°C	Humidity:	50%RH
Ferquency Range:	1 – 25GHz	Test mode:	Ch78
Receiver Detector:	PK. or AV.	Measured Distance:	3m
Tested by:	Chris Hsieh		

Antenna Polarization：Horizontal

Freq./MHz	Cable Loss (dB)	Ant. Fact. (dB)	Reading (dBuV)		Emission (dBuV/m)		Limit Line (dBuV/m)		Margin (dBuV/m)		AZ (o)	EL (m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2480.00(F)	-32.19	28.73	88.4	60.5	84.9	57.0	N/A	N/A	N/A	N/A	40.2	1.7
2483.50	-32.19	28.17	49.9	*	45.9	*	74.0	54.0	-28.1	*	40.2	1.78
4960.00	-30.26	33.77	43.4	*	46.9	*	74.0	54.0	-27.1	*	40	1.7
7440.00	-28.95	36.46	47.6	*	55.1	*	74.0	54.0	-18.9	*	40	1.7

Antenna Polarization：Vertical

Freq./MHz	Cable Loss (dB)	Ant. Fact. (dB)	Reading (dBuV)		Emission (dBuV/m)		Limit Line (dBuV/m)		Margin (dBuV/m)		AZ (o)	EL (m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2480.00(F)	-32.19	28.16	91.0	61.7	86.9	57.7	N/A	N/A	N/A	N/A	353	1.1
2483.50	-32.19	28.17	51.5	39.5	47.5	35.5	74.0	54.0	-26.5	-18.5	0	1.2
4960.00	-30.26	33.77	45.2	*	48.7	*	74.0	54.0	-25.3	*	0	1.2
7440.00	-28.95	36.46	48.3	*	55.8	*	74.0	54.0	-18.2	*	0	1.75

NOTE : 1. Measurement uncertainty is less than +/- 4dB
2. "*": Measurement does not apply for this frequency.
3. Emissiom Level = Reading Value + Ant. Factor + Cable Loss
4. The field strength of other emission frequencies were very low against the limit.
5.(F):The field stregth of fundamental frquency.

5. Antenna application

5.1 Antenna requirement

The EUT' s antenna is met the requirement of FCC part15C section15.203 and 15.204.

FCC part15C section15.247 requirement:
Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

5.2 Result

The EUT' s antenna used a dipole antenna and integrated on PCB. The antenna' s gain is 2dBi and meets the requirement.

6. PHOTOS OF TESTING

- Conducted test



- Radiated test



7. TERMS OF ABRIVATION

AV.	Average detection
AZ(°)	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction