

5.4 PEAK POWER EXCURSION MEASUREMENT

5.4.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

Frequency Band	Limit
5.15 – 5.25 GHz	13dB
5.25 – 5.35 GHz	13dB
5.725 – 5.825 GHz	13dB

5.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
SPECTRUM ANALYZER	8564EC	4208A00660	Nov. 20, 2003

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.4.3 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set the spectrum bandwidth span to view the entire spectrum.
3. Using peak detector and Max-hold function for Trace 1 (RB=1MHz, VB=3MHz) and 2 (RB=1MHz, VB=300KHz).
4. The largest difference between Trace 1 and Trace 2 in any 1MHz band on any frequency was recorded.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.




5.4.7 TEST RESULTS


EUT	Dual-Band A+G Wireless Network PCI Adapter v1.1	MODEL	WMP55AG v1.1
MODE	Normal	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	27deg. C, 62%RH, 991hPa	TESTED BY	Ansen Lei

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
1	5180	6.92	13	PASS
4	5240	5.64	13	PASS
5	5260	6.13	13	PASS
8	5320	7.52	13	PASS
9	5745	6.20	13	PASS
12	5805	6.45	13	PASS

CHANNEL 1




CHANNEL 4







CHANNEL 5




CHANNEL 8



CHANNEL 9



CHANNEL 12






EUT	Dual-Band A+G Wireless Network PCI Adapter v1.1	MODEL	WMP55AG v1.1
MODE	Turbo	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	27deg. C, 62%RH, 991hPa	TESTED BY	Ansen Lei


CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
1	5210	7.10	13	PASS
2	5250	8.31	13	PASS
3	5290	6.36	13	PASS
4	5760	6.79	13	PASS
5	5800	6.99	13	PASS

CHANNEL 1






CHANNEL 2




CHANNEL 3





CHANNEL 4



*RBW 1 MHz
 *VBW 300 kHz
 *Att 30 dB
 *Offset 1.2 dB
 *Delta 2 [T1] 6.99 dB
 *Delta 2 [T1] 0.00000000 Hz
 *TH -77.6 dBm
 *Span 60 MHz
 *Center 5.8 GHz
 *Marker 1 [T2] -4.05 dBm
 *SWT 20 ms

1 PK VIEW
 2 SA * MAXH



5.5 PEAK POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

Frequency Band	Limit
5.15 – 5.25GHz	4dBm
5.25 – 5.35GHz	11dBm
5.725 – 5.825GHz	17dBm

5.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
SPECTRUM ANALYZER	8564EC	4208A00660	Nov. 20, 2003

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.5.3 TEST PROCEDURES

1. The transmitter output was connected to the spectrum analyzer.
2. Set RBW=1MHz, VBW=3MHz. The PPSD is the highest level found across the emission in any 1MHz band.

5.5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5.5 TEST SETUP



5.5.6 EUT OPERATING CONDITIONS

Same as 5.3.6




5.5.7 TEST RESULTS


EUT	Dual-Band A+G Wireless Network PCI Adapter v1.1	MODEL	WMP55AG v1.1
MODE	Normal	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	27deg. C, 62%RH, 991hPa	TESTED BY	Ansen Lei

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 1MHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	5180	-2.31	4	PASS
4	5240	-1.25	4	PASS
5	5260	-1.84	11	PASS
8	5320	-1.86	11	PASS
9	5745	-2.00	17	PASS
12	5805	-3.20	17	PASS


CHANNEL 1




CHANNEL 4




CHANNEL 5




CHANNEL 8



CHANNEL 9



CHANNEL 12







EUT	Dual-Band A+G Wireless Network PCI Adapter v1.1	MODEL	WMP55AG v1.1
MODE	Turbo	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	27deg. C, 62%RH, 991hPa	TESTED BY	Ansen Lei

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 1 MHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	5210	-4.88	4	PASS
2	5250	-5.32	4	PASS
3	5290	-4.72	11	PASS
4	5760	-4.82	17	PASS
5	5800	-5.60	17	PASS


CHANNEL 1




CHANNEL 2



CHANNEL 3



CHANNEL 4



CHANNEL 5

