FCC ID: Q87-WMPGV41

FCC TEST REPORT

REPORT NO.: RF940919L07
MODEL NO.: WMP54G ver. 4.1
RECEIVED: Sep. 19, 2005
TESTED: Sep. 19 ~ Sep. 22, 2005
ISSUED: Sep. 23, 2005

APPLICANT: Cisco-Linksys LLC

ADDRESS: 121 Theory Drive, Irvine, CA 92617 (USA)

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 63 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.

No. 2177-01

0528
ILAC MRA

Table of Contents

1. CERTIFICATION 4
2. SUMMARY OF TEST RESULTS 5
2.1 MEASUREMENT UNCERTAINTY 5
3. GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST 7
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 10
3.4 DESCRIPTION OF SUPPORT UNITS 10
4. TEST TYPES AND RESULTS 11
4.1 CONDUCTED EMISSION MEASUREMENT 11
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 11
4.1.2 TEST INSTRUMENTS 11
4.1.3 TEST PROCEDURES 12
4.1.4 DEVIATION FROM TEST STANDARD 12
4.1.5 TEST SETUP 13
4.1.6 EUT OPERATING CONDITIONS 13
4.1.7 TEST RESULTS 14
4.2 RADIATED EMISSION MEASUREMENT 20
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 20
4.2.2 TEST INSTRUMENTS 21
4.2.3 TEST PROCEDURES 22
4.2.4 DEVIATION FROM TEST STANDARD 22
4.2.5 TEST SETUP 23
4.2.6 EUT OPERATING CONDITIONS 23
4.2.7 TEST RESULTS 24
4.3 6DB BANDWIDTH MEASUREMENT 31
4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 31
4.3.2 TEST INSTRUMENTS 31
4.3.3 TEST PROCEDURE 32
4.3.4 DEVIATION FROM TEST STANDARD 32
4.3.5 TEST SETUP 32
4.3.6 EUT OPERATING CONDITIONS 32
4.3.7 TEST RESULTS 33
4.4 MAXIMUM PEAK OUTPUT POWER 39
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 39
4.4.2 INSTRUMENTS 39
4.4.3 TEST PROCEDURES 40
4.4.4 DEVIATION FROM TEST STANDARD 40

4.4.5 TEST SETUP 40
4.4.6 EUT OPERATING CONDITIONS 40
4.4.7 TEST RESULTS 41
4.5 POWER SPECTRAL DENSITY MEASUREMENT 42
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 42
4.5.2 TEST INSTRUMENTS 42
4.5.3 TEST PROCEDURE 43
4.5.4 DEVIATION FROM TEST STANDARD 43
4.5.5 TEST SETUP 43
4.5.6 EUT OPERATING CONDITION 43
4.5.7 TEST RESULTS 44
4.6 BAND EDGES MEASUREMENT 50
4.6.1 LIMITS OF BAND EDGES MEASUREMENT 50
4.6.2 TEST INSTRUMENTS 50
4.6.3 TEST PROCEDURE 50
4.6.4 DEVIATION FROM TEST STANDARD 50
4.6.5 EUT OPERATING CONDITION 50
4.6.6 TEST RESULTS 51
4.7 ANTENNA REQUIREMENT 59
4.7.1 STANDARD APPLICABLE 59
4.7.2 ANTENNA CONNECTED CONSTRUCTION 59
5. PHOTOGRAPHS OF THE TEST CONFIGURATION 60
6. INFORMATION ON THE TESTING LABORATORIES 62
APPENDIX-A A-1

1. CERTIFICATION

PRODUCT:	Wireless-G PCI Adapter
MODEL:	WMP54G ver. 4.1
BRAND:	Linksys
TESTED:	Sep. 19 ~ Sep. 22, 2005
TEST SAMPLE:	ENGINEERING SAMPLE
APPLICANT:	Cisco-Linksys LLC
STANDARDS:	FCC Part 15, Subpart C (Section 15.247), ANSI C63.4-2003

The above equipment have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Rennie Wang , **DATE:** Sep. 23, 2005
Rennie Wang

TECHNICAL ACCEPTANCE : Gary Chang , **DATE:** Sep. 23, 2005
Responsible for RF
Gary Chang

APPROVED BY : Cody Chang , **DATE:** Sep. 23, 2005
Cody Chang / Deputy Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	**Test Type and Limit**	**Result**	**Remark**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is –17.45dB at 0.963MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is –1.64dB at 2483.50MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Wireless-G PCI Adapter
MODEL NO.	WMP54G ver. 4.1
POWER SUPPLY	5Vdc from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	47.863mW
ANTENNA TYPE	**Antenna 1:** Dipole antenna with 4.98dBi gain **Antenna 2:** Dipole antenna with 7.00dBi gain
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT is a Wireless-G PCI Adapter.
2. Two sets of antenna were provided to this EUT for the test.

SET	ANTENNA TYPE	ANTENNA GAIN (dBi)
1	Dipole	4.98
2	Dipole	7.00

The set 2 (antenna gain: 7.00dBi) was chosen as the representative for testing.

3. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
4. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
5. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT Configure Mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	√	√	√	√	-

Where PLC: Power Line Conducted Emission RE<1G RE: Radiated Emission below 1GHz
RE≥1G: Radiated Emission above 1GHz APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Bandedge Measurement:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6

Antenna Port Conducted Measurement:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless-G PCI Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)
ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved
2	PC	MSI	Hetis 865G	380125734	FCC DoC Approved
3	KEYBOARD	DELL	SK-8115	CN-OJ4635-71616-53A-0C8Q	FCC DoC Approved
4	MOUSE	DELL	MO56U0	516056250	FCC DoC Approved
5	LCD MONITOR	ACER	AL1721	ET.L0408.010404001E6PK00	FCC DoC Approved
6	MODEM	ACEEX	1414V/3	0401008248	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	1.3m shielded cable.
4	1.8m shielded cable.
5	1.8m shielded cable.
6	1.2m shielded cable.

NOTE: 1. All power cords of the above support units are non shielded (1.8m).

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5 0.5-5 5-30	66 to 56 56 60	56 to 46 46 50

NOTE:
1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 06, 2005
RF signal cable Woken	5D-FB	Cable-HyC02-01	Jan. 09, 2006
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 20, 2006
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jan. 20, 2006
Software ADT	ADT_Cond_V3	NA	NA

NOTE:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 3.
3. The VCCI Site Registration No. is C-2047.

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

a. Plugged the EUT to the computer system.
b. The computer system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
c. The computer system sent "H" messages to its screen.
d. The computer system sent "H" messages to its modem.
e. The computer system sent "H" messages to printer and the printer printed them on paper.
f. Steps c ~ e were repeated.

4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	PHASE	Line 1
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	45.75	-	45.86	-	63.91	53.91	-18.05	-
2	0.447	0.13	36.16	-	36.29	-	56.93	46.93	-20.64	-
3	0.963	0.22	36.86	-	37.08	-	56.00	46.00	-18.92	-
4	1.539	0.24	37.04	-	37.28	-	56.00	46.00	-18.72	-
5	3.523	0.28	32.16	-	32.44	-	56.00	46.00	-23.56	-
6	21.217	1.06	21.90	-	22.96	-	60.00	50.00	-37.04	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	PHASE	Line 2
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	45.75	-	45.86	-	63.91	53.91	-18.05	-
2	0.451	0.13	36.33	-	36.46	-	56.86	46.86	-20.40	-
3	0.963	0.22	36.88	-	37.10	-	56.00	46.00	-18.90	-
4	1.793	0.25	34.83	-	35.08	-	56.00	46.00	-20.92	-
5	3.531	0.28	33.87	-	34.15	-	56.00	46.00	-21.85	-
6	23.160	1.13	25.97	-	27.10	-	60.00	50.00	-32.90	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	PHASE	Line 1
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	45.65	-	45.76	-	63.91	53.91	-18.15	-
2	0.384	0.12	35.39	-	35.51	-	58.18	48.18	-22.68	-
3	0.963	0.22	36.60	-	36.82	-	56.00	46.00	-19.18	-
4	1.539	0.24	36.94	-	37.18	-	56.00	46.00	-18.82	-
5	3.461	0.28	33.35	-	33.63	-	56.00	46.00	-22.37	-
6	23.473	1.21	29.23	-	30.44	-	60.00	50.00	-29.56	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	PHASE	Line 2
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	43.05	-	43.16	-	63.91	53.91	-20.75	-
2	0.384	0.12	39.88	-	40.00	-	58.18	48.18	-18.19	-
3	**0.963**	**0.22**	**38.33**	**-**	**38.55**	**-**	**56.00**	**46.00**	**-17.45**	**-**
4	1.988	0.25	35.06	-	35.31	-	56.00	46.00	-20.69	-
5	3.531	0.28	34.28	-	34.56	-	56.00	46.00	-21.44	-
6	21.305	1.04	21.54	-	22.58	-	60.00	50.00	-37.42	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	PHASE	Line 1
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	45.75	-	45.86	-	63.91	53.91	-18.05	-
2	0.384	0.12	35.33	-	35.45	-	58.18	48.18	-22.74	-
3	0.963	0.22	36.72	-	36.94	-	56.00	46.00	-19.06	-
4	2.629	0.26	34.28	-	34.54	-	56.00	46.00	-21.46	-
5	8.277	0.40	26.06	-	26.46	-	60.00	50.00	-33.54	-
6	22.770	1.16	28.41	-	29.57	-	60.00	50.00	-30.43	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	PHASE	Line 2
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Jay Hsu		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.11	43.71	-	43.82	-	63.91	53.91	-20.09	-
2	0.384	0.12	39.44	-	39.56	-	58.18	48.18	-18.63	-
3	1.477	0.24	36.76	-	37.00	-	56.00	46.00	-19.00	-
4	3.527	0.28	34.41	-	34.69	-	56.00	46.00	-21.31	-
5	13.012	0.61	24.53	-	25.14	-	60.00	50.00	-34.86	-
6	20.289	0.99	27.30	-	28.29	-	60.00	50.00	-31.71	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Jan. 07, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Nov. 29, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Jan. 22, 2006
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 05, 2006
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170242	Jan. 23, 2006
Preamplifier Agilent	8447D	2944A10631	Nov. 17, 2005
Preamplifier Agilent	8449B	3008A01960	Nov. 14, 2005
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219272/4	Jan. 26, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219275/4	Jan. 26, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA
Turn Table ADT.	TT100.	TT93021704	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA

NOTE:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The IC Site Registration No. is IC4924-4.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	150.52	27.43 QP	43.50	-16.07	1.25 H	4	12.72	14.70
2	183.57	26.81 QP	43.50	-16.69	2.00 H	286	14.20	12.61
3	399.34	29.87 QP	46.00	-16.13	1.50 H	61	13.16	16.71
4	482.93	39.41 QP	46.00	-6.59	1.75 H	322	21.04	18.38
5	539.30	29.89 QP	46.00	-16.11	2.00 H	37	10.62	19.27
6	943.63	29.82 QP	46.00	-16.18	2.00 H	238	4.55	25.26

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	399.34	36.54 QP	46.00	-9.46	1.25 V	337	19.82	16.71
2	434.33	29.51 QP	46.00	-16.49	1.00 V	331	11.91	17.60
3	496.53	43.67 QP	46.00	-2.33	2.00 V	322	25.14	18.53
4	533.47	32.32 QP	46.00	-13.68	1.00 V	184	13.16	19.17
5	875.59	32.18 QP	46.00	-13.82	1.00 V	298	7.81	24.37
6	933.91	31.06 QP	46.00	-14.94	1.25 V	184	5.90	25.16

REMARKS:1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)

3. The other emission levels were very low against the limit.

4. Margin value = Emission level – Limit value.

802.11b DSSS modulation

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	44.26 PK	74.00	-29.74	1.31 H	315	12.39	31.87
2	*2412.00	99.82 PK			1.31 H	315	67.86	31.96
2	*2412.00	92.57 AV			1.31 H	315	60.61	31.96
3	3216.00	44.58 PK	79.82	-35.24	1.00 H	218	10.61	33.96
3	3216.00	32.18 AV	72.57	-40.39	1.00 H	218	-1.79	33.96
4	4824.00	55.23 PK	74.00	-18.77	1.18 H	225	17.40	37.83
4	4824.00	41.73 AV	54.00	-12.27	1.18 H	225	3.90	37.83

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.54 PK	74.00	-14.46	1.09 V	251	27.67	31.87
1	2390.00	52.03 AV	54.00	-1.97	1.09 V	251	20.16	31.87
2	*2412.00	115.10 PK			1.09 V	251	83.14	31.96
2	*2412.00	107.59 AV			1.09 V	251	75.63	31.96
3	2491.00	61.58 PK	74.00	-12.42	1.09 V	251	29.31	32.27
3	2491.00	52.25 AV	54.00	-1.75	1.09 V	251	19.98	32.27
4	3216.00	46.20 PK	95.10	-48.90	1.09 V	219	12.23	33.96
4	3216.00	37.05 AV	87.59	-50.54	1.09 V	219	3.08	33.96
5	4824.00	60.85 PK	74.00	-13.15	1.08 V	249	23.02	37.83
5	4824.00	48.28 AV	54.00	-5.72	1.08 V	249	10.45	37.83

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	101.87 PK			1.30 H	313	69.81	32.06
1	*2437.00	94.62 AV			1.30 H	313	62.56	32.06
2	3248.00	45.97 PK	81.87	-35.90	1.16 H	107	11.98	33.99
3	4874.00	54.61 PK	74.00	-19.39	1.20 H	236	16.63	37.98
3	4874.00	40.93 AV	54.00	-13.07	1.20 H	236	2.95	37.98

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	117.27 PK			1.09 V	257	85.21	32.06
1	2437.00	109.44 AV			1.09 V	257	77.38	32.06
2	3248.00	47.96 PK	97.27	-49.31	1.02 V	217	13.97	33.99
3	4874.00	63.48 PK	74.00	-10.52	1.06 V	249	25.50	37.98
3	4874.00	50.92 AV	54.00	-3.08	1.06 V	249	12.94	37.98

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	97.86 PK			1.30 H	322	65.70	32.16
1	*2462.00	90.64 AV			1.30 H	322	58.48	32.16
2	2483.50	44.59 PK	74.00	-29.41	1.30 H	322	12.35	32.24
3	3282.00	44.85 PK	77.86	-33.01	1.01 H	165	10.83	34.02
4	4924.00	53.28 PK	74.00	-20.72	1.20 H	234	15.14	38.14
4	4924.00	39.76 AV	54.00	-14.24	1.20 H	234	1.62	38.14

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	113.19 PK			1.09 V	254	81.03	32.16
1	*2462.00	105.35 AV			1.09 V	254	73.19	32.16
2	2483.50	59.92 PK	74.00	-14.08	1.09 V	254	27.68	32.24
2	2483.50	52.08 AV	54.00	-1.92	1.09 V	254	19.84	32.24
3	3282.00	45.87 PK	93.19	-47.32	1.02 V	217	11.85	34.02
4	4924.00	57.62 PK	74.00	-16.38	1.01 V	244	19.48	38.14
4	4924.00	45.19 AV	54.00	-8.81	1.01 V	244	7.05	38.14

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

802.11g OFDM modulation

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	47.23 PK	74.00	-26.77	1.41 H	230	15.36	31.87
2	*2412.00	99.15 PK			1.41 H	230	67.19	31.96
2	*2412.00	90.27 AV			1.41 H	230	58.31	31.96
3	3216.00	48.97 PK	79.15	-30.18	1.06 H	258	15.01	33.96
4	4824.00	51.82 PK	74.00	-22.18	1.13 H	154	13.99	37.83
4	4824.00	38.01 AV	54.00	-15.99	1.13 H	154	0.18	37.83

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.81 PK	74.00	-13.19	1.10 V	253	28.94	31.87
1	2390.00	51.85 AV	54.00	-2.15	1.10 V	253	19.98	31.87
2	*2412.00	112.73 PK			1.10 V	253	80.77	31.96
2	*2412.00	103.77 AV			1.10 V	253	71.81	31.96
3	3216.00	50.62 PK	92.73	-42.11	1.06 V	31	16.66	33.96
3	3216.00	46.45 AV	83.77	-37.32	1.06 V	31	12.49	33.96
4	4824.00	58.56 PK	74.00	-15.44	1.08 V	249	20.73	37.83
4	4824.00	45.68 AV	54.00	-8.32	1.08 V	249	7.85	37.83

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	98.97 PK			1.40 H	228	66.91	32.06
1	*2437.00	90.02 AV			1.40 H	228	57.96	32.06
2	3249.00	46.51 PK	78.97	-32.46	1.07 H	238	12.52	33.99
3	4874.00	51.93 PK	74.00	-22.07	1.09 H	228	13.95	37.98
3	4874.00	38.14 AV	54.00	-15.86	1.09 H	228	0.16	37.98

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	112.20 PK			1.19 V	226	80.14	32.06
1	*2437.00	103.22 AV			1.19 V	226	71.16	32.06
2	2489.00	63.03 PK	74.00	-10.97	1.21 V	225	30.76	32.27
2	2489.00	52.26 AV	54.00	-1.74	1.21 V	225	19.99	32.27
3	3249.00	48.45 PK	92.20	-43.75	1.02 V	63	14.46	33.99
3	3249.00	42.53 AV	83.22	-40.69	1.02 V	63	8.54	33.99
4	4874.00	57.45 PK	74.00	-16.55	1.07 V	249	19.47	37.98
4	4874.00	44.54 AV	54.00	-9.46	1.07 V	249	6.56	37.98

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

EUT	Wireless-G PCI Adapter	MEASUREMENT DETAIL	
MODEL	WMP54G ver. 4.1	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	97.23 PK			1.38 H	233	65.07	32.16
1	*2462.00	88.34 AV			1.38 H	233	56.18	32.16
2	2483.50	47.83 PK	74.00	-26.17	1.38 H	233	15.59	32.24
3	3282.00	46.67 PK	77.23	-30.56	1.09 H	325	12.65	34.02
4	4924.00	48.67 PK	74.00	-25.33	1.03 H	255	10.53	38.14

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.73 PK			1.09 V	253	78.57	32.16
1	*2462.00	101.76 AV			1.09 V	253	69.60	32.16
2	2483.50	61.33 PK	74.00	-12.67	1.09 V	253	29.09	32.24
2	**2483.50**	**52.36 AV**	**54.00**	**-1.64**	**1.09 V**	**253**	**20.12**	**32.24**
3	3282.00	49.67 PK	90.73	-41.06	1.02 V	49	15.65	34.02
4	4924.00	55.79 PK	74.00	-18.21	1.10 V	253	17.65	38.14
4	4924.00	42.87 AV	54.00	-11.13	1.10 V	253	4.73	38.14

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK 30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b DSSS modulation

EUT	Wireless-G PCI Adapter	**MODEL**	WMP54G ver. 4.1
MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	25deg. C, 66%RH, 991hPa
TESTED BY	Gray Chang		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.08	0.5	PASS
6	2437	12.12	0.5	PASS
11	2462	12.04	0.5	PASS

CH1


*RBW 100 kHz Delta 2 [T1]
*VBW 100 kHz 0.91 dB
Ref 20 dBm *Att 30 dB SWT 5 ms 12.080000000 MHz
Marker 1 [T1
-4.19 dBm
2.406000000 GHz
D1 2.37 dBm
D2 -3.63 dBm
F1
F2
Center 2.412 GHz 2 MHz/ Span 20 MHz

CH6


*RBW 100 kHz Delta 2 [T1]
*VBW 100 kHz 0.16 dB
Ref 20 dBm *Att 30 dB SWT 5 ms 12.120000000 MHz
Marker 1 [T1
-1.55 dBm
2.430960000 GHz
D1 4.4 dBm
D2 -1.6 dBm
F1
F2
Center 2.437 GHz 2 MHz/ Span 20 MHz

CH11


*RBW 100 kHz
*VBW 100 kHz
Delta 2 [T1]
0.78 dB
Ref 20 dBm
*Att 30 dB
SWT 5 ms
12.040000000 MHz
Marker 1 [T1]
-6.88 dBm
2.456000000 GHz
D1
D2
F1
F2
Center 2.462 GHz
2 MHz/
Span 20 MHz

802.11g OFDM modulation

EUT	Wireless-G PCI Adapter	**MODEL**	WMP54G ver. 4.1
MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	25deg. C, 66%RH, 991hPa
TESTED BY	Gray Chang		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.56	0.5	PASS
6	2437	16.56	0.5	PASS
11	2462	16.52	0.5	PASS

CH1


*RBW 100 kHz
Delta 2 [T1]
*VBW 100 kHz
1.74 dB
Ref 20 dBm
*Att 30 dB
SWT 5 ms
16.560000000 MHz
Marker 1 [T1]
-6.10 dBm
2.403720000 GHz
D1 -6.39 dBm
D2 -6.59 dBm
F1
F2
Center 2.412 GHz
2 MHz/
Span 20 MHz

CH6


*RBW 100 kHz
Delta 2 [T1]
*VBW 100 kHz
0.86 dB
Ref 20 dBm
*Att 30 dB
SWT 5 ms
16.560000000 MHz
Marker 1 [T1]
-7.16 dBm
2.428720000 GHz
D1 -7.06 dBm
D2 -7.65 dBm
F1
F2
Center 2.437 GHz
2 MHz/
Span 20 MHz

CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006
AGILENT SIGNAL GENERATOR	E8257C	MY4WMP54G VER. 4.10668	Dec. 06, 2005
DIGITAL RT OSCILLOSCOPE	TDS1012	C037299	Dec. 07, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:
The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA..

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS modulation

EUT	Wireless-G PCI Adapter	**MODEL**	WMP54G ver. 4.1
MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	25deg. C, 66%RH, 991hPa
TESTED BY	Gray Chang		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	28.184	14.50	30	PASS
6	2437	47.863	16.80	30	PASS
11	2462	17.783	12.50	30	PASS

802.11g OFDM modulation

EUT	Wireless-G PCI Adapter	**MODEL**	WMP54G ver. 4.1
MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	25deg. C, 66%RH, 991hPa
TESTED BY	Gray Chang		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	28.576	14.56	30	PASS
6	2437	28.249	14.51	30	PASS
11	2462	20.184	13.05	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE:
The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.
The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b DSSS modulation

EUT	Wireless-G PCI Adapter	**MODEL**	WMP54G ver. 4.1
MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	25deg. C, 66%RH, 991hPa
TESTED BY	Gray Chang		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-11.59	8	PASS
6	2437	-9.53	8	PASS
11	2462	-14.37	8	PASS

CH1


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
-11.59 dBm
Ref 20 dBm
*Att 30 dB
2.412261000 GHz
Center 2.412 GHz
150 kHz/
Span 1.5 MHz

CH6


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
-9.53 dBm
Ref 20 dBm
*Att 30 dB
2.437253000 GHz
Center 2.437 GHz
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-14.37 dBm
2.462250000 GHz
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.462 GHz
150 kHz/
Span 1.5 MHz

802.11g OFDM modulation

EUT	Wireless-G PCI Adapter	**MODEL**	WMP54G ver. 4.1
MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	25deg. C, 66%RH, 991hPa
TESTED BY	Gray Chang		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-14.89	8	PASS
6	2437	-15.01	8	PASS
11	2462	-16.08	8	PASS

CH1


*RBW 3 kHz
Marker 1 [T1]
*VBW 30 kHz
-74.89 dBm
Ref 20 dBm
*Att 30 dB
*SWT 500 s
2.411667000 GHz
Center 2.412 GHz
150 kHz/
Span 1.5 MHz

CH6


*RBW 3 kHz
Marker 1 [T1]
*VBW 30 kHz
-15.01 dBm
Ref 20 dBm
*Att 30 dB
*SWT 500 s
2.436667000 GHz
Center 2.437 GHz
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
Marker 1 [T1]
*VBW 30 kHz
-16.08 dBm
Ref 20 dBm
*Att 30 dB
*SWT 500 s
2.451667000 GHz
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.462 GHz
150 kHz/
Span 1.5 MHz

4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 12 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS modulation

NOTE 1: The band edge emission plot on page 52 show 50.34dBc delta between carrier maximum power and local maximum emission in restrict band (2.3732GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 115.10dBuV/m (Peak), so the maximum field strength in restrict band is 115.10-50.34=64.76dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 52 show 55.85dBc delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 107.59dBuV/m (Average), so the maximum field strength in restrict band is 107.59-55.85=51.74dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on the page 53 show 47.43dBc delta between carrier maximum power and local maximum emission in restrict band (2.4899GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 113.19dBuV/m (Peak), so the maximum field strength in restrict band is 113.19-47.43=65.76dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the page 54 show 53.26dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 105.35dBuV/m (Average), so the maximum field strength in restrict band is 105.35-53.26=52.09dBuV/m which is under 54dBuV/m limit.


Ref 20 dBm
Att 30 dB
Center 2.3656 GHz
10 MHz/
Span 100 MHz


Ref 20 dBm
Att 30 dB
Center 2.3656 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
Ref 20 dBm
*Att 30 dB
SWT 2.5 s
Marker 2 [T1]
-42.54 dBm
D1 2.77 dBm
D2 -17.23 dBm
Start 30 MHz
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
Ref 20 dBm
*Att 30 dB
SWT 10 ms
Marker 1 [T1]
Marker 2 [T1]
Marker 3 [T1]
Marker 4 [T1]
D1 6.14 dBm
D2 -19.86 dBm
Center 2.508 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
Marker 1 [T1]
0.07 dBm
2.464200000 GHz
Ref 20 dBm
*Att 30 dB
SWT 25 s
Marker 2 [T1]
-53.19 dBm
Marker 3 [T1]
-53.19 dBm
Marker 4 [T1]
-55.93 dBm
2.300000000 GHz
F1
F2
Center 2.508 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
Marker 1 [T1]
2.427120000 GHz
Ref 20 dBm
*Att 30 dB
SWT 2.5 s
Marker 2 [T1]
-43.42 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

802.11g OFDM modulation

NOTE 1: The band edge emission plot on page 56 show 45.51dBc delta between carrier maximum power and local maximum emission in restrict band (2.3742GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 112.73dBuV/m (Peak), so the maximum field strength in restrict band is 112.73-45.51=67.22dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 56 show 51.88dBc delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 103.77dBuV/m (Average), so the maximum field strength in restrict band is 103.77-51.88=51.89dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on the page 57 show 44.93dBc delta between carrier maximum power and local maximum emission in restrict band (2.4849GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 110.73dBuV/m (Peak), so the maximum field strength in restrict band is 110.73-44.93=65.80dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the page 58 show 49.41dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 101.76dBuV/m (Average), so the maximum field strength in restrict band is 101.76-49.41=52.35dBuV/m which is under 54dBuV/m limit.


Ref 20 dBm
*Att 30 dB
SWT 10 ms
Marker 1 [T1]
-0.92 dBm
2.415600000 GHz
Center 2.3688 GHz
10 MHz/
Span 100 MHz


Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
2.415600000 GHz
Center 2.3688 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
Marker 1 [T1]
Ref 20 dBm
*Att 30 dB
Marker 2 [T1
-42.95 dBm
D1 -0.92 dBm
D2 -20.92 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
Marker 1 [T1]
-2.47 dBm
Ref 20 dBm
*Att 30 dB
SWT 10 ms
Marker 2 [T1
-48.49 dBm
Marker 3 [T1
-47.40 dBm
Marker 4 [T1
50.84 dBm
D2 -2.67 dBm
D2 -22.47 dBm
T1
T2
Center 2.505 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
2.98 dBm
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-52.39 dBm
Marker 3 [T1]
-52.39 dBm
Marker 4 [T1]
-55.98 dBm
D1 -2.98 dBm
D2 -22.98 dBm
F1
F2
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
4.20 dBm
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-43.25 dBm
D2 -22.47 dBm
Start 30 MHz
Stop 25 GHz

4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole antenna with Reverse SMA antenna connector. The maximum Gain of the antenna is 7dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST

RADIATED EMISSION TEST



6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab.
Tel: 886-3-3270910
Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also

APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.